TROGAR NOITOAGNI BLOHAV JAUNNA

ne/80		тилив 1 µ3;	9 OI	9_	<u> </u>			
						•		٠.
	THE ONDION	_i h	um	D	777 JW18	ROTARINO	HAT H)TOI.
'61'988 No	STHE GUALIFICATION REQUIREMENTS IN SECTION			SIHL	contation of soit no	* 1	SSE	Haav
	ОИ (У АИВ СОМРЕЕТЕ)		CFE IDE	ΛΕΗΙ			O GIZ BTATE,	
1KC27X 3'00	OCENTION COPTIONED AND CONTRACT HHORS) 1 1	
SOPPRING SEPVICES SOPPRING SOFTION (OPTIONAL)					R □ TRAILER Ø TRUCK □ BUS	OTOART [(REHTO) [); }(H=1/
	STATE OF THE STATE	WREST OF SPEC		Para de la companya d				
		eterane asia	training and	- TO 100 C			11330 30331	
	ILEM	OBRIANDED BTAO	RIATI	OK	M∃TI	3.	IAGEDS REPAIR	OK
· · · · · · · · · · · · · · · · · · ·	e. Pitman Arm 1. Power Steering		· .	<u>/}</u>	MELECYCLED WHE			
	g. Ball and Socket Joints			7	7 Serving Brake System 2 Service Brakes			71
	h. Tie Rods and Drag Links			1	Strake Drums or Rotors)		1
1	stuN .i			200%	1 Brake Hose			.4
	j. Steering System Molayteratie s.,			1	3. Brake Tubing Warning Device			چ ^{ار} م فسر
an est a filipa de la companione de la comp	s Axle Positioning Parts			1	J. Tractor Protection Valve			سر.
	b. Spring Assembly			, A	n. Air Compressor			1
sinenoqnio	O Torque, Radius or Tracking C			ŕì	Flectric Brakes	· ·		71
	a. Frame Members	ė ·			Hydraulic Brakes Vacuum Systems	1		ų, Ų,
	b. Tire and Wheel Clearance				Antillock Brake System			
6uibil8	c. Adjustable Axle Assemblies (a			1/1	m. Automatic Brake Adjusters	1		
	Subframes)	7			Filth Wheels			/
all with my franchistical security	a. Steer-Axle Tires			1	D. Pintle Hooks			1/
· · · · · · · · · · · · · · · · · · ·	b. All Other Tires			A	C. Drawbar Towbar Eye)		1
	c. Speed-Restricted Tires			13	d. Drawbar/Towbar Tongue		4	Ţ
	STANTHERS WINDS STATE RING			d/V	e, Satety Devices f, Saddle-Mounts			7-9 20-1
	smi Bins alee MV d			- Party	SUDDIM-ADDRES		.	أجمر
	c. Fasteners			<u></u>	a. No leaks forward of/directly below the			18
	sbiew b			ويسر	driver/sleeper compartment.	· .	أغر ا	<u></u>
SƏ)	**************************************			1.8	b. Bus: No leaking/discharging in violation of standard.			11
	etc. (see 393.60 for exceptions)			1	c. Unlikely to burn, char, or damage the			
	SEESIMOREIESSIM SAL				electrical wiring, fuel supply, or any			1
tive wiper, or	sregori na asrt that tinu newog ynA ger tedt afreo benemeb to paissim			111	combustible part of vehicle.	ALCONOMICS CONTROL		
uer it melletilve.	nar tarit ahaq bagamab ro gniaaim SVV=E4450X(05):101700112350				a. No visible leak.			Ą
ecniejλ	Any passenger seat that is not a			11				1
mentalisera and an angles and an angles Angles and an angles and an angles and an angles and an angles and an analysis and an analysis and an analysis	fastened to the vehicle structure			14 e	c. Fuer rank securery assacried.	1]	./}
95is 190	SEE SEE SECULE (1995)			#	e(eff#il/Jefp]=V(e)=S All lighting devices and reflectors required by			_
	proper placement (see 393.86).	.		10	Section 393 shall be operable.			i de la comoción de l
				"	JAMOVOJEKVS	200 mar 200 m 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
	List any other condition(s) which versition of this ve				a. Vehicle parts, foad, dunnage, spare			
. totoli #	provent eate operation of this ve				tire, etc., secured. b. Front End Structure			
<u> </u>					c. Intermodal Container Securement Devices			N
·				5. J.	aifeanch e chann a cha			
			-		s. Steering Wheel Free Play			<u>5 مر</u>
				-	b. Steering Column			1
		· }	. !		 Front Axle Beam/All Other Steering Components 	l (.	1 4	-