

xtpxlib-common

Common code and IDE support

0 Table of Contents

0 Xatapult XML Library - Common code	4
1 Description	5
1.1 Contents	5
1.2 Parameter handling in xtpxlib-common	5
2 XSLT Modules	7
2.1 XSLT (3.0): compare.mod.xsl	7
2.1.1 Named template: xtlc:compare-documents as element(xtlc:message)*	7
2.2 XSLT (3.0): date-time.mod.xsl	7
2.2.1 Function: xtlc:day-in-year-number() as xs:integer	8
2.2.2 Function: xtlc:days-in-month() as xs:integer	8
2.2.3 Function: xtlc:format-date-as-text() as xs:string	9
2.2.4 Function: xtlc:format-date-as-text-short() as xs:string	9
2.2.5 Function: xtlc:is-leap-year() as xs:boolean	9
2.2.6 Function: xtlc:month-name() as xs:string	9
2.2.7 Function: xtlc:month-name-short() as xs:string	9
2.2.8 Function: xtlc:to-date() as xs:date	9
2.2.9 Function: xtlc:unix-epoch() as xs:decimal	9
2.2.10 Function: xtlc:week-number() as xs:integer	10
2.2.11 Function: xtlc:weekday-name() as xs:string	10
2.2.12 Function: xtlc:weekday-number() as xs:integer	10
2.3 XSLT (3.0): format-output.mod.xsl	10
2.3.1 Function: xtlc:duration2str() as xs:string	10
2.3.2 Function: xtlc:format-amount() as xs:string	10
2.3.3 Function: xtlc:format-double() as xs:string	10
2.3.4 Function: xtlc:size2str() as xs:string	11
2.4 XSLT (3.0): general.mod.xsl	11
2.4.1 Named template: xtlc:raise-error	12
2.4.2 Function: xtlc:apos() as xs:string	12
2.4.3 Function: xtlc:att2str() as xs:string	12
2.4.4 Function: xtlc:capitalize() as xs:string	12
2.4.5 Function: xtlc:char-repeat() as xs:string	12
2.4.6 Function: xtlc:count-leading-whitespace() as xs:integer	13
2.4.7 Function: xtlc:elm2str() as xs:string	13
2.4.8 Function: xtlc:item2element() as element()?	13
2.4.9 Function: xtlc:items2str() as xs:string	13
2.4.10 Function: xtlc:prefix-to-length() as xs:string	13
2.4.11 Function: xtlc:q() as xs:string	13
2.4.12 Function: xtlc:str2bln() as xs:boolean	13
2.4.13 Function: xtlc:str2filename-safe() as xs:string	14
2.4.14 Function: xtlc:str2filename-safe() as xs:string	14
2.4.15 Function: xtlc:str2id() as xs:string	14
2.4.16 Function: xtlc:str2id() as xs:string	14
2.4.17 Function: xtlc:str2int() as xs:integer	14
2.4.18 Function: xtlc:str2regexp() as xs:string	14
2.4.19 Function: xtlc:str2regexp() as xs:string	15
2.4.20 Function: xtlc:str2seq() as xs:string*	15
2.4.21 Function: xtlc:text2lines() as xs:string*	15
2.4.22 Function: xtlc:wrap-text() as xs:string*	15
2.5 XSLT (3.0): href.mod.xsl	15
2.5.1 Function: xtlc:href-add-encoding() as xs:string	16
2.5.2 Function: xtlc:href-canonical() as xs:string	16
2.5.3 Function: xtlc:href-concat() as xs:string	16
2.5.4 Function: xtlc:href-decode-uri() as xs:string	16
2.5.5 Function: xtlc:href-ext() as xs:string	17
2.5.6 Function: xtlc:href-is-absolute() as xs:boolean	17
2.5.7 Function: xtlc:href-make-uri() as xs:string	17

2.5.8	Function: xtlc:href-name() as xs:string	17
2.5.9	Function: xtlc:href-name-noext() as xs:string	17
2.5.10	Function: xtlc:href-noext() as xs:string	17
2.5.11	Function: xtlc:href-path() as xs:string	18
2.5.12	Function: xtlc:href-protocol() as xs:string	18
2.5.13	Function: xtlc:href-protocol() as xs:string	18
2.5.14	Function: xtlc:href-protocol-add() as xs:string	18
2.5.15	Function: xtlc:href-protocol-present() as xs:boolean	18
2.5.16	Function: xtlc:href-protocol-remove() as xs:string	18
2.5.17	Function: xtlc:href-relative() as xs:string	19
2.5.18	Function: xtlc:href-relative-from-path() as xs:string	19
2.5.19	Function: xtlc:href-result-doc() as xs:string	19
2.6	XSLT (3.0): macrodefs.mod.xsl	19
2.6.1	Named template: xtlc:expand-macro-definitions	20
2.6.2	Named template: xtlc:macrodefs-as-comment	21
2.6.3	Function: xtlc:expand-macrodefs() as xs:string	21
2.6.4	Function: xtlc:get-standard-macrodef-map() as map(xs:string, xs:string)	21
2.6.5	Function: xtlc:merge-macrodefs() as map(xs:string, xs:string)	21
2.7	XSLT (3.0): message.mod.xsl	22
2.7.1	Named template: xtlc:msg-create as element(xtlc:message)	22
2.8	XSLT (3.0): mimetypes.mod.xsl	22
2.8.1	Function: xtlc:ext2mimetype() as xs:string	22
2.8.2	Function: xtlc:mimetype2ext() as xs:string	22
2.9	XSLT (3.0): parameters.mod.xsl	23
2.9.1	Function: xtlc:expand-text-against-parameters() as xs:string	23
2.9.2	Function: xtlc:parameters-get() as map(xs:string, xs:string*)	23
2.10	XSLT (3.0): simple-macros.mod.xsl	23
2.10.1	Function: xtlc:expand-simple-macros() as xs:string	24
2.10.2	Function: xtlc:expand-simple-macros() as xs:string	24
2.11	XSLT (3.0): uuid.mod.xsl	24
2.11.1	Function: xtlc:get-uuid() as xs:string	24
2.11.2	Function: xtlc:is-real-uuid() as xs:boolean	25
3	XProc 3.0 Support	26
3.1	XProc (3.0) pipeline: copy-dir.xpl	26
3.2	XProc (3.0) pipeline: create-clear-directory.xpl	26
3.3	XProc (3.0) library: expand-generators.mod.xpl	27
3.3.1	Step: xtlc:expand-generators	27
3.3.2	Step: xtlc:handle-generate-element	27
3.4	XProc (3.0) pipeline: expand-macro-definitions.xpl	27
3.5	XProc (3.0) pipeline: is-out-of-date.xpl	28
3.6	XProc (3.0) library: message.xpl	28
3.6.1	Step: xtlc:message	28
3.7	XProc (3.0) pipeline: recursive-directory-list.xpl	29
3.8	XProc (3.0) pipeline: subdir-list.xpl	30
3.9	XProc (3.0) pipeline: validate.xpl	30
3.10	XProc (3.0) pipeline: write-log.xpl	30
3.11	XProc (3.0) pipeline: zip-directory.xpl	31
3.12	oXygen XProc 3.0 support (oXygen versions < 26)	31
4	XProc 1.0 Support	33
4.1	XProc (1.0) library: common.mod.xpl	33
4.1.1	Step: xtlc:copy-directory	33
4.1.2	Step: xtlc:copy-file	33
4.1.3	Step: xtlc:log	34
4.1.4	Step: xtlc:recursive-directory-list	34
4.1.5	Step: xtlc:remove-dir	34
4.1.6	Step: xtlc:tee	34
4.1.7	Step: xtlc:zip-directory	35
5	XSLT Stylesheets	36

5.1	XSLT (3.0): expand-macro-definitions.xsl	36
5.2	XSLT (2.0): get-system-properties.xsl	36
5.3	XSLT (2.0): xslmod2xqmod-stub.xsl	36
6	XML Data Files	37
6.1	XML document: dummy.xml	37
6.2	XML document: fop-default-config.xml	37
6.3	XML document: mimetypes-table.xml	37
7	XML Schemas	38
7.1	XML Schema: message.xsd	38
7.2	XML Schema: mimetypes.xsd	38
7.3	XML Schema: parameters.xsd	38

0 Xatapult XML Library - Common code



xtpplib library - component **xtpplib-common** - v3.1 (2026-03-17)

Xatapult Content Engineering - <http://www.xatapult.com> - +31 6 53260792

Erik Siegel - erik@xatapult.com

xtpplib-common is part of the **xtpplib** library. **xtpplib** contains software for processing XML, using languages like XSLT and XProc. It consists of several separate components, all named **xtpplib-***. Everything can be found on GitHub (<https://github.com/xatapult>).

xtpplib-common is **xtpplib**'s communal component. Most other **xtpplib** components rely on it. It contains:

- XSLT libraries, with functionality for handling parameters, manipulating filenames/URIs, MIME types, etc.
- Parts of the functionality of the XSLT libraries are translated into XQuery.
- XProc (1.0 and 3.0) steps, implementing things like recursive directory lists, creating ZIP files from directories, etc.
- Templates (empty XSLT, XProc, XQuery, etc. files) for use in the oXygen IDE.

Installation and usage information can be found on **xtpplib**'s main website <https://www.xtpplib.org>.

Technical information:

Component documentation: <https://common.xtpplib.org>

License: GNU GENERAL PUBLIC LICENSE - Version 3, 29 June 2007

Git URI: [git@github.com:xatapult/xtpplib-common.git](https://github.com/xatapult/xtpplib-common.git)

Git site: <https://github.com/xatapult/xtpplib-common>

Release information:

v3.1 - 2026-03-17 (current)

Several fixes and enhancements

v3.0 - 2024-12-12

Deprecation of XProc 1.0. Several fixes.

v2.0.1 - 2023-07-22

Weekday-number and week-number calculations now also work with Saxon HE.

v2.0 - 2023-07-19

Added XProc 3.0 support.

v1.3.2 - 2022-03-24

Added indent option to `xtlc:tee`

(Abbreviated. Full release information in `README.md`)

1 Description

xtpxlib-common is xtpxlib's communal component. Most other components in xtpxlib are dependent on it. If you start using xtpxlib, you'll also use it a lot yourself.

1.1 Contents

xtpxlib-common consists of the following parts (by subdirectory):

Directory	Contents
data	XML data files.
doc	Sources for the generation of the component's documentation. Internal use only.
docs	GitHub pages site for this component.
etc	Auxiliary files, mainly for use in the oXygen IDE.
template	Template files. These files contain XSLT, XQuery, XProc, etc. files with the main structure and headers filled in. Contain macros for use in the oXygen IDE. To install/use these files in oXygen, open its preferences dialogue (Options > Preferences...) and add the xtpxlib-common/template subdirectory to its Document templates section.
xpl	General purpose XProc (1.0) pipelines. .
xplmod	General purpose XProc (1.0) modules.
xpl3	General purpose XProc (3.0) pipelines. .
xpl3mod	General purpose XProc (3.0) modules.
xqmod	General purpose XQuery modules. This is a partial translation of the XSLT module's functionality (especially from href.mod.xsl) into XQuery.
xsd	Schemas for some of the document types used in Xatapult XML Library .
xsl	Some general purpose XSLT stylesheets.
xslmod	General purpose XSLT modules.

1.2 Parameter handling in xtpxlib-common

Parameters, as referred to here, are name/value pairs meant for customizing software's behavior. Things like prompts, URIs, etc. The xtpxlib-common component's parameters have the following characteristics:

- Parameters in this component are handled by the XSLT module [parameters.mod.xsl](#). This includes:
 - Reading them from an XML document, either a document on its own or embedded into a bigger XML document. The result will be an XPath map(`xs:string`, `xs:string*`), which can be inspected and used.
 - Expanding parameter references in strings. Parameter references are constructions like `{parameter-name}` (or `#{parameter-name}`), both will yield the same results).
- Parameters are specified within an XML element called `<parameters>`, the namespace does not matter. This element can be the root of a document on its own or embedded in a bigger (XML) document. For instance:

```
<parameters>
  <parameter name="greeting">
    <value>Hello!</value>
  </parameter>
</parameters>
```

There is a [schema](#) available for this.

- A single parameter is specified using a `<parameter name="...">` child element. The value of the `name` attribute will be normalized (whitespace collapsed to a single space character, leading/trailing whitespace removed) and space characters are replaced with an underscore (`_`). So `name=" a b "` will become parameter `a_b`.
- Values for a parameter are specified using `<value>` child element. A parameter can have multiple values. Parameter references inside values (either written as `{parameter-name}` or `#{parameter-name}`) are expanded into their values (for multi-valued parameters only the first value is used).

- It is often useful to specify values for parameters based on different circumstances. For instance based on language (**Hello** in English or **Bonjour** in French), or system type (**https://www...** for production, **http://test...** for test). This is implemented as follows:
 - When initially reading the parameters you can specify a filter map (`map(xs:string, xs:string*)`).
 - The `<value>` elements can have any attributes. These attributes are handled as whitespace separated lists of values.
 - The name of such an attribute is held against the entries in filter map. If a filter entry with this name exists, one of the values of the attribute must be present in the filter map.

For instance, assume the parameters look like this:

```
<parameters>
  <parameter name="greeting">
    <value lang="en">Hello!</value>
    <value lang="nl de">Hallo!</value>
    <value lang="fr">Bonjour!</value>
  </parameter>
  <parameter name="number">
    <value>123</value>
  </parameter>
</parameters>
```

- Reading this with an empty (or absent) filter map, or a filter map that does not have a `lang` entry, will result in a **greeting** parameter with multiple values, **Hello!**, **Hallo!** and **Bonjour!**.
- Reading this with a filter map `map{ 'lang': 'en' }` will return the **greeting** parameter with value **Hello!**.
- Reading this with a filter map `map{ 'lang': 'fr' }` will return the **greeting** parameter with value **Bonjour!**.
- Reading this with a filter map `map{ 'lang': ('en', 'de') }` (not particularly useful) will return the **greeting** parameter with values **Hello!** and **Hallo!**.
- In all cases the **number** parameter will get value **123** (since it has no filtering attributes on its `<value>` element).

It is possible to combine multiple filter attributes on a `<value>` element.

- Another thing that is often useful in specifying parameters is to *group* them. For this you can put a number of `<parameter>` elements inside a `<group name="...">` element. The name of the group is used as a prefix (with a dot (`.`) separator) for the parameters in the group. For instance:

```
<parameters>
  <group name="important">
    <parameter name="greeting">
      <value>Hello!</value>
    </parameter>
  </group>
</parameters>
```

This will result in a parameter called **important.greeting**.

2 XSLT Modules

The xtpxlib-common component contains the following XSLT modules. The ones used most frequently are [general.mod.xsl](#) and [href.mod.xsl](#).

Module/Pipeline	Description
compare.mod.xsl	XSL library module with support for comparing XML documents/elements:
date-time.mod.xsl	XSLT library module containing functions for working with dates and times.
format-output.mod.xsl	XSLT library with functions for formatting output/strings.
general.mod.xsl	XSLT library module with general constants and code.
href.mod.xsl	XSLT library module with functions for the generic handling of href-s (filenames/paths).
macrodefs.mod.xsl	Module for handling macro definitions.
message.mod.xsl	Message related templates.
mimetypes.mod.xsl	MIME type conversion related functions.
parameters.mod.xsl	Takes an XML document with parameters and turns this into a parameter map.
simple-macros.mod.xsl	(DEPRECATED) Support code for simple macro expansion in strings, e.g. \$NAME.
uuid.mod.xsl	UUID related functions.

Table 2-1 - Module overview

2.1 XSLT (3.0): compare.mod.xsl

File: `xslmod/compare.mod.xsl`

XSL library module with support for comparing XML documents/elements:

Prefix	Namespace URI
<code>xtlc</code>	<code>http://www.xtpxlib.nl/ns/common</code>

Named template	Description
xtlc:compare-documents	Compares two XML documents with each other:

2.1.1 Named template: `xtlc:compare-documents` as `element(xtlc:message)*`

Compares two XML documents with each other:

- Comments and processing instructions are ignored
- Text nodes are normalized before comparison
- Empty text nodes (after normalization) are ignored
- The comparison stops after the first difference is encountered.
- The result is either:
 - An empty set, when no differences found
 - One or more `xtlc:message` elements, `status="error"` when differences were found (you can only get more than one message on attribute differences)

Parameter	Type	Rq?	Default	Description
<code>doc1</code>	<code>document-node()</code>	yes		First document to compare.
<code>doc2</code>	<code>document-node()</code>	yes		Second document to compare.

2.2 XSLT (3.0): date-time.mod.xsl

File: `xslmod/date-time.mod.xsl`

XSLT library module containing functions for working with dates and times.

When language based, it only distinguishes between Dutch and non-Dutch (which now means: English).

Prefix	Namespace URI
xtlc	http://www.xtpxlib.nl/ns/common

Variable	Type	Value	Description
xtlc:day-names-en	xs:string+	('Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday')	Sequence with the names of the days in English
xtlc:day-names-nl	xs:string+	('maandag', 'dinsdag', 'woensdag', 'donderdag', 'vrijdag', 'zaterdag', 'zondag')	Sequence with the names of the days in Dutch
xtlc:month-names-en	xs:string+	('January', 'February', 'March', 'April', 'May', 'June', 'July', 'August', 'September', 'October', 'November', 'December')	Sequence with the names of the months in English
xtlc:month-names-nl	xs:string+	('januari', 'februari', 'maart', 'april', 'mei', 'juni', 'juli', 'augustus', 'september', 'oktober', 'november', 'december')	Sequence with the names of the months in Dutch

Function	Description
xtlc:day-in-year-number()	Computes the day number in the year: January 1 is 1, December 31 is 365 (or 366 in leap years).
xtlc:days-in-month()	Computes the number of days in a particular month. If values are out of range it returns 0.
xtlc:format-date-as-text()	Formats a date as a string with the month name in full.
xtlc:format-date-as-text-short()	Formats a date as a string with the month name in short.
xtlc:is-leap-year()	Returns true when a given year is a leap year
xtlc:month-name()	Returns the name of a month.
xtlc:month-name-short()	Returns the name of a month in short (abbreviated to 3 characters).
xtlc:to-date()	Creates a date from its components.
xtlc:unix-epoch()	Computes the UNIX "epoch" code (number of seconds since 1-1-1970) for a given date/time.
xtlc:week-number()	Computes the ISO week number for a given date.
xtlc:weekday-name()	Returns the name of a month.
xtlc:weekday-number()	The number of the weekday (1=Monday, 7=Sunday).

2.2.1 Function: [xtlc:day-in-year-number\(\)](#) as xs:integer

Computes the day number in the year: January 1 is 1, December 31 is 365 (or 366 in leap years).

Parameter	Type	Description
date	xs:date	Date to use.

2.2.2 Function: [xtlc:days-in-month\(\)](#) as xs:integer

Computes the number of days in a particular month. If values are out of range it returns 0.

Parameter	Type	Description
month-number	xs:integer	The month to calculate the number of days for.
year	xs:integer	The year this month is in (important because of leap years).

2.2.3 Function: **xtlc:format-date-as-text()** as xs:string

Formats a date as a string with the month name in full.

Parameter	Type	Description
date	xs:date	The date to format.
lang	xs:string	The language for the conversion.

2.2.4 Function: **xtlc:format-date-as-text-short()** as xs:string

Formats a date as a string with the month name in short.

Parameter	Type	Description
date	xs:date	The date to format.
lang	xs:string	The language for the conversion.

2.2.5 Function: **xtlc:is-leap-year()** as xs:boolean

Returns true when a given year is a leap year

Parameter	Type	Description
year	xs:integer	The year to check.

2.2.6 Function: **xtlc:month-name()** as xs:string

Returns the name of a month.

Parameter	Type	Description
month-number	xs:integer	The month number (1-12).
lang	xs:string	The language you want the month name in.

2.2.7 Function: **xtlc:month-name-short()** as xs:string

Returns the name of a month in short (abbreviated to 3 characters).

Parameter	Type	Description
month-number	xs:integer	The month number (1-12).
lang	xs:string	The language you want the month name in.

2.2.8 Function: **xtlc:to-date()** as xs:date

Creates a date from its components.

Parameter	Type	Description
day	xs:integer	Day number to use.
month	xs:integer	Month number to use.
year	xs:integer	Year to use.

2.2.9 Function: **xtlc:unix-epoch()** as xs:decimal

Computes the UNIX "epoch" code (number of seconds since 1-1-1970) for a given date/time.

Parameter	Type	Description
<code>datetime</code>	<code>xs:dateTime</code>	The date/time to compute the epoch code for.

2.2.10 Function: `xtlc:week-number()` as `xs:integer`

Computes the ISO week number for a given date.

Parameter	Type	Description
<code>date</code>	<code>xs:date</code>	Date to use.

2.2.11 Function: `xtlc:weekday-name()` as `xs:string`

Returns the name of a month.

Parameter	Type	Description
<code>day-number</code>	<code>xs:integer</code>	The day number (1-7).
<code>lang</code>	<code>xs:string</code>	The language you want the month name in.

2.2.12 Function: `xtlc:weekday-number()` as `xs:integer`

The number of the weekday (1=Monday, 7=Sunday).

Parameter	Type	Description
<code>date</code>	<code>xs:date</code>	Date to use.

2.3 XSLT (3.0): `format-output.mod.xsl`

File: `xslmod/format-output.mod.xsl`

XSLT library with functions for formatting output/strings.

When language based, we only distinguish between Dutch and non-Dutch (usually English).

Prefix	Namespace URI
<code>xtlc</code>	<code>http://www.xtpxlib.nl/ns/common</code>

Function	Description
<code>xtlc:duration2str()</code>	Turns a day/time duration into a more readable string, e.g. <code>1d3h40m12s</code>
<code>xtlc:format-amount()</code>	Formats an amount by adding a € sign and always use double digits.
<code>xtlc:format-double()</code>	Formats a double as a string with a given amount of digits.
<code>xtlc:size2str()</code>	Turns an integer (e.g. a file size) into a (rounded) number using a <code>Kb/Mb/Gb</code> suffix.

2.3.1 Function: `xtlc:duration2str()` as `xs:string`

Turns a day/time duration into a more readable string, e.g. `1d3h40m12s`

Parameter	Type	Description
<code>duration</code>	<code>xs:dayTimeDuration</code>	The duration to convert.
<code>round-seconds</code>	<code>xs:boolean</code>	Whether the seconds part must be rounded.

2.3.2 Function: `xtlc:format-amount()` as `xs:string`

Formats an amount by adding a € sign and always use double digits.

For the Dutch language, `.` and `,` are swapped.

Parameter	Type	Description
<code>amount</code>	<code>xs:double</code>	The amount to format.
<code>lang</code>	<code>xs:string</code>	The language for the conversion.

2.3.3 Function: `xtlc:format-double()` as `xs:string`

Formats a double as a string with a given amount of digits.

For the Dutch language, . and , are swapped.

Parameter	Type	Description
dbl	xs:double	Number to convert
digits	xs:integer	The number of digits to use. When < 0 this is left open.
lang	xs:string	The language for the conversion.

2.3.4 Function: xtlc:size2str() as xs:string

Turns an integer (e.g. a file size) into a (rounded) number using a Kb/Mb/Gb suffix.

Parameter	Type	Description
size	xs:integer	The size to convert.

2.4 XSLT (3.0): general.mod.xsl

File: xslmod/general.mod.xsl

XSLT library module with general constants and code.

Prefix	Namespace URI
xtlc	http://www.xtpxlib.nl/ns/common

Variable	Type	Value	Description
xtlc:default-dt-format	xs:string	'[Y]-[M01]-[D01] [H01]:[m01]:[s01]'	Default date/time format string (yyyy-mm-dd ...).
xtlc:default-dt-format-en	xs:string	'[M01]-[D01]-[Y] [H01]:[m01]:[s01]'	Date/time format string (English: mm-dd-yyyy ...).
xtlc:default-dt-format-nl	xs:string	'[D01]-[M01]-[Y] [H01]:[m01]:[s01]'	Date/time format string (Dutch: dd-mm-yyyy ...).
xtlc:internal-error-prompt	xs:string	'Internal error: '	Add this in front of any internal error raised.
xtlc:language-en	xs:string	'en'	Language code for English
xtlc:language-nl	xs:string	'nl'	Language code for Dutch
xtlc:namespace-xtlc-common	xs:string	namespace-uri-for-prefix('xtlc', doc('')/*)	Namespace used for xtpxlib-common.
xtlc:status-codes	xs:string+	(\$xtlc:status-info, \$xtlc:status-warning, \$xtlc:status-error, \$xtlc:status-debug)	Sequence with all valid status codes.
xtlc:status-debug	xs:string	'debug'	Generic debug status/severity code.
xtlc:status-error	xs:string	'error'	Generic error status/severity code.
xtlc:status-info	xs:string	'info'	Generic info (a.k.a. OK) status/severity code.
xtlc:status-warning	xs:string	'warning'	Generic warning status/severity code.

Named template	Description
xtlc:raise-error	Stops any processing by raising an error.

Function	Description
xtlc:apos()	Returns the input string single-quoted ('\$in')
xtlc:att2str()	Turns an attribute into a string representation, suitable for display (e.g. name="value").
xtlc:capitalize()	Capitalizes a string (makes the first character uppercase).
xtlc:char-repeat()	Returns a string with a single character repeated a given number of times.
xtlc:count-leading-whitespace()	Counts the number of whitespace characters at the beginning of a string
xtlc:elm2str()	Turns an element into a descriptive string (the element with all its attributes, excluding schema references).

Function	Description
<code>xtlc:item2element()</code>	Tries to find the element belonging to a given item.
<code>xtlc:items2str()</code>	Creates a string from a sequence of items.
<code>xtlc:prefix-to-length()</code>	Prefixes a string with a given character so it will get at least a given length.
<code>xtlc:q()</code>	Returns the input string quoted (" <code>\$in</code> ")
<code>xtlc:str2bln()</code>	Safe conversion of a string into a boolean.
<code>xtlc:str2filename-safe()</code>	Replaces all characters in a string that are not allowed in filenames with another character.
<code>xtlc:str2filename-safe()</code>	Replaces all characters in a string that are not allowed in filenames with an underscore.
<code>xtlc:str2id()</code>	Turns a string into a valid identifier, adding a prefix.
<code>xtlc:str2id()</code>	Turns a string into a valid identifier.
<code>xtlc:str2int()</code>	Safe conversion of a string to an integer.
<code>xtlc:str2regexp()</code>	Turns a string into a regular expression that matches the input exactly. Optionally anchors the regular expression so the match will be on this string <i>only</i> (result starts with <code>^</code> and ends with <code>\$</code>).
<code>xtlc:str2regexp()</code>	Turns a string into a regular expression that matches the input exactly.
<code>xtlc:str2seq()</code>	Converts a string with a list of words into a sequence of words.
<code>xtlc:text2lines()</code>	Converts text into separate lines.
<code>xtlc:wrap-text()</code>	Takes a string, converts this into words, and puts the words back together again, trying to keep the maximum length of every line below <code>\$line-length</code> . This is not guaranteed, because there may be words that are longer than this!

2.4.1 Named template: `xtlc:raise-error`

Stops any processing by raising an error.

Parameter	Type	Rq?	Default	Description
<code>error-name</code>	<code>xs:string</code>		<code>\$xtlc:status-error</code>	The (optional) name of the error. Must be an NCName.
<code>msg-parts</code>	<code>item()+</code>	yes		Error message to show (in parts, all parts will be concatenated by <code>xtlc:items2str()</code>).

2.4.2 Function: `xtlc:apos()` as `xs:string`

Returns the input string single-quoted ('`$in`')

Parameter	Type	Description
<code>in</code>	<code>xs:string?</code>	String to convert.

2.4.3 Function: `xtlc:att2str()` as `xs:string`

Turns an attribute into a string representation, suitable for display (e.g. `name="value"`).

Parameter	Type	Description
<code>att</code>	<code>attribute()?</code>	Attribute to convert.

2.4.4 Function: `xtlc:capitalize()` as `xs:string`

Capitalizes a string (makes the first character uppercase).

Parameter	Type	Description
<code>in</code>	<code>xs:string</code>	The string to work on.

2.4.5 Function: `xtlc:char-repeat()` as `xs:string`

Returns a string with a single character repeated a given number of times.

Parameter	Type	Description
char	xs:string	The first character of this string is the character to repeat. If empty, an empty string is returned.
repeat	xs:integer	The number of repeats. If ≤ 0 , an empty string is returned.

2.4.6 Function: xtlc:count-leading-whitespace() as xs:integer

Counts the number of whitespace characters at the beginning of a string

Parameter	Type	Description
text	xs:string	Text to work on.

2.4.7 Function: xtlc:elm2str() as xs:string

Turns an element into a descriptive string (the element with all its attributes, excluding schema references).

Parameter	Type	Description
elm	element()?	Element to convert

2.4.8 Function: xtlc:item2element() as element()?

Tries to find the element belonging to a given item.

- When the item is of type `xs:string` or `xs:anyURI`, it is assumed to be a document reference. The root element of this is returned.
- When the item is of type `document-node()`, the root element of this document is returned
- When the item is of type `element()`, this is returned

You can choose whether to produce an error message or `()` when the item cannot be resolved.

Parameter	Type	Description
item	item()	The item to work on
error-on-non-resolve	xs:boolean	Whether to generate an error when <code>\$item</code> could not be resolved. Otherwise, the function will return <code>()</code> .

2.4.9 Function: xtlc:items2str() as xs:string

Creates a string from a sequence of items.

Useful for easy creation of messages consisting of multiple parts and pieces.

Parameter	Type	Description
items	item()*	The message parts to combine

2.4.10 Function: xtlc:prefix-to-length() as xs:string

Prefixes a string with a given character so it will get at least a given length.

Parameter	Type	Description
in	xs:string	String to prefix
prefix-char	xs:string	String to prefix with. Only first character is used. If empty, <code>*</code> is used.
length	xs:integer	The length to reach.

2.4.11 Function: xtlc:q() as xs:string

Returns the input string quoted ("`$in`")

Parameter	Type	Description
in	xs:string?	String to convert.

2.4.12 Function: xtlc:str2bln() as xs:boolean

Safe conversion of a string into a boolean.

When `$in` is empty or not convertible into a boolean, `$default` is returned.

Parameter	Type	Description
<code>in</code>	<code>xs:string?</code>	String to convert.
<code>default</code>	<code>xs:boolean</code>	Default value to return when <code>\$in</code> is empty or cannot be converted.

2.4.13 Function: `xtlc:str2filename-safe()` as `xs:string`

Replaces all characters in a string that are not allowed in filenames with another character.

Parameter	Type	Description
<code>in</code>	<code>xs:string?</code>	String to convert
<code>replace-char</code>	<code>xs:string?</code>	String to replace invalid characters with. Only first character is used. If empty, <code>_</code> is used.

2.4.14 Function: `xtlc:str2filename-safe()` as `xs:string`

Replaces all characters in a string that are not allowed in filenames with an underscore.

Parameter	Type	Description
<code>in</code>	<code>xs:string?</code>	String to convert

2.4.15 Function: `xtlc:str2id()` as `xs:string`

Turns a string into a valid identifier, adding a prefix.

All characters that are not allowed in an identifier are converted into underscores.

When the result does not start with a letter or underscore, the prefix `id-` is added.

Parameter	Type	Description
<code>in</code>	<code>xs:string</code>	String to convert.
<code>prefix</code>	<code>xs:string?</code>	Prefix to apply.

2.4.16 Function: `xtlc:str2id()` as `xs:string`

Turns a string into a valid identifier.

All characters that are not allowed in an identifier are converted into underscores.

When the result does not start with a letter or underscore, the prefix `id-` is added.

Parameter	Type	Description
<code>in</code>	<code>xs:string</code>	String to convert.

2.4.17 Function: `xtlc:str2int()` as `xs:integer`

Safe conversion of a string to an integer.

When `$in` is empty or not convertible to an integer, `$default` is returned.

Parameter	Type	Description
<code>in</code>	<code>xs:string?</code>	String to convert.
<code>default</code>	<code>xs:integer</code>	Default value to return when <code>\$in</code> is empty or cannot be converted.

2.4.18 Function: `xtlc:str2regexp()` as `xs:string`

Turns a string into a regular expression that matches the input exactly. Optionally anchors the regular expression so the match will be on this string *only* (result starts with `^` and ends with `$`).

Parameter	Type	Description
in	xs:string?	String to convert
anchor	xs:boolean	If true, the resulting string will be anchored (start with ^ and ends with \$)

2.4.19 Function: `xtlc:str2regexp()` as `xs:string`

Turns a string into a regular expression that matches the input exactly.

Parameter	Type	Description
in	xs:string?	String to convert

2.4.20 Function: `xtlc:str2seq()` as `xs:string*`

Converts a string with a list of words into a sequence of words.

Parameter	Type	Description
in	xs:string?	String to convert.

2.4.21 Function: `xtlc:text2lines()` as `xs:string*`

Converts text into separate lines.

Uses the LF as separator; CRs are removed.

Parameter	Type	Description
text	xs:string?	The text to convert.
remove-empty-start-end-lines	xs:boolean	When true any empty (containing whitespace only) lines at the beginning and end are removed.
normalize-indents	xs:boolean	When true the indents of the lines are normalized: the indent of the non-whitespace line with the minimum leading whitespace is removed from all other lines. Lines that contain only whitespace will become zero length.

2.4.22 Function: `xtlc:wrap-text()` as `xs:string*`

Takes a string, converts this into words, and puts the words back together again, trying to keep the maximum length of every line below `$line-length`. This is not guaranteed, because there may be words that are longer than this!

If `$line-length` is `le 0`, the function acts like `normalize-space()`.

Any leading and trailing whitespace gets lost.

Parameter	Type	Description
in	xs:string	The input string. An empty sequence returns an empty sequence.
line-length	xs:integer	The maximum line length. If this is <code>le 0</code> , nothing is done beside normalizing the input.

2.5 XSLT (3.0): `href.mod.xsl`

File: `xslmod/href.mod.xsl`

XSLT library module with functions for the generic handling of href-s (filenames/paths).

Prefix	Namespace URI
xtlc	http://www.xtpxlib.nl/ns/common

Variable	Type	Value	Description
xtlc:protocol-file	xs:string	'file'	File protocol specifier.

Function	Description
xtlc:href-add-encoding()	Percent encodes all "strange" characters (%xx). Any existing percentage encodings will be kept as is.
xtlc:href-canonical()	Makes an href canonical (remove any .. and . directory specifiers).
xtlc:href-concat()	Performs a safe concatenation of href components:

Function	Description
<code>xtlc:href-decode-uri()</code>	Reverse function of <code>encode-fo-uri()</code> . Translates percent encodings (%xx) into their actual characters.
<code>xtlc:href-ext()</code>	Returns the extension part of an href.
<code>xtlc:href-is-absolute()</code>	Returns true if the href is considered absolute.
<code>xtlc:href-make-uri()</code>	Turns the concatenation of path components into a true URI. If there is no protocol the file protocol is used.
<code>xtlc:href-name()</code>	Returns the (file)name part of an href.
<code>xtlc:href-name-noext()</code>	Returns the (file)name part of an href without its extension.
<code>xtlc:href-noext()</code>	Returns the complete href path without its extension.
<code>xtlc:href-path()</code>	Returns the path part of an href.
<code>xtlc:href-protocol()</code>	Returns the protocol part of an href (without the <code>://</code>).
<code>xtlc:href-protocol()</code>	Returns the protocol part of an href (without the <code>://</code>) or a default value when none present.
<code>xtlc:href-protocol-add()</code>	Adds a protocol specifier (written without the trailing <code>://</code> , e.g. <code>http</code>) to an href.
<code>xtlc:href-protocol-present()</code>	Returns true when an href has a protocol specifier (e.g. <code>file://</code> or <code>http://</code>).
<code>xtlc:href-protocol-remove()</code>	Removes the protocol part from an href.
<code>xtlc:href-relative()</code>	Computes a relative href from one document to another.
<code>xtlc:href-relative-from-path()</code>	Computes a relative href from a directory path to a document.
<code>xtlc:href-result-doc()</code>	Transforms an href into something <code>xsl:result-document/@href</code> can use.

2.5.1 Function: `xtlc:href-add-encoding()` as `xs:string`

Percent encodes all "strange" characters (%xx). Any existing percentage encodings will be kept as is.

Parameter	Type	Description
href	<code>xs:string</code>	href to work on.

2.5.2 Function: `xtlc:href-canonical()` as `xs:string`

Makes an href canonical (remove any `..` and `.` directory specifiers).

Examples:

- `href-canonical('a/b/./c') ==> 'a/c'`

Parameter	Type	Description
href	<code>xs:string</code>	href to work on.

2.5.3 Function: `xtlc:href-concat()` as `xs:string`

Performs a safe concatenation of href components:

- Translates all backslashes into slashes
- Makes sure that all components are separated with a single slash
- If somewhere in the list is an absolute path, the concatenation stops.

Examples:

- `xtlc:href-concat(('a', 'b', 'c')) ==> 'a/b/c'`
- `xtlc:href-concat(('a', '/b', 'c')) ==> '/b/c'`

Parameter	Type	Description
href-path-components	<code>xs:string*</code>	The path components to concatenate into a full href.

2.5.4 Function: `xtlc:href-decode-uri()` as `xs:string`

Reverse function of `encode-fo-uri()`. Translates percent encodings (%xx) into their actual characters.

Parameter	Type	Description
href	xs:string	href to work on.

2.5.5 Function: xtlc:href-ext() as xs:string

Returns the extension part of an href.

Examples:

- `xtlc:href-ext('a/b/c.xml') ==> 'xml'`
- `xtlc:href-ext('a/b/c') ==> ''`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.6 Function: xtlc:href-is-absolute() as xs:boolean

Returns **true** if the href is considered absolute.

An href is considered absolute when it starts with a / or \, contains a protocol specifier (e.g. **file://**) or starts with a Windows drive letter (e.g. **C:**).

Parameter	Type	Description
href	xs:string	href to work on.

2.5.7 Function: xtlc:href-make-uri() as xs:string

Turns the concatenation of path components into a true URI. If there is no protocol the file protocol is used.

Parameter	Type	Description
href-path-components	xs:string*	The path components to concatenate into a full href.

2.5.8 Function: xtlc:href-name() as xs:string

Returns the (file)name part of an href.

Examples:

- `xtlc:href-name('a/b/c') ==> 'c'`
- `xtlc:href-name('c') ==> 'c'`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.9 Function: xtlc:href-name-noext() as xs:string

Returns the (file)name part of an href without its extension.

Examples:

- `xtlc:href-name-noext('a/b/c.xml') ==> 'c'`
- `xtlc:href-name-noext('a/b/c') ==> 'c'`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.10 Function: xtlc:href-noext() as xs:string

Returns the complete href path without its extension.

Examples:

- `xtlc:href-noext('a/b/c.xml') ==> 'a/b/c'`
- `xtlc:href-noext('a/b/c') ==> 'a/b/c'`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.11 Function: xtlc:href-path() as xs:string

Returns the path part of an href.

Examples:

- `xtlc:href-path('a/b/c') ==> 'a/b'`
- `xtlc:href-path('c') ==> ''`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.12 Function: xtlc:href-protocol() as xs:string

Returns the protocol part of an href (without the `://`).

Examples:

- `xtlc:href-protocol('http://...') ==> 'http'`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.13 Function: xtlc:href-protocol() as xs:string

Returns the protocol part of an href (without the `://`) or a default value when none present.

Examples:

- `xtlc:href-protocol('http://...', 'file') ==> 'http'`
- `xtlc:href-protocol('/a/b/c', 'file') ==> 'file'`

Parameter	Type	Description
href	xs:string	href to work on.
default-protocol	xs:string	Default protocol to return when \$ref contains none.

2.5.14 Function: xtlc:href-protocol-add() as xs:string

Adds a protocol specifier (written without the trailing `://`, e.g. `http`) to an href.

Parameter	Type	Description
href	xs:string	href to work on.
protocol	xs:string	The protocol to add, without a leading <code>://</code> part (e.g. just <code>file</code> or <code>http</code>).
force	xs:boolean	When <code>true</code> an existing protocol is removed first. When <code>false</code> , a reference with an existing protocol is left unchanged.

2.5.15 Function: xtlc:href-protocol-present() as xs:boolean

Returns true when an href has a protocol specifier (e.g. `file://` or `http://`).

Parameter	Type	Description
href	xs:string	href to work on.

2.5.16 Function: xtlc:href-protocol-remove() as xs:string

Removes the protocol part from an href.

Examples:

- `xtlc:protocol-remove('file:///a/b/c') ==> '/a/b/c'`

Weird exceptions:

- `xtlc:protocol-remove('file:/a/b/c') ==> '/a/b/c'`
- `xtlc:protocol-remove('file:/C:/a/b/c') ==> 'C:/a/b/c'`

Parameter	Type	Description
href	xs:string	href to work on.

2.5.17 Function: `xtlc:href-relative()` as `xs:string`

Computes a relative href from one document to another.

Examples:

- `href-relative('a/b/c/from.xml', 'a/b/to.xml') ==> '../to.xml'`
- `href-relative('a/b/c/from.xml', 'a/b/d/to.xml') ==> '../d/to.xml'`

Parameter	Type	Description
from-href	xs:string	href (of a document) of the starting point.
to-href	xs:string	href (of a document) of the target.

2.5.18 Function: `xtlc:href-relative-from-path()` as `xs:string`

Computes a relative href from a directory path to a document.

Examples:

- `href-relative-from-path('a/b/c', 'a/b/to.xml') ==> '../to.xml'`
- `href-relative-from-path('a/b/c', 'a/b/d/to.xml') ==> '../d/to.xml'`

Parameter	Type	Description
from-href-path	xs:string	href (of a directory) of the starting point.
to-href	xs:string	href (of a document) of the target.

2.5.19 Function: `xtlc:href-result-doc()` as `xs:string`

Transforms an href into something `xml:result-document/@href` can use.

`xml:result-document/@href` needs a `file://` in front and has some strict rules about the formatting. The input to this function *must* be an absolute href!

Parameter	Type	Description
href	xs:string	href to work on. Must be absolute!

2.6 XSLT (3.0): `macrodefs.mod.xml`

File: `xmlmod/macrodefs.mod.xml`

Module for handling macro definitions.

A macro definition is a simple `name=value` construct. They are passed around in maps (`map(xs:string, xs:string)`).

The `xtlc:expand-macrodefs()` function expands macro definition references within strings by using `${...}` or `{${...}}`. To prevent the expansion of these constructions, simply double the opening curly brace. All referenced macro definitions must exist, otherwise an error will be raised.

Macro definitions can reference other macro definitions.

Additionally, you can modify the value of a macro by appending one or more flags (separated by colons), for instance `${MACRO:cap:fn:sx}`. For more information on the available flags, refer to the `$xtlc:macrodef-flag-*` global variables.

There are a number of standard macros that can be used. See the `$xtlc:macrodef-standard-*` global variables.

Prefix	Namespace URI
xtlc	http://www.xtpplib.nl/ns/common

Variable	Type	Value	Description
xtlc:macrodef-flag-capitalize	xs:string	'cap'	Macro flag: capitalize (upper-case first character)
xtlc:macrodef-flag-compact	xs:string	'compact'	Macro flag: remove all whitespace
xtlc:macrodef-flag-filename-safe	xs:string	'fns'	Macro flag: make filename safe (replace all characters forbidden in file/directory names with underscores)
xtlc:macrodef-flag-filename-safe-extra	xs:string	'fnsx'	Macro flag: make filename safe, extended (replace all characters forbidden in file/directory names and all whitespace with underscores)
xtlc:macrodef-flag-lower-case	xs:string	'lc'	Macro flag: lower-case
xtlc:macrodef-flag-normalize	xs:string	'normalize'	Macro flag: normalize space
xtlc:macrodef-flag-separator-character	xs:string	':'	Character that separates a macro reference from its flags.
xtlc:macrodef-flag-upper-case	xs:string	'uc'	Macro flag: upper-case
xtlc:macrodef-standard-date	xs:string	'DATE'	Standard macro: date only (YYYY-MM-DD)
xtlc:macrodef-standard-date-compact	xs:string	'DATECOMPACT'	Standard macro: date only, compact (YYYYMMDD)
xtlc:macrodef-standard-datetimeiso	xs:string	'DATETIMEISO'	Standard macro: date/time in ISO format
xtlc:macrodef-standard-time	xs:string	'TIME'	Standard macro: time only (hh:mm:ss)
xtlc:macrodef-standard-time-compact	xs:string	'TIMECOMPACT'	Standard macro: time only, compact (hhmmss)
xtlc:macrodef-standard-time-short	xs:string	'TIMESHORT'	Standard macro: time only without seconds (hh:mm)
xtlc:macrodef-standard-time-short-compact	xs:string	'TIMESHORTCOMPACT'	Standard macro: time only without seconds, compact (hhmm)
xtlc:macrodef-start-character	xs:string	'\$'	Character that starts a macro definition reference.

Named template	Description
xtlc:expand-macro-definitions	Expands macro definitions in text nodes and/or attribute values.
xtlc:macrodefs-as-comment	Outputs a simple comment showing the contents of <code>\$macrodef-map</code> .

Function	Description
xtlc:expand-macrodefs()	Expands macro definition references in a string against the macro definitions in <code>\$macrodef-map</code> . Checks for circular references.
xtlc:get-standard-macrodef-map()	Returns a map with standard macro definitions. See the <code>\$xtlc:macrodef-standard-*</code> global variable definitions.
xtlc:merge-macrodefs()	Merges multiple macro definition maps, taking care that newer definitions override existing ones. Will return an empty map if the input is the empty sequence.

2.6.1 Named template: xtlc:expand-macro-definitions

Expands macro definitions in text nodes and/or attribute values.

The template checks for `<:macrodefs>` elements that are the first child of any element. If so, any `<:macrodef>` children are used to define (or override) macro definitions. These elements can be in any namespace.

See also `xsdmod/macrodefs.mod.xsd`.

You can customize its functionality by using the template parameters.

Parameter	Type	Rq?	Default	Description
add-macrodef-comments	xs:boolean		false()	Whether to add a macro definition comment (summarizing all macro definitions) when a <code><*:macrodefs></code> element is processed.
expand-in-attributes	xs:boolean		true()	Whether to expand the macro definitions in attributes.
expand-in-text	xs:boolean		true()	Whether to expand the macro definitions in text nodes.
ignore-attributes	xs:string*		()	
ignore-elements	xs:string*		()	
in	node()		.	The node for which to expand the macro definitions. Must be an element or a document node.
macrodefs	map(xs:string, xs:string)*		()	Any initial macro definitions.
use-local-macrodefs	xs:boolean		true()	Check for <code><*:macrodefs></code> element as first child and process accordingly
use-standard-macrodefs	xs:boolean		true()	Whether to use the standard macro definitions.

2.6.2 Named template: `xtlc:macrodefs-as-comment`

Outputs a simple comment showing the contents of `$macrodef-map`.

Parameter	Type	Rq?	Default	Description
macrodef-map	map(xs:string, xs:string)	yes		The macro definitions to show in the comment.

2.6.3 Function: `xtlc:expand-macrodefs()` as `xs:string`

Expands macro definition references in a string against the macro definitions in `$macrodef-map`. Checks for circular references.

Parameter	Type	Description
text	xs:string	
macrodef-map	map(xs:string, xs:string)	

2.6.4 Function: `xtlc:get-standard-macrodef-map()` as `map(xs:string, xs:string)`

Returns a map with standard macro definitions. See the `$xtlc:macrodef-standard-*` global variable definitions.

2.6.5 Function: `xtlc:merge-macrodefs()` as `map(xs:string, xs:string)`

Merges multiple macro definition maps, taking care that newer definitions override existing ones. Will return an empty map if the input is the empty sequence.

Parameter	Type	Description
macrodefs	map(xs:string, xs:string)*	The macro definition maps to merge.

2.7 XSLT (3.0): message.mod.xsl

File: xslmod/message.mod.xsl

Message related templates.

A [message](#) is a standardized piece of XML used for inserting (error, debug, etc.) messages into XML documents.

Prefix	Namespace URI
xtlc	http://www.xtpplib.nl/ns/common

Named template	Description
xtlc:msg-create	Generates a standard <code>xtlc:message</code> element.

2.7.1 Named template: xtlc:msg-create as element(xtlc:message)

Generates a standard `xtlc:message` element.

Parameter	Type	Rq?	Default	Description
extra-attributes	attribute()*		()	Any extra attributes to add to the message.
extra-contents	element()*		()	Any extra elements to add to the message.
msg-parts	item()+	yes		Message to show (parts will be concatenated by <code>xtlc:items2str()</code>).
status	xs:string	yes		The status of the message. Must be one of the <code>\$xtlc:status-*</code> constants as defined in general.mod.xsl .

2.8 XSLT (3.0): mimetypes.mod.xsl

File: xslmod/mimetypes.mod.xsl

MIME type conversion related functions.

These conversions work with an [external MIME type/extension table](#).

Prefix	Namespace URI
xtlc	http://www.xtpplib.nl/ns/common

Function	Description
xtlc:ext2mimetype()	Turns an href extension (e.g. <code>xml</code>) into the correct MIME type (<code>'text/xml'</code>).
xtlc:mimetype2ext()	Turns a MIME type (e.g. <code>'text/xml'</code>) into a corresponding href extension (<code>'xml'</code>).

2.8.1 Function: xtlc:ext2mimetype() as xs:string

Turns an href extension (e.g. `xml`) into the correct MIME type (`'text/xml'`).

When it cannot find an appropriate MIME type it returns the empty string.

Parameter	Type	Description
ext	xs:string	The extension to convert.

2.8.2 Function: xtlc:mimetype2ext() as xs:string

Turns a MIME type (e.g. `'text/xml'`) into a corresponding href extension (`'xml'`).

When it doesn't recognize the MIME type it returns the empty string.

Parameter	Type	Description
mimetype	xs:string	The MIME type to convert.

2.9 XSLT (3.0): parameters.mod.xsl

File: xslmod/parameters.mod.xsl

Takes an XML document with parameters and turns this into a parameter map.

More information [here](#).

Prefix	Namespace URI
xtlc	http://www.xtpxlib.nl/ns/common

Variable	Type	Value	Description
xtlc:parameter-group-separator	xs:string	'.'	When a <group> element is encountered, this character is used as a separator after the group's name.
xtlc:parameter-main-trigger-character	xs:string	'\$'	Use this variable for a quick check on whether something might contain a parameter: <code>contains(..., \$xtlc:parameter-main-trigger-character)</code>

Function	Description
xtlc:expand-text-against-parameters()	Expands parameter references in <code>\$text</code> (either <code>{\$....}</code> or <code>#{...}</code>) against the parameters in <code>\$parameter-map</code> . If a parameter has multiple values, only the first one is used.
xtlc:parameters-get()	Tries to locate a <parameters> element (in any namespace) underneath <code>\$root-item</code> and processes the child <parameter> and <group> elements in here into a parameter map.

2.9.1 Function: xtlc:expand-text-against-parameters() as xs:string

Expands parameter references in `$text` (either `{$....}` or `#{...}`) against the parameters in `$parameter-map`. If a parameter has multiple values, only the first one is used.

Parameter	Type	Description
text	xs:string	Text to expand.
parameter-map	map(xs:string, xs:string*)	Map with parameter values.

2.9.2 Function: xtlc:parameters-get() as map(xs:string, xs:string*)

Tries to locate a <parameters> element (in any namespace) underneath `$root-item` and processes the child <parameter> and <group> elements in here into a parameter map.

The <value> elements are filtered according to the entries in `$filters`.

Parameter references in values (either `{$....}` or `#{...}`) are expanded. If a parameter has multiple values, only the first one is used.

Parameter	Type	Description
root-item	item()	Root item under which the first <parameters> element is processed. Can be an href, a document node or an element. See xtlc:item2element() on how this is processed.
filters	map(xs:string, xs:string*)?	Any filters for the parameter's <value> elements.

2.10 XSLT (3.0): simple-macros.mod.xsl

File: xslmod/simple-macros.mod.xsl

(DEPRECATED) Support code for simple macro expansion in strings, e.g. `$NAME`.

Consider using `macrodefs.mod.xsl` instead! There are bugs in the macro expansion (that will not be solved for now).

To stop a macro from expanding, double the `$` character (`$$NAME` becomes `$NAME`).

What is expanded must be in a map formatted as `map{macro: expansion}`, e.g. `map{'NAME': 'thenameofthething'}`

Macros in the string must start with the `xtlc:simpleMacroStart` character (\$).

Prefix	Namespace URI		
<code>xtlc</code>	<code>http://www.xtpxlib.nl/ns/common</code>		
Variable	Type	Value	Description
<code>xtlc:simple-macro-start-character</code>	<code>xs:string</code>	<code>'\$'</code>	
Function	Description		
<code>xtlc:expand-simple-macros()</code>	Expands simple macro's in a string with values. All macros to expand must start with <code>\$xtlc:simple-macro-start-character</code> (\$), for instance: <code>\$DATE</code> .		
<code>xtlc:expand-simple-macros()</code>	Expands simple macro's in a string with values. See <code>xtlc:expand-simple-macros#3</code>		

2.10.1 Function: `xtlc:expand-simple-macros()` as `xs:string`

Expands simple macro's in a string with values. All macros to expand must start with `$xtlc:simple-macro-start-character` (\$), for instance: `$DATE`.

The substitution values are in a map. The keys must be the macro strings. For instance: `map{'DATE': '2023-04-04', 'TIME': '16:04:35'}`

Parameter	Type	Description
<code>in</code>	<code>xs:string</code>	The string to convert.
<code>macros-map</code>	<code>map(xs:string, xs:string)</code>	The map with the macro/substitution values.
<code>filename-safe</code>	<code>xs:boolean</code>	Whether to make all substitutions "filename safe", replacing all invalid characters for a file/directory name with an underscore. Use this when replacing macros in file/directory name strings.

2.10.2 Function: `xtlc:expand-simple-macros()` as `xs:string`

Expands simple macro's in a string with values. See `xtlc:expand-simple-macros#3`

Parameter	Type	Description
<code>in</code>	<code>xs:string</code>	The string to convert.
<code>macros-map</code>	<code>map(xs:string, xs:string)</code>	The map with the macro/substitution values.

2.11 XSLT (3.0): `uuid.mod.xsl`

File: `xslmod/uuid.mod.xsl`

UUID related functions.

Works only in Saxon PE or EE (not in the free HE), because we are calling an underlying Java function.

Prefix	Namespace URI		
<code>xtlc</code>	<code>http://www.xtpxlib.nl/ns/common</code>		
Function	Description		
<code>xtlc:get-uuid()</code>	Returns a random unique UUID (by calling an underlying Java function)		
<code>xtlc:is-real-uuid()</code>	Checks whether a string contains a "real" UUID (conforms to the UUID formatting rules).		

2.11.1 Function: `xtlc:get-uuid()` as `xs:string`

Returns a random unique UUID (by calling an underlying Java function)

2.11.2 Function: `xtlc:is-real-uuid()` as `xs:boolean`

Checks whether a string contains a "real" UUID (conforms to the UUID formatting rules).

Example: `5EAE5C68-7394-48d7-A50B-1669E8D3A6C9` (upper/lower-case both admitted)

Parameter	Type	Description
<code>id</code>	<code>xs:string?</code>	UUID to check.

3 XProc 3.0 Support

Module/Pipeline	Description
copy-dir.xpl	This step copies a directory and all its contents from one location to the other.
create-clear-directory.xpl	This step does two things:
expand-generators.mod.xpl	Library with steps for handling generate elements (see ../xsdmod/generate.mod.xsd).
expand-macro-definitions.xpl	This is an XProc driver for the <code>xtlc:expand-macro-definitions</code> template in <code>xs1mod/macroddefs.mod.xsl</code> .
is-out-of-date.xpl	Step that finds out if a list of target files is out-of-date against a list of source files.
message.xpl	
recursive-directory-list.xpl	Extension of standard the <code>p:directory</code> list step. Returns the contents of a directory, going into sub-directories recursively. Adds the possibility to "flatten" the list.
subdir-list.xpl	Returns an XML document with the sub-directories of a given directory.
validate.xpl	This step performs validation using a W3C Schema and/or Schematron. It breaks the processing if something is wrong.
write-log.xpl	Writes an entry to a log file.
zip-directory.xpl	Zips a directory into a single zip file.

Table 3-1 - Module overview

3.1 XProc (3.0) pipeline: copy-dir.xpl

File: `xpl3mod/copy-dir/copy-dir.xpl`

Type: `xtlc:copy-dir`

This step copies a directory and all its contents from one location to the other.

- If `$clear-target` is true (default), before copying the target directory is cleared/emptied.
- If the source directory is empty, it simply creates an empty target directory.
- It can do include/exclude filtering, like `p:directory-list`

The step itself acts as an identity step.

Port	Type	Primary?	Description
source	in	yes	
result	out	yes	

Option	Type	Rq?	Default	Description
clear-target	xs:boolean		true()	Whether to clear the target before copying.
depth	xs:integer		-1	The sub-directory depth to go. When it 0, all sub-directories are processed.
exclude-filter	xs:string*		'\..git/'	Regular expression(s) for files to be excluded from the copy. By default, git directories are excluded
href-source	xs:string	yes		The full path/URI of the source directory. If the directory does not exist, nothing will happen.
href-target	xs:string	yes		The full path/URI of the target directory. Any non-existing parent directories leading up to this directory will be automatically created.
include-filter	xs:string*		()	Regular expression(s) files to be included in the copy.

3.2 XProc (3.0) pipeline: create-clear-directory.xpl

File: `xpl3mod/create-clear-directory/create-clear-directory.xpl`

Type: `xtlc:create-clear-directory`

This step does two things:

- When `$clear` is true, it removes an (optionally) existing directory
- Then it makes sure the directory always exists

It doesn't matter whether the directory exists beforehand.

The step itself acts as an identity step.

Port	Type	Primary?	Description
source	in	yes	
result	out	yes	

Option	Type	Rq?	Default	Description
clear	xs:boolean		true()	Whether or not to empty an existing directory.
href-dir	xs:string	yes		The full path/URI of the directory to delete.

3.3 XProc (3.0) library: expand-generators.mod.xpl

File: xpl3mod/expand-generators/expand-generators.mod.xpl

Library with steps for handling generate elements (see ../../xsdmod/generate.mod.xsd).

A generator is either a stylesheet or a pipeline:

- The stylesheet gets the generate element as its input.
- The pipeline must have a primary input called source and output port called result. Both XML, non-sequence. The generate element will be present on its input port.

The outcome of a generator must be a single well-formed XML document.

- If the root element is `_GENERATED`, it will be removed/unwrapped. This allows returning multiple elements.
- If the root element is `_EMPTY`, the result will be discarded.

Prefix	Namespace URI
xtlc	http://www.xtpxlib.nl/ns/common

Step	Description
xtlc:expand-generators	Expands all the generate elements in a document.
xtlc:handle-generate-element	Handles a single generate element(on its source port).

3.3.1 Step: xtlc:expand-generators

Expands all the generate elements in a document.

Port	Type	Primary?	Description
source	in	yes	The document to expand the generate elements in.
result	out	yes	The resulting document.

3.3.2 Step: xtlc:handle-generate-element

Handles a single generate element(on its source port).

Port	Type	Primary?	Description
source	in	yes	The generate element to handle
result	out	yes	The resulting XML. This might be empty.

3.4 XProc (3.0) pipeline: expand-macro-definitions.xpl

File: xpl3mod/expand-macro-definitions/expand-macro-definitions.xpl

Type: xtlc:expand-macro-definitions

This is an XProc driver for the `xtlc:expand-macro-definitions` template in `xslmod/macrodefs.mod.xsl`.

Port	Type	Primary?	Description
source	in	yes	The document to expand the macro definition references in
result	out	yes	The resulting document with the macro definitions expanded.

Option	Type	Rq?	Default	Description
add-macrodef-comments	xs:boolean		false()	Whether to add a macro definition comment (summarizing all macro definitions) when a <code><*:macrodefs></code> element is processed.
expand-in-attributes	xs:boolean		true()	Whether to expand the macro definitions in attributes.
expand-in-text	xs:boolean		true()	Whether to expand the macro definitions in text nodes.
ignore-attributes	xs:string*		()	Attribute names to ignore.
ignore-elements	xs:string*		()	Element names to ignore.
macrodefs	map(xs:string, xs:string)*		()	Any initial macro definitions.
use-local-macrodefs	xs:boolean		true()	Check for <code><*:macrodefs></code> element as first child and process accordingly
use-standard-macrodefs	xs:boolean		true()	Whether to use the standard macro definitions.

3.5 XProc (3.0) pipeline: is-out-of-date.xpl

File: xpl3mod/is-out-of-date/is-out-of-date.xpl

Type: xtlc:is-out-of-date

Step that finds out if a list of target files is out-of-date against a list of source files.

Port	Type	Primary?	Description
result	out	yes	A single c:result document, containing either true (out-of-date) or false(not out-of-date).

Option	Type	Rq?	Default	Description
href-sources	xs:string+	yes		A list of source files. These files must exist.
href-targets	xs:string+	yes		A list of target files. If one of these does not exist, the whole thing is out-of-date.
process-xincludes	xs:boolean		false()	Whether to take XInclude-d files also into account (recursively).

3.6 XProc (3.0) library: message.xpl

File: xpl3mod/message/message.xpl

Prefix	Namespace URI
xtlc	http://www.xtpplib.nl/ns/common

3.6.1 Step: xtlc:message

Writes a message to the console, taking care of indents and a prompt. The step itself acts as an identity step.

Port	Type	Primary?	Description
source	in	yes	
result	out	yes	

Option	Type	Rq?	Default	Description
debug	xs:boolean		false()	Turns the prompt into \$debug-marker in-between the prompt characters to signify a debug message.
debug-marker	xs:string		\$xtlc:default-message-debug-marker	The marker for a debug message.
enabled	xs:boolean		true()	Another way to determine whether the message should appear.
level	xs:integer		0	The indent for the message.
prompt-string	xs:string		\$xtlc:default-message-prompt	The prompting character(s) to use (after an indent).
silent	xs:boolean		false()	Whether the message should appear.
text	xs:string*		()	Every member of this sequence gets a line on its own. If empty, an empty line is output.

3.7 XProc (3.0) pipeline: recursive-directory-list.xpl

File: xpl3mod/recursive-directory-list/recursive-directory-list.xpl

Type: xtlc:recursive-directory-list

Extension of standard the `p:directory` list step. Returns the contents of a directory, going into sub-directories recursively. Adds the possibility to "flatten" the list.

This step will also *not* throw an error when the directory does not exist. Instead it will simply return an empty result (with an `error="true"` attribute).

Port	Type	Primary?	Description
result	out	yes	The resulting directory structure in XML format. See the standard <code>p:directory-list</code> step for a more detailed description.

Option	Type	Rq?	Default	Description
add-decoded	xs:boolean		false()	When <code>true</code> and <code>\$flatten</code> is <code>true</code> , attributes <code>@href-rel-decoded</code> and <code>@href-abs-decoded</code> are added in which any percent encoded characters are decoded.
depth	xs:integer		-1	The sub-directory depth to go. When lt 0, all sub-directories are processed.
detailed	xs:boolean		false()	Whether to add detailed information.
exclude-filter	xs:string*		'.git/'	Optional regular expression exclude filters. By default, git directories are excluded.
flatten	xs:boolean		false()	When <code>true</code> , the list will be "flattened": All <code>c:file</code> children will be direct children of the root's <code>c:directory</code> element. These <code>c:file</code> elements get a <code>@name</code> , <code>@href-abs</code> (absolute filename) and <code>@href-rel</code> (relative filename) attribute.
include-filter	xs:string*			Optional regular expression include filters.

Option	Type	Rq?	Default	Description
override-content-types	array(array(xs:string))?		()	Override content types specification (see description of p:directory-list).
path	xs:string	yes		The path to get the directory listing from.

3.8 XProc (3.0) pipeline: subdir-list.xpl

File: xpl3mod/subdir-list/subdir-list.xpl

Type: xtlc:subdir-list

Returns an XML document with the sub-directories of a given directory.

```
<subdir-list href="...">
  <subdir href="..." name="..." />
  ...
</subdir-list>
```

If an error occurs, it will only return the root element with an additional error="true" attribute. Will not recurse!

Port	Type	Primary?	Description
result	out	yes	The sub-directory listing (as described above).

Option	Type	Rq?	Default	Description
path	xs:string	yes		The path to get the sub-directories from. Always use an absolute path!

3.9 XProc (3.0) pipeline: validate.xpl

File: xpl3mod/validate/validate.xpl

Type: xtlc:validate

This step performs validation using a W3C Schema and/or Schematron. It breaks the processing if something is wrong.

This might seem superfluous (there are already **p:validate-with...** steps), but often these steps *change* the document. This step performs like a real identity step.

Port	Type	Primary?	Description
source	in	yes	Document to validate.
result	out	yes	The same as the input document.

Option	Type	Rq?	Default	Description
enabled	xs:boolean		true()	Whether all validation is enabled. If false, nothing happens.
href-schema	xs:string?		()	Optional reference to an W3C Schema to validate the document with. If (), no schema validation will be performed.
href-schematron	xs:string?		()	Optional reference to a Schematron Schema to validate the document with. If (), no Schematron validation will be performed.
schema-version	xs:string?		()	The W3C Schema version to use. If empty, the pipeline tries to detect the version.
simplify-error-messages	xs:boolean		false()	Whether to simplify the error messages. Only output the first error.

3.10 XProc (3.0) pipeline: write-log.xpl

File: xpl3mod/write-log/write-log.xpl

Type: xtlc:write-log

Writes an entry to a log file.

With regards to documents flowing through, acts like a **p:identity** step.

Port	Type	Primary?	Description
source	in	yes	Documents will be passed unchanged to the result port.
result	out	yes	Documents coming from the source port, unchanged.

Option	Type	Rq?	Default	Description
additional-attributes	map(xs:QName, xs:string)?		()	A map with additional attributes to add to the log entry's entry element.
additional-elements	element()*		()	Elements with additional information to add to this log entry.
enable	xs:boolean		true()	Whether the logging will be done at all.
enable-debug-messages	xs:boolean		true()	Whether messages with debug status will be written as well.
href-log	xs:string	yes		URI of the file to write the log entries to.
keep-entries	xs:integer		0	The number of entries to keep in the logfile. If le 0, all messages are kept.
log-comments	xs:string*		()	Any comments to write as file header when creating a new log file. Ignored on an existing log file.
messages	xs:string+	yes		The actual texts/lines of the log entry to write. All will become a separate message element.
status	xs:string		'info'	Status of the entry. Must be info , warning , error or debug .

3.11 XProc (3.0) pipeline: zip-directory.xpl

File: xpl3mod/zip-directory/zip-directory.xpl

Type: xtlc:zip-directory

Zips a directory into a single zip file.

Port	Type	Primary?	Description
result	out	yes	The archive manifest of the created zip file.

Option	Type	Rq?	Default	Description
base-path	xs:string	yes		URI of the directory which contents will be stored in the zip.
depth	xs:integer		-1	The sub-directory depth to go. When lt 0, all sub-directories are processed.
exclude-filter	xs:string*		'.git/'	Optional regular expression exclude filters. By default, git directories are excluded.
href-target-zip	xs:string	yes		URI for the zip file to produce.
include-base	xs:boolean		true()	When true, the last part of \$base-path (for instance a/b/c ==> c) is used as root directory for entries in the zip file.
include-filter	xs:string*			Optional regular expression include filters.

3.12 oXygen XProc 3.0 support (oXygen versions < 26)

oXygen versions < 26 had nor editing support for XProc 3.0. The component contains an oXygen framework that enables validating XProc 3.0 documents. To use this:

- Add the framework to the oXygen configuration:
 - Menu: Options / Preferences...
 - Navigate to: Document Type Association / Locations
 - Add the full path to **xtpxlib-common/frameworks**

- Navigate on up to: Document Type Association
- Check that the XProc 3.0 framework is enabled
- Disable the use of the XProc 1.0 support in oXygen. To do this:
 - Menu: Options / Preferences...
 - Navigate to: File types
 - Associate the file types that you use for XProc 3.0 (in my case `.xp1` files) with the plain XML editor

4 XProc 1.0 Support

The xtpxlib-common component contains the following XProc 1.0 library module:

WARNING: XProc 1.0 support is considered deprecated and will be removed in the near future!

Module/Pipeline	Description
common.mod.xpl	XProc (1.0) library with generic steps.

Table 4-1 - Module overview

4.1 XProc (1.0) library: common.mod.xpl

File: `xplmod/common.mod/common.mod.xpl`

XProc (1.0) library with generic steps.

Prefix	Namespace URI
<code>xtlc</code>	<code>http://www.xtpxlib.nl/ns/common</code>

Step	Description
xtlc:copy-directory	Copies a full directory structure.
xtlc:copy-file	Copies a file, if necessary from inside a zip file.
xtlc:log	Writes a message to a log file.
xtlc:recursive-directory-list	Returns the contents of a directory, going into sub-directories recursively. When the requested directory does not exist, it returns only a <code>c:directory</code> root element with an <code>error="true"</code> attribute.
xtlc:remove-dir	Removes a full directory. When the directory does not exist, everything continues without error.
xtlc:tee	Tees the input to a file and passes it unchanged (like the Unix tee command).
xtlc:zip-directory	Zips a directory and its sub-directories into a single zip file.

4.1.1 Step: [xtlc:copy-directory](#)

Copies a full directory structure.

Port	Type	Primary?	Description
<code>source</code>	in	yes	Input, will be passed unchanged.
<code>result</code>	out	yes	The input unchanged.

Option	Rq?	Default	Description
<code>href-source-dir</code>	yes		Reference to the directory to copy from (must have a leading <code>file:/</code> specifier!).
<code>href-target-dir</code>	yes		Reference to the directory to copy to (must have a leading <code>file:/</code> specifier!). If it does not exist the step will try to create it.

4.1.2 Step: [xtlc:copy-file](#)

Copies a file, if necessary from inside a zip file.

Port	Type	Primary?	Description
<code>source</code>	in	yes	Input, will be passed unchanged.
<code>result</code>	out	yes	The input unchanged.

Option	Rq?	Default	Description
<code>enable</code>		<code>true()</code>	Whether the copying is done at all.
<code>href-source</code>	yes		Reference to the source file to copy (must have a leading <code>file:/</code> specifier!).
<code>href-source-zip</code>		<code>''</code>	Document reference to a zip file (must have a leading <code>file:/</code> specifier!). When filled, <code>\$href-source</code> is assumed to be a path inside this zip.
<code>href-target</code>	yes		Reference to the target.

4.1.3 Step: xtlc:log

Writes a message to a log file.

Port	Type	Primary?	Description
source	in	yes	Input to the logging, will be passed unchanged to the output
result	out	yes	The input unchanged.

Option	Rq?	Default	Description
enable		true()	Whether the logging will be done at all.
href-log	yes		Name of the file to write the log messages to (must have a leading file:/ specifier!).
keep-messages		100	The number of messages to keep in the logfile. If le 0, all messages are kept. Set by default to 100 to prevent overflowing files...
message	yes		The actual log message to write.
status		'ok'	Status of the message. Must be ok, warning, error or debug.

4.1.4 Step: xtlc:recursive-directory-list

Returns the contents of a directory, going into sub-directories recursively. When the requested directory does not exist, it returns only a **c:directory** root element with an **error="true"** attribute.

Adapted from Norman Walsh's [example code](#).

Port	Type	Primary?	Description
result	out	yes	The resulting directory structure listing in XML format.

Option	Rq?	Default	Description
depth		-1	The sub-directory depth to go. When le 0, all sub-directories are processed.
exclude-filter			An optional regular expression exclude filter.
flatten		false()	When true, the list will be "flattened": All c:file children will be direct children of the root's c:directory element. These c:file elements get a @name , @href-abs (absolute filename) and @href-rel (relative filename) attribute.
include-filter			An optional regular expression include filter.
path	yes		The path to get the directory listing from.

4.1.5 Step: xtlc:remove-dir

Removes a full directory When the directory does not exist, everything continues without error.

Port	Type	Primary?	Description
source	in	yes	Input, will be passed unchanged.
result	out	yes	The input unchanged.

Option	Rq?	Default	Description
enable		true()	Whether the removal is done at all.
href-dir	yes		Reference to the directory to remove (must have a leading file:/ specifier!).

4.1.6 Step: xtlc:tee

Tees the input to a file and passes it unchanged (like the Unix tee command).

Port	Type	Primary?	Description
source	in	yes	Input to the tee.
result	out	yes	The input unchanged (unless a <code>\$root-attribute-href</code> was specified).

Option	Rq?	Default	Description
enable		true()	Whether to actually do the write. When false , nothing happens.
href	yes		Name of the file to write to (must have a leading file:/ specifier!)
indent		true()	Whether or not to indent the tee-d output.
root-attribute-href		' '	If filled, \$href is recorded as an attribute with this name on the root element of the original input. Must be a valid attribute name.

4.1.7 Step: xtlc:zip-directory

Zips a directory and its sub-directories into a single zip file.

Port	Type	Primary?	Description
result	out	yes	The output of the actual zip step, listing all the files that went in.

Option	Rq?	Default	Description
base-path	yes		Directory which contents will be stored in the zip (must have a leading file:/ specifier!)
href-target-zip	yes		Document reference for the zip file to produce (must have a leading file:/ specifier!)
include-base		true()	When true, the last part of \$base-path (e.g. a/b/c ==> c) is used as the root directory in the zip file.

5 XSLT Stylesheets

The xtpplib-common component contains the following XSLT Stylesheets:

Module/Pipeline	Description
expand-macro-definitions.xsl	This is a driver for the <code>xtlc:expand-macro-definitions</code> template in <code>xslmod/macrodefs.mod.xsl</code> .
get-system-properties.xsl	Gets all the XSLT available system properties (as returned by <code>system-property()</code>).
xslmod2xqmod-stub.xsl	This stylesheet translates an XSLT module (in <code>xtpplib</code> "style") into a stub for an XQuery Module. After this you still need to hand-edit it to make it all work.

Table 5-1 - Module overview

5.1 XSLT (3.0): expand-macro-definitions.xsl

File: `xsl/expand-macro-definitions.xsl`

This is a driver for the `xtlc:expand-macro-definitions` template in `xslmod/macrodefs.mod.xsl`.

Parameter	Type	Rq?	Default	Description
<code>add-macrodef-comments</code>	<code>xs:boolean</code>		<code>false()</code>	Whether to add a macro definition comment (summarizing all macro definitions) when a <code><*:macrodefs></code> element is processed.
<code>expand-in-attributes</code>	<code>xs:boolean</code>		<code>true()</code>	Whether to expand the macro definitions in attributes.
<code>expand-in-text</code>	<code>xs:boolean</code>		<code>true()</code>	Whether to expand the macro definitions in text nodes.
<code>ignore-attributes</code>	<code>xs:string*</code>		<code>()</code>	
<code>ignore-elements</code>	<code>xs:string*</code>		<code>()</code>	
<code>in</code>	<code>node()</code>		<code>.</code>	The node for which to expand the macro definitions. Must be an element or a document node.
<code>macrodefs</code>	<code>map(xs:string, xs:string)*</code>		<code>()</code>	Any initial macro definitions.
<code>use-local-macrodefs</code>	<code>xs:boolean</code>		<code>true()</code>	Check for <code><*:macrodefs></code> element as first child and process accordingly
<code>use-standard-macrodefs</code>	<code>xs:boolean</code>		<code>true()</code>	Whether to use the standard macro definitions.

5.2 XSLT (2.0): get-system-properties.xsl

File: `xsl/get-system-properties.xsl`

Gets all the XSLT available system properties (as returned by `system-property()`).

5.3 XSLT (2.0): xslmod2xqmod-stub.xsl

File: `xsl/xslmod2xqmod-stub.xsl`

This stylesheet translates an XSLT module (in `xtpplib` "style") into a stub for an XQuery Module. After this you still need to hand-edit it to make it all work.

See as an example [href.mod.xsl](#). Large parts of this module were turned into XQuery by this stylesheet. The result (edited after this initial conversion) is in the `xqmod` directory of this component.

6 XML Data Files

The xtpxlib-common component contains the following XML data files:

Module/Pipeline	Description
dummy.xml	Dummy file to use as input for processes that require an XML input document but the input is ignored.
fop-default-config.xml	Default configuration file for the FOP XSL-FO renderer.
mimetypes-table.xml	Table used for transforming file extensions into a MIME type and vice versa.

Table 6-1 - Module overview

6.1 XML document: dummy.xml

File: `data/dummy.xml`

Root element: `<dummy>`

Dummy file to use as input for processes that require an XML input document but the input is ignored.

6.2 XML document: fop-default-config.xml

File: `data/fop-default-config.xml`

Root element: `<fop>`

Default configuration file for the FOP XSL-FO renderer.

The only thing this configuration file does is set the font handling to "auto-detect" (meaning it will try the use the system fonts).

6.3 XML document: mimetypes-table.xml

File: `data/mimetypes-table.xml`

Root element: `<mimetypes>` (namespace: `http://www.xtpxlib.nl/ns/mimetypes`)

Table used for transforming file extensions into a MIME type and vice versa.

Follows the [mimetypes.xsd](#) schema. Used internally by the [mimetypes.mod.xsl](#) module, but might also be useful in other situations.

7 XML Schemas

The xtpplib-common component contains the following XML Schemas:

Module/Pipeline	Description
message.xsd	Schema for messages used and created by this component.
mimetypes.xsd	Schema for the MIME type association datafile.
parameters.xsd	Schema for sets of parameters as used by this library.

Table 7-1 - Module overview

7.1 XML Schema: message.xsd

File: `xsd/message.xsd`

Target namespace: `http://www.xtpplib.nl/ns/common`

Schema for messages used and created by this component.

See also [message.mod.xsl](#).

Element	Description
message	A message generated by this component.

7.2 XML Schema: mimetypes.xsd

File: `xsd/mimetypes.xsd`

Target namespace: `http://www.xtpplib.nl/ns/mimetypes`

Schema for the MIME type association datafile.

See also [mimetypes-table.xml](#) and [mimetypes.mod.xsl](#).

Element	Description
mimetypes	Root element of the MIME types associaton list.

7.3 XML Schema: parameters.xsd

File: `xsd/parameters.xsd`

Schema for sets of parameters as used by this library.

Use [parameters.mod.xsl](#) for turning these lists into maps. An explanation of the parameter mechanism can be found [here](#).

Although this is schema for no namespace, parameters can be in *any* namespace (if you use [parameters.mod.xsl](#) for processing them).

Element	Description
parameters	Root element for a set of parameters (either in a document on its own or embedded).