

xtpxlib-xdoc

An xtpxlib component for generating documentation

0 Table of Contents

0 Documentation generation with xtpxlib-xdoc	2
1 Description	3
1.1 The main toolchain	3
2 Instructions	5
2.1 Getting started	5
2.2 Validation	5
2.3 Parameter substitution	5
2.4 xdoc transforms	6
3 xdoc transforms	7
3.1 Running an xdoc transform	7
3.2 Built-in xdoc transformations	7
3.2.1 XProc (1.0) pipeline: code-docgen-dir.xpl	7
3.2.2 XProc (1.0) pipeline: code-docgen.xpl (xdoc:code-docgen)	8
3.2.3 XProc (1.0) pipeline: include-docbook.xpl	8
3.2.4 XProc (1.0) pipeline: xml-description.xpl	9
3.3 Writing your own xdoc transformations	9
4 XProc Pipelines	11
4.1 XProc (1.0) pipeline: docbook-to-pdf.xpl (xdoc:docbook-to-pdf)	11
4.2 XProc (1.0) pipeline: docbook-to-xhtml.xpl (xdoc:docbook-to-xhtml)	11
4.3 XProc (1.0) pipeline: xdoc-to-docbook.xpl (xdoc:xdoc-to-docbook)	12
4.4 XProc (1.0) pipeline: xdoc-to-pdf.xpl (xdoc:xdoc-to-pdf)	12
4.5 XProc (1.0) pipeline: xdoc-to-xhtml.xpl (xdoc:xdoc-to-xhtml)	13
5 XProc Libraries	14
5.1 XProc (1.0) library: xtpxlib-xdoc.mod.xpl	14
5.1.1 Step: xdoc:markdown-to-docbook	14
6 DocBook dialect	15
6.1 Supported root elements	15
6.2 Document information	15
6.3 Chapter/Section structure	15
6.4 Block constructions	15
6.5 Inline elements	17
6.6 Other constructs	19
6.7 Fixed-width column mechanism	19

0 Documentation generation with xtpxlib-xdoc



xtpxlib library - component **xtpxlib-xdoc** - **v0.0** (2019-11-28)

Xatapult Content Engineering - <http://www.xatapult.com> - +31 6 53260792

Erik Siegel - erik@xatapult.com

xtpxlib-xdoc is part of the **xtpxlib** library. **xtpxlib** contains software for processing XML, using languages like XSLT and XProc. It consists of several separate components, all named **xtpxlib-***. Everything can be found on GitHub (<https://github.com/xatapult>).

xtpxlib-xdoc TBD

Installation and usage information can be found on **xtpxlib**'s main website <https://www.xtpxlib.org>.

Technical information:

Component documentation: <https://xdoc.xtpxlib.org>

License: GNU GENERAL PUBLIC LICENSE - Version 3, 29 June 2007

Git URI: `git@github.com:xatapult/xtpxlib-xdoc.git`

Git site: <https://github.com/xatapult/xtpxlib-xdoc>

This component depends on:

- [xtpxlib-container](#) (Support for XML containers (multiple files wrapped into one))
- [xtpxlib-common](#) (Common component: Shared libraries and IDE support)

1 Description

Have you ever struggled with producing technical documentation for your software, content model or anything else? Big chance that you have had to deal with repeating constructs: Explaining XML elements and attributes, documenting functions, procedures and variables, etc. The same constructs over and over again, usually with complex tables, little pieces of program listings or other things that are difficult to keep consistent and maintain. The xtpplib component **xtpplib-xdoc** tries to alleviate this problem. **xtpplib-xdoc**'s starting point is *narrative* documentation written in [DocBook 5.1](#). On top of this it adds a number of extensions. This source format, DocBook + extensions, is called *xdoc*.

The **xtpplib-xdoc** XProc (1.0) pipelines turns the *xdoc* format into "pure" DocBook. From there it can be converted into PDF or HTML using standard DocBook technology. The **xtpplib-xdoc** component itself also contains conversions into PDF (through XSL-FO) and HTML. These work out of the box but, especially the PDF one, uses a layout that might not be what you want or need. But since the source is available you can tweak it to your heart's desire.

xtpplib-xdoc currently allows two types of extensions on top of DocBook:

Parameter expansion

Parameters, coming from some parameter source, are expanded. This useful for, for instance, status information, dates/times, standard words and phrases, etc. This uses the [parameter mechanism](#) as introduced in xtpplib's [common component](#).

Transforms

The so-called *xdoc* transforms convert something, usually some piece of XML, into DocBook and insert the result back in the main document. This is extremely useful for *consistent* and *repeating* documentation generation.

Curious to see it in action. Want to know more? Checkout the "Instructions" on page 5 section.

1.1 The main toolchain

The following figure illustrates **xtpplib-xdoc**'s main toolchain:




Figure 1-1 - **xtpplib-xdoc**'s main toolchain

1. The **xtpplib-xdoc** module uses a format called *xdoc* as its source format. The basis of *xdoc* is [DocBook 5.1](#). On top of this *xdoc* adds extensions for parameter handling and code/markup/text generation.
2. The first processing step in the toolchain performs basic XInclude processing. This means that you can build your document from smaller parts, for instance one document per chapter.
Another application of the XInclude processing is to get the data in for the *xdoc* transform processing in step 5.
3. The next step is to expand any parameter references in the source document. A parameter is a name/value pair. To expand its value in the document use either `${name}` or `{ $name }` (both mean the same). Parameters are expanded both in text and in attribute values.

4. Parameters come from two sources:

- An (optional) parameter document. This document must use the format as handled by the [parameter mechanism](#) of xtpxlib's [common component](#).
- The toolchain automatically creates some parameters.

See here for details and usage instructions

5. Next the so-called *xdoc transforms* are processed. A transform consists of an `<xdoc:transform>` element (the namespace prefix `xdoc:` must be bound to `http://www.xtpxlib.nl/ns/xdoc`). An XSLT stylesheet or XProc (1.0) pipeline is triggered that gets this `<xdoc:transform>` element (with all attributes and child elements) as input and results in the injection of generated DocBook.

6. The transformations triggered by `<xdoc:transform>` can come from two sources:

- Transformations that are built into the **xtpxlib-xdoc** component. These are generic transformations for, for instance, documenting XML structures or generating code documentation. An overview of these can be found in [\[TBD\]](#).
- Your own transformations. Guidelines on how to write these can found in [\[TBD\]](#).

7. The result of the toolchain so-far is a document in "pure" [DocBook 5.1](#).

8. From this you can transform to some target format.

The **xtpxlib-xdoc** component contains transformations to both PDF and HTML (see [\[TBD\]](#)).

These transformations can only handle a subset of the full DocBook standard. The result will be rather specific for the **xtpxlib-xdoc** component and might not be directly usable for other use-cases. To amend this you can copy-and-adapt these transformations or use some other DocBook conversion.

9. Finally, the result of all this is a document in the desired target format.

Information about the pipelines that implement this toolchain can be found in [\[TBD\]](#)

2 Instructions

2.1 Getting started

The `template/` sub-directory of `xtpxlib-xdoc` contains several template files that can be used as a starting point. These templates also declare the necessary namespace `http://www.xtpxlib.nl/ns/xdoc`, bound to the prefix `xdoc:`.

Use one of the XProc (1.0) processing pipelines to process an `xdoc` source into DocBook, PDF or HTML. For instance `xdoc-to-docbook` will turn your `xdoc` source into "pure" DocBook.

2.2 Validation

The `xtpxlib-xdoc` component contains an enhanced DocBook NVDL schema, `xsd/docbook/docbook.nvdl`, that allows the `xdoc` extensions.

The template files in the `template/` sub-directory reference this schema. Don't forget to change this reference and keep it valid if you copy such a template to a directory of your own!

2.3 Parameter substitution

The `xdoc` framework performs parameter substitution. `${parameter-name}` and `{parameter-name}` (both mean the same) are substituted with the parameter's value (if it exists). Substitution takes place in attribute and text values. To stop such a `${...}` construction from being substituted, *double* the opening curly brace (`{{}}`).

The `xdoc` toolchain automatically creates a number of parameters:

Parameter	Description	Example value(s)
DATETIME	The date and time the toolchain executed in YYYY-MM-DD hh:mm:ss format.	2019-11-11 12:12:12
DATE	The date part of the DATETIME parameter.	2019-11-11
TIME	The time part of the DATETIME parameter.	12:12:12
HREF-SOURCE	The main source's filename.	C:/my/path/sourcedoc.xml /my/path/sourcedoc.xml

Table 2-1 - Parameters added by the **xtpxlib-xdoc** toolchain

To specify your own parameters, create an XML document that looks like this:

```
<parameters>
  <parameter name="my-parameter">
    <value>Some value...</value>
  </parameter>
</parameters>
```

The parameter XML format has several additional features, like filtering and grouping values. It's also namespace independent and might be embedded in a bigger document. See the format's [description](#) for more information.

A reference to such a parameter document must be passed as option `href-parameters` to one of the processing pipelines.

To see which parameters are available in your `xdoc` pipelines, add the following to your document:

```
<xdoc:dump-parameters type="table"/>
```

The documentation you're looking at is also produced with the `xdoc` mechanism. The result of a parameter dump during its build process is:

Parameter	Value
DATE	2019-12-17
DATETIME	2019-12-17 11:37:23
HREF-SOURCE	C:/Data/Erik/work/xatapult/xtpxlib-xdoc/doc/source/xtpxlib-xdoc-chapter-instructions.xml
TIME	11:37:23

Parameter	Value
active-components	xtpplib-common
author-email-address	erik@xatapult.com
author-name	Erik Siegel
component-current-release-date	2019-11-28
component-current-release-version	0.0
component-display-name	xtpplib-xdoc
component-documentation-uri	https://xdoc.xtpplib.org
component-git-site-uri	https://github.com/xatapult/xtpplib-xdoc
component-git-uri	git@github.com:xatapult/xtpplib-xdoc.git
component-name	xtpplib-xdoc
component-title	xdoc component
library-name	Xatapult XML Library
license	GNU GENERAL PUBLIC LICENSE - Version 3, 29 June 2007
owner-company-git-site-uri	https://github.com/xatapult
owner-company-name	Xatapult Content Engineering
owner-company-phone	+31 6 53260792
owner-company-website	http://www.xatapult.com

Table 2-2 - Parameters

You can also specify `type="comment"`. As the name implies, the parameters will be added as an XML comment so you'll have to dive into the produced DocBook to see them.

2.4 xdoc transforms

An xdoc transform is an XSLT stylesheet or XProc (1.0) pipeline that is triggered from your source document and inserts generated DocBook contents. There are several of these transforms built into the xtpplib-xdoc component but its also easy to write one of your own. Detailed information can be found [here](#).

As an example: xtpplib-xdoc contains transforms to extract documentation from XML documents and programs. Among others, the documentation sections for the pipelines and libraries are generated with this. Now assume you want to insert the documentation of the xdoc-to-docbook pipeline somewhere in a document of your own. You could do this by adding a reference to the **[TBD]** transform to your xdoc source:

```
<xdoc:transform href="$xdoc/code-docgen.xpl" filecomponents="2">
  <xi:include href="../../../xpl/xdoc-to-docbook.xpl"/>
</xdoc:transform>
```

The result will be:

XProc (1.0) pipeline: xdoc-to-docbook.xpl (xdoc:xdoc-to-docbook)

File: xpl/xdoc-to-docbook.xpl

Pipeline that transforms a DocBook source containing xdoc extensions into "pure" DocBook format.

Port	Type	Primary?	Description
source	in	yes	The DocBook source with xdoc extensions
result	out	yes	The resulting DocBook

Option	Rq?	Default	Description
href-parameters		()	Optional reference to a document with parameter settings. See here for details.
parameter-filters		()	Optional filter settings for processing the parameters. Format: name=value name=value

3 xdoc transforms

An xdoc transform is an XSLT stylesheet or XProc (1.0) pipeline that is triggered from your source document and inserts generated DocBook contents. There are several of these transforms built into the xtpxlib-xdoc component but its also easy to write one of your own.

3.1 Running an xdoc transform

The `<xdoc:transform>` extension element runs an xdoc transformation (either XProc (1.0) or XSLT (2.0 or 3.0)). It is completely replaced by the outcome of the transformation.

```
<xdoc:transform href = xs:anyURI
  (any)? >
  <!-- (Optional) XML to transform and/
  or an <xi:include> element to load this from an external source. -->
</xdoc:transform>
```

Attribute	#	Type	Description
href	1	xs:anyURI	Reference to the actual transformation. Relative names are resolved against the location of the source document. This file's extension determines whether an XProc 1.0 (extension: .xpl) or an XSLT (extension: .xsl) is done. A value that starts with \$xdoc is assumed to be an xtpxlib-xdoc built-in transformation (e.g. href="\$xdoc/code-docgen.xpl"). See also "Built-in xdoc transformations" on page 7.
(any)	?		Often transformations specify additional attributes on the <code><xdoc:transform></code> element to parametrize their functionality. Any additional attribute is allowed here.

3.2 Built-in xdoc transformations

The xtpxlib-xdoc has several transforms built in. You can easily reference these by prefixing their name with \$xdoc, for instance \$xdoc/code-docgen.xpl.

Module	Description
code-docgen-dir.xpl	Runs the \$xdoc/code-docgen.xpl transform over multiple files in a directory.
code-docgen.xpl	Takes an XML document (XSL, XSD, XProc, ordinary XML) and generates documentation out of it.
include-docbook.xpl	Takes an XML document and unwraps the root element from it. It then copies all the children to the output, with the exception of any db:info elements.
xml-description.xpl	Takes a document that <i>describes</i> an XML document, using special markup for this, and turns this into DocBook.

Table 3-2 - Module overview

3.2.1 XProc (1.0) pipeline: code-docgen-dir.xpl

File: transforms/code-docgen-dir.xpl

Runs the \$xdoc/code-docgen.xpl transform over multiple files in a directory.

Typical usage (within an xdoc source document):

```
<xdoc:transform href="$xdoc/code-docgen-dir.xpl"
  dir="..."
  depth="..."
  filter="..."
  toc-only="..." />
```

- @dir: Directory to process
- @depth: (integer, default -1) The depth in traversing the directory tree.
 - When le 0, @dir and all its subdirectories are processed.
 - When eq 1, only @dir is processed.
 - When gt 1, the sub-directories up to this depth are processed.

- `@filter`: optional regexp filter (e.g. get only XProc files with `filter=".xpl$"`)
- `@toc-only`: (boolean, default `false`) Whether to produce a ToC table only.

All (other) attributes are passed to `code-docgen.xpl`.

Port	Type	Primary?	Description
source	in	yes	The triggering <code>xdoc:transform</code> element.
result	out	yes	The resulting DocBook output.

3.2.2 XProc (1.0) pipeline: `code-docgen.xpl` (`xdoc:code-docgen`)

File: `transforms/code-docgen.xpl`

Takes an XML document (XSL, XSD, XProc, ordinary XML) and generates documentation out of it.

Typical usage (within an `xdoc` source document):

```
<xdoc:transform href="$xdoc/code-docgen.xpl"
  filecomponents="..."
  header-level="..."
  add-table-titles="..."
  sublevels="..."
  id="..." >
  <xi:include href="path/to/document/to/generate/documentation/for"/>
</xdoc:transform>
```

- `@filecomponents`: (integer, default 0) Determines the display of the filename:
 - When `lt 0`, no filename is displayed
 - When `eq 0`, the full filename (with full path) is displayed
 - When `gt 0`, this number of filename components is displayed. So 1 means filename only, 2 means filename and direct foldername, etc.
- `@header-level`: (integer, default 0) Determines what kind of DocBook section is created:
 - When `le 0`, no separate section is created, all titles will be output as bridgehead elements.
 - Otherwise a title with this level is created (e.g. `header-level="1"` means a `sect1` element).
- `@add-table-titles`: (boolean, default `false`) Whether to add titles to generated tables.
- `@sublevels`: (boolean, default `true`) If `true` only the main section will be a "real" section. All sublevels will become bridgeheads.
- `@id`: Optional identifier of this section. If absent the id will become the document's filename.

If the format to document has means to add documentation of itself (like XProc (`p:documentation`) or XML Schema (`xs:annotation`)), this is used. If there is no such thing (like for XSLT and straight XML), comments starting with a tilde (~) are used.

All descriptions and documentation sections can contain simple Markdown.

The following formats are supported

- XML documents: only the header comment is used.
- XSLT (2.0 and 3.0) stylesheets: document all *exported* parameters, variables, functions and named templates. Something is supposed to be for export if its *not* in the `no` or `local` namespace.
- XProc pipelines and libraries
- XML Schemas: Uses the global annotation and lists the global elements using their annotations.

Port	Type	Primary?	Description
source	in	yes	The document to generate documentation for, wrapped in an <code>xdoc:transform</code> element.
result	out	yes	The resulting DocBook output.

3.2.3 XProc (1.0) pipeline: `include-docbook.xpl`

File: `transforms/include-docbook.xpl`

Takes an XML document and unwraps the root element from it. It then copies all the children to the output, with the exception of any `db:info` elements.

It is the responsibility of the author to make sure that everything that results is in the DocBook (<http://docbook.org/ns/docbook>) namespace!

Typical usage (within an `xdoc` source document):

```
<xdoc:transform href="$xdoc/include-docbook.xpl">
  <xi:include href="path/to/xml/to/include.xml"/>
</xdoc:transform>
```

Port	Type	Primary?	Description
source	in	yes	The document containing the parts to include, wrapped in an <code>xdoc:transform</code> element.
result	out	yes	The resulting DocBook output.

3.2.4 XProc (1.0) pipeline: xml-description.xpl

File: transforms/xml-description.xpl

Takes a document that *describes* an XML document, using special markup for this, and turns this into DocBook.

A schema for this markup format can be found in `xsd/element-description.xml`.

Typical usage (within an `xdoc` source document):

```
<xdoc:transform href="$xdoc/xml-description.xpl">
  <xi:include href="path/to/xml/description.xml"/>
</xdoc:transform>
```

Port	Type	Primary?	Description
source	in	yes	The document containing the XML description, wrapped in an <code>xdoc:transform</code> element.
result	out	yes	The resulting DocBook output.

3.3 Writing your own xdoc transformations

- To add an `xdoc` transform of your own you need to write an XSLT stylesheet or an XProc pipeline.
- Such a stylesheet or transformation gets the **full** `<xdoc:transform>` element as its input. It can inspect the `<xdoc:transform>` root element itself for its attributes.
- The output of the stylesheet/pipeline must be the resulting (valid!) DocBook.
- If the resulting DocBook contains multiple elements you can wrap them all in an `<xdoc:GROUP>` element to make the result a single well-formed document. The `<xdoc:GROUP>` wrapper is removed later on by the `xdoc` processing.
- You must reference your stylesheet or pipeline using `<xdoc:transform>`'s `href` attribute.

Here is a simple example of something that is actually quite useful. Tables in DocBook are complex things. When you to have format the same kind of data over and over again in a table, it becomes very boring and hard to keep consistent and maintainable. Using `xdoc` transforms you can automate the data to DocBook part.

Assume we have, all over the document, weather data, that comes in this source format:

```
<weather-data>
  <data city="Amsterdam" temp="20"/>
  <data city="Stavanger" temp="-5"/>
</weather-data>
```

You want to show this as tables. The following XSLT stylesheet (called `transform-weather-data.xsl`) will do the xdoc transform trick. As its input it gets the weather data wrapped in the `<xdoc:transform>` element (see below).

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="3.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:xdoc="http://www.xtpxlib.nl/ns/xdoc"
  xmlns="http://docbook.org/ns/docbook">

  <xsl:template match="/">
    <table>
      <title>Example weather data</title>
      <tgroup cols="2">
        <colspec colwidth="4cm"/>
        <colspec/>
        <thead>
          <row>
            <entry>
              <para>City</para>
            </entry>
            <entry>
              <para>Temperature (C)</para>
            </entry>
          </row>
        </thead>
        <tbody>
          <xsl:for-each select="/xdoc:transform/weather-data/data">
            <row>
              <entry>
                <para>
                  <xsl:value-of select="@city"/>
                </para>
              </entry>
              <entry>
                <para><xsl:value-of select="@temp"/></para>
              </entry>
            </row>
          </xsl:for-each>
        </tbody>
      </tgroup>
    </table>
  </xsl:template>

</xsl:stylesheet>
```

In your document you add:

```
<xdoc:transform href="path/to/transform-weather-data.xsl">
  <xi:include href="path/to/your/weather/data.xml"/>
</xdoc:transform>
```

And the result for this example is:

City	Temperature (C)
Amsterdam	20
Stavanger	-5

Table 3-7 - Example weather data

4 XProc Pipelines

The xtpxlib-xdoc component contains the following XProc (1.0) pipelines:

Module	Description
docbook-to-pdf.xpl	This turns Docbook (5.1) into a PDF using FOP.
docbook-to-xhtml.xpl	This turns Docbook (5.1) into XHTML.
xdoc-to-docbook.xpl	Pipeline that transforms a DocBook source containing xdoc extensions into "pure" DocBook format.
xdoc-to-pdf.xpl	Convenience pipeline: Combines the xdoc-to-docbook and the docbook-to-pdf steps in one.
xdoc-to-xhtml.xpl	Convenience pipeline: Combines the xdoc-to-docbook and the docbook-to-xhtml steps in one.

Table 4-1 - Module overview

4.1 XProc (1.0) pipeline: docbook-to-pdf.xpl (xdoc:docbook-to-pdf)

File: xpl/docbook-to-pdf.xpl

This turns Docbook (5.1) into a PDF using FOP.

All necessary xdoc pre-processing (usually with xdoc-to-docbook.xpl) must have been done.

It will only convert a partial DocBook tagset.

If you don't use xdoc-to-docbook.xpl, you have to make sure to get correct `xml:base` attributes in, so the pipeline can find includes and images. The following XProc (1.0) code takes care of that:

```
<p:xinclude>
  <p:with-option name="fixup-xml-base" select="true()"/>
</p:xinclude>
<p:add-attribute attribute-name="xml:base" match="/*">
  <p:with-option name="attribute-value" select="/reference/to/source/document.xml"/>
</p:add-attribute>
```

Port	Type	Primary?	Description
source	in	yes	The docbook source document, fully expanded (with appropriate <code>xml:base</code> attributes)
result	out	yes	The resulting XSL-FO (that was transformed into the PDF).

Option	Rq?	Default	Description
chapter-id		' '	Specific chapter identifier to output.
fop-config		<code>resolve-uri('../..//xtpxlib-common/data/fop-default-config.xml', static-base-uri())</code>	Reference to the FOP configuration file
global-resources-directory		()	Images that are tagged as <code>role="global"</code> are searched here (discarding any directory information in the image's URI)
href-pdf	yes		The name of the resulting PDF file (must have <code>file://</code> in front).
main-font-size		10	Main font size as an integer. Usual values somewhere between 8 and 10.
output-type		'a4'	Output type. Use either <code>a4</code> or <code>sb</code> (= standard book size)
preliminary-version		<code>false()</code>	If true, adds a preliminary version marker and output any <code>db:remark</code> elements. If false, output of <code>db:remark</code> elements will be suppressed.

4.2 XProc (1.0) pipeline: docbook-to-xhtml.xpl (xdoc:docbook-to-xhtml)

File: xpl/docbook-to-xhtml.xpl

This turns Docbook (5.1) into XHTML.

All necessary `xdoc` pre-processing (usually with `xdoc-to-docbook.xpl`) must have been done.

It will only convert a partial DocBook tagset.

The resulting XHTML will not be directly useable, post-processing the result into a complete and correct HTML page is necessary. The result of this pipeline consists of nested `div` elements. There is no surrounding `html` or `body` element.

Port	Type	Primary?	Description
source	in	yes	The docbook source document.
result	out	yes	The resulting XHTML

4.3 XProc (1.0) pipeline: `xdoc-to-docbook.xpl` (`xdoc:xdoc-to-docbook`)

File: `xpl/xdoc-to-docbook.xpl`

Pipeline that transforms a DocBook source containing `xdoc` extensions into "pure" DocBook format.

Port	Type	Primary?	Description
source	in	yes	The DocBook source with <code>xdoc</code> extensions
result	out	yes	The resulting DocBook

Option	Rq?	Default	Description
<code>href-parameters</code>		<code>()</code>	Optional reference to a document with parameter settings. See here for details.
<code>parameter-filters</code>		<code>()</code>	Optional filter settings for processing the parameters. Format: <code>name=value name=value ...</code>

4.4 XProc (1.0) pipeline: `xdoc-to-pdf.xpl` (`xdoc:xdoc-to-pdf`)

File: `xpl/xdoc-to-pdf.xpl`

Convenience pipeline: Combines the `xdoc-to-docbook` and the `docbook-to-pdf` steps in one.

Port	Type	Primary?	Description
source	in	yes	The DocBook source with <code>xdoc</code> extensions
result	out	yes	Some XML report about the conversion

Option	Rq?	Default	Description
<code>chapter-id</code>		<code>' '</code>	Specific chapter identifier to output.
<code>fop-config</code>		<code>resolve-uri('../..//xtpxlib-common/data/fop-default-config.xml', static-base-uri())</code>	Reference to the FOP configuration file
<code>global-resources-directory</code>		<code>()</code>	Images that are tagged as <code>role="global"</code> are searched here (discarding any directory information in the image's URI)
<code>href-parameters</code>		<code>()</code>	Optional reference to a document with parameter settings. See here for details.
<code>href-pdf</code>	yes		The name of the resulting PDF file
<code>main-font-size</code>		<code>10</code>	Main font size as an integer. Usual values somewhere between 8 and 10.
<code>output-type</code>		<code>'a4'</code>	Output type. Use either <code>a4</code> or <code>sb</code> (= standard book size)
<code>parameter-filters</code>		<code>()</code>	Optional filter settings for processing the parameters. Format: <code>name=value name=value ...</code>
<code>preliminary-version</code>		<code>false()</code>	If <code>true</code> , adds a preliminary version marker and output any <code>db:remark</code> elements. If <code>false</code> , output of <code>db:remark</code> elements will be suppressed.

4.5 XProc (1.0) pipeline: xdoc-to-xhtml.xpl (xdoc:xdoc-to-xhtml)

File: `xpl/xdoc-to-xhtml.xpl`

Convenience pipeline: Combines the `xdoc-to-docbook` and the `docbook-to-xhtml` steps in one.

Port	Type	Primary?	Description
source	in	yes	The DocBook source with <code>xdoc</code> extensions
result	out	yes	The resulting XHTML

Option	Rq?	Default	Description
<code>href-parameters</code>		<code>()</code>	Optional reference to a document with parameter settings. See here for details.
<code>parameter-filters</code>		<code>()</code>	Optional filter settings for processing the parameters. Format: <code>name=value name=value</code>

5 XProc Libraries

The xtpxlib-xdoc component contains the following XProc (1.0) library module:

Module	Description
xtpxlib-xdoc.mod.xpl	TBD Generic library

Table 5-1 - Module overview

5.1 XProc (1.0) library: xtpxlib-xdoc.mod.xpl

File: xplmod/xtpxlib-xdoc.mod/xtpxlib-xdoc.mod.xpl

TBD Generic library

Prefix	Namespace URI
xdoc	http://www.xtpxlib.nl/ns/xdoc

5.1.1 Step: xdoc:markdown-to-docbook

Checks for elements xdoc:MARKDOWN. Replaces these with Docbook contents.

Only simple Markdown is supported (e.g. no tables).

Port	Type	Primary?	Description
source	in	yes	
result	out	yes	

6 DocBook dialect

The xtpxlib-xdoc component uses [DocBook 5.1](#) as its source and target vocabulary. However, *for generating output* it does not implement the full standard (which is huge!) but only those elements/attributes that were deemed necessary. This document will explain what is in and what's not.

6.1 Supported root elements

Both the <book> and the <article> root element are supported. **[TBD rephrase]** A <book> root results in paged output (for, as the name implies, a book. The <article> root results in something more memo style (like this).

6.2 Document information

Document information: The only document information elements recognized are (any others are ignored):

```
<info>

  <title> ... main title ... </title>
  <subtitle> ... subtitle ...</subtitle>
  <pubdate> ... publication date ... </pubdate>
  <author>
    <personname> ... author name ...</personname>
  </author>

  <orgname> ... organization ... </orgname>

  <mediaobject role="top-logo">
    <!-- Use either role="top-logo" or no role attribute. -->
    <imageobject>
      <imagedata fileref="..." width="...(opt)" height="...(opt)"/>
    </imageobject>
  </mediaobject>

  <mediaobject role="center-page">
    <imageobject>
      <imagedata fileref="..." width="...(opt)" height="...(opt)"/>
    </imageobject>
  </mediaobject>

</info>
```

All elements are optional.

6.3 Chapter/Section structure

- For books, <preface>, <chapter>, <appendix> and <sect1> to <sect3> are recognized and handled.
- In articles only <sect1> to <sect3> are allowed.

6.4 Block constructions

the following block level constructions are recognized and handled:

- **Paragraphs:** Normal <para> elements recognize the following role attribute values (multiple, whitespace separated, values allowed):

@role value	Description
break, smallbreak	Inserts an empty line, either full or small height. The contents of the <para> element is ignored.
break-before break-after	Adds extra whitespace before or after the paragraph
header keep-with-next	Keeps this paragraph with the next one together on a page.

@role value	Description
keep-with-previous	Keeps this paragraph with the previous one together on a page.

Table 6-1

- **Lists:** Both `<itemizedlist>` and `<orderedlist>` are allowed.
- **Tables:** Both `<table>` and `<informaltable>` are allowed. An example of a formal table above. An informal table below.

Example	of
an	informal table

Add `role="nonumber"` to a table to stop it from getting a number:

Blurp	Blorb
Example	of
an	unnumbered table

Unnumbered table

Tables are notoriously difficult in that FOP cannot compute column widths automatically. To amand this (a little bit) add `colspec/@colwidth` information. There is also a mechanism for columns with code (set in a fixed-width font), see "Fixed-width column mechanism" on page 19.

- **Program listings:** For program listings use the `<programlisting>` element
The easiest way to handle this turned out to put longer program listings in external files and use an `<xi:include parse="text">` construction:

```
<programlisting><xi:include href="ref" parse="text" /></programlisting>
```

 Or use a `<![CDATA[` construction around the piece of code.
- **Figures:** Both `<figure>` and `<informalfigure>` are allowed. Width and height can be set on the image data.

Figure 6-1 - An example of a figure... (this in fixed width)

Add `role="nonumber"` to a figure to stop it from getting a number.

- **Bridgeheads:** The `<bridgehead>` element inserts a bridgehead paragraph (bold, underlined and with an empty line before):

This is a bridgehead...

- **Simple lists:** The `<simplelist>` element inserts a simple list:

An entry
Another entry...

- **Variable lists:** The `<variablelist>` element inserts a variable list list (also very useful for explaining terms, definitions, etc.):

The first entry

The explanation of the first entry!

The second entry

The explanation of the second entry!

- **Notes and warnings:** The `<note>` element inserts a note and `<warning>` a warning:

NOTE:

This is a note! Nulla ac ex urna. Ut auctor odio quis nulla porta bibendum. Proin hendrerit molestie velit sit amet tristique. Vivamus laoreet ligula leo, vitae placerat ipsum porta sed. Morbi blandit ex mauris, eu volutpat tortor mattis eu. Nam et molestie mi. Aliquam erat volutpat. Aenean a imperdiet lectus. Phasellus condimentum dignissim laoreet.

WARNING:

This is a warning! Nulla ac ex urna. Ut auctor odio quis nulla porta bibendum. Proin hendrerit molestie velit sit amet tristique. Vivamus laoreet ligula leo, vitae placerat ipsum porta sed. Morbi blandit ex mauris, eu volutpat tortor mattis eu. Nam et molestie mi. Aliquam erat volutpat. Aenean a imperdiet lectus. Phasellus condimentum dignissim laoreet.

If you add a `<title>` element, the standard title (NOTE/WARNING) will be replaced by its contents.

- **Sidebars:** The `<sidebar>` element inserts sidebar section:

Title of the sidebar

Contents of the sidebar. Nulla ac ex urna. Ut auctor odio quis nulla porta bibendum. Proin hendrerit molestie velit sit amet tristique. Vivamus laoreet ligula leo, vitae placerat ipsum porta sed. Morbi blandit ex mauris, eu volutpat tortor mattis eu. Nam et molestie mi. Aliquam erat volutpat. Aenean a imperdiet lectus. Phasellus condimentum dignissim laoreet.

- **Examples:** The `<example>` element inserts an example:

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Vivamus elementum diam nec nunc elementum, eget dapibus dui malesuada. Aenean facilisis consequat odio, vitae euismod eros tempor nec. Vestibulum cursus tortor tortor, semper euismod sapien sagittis et.

Example 6-1 - Example of an example

Add `role="nonumber"` to an example to stop it from getting a number.

6.5 Inline elements

the following inline elements are recognized and handled:

- **`<emphasis>`:** Sets *emphasis*.
Use `role="bold"` or `role="underline"` to set a specific type of emphasis.
- **`<literal>` or `<code>`:** Creates a piece of literal, mono-spaced text.
- **`<link>`:** Outputs some link (e.g. a web address). This is either the contents of the element or, if not available, the contents of the `xlink:href` attribute.
Like [this](#) or like this <http://www.xatapult.nl>.
- **`<inlinemediaobject>`:** Inserts an inline image , like this.
- **`<citation>`:** Inserts a citation between square brackets like this: [CITATION].
- **`<command>`:** Use to indicate an executable program or a user provided command, like this: *git checkout origin*

- **<email>**: Use to indicate an email address, like this: *info@xatapult.com*
- **<filename>**: Use to indicate a filename, like this: *blabla.xml*
- **<replaceable>**: Use to indicate text to be replaced with user or context supplied values, like this:
add your own stuff here
- **<keycap>**: Use to indicate a keyboard physical key, like this: Return
- **<superscript>**, **<subscript>**: For super- and subscripts, like this: XX^{super} YY_{sub}
- **<userinput>**: Use to indicate data entered by the user, like this: **data entered here**
- **<tag>**: Indicates an object from the XML vocabulary. The `class` attribute signifies what:

@class value	Result example(s)
attribute	@attribute @class
attvalue	"attribute value" "some value for an attribute"
emptytag	<element/> <docbook/>
endtag	</element> </docbook>
pi	<?processing-instruction x="y"?>
comment	<!-- Some comment line... -->
Anything else defaults to element	<element> <docbook>

Table 6-3

- **<xref>**: Inserts a cross-reference to the id referenced by @linkend
 - Use `role="page-number-only"` to get just a page number.
 - Use `role="simple"` to always get: page #
 - Use `role="text"` to only get the (unquoted) text only in cases where a "..." on page ... would normally appear.
 - Use `role="capitalize"` to force the reference string (for chapters/appendices/pages/figures/tables/...) to start with an upper-case character (so you can be sure a sentence that starts with an `<xref>` always starts with a capital).

Otherwise it depends on what is pointed to:

Target	Result/Examples
To anything that holds an <code>xreflabel</code> attribute	"paragraph with xreflabel attribute" on page 15
To a chapter or appendix	chapter # or appendix #
To a section	"Document information" on page 15
To a table (with a number), like this one	table 6-4
To a figure (with a number)	figure 6-1
To an example (with a number)	example 6-1
To anything else	First paragraph: page 15 Unnumbered table: page 16

Table 6-4 - Examples of `<xref>` usage

6.6 Other constructs

- **To-be-done marker:** Start a to-be-done marker with `[TBD` and end it with `]`. For instance: `[TBD this needs to be done...]`

6.7 Fixed-width column mechanism

FOP (in the current version, 3Q19) cannot compute the column-widths automatically. It divides the space and you can set a fixed column-width (with `colspec/@colwidth`). For the case that a column contains code stuff (text in a fixed-width font) *and* you want the column-width to be dependent on the text in such a column, there is a (unfortunately a bit complicated) mechanism for this.

The fixed-width column mechanism consists of two parts:

Dynamically compute the column width

This part is optional.

Add a `role` attribute to the `<colspec>` element with, as one of the roles, `code-width-cm:min-max`, where `min` and `max` are (positive) doubles. For instance `<colspec role="code-width-cm:1.2-4">`. `min` and `max` are the minimum and maximum column-widths, expressed in cm.

The PDF conversion will now look in all the contents of this particular column for entries `<code role="code-width-limited">`. Based on the length of these entries it computes an optimal column-width, but always between `min` and `max`.

Output code width-limited

If a table entry contains contents in a `<code role="code-width-limited">` element, it tries to make it fit within the available column-width. If necessary the line is split to prevent overflowing of table cell contents.

This is (currently) not completely fool-proof: if the contents contains whitespace or hyphens, it is assumed to line-break correctly by itself. That, of course, does not guarantee correct results. So it may need a little experimenting before things look right.

A column that contains `<code role="code-width-limited">` contents *must* have a column width set *in cm* (either directly with `<colspec colwidth="...cm">` or by the dynamic mechanism described above).