

Introduction

Baroid Core Homework 17

Assessment Feedback

Congratulations, you passed.

Total score: 28 out of 29, 97%

Question Feedback

Question

1 of 17

What are the most common contaminants that may cause negative impact in the IEF systems?

- ☐ Cement
- ☐ Anhydrite
- ☒ Drill solids
- ☒ Water flows
- ☐ Carbonates

2 out of 2

Question

2 of 17

Drilled solids are basically inert in NAF systems and they are tolerated to a certain limit

- ☒ True
- ☐ False

1 out of 1

Question

3 of 17

What is the different between a contamination with fresh water and salt water on IEF system?

- ☐ During a contamination with fresh water, the water phase salinity will drop less than with salt water

- ☒ During a contamination with fresh water, the water phase salinity will drop more than with salt water
- ☐ During a contamination with fresh water, the water phase salinity will stay the same and with salt water it will increase
- ☐ None of the above

1 out of 1

Question

4 of 17

What are the recommended treatments If we have contamination with drilled solids on IEF systems?

- ☐ Increase the WPS
- ☐ Dilute with fresh water
- ☒ Dilute with NAP
- ☒ Optimize solid control equipment
- ☐ Add alkalinity source (lime)

2 out of 2

Question

5 of 17

How can we identify a contamination with acid gases on a IEF systems?

- ☒ Increase of filtrate loss
- ☐ Increase in alkalinity
- ☐ Increase of density
- ☒ Drop in density
- ☒ Drop in alkalinity
- ☐ Drop on filtrate loss

3 out of 3

Question

6 of 17

Saturation with salt of a IEF system can cause:

- ☐ Increase of the electrical stability
- ☐ Increase of density
- ☒ Drop of density
- ☐ Water wetting of solids
- ☒ Breakup of the emulsion

1 out of 2

Question

7 of 17

Monovalent cation based materials like caustic soda, potassium hydroxide, soda ash or soda bicarbonate should never be added to an NAF system, because it could break the invert emulsion

- ☒ True
- ☐ False

1 out of 1

Question

8 of 17

In the case of a contamination event, lime can be used for:

- ☐ Lower the WPS
- ☒ Combat acid gases
- ☐ Increase the rheology
- ☐ Lower the filtration control

1 out of 1

Question

9 of 17

In the IEF systems, materials like anhydrite, cement, sodium chloride and potassium chloride should act like any other low gravity solid if the fluid specifications are properly designed

- ☒ True
- ☐ False

1 out of 1

Question

10 of 17

If there's a contamination while drilling a salt layer, what would be the main chemical that could help to treat the system?

- ☒ Fresh water
- ☐ Saturated brine
- ☐ Barite

☐ Alkalinity source

1 out of 1

Question

11 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a) The contaminant is

Drilled Solids ▼

b) The primary treatment is

Mechanical Separation/Dilution ▼

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	12.1
Fun. Vis	65	72
PV	32	42
YP	18	19
Gels	7/11	14 / 26
HTHP	4.0	5.4
Oil	54	53
Water	18	17
Solids	28	30
Alk	2.10	2.0
Cl	31500	31500
Ca	22000	22000
WPS	215000	215000
ES	585	474

2 out of 2

Question

12 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a) The contaminant is

Acid Gas (CO2) ▼

b) The primary treatment is

Lime ▼

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	11.8
Vis	65	66
PV	32	34
YP	18	19
Gels	7/11	7/11
HTHP	4.0	7.5
Oil	54	54
Water	18	18
Solids	28	28
Alk	3.10	0.00
Cl	31500	31500
Ca	22000	21000
WPS	21500	21500
ES	485	319

2 out of 2

Question

13 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a)The contaminant is

Hydrocarbons

b) The primary treatment is

Dilution with brine

	Day 1	Day 2
Fl Temp	120	128
Weight	12.2	12.1
Vis	65	62
PV	32	30
YP	18	17
Gels	7/11	6/10
HTHP	4.0	6.5
Oil	54	56
Water	18	17
Solids	28	27
Alk	2.10	4.8
Cl	31500	31500
Ca	22000	22000
WPS	215000	215000
ES	485	502

2 out of 2

Question

14 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a)The contaminant is

Fresh water ▼

b) The primary treatment is

Dilution with base fluid ▼

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	11.6
Vis	65	97
PV	32	53
YP	18	29
Gels	7/11	9/19
HTHP	4.0	6.5
Oil	54	47
Water	18	28
Solids	28	25
Alk	2.10	1.8
Cl	31500	13000
Ca	22000	9000
WPS	215000	101500
ES	485	136

2 out of 2

Question

15 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a)The contaminant is

Salt (formation) ▼

b) The primary treatment is

Dilution with fresh water ▼

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	12.1
Vis	65	66
PV	32	34
YP	18	19
Gels	7/11	7/11
HTHP	4.0	6.5
Oil	54	53.5
Water	18	17.5
Solids	28	29
Alk	2.10	2.1
Cl	31500	42000
Ca	22000	22000
WPS	215000	252800
ES	585	416

2 out of 2

Question

16 of 17
Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a)The contaminant is

Cement 

b) The primary treatment is

Mechanical Separation/Dilution 

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	12.1
Vis	65	66
PV	32	34
YP	18	19
Gels	7/11	7/11
HTHP	4.0	6.5
Oil	54	53.5
Water	18	17.5
Solids	28	29
Alk	2.10	4.8
Cl	31500	31500
Ca	22000	24000
WPS	215000	215000
ES	485	506

2 out of 2

Question

17 of 17

Using the information from the fluid check below, identify the contamination and the primary treatment for fixing the issue:

a) The contaminant is

Salt Water ▼

b) The primary treatment is

Dilution with base fluid ▼

	Day 1	Day 2
Fl Temp	120	128
Weight	12.0	11.6
Vis	65	97
PV	32	53
YP	18	29
Gels	7/11	9/19
HTHP	4.0	6.5
Oil	54	47
Water	18	28
Solids	28	25
Alk	2.1	1.8
Cl	31500	23000
Ca	22000	12000
WPS	215000	167200
ES	485	136

2 out of 2