

Introduction

Baroid Core Homework 13

Assessment Feedback

Congratulations, you passed.

Total score: 37 out of 37, 100%

Question Feedback

Question

1 of 26

Select the advantages of Non-aqueous fluids over water based fluids:

- ☐ Better hole instability
- ☒ Better tolerance to contaminants
- ☐ Environmentally friendly
- ☒ Excellent lubricity
- ☒ Better hole gauge
- ☒ Superior temperature stability
- ☐ Promotes corrosion

3 out of 3

Question

2 of 26

What is the major difference between High Performance NAF's and Conventional NAF's?

- ☐ Extreme temperature stability
- ☐ No diesel in the base fluid
- ☒ No commercial clays or lignites added to the system
- ☐ Less water content in the fluid

1 out of 1

Question

3 of 26

The most common types of base fluids of Non Aqueous fluids are:

- ☒ Diesel Oil
- ☐ Filtered brines
- ☒ Non Petroleum oil
- ☒ Mineral Oil

3 out of 3

Question

4 of 26

Which of the following contributes to the discontinuous phase of an NAF (select all applicable answers)?

- ☒ Organophilic lignites
- ☒ Drilled solids
- ☐ Oil
- ☒ Water
- ☒ Commercial clays

4 out of 4

Question

5 of 26

Isomerized Olefin base fluids outperform oil, ester, and ester blend base fluids in extreme temperatures.

- ☒ True
- ☐ False

1 out of 1

Question

6 of 26

The Baroid Family of Non Aqueous Fluids consist of conventional NAF and high performance IEF .

2 out of 2

Question

7 of 26

Emulsifiers are used in NAF's for which of the following purposes?

- ☐ Limiting sand content
- ☒ Creating and maintaining a water in oil emulsion

☐ Lowering your ASG

1 out of 1

Question

8 of 26

A product is considered organophillic when it has been treated with amines to make them oil-dispersible.

- ☒ True
☐ False

1 out of 1

Question

9 of 26

The whole fluid chloride and whole fluid calcium content are maintained to directly affect which NAF property?

- ☒ Water phase salinity
☐ Oil to water ratio
☐ Solids content

1 out of 1

Question

10 of 26

If the content by volume of water increases, the viscosity of the fluid decreases causing the fluid to be thinner.

- ☐ True
☒ False

1 out of 1

Question

11 of 26

Emulsifiers target the interfacial tension between

- ☒ Two immiscible fluids
☐ Solids and other solids
☐ The wellbore and the drilling fluid
☐ Solids and fluids

1 out of 1

Question

12 of 26

The “salt” in an NAF is contained in which of the following?

- ☐ The continuous phase
- ☐ The oil phase
- ☐ The solids phase
- ☒ The water phase

1 out of 1

Question

13 of 26

Wetting Agents target the interfacial tension between solids and liquid .

2 out of 2

Question

14 of 26

According to the API guidelines, rheological test on an NAF are performed at which temperatures? (select all applicable answers)

- ☐ Room temperature
- ☐ 49 F
- ☐ Bottom hole temperature
- ☒ 120 F
- ☒ 150 F
- ☐ 66 F

2 out of 2

Question

15 of 26

Invert Emulsion means:

- ☒ Water emulsified into a non-aqueous based fluid
- ☐ Oil emulsified in water
- ☐ Solids emulsified in water

1 out of 1

Question

16 of 26

Organophilic clays and lignites are not used in clay-free fluids because they can negatively impact drilling performance and reservoir producibility.

- ☒ True
☐ False

1 out of 1

Question

17 of 26

When working with Non-Aqueous fluids, one of the main concerns is the environmental impact of the systems. Environmental responsibility and sustainability is becoming a critical factor in drilling practices.

- ☒ True
☐ False

1 out of 1

Question

18 of 26

When dealing with NAF and environmental challenges, there are several aspects to consider:

- ☐ Fluid performance, regulations, cost management and risk mitigation
☐ Fluid performance, regulations, cost management and waste volume
☒ Fluid performance, regulations, waste management and risk mitigation

1 out of 1

Question

19 of 26

Drilling Waste Management ▼ is a strategy of maximizing drilling efficiency while minimizing environmental liability for the customer.

1 out of 1

Question

20 of 26

Given the following results from a retort analysis, calculate the NAP/Water ratio:

Retort Oil = 6.4ml Retort Water = 1.6ml

NAP ratio 80 Water ratio 20

2 out of 2

Question

21 of 26

The content of Low gravity solids is not a concern in non aqueous fluids.

- ☐ True
- ☒ False

1 out of 1

Question

22 of 26

One of the best advantages of the BaraPure® system is that it has a lower environmental impact than other NAF because it does not contain added salts.

- ☒ True
- ☐ False

1 out of 1

Question

23 of 26

All High performance fluids are stable up to 450°F.

- ☐ True
- ☒ False

1 out of 1

Question

24 of 26

The Non-Aqueous fluid system that contains an enhanced suspension package and has superior rheological properties is called:

- ☐ BaraPure®
- ☒ BaraECD®
- ☐ ENCORE®

☐ BaraNext

1 out of 1

Question

25 of 26

In non-aqueous systems a low alkalinity is desired, to avoid corrosion.

- ☐ True
☒ False

1 out of 1

Question

26 of 26

Non-Aqueous fluids are usually built in the rigsite without mayor logistical concerns.

- ☐ True
☒ False

1 out of 1