

Contents

1 Snippets	2		
1.1 Foreach	2		
1.2 Show	2		
1.3 toBin	2		
1.4 FreOpen	2		
1.5 Time	2		
1.6 Size	3		
1.7 IsOdd	3		
1.8 Assert	3		
1.9 StructPriorityQueue	3		
1.10 utilities Directives1	3		
1.11 utilities Namespace1	3		
1.12 utilities ClassPointers	3		
1.13 utilities Debug	4		
1.14 utilities Directives2	4		
1.15 utilities PointersDeclaration	4		
1.16 utilities PredefinedMacros	4		
1.17 utilities Template	4		
1.18 utilities Namespace2	5		
1.19 utilities CommaOperator	5		
1.20 utilities ArrayPointers	5		
1.21 template	5		
1.22 For	6		
1.23 Swap	6		
1.24 StringStream	6		
1.25 UpperLowerBound	6		
1.26 CompareDoubles	6		
2 BasicOperations	6		
2.1 Exponentiation	6		
2.2 SumArray	7		
3 Structures	7		
3.1 DisjointSets	7		
3.2 RecoveryTree	7		
3.3 Prim	7		
3.4 SegmentTree	8		
3.5 FenwickTree	8		
3.6 MaxMinPHeap	9		
3.7 BinaryTree	9		
3.8 Trie	9		
		3.9 Kruskals	9
		3.10 MaxFlow	10
	4	NP_{problem}	11
		4.1 Knapsack	11
	5	Combinatory	11
		5.1 BinomialCPP	11
		5.2 BinomialPYTHON	11
	6	Primes	11
		6.1 PollarRhoCPP	11
		6.2 PollarRhoPYTHON	12
		6.3 MillerTest	12
		6.4 IsPrime	12
		6.5 Sieve	12
		6.6 PrimalyTest	13
		6.7 Factorize	13
	7	Search	13
		7.1 BinarySearch	13
	8	Sorting	14
		8.1 SelectionSort SelectionSortPYTHON	14
		8.2 SelectionSort SelectionSortCPP	14
		8.3 InsertionSort InsertionSortPYTHON	14
		8.4 InsertionSort InsertionSortCPP	14
		8.5 BubbleSort Bubble	15
		8.6 MergeSort MergeSortCPP	15
		8.7 MergeSort MergeSortPY	15
		8.8 StandardSort	16
	9	Strings	16
		9.1 Palindrome	16
		9.2 FunctionsOverChart	16
		9.3 Split	16
		9.4 Regex	16
		9.5 KMP	17
		9.6 LCI	17
		9.7 LCS	17

10 Math	17
10.1 Matrix GaussianElimination	17
10.2 Polynomial HornersRule	19
10.3 NumberTheory GCD _{LCM}	19
10.4 NumberTheory DivisorsCPP	19
10.5 NumberTheory DivisorsPYTHON	19
10.6 NumberTheory Josephus	19
10.7 Pow FastPow	20
10.8 NumberSystems ChangeBases	20
10.9 NumberSystems ChangeBases	20
11 Sequences	20
11.1 MatrixFibo	20
12 probability	21
12.1 ComposedProbability	21
13 Geometry	21
13.1 RayCasting	21
13.2 LineIntersect2	22
13.3 PickTheorem	22
13.4 EulerFormule	22
13.5 Line2Point	22
13.6 PolygonArea	23
13.7 ConvexHull	23
13.8 CircleCenter	24
14 Arrays	24
14.1 PermutationPYTHON	24
14.2 Operations	24
14.3 MapFunctions	24
14.4 Kadane	24
14.5 Combination	25
14.6 PermutationCPP	25
15 Graphs	25
15.1 Traverse BFS	25
15.2 Traverse DFS	25
15.3 BestPath DijkstraHeap	26
15.4 BestPath Dijkstra	26
15.5 BestPath BellmanFord	27
15.6 BestPath FloydWarshal	27

1 Snippets

1.1 Foreach

```
#include <iterator>
#define foreach (x,v) for (typeof(v).begin() x=(v).begin(); x!=(v).end(); ++x)
using namespace std;
int main(){
    return 0;
}
```

1.2 Show

```
#include <iostream>
#define show(x) cout << #x << " = " << x << endl;
using namespace std;
int main(){
    int e =32;
    show(e);
}
```

1.3 toBin

```
#include <bits/stdc++.h>
using namespace std;
void toBin(int x){
    for (int i =31; i>=0; --i){
        cout << ((x&(1LL<<i))!=0);
    }
}
int main (){
    toBin(10);
    return 0;
}
```

1.4 FreOpen

```
#include <iostream>
#include <stdio.h>
using namespace std;
int main (){
    freopen("data.in", "r", stdin);
    freopen("data.out", "w", stdout);
    return 0;
}
```

1.5 Time

```
#include <chrono>
#include <iostream>
using namespace std;
int main(){
    auto start = chrono::high_resolution_clock::now();
    for(long long i = 0; i < 10000000; i++)

    auto end = chrono::high_resolution_clock::now();
    chrono::duration<double> diff = end-start;
    cout << diff.count() << endl ;
    return 0;
}
```

1.6 Size

```
#include <vector>
#include <string>
#include <iostream>
#define sz(a) ((int)(a).size())
using namespace std;
int main(){
    string t = "Hello, what's up";
    vector<int> c (10);
    cout << sz(t) << endl;
    cout << sz(c) << endl;
}
```

1.7 IsOdd

```
#include <iostream>
#define isOdd(x) (x & 0x01)
using namespace std;
int main (){
    int a =57, b= 32;
    cout << isOdd(a) << endl;
    cout << isOdd(b) << endl;
    return 0;
}
```

1.8 Assert

```
#include <iostream>
#include <assert.h>
#define isOdd(x) (x & 0x01)
using namespace std;

void test(int num){
    assert(isOdd(num) == 0);
    cout << "Hello: " << num << endl;
}

int main(){
    int a=10, b=21;
    test(a);
    test(b);
}
```

1.9 StructPriorityQueue

```
#include <iostream>
#include <queue>
using namespace std;
typedef priority_queue<edge> pq;
struct edge{
    int to, weight;
    edge(){}
    edge(int _to, int _weight){
        to = _to;
        weight = _weight;
    }
    bool operator < (edge e) const {
        return weight > e.weight;
    }
}
```

```
};
int main(){
    pq edges;
    edges.push(edge(1, 23));
    edges.push(edge(2, 3));
    edges.push(edge(3, 10));
    edges.push(edge(4, 11));
    edges.push(edge(5, 4));
    while(!edges.empty()){
        edge a = edges.top();
        edges.pop();
        cout << a.to << endl;
    }
}
```

1.10 utilities Directives1

```
#include <iostream>
using namespace std;
#define concat(a, b) a ## b

int main() {
    int xy = 100;
    cout << concat(x, y);
    return 0;
}
```

1.11 utilities Namespace1

```
#include <iostream>
using namespace std;

/*REFERENCE
 *https://www.tutorialspoint.com/cplusplus/cpp_namespaces.htm
 */

// first name space
namespace first_space{
    void func(){
        cout << "Inside first_space" << endl;
    }
}

// second name space
namespace second_space{
    void func(){
        cout << "Inside second_space" << endl;
    }
}

int main () {

    // Calls function from first name space.
    first_space::func();

    // Calls function from second name space.
    second_space::func();

    return 0;
}
```

1.12 utilities ClassPointers

```
#include <iostream>
using namespace std;

class Person {
public:
    Person() {
        cout << "Constructor called!" << endl;
    }

    ~Person() {
        cout << "Destructor called!" << endl;
    }
};

int main( ) {
    Person* myBoxArray = new Person[4];
    delete [] myBoxArray; // Delete array
    return 0;
}
```

1.13 utilities Debug

```
#include <iostream>
using namespace std;
#define DEBUG

#define MIN(a,b) (((a)<(b)) ? a : b)

int main () {
    int i, j;
    i = 100;
    j = 30;

    #ifdef DEBUG
        cerr << "Trace: Inside main function" << endl;
    #endif

    #if 0
        /* This is commented part */
        cout << MKSTR(HELLO C++) << endl;
    #endif

    cout << "The minimum is " << MIN(i, j) << endl;

    #ifdef DEBUG
        cerr << "Trace: Coming out of main function" << endl;
    #endif
    return 0;
}
```

1.14 utilities Directives2

```
#include<iostream>

using std::cout;
using std::cin;
using std::endl;

/*
 * g++ -E test.cpp > sal.out
 * compile with that command and see how the compiler replace the
 * constant
 */
#define PI 3.141516
#define MIN(a,b) (((a)<(b)) ? a : b)

int main(){
```

```
    cout << "The number PI is " << PI << endl;
    cout << "The minimum is " << MIN(i, j) << endl;
    return 0;
}
```

1.15 utilities PointersDeclaration

```
#include <iostream>
using namespace std;

int main(){

    double * data;
    data = new double;

    *data = 123.34;

    cout << *data << endl;

    delete data;

    return 0;
}
```

1.16 utilities PredefinedMacros

```
#include <iostream>
using namespace std;

int main () {
    cout << "Value of __LINE__ : " << __LINE__ << endl;
    cout << "Value of __FILE__ : " << __FILE__ << endl;
    cout << "Value of __DATE__ : " << __DATE__ << endl;
    cout << "Value of __TIME__ : " << __TIME__ << endl;

    return 0;
}
```

1.17 utilities Template

```
#include <iostream>
#include <string>

/*REFERENCES
 * https://www.tutorialspoint.com/cplusplus/cpp\_templates.htm
 */
using namespace std;

template <typename T>
inline T const& Max (T const& a, T const& b) {
    return a < b ? b:a;
}

int main () {

    int i = 39;
    int j = 20;
    cout << "Max(i, j): " << Max(i, j) << endl;

    double f1 = 13.5;
    double f2 = 20.7;
    cout << "Max(f1, f2): " << Max(f1, f2) << endl;
}
```

```

string s1 = "Hello";
string s2 = "World";
cout << "Max(s1, s2): " << Max(s1, s2) << endl;

return 0;
};

```

1.18 utilities Namespace2

```

#include <iostream>
using namespace std;

/*REFERENCES
*https://www.tutorialspoint.com/cplusplus/cpp\_namespaces.htm
*/
// first name space
namespace first_space{
    void func(){
        cout << "Inside first_space" << endl;
    }
}

// second name space
namespace second_space{
    void func(){
        cout << "Inside second_space" << endl;
    }
}

using namespace first_space;
int main () {

    // This calls function from first name space.
    func();

    return 0;
}

```

1.19 utilities CommaOperator

```

#include <iostream>
using namespace std;

int main() {
    int i, j;

    j = 10;
    i = (j++, j+100, 999+j);

    cout << i;

    return 0;
}

```

1.20 utilities ArrayPointers

```

#include <iostream>
using namespace std;

inline void example_1(){
    char * name;
    name = new char[10];
}

```

```

delete [] name;
}

inline void example_2(){
    int row = 4;
    int col = 3;

    //Allocate memory for rows
    double **pvalue = new double* [row];
    //Now allocate memory for columns
    for (int i=0; i<col; i++){
        pvalue[i] = new double[col];
    }

    //Now release memory
    for(int i = 0; i < row; i++) {
        delete [] pvalue[i];
    }
    delete [] pvalue;
}

int main(){
    example_1();
    example_2();

    return 0;
}

```

1.21 template

```

//Constants and defines
#define show(x) cout << #x << " = " << x << endl;
#define endl '\n'
#define f first
#define s second
#define mp make_pair
#define pb push_back
const double PI = acos(-1);
const ld INF = 1e18;
const double EPS = 1e-15;
// INT_MAX -> limits.h
typedef long long ll;
typedef vector < int > vi;
typedef vector < vi > vii;

//Geometry
inline ld cross(point o, point d){ return(o.x * d.y) - (o.y * d.x); }
inline ld dot(point o, point d){ return (o.x * d.x) + (o.y * d.y); }
inline point diff(point o, point d){ return {d.x-o.x, d.y - o.y}; }
inline ld dist(point o, point d){ return sqrt(dot(r(o,d) , r(o,d))); }

//Input
scanf("%d",&value); //int
scanf("%ld",&value); //long y long int
scanf("%c",&value); //char
scanf("%f",&value); //float
scanf("%lf",&value); //double
scanf("%s",&value); //char*
scanf("%lld",&value); //long long int
scanf("%x",&value); //int hexadecimal
scanf("%o",&value); //int octal

```

```
//Main
int main(){
    ios::sync_with_stdio(false);
    cin.tie(NULL);
#ifdef UDVORAK
    freopen("in.txt", "r", stdin);
    freopen("out.txt", "w", stdout);
#endif
}
```

1.22 For

```
#include <iostream>
#define forn(i, n) for(int i = 0 ; (i) < (n) ; ++i)
using namespace std;
int main(){
    forn(_,10){
        cout << "with out variable" << endl;
    }
    forn(i,10){
        cout << "with variable: " << i << endl;
    }
    return 0;
}
```

1.23 Swap

```
#include <iostream>
#define swap(x,y) (x^=y, y^=x, x^=y)
using namespace std;
int main(){
    int x=324, y=232;
    cout << x << " " << y << endl;
    swap(x,y);
    cout << x << " " << y << endl;
    return 0;
}
```

1.24 StringStream

```
#include <bits/stdc++.h>
using namespace std;
int main(){
    string line;
    while (getline(cin, line)){
        stringstream ss(line);
        string word;
        int count = 0;
        while (ss >> word) count ++;
        cout << endl << "# Words: " << count << endl;
    }
}
```

1.25 UpperLowerBound

```
#include <bits/stdc++.h>
using namespace std;
int main () {
```

```
int myints[] = {10,20,30,30,20,10,10,20};
vector<int> v(myints,myints+8); // 10 20 30 30 20 10
// 10 20
sort (v.begin(), v.end()); // 10 10 10 20 20 20
// 30 30
vector<int>::iterator low,up;
low=lower_bound (v.begin(), v.end(), 20); //
up= upper_bound (v.begin(), v.end(), 20); //
cout << "lower_bound at position " << (low- v.begin()) << '\n';
cout << "upper_bound at position " << (up - v.begin()) << '\n';
return 0;
}
```

1.26 CompareDoubles

```
#include <stdio.h>
using namespace std;
const double EPS = 1e-15;
/*
 * Return
 * -1 if x < y
 * 0 if x == y
 * 1 if x > y
 */
int cmp (double x, double y){
    return (x <= y + EPS) ? (x + EPS < y) ? -1 : 0 : 1;
}
int main(){
    double d1 = 0.0000000000000212;
    double d2 = 0.0000000000000213;
    int res = cmp(d1,d2);
    if (res == 0){
        printf("Equal \n");
    }else if(res == 1){
        printf("Greater\n");
    }else {
        printf("Less \n");
    }
}
```

2 BasicOperations

2.1 Exponentiation

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
ll expo(ll a, ll b, ll c){
    if (b == 0) return 1;
    if (b % 2 == 0) {
        ll temp = expo(a, b/2, c);
        return (temp * temp) % c;
    } else {
        ll temp = expo(a, b-1, c);
        return (temp * a) % c;
    }
}
int main(){
    cout << expo(2, 100, 1025);
    return 0;
}
```

2.2 SumArray

```
#include <bits/stdc++.h>
using namespace std;
typedef vector<int> vi;
inline void show(vi &n2){
    for (int i = 0; i < n2.size() ; i++){
        cout << n2[i];
    }
    cout << endl;
}
inline vi sum_arrays(vi &a1, vi &a2){
    int tam = a1.size();
    vi result(tam + 1,0);
    int carry = 0, aux = 0;
    for (int i = tam; i >= 0; i--){
        aux = a1[i] + a2[i] + carry;
        result[i+1] = aux % 10;
        carry = aux >= 10 ? 1 : 0;
    }
    result[0] = carry;
    return result;
}

int main(){
    int vals[] =
        {3,4,1,0,9,8,7,3,4,9,4,3,5,9,2,3,9,0,4,5,8,7,0,2,4,5,2};
    int val2[] =
        {9,4,1,0,2,8,7,3,4,9,4,3,5,9,2,3,9,0,4,5,8,7,0,2,4,5,2};
    vi n1(begin(vals), end(vals));
    vi n2(begin(val2), end(val2));
    vi result1 = sum_arrays(n1, n2);
    show(result1);
    return 0;
}
```

3 Structures

3.1 DisjointSets

```
#include <bits/stdc++.h>
using namespace std;
typedef vector<int> vi;
struct union_find {
    vi data, pe;
    union_find(int n) : data(vi(n)), pe(vi(n)) {
        for(int i=0; i<data.size(); i++)
            data[i] = i;
    }
    int find(int x) {
        if(x == data[x]) return x;
        data[x] = find(data[x]);
        return data[x];
    }
    bool unite(int x, int y) {
        int px = find(x);
        int py = find(y);
        if(px == py) return false;
        if(pe[px] > pe[py]) swap(px, py);
        pe[px] += pe[py];
        data[py] = px;
    }
}
```

```
        return true;
    }
};
int main() {
    union_find uf(10);
    uf.unite(0, 2);
    cout << uf.find(0) << endl;
    cout << uf.find(2) << endl;
    assert(uf.find(0) == uf.find(2));
    assert(uf.find(0) != uf.find(1));
    return 0;
}
```

3.2 RecoveryTree

```
#include <iostream>
using namespace std;
/**Build a binary tree form a inorder and preoder string **/
int preIndex = 0;
struct node {
    char key;
    node *left, *right;
    node(int k) {
        key = k;
        left = NULL;
        right = NULL;
    }
};
int search(string word, int b, int e, char c) {
    for(int i=b; i<=e; i++) {
        if(word[i] == c) return i;
    }
    return -1;
}
//Set preIndex to 0 to build another tree
node* build(string in, string pre, int b, int e) {
    if(b > e) return NULL;
    node *root = new node(pre[preIndex++]);
    if(b == e) return root;
    int inIndex = search(in, b, e, root->key);
    root->left = build(in, pre, b, inIndex - 1);
    root->right = build(in, pre, inIndex + 1, e);
    return root;
}

int main() {
    string pre, in;
    node *tree;
    while(cin >> pre >> in) {
        tree = build(in, pre, 0, pre.size() - 1);
        preIndex = 0;
    }
    return 0;
}
```

3.3 Prim

```
#include <bits/stdc++.h>
using namespace std;
const int MAXN = 10005;
#define pb push_back
typedef pair<int, int> edge;
// Pareja (nodo, peso)
typedef pair<int, int> weight_node; // Pareja (peso, nodo)
```

```

vector <edge> g[MAXN];
// Lista de adyacencia
bool visited[MAXN];
// Retorna el costo total del MST
int prim(int n){ // n = n mero de nodos
    for (int i = 0; i <= n; ++i) visited[i] = false;
    int total = 0;
    priority_queue<weight_node, vector <weight_node>,
    greater<weight_node> > q;
    // Empezar el MST desde 0 (cambiar si el nodo 0 no existe)
    q.push(weight_node(0, 0));
    while (!q.empty()){
        int u = q.top().second;
        int w = q.top().first;
        q.pop();

        if (visited[u]) continue;
        visited[u] = true;
        total += w;
        for (int i = 0; i < g[u].size(); ++i){
            int v = g[u][i].first;
            int next_w = g[u][i].second;
            if (!visited[v]){
                q.push(weight_node(next_w, v));
            }
        }
    }
    return total;
}

int main(){
    //Nodo 0 se une al 1 con peso 1
    g[0].pb(edge(1,1));
    //Nodo 0 se une al 2 con peso 2
    g[0].pb(edge(2,2));
    //Nodo 0 se une al 3 con peso 3
    g[0].pb(edge(3,3));
    g[1].pb(edge(5,4));
    g[2].pb(edge(4,5));
    g[3].pb(edge(4,1));
    cout << prim(4);
    return 0;
}

```

3.4 SegmentTree

```

#include <iostream>
#define left(x) x << 1
#define right(x) x << 1 | 1
#define ROOT 1
using namespace std;

void build(int *T, int *A, int node, int start, int end) {
    if(start == end) {
        T[node] = A[start];
    } else {
        int mid = (start + end) / 2;
        build(T, A, left(node), start, mid);
        build(T, A, right(node), mid + 1, end);
        // Merging the children
        T[node] = T[left(node)] + T[right(node)];
    }
}

void update(int *T, int *A, int node, int start, int end, int i,
int val ) {

```

```

    if(start == end) {
        A[i] = val;
        T[node] = val;
    } else {
        int mid = (start + end) / 2;
        if(start <= i && i <= mid)
            update(T, A, left(node), start, mid, i, val);
        else
            update(T, A, right(node), mid + 1, end, i, val);
        T[node] = T[left(node)] + T[right(node)];
    }
}

int query(int *T, int node, int start, int end, int a, int b) {
    if(b < start || end < a) // out of the boundaries
        return 0;
    if(a <= start && end <= b)
        return T[node];
    int mid = (start + end) / 2;
    int p1 = query(T, left(node), start, mid, a, b);
    int p2 = query(T, right(node), mid + 1, end, a, b);
    return p1 + p2;
}

int main() {
    int size = 5;
    int *a = new int[size];
    int *stree = new int[4 * size];
    for (int i = 0; i < size ; i++) a[i] = i + 1;
    build(stree, a, ROOT, 0, size - 1);
    int from = 0, to = 4;
    cout << query(stree, ROOT, 0, size-1, from, to) << endl;
    return 0;
}

```

3.5 FenwickTree

```

#include <bits/stdc++.h>
using namespace std;
#define flag(x) printf("[%d]\n", x)
typedef vector<int> vi;
struct fenwick_tree {
    vi data;
    fenwick_tree(int _n) : data(vi(_n + 1, 0)) {}
    void update(int i, int val) {
        while(i < data.size()) {
            data[i] += val;
            i += i & (-i);
        }
    }
    int query(int i) {
        int sum = 0;
        while(i > 0) {
            sum += data[i];
            i -= i & (-i);
        }
        return sum;
    }
    int query_segment(int a, int b) {
        return query(b) - query(a - 1);
    }
};

int main() {
    int x[5] = {1, 2, 3, 4, 5};
    fenwick_tree *fq = new fenwick_tree(8);
    for(int i=0; i<5; i++)
        fq->update(i + 1, x[i]);
}

```



```
//Node 0 -> dummy node
for(int i=1; i<fq->data.size(); i++) {
    cout << fq->data[i] << ' ';
}cout << endl;
//Sum interval [1 - 4]
flag(fq->query(4));
//Sum interval [3 - 5]
flag(fq->query_segment(3, 5));
return 0;
}
```

3.6 MaxMinPHeap

```
/**Utility STL Data Structures*/
/**Max Heaps*/
priority_queue <int> pq;
/**Min Heaps*/
priority_queue <int, vector<int>, greater<int> > pq;
```

3.7 BinaryTree

```
#include <iostream>
using namespace std;
struct node {
    int val = 0;
    node * l = nullptr;
    node * r = nullptr;
};
inline node* build(node *head, int value){
    node *son = new node;
    son->val = value;
    if (head == nullptr) return son;
    node * aux = head, * nxt = head;
    while(nxt != nullptr){
        aux = nxt;
        if (value > nxt->val) nxt = nxt->r;
        else nxt = nxt->l;
    }
    if(value > aux-> val) aux->r = son;
    else aux->l = son;
    return head;
}
inline void show(node* head){
    if (head==nullptr) return;
    show(head->l);
    cout << head->val << endl;
    show(head->r);
}
int main(){
    node *head = new node;
    head->val = 5;
    head = build(head, 45);
    head = build(head, 20);
    show(head);
    return 0;
}
```

3.8 Trie

```
#include <bits/stdc++.h>
```

```
using namespace std;

/*
 * Struct for a trie
 */
struct node {
    node * son[26];
    bool is_end;
    int num_times;

    node(){
        memset(son, 0, sizeof(son));
        is_end =false;
        num_times =0;
    }
};

/*
 * insert a word in the trie
 */
void insert(node* nd, char *s){
    if(*s){
        int pos = *s - 'a';
        if(!nd->son[pos]) nd->son[pos]=new node();
        insert(nd->son[pos], s+1);
    }else{
        nd->is_end = true;
    }
}

/*
 * Check if the word is in the trie
 */
int contains(node *nd, char *s){
    if(*s){
        int pos = *s - 'a';
        if(!nd->son[pos]) return false;
        return contains(nd->son[pos], s+1);
    }else{
        return nd->is_end;
    }
}

//This is just the driver program
int main(){
    node * trie = new node();
    string a = "word";
    char *cstr = new char[a.length() + 1];
    strcpy(cstr, a.c_str());
    insert (trie, cstr);
    string b = "banani";
    strcpy(cstr, b.c_str());
    insert (trie, cstr);
    if (contains(trie, cstr)){
        cout << "ohh holly xx." << endl;
    }else{
        cout << "mother ..." << endl;
    }
    return 0;
}
```

3.9 Kruskals

```
#include <bits/stdc++.h>
using namespace std;
typedef vector<int> vi;
```

```

typedef vector<bool> vb;
typedef pair<int, int> pii;
typedef pair<long long, pii> edge;
typedef vector<pii> vpii;
typedef vector<edge> E;

long long weight;
int vertex;

vpii mst(int n, E &edges, vb &vis) {
    weight = 0; vertex = 0;
    union_find uf(n);
    sort(edges.begin(), edges.end());
    vpii res;
    for(int i=0; i<edges.size(); i++) {
        int x = edges[i].second.first;
        int y = edges[i].second.second;
        if(uf.find(x) != uf.find(y)) {
            if(!vis[x]) {
                vertex++;
                vis[x] = true;
            }
            if(!vis[y]) {
                vertex++;
                vis[y] = true;
            }
            weight += edges[i].first;
            res.push_back(pii(min(x, y), max(x, y)));
            uf.unite(x, y);
        }
    }
    return res;
}

int main() {
    int v, e, x, y, w;
    while(scanf("%d %d", &v, &e) && (v + e)){
        E list(e);
        vb vis(v);
        for(int i=0; i<e; i++) {
            scanf("%d %d %d", &x, &y, &w);
            list[i] = edge(w, pii(x, y));
        }
        vpii answ = mst(v, list, vis);
        if(vertex == v) {
            printf("%lld\n", weight);
            sort(answ.begin(), answ.end());
            for(int i=0; i<answ.size(); i++){
                printf("%d %d\n", answ[i].first, answ[i].second);
            }
        }
        else printf("Impossible\n");
    }
    return 0;
}

```

3.10 MaxFlow

```

#include <bits/stdc++.h>
using namespace std;
#define V 6
bool bfs(int rGraph[V][V], int s, int t, int parent[]){
    bool visited[V];
    memset(visited, 0, sizeof(visited));
    queue<int> q;
    q.push(s);
    visited[s] = true;

```

```

    parent[s] = -1;
    while (!q.empty()){
        int u = q.front();
        q.pop();
        for (int v=0; v<V; v++){
            if (visited[v]==false && rGraph[u][v] > 0)
                {
                    q.push(v);
                    parent[v] = u;
                    visited[v] = true;
                }
        }
    }
    return (visited[t] == true);
}

int fordFulkerson(int graph[V][V], int s, int t){
    int u, v;
    int rGraph[V][V]; // Residual graph where rGraph[i][j]
                       // indicates
                       // residual capacity of
                       // edge from i to j (if
                       // there
                       // is an edge. If rGraph[i
                       // ][j] is 0, then there
                       // is not)

    for (u = 0; u < V; u++)
        for (v = 0; v < V; v++)
            rGraph[u][v] = graph[u][v];

    int parent[V];
    int max_flow = 0; // There is no flow initially
    while (bfs(rGraph, s, t, parent)){
        int path_flow = INT_MAX;
        for (v=t; v!=s; v=parent[v]){
            u = parent[v];
            path_flow = min(path_flow, rGraph[u][v]);
        }
        for (v=t; v != s; v=parent[v]){
            u = parent[v];
            rGraph[u][v] -= path_flow;
            rGraph[v][u] += path_flow;
        }
        max_flow += path_flow;
    }
    return max_flow;
}

int main(){
    int graph[V][V] = { {0, 16, 13, 0, 0, 0},
                        {0, 0, 10, 12, 0,
                          0},
                        {0, 4, 0, 0, 14,
                          0},
                        {0, 0, 9, 0, 0,
                          20},
                        {0, 0, 0, 7, 0,
                          4},
                        {0, 0, 0, 0, 0, 0}
                      };

    int origen = 0;
    int dest = 5;
    cout << "The maximum possible flow is "
    << fordFulkerson(graph, origen, dest);

    return 0;
}

```

4 NP_{problem}

4.1 Knapsack

```
#include <bits/stdc++.h>
using namespace std;

typedef vector < int > vi;
typedef vector < vi > vii;
// w[i] = peso del objeto i (i comienza en 1)
vi w;
vi v;
// dp[i][j] maxima ganancia si se toman un subconjunto de los
// objetos 1 .. i y se tiene una capacidad de j
int ** dp;

int knapsack(int n, int W){
    for (int j = 0; j <= W; ++j) dp[0][j] = 0;
    for (int i = 1; i <= n; ++i){
        for (int j = 0; j <= W; ++j){
            dp[i][j] = dp[i-1][j];
            if (j - w[i] >= 0){
                dp[i][j] = max(dp[i][j],
                    dp[i-1][j-w[i]] + v[i]);
            }
        }
    }
    return dp[n][W];
}

int main(){
    int numObjects = 10;
    int maxCapacity = 100;
    dp = new int*[numObjects];
    for (int i = 0; i < maxCapacity; i++){
        dp[i] = new int[maxCapacity];

        w.resize(numObjects);
        v.resize(numObjects);
        int cont = numObjects;
        for (int i = 1; i < numObjects; i++){
            w[i] = i;
            v[i] = cont--;
        }
        cout << knapsack(10, 100);
    }
}
```

5 Combinatory

5.1 BinomialCPP

```
#include <iostream>
using namespace std;
const int MAXN = 66;
unsigned long long choose[MAXN+5][MAXN+5];
void binomial(int N){
    for (int n = 0; n <= N; ++n)
        choose[n][0] = choose[n][n] = 1;
    for (int n = 1; n <= N; ++n){
        for (int k = 1; k < n; ++k){
            choose[n][k] = choose[n-1][k-1] + choose[n-1][k];
        }
    }
}
```

```
    }
}

int main(){
    binomial(10);
    cout << choose[10][2] << endl;
}
```

5.2 BinomialPYTHON

```
import math, sys
MAXN = 431
choose = []
for i in range (0, MAXN+5):
    choose.append([0]*(MAXN+5))
def binomial(N):
    for n in range (0, N+1):
        choose[n][0] = choose[n][n] = 1
    for n in range(1, N+1):
        for k in range(1, n):
            choose[n][k] = choose[n-1][k-1] + choose[n-1][k]
if __name__ == "__main__":
    N = 431
    binomial(N)
    n, k = 10, 4
    print(choose[n][k])
```

6 Primes

6.1 PollardRhoCPP

```
#include <bits/stdc++.h>
using namespace std;

typedef long long ll;
ll num;

int modular_pow(ll base, int exponent, ll modulus){
    ll result = 1;
    while (exponent > 0){
        if (exponent & 1)
            result = (result * base) % modulus;
        exponent = exponent >> 1;
        base = (base * base) % modulus;
    }
    return result;
}

ll PollardRho(ll n){
    srand (time(NULL));
    if (n==1) return n;
    if (n % 2 == 0) return 2;
    ll x = (rand()%(n-2))+2;
    ll y = x;
    ll c = (rand()%(n-1))+1;
    ll d = 1;
    cout << n << endl;
    while (d==1){
        x = (modular_pow(x, 2, n) + c + n)%n;
        y = (modular_pow(y, 2, n) + c + n)%n;
        y = (modular_pow(y, 2, n) + c + n)%n;
        d = __gcd(abs(x-y), n);
        if (d==n) return PollardRho(n);
    }
}
```

```

    }
    return d;
}

int main(){
    num = 124554;
    printf("One of the divisors for %lld is %lld.", num,
        PollardRho(num));
    return 0;
}

```

6.2 PollardRhoPYTHON

```

import random as r
def gcd( a, b):
    if(b == 0): return a;
    return gcd(b, a % b);
def pollardRho(N):
    if N%2==0: return 2
    x = r.randint(1, N-1)
    y = x
    c = r.randint(1, N-1)
    g = 1
    while g==1:
        x = ((x*x)%N+c)%N
        y = ((y*y)%N+c)%N
        y = ((y*y)%N+c)%N
        g = gcd(abs(x-y),N)
    return g
if(__name__=="__main__"):
    print(pollardRho(10967535067))
    print(pollardRho(113))

```

6.3 MillerTest

```

#include <bits/stdc++.h>
using namespace std;
typedef unsigned long long ll;
int power(ll x, ll y, ll p){
    int res = 1;
    x = x % p;
    while (y > 0){
        if (y & 1) res = (res*x) % p;
        y = y >> 1;
        x = (x * x) % p;
    }
    return res;
}

bool miillerTest(long long d, long n){
    ll a = 2 + rand() % (n - 4);
    ll x = (ll)power(a, d, n);
    if (x == 1 || x == n-1)
        return true;
    while (d != n-1){
        x = (ll)(x * x) % n;
        d *= 2;
        if (x == 1) return false;
        if (x == n-1) return true;
    }
    return false;
}

bool isPrime(ll n, ll k){
    if (n <= 1 || n == 4) return false;

```

```

    if (n <= 3) return true;
    ll d = n - 1;
    while (d % 2 == 0) d /= 2;
    // Iterate given nber of 'k' times
    for (ll i = 0; i < k; i++){
        if (miillerTest(d, n) == false)
            return false;
        return true;
    }
    int main(){
        ll k = 4; // Number of iterations
        ll n = 982451653;
        cout << (isPrime(n, k)?"True":"False") << endl;
        return 0;
    }

```

6.4 IsPrime

```

import java.math.BigInteger;
import java.util.Scanner;
public class prime {
    public static void main(String[] args) {
        BigInteger a = new BigInteger("1299827");
        //User miller rabin & Lucas Lehmer
        boolean res = a.isProbablePrime(10);
        System.out.println(res? "It's prime":"It's not
        prime");
    }
}

```

6.5 Sieve

```

#include <bits/stdc++.h>
#define tam 1000
using namespace std;
typedef long long ll;
typedef vector< bool > vbool;
void show (vbool primes){
    int cap = primes.size();
    for(int i = 0; i < cap; i++){
        cout << i << " : " << primes[i] << endl;
    }
}

vbool sieve(ll n){
    vbool sieve (tam);
    for (int i = 0; i < tam; i++)
        sieve[i] = true;
    sieve[0] = sieve[1] = false;
    ll root = sqrt(n);
    for (int i = 2; i < root; i++){ //find primes
        if(sieve[i]){
            //removes all the multiples
            //of the current prime
            for (int k = i*i; k <= n; k+=i){
                sieve[k] = false;
            }
        }
    }
    return sieve;
}

int main(){
    vbool primes = sieve(1000);
    show(primes);
    primes.clear();

```

```
    return 0;
}
```

6.6 PrimalityTest

```
#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
bool isPrime(ll n){
    if (n < 2) return false;
    if (n < 4) return true;
    if (n % 2 == 0 || n % 3 == 0) return false;
    if (n < 25) return true;
    for(int i = 5; i*i <= n; i += 6){
        if(n % i == 0 || n % (i + 2) == 0)
            return false;
    }
    return true;
}
int main(){
    cout << isPrime(23234) << endl;
    cout << isPrime(2) << endl;
    cout << isPrime(7454) << endl;
    cout << isPrime(976) << endl;
    cout << isPrime(1973) << endl;
    return 0;
}
```

6.7 Factorize

```
#include <bits/stdc++.h>
#define pb push_back
#define show(x) cout << #x << " = " << x << endl;
using namespace std;
const int MAXN = 1000000;
bool sieve[MAXN + 5];
typedef long long ll;
vector <ll> pri; //primes

void build_sieve(){
    memset(sieve, false, sizeof(sieve));
    sieve[0] = sieve[1] = true;
    for (ll i = 2LL; i * i <= MAXN; i++){
        if (!sieve[i]){
            for (ll j = i * i; j <= MAXN; j += i){
                sieve[j] = true;
            }
        }
    }
    for (ll i = 2; i <= MAXN; ++i){
        if (!sieve[i]) pri.pb(i);
    }
}
//before call this call build_sieve
vector <ll> fact(long long a){
    vector <ll> ans;
    ll b = a;
    for (int i = 0; 1LL * pri[i] * pri[i] <= a; ++i){
        int p = pri[i];
        while (b % p == 0){
            ans.push_back(p);
            b /= p;
        }
    }
}
```

```
    }
    if (b != 1) ans.push_back(b);
    return ans;
}
int main(){
    build_sieve();
    ll num_to_fact= 128234234LL;
    vector < long long > vll = fact(num_to_fact);
    for (int x=0; x< vll.size(); x++){
        cout << vll[x] << " ";
    }
    cout << endl;
}
```

7 Search

7.1 BinarySearch

```
#include <bits/stdc++.h>
using namespace std;
const int TAM = 5;
int arr[TAM];
/* Recursive
 * l -> left
 * r -> right
 * x -> element to search
 */
int binarySearchRec(int l, int r, int x){
    if (r >= l){
        int mid = l + (r - l)/2;
        // The element in the middle
        if (arr[mid] == x) return mid;
        // Smaller of the middle element
        if (arr[mid] > x) return binarySearchRec( l, mid-1, x);
        // Greater that the middle element
        return binarySearchRec(mid+1, r, x);
    }
    return -1;
}

/* Iterative
 * l -> left
 * r -> right
 * x -> element to search
 */
int binarySearchIte( int l, int r, int x){
    while (l <= r){
        int m = l + (r-l)/2;
        // The element in the middle
        if (arr[m] == x) return m;
        // Smaller of the middle element
        if (arr[m] < x) l = m + 1;
        // Greater that the middle element
        else r = m - 1;
    }
    // if we reach here, then element was not present
    return -1;
}

int main(void){
    arr[0] = 2;
    arr[1] = 3;
    arr[2] = 4;
    arr[3] = 10;
```

```

    arr[4] = 40;
    int x = 10;
    int result = binarySearchIte(0, TAM-1, x);
    (result == -1)? printf("Element is not present in array")
                  : printf("Element is present at index %d \n",
                           result);

    return 0;
}

```

8 Sorting

8.1 SelectionSort SelectionSortPYTHON

```

def show(elements):
    for element in elements:
        print(element, end = " ")
    print("")

def sort(elements, array_length):
    for i in range(0, array_length):
        smallest = elements[i]
        pos_smallest = i
        for index in range(i+1, array_length):
            if elements[index] < elements[pos_smallest]:
                pos_smallest = index
        aux = elements[i]
        elements[i] = elements[pos_smallest]
        elements[pos_smallest] = aux

if __name__ == "__main__":
    elements = [23, -3, 85, 0, 21, -10, 40]
    array_length = len(elements)
    print("original array")
    show(elements)
    print("sorted array")
    sort(elements, array_length)
    show(elements)

```

8.2 SelectionSort SelectionSortCPP

```

#include<iostream>
using namespace std;
int show(int array[], int length_array){
    for (int index = 0 ; index < length_array; index++){
        cout << array[index] << " ";
    }
    cout << endl;
}

int sort(int array[], int length_array){
    for (int index = 0; index < length_array; index++){
        int pos_smallest = index;
        for(int index_aux = index+1; index_aux < length_array;
            index_aux++){
            if (array[pos_smallest] > array[index_aux]){
                pos_smallest = index_aux;
            }
        }
        //Swap
        if( pos_smallest != index){
            int aux = array[index];
            array[index] = array[pos_smallest];
            array[pos_smallest] = aux;
        }
    }
}

```

```

    }
}

int main(){
    int length_array = 7;
    int array [] = {58, -5, 10, 8, 78 ,234, 43};
    cout << "Original Array" << endl;
    show(array, length_array);
    sort(array, length_array);
    cout << "Sorted Array" << endl;
    show(array, length_array);
}

```

8.3 InsertionSort InsertionSortPYTHON

```

def show(array):
    for element in array:
        print(element, end = " ")
    print("")

def sort(array, length_array):
    for index in range(1, length_array):
        key = array[index]
        index_aux = index - 1
        while index_aux >= 0 and array[index_aux] > key:
            array[index_aux+1] = array[index_aux]
            index_aux = index_aux - 1
        array[index_aux+1] = key

def main():
    array = [50, 885, 1, -8, 54, 2, 54, 0]
    print("Original array")
    show(array)
    print("Sorted array")
    sort(array, len(array))
    print(array)

main()

```

8.4 InsertionSort InsertionSortCPP

```

#include <iostream>
using namespace std;
void show(int array[], int length_array){
    for (int index = 0; index < length_array; index ++){
        cout << array[index] << " ";
    }
    cout << endl;
}

void sort(int array[], int length_array){
    for (int index = 1; index < length_array; index ++){
        int key = array[index];
        int index_aux = index - 1;
        while (index_aux >= 0 && array[index_aux] > key){
            array[index_aux + 1] = array[index_aux];
            index_aux = index_aux - 1;
        }
        array[index_aux + 1] = key;
    }
}

int main(){
    int length_array = 8;
    int array[] = {50, 885, 1, -8, 54, 2, 54, 0};
    show(array, length_array);
    sort(array, length_array);
    show(array, length_array);
}

```

8.5 BubbleSort Bubble

```
#include <bits/stdc++.h>
#define forn(i,j,k) for (int i=j; i<k; i++)
using namespace std;
typedef long long ll;
inline void sort(ll *arr, int size){
    forn(i,0,size-1)
        forn(j,0, size-i-1)
            if (arr[j] > arr[j+1])
                swap(arr[j], arr[j+1]);
}

int main(){
    int size =8;
    ll *data = new ll[size];
    forn(i, 0, size)
        scanf("%lld", &data[i]);
    sort(data, size);
    forn(i, 0, size)
        printf("%lld ",data[i]);
    return 0;
}
```

8.6 MergeSort MergeSortCPP

```
#include<bits/stdc++.h>
using namespace std;
void show(int array [], int length_array){
    int index = 0;
    // cout<< "size : "<< array.size() <<endl;
    while(index<length_array){
        printf("%d ",array[index]);
        index = index +1;
    }
    printf("\n");
}

void sort(int array[], int pos_ini, int pos_final){
    /*In this condition the len of the array
    left and right half arrays will be
    of 1 element both */
    if(pos_final > pos_ini){
        //first calc the half point
        int pos_mid = (pos_ini+pos_final)/2;
        sort(array, pos_ini, pos_mid);
        sort(array, pos_mid +1, pos_final);
        merge(array, pos_ini, pos_mid, pos_final);
    }
}

void merge( int array[], int pos_ini, int pos_mid,int pos_final){
    int size_left = pos_mid - pos_ini + 1;
    int size_right = pos_final - pos_mid;
    /* create temp arrays */
    int lefthalf[size_left], righthalf[size_right];
    for (int i = 0; i < size_left; i++)
        lefthalf[i] = array[pos_ini + i];
    for (int j = 0; j < size_right; j++)
        righthalf[j] = array[pos_mid + 1+ j];
    int index_right_half = 0;
    int index_left_half = 0;
    int index = pos_ini;
    while (index_left_half < size_left && index_right_half <
        size_right) {
```

```
        if(lefthalf[index_left_half] <= righthalf[index_right_half]){
            array[index] = lefthalf[index_left_half];
            index_left_half = index_left_half +1;
        }else{
            array[index] = righthalf[index_right_half];
            index_right_half = index_right_half+1;
        }
        index = index +1;
    }
    //Copy the remaining elements if there is any
    while( index_left_half < size_left){
        array[index] = lefthalf[index_left_half];
        index_left_half = index_left_half +1;
        index = index +1;
    }
    while( index_right_half < size_right){
        array[index] = righthalf[index_right_half];
        index_right_half = index_right_half +1;
        index = index +1;
    }
}

int main(){
    int array[] = {-10, 37, 98 , 0 ,12, 192, 5};
    int length_array = sizeof(array)/ sizeof(array[0]);
    show(array, length_array);
    sort(array, 0, length_array -1);
    show(array, length_array);
}
```

8.7 MergeSort MergeSortPY

```
def merge_sort(array):
    ##Stop when the len of the array is less or equal than one
    if len(array)>1:
        #Calc the mid of the array
        mid = len(array) // 2 # // mean integer division

        #Create two arrays left and right
        lefthalf = array[:mid]
        print(lefthalf)

        righthalf = array[mid:]
        print(righthalf)

        #Divide the subarrays left and right
        merge_sort(lefthalf)
        merge_sort(righthalf)

        ##I send the array as a argument to change the same array
        and not another
        merge(lefthalf, righthalf, array)

def merge(lefthalf, righthalf, array):
    index_array_left=0
    index_array_right=0
    k=0
    while index_array_left < len(lefthalf) and \
        index_array_right < len(righthalf):
        if lefthalf[index_array_left] < \
            righthalf[index_array_right]:
            #assign the less to the new array
            array[k]=lefthalf[index_array_left]

            ""As the less was an element in the lefthalf we dont
            need to compare this again so we increase the index
```

```

        of the left array""
        index_array_left=index_array_left+1
    else:
        array[k]=righthalf[index_array_right]

        ""As the less was an element in the righthalf we dont
        need to compare this again so we increase the index
        of the left array""
        index_array_right=index_array_right+1

        #It is necessary increase the pos of the original array
        k=k+1

##add the remaining elements
while index_array_left < len(lefthalf):
    array[k]=lefthalf[index_array_left]
    index_array_left=index_array_left+1
    k=k+1

while index_array_right < len(righthalf):
    array[k]=righthalf[index_array_right]
    index_array_right=index_array_right+1
    k=k+1

def main():
    array = [-10, 37, 98 , 0 ,12, 192, 5]
    print("Original Array")
    print(array)
    merge_sort(array)

    print("Sorted Array")
    print(array)
main()

```

8.8 StandardSort

```

#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
typedef vector < ll > vl;
int main(){
    vl data = {234234LL, 2322LL,1LL, -1LL, 3454LL};
    sort(data.begin(), data.end());
    for (int i=0; i< data.size(); i++)
        printf("%lld ", data[i]);
    return 0;
}

```

9 Strings

9.1 Palindrome

```

#include <iostream>
#include <string>

using namespace std;
inline bool evaluate(string word, int i, int j){
    if (i >= j) return true;
    else if (word[i] != word[j]) return false;
    return evaluate(word, i+1, j-1);
}

inline bool is_palindrome(string word){
    int length = word.length();
    if (length == 1) return true;

```

```

    return evaluate(word, 0, length-1);
}

int main(){
    string word = "anamariaairamana";
    string word2 = "Thississ";
    cout << word << " ";
    cout << is_palindrome(word) << endl;
    cout << word2 << " ";
    cout << is_palindrome(word2) << endl;
    return 0;
}

```

9.2 FunctionsOverChart

```

#include <bits/stdc++.h>
using namespace std;
int main(){
    char a = 'a';
    cout << (isalnum(a)?"true":"false") << endl;
    cout << (isalpha(a)?"true":"false") << endl;
    cout << (isblank(a)?"true":"false") << endl;
    cout << (isdigit(a)?"true":"false") << endl;
    cout << (islower(a)?"true":"false") << endl;
    cout << (ispunct(a)?"true":"false") << endl;
    cout << (isupper(a)?"true":"false") << endl;
    cout << (isxdigit(a)?"true":"false") << endl;
    cout << (char)tolower(a) << endl;
    cout << (char)toupper(a) << endl;
    return 0;
}

```

9.3 Split

```

#include <bits/stdc++.h>
using namespace std;
/* Split by space */
int main(){
    string line;
    while(getline(cin, line)){
        stringstream ss;
        ss.str(line);
        string item;
        while (getline(ss, item, ' ')) {
            cout << item << endl;
        }
    }
    return 0;
}

```

9.4 Regex

```

#include <iostream>
#include <iterator>
#include <regex>
#include <string>
using namespace std;
int main(){
    string s = "123daniel , jajaja, lol, 234234534, I am from
                Earth";

```



```

regex tel("\\d{8},\\sI");
auto words_begin = sregex_iterator(s.begin(), s.end(), tel);
auto words_end = sregex_iterator();
cout << "Found " << distance(words_begin, words_end)<< " words
\n";
const int N = 6;
for (sregex_iterator i = words_begin; i != words_end; ++i) {
    smatch match = *i;
    string match_str = match.str();
    if (match_str.size() > N) {
        cout << " " << match_str << '\n';
    }
}
return 0;
}

```

9.5 KMP

```

#include <bits/stdc++.h>
using namespace std;
bool kmp(const string &needle, const string &haystack){
    int m = needle.size();
    vector<int> border(m);
    border[0] = 0;
    for (int i = 1; i < m; ++i) {
        border[i] = border[i - 1];
        while (border[i] > 0 and needle[i] != needle[border[i]])
            border[i] = border[border[i] - 1];
        if (needle[i] == needle[border[i]]) border[i]++;
    }
    int n = haystack.size();
    int seen = 0;
    for (int i = 0; i < n; ++i){
        while (seen > 0 and haystack[i] != needle[seen])
            seen = border[seen - 1];
        if (haystack[i] == needle[seen]) seen++;
        if (seen == m) return true; // Ocurre entre [i - m + 1, i]
    }
    return false;
}

int main(){
    string a = "hola";
    string b = "thauautholueeo";
    cout << kmp(a, b);
}

```

9.6 LCI

```

#include <bits/stdc++.h>
using namespace std;
//Compute the largest increasing subsequence
int lis( int arr[], int n ){
    int *lis, i, j, max = 0;
    lis = (int*) malloc ( sizeof( int ) * n );
    for ( i = 0; i < n; i++ )
        lis[i] = 1;
    for ( i = 1; i < n; i++ )
        for ( j = 0; j < i; j++ )
            if ( arr[i] > arr[j] && lis[i] < lis[j] + 1 )
                lis[i] = lis[j] + 1;
    for ( i = 0; i < n; i++ )

```

```

        if (max < lis[i])
            max = lis[i];
    free(lis);
    return max;
}

int main(){
    int arr[] = { 10, 22, 9, 33, 21, 50, 41, 60 };
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("Length of lis is %d\n", lis( arr, n ) );
    //sol = 10, 22, 33, 50, 60
    return 0;
}

```

9.7 LCS

```

#include <bits/stdc++.h>
#define endl '\n'
using namespace std;
const int M_MAX = 20; // Mximo size del String 1
const int N_MAX = 20; // Mximo size del String 2
int m, n; // Size de Strings 1 y 2
string X; // String 1
string Y; // String 2
int memo[M_MAX + 1][N_MAX + 1];
int lcs (int m, int n) {
    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0 || j == 0) memo[i][j] = 0;
            else if (X[i - 1] == Y[j - 1]) memo[i][j] = memo[i - 1][j - 1] + 1;
            else memo[i][j] = max(memo[i - 1][j], memo[i][j - 1]);
        }
    }
    return memo[m][n];
}

int main(){
    X = "XMJYAUZ";
    Y = "MZJAWXU";
    cout << lcs(X.size(), Y.size()) << endl;
    //Sol = MJAU
    return 0;
}

```

10 Math

10.1 Matrix Gaussian Elimination

```

// C++ program to demonstrate working of Gaussian Elimination
// method
#include <bits/stdc++.h>
using namespace std;

#define N 3 // Number of unknowns

// function to reduce matrix to r.e.f. Returns a value to
// indicate whether matrix is singular or not
int forwardElim(double mat[N][N+1]);

// function to calculate the values of the unknowns
void backSub(double mat[N][N+1]);

// function to get matrix content
void gaussianElimination(double mat[N][N+1])

```

```

{
    /* reduction into r.e.f. */
    int singular_flag = forwardElim(mat);

    /* if matrix is singular */
    if (singular_flag != -1)
    {
        printf("Singular Matrix.\n");

        /* if the RHS of equation corresponding to
        zero row is 0, * system has infinitely
        many solutions, else inconsistent*/
        if (mat[singular_flag][N])
            printf("Inconsistent System.");
        else
            printf("May have infinitely many "
                "solutions.");

        return;
    }

    /* get solution to system and print it using
    backward substitution */
    backSub(mat);
}

// function for elementary operation of swapping two rows
void swap_row(double mat[N][N+1], int i, int j)
{
    //printf("Swapped rows %d and %d\n", i, j);

    for (int k=0; k<=N; k++)
    {
        double temp = mat[i][k];
        mat[i][k] = mat[j][k];
        mat[j][k] = temp;
    }
}

// function to print matrix content at any stage
void print(double mat[N][N+1])
{
    for (int i=0; i<N; i++, printf("\n"))
        for (int j=0; j<=N; j++)
            printf("%1f ", mat[i][j]);

    printf("\n");
}

// function to reduce matrix to r.e.f.
int forwardElim(double mat[N][N+1])
{
    for (int k=0; k<N; k++)
    {
        // Initialize maximum value and index for pivot
        int i_max = k;
        int v_max = mat[i_max][k];

        /* find greater amplitude for pivot if any */
        for (int i = k+1; i < N; i++)
            if (abs(mat[i][k]) > v_max)
                v_max = mat[i][k], i_max = i;

        /* if a principal diagonal element is zero,
        * it denotes that matrix is singular, and
        * will lead to a division-by-zero later. */
        if (!mat[k][i_max])
            return k; /* Matrix is singular

        /* Swap the greatest value row with current row */
        if (i_max != k)
            swap_row(mat, k, i_max);

        for (int i=k+1; i<N; i++)
        {
            /* factor f to set current row kth elemnt
            to 0,
            * and subsequently remaining kth column to
            0 */
            double f = mat[i][k]/mat[k][k];

            /* subtract fth multiple of corresponding
            kth
            row element*/
            for (int j=k+1; j<=N; j++)
                mat[i][j] -= mat[k][j]*f;

            /* filling lower triangular matrix with
            zeros*/
            mat[i][k] = 0;
        }

        //print(mat); //for matrix state
    }
    //print(mat); //for matrix state
    return -1;
}

// function to calculate the values of the unknowns
void backSub(double mat[N][N+1])
{
    double x[N]; // An array to store solution

    /* Start calculating from last equation up to the
    first */
    for (int i = N-1; i >= 0; i--)
    {
        /* start with the RHS of the equation */
        x[i] = mat[i][N];

        /* Initialize j to i+1 since matrix is upper
        triangular*/
        for (int j=i+1; j<N; j++)
        {
            /* subtract all the lhs values
            * except the coefficient of the variable
            * whose value is being calculated */
            x[i] -= mat[i][j]*x[j];
        }

        /* divide the RHS by the coefficient of the
        unknown being calculated */
        x[i] = x[i]/mat[i][i];
    }

    printf("\nSolution for the system:\n");
    for (int i=0; i<N; i++)
        printf("%1f\n", x[i]);
}

// Driver program
int main()
{
    /* input matrix */
    double mat[N][N+1] = {{3.0, 2.0, -4.0, 3.0},
                          {2.0, 3.0, 3.0,
                           15.0},
                          {5.0, -3, 1.0,
```

```

        14.0}
    };

    gaussianElimination(mat);
    return 0;
}

```

10.2 Polynomial HornersRule

```

#include <iostream>
using namespace std;
/* Example
 * given the polynomial  $f(x) = 2x^3 - 6x^2 - 2x - 1$ 
 * we want to know  $f(8)$ 
 * -the traditional form in evaluate it
 * by the horners method is by syntetic division
 * 8 |  $X^3$   $X^2$   $X^1$   $X^0$ 
 *   | 2  -6  -2  -1
 *   |      16  80  624
 *   -----
 *      2   10   78   623
 * With these we can say that the remainder is 623
 *  $f(8) = 623$ 
 * Wow a pretty good ALGORITHM
 */
int Horner( int a[], int n, int x ){
    int result = a[n];
    for(int i=n-1; i >= 0 ; --i)
        result = result * x + a[i];
    return result;
}

int main(){
    int grade = 3;
    // -1 -2x -6x^2 +2x^3
    int a[] = {-1,-2,-6,2};
    int x = 8;
    cout << Horner (a, grade, x);
    return 0;
}

```

10.3 NumberTheory GCD_{LCM}

```

#include<cstdio>
using namespace std;
int gcd(int a, int b){
    if(b == 0) return a;
    return gcd(b, a % b);
}

int lcm(int n1, int n2){
    return (n1 * n2) / gcd(n1,n2);
}

int main(){
    int n1=2366, n2=273;
    printf("gcd(%ld, %ld) = %ld\n",
        n1, n2, gcd(n1,n2));
    return 0;
}

```

10.4 NumberTheory DivisorsCPP

```

#include <bits/stdc++.h>
using namespace std;
typedef set<int> si;
/* Get the divisors of a number */
si divisors(int n) {
    si d;
    int r = sqrt(n);
    for(int i = 1; i <= r; i++) {
        if(n % i == 0) {
            d.insert(i);
            d.insert(n / i);
        }
    }
    return d;
}

int main() {
    si divi = divisors(10);
    for (set<int>::iterator it=divi.begin(); it!=divi.end(); ++it)
        printf("%d ", *it);
    printf("\n");
}

```

10.5 NumberTheory DivisorsPYTHON

```

import math
"""Get the divisors of a number"""
def listDivisors(n):
    divisors = set()
    lim = int(math.sqrt(n))
    for i in range(1, lim + 1):
        if n % i == 0:
            divisors.add(i)
            divisors.add(n // i)
    return divisors

def main():
    d = listDivisors(100)
    print(len(d))
    print(d)

main()

```

10.6 NumberTheory Josephus

```

#include <bits/stdc++.h>
#define show(x) cout << #x << " = "<< x << endl;
using namespace std;
//https://www.youtube.com/watch?v=uCsD3ZGzMgE
int jose(int n, int k) {
    if (n == 1) return 0;
    if (n < k) return (jose(n-1,k)+k)%n;
    int np = n - n/k;
    return k*((jose(np,k)+np-n%k*np)%np) / (k-1);
}

int maxBit(int x){
    for (int i =31; i>=0; i--){
        if(x&(1LL<<i)){
            return i;
        }
    }
    return 0;
}

//always start with soldier 1
int sol(int numSoldiers){

```

```

int maxr = maxBit(numSoldiers) + 1;
int it = (numSoldiers << 1) - (1LL<<maxr) + 1;
return it; //soldier that survives
}

int main(){
    int n = 10;
    int res = sol(n);
    show(res);
    return 0;
}

```

10.7 Pow FastPow

```

#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
ll modular_pow(ll base, int exponent, ll modulus){
    ll result = 1;
    while (exponent > 0){
        /* if y is odd, multiply base with result */
        if (exponent & 1)
            result = (result * base) % modulus;
        /* exponent = exponent/2 */
        exponent = exponent >> 1;
        /* base = base * base */
        base = (base * base) % modulus;
    }
    return result;
}

int main(){
    ll exp = 1023;
    cout << modular_pow (2, exp, 999) << endl;
}

```

10.8 NumberSystems ChangeBases

```

# coding=utf-8
""" CHANGE THE BASE OF A NUMBER
    ob -> origin base
    od -> destiny base
"""

chars = "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZ"

def changeBase(number, ob,od):
    if ob == 10:
        return tob(number, od)
    return tob(to10(number,ob),od)

""" FROM ANY BASE TO BASE 10
    b -> base of the number n
    pos -> location of a sub-number in n
"""

def to10(n, b, pos =0):
    if n == 0: return 0
    return (n % 10)* (b ** pos) + to10(n / 10, b, pos+1)

"""FROM TEN BASE TO ANOTHER BASE"""
def tob(n, b):
    if n == 0: return ""
    return tob(n // b, b) + chars[n % b]

def main():
    print ( tob(7,2))

```

```

print ( tob(252,16))
print ( tob(234,15))
print ( to10(1000,2))
print ( changeBase(111,2,10))

main()

```

10.9 NumberSystems ChangeBases

```

#include<bits/stdc++.h>
#define endl '\n'
#define show(x) cout <<#x << " =" <<x <<endl;
using namespace std;
string chars = "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZ";

int to10(int n , int b, int pos){
    if (n ==0 ) return 0;
    return ((n % 10)* pow(b,pos)) + to10(n / 10, b, pos+1);
}

string tob(int n, int b){
    if (n == 0) return "";
    return tob(n / b, b) + chars[n % b];
}

/*
 * ob -> origin base
 * db -> destiny base
 */

string changeBase(int num, int ob, int db){
    if (ob == 10) return tob(num, db);
    return tob(to10(num, ob, 0), db);
}

int main(){
    cout << changeBase(8757,2,16) <<endl;
}

```

11 Sequences

11.1 MatrixFibo

```

#include <iostream>
using namespace std;
typedef long long ll;
ll *f;

int fib(ll n){
    if (n == 0) return 0;
    if (n == 1 || n == 2) return (f[n] = 1);
    if (f[n]) return f[n];
    int k = (n & 1)? (n+1)/2 : n/2;
    if (n&1){
        f[n] = (ll) fib(k) * fib(k) + fib(k-1) * fib(k-1) ;
    }else{
        f[n] = (2*fib(k-1) + fib(k))*fib(k);
    }
    return f[n];
}

int main(){
    ll n = 10;
    f = new ll[n];
    cout<< fib(n);
    return 0;
}

```

```
}
```

12 probability

12.1 ComposedProbability

```
#include <iostream>
#include <vector>
#define forn(i,n) for (int i=0; i<n; i++)
#define s(a) ((int) a.size())

using namespace std;
typedef double d;
typedef vector < d > vd;

/*
 * N --> Number of faces
 * toss -> number of toss
 */
void prob(int N, int t){
    vd P = {1.0};
    /*
     * RANDOM VARIABLES
     * X,Y
     * Z = X + Y
     * f(Z) = f(X) CONVOLUCION f(Y)
     */
    forn(_, t){
        vd Pr(s(P) + N - 1, 0);
        forn (j, s(P)){
            forn (k, N){
                Pr[j + k] += P[j] / N;
            }
        }
        P.swap(Pr);
    }
    forn(i, s(P)){
        cout << "P(" << (i+t) << "):" << P[i] << endl;
    }
}

int main(){
    prob(6, 1);
    cout << endl;
    prob(6, 2);
    cout << endl;
    prob(6, 3);
}
```

13 Geometry

13.1 RayCasting

```
#include <bits/stdc++.h>
#define pb push_back
#define mp make_pair
using namespace std;

/*
 * This program implements the ray casting algorithm to check
 * if a point is inside or outside of a simple polygon
 */
```

```
*/
typedef double ld;
struct point {
    ld x, y;
    point(){}
    point(ld x, ld y){
        this->x = x;
        this->y = y;
    }
};

struct vert {
    point o,d;
};

typedef vector < point > polygon;

inline ld cross(point o, point d){ return(o.x * d.y) - ( o.y * d.x); }
inline ld dot(point o, point d){ return (o.x * d.x) + ( o.y * d.y ); }
inline point diff(point o, point d){ return {d.x-o.x, d.y - o.y} ;}
inline ld dist(point o, point d){ return sqrt(dot(diff(o,d) , diff(o,d))); }

inline bool segments_parallel(point a, point b, point c){
    return abs(cross(diff(c,a),diff(b,a))) == 0;
}

inline bool point_on_segment(polygon v, point c){
    int cant = v.size();
    for (int i=0;i<cant;i++){
        if (dist(v[i],c)==0) return true;
        if (dist(v[(i+1)%cant],c)==0) return true;
        if(segments_parallel(v[i], v[(i+1)%cant], c) && dot(diff(c,v[i]), diff(c,v[(i+1)%cant])) < 0) {
            return true;
        }
    }
    return false;
}

/* Ray Casting algorithm
 * true inside
 * false outside
 */
bool point_in_polygon(point p, polygon a){
    bool inside = false;
    int cant = a.size();
    for (int i=0;i<cant;i++){
        int j = (i+1) % cant;
        point aux = a[i];
        point nxt = a[j];
        bool cond1 = (p.y < aux.y != p.y < nxt.y);
        bool cond2 = (p.x < aux.x + (nxt.x - aux.x) * (p.y - aux.y) / (nxt.y - aux.y));
        if ( cond1 && cond2 ){
            inside = !inside;
        }
    }
    return inside;
}

inline void test_point(polygon v, point pun){
    if(point_on_segment(v,pun)){
        cout << "on"<<endl;
    }else if (point_in_polygon(pun, v)){
        cout << "in"<<endl;
    }else{
        cout <<"out"<<endl;
    }
}
```

```

}
int main(){
    polygon p;
    p.pb(point(1,0)); p.pb(point(2,1));
    p.pb(point(1,2)); p.pb(point(0,1));
    test_point(p, point(0,0));
    test_point(p, point(1,1));
    test_point(p, point(1.5,0.5));
    return 0;
}

```

13.2 LineIntersect2

```

#include <bits/stdc++.h>
#define mp make_pair
#define f first
#define s second
using namespace std;
#define show(x) cout << #x << " = " << x << endl;
typedef long double ld;
struct point {
    ld x;
    ld y;
    point (){}
    point (int _x, int _y){
        x = _x;
        y = _y;
    }
};
typedef vector < point > vp;
struct line {
    point o, d;
    line(){}
    line (point _o, point _d){
        o=_o;
        d=_d;
    }
};
pair < bool, point> getLineIntersection(line l1, line l2){
    point p0 =l1.o, p1=l1.d, p2=l2.o, p3=l2.d;
    point AB( p1.x - p0.x, p1.y -p0.y);
    point DC( p3.x - p2.x, p3.y - p2.y);

    ld s, t;
    point i;

    int dx = p0.x - p2.x;
    int dy = p0.y - p2.y;
    s = (-AB.y * dx + AB.x * dy) / (-DC.x * AB.y + AB.x * DC.y);
    t = ( DC.x * dy - DC.y * dx) / (-DC.x * AB.y + AB.x * DC.y);

    if (s >= 0 && s <= 1 && t >= 0 && t <= 1){
        // Collision detected
        i.x = p0.x + (t * AB.x);
        i.y = p0.y + (t * AB.y);
        return mp(true, i);
    }
    return mp(false, i); // No collision
}

int main(){
    line l1(point(0,1),point(2,3));
    line l2(point(3,0),point(0,3));
    pair<bool, point> i = getLineIntersection(l1,l2);
    // intersect x=1, y=2
    if (i.f){

```

```

        printf("The lines does collide in: \n");
        show(i.s.x);
        show(i.s.y);
    }else {
        printf("There is no collision.\n");
    }
    return 0;
}

```

13.3 PickTheorem

```

#include <stdio.h>
using namespace std;
/*
 * Pick's theorem is a useful method for determining the area of
 * any polygon whose
 * vertices are points on a lattice, a regularly spaced array of
 * points.
 */
/*
 * b boundary point : a lattice point on the polygon including
 * vertices
 * i interior point : a lattice points on the polygon's interior
 * region
 */
double area_poligon(double b, double i){
    return (b/2) + i -1;
}
int main(){
    printf("%f",area_poligon(5,5));
    return 0;
}

```

13.4 EulerFormule

```

#include <stdio.h>
using namespace std;
typedef long long ll;
bool is_a_poligon(ll V, ll E, ll F){
    return V - E + F == 2;
}
int main(){
    printf("%s\n",
        is_a_poligon(3, 34,5) ? "true" : "false");
    //This is a cube
    printf("%s\n",
        is_a_poligon(8,12,6) ? "true" : "false");
    return 0;
}

```

13.5 Line2Point

```

#include<bits/stdc++.h>
#define f first
#define s second
#define mp make_pair
#define magnitude(x) (sqrt(x.f*x.f + x.s*x.s))
#define show(x) cout << #x << " = " << x << endl;
using namespace std;

typedef long double ld;
typedef pair< ld, ld> point;

```

```

struct line {
    point o, d;
    line(point _o, point _d){
        o = _o;
        d = _d;
    }
};

inline point diff(point o, point d){
    return mp(d.f - o.f, d.s - o.s);
}

inline ld crossProduct(point o, point d){
    ld cross = (o.f * d.s) - (o.s * d.f);
    return cross > 0 ? cross : cross * -1;
}

/*
 * Find the minimum distance from a point to a line
 * just having two points 'AB' of the line and the point C
 */
ld distance(line l, point C){
    //A, B points in the line
    point A = l.o, B=l.d;
    point AB = diff(A,B); //base
    point AC = diff(A,C);
    ld area = crossProduct(AB, AC);
    ld distance1 = area / magnitude(AB);
    ld distance2 = area / magnitude(AC);
    return min(distance1, distance2);
}

int main(){
    point A,B,C;
    A = mp(2,4);
    B = mp(5,0);
    C = mp(6,4);
    cout << distance(line(A,B),C);
    return 0;
}

```

13.6 PolygonArea

```

#include <bits/stdc++.h>
#define f first
#define s second
#define mp make_pair
#define pb push_back
using namespace std;
typedef long double ld;
typedef pair<ld, ld> point;
typedef vector<point> polygon;
inline point diff(point o, point d){
    return mp(d.f-o.f, d.s - o.s);
}

inline ld crossProduct(point o, point d){
    ld cross = (o.f * d.s) - (o.s * d.f);
    return cross > 0 ? cross : cross * -1;
}

inline ld area(polygon p){
    int num_points = p.size();
    ld area = 0;
    for (int i = 1; i < num_points - 1; i++){
        point l1 = diff(p[0],p[i]);
        point l2 = diff(p[0],p[i+1]);
        area += crossProduct(l1,l2);
    }
    return abs(area/2.0);
}

int main(){

```

```

    polygon p;
    p.pb(mp(1,0)); p.pb(mp(2,1));
    p.pb(mp(1,2)); p.pb(mp(0,1));
    cout << area(p);
    return 0;
}

```

13.7 ConvexHull

```

#include <bits/stdc++.h>
using namespace std;
struct Point{
    int x, y;
};
Point p0;
Point nextToTop(stack<Point> &S){
    Point p = S.top();
    S.pop();
    Point res = S.top();
    S.push(p);
    return res;
}

int swap(Point &p1, Point &p2){
    Point temp = p1;
    p1 = p2;
    p2 = temp;
}

int distSq(Point p1, Point p2){
    return (p1.x - p2.x)*(p1.x - p2.x) +
        (p1.y - p2.y)*(p1.y - p2.y);
}

int orientation(Point p, Point q, Point r){
    int val = (q.y - p.y) * (r.x - q.x) -
        (q.x - p.x) * (r.y - q.y);
    if (val == 0) return 0; // colinear
    return (val > 0) ? 1 : 2; // clock or counterclock wise
}

int compare(const void *vp1, const void *vp2){
    Point *p1 = (Point *)vp1;
    Point *p2 = (Point *)vp2;
    int o = orientation(p0, *p1, *p2);
    if (o == 0)
        return (distSq(p0, *p2) >= distSq(p0, *p1)) ? -1 : 1;
    return (o == 2) ? -1 : 1;
}

void convexHull(Point points[], int n){
    int ymin = points[0].y, min = 0;
    for (int i = 1; i < n; i++){
        int y = points[i].y;
        if ((y < ymin) || (ymin == y && points[i].x < points[min].x))
            ymin = points[i].y, min = i;
    }
    swap(points[0], points[min]);
    p0 = points[0];
    qsort(&points[1], n-1, sizeof(Point), compare);
    int m = 1;
    for (int i=1; i<n; i++){
        while (i < n-1 && orientation(p0, points[i], points[i+1])
            == 0){
            i++;
        }
        points[m] = points[i];

```

```

    m++;
}
if (m < 3) return;
stack<Point> S;
S.push(points[0]);
S.push(points[1]);
S.push(points[2]);

for (int i = 3; i < m; i++){
    while (orientation(nextToTop(S), S.top(), points[i]) != 2)
        S.pop();
    S.push(points[i]);
}
while (!S.empty()){
    Point p = S.top();
    cout << "(" << p.x << ", " << p.y << ")" << endl;
    S.pop();
}
}

int main(){
    Point points[] = {{0, 3}, {1, 1}, {2, 2}, {4, 4},
                     {0, 0}, {1, 2}, {3, 1}, {3, 3}};
    int n = sizeof(points)/sizeof(points[0]);
    convexHull(points, n);
    return 0;
}

```

13.8 CircleCenter

```

#include <bits/stdc++.h>
using namespace std;
const double PI = acos(-1);
#define show(x) cout << #x << " = " << x << endl;
struct point {
    double x;
    double y;
    point (){}
    point (double _x, double _y){
        x = _x;
        y = _y;
    }
};
inline point getCenter(point p1, point p2, point p3){
    point center;
    float m1 = (p2.y - p1.y)/(p2.x - p1.x);
    float m2 = (p3.y - p2.y)/(p3.x - p2.x);
    center.x = ( m1 * m2 * (p1.y - p3.y) + m2 * ( p1.x + p2.x)
                - m1 * (p2.x + p3.x) )
                / (2 * (m2 - m1) );
    center.y = -1 * (center.x - (p1.x + p2.x) / 2) / m1 + (p1.y +
        p2.y) / 2;
    return center;
}

int main(){
    point p1(1,1), p2(2,4), p3(5,3);
    point res = getCenter(p1, p2, p3);
    show(res.x)
    show(res.y)
    return 0;
}

```

14 Arrays

14.1 PermutationPYTHON

```

def permutation(array, start = 0):
    if (start == len(array)):
        print(array)
        return
    for i in range(start, len(array)):
        array[start], array[i] = array[i], array[start]
        permutation(array, start + 1)
        array[start], array[i] = array[i], array[start]
    if __name__ == "__main__":
        permutation(['d', 'a', 'n'])

```

14.2 Operations

```

from itertools import permutations, combinations

def pers(array):
    ps = permutations(array)
    for p in ps: print (p)

def combs(array, r=2):
    cmb = combinations(array, r)
    for c in cmb: print (c)

if __name__ == "__main__":
    pers([1,2,3,4,5])
    combs([1,2,3,4,5])

```

14.3 MapFunctions

```

"""
Apply different function over an array
"""
def square(num): return num ** 2
def cube(num): return num ** 3
def is_pair(num): return num % 2
functions = [square, cube, is_pair]
array = [1, 7, -2, 4, 5, 10, 0]
for elemn in array:
    value = map(lambda x: x(elemn), functions)
    print (elemn, end=" :")
    [print (x, end=" ") for x in value if x != None]
    print()

```

14.4 Kadane

```

#include <bits/stdc++.h>
#define forn(i,j,k) for(int i=j; i<k; i++)
using namespace std;
typedef long long ll;
/*
 * Largest Sum Contiguous Subarray
 * Kadane Algorithm
 * Complexity O(n)
 */

```



```

inline ll get_max_sum(ll data[8], int size){
    ll max_so_far= data[0];
    ll max_ending_here = data[0];
    forn(i, 1, size){
        max_ending_here = max(data[i], \
            data[i] + max_ending_here);
        max_so_far = max(max_so_far, max_ending_here);
    }
    return max_so_far;
}

int main(){
    int size = 8;
    ll data[8] = {-1,2,4,-3,5,2,-5,2};
    ll res = get_max_sum(data, size);
    printf("The max sum that can be done with \n \
        Contiguous elements is: %lld \n", res);
    return 0;
}

```

14.5 Combination

```

def combination(array, data, start, end, index, r):
    if (index == r):
        print (data)
        return
    for i in range(start, end+1):
        """ end-i+1 >= r-index" makes sure that
            including one element at index will
            make a combination with remaining
            elementsat remaining positions
        """
        if (end - i + 1 >= r - index):
            data[index] = array[i]
            combination(array, data, i+1, end, index + 1, r)

def get_combinations(array, r, n):
    combination(array, [0] * r, 0, n-1, 0, r)

if __name__ == "__main__":
    array = [0,1,2,3,4,5]
    get_combinations(array, r=3, n=len(array))

```

14.6 PermutationCPP

```

#include <bits/stdc++.h>
using namespace std;
typedef vector <int > vi;
inline void show(vi &data, int &size){
    for (int i=0; i<size; i++)
        printf("%d \t", data[i]);
    printf("\n");
}

inline void permutation(vi data, int size){
    sort(data.begin(), data.end());
    do {
        show(data, size);
    }while(next_permutation(data.begin(), data.end()));
    show(data, size);
}

int main(){
    int size = 3 ;
    int data[] = {1,4,-1};

```

```

    vi vals(begin(data), end(data));
    permutation(vals, size);
    return 0;
}

```

15 Graphs

15.1 Traverse BFS

```

#include <bits/stdc++.h>
#define pb push_back
using namespace std;
typedef vector < int > vi;
vi dis;
vector < vi > graph;
void show_distances(){
    for( int i = 0; i< dis.size(); i++){
        cout << i << " : " << dis[i] << "\n";
    }
}

void bfs(int origin){
    queue < int > q;
    dis[origin] = 0;
    q.push(origin);
    while( q.size() > 0){
        int front = q.front(); q.pop();
        for(int son: graph[front]){
            if(dis[son] == -1){
                dis[son] = dis[front] +1;
                q.push(son);
            }
        }
    }
}

int main(){
    int num_nodes = 5;
    dis.assign(num_nodes, -1);
    graph.resize(num_nodes);
    graph[0].pb(1);
    graph[0].pb(2);
    graph[0].pb(3);
    graph[1].pb(4);
    bfs(0);
    show_distances();
    return 0;
}

```

15.2 Traverse DFS

```

#include <bits/stdc++.h>
#define pb push_back
#define NUM_NODES 20
using namespace std;
vector < int > g[NUM_NODES];
int vis[NUM_NODES];
enum {WHITE, GRAY, BLACK};
void dfs(int o){
    vis [o] = GRAY; //semi-visited
    for (int i = 0; i < g[o].size(); i++){
        int v = g[o][i];
        if (vis[v] == GRAY)

```

```

        cout << "Cycle to " << o << endl;
        // visit neighbors
        else if (vis[v] == WHITE) dfs(v);
    }
    cout << o << endl;
    vis[o] = BLACK; //visited;
}
int main(){
    g[0].pb(1); g[0].pb(2);
    g[0].pb(3); g[1].pb(4);
    g[1].pb(5); g[2].pb(6);
    g[3].pb(7); g[4].pb(0);
    g[6].pb(0);
    dfs(0);
    return 0;
}

```

15.3 BestPath DijkstraHeap

```

#include <bits/stdc++.h>
#define pb push_back
using namespace std;
#define forn(i,a) for (int i=0; i<a ; i++)
#define INF 2e7
struct edge{
    int to, weight;
    edge(){}
    edge(int _to, int _weight){
        to = _to;
        weight = _weight;
    }
    bool operator < (edge e) const {
        return weight > e.weight;
    }
};
typedef vector < edge > ve;
typedef vector < ve > vve;
typedef vector < int > vi;
typedef priority_queue< edge> pq;
inline void dijkstra(vve &adj, int src, int num_nodes){
    vi dist = vi(num_nodes+1, INF);
    pq q;
    //by default
    q.push(edge(src, 0));
    dist[src] = 0;
    //apply bfs
    while(!q.empty()){
        edge top = q.top();
        q.pop();
        int u = top.to;
        for(int i=0; i<adj[u].size(); i++){
            int v = adj[u][i].to;
            if(dist[u] + adj[u][i].weight < dist[v]){
                dist[v] = dist[u] + adj[u][i].weight;
                q.push(edge(v, dist[v]));
            }
        }
    }
    //Show results of distances
    cout << "Distancias desde el origen ";
    cout << src << endl;
    forn(i, num_nodes){
        cout << "Costo al nodo: " << i;
        cout << " = " << dist[i] << endl;
    }
}

```

```

int main(){
    int nodes =5;
    vve adj(nodes);
    //from to - weight
    adj[0].pb(edge(1, 6));
    adj[0].pb(edge(2, 2));
    adj[1].pb(edge(3, 5));
    adj[1].pb(edge(4, 7));

    int src = 1;
    dijkstra(adj, src, nodes);
    return 0;
}

```

15.4 BestPath Dijkstra

```

#include <bits/stdc++.h>
#define numVertices 9
inline int showSol(int dist[], int n){
    printf("numVerticesertex\tDistance from Source\n");
    for (int i = 0; i < numVertices; i++)
        printf("%d\t%d\n", i, dist[i]);
}
int minDis(int dist[], bool is_set[]){
    int min = INT_MAX, min_index;
    for (int v = 0; v < numVertices; v++){
        if (is_set[v] == false && dist[v] <= min){
            min = dist[v], min_index = v;
        }
    }
    return min_index;
}
inline void dijkstra(int graph[numVertices][numVertices], int src)
{
    int dist[numVertices];
    bool is_set[numVertices];
    for (int i = 0; i < numVertices; i++){
        dist[i] = INT_MAX, is_set[i] = false;
    }
    dist[src] = 0;
    for (int count = 0; count < numVertices-1; count++){
        int u = minDis(dist, is_set);
        is_set[u] = true;
        for (int v = 0; v < numVertices; v++){
            if (!is_set[v] && graph[u][v]
                && dist[u] != INT_MAX
                && dist[u]+graph[u][v] < dist[v])
                dist[v] = dist[u] + graph[u][v];
        }
    }
    showSol(dist, numVertices);
}
int main(){
    int graph[numVertices][numVertices] =
    {{0, 4, 0, 0, 0, 0, 0, 8, 0},
    {4, 0, 8, 0, 0, 0, 0, 11, 0},
    {0, 8, 0, 7, 0, 4, 0, 0, 2},
    {0, 0, 7, 0, 9, 14, 0, 0, 0},
    {0, 0, 0, 9, 0, 10, 0, 0, 0},
    {0, 0, 4, 14, 10, 0, 2, 0, 0},
    {0, 0, 0, 0, 0, 2, 0, 1, 6},
    {8, 11, 0, 0, 0, 0, 1, 0, 7},
    {0, 0, 2, 0, 0, 0, 6, 7, 0}};
}

```

```

    //distances from all points to 1
    dijkstra(graph, 1);
    return 0;
}

```

15.5 BestPath BellmanFord

```

#include <cstdio>
#include <vector>
#define f first
#define s second
#define pb push_back
#define MAX 2e9
using namespace std;

typedef vector<int> vi;
typedef pair<int, int> pii;
typedef vector<pii> vpii;
typedef vector<vpii> vvpii;

void init(vi &distances, int src) {
    for(int i=0; i<distances.size(); i++)
        distances[i] = MAX;
    distances[src] = 0;
}

/*
 *Given a graph and a source vertex src in graph,
 *find shortest paths from src to all vertices in
 *the given graph. The graph may contain negative weight edges.
 */
void bellmanFord(vvpii &graph, vi &dist) {
    for(int i=0; i<graph.size() - 1; i++) {
        for(int u = 0; u < graph.size(); u++) {
            for(pii v : graph[u]) {
                dist[v.f] = min(dist[v.f], v.s + dist[u]);
            }
        }
    }
}

int main() {
    vvpii adj(5);
    vi d(5);
    int src = 0;
    init(d, src);
    adj[0].pb({1, 6}); adj[0].pb({3, 7});
    adj[1].pb({2, 5}); adj[1].pb({3, 8});
    adj[1].pb({4, -4}); adj[2].pb({1, -2});
    adj[3].pb({2, -3}); adj[3].pb({4, 9});
    adj[4].pb({0, 2}); adj[4].pb({2, 7});
    bellmanFord(adj, d);
    printf("from node= %d\n", src);
    for(int i=0; i<d.size(); i++) {
        printf("to %d = %d \n", i, d[i]);
    }
}

```

```

    printf("\n");
    return 0;
}

```

15.6 BestPath FloydWarshal

```

#include<iostream>
#include<stdio.h>
using namespace std;
/*
 * Floyd-Warshall gives us the shortest paths
 * from all sources to all target nodes.
 */
#define V 4 //number of vertex
#define INF 9999999

void print_sol(int dist[][V]){
    printf ("shortest distances \n");
    for (int i = 0; i < V; i++){
        for (int j = 0; j < V; j++){
            if (dist[i][j] == INF)
                printf("%7s", "INF");
            else
                printf ("%7d", dist[i][j]);
        }
        printf("\n");
    }
}

void floyd (int graph[][V]){
    int dist[V][V], i, j, k;
    for (i = 0; i < V; i++)
        for (j = 0; j < V; j++)
            dist[i][j] = graph[i][j];
    for (k = 0; k < V; k++){
        for (i = 0; i < V; i++){
            for (j = 0; j < V; j++){
                if (dist[i][k] + dist[k][j] < dist[i][j])
                    dist[i][j] = dist[i][k] + dist[k][j];
            }
        }
    }
    print_sol(dist);
}

int main(){
    int graph[V][V] = { {0, 5, INF, 10},
                        {INF, 0, 3, INF},
                        {INF, INF, 0, 1},
                        {INF, INF, INF, 0}
    };

    floyd(graph);
    return 0;
}

```