

Contents

1 Snippets	2	6 Primes	9
1.1 Snippets Show	2	6.1 Primes PollarRhoPYTHON	9
1.2 Snippets Time	2	6.2 Primes MillerTest	9
1.3 Snippets Size	2	6.3 Primes IsPrime	9
1.4 Snippets IsOdd	2	6.4 Primes Sieve	9
1.5 Snippets Assert	2	6.5 Primes PrimalityTest	10
1.6 Snippets StructPriorityQueue	2	6.6 Primes Factorize	10
1.7 Snippets utilities Directives1	3	7 Search	10
1.8 Snippets utilities Namespace1	3	8 Sorting	10
1.9 Snippets utilities ClassPointers	3	8.1 Sorting SelectionSort SelectionSortCPP	10
1.10 Snippets utilities Debug	3	8.2 Sorting InsertionSort InsertionSortPYTHON	11
1.11 Snippets utilities Directives2	3	8.3 Sorting InsertionSort InsertionSortCPP	11
1.12 Snippets utilities PointersDeclaration	4	8.4 Sorting BubbleSort Bubble	11
1.13 Snippets utilities PredefinedMacros	4	8.5 Sorting MergeSort MergeSortCPP	12
1.14 Snippets utilities Template	4	8.6 Sorting MergeSort MergeSortPY	12
1.15 Snippets utilities Namespace2	4	8.7 Sorting StandardSort	13
1.16 Snippets utilities CommaOperator	4	9 Strings	13
1.17 Snippets utilities ArrayPointers	5	9.1 Strings Palindrome	13
1.18 Snippets For	5	9.2 Strings FunctionsOverChart	13
1.19 Snippets Swap	5	9.3 Strings Split	13
1.20 Snippets FreeOpen	5	9.4 Strings Regex	13
1.21 Snippets StringStream	5	10 Math	14
1.22 Snippets UpperLowerBound	5	10.1 Math NumberTheory GCD _L CM	14
1.23 Snippets CompareDoubles	6	10.2 Math NumberTheory DivisorsCPP	14
2 BasicOperations	6	10.3 Math NumberTheory DivisorsPYTHON	14
3 Structures	6	10.4 Math NumberTheory Josephus	14
3.1 Structures RecoveryTree	6	10.5 Math Pow FastPow	14
3.2 Structures Prim	6	10.6 Math NumberSystems ChangeBases	15
3.3 Structures SegmentTree	7	11 Sequences	15
3.4 Structures FenwickTree	7	12 probability	15
3.5 Structures MaxMinPHeap	7	13 Geometry	15
3.6 Structures BinaryTree	8	13.1 Geometry LineIntersect2	15
3.7 Structures Trie	8	13.2 Geometry PointInteriorBoundary	16
4 NP_{problem}	8	13.3 Geometry PickTheorem	17
5 Combinatory	8	13.4 Geometry EulerFormule	17
5.1 Combinatory BinomialPYTHON	8	13.5 Geometry LineIntersect1	17
		13.6 Geometry Line2Point	18
		13.7 Geometry PolygonArea	18
		13.8 Geometry ConvexHull	19
		13.9 Geometry CircleCenter	20

14 Arrays	20
14.1 Arrays PermutationJAVA	20
14.2 Arrays Operations	20
14.3 Arrays maximum_subarray_problemKadane	21
14.4 Arrays MapFunctions	21
14.5 Arrays Combination	21
14.6 Arrays PermutationCPP	21
15 Graphs	22
15.1 Graphs Traverse DFSJAVA	22
15.2 Graphs Traverse DFSPY	22
15.3 Graphs Traverse DFSCPP	22
15.4 Graphs BestPath DijkstraHeap	23
15.5 Graphs BestPath Dijkstra	23
15.6 Graphs BestPath BellmanFord	24
15.7 Graphs BestPath FloydWarshal	24

1 Snippets

1.1 Snippets Show

```
#include <iostream>
#define show(x) cout << #x << " = " << x << endl;

using namespace std;

int main(){
    int e =32;
    show(e);
}
```

1.2 Snippets Time

```
#include <chrono>
#include <iostream>
using namespace std;
int main(){

    auto start = chrono::high_resolution_clock::now();
    for(long long i = 0; i < 100000000; i++)
        continue;

    auto end = chrono::high_resolution_clock::now();
    chrono::duration<double> diff = end-start;
    cout << diff.count() << endl ;

    return 0;
}
```

1.3 Snippets Size

```
#include <vector>
#include <string>
#include <iostream>
#define sz(a) ((int)(a).size())

using namespace std;

int main(){
    string t = "Hello, what's up";
    vector<int> c (10);
    cout << sz(t) << endl;
    cout << sz(c) << endl;
}
```

1.4 Snippets IsOdd

```
#include <iostream>
#define isOdd(x) (x & 0x01)

using namespace std;

int main (){
    int a =57;
    int b= 32;
    cout << isOdd(a) << endl;
    cout << isOdd(b) << endl;
    return 0;
}
```

1.5 Snippets Assert

```
#include <iostream>
#include <assert.h>
#define isOdd(x) (x & 0x01)
using namespace std;

void test(int num){
    assert(isOdd(num) == 0);
    cout << "Hello: " << num << endl;
}

int main(){
    int a=10, b=22, c=23, d=32;
    test(a);
    test(b);
    test(c);
    test(d);
}
```

1.6 Snippets StructPriorityQueue

```
#include <iostream>
#include <queue>

using namespace std;

typedef priority_queue<edge> pq;

struct edge{
    int to, weight;
    edge(){}
    edge(int _to, int _weight){
        to = _to;
    }
}
```

```

        weight = _weight;
    }
    bool operator < (edge e) const {
        return weight > e.weight;
    }
};

int main(){
    pq edges;

    edges.push(edge(1, 23));
    edges.push(edge(2, 3));
    edges.push(edge(3, 10));
    edges.push(edge(4, 11));
    edges.push(edge(5, 4));

    while(!edges.empty()){
        edge a = edges.top();
        edges.pop();
        cout << a.to << endl;
    }
}

```

1.7 Snippets utilities Directives1

```

#include <iostream>
using namespace std;
#define concat(a, b) a ## b

int main() {
    int xy = 100;
    cout << concat(x, y);
    return 0;
}

```

1.8 Snippets utilities Namespace1

```

#include <iostream>
using namespace std;

/*REFERENCE
 *https://www.tutorialspoint.com/cplusplus/cpp_namespaces.htm
 */

// first name space
namespace first_space{
    void func(){
        cout << "Inside first_space" << endl;
    }
}

// second name space
namespace second_space{
    void func(){
        cout << "Inside second_space" << endl;
    }
}

int main () {

    // Calls function from first name space.
    first_space::func();

    // Calls function from second name space.
}

```

```

second_space::func();
return 0;
}

```

1.9 Snippets utilities ClassPointers

```

#include <iostream>
using namespace std;

class Person {
public:
    Person() {
        cout << "Constructor called!" << endl;
    }

    ~Person() {
        cout << "Destructor called!" << endl;
    }
};

int main( ) {
    Person* myBoxArray = new Person[4];
    delete [] myBoxArray; // Delete array
    return 0;
}

```

1.10 Snippets utilities Debug

```

#include <iostream>
using namespace std;
#define DEBUG

#define MIN(a,b) (((a)<(b)) ? a : b)

int main () {
    int i, j;
    i = 100;
    j = 30;

    #ifdef DEBUG
        cerr << "Trace: Inside main function" << endl;
    #endif

    #if 0
        /* This is commented part */
        cout << MKSTR(HELLO C++) << endl;
    #endif

    cout << "The minimum is " << MIN(i, j) << endl;

    #ifdef DEBUG
        cerr << "Trace: Coming out of main function" << endl;
    #endif
    return 0;
}

```

1.11 Snippets utilities Directives2

```

#include<iostream>

using std::cout;
using std::cin;
using std::endl;

```

```

/*
 * g++ -E test.cpp > sal.out
 * compile with that command and see how the compiler replace the
 * constant
 */
#define PI 3.141516
#define MIN(a,b) (((a)<(b)) ? a : b)

int main(){
    cout << "The number PI is " << PI << endl;
    cout << "The minimum is " << MIN(i, j) << endl;
    return 0;
}

```

1.12 Snippets utilities PointersDeclaration

```

#include <iostream>
using namespace std;

int main(){
    double * data;
    data = new double;
    *data = 123.34;
    cout << *data << endl;
    delete data;
    return 0;
}

```

1.13 Snippets utilities PredefinedMacros

```

#include <iostream>
using namespace std;

int main () {
    cout << "Value of __LINE__ : " << __LINE__ << endl;
    cout << "Value of __FILE__ : " << __FILE__ << endl;
    cout << "Value of __DATE__ : " << __DATE__ << endl;
    cout << "Value of __TIME__ : " << __TIME__ << endl;
    return 0;
}

```

1.14 Snippets utilities Template

```

#include <iostream>
#include <string>

/*REFERENCES
 * https://www.tutorialspoint.com/cplusplus/cpp_templates.htm
 */
using namespace std;

template <typename T>
inline T const& Max (T const& a, T const& b) {
    return a < b ? b:a;
}

```

```

}

int main () {
    int i = 39;
    int j = 20;
    cout << "Max(i, j): " << Max(i, j) << endl;

    double f1 = 13.5;
    double f2 = 20.7;
    cout << "Max(f1, f2): " << Max(f1, f2) << endl;

    string s1 = "Hello";
    string s2 = "World";
    cout << "Max(s1, s2): " << Max(s1, s2) << endl;

    return 0;
};

```

1.15 Snippets utilities Namespace2

```

#include <iostream>
using namespace std;

/*REFERENCES
 *https://www.tutorialspoint.com/cplusplus/cpp_namespaces.htm
 */
// first name space
namespace first_space{
    void func(){
        cout << "Inside first_space" << endl;
    }
}

// second name space
namespace second_space{
    void func(){
        cout << "Inside second_space" << endl;
    }
}

using namespace first_space;
int main () {
    // This calls function from first name space.
    func();
    return 0;
}

```

1.16 Snippets utilities CommaOperator

```

#include <iostream>
using namespace std;

int main() {
    int i, j;

    j = 10;
    i = (j++, j+100, 999+j);

    cout << i;

    return 0;
}

```

1.17 Snippets utilities ArrayPointers

```
#include <iostream>

using namespace std;

inline void example_1(){
    char * name;
    name = new char[10];
    delete [] name;
}

inline void example_2(){
    int row = 4;
    int col = 3;

    //Allocate memory for rows
    double **pvalue = new double* [row];
    //Now allocate memory for columns
    for (int i=0; i<col; i++){
        pvalue[i] = new double[col];
    }

    //Now release memory
    for(int i = 0; i < row; i++) {
        delete [] pvalue[i];
    }
    delete [] pvalue;
}

int main(){
    example_1();
    example_2();

    return 0;
}
```

1.18 Snippets For

```
#include <iostream>

#define forn(i, n) for(int i = 0 ; (i) < (n) ; ++i)

using namespace std;

int main(){
    forn(_,10){
        cout << "with out variable" << endl;
    }
    forn(i,10){
        cout << "with variable: " << i << endl;
    }
    return 0;
}
```

1.19 Snippets Swap

```
#include <iostream>
#define swap(x,y) (x^=y, y^=x, x^=y)
```

```
using namespace std;

int main(){
    int x=324;
    int y=232;
    cout << x << " " << y << endl;
    swap(x,y);
    cout << x << " " << y << endl;
    return 0;
}
```

1.20 Snippets FreeOpen

```
#include <iostream>
#include <stdio.h>

using namespace std;

int main (){
    freopen("data.in", "r", stdin);
    freopen("data.out", "w", stdout);

    return 0;
}
```

1.21 Snippets StringStream

```
#include <iostream>
#include <sstream>
#include <string>
using namespace std;

int main(){
    string line;
    while (getline(cin, line)){
        stringstream ss(line);
        string word;
        int count = 0;
        while ( ss >> word) count ++;
        cout << endl << "# Words: " << count << endl;
    }
}
```

1.22 Snippets UpperLowerBound

```
// lower_bound/upper_bound example
#include <iostream> // cout
#include <algorithm> // lower_bound, upper_bound, sort
#include <vector> // vector
using namespace std;

int main () {
    int myints[] = {10,20,30,30,20,10,10,20};
    vector<int> v(myints,myints+8); // 10 20 30 30 20 10
    // 10 20

    sort (v.begin(), v.end()); // 10 10 10 20 20 20
    // 30 30

    vector<int>::iterator low,up;
    low=lower_bound (v.begin(), v.end(), 20); //
    up= upper_bound (v.begin(), v.end(), 20); //
```

```

    cout << "lower_bound at position " << (low- v.begin()) << '\n';
    cout << "upper_bound at position " << (up - v.begin()) << '\n';
    /*
    lower_bound at position 3
    upper_bound at position 6
    */

    return 0;
}

```

1.23 Snippets CompareDoubles

```

#include <stdio.h>

using namespace std;
const double EPS = 1e-15;

/*
 * Return
 * -1 if x < y
 * 0 if x == y
 * 1 if x > y
 */
int cmp (double x, double y){
    return (x <= y + EPS) ? (x + EPS < y) ? -1 : 0 : 1;
}

int main(){
    double d1 = 0.000000000000212;
    double d2 = 0.000000000000213;
    int res = cmp(d1,d2);
    if (res == 0){
        printf("Equal \n");
    }else if(res == 1){
        printf("Greater\n");
    }else {
        printf("Less \n");
    }
}

```

2 BasicOperations

3 Structures

3.1 Structures RecoveryTree

```

#include <iostream>
using namespace std;
/**Build a binary tree form a
inorder and preorder string */

int preIndex = 0;
struct node {
    char key;
    node *left, *right;

    node(int k) {
        key = k;
        left = NULL;
        right = NULL;
    }
}

```

```

};

int search(string word, int b, int e, char c) {
    for(int i=b; i<=e; i++) {
        if(word[i] == c) return i;
    }
    return -1;
}

//Set preIndex to 0 to build another tree
node* build(string in, string pre, int b, int e) {
    if(b > e)
        return NULL;
    node *root = new node(pre[preIndex++]);
    if(b == e)
        return root;
    int inIndex = search(in, b, e, root->key);
    root->left = build(in, pre, b, inIndex - 1);
    root->right = build(in, pre, inIndex + 1, e);
    return root;
}

int main() {
    string pre, in;
    node *tree;
    while(cin >> pre >> in) {
        tree = build(in, pre, 0, pre.size() - 1);
        preIndex = 0;
    }
    return 0;
}

```

3.2 Structures Prim

```

#include <bits/stdc++.h>

using namespace std;
const int MAXN = 10005;
typedef pair <int, int> edge;
// Pareja (nodo, peso)
typedef pair <int, int> weight_node; // Pareja (peso, nodo)
vector <edge> g[MAXN];
// Lista de adyacencia
bool visited[MAXN];

// Retorna el costo total del MST
int prim(int n){ // n = n mero de nodos
    for (int i = 0; i <= n; ++i) visited[i] = false;
    int total = 0;
    priority_queue<weight_node, vector <weight_node>,
greater<weight_node> > q;
    // Empezar el MST desde 0 (cambiar si el nodo 0 no existe)
    q.push(weight_node(0, 0));
    while (!q.empty()){
        int u = q.top().second;
        int w = q.top().first;
        q.pop();

        if (visited[u]) continue;
        visited[u] = true;
        total += w;
        for (int i = 0; i < g[u].size(); ++i){
            int v = g[u][i].first;
            int next_w = g[u][i].second;
            if (!visited[v]){
                q.push(weight_node(next_w, v));
            }
        }
    }
}

```

```

    }
    return total;
}

int main(){
    //Nodo 0 se une al 1 con peso 1
    g[0].push_back(edge(1,1));
    //Nodo 0 se une al 2 con peso 2
    g[0].push_back(edge(2,2));
    //Nodo 0 se une al 3 con peso 3
    g[0].push_back(edge(3,3));

    g[1].push_back(edge(5,4));
    g[2].push_back(edge(4,5));
    g[3].push_back(edge(4,1));

    cout << prim(4);

    return 0;
}

```

3.3 Structures SegmentTree

```

#include <iostream>
#define left(x) x << 1
#define right(x) x << 1 | 1
#define ROOT 1
using namespace std;

void build(int *T, int *A, int node, int start, int end) {
    if(start == end) {
        T[node] = A[start];
    } else {
        int mid = (start + end) / 2;
        build(T, A, left(node), start, mid);
        build(T, A, right(node), mid + 1, end);
        // Merging the children
        T[node] = T[left(node)] + T[right(node)];
    }
}

void update(int *T, int *A, int node, int start, int end, int i,
            int val) {
    if(start == end) {
        A[i] = val;
        T[node] = val;
    } else {
        int mid = (start + end) / 2;
        if(start <= i && i <= mid)
            update(T, A, left(node), start, mid, i, val);
        else
            update(T, A, right(node), mid + 1, end, i, val);
        T[node] = T[left(node)] + T[right(node)];
    }
}

int query(int *T, int node, int start, int end, int a, int b) {
    if(b < start || end < a) // out of he boundaries
        return 0;
    if(a <= start && end <= b)
        return T[node];

    int mid = (start + end) / 2;
    int p1 = query(T, left(node), start, mid, a, b);
    int p2 = query(T, right(node), mid + 1, end, a, b);

    return p1 + p2;
}

```

```

}

int main() {
    int size = 5;

    int *a = new int[size];
    int *stree = new int[4 * size];

    for (int i = 0; i < size ; i++) a[i] = i + 1;

    build(stree, a, ROOT, 0, size - 1);

    int from = 0, to = 4;
    cout << query(stree, ROOT, 0, size-1, from, to) << endl;
    return 0;
}

```

3.4 Structures FenwickTree

```

#include <bits/stdc++.h>
using namespace std;
#define flag(x) printf("[%d]\n", x)
typedef vector<int> vi;
struct fenwick_tree {
    vi data;
    fenwick_tree(int _n) : data(vi(_n + 1, 0)) {}
    void update(int i, int val) {
        while(i < data.size()) {
            data[i] += val;
            i += i & (-i);
        }
    }
    int query(int i) {
        int sum = 0;
        while(i > 0) {
            sum += data[i];
            i -= i & (-i);
        }
        return sum;
    }
    int query_segment(int a, int b) {
        return query(b) - query(a - 1);
    }
};

int main() {
    int x[5] = {1, 2, 3, 4, 5};
    fenwick_tree *fq = new fenwick_tree(8);
    for(int i=0; i<5; i++)
        fq->update(i + 1, x[i]);
    //Node 0 -> dummy node
    for(int i=1; i<fq->data.size(); i++) {
        cout << fq->data[i] << ' ';
    }cout << endl;
    //Sum interval [1 - 4]
    flag(fq->query(4));
    //Sum interval [3 - 5]
    flag(fq->query_segment(3, 5));
    return 0;
}

```

3.5 Structures MaxMinPHeap

```

/**Utility STL Data Structures*/
/**Max Heaps*/
priority_queue <int> pq;

```

```
/**Min Heaps*/
priority_queue <int, vector<int>, greater<int> > pq;
```

3.6 Structures BinaryTree

```
#include <iostream>
using namespace std;

struct node {
    int val = 0;
    node * l = nullptr;
    node * r = nullptr;
};

inline node* build(node *head, int value){
    node *son = new node;
    son->val = value;
    if (head == nullptr) return son;
    node * aux = head, * nxt = head;
    while(nxt != nullptr){
        aux = nxt;
        if (value > nxt->val) nxt = nxt->r;
        else nxt = nxt->l;
    }
    if(value > aux->val) aux->r = son;
    else aux->l = son;
    return head;
}

inline void show(node* head){
    if (head==nullptr) return;
    show(head->l);
    cout << head->val << endl;
    show(head->r);
}

int main(){
    node *head = new node;
    head->val = 5;

    head = build(head, 45);
    head = build(head, 20);

    show(head);
    return 0;
}
```

3.7 Structures Trie

```
#include <bits/stdc++.h>
using namespace std;

/*
 * Struct for a trie
 */
struct node {
    node * son[26];
    bool is_end;
    int num_times;

    node(){
        memset(son, 0, sizeof(son));
        is_end =false;
        num_times =0;
    }
}
```

```
};

/*
 * insert a word in the trie
 */
void insert(node* nd, char *s){
    if(*s){
        int pos = *s - 'a';
        if(!nd->son[pos]) nd->son[pos]=new node();
        insert(nd->son[pos], s+1);
    }else{
        nd->is_end = true;
    }
}

/*
 * Check if the word is in the trie
 */
int contains(node *nd, char *s){
    if(*s){
        int pos = *s - 'a';
        if(!nd->son[pos]) return false;
        return contains(nd->son[pos], s+1);
    }else{
        return nd->is_end;
    }
}

//This is just the driver program
int main(){
    node * trie = new node();

    string a = "word";
    char *cstr = new char[a.length() + 1];
    strcpy(cstr, a.c_str());
    insert (trie, cstr);

    string b = "banani";
    strcpy(cstr, b.c_str());
    insert (trie, cstr);

    if (contains(trie, cstr)){
        cout << "ohh holly xx." << endl;
    }else{
        cout << "mother ..." << endl;
    }

    return 0;
}
```

4 NP_{problem}

5 Combinatory

5.1 Combinatory BinomialPYTHON

```
import math
import sys

MAXN = 431
choose = []
for i in range (0, MAXN+5):
    choose.append([0]*(MAXN+5))

def binomial(N):
```



```

for n in range(0, N+1):
    choose[n][0] = choose[n][n] = 1
for n in range(1, N+1):
    for k in range(1, n):
        choose[n][k] = choose[n-1][k-1] + choose[n-1][k]
N = 431
binomial(N)
for line in sys.stdin:
    n, k = [int(y) for y in line.split()]
    val = choose[n][k]
    print(val)

```

6 Primes

6.1 Primes PollardRhoPYTHON

```

import random

def gcd(a, b):
    if(b == 0): return a;
    return gcd(b, a % b);

def pollardRho(N):
    if N%2==0:
        return 2
    x = random.randint(1, N-1)
    y = x
    c = random.randint(1, N-1)
    g = 1
    while g==1:
        x = ((x*x)%N+c)%N
        y = ((y*y)%N+c)%N
        y = ((y*y)%N+c)%N
        g = gcd(abs(x-y),N)
    return g

print(pollardRho(10967535067))
print(pollardRho(113))

```

6.2 Primes MillerTest

```

// C++ program Miller-Rabin primality test
#include <bits/stdc++.h>
using namespace std;

int power(long long x, unsigned long long y, long p){
    int res = 1; // Initialize result
    x = x % p; // Update x if it is more than or
                // equal to p
    while (y > 0){
        if (y & 1)
            res = (res*x) % p;
        y = y>>1; // y = y/2
        x = (x*x) % p;
    }
    return res;
}

bool miillerTest(long long d, long n){
    long long a = 2 + rand() % (n - 4);

    long long x = (long long)power(a, d, n);

    if (x == 1 || x == n-1)

```

```

return true;
while (d != n-1){
    x = (long long)(x * x) % n;
    d *= 2;
    if (x == 1) return false;
    if (x == n-1) return true;
}

return false;
}

bool isPrime(long long n, long long k){
    // Corner cases
    if (n <= 1 || n == 4) return false;
    if (n <= 3) return true;

    // Find r such that n = 2^d * r + 1 for some r >= 1
    long long d = n - 1;
    while (d % 2 == 0)
        d /= 2;

    // Iterate given nber of 'k' times
    for (long i = 0; i < k; i++)
        if (miillerTest(d, n) == false)
            return false;

    return true;
}

// Driver program
int main(){
    long k = 4; // Number of iterations

    long long n = 982451653;
    cout << isPrime(n, k) << endl;

    return 0;
}

```

6.3 Primes IsPrime

```

import java.math.BigInteger;
import java.util.Scanner;

public class prime {

    public static void main(String[] args) {
        BigInteger a = new BigInteger("1299827");
        //User miller rabin & Lucas Lehmer
        boolean res = a.isProbablePrime(10);
        System.out.println(res? "It's prime":"It's not
        prime");
    }

}

```

6.4 Primes Sieve

```

#include <iostream>
#include <math.h>
#include <vector>
#define tam 1000

using namespace std;

typedef long long ll;
typedef vector< bool > vbool;

void show (vbool primes){

```

```

int cap = primes.size();
for(int i = 0; i < cap; i++){
    cout << i << " : " << primes[i] << endl;
}
}
vbool sieve(ll n){
    vbool sieve (tam);
    for (int i = 0; i < tam; i++)
        sieve[i] = true;
    sieve[0] = sieve[1] = false;
    ll root = sqrt(n);
    for (int i = 2; i < root; i++){ //find primes
        if(sieve[i]){
            //removes all the multiples
            //of the current prime
            for (int k = i*i; k <= n; k+=i){
                sieve[k] = false;
            }
        }
    }
    return sieve;
}
int main(){
    //Initialize the array
    vbool primes = sieve(1000);
    show(primes);
    primes.clear();
    return 0;
}

```

6.5 Primes PrimalityTest

```

#include <iostream>
#include <math.h>

using namespace std;
typedef long long ll;

bool is_prime(ll n){
    if (n < 2) return false;
    if (n < 4) return true;
    if (n % 2 == 0 || n % 3 == 0) return false;
    if (n < 25) return true;
    for(int i = 5; i*i <= n; i += 6){
        if(n % i == 0 || n % (i + 2) == 0)
            return false;
    }
    return true;
}

int main(){
    cout << is_prime(23234) << endl;
    cout << is_prime(2) << endl;
    cout << is_prime(7454) << endl;
    cout << is_prime(976) << endl;
    cout << is_prime(1973) << endl;
    return 0;
}

```

6.6 Primes Factorize

```

#include <bits/stdc++.h>

```

```

using namespace std;
const int MAXN = 1000000;
bool sieve[MAXN + 5];
vector <int> pri; //pri

void build_sieve(){
    memset(sieve, false, sizeof(sieve));
    sieve[0] = sieve[1] = true;
    for (int i = 2; i * i <= MAXN; i++){
        if (!sieve[i]){
            for (int j = i * i; j <= MAXN; j += i){
                sieve[j] = true;
            }
        }
    }
    for (int i = 2; i <= MAXN; ++i){
        if (!sieve[i]) pri.push_back(i);
    }
}

vector <long long> fact(long long a){
    // Se asume que se tiene y
    // se llama la funci n build_sieve()
    vector <long long> ans;
    long long b = a;
    for (int i = 0; 1LL * pri[i] * pri[i] <= a; ++i){
        int p = pri[i];
        while (b % p == 0){
            ans.push_back(p);
            b /= p;
        }
    }
    if (b != 1) ans.push_back(b);
    return ans;
}

int main(){
    build_sieve();
    long long num_to_fact;
    cin >> num_to_fact;
    vector < long long > vll = fact(num_to_fact);

    for (int x=0; x < vll.size(); x++){
        cout << vll[x] << " ";
    }
    cout << endl;
}

```

7 Search

8 Sorting

8.1 Sorting SelectionSort SelectionSortCPP

```

#include<iostream>
using namespace std;

int show(int array[], int length_array);
int sort(int array[], int length_array);

int show(int array[], int length_array){
    for (int index = 0 ; index < length_array; index++){
        cout << array[index] << " ";
    }
}

```

```

        cout << endl;
    }
    int sort(int array[], int length_array){
        for (int index = 0; index < length_array; index++){
            int pos_smallest = index;
            for(int index_aux = index+1; index_aux < length_array;
                index_aux++){
                if (array[pos_smallest] > array[index_aux]){
                    pos_smallest = index_aux;
                }
            }
            //Swap
            if( pos_smallest != index){
                int aux = array[index];
                array[index] = array[pos_smallest];
                array[pos_smallest] = aux;
            }
        }
    }

    int main(){
        int length_array = 7;
        int array [] = {58, -5, 10, 8, 78 ,234, 43};

        cout << "Original Array" << endl;
        show(array, length_array);

        sort(array, length_array);

        cout << "Sorted Array" << endl;
        show(array, length_array);
    }
}

```

8.2 Sorting InsertionSort InsertionSortPYTHON

```

def show(array):
    for element in array:
        print(element, end = " ")
    print("")

def sort(array, length_array):
    for index in range(1,length_array):
        key = array[index]
        index_aux = index -1
        while index_aux >=0 and array[index_aux]>key:
            array[index_aux+1] = array[index_aux]
            index_aux = index_aux -1
        array[index_aux+1]=key

def main():
    array = [50, 885, 1 , -8 , 54 , 2, 54, 0]
    print("Original array")
    show(array)
    print("Sorted array")
    sort(array, len(array))
    print(array)
main()

```

8.3 Sorting InsertionSort InsertionSortCPP

```

#include <iostream>

using namespace std;

void show(int array[], int length_array);
void sort(int array[], int length_array);

void show(int array[], int length_array){
    for (int index = 0; index < length_array; index ++){
        cout << array[index] << " ";
        cout<< endl;
    }
}

void sort(int array[], int length_array){
    for (int index = 1; index < length_array; index ++){
        int key = array[index];
        int index_aux = index - 1;
        while (index_aux >= 0 && array[index_aux] > key){
            array[index_aux + 1 ] = array[index_aux];
            index_aux = index_aux -1;
        }
        array[index_aux + 1] = key;
    }
}

int main(){
    int length_array = 8;
    int array[] = {50, 885, 1 , -8 , 54 , 2, 54, 0};
    show(array, length_array);
    sort(array, length_array);
    show(array, length_array);
}

```

8.4 Sorting BubbleSort Bubble

```

#include <bits/stdc++.h>
#define forn(i,j,k) for (int i=j; i<k; i++)
using namespace std;

typedef long long ll;

inline void sort(ll *arr, int size){
    forn(i,0,size-1)
        forn(j,0, size-i-1)
            if (arr[j] > arr[j+1])
                swap(arr[j], arr[j+1]);
}

int main(){
    ios::sync_with_stdio(false);
    cin.tie(0);

    int size =8;
    ll *data = new ll[size];

    forn(i, 0, size)
        scanf("%lld", &data[i]);

    sort(data, size);

    forn(i, 0, size)
        printf("%lld ",data[i]);

    return 0;
}

```

8.5 Sorting MergeSort MergeSortCPP

```
#include <stdio.h>
#include <iostream>
#include <vector>

using namespace std;

void show(int array[], int length_array);
void sort(int array[], int pos_ini, int pos_final);
void merge(int array[], int pos_ini, int pos_mid,int pos_final);

void show(int array [], int length_array){
    int index = 0;
    // cout<< "size : "<< array.size() <<endl;
    while(index<length_array){
        printf("%d ",array[index]);
        index = index +1;
    }
    printf("\n");
}

void sort(int array[], int pos_ini, int pos_final){

    /*In this condition the len of the array
    left and right half arrays will be
    of 1 element both */
    if(pos_final > pos_ini){
        //first calc the half point
        int pos_mid = (pos_ini+pos_final)/2;

        sort(array, pos_ini, pos_mid);
        sort(array, pos_mid +1, pos_final);
        merge(array, pos_ini, pos_mid, pos_final);
    }
}

void merge( int array[], int pos_ini, int pos_mid,int pos_final){

    int size_left = pos_mid - pos_ini + 1;
    int size_right = pos_final - pos_mid;

    /* create temp arrays */
    int lefthalf[size_left], righthalf[size_right];

    for (int i = 0; i < size_left; i++)
        lefthalf[i] = array[pos_ini + i];
    for (int j = 0; j < size_right; j++)
        righthalf[j] = array[pos_mid + 1+ j];

    int index_right_half = 0;
    int index_left_half = 0;
    int index = pos_ini;
    while (index_left_half < size_left && index_right_half <
        size_right) {
        if(lefthalf[index_left_half] <= righthalf[index_right_half]
        ){
            array[index] = lefthalf[index_left_half];
            index_left_half = index_left_half +1;
        }else{
            array[index] = righthalf[index_right_half];
            index_right_half = index_right_half+1;
        }
        index = index +1;
    }
}
```

```

    }
    //Copy the remaining elements if there is any
    while( index_left_half < size_left){
        array[index] = lefthalf[index_left_half];
        index_left_half = index_left_half +1;
        index = index +1;
    }
    while( index_right_half < size_right){
        array[index] = righthalf[index_right_half];
        index_right_half = index_right_half +1;
        index = index +1;
    }
}

int main(){
    int array[] = {-10, 37, 98 , 0 ,12, 192, 5};
    int length_array = sizeof(array)/ sizeof(array[0]);
    show(array, length_array);
    sort(array, 0, length_array -1);
    show(array, length_array);
}

```

8.6 Sorting MergeSort MergeSortPY

```
def merge_sort(array):
    ##Stop when the len of the array is less or equal than one
    if len(array)>1:
        #Calc the mid of the array
        mid = len(array) // 2 # // mean integer division

        #Create two arrays left and right
        lefthalf = array[:mid]
        print(lefthalf)

        righthalf = array[mid:]
        print(righthalf)

        #Divide the subarrays left and right
        merge_sort(lefthalf)
        merge_sort(righthalf)

        ##I send the array as a argument to change the same array
        and not another
        merge(lefthalf, righthalf, array)

def merge(lefthalf, righthalf, array):
    index_array_left=0
    index_array_right=0
    k=0
    while index_array_left < len(lefthalf) and \
        index_array_right < len(righthalf):

        if lefthalf[index_array_left] < \
            righthalf[index_array_right]:

            #assign the less to the new array
            array[k]=lefthalf[index_array_left]

            ""As the less was an element in the lefthalf we dont
            need to compare this again so we increase the index
            of the left array""
            index_array_left=index_array_left+1

        else:
            array[k]=righthalf[index_array_right]

            ""As the less was an element in the righthalf we dont
            need to compare this again so we increase the index
            of the left array""
```

```

        index_array_right=index_array_right+1
        #It is necessary increase the pos of the original array
        k=k+1
##add the remaining elements
while index_array_left < len(lefthalf):
    array[k]=lefthalf[index_array_left]
    index_array_left=index_array_left+1
    k=k+1

while index_array_right < len(righthalf):
    array[k]=righthalf[index_array_right]
    index_array_right=index_array_right+1
    k=k+1

def main():
    array = [-10, 37, 98 , 0 ,12, 192, 5]
    print("Original Array")
    print(array)
    merge_sort(array)

    print("Sorted Array")
    print(array)
main()

```

8.7 Sorting StandardSort

```

#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
typedef vector < ll > vl;
int main(){
    vl data = {234234LL, 2322LL,1LL, -1LL, 3454LL};

    sort(data.begin(), data.end());

    for (int i=0; i< data.size(); i++)
        printf("%lld ", data[i]);
    return 0;
}

```

9 Strings

9.1 Strings Palindrome

```

#include <iostream>
#include <string>
using namespace std;
/*
* i,j positions letters in the word
*/
inline bool evaluate(string word, int i, int j){
    if (i >= j)
        return true;
    else if (word[i] != word[j])
        return false;
    return evaluate(word, i+1, j-1);
}

inline bool is_palindrome(string word){

```

```

    int length = word.length();
    if (length == 1)
        return true;
    return evaluate(word, 0, length-1);
}

int main(){
    string word = "anamariaaairamana";
    string word2 = "Thisssiss";
    cout << word << " ";
    cout << is_palindrome(word) << endl;
    cout << word2 << " ";
    cout << is_palindrome(word2) << endl;
    return 0;
}

```

9.2 Strings FunctionsOverChart

```

#include <bits/stdc++.h>
using namespace std;

int main(){
    char a = 'a';
    cout << (isalnum(a)?"true":"false") << endl;
    cout << (isalpha(a)?"true":"false") << endl;
    cout << (isblank(a)?"true":"false") << endl;
    cout << (isdigit(a)?"true":"false") << endl;
    cout << (islower(a)?"true":"false") << endl;
    cout << (ispunct(a)?"true":"false") << endl;
    cout << (isupper(a)?"true":"false") << endl;
    cout << (isxdigit(a)?"true":"false") << endl;
    cout << (char)tolower(a) << endl;
    cout << (char)toupper(a) << endl;
    return 0;
}

```

9.3 Strings Split

```

#include <bits/stdc++.h>
using namespace std;
/*
* Split by space
*/
int main(){
    string line;
    while(getline(cin, line)){
        stringstream ss;
        ss.str(line);
        string item;
        while (getline(ss, item, ' ')) {
            cout << item << endl;
        }
    }
    return 0;
}

```

9.4 Strings Regex

```

#include <iostream>
#include <iterator>
#include <regex>
#include <string>

```

```
using namespace std;
int main(){
    string s = "123daniel , jajaja, lol, 234234534, I am from
    Earth";
    regex tel("\\d{8},\\sI");
    auto words_begin = sregex_iterator(s.begin(), s.end(), tel);
    auto words_end = sregex_iterator();

    cout << "Found " << distance(words_begin, words_end)<< " words
    \n";

    const int N = 6;
    for (sregex_iterator i = words_begin; i != words_end; ++i) {
        smatch match = *i;
        string match_str = match.str();
        if (match_str.size() > N) {
            cout << " " << match_str << '\n';
        }
    }
    return 0;
}
```

10 Math

10.1 Math NumberTheory GCD_{LCM}

```
#include<cstdio>
using namespace std;

int gcd(int a, int b){
    if(b == 0) return a;
    return gcd(b, a % b);
}

int lcm(int n1, int n2){
    return (n1 * n2) / gcd(n1,n2);
}

int main(){
    int n1=2366, n2=273;
    printf("gcd(%ld, %ld) = %ld\n",
        n1, n2, gcd(n1,n2));
    return 0;
}
```

10.2 Math NumberTheory DivisorsCPP

```
#include <algorithm>
#include <math.h>
#include <set>
#include <stdio.h>
using namespace std;

typedef set<int> si;
/* Get the divisors of a number */
si divisores(int n) {
    si d;
    int r = sqrt(n);
```

```
for(int i = 1; i <= r; i++) {
    if(n % i == 0) {
        d.insert(i);
        d.insert(n / i);
    }
}
return d;
}

int main() {
    si divi = divisores(10);
    for (set<int>::iterator it=divi.begin();
        it!=divi.end(); ++it)
        printf("%d ", *it);
    printf("\n");
}
```

10.3 Math NumberTheory DivisorsPYTHON

```
import math
"""Get the divisors of a number"""
def listDivisors(n):
    divisors = set()
    lim = int(math.sqrt(n))

    for i in range(1, lim + 1):
        if n % i == 0:
            divisors.add(i)
            divisors.add(n // i)

    return divisors

def main():
    d = listDivisors(100)
    print(len(d))
    print(d)

main()
```

10.4 Math NumberTheory Josephus

```
//https://www.youtube.com/watch?v=uCsD3ZGzMgE
int j(int n, int k) {
    if (n == 1) return 0;
    if (n < k) return (j(n-1,k)+k)%n;
    int np = n - n/k;
    return k*((j(np,k)+np-n%k*np)%np) / (k-1);
}
```

10.5 Math Pow FastPow

```
#include <bits/stdc++.h>

using namespace std;

ll modular_pow(ll base, int exponent, ll modulus){
    ll result = 1;
    while (exponent > 0){
        /* if y is odd, multiply base with result */
        if (exponent & 1)
            result = (result * base) % modulus;
        /* exponent = exponent/2 */
        exponent = exponent >> 1;
    }
```

```

        /* base = base * base */
        base = (base * base) % modulus;
    }
    return result;
}

int main(){

}

```

10.6 Math NumberSystems ChangeBases

```

# coding=utf-8
""" CHANGE THE BASE OF A NUMBER
    ob -> origin base
    od -> destiny base
"""

chars = "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZ"

def changeBase(number, ob,od):
    if ob == 10:
        return tob(number, od)
    return tob(to10(number,ob),od)

""" FROM ANY BASE TO BASE 10
    b -> base of the number n
    pos -> location of a sub-number in n
"""
def to10(n, b, pos =0):
    if n == 0: return 0
    return (n % 10)*(b ** pos) + to10(n / 10, b, pos+1)

"""FROM TEN BASE TO ANOTHER BASE"""
def tob(n, b):
    if n == 0: return ""
    return tob(n // b, b) + chars[n % b]

def main():
    print ( tob(7,2))
    print ( tob(252,16))
    print ( tob(234,15))
    print ( to10(1000,2))
    print ( changeBase(111,2,10))
main()

```

11 Sequences

12 probability

13 Geometry

13.1 Geometry LineIntersect2

```

#include <iostream>
#include <stdio.h>
#include <vector>

using namespace std;

```

```

/*
 *BETTER VERSION
 * http://stackoverflow.com/questions/563198/how-do-you-detect-
 * where-two-line-segments-intersect
 */

typedef long double ld;
typedef struct point {
    ld x;
    ld y;
} point;

typedef vector < point > vp;

/*
 * i ---> is the intersection
 */
bool get_line_intersection(point p0, point p1, point p2, point p3,
    point i){
    ld s1_x, s1_y, s2_x, s2_y;
    point AB, DC;

    AB.x = p1.x - p0.x; AB.y = p1.y -p0.y;
    DC.x = p3.x - p2.x; DC.y = p3.y - p2.y;

    ld s, t;

    s = (-AB.y * (p0.x - p2.x) + AB.x * (p0.y - p2.y))
        / (-DC.x * AB.y + AB.x * DC.y);
    t = ( DC.x * (p0.y - p2.y) - DC.y * (p0.x - p2.x))
        / (-DC.x * AB.y + AB.x * DC.y);

    if (s >= 0 && s <= 1 && t >= 0 && t <= 1){
        // Collision detected
        i.x = p0.x + (t * AB.x);
        i.y = p0.y + (t * AB.y);
        cout << " x = " << i.x << " y= " << i.y << endl;
        return true;
    }

    return false; // No collision
}

int main(){
    vp p(4);
    point inter;

    //line 1
    p[0] = {0,1};
    p[1] = {2,3};

    //line 2
    p[2] = {3,0};
    p[3] = {0,3};

    bool is = get_line_intersection(p[0], p[1], p[2], p[3], inter)
    ;
    printf("%s\n", is ? "Las lineas chocan": " There is not
        collision");

    return 0;
}

```

13.2 Geometry PointInteriorBoundary

```
#include <iostream>
#include <algorithm>
#include <stdlib.h>      /* srand, rand */
#include <time.h>        /* time */
#include <vector>
#include <math.h>

#define magnitude(a) (sqrt(a.x*a.x + a.y*a.y))

using namespace std;
/*
 * This script helps to find if a point is inside, outside
 * or in the boundaries of a polygon
 */

typedef long double ld;

typedef struct point {
    ld x;
    ld y;
} point;

typedef struct vert {
    point o; //origin
    point d; //destiny
} vert;

typedef vector < point > verts;

/*
 * Check if a point is inside or outside of a figure
 */

/*Cross product*/
inline ld cross_product(point o, point d){
    ld cross = (o.x * d.y) - (o.y * d.x);
    return cross > 0 ? cross : cross * -1;
}

inline vert r2(point o, point d){
    return {o, d};
}

inline point r(point o, point d){
    return {d.x-o.x, d.y - o.y};
}

ld dist_to_point(point A, point B, point C){
    //First create vector AB and AC

    point AB = r(A,B);
    point AC = r(A,C);

    ld cross = cross_product(AB, AC);
    ld distance1 = cross / magnitude(AB);
    ld distance2 = cross / magnitude(AC);

    return min(distance1, distance2);
}
```

```
/*
 * i ----> is the intersection
 */

bool segments_intersect(vert v0, vert v1){
    point p0 = v0.o;
    point p1 = v0.d;
    point p2 = v1.o;
    point p3 = v1.d;
    point i;

    ld s1_x, s1_y, s2_x, s2_y;
    point AB, DC;

    AB.x = p1.x - p0.x; AB.y = p1.y - p0.y;
    DC.x = p3.x - p2.x; DC.y = p3.y - p2.y;

    ld s, t;

    s = (-AB.y * (p0.x - p2.x) + AB.x * (p0.y - p2.y)) / (-DC.x *
        AB.y + AB.x * DC.y);
    t = (DC.x * (p0.y - p2.y) - DC.y * (p0.x - p2.x)) / (-DC.x *
        AB.y + AB.x * DC.y);

    if (s >= 0 && s <= 1 && t >= 0 && t <= 1){
        // Collision detected
        i.x = p0.x + (t * AB.x);
        i.y = p0.y + (t * AB.y);
        // cout << " x = " << i.x << " y= " << i.y << endl;
        return true;
    }

    return false; // No collision
}

inline void test_point(verts v, point pun){
    int cant = v.size();

    /*
     * Create a imaginary point to create a ray between the point
     * and it.
     */

    point p;
    int cont = 0; // times that the point intersects
    p.x = rand() % 1000000 + 1;
    p.y = rand() % 1000000 + 1;

    if (cant > 0){
        for (int i = 0; i < cant; i++){
            if (dist_to_point(v[i], v[(i+1)%cant], pun) == 0){
                cout << "The point is in the boundaries" << endl;
            }
            if (segments_intersect(r2(v[i], v[(i+1)%cant]), r2(pun,
                p))){
                cont = cont + 1;
            }
        }
    }
    if (cont % 2 == 0){
        cout << "The point is an exterior point " << endl;
    } else {
        cout << "The point is an interior point " << endl;
    }
}
```



```

int main(){
    /*The vertex of the polygon*/
    verts v(3);
    v[0] = {0,0};
    v[1] = {10,0};
    v[2] = {0,10};

    /* Point to check the program */

    point p1 = {4,5};
    point p2 = {5,5};

    test_point( v, p1);
    test_point( v, p2);

    return 0;
}

```

13.3 Geometry PickTheorem

```

#include <stdio.h>
using namespace std;

/*
 * Pick's theorem is a useful method for determining the area of
 * any polygon whose
 * vertices are points on a lattice, a regularly spaced array of
 * points.
 */

typedef double d;

/*
 * b boundary point : a lattice point on the polygon including
 * vertices
 * i interior point : a lattice points on the polygon's interior
 * region
 */
d area_polygon(d b, d i){
    return (b/2) + i -1;
}

int main(){
    printf("%f",area_polygon(5,5));
    return 0;
}

```

13.4 Geometry EulerFormule

```

#include <stdio.h>
using namespace std;
typedef long long ll;

b is_a_polygon(ll V, ll E, ll F){
    return V - E + F == 2;
}

int main(){
    printf("%s\n",
        is_a_polygon(3, 34,5) ? "true" : "false");
    //This is a cube

```

```

printf("%s\n",
        is_a_polygon(8,12,6) ? "true" : "false");
return 0;
}

```

13.5 Geometry LineIntersect1

```

#include <iostream>
#include <algorithm>
#include <limits>

using namespace std;

typedef long double ld;
typedef pair < ld, ld> point;
const ld INF = 9000000000000000000;

typedef struct line{
    // vy(y) + vx (x) = c; vy = 1
    ld vy; //value y
    ld vx; //value x
    ld c; // value coeficient
    point origin; //In the case of a segment
    bool segment;
    point destiny; //In the case of a segment
} line;

inline ld det(line l1, line l2){
    ld dete = (l1.vx * l2.vy) - (l1.vy * l2.vx);
    return dete;
}

inline point intersect( line l1, line l2){
    //if det == 0 lines are parallel
    ld dete = det(l1,l2);
    if (dete != 0){
        //Apply crammer for compute the intersection
        ld x = ((l1.c * l2.vy) - (l2.c * l1.vy)) / dete;
        ld y = ((l1.vx * l2.c) - (l2.vx * l1.c)) / dete;
        return make_pair(x,y);
    }
    return make_pair(INF, INF);
}

/*
 *Return the negative slope
 */
inline ld slope(line l1){
    ld m = (l1.destiny.second - l1.origin.second) / ( l1.destiny.
        first - l1.origin.first);
    return -1* m;
}

/*
 * Compute the independent coeffiecient
 */
inline ld coefficient(line l1){
    //y -mx = b
    ld c = l1.origin.second + l1.vx*l1.origin.first;
    return c;
}

/*
 * Based on the intersection and the lines check if
 * the intersection is valid, checking the boundaries
 */

```

```

inline bool mintersect(point inter, line l1, line l2){
    ld x= inter.first;
    ld y= inter.second;

    if( x != INF ){
        if(l1.segment && l2.segment){
            if( x >= min(l1.origin.first, l1.destiny.first) &&
                x >= min(l2.origin.first, l2.destiny.first) &&
                x <= max(l2.origin.first, l2.destiny.first) &&
                x <= max(l1.origin.first, l1.destiny.first) &&
                y <= min(l1.origin.second, l1.destiny.second) &&
                y >= min(l2.origin.second, l2.destiny.second) &&
                y <= max(l2.origin.second, l2.destiny.second) &&
                y <= max(l1.origin.second, l1.destiny.second) ){

                cout << "x= " << x<< " y= " <<y <<endl;
                return true;
            }else{
                cout << "The lines does not collide";
                return false;
            }
        }else{
            cout << "x= " << x<< " y= " <<y <<endl;
            return true;
        }
    }else{
        cout<<"Lines are parallel \n";
        return false;
    }
}

int main(){
    line l1, l2;
    l1 = l2 = {}; //its valid only with -std=c++11

    l1.origin = make_pair(0,0);
    l1.destiny = make_pair(-2,2);
    l1.vx = slope(l1);
    l1.vy = 1;
    l1.segment =true;
    l1.c = coefficient(l1);

    l2.origin = make_pair(0,0);
    l2.destiny = make_pair(-3,2);
    l2.vx = slope(l2);
    l2.vy = 1;
    l2.segment = true;
    l2.c = coefficient(l2);

    point inter = intersect(l1, l2);

    mintersect(inter, l1, l2);
}

```

13.6 Geometry Line2Point

```

#include<iostream>
#include<vector>
#include<math.h>
#include<algorithm>

#define magnitude(x) (sqrt(x.first*x.first + x.second*x.second))

using namespace std;

```

```

typedef long double ld;
typedef pair< ld, ld> point;

/* Difference between two points */
inline point r(point o, point d){
    return make_pair(d.first-o.first, d.second - o.second) ;
}

/*Cross product*/
inline ld cross_product(point o, point d){
    ld cross = (o.first * d.second) - ( o.second * d.first);
    return cross>0? cross: cross * -1;
}

/*
*First find cross product
*/
ld distance(point A, point B, point C){
    //First create vector AB and AC
    point AB = r(A,B);
    point AC = r(A,C);

    ld cross = cross_product(AB, AC);
    ld distance1 = cross / magnitude(AB);
    ld distance2 = cross / magnitude(AC);

    return min(distance1, distance2);
}

/*
*Find the distance from the segment AB to C
*/

int main(){
    //Fast input and output
    ios::sync_with_stdio(false);
    cin.tie(NULL);

    point A,B,C;

    A = make_pair(0,0);
    B = make_pair(0,2);
    C = make_pair(5,0);

    cout << distance(A,B,C);
    return 0;
}

```

13.7 Geometry PolygonArea

```

#include <iostream>
#include <vector>
#define f first
#define s s

using namespace std;

typedef long double ld;
typedef pair<ld, ld> point;
typedef vector< point > polygon;

inline point r(point o, point d){
    return make_pair(d.f-o.f, d.s - o.s) ;
}

inline ld cross_product(point o, point d){
    ld cross = (o.f * d.s) - ( o.s * d.f);
    return cross > 0 ? cross : cross * -1;
}

```

```

inline ld area(polygon p){
    int num_points = p.size();
    ld area = 0;
    for (int i = 1; i < num_points - 1 ; i++){
        point l1 = r(p[0],p[i]);
        point l2 = r(p[0],p[i+1]);
        area += cross_product(l1,l2);
    }
    return area < 0 ?( -1 * area)/2:
        (area/2 );
}

int main(){
    //Fast input and output
    ios::sync_with_stdio(false);
    cin.tie(NULL);

    point A, B, C, D;
    A = make_pair(1,0);
    B = make_pair(2,1);
    C = make_pair(1,2);
    D = make_pair(0,1);

    polygon p(4);
    p[0] = A;
    p[1] = B;
    p[2] = C;
    p[3] = D;

    cout << area(p);

    return 0;
}

```

13.8 Geometry ConvexHull

```

#include <iostream>
#include <math.h>
#include <vector>

using namespace std;
/* CONVEX HULL: Minimum Convex Polygon
 * Convex hull is the smallest set of points that containss the
 * set X.
 */

/*
 * Steps for the algorithm
 * 1- loop through all of the points and find the most left point
 *   if there is a tie, pick the highest point
 * 2- from the most left we are going to use cross product for
 *   finding
 *   the further clockwise from the current possition
 * 3- If there is no colinear points the code is straightforward.
 */

typedef long double ld;
const ld INF = 9000000000000000000;
typedef struct point {
    ld x;
    ld y;
} point;

typedef vector< point > points;
#define magnitud(p) (sqrt(p.x * p.x + p.y * p.y))

```

```

#define crossproduct(a,b) (a.x * b.y - a.y * b.x)
#define dist(a,b) (sqrt(pow((b.x - a.x),2) + pow((b.y - a.y),2)))
/*
 * Return the index of the most left point
 */
inline int left_most(points p){
    int cant = p.size();
    if(cant > 0){
        int ref = 0;
        for( int i = 1; i < cant; i++){
            if (p[i].x < p[ref].x ){
                ref = i;
            }
        }
        return ref;
    }
    return -1;
}

/* Create a vector based on two points
 */
inline point cv(point a, point b){
    return {b.x - a.x, b.y - a.y};
}

/*
 * lm -> stands out the left most point
 * more_points -> if is true use as many points as possible
 *                  for the convex hull otherwise use as few
 *                  as possible
 */
inline void convex_hull(points p, int lm, bool more_points){
    int cant = p.size();
    vector< bool > used (cant, false);
    /*
     * Just to clarify
     */
    int start = lm;

    do
    {
        int n = -1;
        ld dist = more_points?INF:0;

        cout << "Left most is " << lm << ": x= " << p[lm].x << " y
            = " << p[lm].y << endl;

        for (int i = 0; i < cant ; i++){

            //Do not go back to the same point
            if (i == lm) continue;

            //Do not reuse
            if(used[i])continue;

            //Set N
            if ( n==-1) {
                n=i;
                continue; //if I do not put this continue, the
                           //program will do a cross product
                           //with the same line
            }

            ld cross = crossproduct(cv(p[i],p[lm]), cv(p[n],p[lm])
                );

```

```

    ld d = dist(p[i], p[lm]);
    if (cross < 0 ){ //This is the magic
        n = i;
        dist = d;
    }else if (cross == 0){
        //In this case, both N and X are in the
        //same direction. If more_points is true, pick
        the
        //closest one, otherwise pick the farthest one.
        if(more_points && d < dist){
            dist = d;
            n = i;
        }else if(!more_points && d > dist){
            dist = d;
            n = i;
        }
    }
}

lm = n; //change the most left;
used[lm] = true;
}while(start != lm);
}

int main(){
    ios::sync_with_stdio(false);
    cin.tie(NULL);

    points p(6);

    p[0] = {0,2};
    p[1] = {3,5};
    p[2] = {4,3};
    p[3] = {3,0};
    p[4] = {3,3};
    p[5] = {4,6};
    convex_hull(p, left_most(p), false);

    return 0;
}

```

13.9 Geometry CircleCenter

```

#include <bits/stdc++.h>

using namespace std;
// Constants
const double PI = acos(-1);
struct point {
    double x;
    double y;
    point (){}
    point (double _x, double _y){
        x = _x;
        y = _y;
    }
};

inline point get_center(point A, point B, point C){

    float yDelta_a = B.y - A.y;
    float xDelta_a = B.x - A.x;
    float yDelta_b = C.y - B.y;
    float xDelta_b = C.x - B.x;

    point center;

```

```

float aSlope = yDelta_a/xDelta_a;
float bSlope = yDelta_b/xDelta_b;

center.x = ( aSlope * bSlope * (A.y - C.y)
            + bSlope*(A.x + B.x)
            - aSlope*(B.x+C.x) )/(2* (bSlope-aSlope) );

center.y = -1*(center.x - (A.x+B.x)/2)/aSlope + (A.y+B.y)/2;
return center;
}

```

14 Arrays

14.1 Arrays PermutationJAVA

```

public class Permutation{

    public static void main(String[] args){
        int[] array={3,5,0};
        permute(0, array);
    }

    public static void swap(int [] array, int i, int j){
        int temp = array[i];
        array[i] = array[j];
        array[j] = temp;
    }

    public static void show(int[] input){
        for(int x: input){
            System.out.print(x);
        }
        System.out.println("");
    }

    public static void permute(int start, int[] input ) {
        if (start == input.length) {
            show(input);
            return;
        }
        for (int i = start; i < input.length; i++) {
            swap(input, i, start);
            permute(start + 1, input);
            swap(input, i, start);
        }
    }
}

```

14.2 Arrays Operations

```

from itertools import permutations, combinations

def pers(array):
    ps = permutations(array)
    for p in ps:
        print (p)

def combs(array, r=2):
    cmb = combinations(array, r)
    for c in cmb:
        print (c)

```

```
if __name__ == "__main__":
    pers([1,2,3,4,5])
    combs([1,2,3,4,5])
```

14.3 Arrays maximun_subarray_pproblemKadane

```
#include <bits/stdc++.h>
#define forn(i,j,k) for(int i=j; i<k; i++)
using namespace std;

typedef long long ll;

/*
 * Largest Sum Contiguous Subarray
 * Kadane Algorithm
 * Complexity O(n)
 */
inline ll get_max_sum(ll * data, int size){
    ll max_so_far= data[0];
    ll max_ending_here = data[0];
    forn(i, 1, size){
        max_ending_here = max(data[i], \
            data[i] + max_ending_here);
        max_so_far = max(max_so_far, max_ending_here);
    }
    return max_so_far;
}

int main(){
    //Faster input and output
    ios::sync_with_stdio(false);
    cin.tie(0);

    int size = 8;
    ll *data = new ll[size];

    forn(i, 0, size)
        scanf("%lld", &data[i]);

    ll res = get_max_sum(data, size);
    printf("The max sum that can be done with \n \
        Contiguous elements is: %lld \n", res);

    return 0;
}
```

14.4 Arrays MapFunctions

```
"""
    Apply different function over an array
"""

def square(num):
    return num ** 2

def cube(num):
    return num ** 3

def is_pair(num):
    return num % 2

functions = [square, cube, is_pair]

array = range(0,20)

for elemn in array:
```

```
value = map(lambda x: x(elemn), functions)
print (elemn, value)
```

14.5 Arrays Combination

```
"""
reference: http://www.geeksforgeeks.org/print-all-possible-
combinations-of-r-elements-in-a-given-array-of-size-n/
"""

def combination(array, data, start, end, index, r):
    if (index == r):
        print (data)
        return
    for i in range(start, end+1):
        """ "end-i+1 >= r-index" makes sure that
            including one element at index will
            make a combination with remaining
            elementsat remaining positions
        """
        if (end - i + 1 >= r - index):
            data[index] = array[i]
            combination(array, data, i+1, end, index + 1, r)

def get_combinations(array, r, n):
    combination(array, [0] * r, 0, n-1, 0, r)

if __name__ == "__main__":
    array = [0,1,2,3,4,5]
    r = 5
    n = len(array)
    get_combinations(array, r, n)
```

14.6 Arrays PermutationCPP

```
#include <stdio.h>
#include <algorithm>
#include <iterator>
#include <vector>

using namespace std;

typedef vector <int > vi;

inline void show(vi &data, int &size){
    for (int i=0; i<size; i++)
        printf("%d \t", data[i]);
    printf("\n");
}

inline void permutation(vi data, int size){
    sort(data.begin(), data.end());
    do {
        show(data, size);
    }while(next_permutation(data.begin(), data.end()));
    show(data, size);
}

int main(){
    int size = 3 ;
    int data[] = {1,4,-1};
    vi vals(begin(data), end(data));
    permutation(vals, size);
    return 0;
}
```

15 Graphs

15.1 Graphs Traverse DFSJAVA

```
import java.util.*;

public class DFS {

    public static void dfs(node start){
        ArrayDeque<node> s = new ArrayDeque<node>();
        s.push(start);
        while(s.isEmpty() == false){
            node top = s.pop();

            if(top.visited == false){
                top.visited = true;
                System.out.println("Visit " + top.name);
                ArrayList<node> n;
                n = top.neighbors;
                for (node a: n){
                    s.push(a);
                }
            }
        }

        public static void main(String args[]){
            node a = new node("A");
            node b = new node("B");
            node c = new node("C");
            node d = new node("D");

            ArrayList<node> la = new ArrayList<node>();
            la.add(b);
            la.add(c);
            ArrayList<node> lc = new ArrayList<node>();
            lc.add(d);

            a.neighbors = la;
            c.neighbors = lc;

            dfs(a);
        }

        class node {
            ArrayList<node> neighbors;
            String name;
            boolean visited;
            public node(String name){
                this.name = name;
                this.visited = false;
                this.neighbors = new ArrayList<node>();
            }
        }
    }
}
```

15.2 Graphs Traverse DFSPY

```
class node:
    def __init__(self,n):
```

```
        self.neighbors = []
        self.visited = False
        self.name = n

def dfs(start):
    stack = []
    stack.append(start)

    while (stack != []):
        top = stack.pop()

        if (top.visited == False):
            top.visited = True
            print(top.name)
            #In this part in the termination condition
            n = top.neighbors
            for i in n:
                stack.append(i)

a = node("a")
b = node("b")
c = node("c")
d = node("d")

a.neighbors = [b,c]
c.neighbors = [d]
dfs(a)
```

15.3 Graphs Traverse DFSCPP

```
#include <bits/stdc++.h>
#define NUM_NODES 20

using namespace std;
vector<int> g[NUM_NODES];
int vis[NUM_NODES];
enum {WHITE, GRAY, BLACK};
void dfs(int o){
    vis[o] = GRAY; //semi-visited
    for (int i = 0; i < g[o].size(); i++){
        int v = g[o][i];
        if (vis[v] == GRAY)
            cout << "There is a cycle. to " << o << endl;
        // visit neighbors
        else if (vis[v] == WHITE) dfs(v);
    }
    cout << o << endl;
    vis[o] = BLACK; //visited;
}

int main(){
    g[0].push_back(1);
    g[0].push_back(2);
    g[0].push_back(3);
    g[1].push_back(4);
    g[1].push_back(5);
    g[2].push_back(6);
    g[3].push_back(7);
    g[4].push_back(0);
    g[6].push_back(0);

    dfs(0);
    return 0;
}
```

15.4 Graphs BestPath DijkstraHeap

```
#include <iostream>
#include <queue>
#include <vector>
using namespace std;

#define forn(i,a) for (int i=0; i<a ; i++)
#define INF 2e7

struct edge{
    int to, weight;
    edge(){}
    edge(int _to, int _weight){
        to = _to;
        weight = _weight;
    }
    bool operator < (edge e) const {
        return weight > e.weight;
    }
};

typedef vector < edge > vve;
typedef vector < ve > vve;
typedef vector < int > vi;
typedef priority_queue< edge> pq;

inline void show(vve &adj, int nodes){
    forn(i,nodes){
        cout << " Node:" << i << endl;
        forn (j, adj[i].size()){
            cout << "\t" << adj[i][j].to << endl;
        }
    }
}

inline void dijkstra(vve &adj, int src, int num_nodes){
    vi dist = vi(num_nodes+1,INF);
    pq q;
    //by default
    q.push(edge(src,0));
    dist[src] = 0;
    //apply bfs
    while(!q.empty()){
        edge top = q.top();
        q.pop();
        int u = top.to;
        for(int i=0;i<adj[u].size();i++){
            int v = adj[u][i].to;
            if(dist[u] + adj[u][i].weight < dist[v]){
                dist[v] = dist[u] + adj[u][i].weight;
                q.push(edge(v,dist[v]));
            }
        }
    }
    //Show results of distances
    cout << "Distancias desde el origen ";
    cout << src << endl;
    forn(i, num_nodes){
        cout <<"Costo al nodo: " << i;
        cout << " ="<< dist[i] << endl;
    }
}

int main(){
    int nodes, vertex, from, to, weight;
    cin >> nodes >> vertex;
    vve adj(nodes);
```

```
//Read the connections
forn(i, vertex){
    cin >> from >> to >> weight;
    adj[from].push_back(edge(to, weight));
}
// show(adj, nodes);
int src = 1;
dijkstra(adj, src, nodes);
return 0;
}
```

15.5 Graphs BestPath Dijkstra

```
#include <stdio.h>
#include <limits.h>
#define V 9

inline int show_sol(int dist[], int n){
    printf("Vertex Distance from Source\n");
    for (int i = 0; i < V; i++){
        printf("%d \t %d\n", i, dist[i]);
    }
}

int min_dis(int dist[], bool is_set[]){
    int min = INT_MAX, min_index;
    for (int v = 0; v < V; v++){
        if (is_set[v] == false && dist[v] <= min){
            min = dist[v], min_index = v;
        }
    }
    return min_index;
}

inline void dijkstra(int graph[V][V], int src){
    int dist[V];
    bool is_set[V];
    for (int i = 0; i < V; i++){
        dist[i] = INT_MAX, is_set[i] = false;
    }
    dist[src] = 0;
    for (int count = 0; count < V-1; count++){
        int u = min_dis(dist, is_set);
        is_set[u] = true;

        for (int v = 0; v < V; v++){
            if (!is_set[v] && graph[u][v]
                && dist[u] != INT_MAX
                && dist[u]+graph[u][v] < dist[v])
                dist[v] = dist[u] + graph[u][v];
        }
    }
    show_sol(dist, V);
}

int main(){
    int graph[V][V] = {{0, 4, 0, 0, 0, 0, 0, 8, 0},
                        {4, 0, 8, 0, 0, 0, 0, 11, 0},
                        {0, 8, 0, 7, 0, 4, 0, 0, 2},
                        {0, 0, 7, 0, 9, 14, 0, 0, 0},
                        {0, 0, 0, 9, 0, 10, 0, 0, 0},
                        {0, 0, 4, 14, 10, 0, 2, 0, 0},
                        {0, 0, 0, 0, 0, 2, 0, 1, 6},
                        {8, 11, 0, 0, 0, 0, 1, 0, 7},
                        {0, 0, 2, 0, 0, 0, 6, 7, 0}};
```

```

    //distances from all points to 1
    dijkstra(graph, 1);
    return 0;
}

```

15.6 Graphs BestPath BellmanFord

```

#include <cstdio>
#include <vector>
#define f first
#define s second
#define pb push_back
using namespace std;

#define MAX 2e9

typedef vector<int> vi;
typedef pair<int, int> pii;
typedef vector<pii> vpii;
typedef vector<vpii> vvpvii;

void init(vi &distances, int s) {
    for(int i=0; i<distances.size(); i++)
        distances[i] = MAX;
    distances[s] = 0;
}

void bellman_ford(vvpvii &graph, vi &dist) {
    for(int i=0; i<graph.size() - 1; i++) {
        for(int u = 0; u < graph.size(); u++) {
            for(pii v : graph[u]) {
                dist[v.f] =
                    min(dist[v.f], v.s + dist[u]);
            }
        }
    }
}

int main() {
    vvpvii adjList(5);
    vi d(5);
    init(d, 0);
    adjList[0].pb({1, 6});
    adjList[0].pb({3, 7});
    adjList[1].pb({2, 5});
    adjList[1].pb({3, 8});
    adjList[1].pb({4, -4});
    adjList[2].pb({1, -2});
    adjList[3].pb({2, -3});
    adjList[3].pb({4, 9});
    adjList[4].pb({0, 2});
    adjList[4].pb({2, 7});

    bellman_ford(adjList, d);

    for(int i=0; i<d.size(); i++) {
        printf("%d ", d[i]);
    }
}

```

```

    printf("\n");
    return 0;
}

```

15.7 Graphs BestPath FloydWarshal

```

#include<iostream>
#include<stdio.h>
using namespace std;
/*
 * Floyd-Warshall gives us the shortest paths
 * from all sources to all target nodes.
 */
#define V 4 //number of vertex
#define INF 9999999

void print_sol(int dist[][V]){
    printf ("shortest distances \n");
    for (int i = 0; i < V; i++){
        for (int j = 0; j < V; j++){
            if (dist[i][j] == INF)
                printf ("%7s", "INF");
            else
                printf ("%7d", dist[i][j]);
        }
        printf ("\n");
    }
}

void floyd (int graph[][V]){
    int dist[V][V], i, j, k;
    for (i = 0; i < V; i++)
        for (j = 0; j < V; j++)
            dist[i][j] = graph[i][j];

    for (k = 0; k < V; k++){
        for (i = 0; i < V; i++){
            for (j = 0; j < V; j++){
                if (dist[i][k] + dist[k][j] < dist[i][j])
                    dist[i][j] = dist[i][k] + dist[k][j];
            }
        }
        print_sol(dist);
    }
}

int main(){
    int graph[V][V] = { {0, 5, INF, 10},
                        {INF, 0, 3, INF},
                        {INF, INF, 0, 1},
                        {INF, INF, INF, 0}
    };

    floyd(graph);
    return 0;
}

```