

AI-Assisted Parallelization of bzip2 Compression

Final Project — Parallel Programming, Spring 2026

Lin Ching-Yun, Hsieh Tien-Hua, Cheng Yu-Shiang
Department of Computer Science and Information Engineering
National Taiwan University
{b12902116, b11902088, b12902025}@ntu.edu.tw

Abstract—Data compression is a critical component of high-performance computing, with algorithms like bzip2 prized for their high compression ratios. bzip2 internally processes data in blocks, making it a potential candidate for parallelization. However, effectively parallelizing this process requires careful management of output ordering, synchronization overhead, and I/O bottlenecks. This paper explores the efficacy of Large Language Models (LLMs) in automating the parallelization of a sequential bzip2 compressor (pbzx). We evaluate an AI-assisted development workflow across three progressive stages of guidance: naive prompting, constraint-guided design, and profiling-guided optimization. By comparing these AI-generated implementations against a sequential pbzx baseline and two mature parallel references (lzip2 and pbzip2), we analyze how varying levels of system-level feedback impact the correctness, speedup, and parallel efficiency of AI-generated C code. Our results show that profiling-guided optimization achieves the best performance, reaching throughput parity with hand-optimized tools, while strict constraint-guided prompting inadvertently introduces structural bottlenecks.

Index Terms—Data compression, bzip2, parallel programming, LLM code generation, AI-assisted development, performance profiling

Project Category: ☒ A (Self-chosen topic) ☐ B (AI-agent code optimization)
--

I. INTRODUCTION

Large language models may help identify parallelizable components, generate multithreaded code, suggest pipeline designs, and optimize performance. However, AI may not fully understand the target machine, runtime behavior, synchronization costs, or the actual performance bottlenecks after parallelization. Therefore, we plan to guide AI using profiling results and system-level feedback.

The objective of this project is to explore different ways of using AI to assist in parallelizing a bzip2-like compression system, and to evaluate whether AI-generated or AI-assisted parallel versions can improve performance while preserving correctness. Rather than simply dividing blocks among threads, effective parallelization requires overcoming distinct challenges, such as managing I/O bottlenecks, minimizing lock contention, and maintaining strict output ordering. We contribute an evaluation of a multi-stage AI-agent workflow, demonstrating that shifting from naive generation to bottleneck-aware, profiling-driven prompting allows LLMs to successfully navigate the complexities of parallel code optimization.

II. BACKGROUND AND RELATED WORK

A. The bzip2 Algorithm

bzip2 processes data in independent blocks, so block-level parallelism is possible. Since different data blocks can be compressed independently, multiple blocks may be assigned to different worker threads and processed in parallel. In addition, block size may affect both compression ratio and parallel efficiency.

B. Existing Parallel bzip2 Implementations

Two mature open-source tools parallelize bzip2 compression and serve as external references in our evaluation.

1) *lzip2*: lzip2 is an algorithmically optimized reference: it emits byte-compatible .bz2 output but, unlike pbzx, does not link libbz2. It replaces bzip2’s comparison-based blocksort with its own libdivsufsort-style suffix-array BWT (divbwt), computing the identical transform with far less work, and parallelizes through a hand-built pthread pipeline rather than OpenMP fork/join. It was the fastest *per-core* implementation in our sweeps; profiling showed it to be branch-prediction-bound and already near the hardware ceiling, so we use it unmodified.

2) *pbzip2*: pbzip2 is the closest reference to our own design: like pbzx, it is a block-parallel front-end *on top of* stock libbz2, so it shares bzip2’s codec and thus the same per-core BWT cost and compression ratio. It differs only in how work is distributed — a hand-built POSIX-threads producer/worker/writer pipeline with order-preserving output, in place of pbzx’s OpenMP fork/join. It is, in effect, the hand-coded ancestor of the same block-parallel idea our AI-assisted versions express through OpenMP.

III. METHODOLOGY

Instead of only asking AI to “make the code faster,” we designed a structured three-stage workflow to guide the agent step by step. The project isolates the development of each AI-assisted implementation on dedicated Git branches stemming from the main baseline.

A. Sequential Baseline and AI-Agent Setup

To isolate the effects of our parallelization strategies, we start from pbzx, a custom C11 baseline that sequentially compresses blocks using vendored libbz2. All AI-assisted work is carried out by the Claude Code agent, which operates

autonomously within isolated Git worktrees — one per stage — branched from this baseline, keeping each implementation independent and reproducible.

B. Stage 1: Naive AI Parallelization

In the first stage, we provided the agent with the sequential bzip2 compression code and asked it to parallelize the program. The agent receives a minimal prompt without hints regarding the parallelization strategy. This stage tests whether AI can independently identify the parallelizable parts of the program.

C. Stage 2: Constraint-Guided AI Parallelization

In the second stage, we provided the agent with clearer design requirements. The agent is prompted to use block-level parallelism, assign unique block IDs, use worker threads to compress independently, and employ a writer thread to maintain original output order. The agent is also instructed to avoid race conditions and unnecessary global locks. This stage tests whether explicit system design constraints can help AI generate more correct and maintainable parallel code.

D. Stage 3: Profiling-Guided Optimization

In the third stage, we ran the AI-generated parallel version and collected profiling information, such as CPU utilization, runtime breakdown, I/O waiting time, lock contention, memory usage, thread idle time, and scalability under different thread counts. We fed this empirical bottleneck data back into the LLM context. This stage tests whether profiling feedback can help AI move from superficial code changes to bottleneck-driven optimization.

IV. EXPERIMENTAL SETUP

A. Hardware and Software Environment

The experiments were conducted on a dual-socket server running Ubuntu 24.04 Server, equipped with two Intel Xeon Platinum 8352V processors (Ice Lake architecture) operating at a 2.10 GHz base clock (up to 3.50 GHz turbo). The system provides a total of 72 physical cores (36 per socket) and 144 logical threads via Intel Hyper-Threading, partitioned into two NUMA nodes. The cache hierarchy consists of 48 KB L1d, 32 KB L1i, and 1.25 MB L2 cache per physical core, backed by a shared 54 MB L3 cache per socket, with support for AVX-512 instruction set extensions.

The target software environment utilizes C11 with pthreads or OpenMP, orchestrated by a Python-based benchmarking harness. Profiling data is gathered using hardware performance counters via `perf stat`, call-graph hotspots via `perf record`, and resource monitoring via `GNU /usr/bin/time -v`. We evaluate both system performance and AI effectiveness, defining success as achieving measurable parallel speedup while preserving byte-for-byte data integrity.

B. Workload and Benchmark Configuration

The primary workload for all benchmark sweeps is a ~ 1.08 GB file (1,082,774,528 bytes) produced by concatenating the Canterbury Corpus large reference tarball (11,162,624 bytes) 97 times, providing a realistic and compressible dataset. Against this input we swept thread counts $\{1, 2, 4, 8, 16, 32\}$ with block size 900 KB, compression level 9, and 3 repeats per configuration. Each AI-assisted stage was benchmarked in its own isolated Git worktree, and the lbzip2 and pbzip2 references were benchmarked on the same input and thread sweep.

C. Evaluation Metrics

The metrics tracked by the harness include:

- **Runtime:** Total compression time.
- **Throughput:** Input size divided by compression time, measured in MB/s.
- **Speedup:** Sequential runtime divided by parallel runtime.
- **Parallel Efficiency:** Speedup divided by number of threads.
- **Memory Usage:** Peak memory consumption.
- **Correctness:** Whether decompressed output matches the original file.

Performance improvements are quantified mathematically using the following standard definitions:

$$Speedup = \frac{T_{\text{sequential}}}{T_{\text{parallel}}} \quad (1)$$

$$Throughput = \frac{Input_Size}{T_{\text{compression}}} \quad (2)$$

V. RESULTS

All results below use the workload and benchmark configuration described in Section IV-B: the 1.08GB Canterbury Corpus input, the thread sweep $\{1, 2, 4, 8, 16, 32\}$, block size 900 KB, and compression level 9.

A. Correctness

All three AI-assisted stages produce **byte-identical compressed output** regardless of thread count, while lbzip2 differs only slightly in output size due to its block framing — not a correctness issue. Round-trip decompression against the original 1.08GB input passes for all five parallel implementations (the three AI-assisted stages plus the lbzip2 and pbzip2 references) at every thread count tested. This confirms that increasing thread count does not change the compressed output or break correctness for any of the three AI-generated parallel versions.

B. Runtime and Throughput

Table I reports mean compression time (seconds, averaged over 3 repeats) at each thread count.

In absolute terms, **Stage 3 (profiling-guided) is the fastest of the three AI-assisted stages at every thread count**, and is competitive with — even marginally faster than — the mature lbzip2 reference at high thread counts (3.03s vs. 3.14s at 32

TABLE I
MEAN COMPRESSION TIME (S) ON THE 1.08GB INPUT

Threads	Stage 1 (naive)	Stage 2 (constrained)	Stage 3 (profiling)	lbzip2 (reference)	pbzip2 (reference)
1	80.84	81.77	78.72	67.90	81.13
2	40.63	40.62	39.43	34.51	41.33
4	20.80	20.74	20.02	17.58	20.89
8	10.53	10.50	10.23	9.10	10.75
16	5.52	5.50	5.36	4.96	5.89
32	3.06	3.49	3.03	3.14	3.79




Fig. 1. Compression time vs. thread count (log-log scale) for all five parallel implementations and the sequential baseline on the 1.08GB input.

threads). Stage 1 (naive) and Stage 2 (constraint-guided) are otherwise nearly indistinguishable through the middle of the sweep (within hundredths of a second at 2–16 threads); Stage 2 differs mainly at the two ends, with the highest single-threaded baseline (81.77s) and the weakest 32-thread time (3.49s, vs. 3.03–3.06s for Stage 1 and Stage 3) — a gap we trace to its synchronization design in Section VI-A. The second external reference, pbzip2, tracks the AI stages closely through 8 threads but falls behind from 16 threads onward, ending as the slowest implementation at 32 threads (3.79s).

Figure 2 shows the corresponding throughput curves, which mirror the runtime results: all five parallel implementations reach roughly 285–360 MB/s at 32 threads (Stage 3 highest at ≈ 359 MB/s, pbzip2 lowest at ≈ 286 MB/s), up from approximately 13–16 MB/s single-threaded.

C. Speedup

Table II reports speedup relative to each implementation’s own single-threaded time, and Figure 3 plots the same data against an ideal linear-speedup reference line.

All three AI-assisted stages — along with both external references (lbzip2 and pbzip2) — track the ideal linear-speedup line closely up to 16 threads ($\sim 2\times$, $\sim 4\times$, $\sim 8\times$, and ~ 14 – $15\times$ at each doubling), confirming that block-level parallelism is, as expected, embarrassingly parallel for a sufficiently large input (1,204 blocks at 900 KB each leaves ample work to keep 16 threads fed). Scaling tapers off at 32 threads for every




Fig. 2. Throughput (MB/s) vs. thread count for all five parallel implementations and the sequential baseline on the 1.08GB input.

TABLE II
SPEEDUP RELATIVE TO EACH IMPLEMENTATION’S OWN 1-THREAD
BASELINE

Threads	Stage 1 (naive)	Stage 2 (constrained)	Stage 3 (profiling)	lbzip2 (reference)	pbzip2 (reference)
1	1.00×	1.00×	1.00×	1.00×	1.00×
2	1.99×	2.01×	2.00×	1.97×	1.96×
4	3.89×	3.94×	3.93×	3.86×	3.88×
8	7.68×	7.79×	7.69×	7.46×	7.54×
16	14.64×	14.87×	14.69×	13.69×	13.77×
32	26.44×	23.43×	25.95×	21.64×	21.41×




Fig. 3. Speedup vs. thread count relative to each implementation’s own single-threaded baseline, with an ideal linear-speedup reference line (dashed).

implementation, plateauing around 21–26 $\times$ — even though the machine has many more physical cores available (72). This suggests that the bottleneck is not simply core count, but more likely a combination of memory bandwidth, NUMA effects, block granularity, and synchronization overhead, consistent with the profiling-stage finding that performance becomes limited by factors beyond software-level parallelism at high

thread counts.

Note that the two external references post the *lowest* relative speedups at 32 threads (pbzip2 21.41 $\times$, lbzip2 21.64 $\times$), but for different reasons. lbzip2’s is low purely because its single-threaded baseline is already the fastest of all (67.90s vs. 78–82s for the AI stages) — it has comparatively less headroom to climb. pbzip2, by contrast, starts from one of the slowest single-threaded baselines (81.13s) yet still scales the worst in absolute terms, so its low relative speedup reflects a genuine efficiency loss rather than a fast starting point. In **absolute** terms (Table I, Figure 1), lbzip2 remains competitive with, but does not dominate, the AI-assisted stages: Stage 1 and Stage 3 match or marginally beat it at 32 threads, while pbzip2 is the slowest implementation at that point (3.79s).

VI. DISCUSSION AND ANALYSIS

Contrary to the concern that naive AI prompting may produce incomplete or unsafe parallelization, Stage 1 already produces a correct, near-linearly-scaling OpenMP implementation. This suggests that block-level parallelization of pbzx is a sufficiently well-isolated transformation that even a minimally-guided agent can identify and implement it correctly.

A. Root-Cause Analysis of AI Failures (Stage 2)

Constraint-guided prompting (Stage 2) did not yield a clear runtime advantage over the naive version — if anything, its pthread-pipeline design carries more baseline overhead, resulting in the highest single-threaded time (81.77s) and the lowest absolute throughput at every thread count.

Root Cause: The explicit architectural constraints provided in the prompt (mandating unique block IDs, a separate writer thread, and strict output ordering) forced the AI into a heavy synchronization design. By constraining the agent’s architectural freedom, it inadvertently introduced excessive lock contention and high per-block malloc/free overhead. While its main benefits (ordered output via a writer thread, avoidance of global locks) met the original design goals regarding code structure and maintainability, the AI prioritized fulfilling the complex structural prompt over writing performant code. This demonstrates that over-constraining an LLM without providing empirical performance data can degrade baseline efficiency.

B. Success of Profiling Feedback

Profiling-guided optimization (Stage 3) delivered the expected payoff. Starting from the verified Stage 2 source, feeding back empirical bottleneck data (e.g., page-fault counts dropping from $\sim 674\text{K}$ to $\sim 181\text{K}$ after replacing per-block malloc/free with a per-thread bump-arena allocator) measurably reduced both the single-threaded baseline and the absolute runtime at every thread count. This direct system feedback was critical to making it the fastest of the three AI stages overall and putting it on par with lbzip2.

C. Limitations

Block size and thread count clearly affect speedup, as expected. Scaling is near-linear up to 16 threads and begins

to taper at 32 for all five parallel implementations alike, even though the machine has many more physical cores available. This suggests that the bottleneck is not simply core count, but may involve memory bandwidth, NUMA effects, block granularity, or synchronization overhead rather than an implementation-specific software bottleneck at the high end.

D. Additional Study: GPU Acceleration Inside libbz2

Beyond the CPU-side, block-level parallelization studied above, we conducted a follow-up experiment on a separate GPU branch to assess whether the *intra-block* stages of the standard libbz2 compression path could be offloaded to CUDA while preserving both the .bz2 format and the public API.

Profiling the single-threaded path showed that block sorting dominated runtime, making it the natural first GPU target. We implemented three optimizations: (i) offloading BZ2_blockSort to CUDA; (ii) generating the BWT last column directly on the GPU (BZ2_CUDA_BWT), so the subsequent MTF stage reads the transformed block sequentially rather than through the random-access block[ptr[i]-1] pattern; and (iii) a CUDA-assisted Huffman table optimization (BZ2_CUDA_HUFFMAN) that parallelizes per-group code-cost evaluation and frequency accumulation, while leaving final bitstream emission on the CPU to preserve the stream format.

Table III summarizes results on the 1 GB input. The CPU fallback required 85.80s, of which block sorting accounted for 60.97s (76.6%). Offloading sorting to CUDA cut total time to 33.44s; GPU-side BWT generation further reduced it to 29.95s (MTF: 11.88s $\rightarrow$ 8.11s); and CUDA-assisted Huffman optimization brought it to 27.04s (bitstream phase: 6.88s $\rightarrow$ 4.18s), a 3.17 $\times$ end-to-end speedup over the fallback.

TABLE III
GPU EXTENSION RESULTS ON THE 1 GB INPUT

Configuration	Time (s)	Bottleneck after
CPU fallback	85.80	CPU block sort
+ CUDA block sort	33.44	CPU MTF / Huffman
+ GPU BWT	29.95	CPU MTF / Huffman
+ CUDA Huffman	27.04	MTF (sequential)

Not all stages benefited. An experimental CUDA MTF prototype, which computed MTF ranks on the GPU while leaving zero-run compaction on the CPU, preserved correctness but degraded performance severely: total time rose to 136.14s, with the MTF phase alone reaching 114.41s. This reflects the inherently sequential nature of MTF—each symbol depends on the evolving recency ordering of earlier symbols—so a naive parallel backward-scan incurs excessive repeated work and poor memory behavior on the GPU. The prototype was therefore removed from the final path.

The broader lesson mirrors the CPU study: selective acceleration is most effective when applied to phases with strong data parallelism (block sorting, table optimization), whereas accelerating one dominant phase merely migrates the bottleneck to the next, inherently sequential stage (here, MTF and final encoding), which resists efficient GPU implementation.

VII. CONCLUSION

This study illustrates that while naive AI prompting can sometimes identify basic parallel loops successfully, strictly constraining the AI’s architectural design without performance context can introduce significant synchronization overhead. To mitigate the risk of the AI ignoring I/O bottlenecks, our pipeline strictly enforces the use of profiling tools to measure I/O waiting time and guide AI toward pipeline optimization. Profiling-guided feedback proved to be the most effective strategy, enabling the LLM to perform targeted root-cause analysis and optimize memory management, ultimately achieving throughput parity with established parallel compression tools.

ACKNOWLEDGMENT

REFERENCES

- [1] “Bzip2,” *Wikipedia*. [Online]. Available: <https://zh.wikipedia.org/zh-tw/Bzip2>. [Accessed: Jun. 13, 2026].
- [2] “pbzip2,” *Compression*. [Online]. Available: <https://compression.great-site.net/pbzip2/?i=1>. [Accessed: Jun. 13, 2026].
- [3] K. J. Nesbitt, “lbzip2: Parallel bzip2 utility,” GitHub repository. [Online]. Available: <https://github.com/kjn/lbzip2>. [Accessed: Jun. 13, 2026].
- [4] “bzip2,” GitLab repository. [Online]. Available: <https://gitlab.com/bzip2/bzip2>. [Accessed: Jun. 13, 2026].

APPENDIX A INPUT PROMPT

[Paste your input prompt here verbatim.]

APPENDIX B SYSTEM PROMPT

[Paste your system prompt here verbatim.]

APPENDIX C REPRESENTATIVE AGENT OUTPUT

[Paste representative agent output here.]

APPENDIX D CHANGES MADE TO THE AGENT

The Claude Code agent was provided isolated Git worktrees and varying levels of command permissions via per-branch CLAUDE.md files. In Stage 2, it was granted permissions to run machine-discovery commands (lscpu, free, nproc). In Stage 3, the agent context was dynamically updated to include raw outputs from perf stat and /usr/bin/time -v, granting it full visibility into its own execution bottlenecks.