

BandHiC

Weibing Wang

Dec 30, 2025

CONTENTS

1	Quick Start	11
1.1	Overview	11
1.2	Installation	11
1.2.1	Required Package	11
1.2.2	Option 1: Install via pip	12
1.2.3	Option 2: Install from source with conda	12
1.2.4	Optional dependency for .hic file support: hic-straw	12
1.2.4.1	Method 1: Install via pip	12
1.2.4.2	Method 2: Install via Conda	13
1.2.4.3	Upstream installation guide	13
1.3	What is BandHiC?	13
1.3.1	Data structure of BandHiC	13
1.3.2	Functions of BandHiC	14
2	Tutorials	15
2.1	Prerequisites	15
2.2	Import bandhic package	15
2.3	Initialize a band_hic_matrix object	16
2.4	Load or save a band_hic_matrix object	16
2.5	Construct a band_hic_matrix object	16
2.6	Indexing on band_hic_matrix	17
2.7	Masking	18
2.8	Universal functions (ufunc)	19
2.9	Other Array Functions	20
3	API Reference	23
3.1	band_hic_matrix Class	23
3.1.1	Class Overview and Initialization	24
3.1.2	Masking Methods	27
3.1.2.1	bandhic.band_hic_matrix.init_mask	27
3.1.2.2	bandhic.band_hic_matrix.add_mask	28
3.1.2.3	bandhic.band_hic_matrix.get_mask	28
3.1.2.4	bandhic.band_hic_matrix.unmask	29
3.1.2.5	bandhic.band_hic_matrix.drop_mask	29
3.1.2.6	bandhic.band_hic_matrix.add_mask_row_col	30
3.1.2.7	bandhic.band_hic_matrix.get_mask_row_col	31
3.1.2.8	bandhic.band_hic_matrix.drop_mask_row_col	31
3.1.2.9	bandhic.band_hic_matrix.clear_mask	31
3.1.2.10	bandhic.band_hic_matrix.count_masked	32
3.1.2.11	bandhic.band_hic_matrix.count_unmasked	32

3.1.2.12	bandhic.band_hic_matrix.count_in_band_masked	32
3.1.2.13	bandhic.band_hic_matrix.count_out_band_masked	33
3.1.2.14	bandhic.band_hic_matrix.count_in_band	33
3.1.2.15	bandhic.band_hic_matrix.count_out_band	34
3.1.3	Data Indexing and Modification	34
3.1.3.1	bandhic.band_hic_matrix.__getitem__	35
3.1.3.2	bandhic.band_hic_matrix.__setitem__	37
3.1.3.3	bandhic.band_hic_matrix.get_values	39
3.1.3.4	bandhic.band_hic_matrix.set_values	39
3.1.3.5	bandhic.band_hic_matrix.diag	40
3.1.3.6	bandhic.band_hic_matrix.set_diag	41
3.1.3.7	bandhic.band_hic_matrix.extract_row	41
3.1.3.8	bandhic.band_hic_matrix.__iter__	42
3.1.3.9	bandhic.band_hic_matrix.iterwindows	42
3.1.3.10	bandhic.band_hic_matrix.iterrows	43
3.1.3.11	bandhic.band_hic_matrix.itercols	43
3.1.3.12	bandhic.band_hic_matrix.filled	44
3.1.3.13	bandhic.band_hic_matrix.clip	45
3.1.4	Data Reduction and Normalization	45
3.1.4.1	bandhic.band_hic_matrix.min	46
3.1.4.2	bandhic.band_hic_matrix.max	47
3.1.4.3	bandhic.band_hic_matrix.sum	48
3.1.4.4	bandhic.band_hic_matrix.mean	48
3.1.4.5	bandhic.band_hic_matrix.std	49
3.1.4.6	bandhic.band_hic_matrix.var	50
3.1.4.7	bandhic.band_hic_matrix.prod	50
3.1.4.8	bandhic.band_hic_matrix.ptp	51
3.1.4.9	bandhic.band_hic_matrix.all	52
3.1.4.10	bandhic.band_hic_matrix.any	52
3.1.4.11	bandhic.band_hic_matrix.normalize	53
3.1.5	Vectorized Computation Methods	53
3.1.5.1	bandhic.band_hic_matrix.absolute	55
3.1.5.2	bandhic.band_hic_matrix.add	56
3.1.5.3	bandhic.band_hic_matrix.arccos	56
3.1.5.4	bandhic.band_hic_matrix.arccosh	57
3.1.5.5	bandhic.band_hic_matrix.arcsin	57
3.1.5.6	bandhic.band_hic_matrix.arcsinh	58
3.1.5.7	bandhic.band_hic_matrix.arctan	58
3.1.5.8	bandhic.band_hic_matrix.arctan2	59
3.1.5.9	bandhic.band_hic_matrix.arctanh	60
3.1.5.10	bandhic.band_hic_matrix.bitwise_and	60
3.1.5.11	bandhic.band_hic_matrix.bitwise_or	61
3.1.5.12	bandhic.band_hic_matrix.bitwise_xor	61
3.1.5.13	bandhic.band_hic_matrix.cbRT	62
3.1.5.14	bandhic.band_hic_matrix.conj	62
3.1.5.15	bandhic.band_hic_matrix.conjugate	63
3.1.5.16	bandhic.band_hic_matrix.cos	63
3.1.5.17	bandhic.band_hic_matrix.cosh	64
3.1.5.18	bandhic.band_hic_matrix.deg2rad	64
3.1.5.19	bandhic.band_hic_matrix.degrees	65
3.1.5.20	bandhic.band_hic_matrix.divide	65
3.1.5.21	bandhic.band_hic_matrix.divmod	66
3.1.5.22	bandhic.band_hic_matrix.equal	67
3.1.5.23	bandhic.band_hic_matrix.exp	67

3.1.5.24	bandhic.band_hic_matrix.exp2	68
3.1.5.25	bandhic.band_hic_matrix.expm1	68
3.1.5.26	bandhic.band_hic_matrix.fabs	69
3.1.5.27	bandhic.band_hic_matrix.float_power	69
3.1.5.28	bandhic.band_hic_matrix.floor_divide	70
3.1.5.29	bandhic.band_hic_matrix.fmod	70
3.1.5.30	bandhic.band_hic_matrix.gcd	71
3.1.5.31	bandhic.band_hic_matrix.greater	72
3.1.5.32	bandhic.band_hic_matrix.greater_equal	72
3.1.5.33	bandhic.band_hic_matrix.heaviside	73
3.1.5.34	bandhic.band_hic_matrix.hypot	73
3.1.5.35	bandhic.band_hic_matrix.invert	74
3.1.5.36	bandhic.band_hic_matrix.lcm	74
3.1.5.37	bandhic.band_hic_matrix.left_shift	75
3.1.5.38	bandhic.band_hic_matrix.less	76
3.1.5.39	bandhic.band_hic_matrix.less_equal	76
3.1.5.40	bandhic.band_hic_matrix.log	77
3.1.5.41	bandhic.band_hic_matrix.log1p	77
3.1.5.42	bandhic.band_hic_matrix.log2	78
3.1.5.43	bandhic.band_hic_matrix.log10	78
3.1.5.44	bandhic.band_hic_matrix.logaddexp	79
3.1.5.45	bandhic.band_hic_matrix.logaddexp2	79
3.1.5.46	bandhic.band_hic_matrix.logical_and	80
3.1.5.47	bandhic.band_hic_matrix.logical_or	80
3.1.5.48	bandhic.band_hic_matrix.logical_xor	81
3.1.5.49	bandhic.band_hic_matrix.maximum	82
3.1.5.50	bandhic.band_hic_matrix.minimum	82
3.1.5.51	bandhic.band_hic_matrix.mod	83
3.1.5.52	bandhic.band_hic_matrix.multiply	83
3.1.5.53	bandhic.band_hic_matrix.negative	84
3.1.5.54	bandhic.band_hic_matrix.not_equal	84
3.1.5.55	bandhic.band_hic_matrix.positive	85
3.1.5.56	bandhic.band_hic_matrix.power	86
3.1.5.57	bandhic.band_hic_matrix.rad2deg	86
3.1.5.58	bandhic.band_hic_matrix.radians	87
3.1.5.59	bandhic.band_hic_matrix.reciprocal	87
3.1.5.60	bandhic.band_hic_matrix.remainder	88
3.1.5.61	bandhic.band_hic_matrix.right_shift	88
3.1.5.62	bandhic.band_hic_matrix rint	89
3.1.5.63	bandhic.band_hic_matrix.sign	89
3.1.5.64	bandhic.band_hic_matrix.sin	90
3.1.5.65	bandhic.band_hic_matrix.sinh	90
3.1.5.66	bandhic.band_hic_matrix.sqrt	91
3.1.5.67	bandhic.band_hic_matrix.square	91
3.1.5.68	bandhic.band_hic_matrix.subtract	92
3.1.5.69	bandhic.band_hic_matrix.tan	92
3.1.5.70	bandhic.band_hic_matrix.tanh	93
3.1.5.71	bandhic.band_hic_matrix.true_divide	93
3.1.6	Data Type Conversion and Representation	94
3.1.6.1	bandhic.band_hic_matrix.todense	94
3.1.6.2	bandhic.band_hic_matrix.tocoo	95
3.1.6.3	bandhic.band_hic_matrix.tocsr	95
3.1.6.4	bandhic.band_hic_matrix.copy	96
3.1.6.5	bandhic.band_hic_matrix.astype	96

3.1.6.6	bandhic.band_hic_matrix.__repr__	97
3.1.6.7	bandhic.band_hic_matrix.__str__	97
3.1.6.8	bandhic.band_hic_matrix.__array__	97
3.1.6.9	bandhic.band_hic_matrix.__array_priority__	98
3.1.7	Other Methods	98
3.1.7.1	bandhic.band_hic_matrix.memory_usage	98
3.1.7.2	bandhic.band_hic_matrix.__len__	99
3.1.7.3	bandhic.band_hic_matrix.__hash__	99
3.1.7.4	bandhic.band_hic_matrix.__bool__	100
3.1.7.5	bandhic.band_hic_matrix.dump	100
3.2	Creation Functions	100
3.2.1	bandhic.ones	101
3.2.2	bandhic.zeros	101
3.2.3	bandhic.eye	102
3.2.4	bandhic.full	102
3.2.5	bandhic.ones_like	103
3.2.6	bandhic.zeros_like	103
3.2.7	bandhic.eye_like	104
3.2.8	bandhic.full_like	104
3.3	Input/Output Functions	105
3.3.1	bandhic.save_npz	105
3.3.2	bandhic.load_npz	106
3.3.3	bandhic.straw_chr	106
3.3.4	bandhic.straw_all_chrs	107
3.3.5	bandhic.cooler_chr	108
3.3.6	bandhic.cooler_all_chrs	109
3.4	Vectorized operations for BandHiC matrices	109
3.4.1	bandhic.absolute	111
3.4.2	bandhic.add	112
3.4.3	bandhic.arccos	112
3.4.4	bandhic.arccosh	113
3.4.5	bandhic.arcsin	113
3.4.6	bandhic.arcsinh	114
3.4.7	bandhic.arctan	115
3.4.8	bandhic.arctan2	115
3.4.9	bandhic.arctanh	116
3.4.10	bandhic.bitwise_and	116
3.4.11	bandhic.bitwise_or	117
3.4.12	bandhic.bitwise_xor	117
3.4.13	bandhic.cbrt	118
3.4.14	bandhic.conj	119
3.4.15	bandhic.conjugate	119
3.4.16	bandhic.cos	120
3.4.17	bandhic.cosh	120
3.4.18	bandhic.deg2rad	121
3.4.19	bandhic.degrees	121
3.4.20	bandhic.divide	122
3.4.21	bandhic.divmod	122
3.4.22	bandhic.equal	123
3.4.23	bandhic.exp	124
3.4.24	bandhic.exp2	124
3.4.25	bandhic.expm1	125
3.4.26	bandhic.fabs	125
3.4.27	bandhic.float_power	126

3.4.28	bandhic.floor_divide	126
3.4.29	bandhic.fmod	127
3.4.30	bandhic.gcd	128
3.4.31	bandhic.greater	128
3.4.32	bandhic.greater_equal	129
3.4.33	bandhic.heaviside	129
3.4.34	bandhic.hypot	130
3.4.35	bandhic.invert	131
3.4.36	bandhic.lcm	131
3.4.37	bandhic.left_shift	132
3.4.38	bandhic.less	132
3.4.39	bandhic.less_equal	133
3.4.40	bandhic.log	134
3.4.41	bandhic.log1p	134
3.4.42	bandhic.log2	135
3.4.43	bandhic.log10	135
3.4.44	bandhic.logaddexp	136
3.4.45	bandhic.logaddexp2	136
3.4.46	bandhic.logical_and	137
3.4.47	bandhic.logical_or	138
3.4.48	bandhic.logical_xor	138
3.4.49	bandhic.maximum	139
3.4.50	bandhic.minimum	139
3.4.51	bandhic.mod	140
3.4.52	bandhic.multiply	141
3.4.53	bandhic.negative	141
3.4.54	bandhic.not_equal	142
3.4.55	bandhic.positive	142
3.4.56	bandhic.power	143
3.4.57	bandhic.rad2deg	143
3.4.58	bandhic.radians	144
3.4.59	bandhic.reciprocal	144
3.4.60	bandhic.remainder	145
3.4.61	bandhic.right_shift	146
3.4.62	bandhic rint	146
3.4.63	bandhic.sign	147
3.4.64	bandhic.sin	147
3.4.65	bandhic.sinh	148
3.4.66	bandhic.sqrt	148
3.4.67	bandhic.square	149
3.4.68	bandhic.subtract	149
3.4.69	bandhic.tan	150
3.4.70	bandhic.tanh	150
3.4.71	bandhic.true_divide	151
3.5	Data Reduction and Normalization	151
3.5.1	bandhic.min	152
3.5.2	bandhic.max	152
3.5.3	bandhic.sum	152
3.5.4	bandhic.mean	152
3.5.5	bandhic.std	153
3.5.6	bandhic.var	153
3.5.7	bandhic.prod	153
3.5.8	bandhic.ptp	153
3.5.9	bandhic.all	153

3.5.10	bandhic.any	153
3.5.11	bandhic.clip	154
3.5.12	bandhic.normalize	154
3.6	Other Functions	154
3.6.1	bandhic.matrix_equal	154
3.6.2	bandhic.assert_band_matrix_equal	155
3.6.3	bandhic.compute_bin_bias	155
3.6.4	bandhic.call_tad	156
3.6.5	bandhic.topdom	156
3.6.6	bandhic.apa	157
3.6.7	bandhic.hiccups	158
3.6.8	bandhic.load_norm_vector_from_hic	159
3.6.9	bandhic.load_norm_vector_from_cooler	159
3.6.10	bandhic.scc	159
4	Indices and Tables	161
	Index	163

Version: 0.1.9

Welcome to the BandHiC documentation!

This documentation provides a comprehensive guide to the BandHiC library, including its features, installation instructions, and API reference. It is designed to help you efficiently store and manipulate Hi-C contact matrices in a banded form, enabling NumPy-compatible operations, matrix masking, diagonal reduction, file I/O, and domain-level interaction analysis.

If you have any questions, please contact us:

Author: Wang Weibing

Email: wangweibing@xidian.edu.cn

Useful links: [PDF Download](#) | [Website](#) | [PyPI](#) | [GitHub](#)

QUICK START

This section shows basic usage of the **BandHiC** package, including installation and a brief introduction to its features.

1.1 Overview

BandHiC is a Python package for efficient storage, manipulation, and analysis of Hi-C matrices using a banded matrix representation.

BandHiC adopts a banded storage scheme that stores only a configurable diagonal bandwidth of the dense Hi-C contact matrices. This design can reduce memory usage by up to 99% compared to dense matrices, while still supporting fast random access and user-friendly indexing operations.

Main features include:

- Efficient storage of Hi-C matrices using a banded representation.
- Fast random access and indexing operations.
- Support for flexible masking of missing values, outliers, and unmappable regions.
- Vectorized operations optimized with NumPy for high performance.
- Scalable for ultra-high-resolution Hi-C data analysis.

1.2 Installation

1.2.1 Required Package

BandHiC can be installed on Linux-like systems and requires the following dependencies:

1. python $\geq$ 3.11
2. numpy $\geq$ 2.3
3. pandas $\geq$ 2.3
4. scipy $\geq$ 1.16
5. cooler $\geq$ 0.10
6. hic_straw $\geq$ 1.3
7. joblib $\geq$ 1.2
8. numba $\geq$ 0.59

There are two recommended ways to install **BandHiC**:

1.2.2 Option 1: Install via pip

If you already have Python ≥ 3.11 installed:

```
pip install bandhic
```

If the installation fails due to dependency issues, please manually install the dependencies and then rerun the above command.

1.2.3 Option 2: Install from source with conda

1. Clone the repository

```
git clone https://github.com/xdwbb/BandHiC-Master.git  
cd BandHiC-Master
```

2. Create the environment and activate it

```
conda env create -f environment.yml  
conda activate bandhic
```

3. Install BandHiC

```
pip install .
```

1.2.4 Optional dependency for .hic file support: hic-straw

Support for reading .hic format Hi-C data relies on the third-party package **hic-straw**, which is **not installed automatically** with BandHiC.

If you do **not** need to read .hic files, you can ignore this dependency and use BandHiC normally.

If you **do** need .hic support, please install hic-straw manually using one of the following methods.

1.2.4.1 Method 1: Install via pip

```
pip install hic-straw
```

Note that hic-straw includes native C/C++ extensions. Installation via pip may require a compatible compiler toolchain and system libraries (e.g. libcurl development headers).

1.2.4.2 Method 2: Install via Conda

```
conda install -c bioconda hic-straw
```

Using Conda provides prebuilt binaries on many platforms and avoids local compilation issues.

1.2.4.3 Upstream installation guide

For detailed, system-specific installation instructions, please refer to the official *straw* repository maintained by the Aiden Lab:

<https://github.com/aidenlab/straw>

1.3 What is BandHiC?




Fig. 1.1: Data structure of BandHiC. Schematic illustration of converting a dense symmetric matrix A into a banded representation consisting of a data matrix D , an element-wise mask matrix M , a row/column mask matrix X , and a default value d for out-of-band entries. Diagonal elements from A are reorganized into columns of D ; M marks missing or outlier entries; X indicates masked rows or columns.

1.3.1 Data structure of BandHiC

To address the growing memory demands posed by high-resolution Hi-C data, we introduce `band_hic_matrix`, the core class implemented in the BandHiC package. For a Hi-C contact matrix $A \in \mathbb{R}^{n \times n}$ at resolution r , `band_hic_matrix` retains only the diagonals within a user-defined bandwidth k , yielding a compact representation $D \in \mathbb{R}^{n \times k}$. This format ensures that each column in D corresponds to a fixed diagonal of A , such that the mapping $A[i, j] = D[i, j - i]$ holds for $|i - j| \leq k$.

The memory efficiency achieved by this strategy is substantial. When $k \ll n$, the memory footprint of `band_hic_matrix` is reduced from $\mathcal{O}(n^2)$ to $\mathcal{O}(nk)$. For example, assuming a resolution of 1 kb and a bandwidth of 2 Mb ($k = 200$), the representation of chromosome 1 of the human genome (~249 Mb) requires 3.7 GB of memory, less than 1% of the memory required by the dense matrix (~461.9 GB). This compression enables the use of high-resolution Hi-C data on commodity hardware without sacrificing random access efficiency.

To further enhance flexibility of usage, `band_hic_matrix` integrates an optional two-tier masking mechanism. The element-wise mask matrix $M \in \{0, 1\}^{n \times k}$ allows users to selectively ignore missing or outlier contacts, enabling robust statistical estimation on unmasked subsets. Additionally, a bin-level mask $X \in \{0, 1\}^n$ supports the exclusion of entire rows or columns, which is particularly useful for removing repetitive genomic regions devoid of a valid Hi-C signal. These masking features facilitate downstream tasks such as the estimation of average contact intensity at given distances, while confirming statistical validity.

Lastly, a scalar default value d is defined to fill in the undefined entries of A not covered by the band matrix D . This default is typically set to 0, consistent with the assumption that long-range interactions are negligibly sparse. It also ensures that reconstruction of the full matrix A (if required) can be achieved seamlessly by combining D , M , X , and d . Overall, `band_hic_matrix` provides an efficient, flexible data structure for scalable Hi-C data analysis.

1.3.2 Functions of BandHiC

A key feature of `band_hic_matrix` is its direct coordinate mapping between the banded matrix B and the full dense matrix A . For any pair of genomic loci (i, j) satisfying the band constraint $|i - j| \leq k$, the interaction frequency $A[i, j]$ can be accessed in constant time via $D[i, j - i]$. This structure ensures random access in $\mathcal{O}(1)$ time, which is critical for performance-sensitive Hi-C analyses, particularly when memory constraints prohibit the use of fully dense matrices. Data access in `band_hic_matrix` is fully consistent with that of a dense matrix, as each entry is accessed via $B[i, j] = D[i, j - i] = A[i, j]$, allowing users to interact with `band_hic_matrix` objects as if they were dense matrices without needing to consider the underlying implementation.

Owing to this random-access capability, `band_hic_matrix` supports NumPy-like indexing semantics, including slicing, boolean indexing, and fancy indexing. This design allows users to easily query local chromatin contacts. For instance, a slice operation such as `B[i:j, i:j]` retrieves a banded submatrix. Combined with the `todense` operation, this enables reconstruction of the dense submatrix for downstream analysis or visualization.

In addition to flexible data access, `band_hic_matrix` also supports a wide range of numerical operations, including element-wise arithmetic operations and reduction operations. These operations are implemented using NumPy for efficiency. Standard reduction operations such as `sum`, `min`, and `max` are supported along conventional axes (rows or columns), as well as along the diagonal axis, which is particularly useful in summarizing interaction intensities by genomic distance. This feature facilitates common Hi-C analyses such as distance-decay profiling.

Taken together, `band_hic_matrix` combines the memory efficiency of a banded storage model with the expressiveness of NumPy's interface. By mimicking both NumPy's `ndarray` and `MaskedArray` behaviors, it provides an intuitive and powerful interface for users, substantially lowering the barrier to adoption and promoting integration into existing Hi-C data analysis workflows.

TUTORIALS

This section provides detailed tutorials on how to use the **BandHiC** package effectively.

- *Prerequisites*
- *Import bandhic package*
- *Initialize a band_hic_matrix object*
- *Load or save a band_hic_matrix object*
- *Construct a band_hic_matrix object*
- *Indexing on band_hic_matrix*
- *Masking*
- *Universal functions (ufunc)*
- *Other Array Functions*

2.1 Prerequisites

BandHiC can serve as an alternative to the NumPy package when managing and manipulating Hi-C data, aiming to address the issue of excessive memory usage caused by storing dense matrices using NumPy's `ndarray`. At the same time, BandHiC supports masking operations similar to NumPy's `ma.MaskedArray` module, with enhancements tailored for Hi-C data.

Users can leverage their experience with NumPy when using the BandHiC package, so it is recommended that users have some basic knowledge of NumPy. A link to NumPy is provided below: <https://numpy.org>

2.2 Import bandhic package

```
>>> import bandhic as bh
```

2.3 Initialize a band_hic_matrix object

Initialize from a SciPy coo_matrix object:

```
>>> import bandhic as bh
>>> import numpy as np
>>> from scipy.sparse import coo_matrix
>>> coo = coo_matrix(([1, 2, 3], ([0, 1, 2], [0, 1, 2])), shape=(3,3))
>>> mat1 = bh.band_hic_matrix(coo, diag_num=2)
```

Initialize from a tuple (data, (row, col)):

```
>>> mat2 = bh.band_hic_matrix(([4, 5, 6], ([0, 1, 2], [2, 1, 0])), diag_num=1)
```

Initialize from a full dense array, only upper-triangular part is stored, lower part is symmetrized:

```
>>> arr = np.arange(16).reshape(4,4)
>>> mat3 = bh.band_hic_matrix(arr, diag_num=3)
```

2.4 Load or save a band_hic_matrix object

```
>>> bh.save_npz('./sample.npz', mat)
>>> mat = bh.load_npz('./sample.npz')
```

Load from .hic file:

```
>>> mat = bh.straw_chr('sample.hic',
                      'chr1',
                      resolution=10000,
                      diag_num=200
                      )
```

Load from .mcool file:

```
>>> mat = bh.cooler_chr('sample.mcool',
                       'chr1',
                       diag_num=200
                       resolution=10000,
                       )
```

2.5 Construct a band_hic_matrix object

Create a band_hic_matrix object filled with zeros.

```
>>> mat1 = bh.zeros((5, 5), diag_num=3, dtype=float)
```

Create a band_hic_matrix object filled with ones.

```
>>> mat2 = bh.ones((5, 5), diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object filled as an identity matrix.

```
>>> mat3 = bh.eye((5, 5), diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object filled with a specified value.

```
>>> mat4 = bh.full((5, 5), fill_value=0.1, diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object matching another matrix, filled with zeros.

```
>>> mat5 = bh.zeros_like(mat1, diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object matching another matrix, filled with ones.

```
>>> mat6 = bh.ones_like(mat1, diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object matching another matrix, filled as an identity matrix.

```
>>> mat7 = bh.eye_like(mat1, diag_num=3, dtype=float)
```

Create a `band_hic_matrix` object matching another matrix, filled with a specified value.

```
>>> mat8 = bh.full_like(mat1, fill_value=0.1, diag_num=3, dtype=float)
```

2.6 Indexing on `band_hic_matrix`

First, we create a `band_hic_matrix` object:

```
>>> import numpy as np
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(16).reshape(4,4), diag_num=2)
```

Single-element access (scalar)

```
>>> mat[1, 2]
6
```

Masked element returns masked

```
>>> mat2 = bh.band_hic_matrix(np.eye(4), dtype=int, diag_num=2, mask=([0],[1]))
>>> mat2[0, 1]
masked
```

Square submatrix via two-slice indexing returns `band_hic_matrix`

```
>>> sub = mat[1:3, 1:3]
>>> isinstance(sub, bh.band_hic_matrix)
True
```

Single-axis slice returns `band_hic_matrix` for square region

```
>>> sub2 = mat[0:2] # equivalent to mat[0:2, 0:2]
>>> isinstance(sub2, bh.band_hic_matrix)
True
```

Fancy indexing returns ndarray or MaskedArray

```
>>> arr = mat[[0,2,3], [1,2,0]]
>>> isinstance(arr, np.ndarray)
True

>>> mat.add_mask([0,1],[1,2]) # Add mask to some entries
>>> masked_arr = mat[[0,1], [1,2]]
>>> isinstance(masked_arr, np.ma.MaskedArray)
True
```

Boolean indexing with band_hic_matrix

```
>>> mat3 = bh.band_hic_matrix(np.eye(4), diag_num=2, mask=([0,1],[1,2]))
>>> bool_mask = mat3 > 0 # Create a boolean mask
>>> result = mat3[bool_mask] # Use boolean mask for indexing
>>> isinstance(result, np.ma.MaskedArray)
True
>>> result
masked_array(data=[1.0, 1.0, 1.0, 1.0],
             mask=[False, False, False, False],
             fill_value=0.0)
```

2.7 Masking

Add item-wise mask:

```
>>> mat.add_mask([0, 1], [1, 2])
```

Add row/column mask:

```
>>> mask = np.array([True, False, False])
>>> mat.add_mask_row_col(mask)
```

Remove mask for specified indices.

```
>>> mat.unmask(( [0], [1] ))
```

Remove all item-wise mask and row/column mask.

```
>>> mat.unmask()
```

Remove all item-wise mask and row/column mask.

```
>>> mat.clear_mask()
```

Drop all item-wise mask but preserve all row/column mask.

```
>>> mat.drop_mask()
```

Drop all row/column mask.

```
>>> mat.drop_mask_row_col()
```

Access masked *band_hic_matrix* will obtain *np.ma.MaskedArray* object:

```
>>> mat.add_mask([0, 1], [1, 2])
>>> masked_arr = mat[[0,1], [1,2]]
>>> isinstance(masked_arr, np.ma.MaskedArray)
True
```

2.8 Universal functions (ufunc)

Universal functions that BandHiC supports:

Function	Description	Function	Description
absolute	Absolute value	add	Element-wise addition
arccos	Inverse cosine	arccosh	Inverse hyperbolic cosine
arcsin	Inverse sine	arcsinh	Inverse hyperbolic sine
arctan	Inverse tangent	arctan2	Arctangent of y/x with quadrant
arctanh	Inverse hyperbolic tangent	bitwise_and	Element-wise bitwise AND
bitwise_or	Element-wise bitwise OR	bitwise_xor	Element-wise bitwise XOR
cbrt	Cube root	conj	Complex conjugate
conjugate	Alias for conj	cos	Cosine function
cosh	Hyperbolic cosine	deg2rad	Degrees to radians
degrees	Radians to degrees	divide	Element-wise division
divmod	Quotient and remainder	equal	Element-wise equality test
exp	Exponential	exp2	Base-2 exponential
expm1	$\exp(x) - 1$	fabs	Absolute value (float)
float_power	Floating-point power	floor_divide	Integer division (floor)
fmod	Modulo operation	gcd	Greatest common divisor
greater	Element-wise greater-than test	greater_equal	Greater-than or equal test
heaviside	Heaviside step function	hypot	Euclidean norm
invert	Bitwise inversion	lcm	Least common multiple
left_shift	Bitwise left shift	less	Element-wise less-than test
less_equal	Less-than or equal test	log	Natural logarithm
log1p	$\log(1 + x)$	log2	Base-2 logarithm
log10	Base-10 logarithm	logaddexp	$\log(\exp(x) + \exp(y))$
logaddexp2	Base-2 version of logaddexp	logical_and	Element-wise logical AND
logical_or	Element-wise logical OR	logical_xor	Element-wise logical XOR
maximum	Element-wise maximum	minimum	Element-wise minimum
mod	Remainder (modulo)	multiply	Element-wise multiplication
negative	Element-wise negation	not_equal	Element-wise inequality test
positive	Returns input unchanged	power	Raise to power
rad2deg	Radians to degrees	radians	Degrees to radians
reciprocal	Element-wise reciprocal	remainder	Modulo remainder
right_shift	Bitwise right shift	rint	Round to nearest integer
sign	Sign of input	sin	Sine function
sinh	Hyperbolic sine	sqrt	Square root
square	Square of input	subtract	Element-wise subtraction
tan	Tangent function	tanh	Hyperbolic tangent

continues on next page

Table 2.1 – continued from previous page

Function	Description	Function	Description
true_divide	Division that returns float		

BandHiC supports these universal functions, and they can be used in the following four ways:

1. As methods of the `band_hic_matrix` object:

When two `band_hic_matrix` objects are involved, their shape and `diag_num` must match

```
>>> mat3 = mat1.add(mat2)
>>> mat4 = mat1.less(mat2)
>>> mat5 = mat1.negative()
```

2. As functions of the BandHiC package

```
>>> mat3 = bh.add(mat1, mat2)
>>> mat4 = bh.less(mat1, mat2)
>>> mat5 = bh.negative(mat1)
```

3. Using mathematical operators:

```
>>> mat3 = mat1 + mat2
>>> mat4 = mat1 < mat2
>>> mat5 = - mat1
```

4. Calling NumPy's universal functions:

```
>>> mat3 = np.add(mat1, mat2)
>>> mat4 = np.less(mat1, mat2)
>>> mat5 = np.negative(mat1)
```

2.9 Other Array Functions

Function	Description
sum	Compute the sum of all elements along the specified axis
prod	Compute the product of all elements along the specified axis
min	Return the minimum value along the specified axis
max	Return the maximum value along the specified axis
mean	Compute the arithmetic mean along the specified axis
var	Compute the variance (average squared deviation)
std	Compute the standard deviation (square root of variance)
ptp	Compute the range (max - min) of values along the axis
all	Return True if all elements evaluate to True
any	Return True if any element evaluates to True
clip	Limit values to a specified min and max range

BandHiC supports these functions, and they can be used in the following three ways:

1. As methods of the `band_hic_matrix` object:

Compute the sum of all elements including out-of-band values filled with *default_value*.

```
>>> result0 = mat1.sum()
```

Compute the sum of all elements along the *row* axis

```
>>> result1 = mat1.sum(axis=0)
>>> result1 = mat1.sum(axis='row')
```

Compute the sum of all elements along the *diag* axis

```
>>> result2 = mat1.sum(axis='diag')
```

2. Calling BandHiC's functions:

```
>>> result0 = bh.sum(mat1)
>>> result1 = bh.sum(mat1, axis=0)
>>> result2 = bh.sum(mat1, axis='diag')
```

3. Calling NumPy's functions:

```
>>> result0 = np.sum(mat1)
>>> result1 = np.sum(mat1, axis=0)
>>> result2 = np.sum(mat1, axis='diag')
```


API REFERENCE

This page provides a full API overview of the BandHiC module, including the core `band_hic_matrix` class and its utilities.

The *bandhic* module defines data structures and utilities for efficiently storing and manipulating Hi-C contact matrices in a banded form. It enables NumPy-compatible operations, matrix masking, diagonal reduction, file I/O, and domain-level interaction analysis.

Core components:

- *band_hic_matrix*: A memory-efficient matrix class supporting banded Hi-C data.
- Utility functions: loaders (*cooler_chr*) and constructors (*ones*, *zeros*, etc.).

3.1 `band_hic_matrix` Class

The `band_hic_matrix` class is the core data structure in the BandHiC package, designed for efficient storage and manipulation of Hi-C contact matrices using a banded representation. It supports various operations similar to those in NumPy, while optimizing memory usage and performance.

- *Class Overview and Initialization*
- *Masking Methods*
- *Data Indexing and Modification*
- *Data Reduction and Normalization*
- *Vectorized Computation Methods*
- *Data Type Conversion and Representation*
- *Other Methods*

3.1.1 Class Overview and Initialization

```
class bandhic.band_hic_matrix(contacts, diag_num=1, mask_row_col=None, mask=None, dtype=None,  
                             default_value=0, band_data_input=False)
```

Symmetric banded matrix stored in upper-triangular format. This storage format is motivated by high-resolution Hi-C data characteristics:

1. Symmetry of contact maps.
2. Interaction frequency concentrated near the diagonal; long-range contacts are sparse (mostly zero).
3. Contact frequency decays sharply with genomic distance.

By storing only the main and a fixed number of super-diagonals as columns of a band matrix (diagonal-major storage: diagonal k stored in column k), we drastically reduce memory usage while enabling random access to Hi-C contacts. Additionally, `mask` and `mask_row_col` arrays track invalid or masked contacts to support downstream analysis.

Operations on this `band_hic_matrix` are as simple as on a `numpy.ndarray`; users can ignore these storage details.

This class stores only the main diagonal and up to $(\text{diag_num} - 1)$ super-diagonals, exploiting symmetry by mirroring values for lower-triangular access.

Parameters

- **contacts** (*Union[coo_array, coo_matrix, tuple, ndarray]*) –
- **diag_num** (*int*) –
- **mask_row_col** (*Optional[ndarray]*) –
- **mask** (*Optional[Tuple[ndarray, ndarray]]*) –
- **dtype** (*Optional[type]*) –
- **default_value** (*Union[int, float]*) –
- **band_data_input** (*bool*) –

shape

Shape of the original full Hi-C contact matrix (`bin_num, bin_num`), regardless of internal band storage format.

Type

tuple of int

dtype

Data type of the matrix elements, compatible with numpy dtypes.

Type

data-type

diag_num

Number of diagonals stored.

Type

int

bin_num

Number of bins (rows/columns) of the Hi-C matrix.

Type

int

data

Array of shape $(bin_num, diag_num)$ storing banded Hi-C data.

Type

ndarray

mask

Mask for individual invalid entries. Stored as a boolean ndarray of shape $(bin_num, diag_num)$ with the same shape as *data*.

Type

ndarray of bool or None

mask_row_col

Mask for entire rows and corresponding columns, indicating invalid bins. Stored as a boolean ndarray of shape $(bin_num,)$. For computational convenience, row/column masks are also applied to the *mask* array to track masked entries.

Type

ndarray of bool or None

default_value

Default value for out-of-band entries. Entries out of the banded region and not stored in the data array will be set to this value.

Type

scalar

Examples

```
>>> import bandhic as bh
>>> import numpy as np
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.shape
(4, 4)
```

```
__init__(contacts, diag_num=1, mask_row_col=None, mask=None, dtype=None, default_value=0,
         band_data_input=False)
```

Initialize a band_hic_matrix instance.

Parameters

- **contacts** (*{coo_array, coo_matrix, tuple, ndarray}*) – Input Hi-C data in COO format, tuple (data, (row, col)), full square array, or banded stored ndarray. For non-symmetric full arrays, only the upper-triangular part is used and the matrix is symmetrized. Full square arrays are not recommended for large matrices due to memory constraints.
- **diag_num** (*int, optional*) – Number of diagonals to store. Must be ≥ 1 and $\leq$ matrix dimension. Default is 1.
- **mask_row_col** (*ndarray of bool or indices, optional*) – Mask for invalid rows/columns. Can be specified as:
 - A boolean array of shape $(bin_num,)$ indicating which rows/columns to mask.
 - A list of indices to mask.Defaults to None (no masking).

- **mask** (*ndarray pair of (row_indices, col_indices), optional*) – Mask for invalid matrix entries. Can be specified as:
 - A tuple of two ndarray (row_indices, col_indices) listing positions to mask.
 Defaults to None (no masking).
- **dtype** (*data-type, optional*) – Desired numpy dtype; defaults to ‘contacts’ data dtype; compatible with numpy dtypes.
- **default_value** (*scalar, optional*) – Default value for unstored out-of-band entries. Default is 0.
- **band_data_input** (*bool, optional*) – If True, contacts is treated as precomputed band storage. Default is False.

Raises

ValueError – If contacts type is invalid, diag_num out of range, or array shape invalid.

Return type

None

Examples

Initialize from a SciPy COO matrix:

```
>>> import bandhic as bh
>>> import numpy as np
>>> from scipy.sparse import coo_matrix
>>> coo = coo_matrix(([1, 2, 3], ([0, 1, 2],[0, 1, 2])), shape=(3,3))
>>> mat1 = bh.band_hic_matrix(coo, diag_num=2)
>>> mat1.data.shape
(3, 2)
```

Initialize from a tuple (data, (row, col)):

```
>>> mat2 = bh.band_hic_matrix(([4, 5, 6], ([0, 1, 2],[2, 1, 0])), diag_num=1)
>>> mat2.data.shape
(3, 1)
```

Initialize from a full dense array, only upper-triangular part is stored, lower part is symmetrized:

```
>>> arr = np.arange(16).reshape(4,4)
>>> mat3 = bh.band_hic_matrix(arr, diag_num=3)
>>> mat3.data.shape
(4, 3)
```

Initialize with row/column mask, this masks entire rows and corresponding columns:

```
>>> mask = np.array([True, False, False, True])
>>> mat4 = bh.band_hic_matrix(arr, diag_num=2, mask_row_col=mask)
>>> mat4.mask_row_col
array([ True, False, False,  True])
```

mask_row_col is also supported as a list of indices:

```
>>> mat4 = bh.band_hic_matrix(arr, diag_num=2, mask_row_col=[0, 3])
>>> mat4.mask_row_col
array([ True, False, False,  True])
```

Initialize from precomputed banded storage:

```
>>> band = mat3.data.copy()
>>> mat5 = bh.band_hic_matrix(band, band_data_input=True)
>>> mat5.data.shape
(4, 3)
```

3.1.2 Masking Methods

These methods allow for the application and manipulation of masks within the matrix. Masks can be used to exclude or highlight specific parts of the matrix during computations.

<code>band_hic_matrix.init_mask()</code>	Initialize mask for invalid entries based on matrix shape.
<code>band_hic_matrix.add_mask(row_idx, col_idx)</code>	Add mask entries for specified indices.
<code>band_hic_matrix.get_mask()</code>	Get current mask array.
<code>band_hic_matrix.unmask([indices])</code>	Remove mask entries for specified indices or clear all.
<code>band_hic_matrix.drop_mask()</code>	Clear the current mask by entry-level, but retain the row/column mask.
<code>band_hic_matrix.add_mask_row_col(mask_row_col)</code>	Mask entire rows and corresponding columns.
<code>band_hic_matrix.get_mask_row_col()</code>	Get current row/column mask.
<code>band_hic_matrix.drop_mask_row_col()</code>	Clear the current row/column mask.
<code>band_hic_matrix.clear_mask()</code>	Clear all masks (both entry-level and row/column-level).
<code>band_hic_matrix.count_masked()</code>	Count the number of masked entries in the banded matrix.
<code>band_hic_matrix.count_unmasked()</code>	Count the number of unmasked entries in the banded matrix.
<code>band_hic_matrix.count_in_band_masked()</code>	Count the number of masked entries in the in-band region.
<code>band_hic_matrix.count_out_band_masked()</code>	Count the number of masked entries in the out-of-band region.
<code>band_hic_matrix.count_in_band()</code>	Count the number of valid entries in the in-band region.
<code>band_hic_matrix.count_out_band()</code>	Count the number of valid entries in the out-of-band region.

3.1.2.1 bandhic.band_hic_matrix.init_mask

`band_hic_matrix.init_mask()`

Initialize mask for invalid entries based on matrix shape.

Raises

ValueError – If mask is already initialized.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.init_mask()
```

3.1.2.2 bandhic.band_hic_matrix.add_mask

`band_hic_matrix.add_mask(row_idx, col_idx)`

Add mask entries for specified indices.

Parameters

- **row_idx** (*array-like of int*) – Row indices to mask.
- **col_idx** (*array-like of int*) – Column indices to mask.

Raises

ValueError – If `row_idx` and `col_idx` have different shapes.

Return type

None

Examples

```
>>> import bandhic as bh
>>> import numpy as np
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.add_mask([0, 1], [1, 2])
```

Return type

None

Parameters

- **row_idx** (*Union[Sequence[int], ndarray]*) –
- **col_idx** (*Union[Sequence[int], ndarray]*) –

3.1.2.3 bandhic.band_hic_matrix.get_mask

`band_hic_matrix.get_mask()`

Get current mask array.

Returns

Current mask array or None if no mask.

Return type

ndarray or None

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mask = mat.get_mask()
```

3.1.2.4 bandhic.band_hic_matrix.unmask

`band_hic_matrix.unmask(indices=None)`

Remove mask entries for specified indices or clear all.

Parameters

indices (*tuple of array-like or None*) – Tuple (row_idx, col_idx) to unmask, or None to clear all.

Raises

Warning – If no mask exists when trying to remove.

Return type

None

Notes

If *indices* is None, this will clear all masks (both entry-level and row/column), equivalent to *clear_mask()*.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> mat.unmask(( [0], [0] ))
>>> mat.unmask()
```

Return type

None

Parameters

indices (*Optional[Tuple[ndarray, ndarray]]*) –

3.1.2.5 bandhic.band_hic_matrix.drop_mask

`band_hic_matrix.drop_mask()`

Clear the current mask by entry-level, but retain the row/column mask.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2, mask=(np.array([[0, 1], [1, 0],
↪ 2]])))
>>> mat.drop_mask()
```

Notes

This method is useful when you want to keep the row/column mask but clear the entry-level mask. It will not affect the row/column mask, allowing you to maintain the masking of entire rows and columns.

Return type

None

3.1.2.6 bandhic.band_hic_matrix.add_mask_row_col

`band_hic_matrix.add_mask_row_col(mask_row_col)`

Mask entire rows and corresponding columns.

Parameters

mask_row_col (*array-like of int or bool*) – If boolean array of shape (bin_num,), True entries indicate rows/columns to mask. If integer array or sequence, treated as indices of rows/columns to mask.

Raises

ValueError – If integer indices are out of bounds.

Return type

None

Examples

```
>>> import bandhic as bh
>>> mask = np.array([True, False, False])
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> mat.add_mask_row_col(mask)
```

Return type

None

Parameters

mask_row_col (*Union[Sequence[int], Sequence[bool], ndarray, int]*) –

3.1.2.7 bandhic.band_hic_matrix.get_mask_row_col

`band_hic_matrix.get_mask_row_col()`

Get current row/column mask.

Returns

Current row/column mask or None if no mask.

Return type

ndarray or None

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mask_row_col = mat.get_mask_row_col()
```

3.1.2.8 bandhic.band_hic_matrix.drop_mask_row_col

`band_hic_matrix.drop_mask_row_col()`

Clear the current row/column mask.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.drop_mask_row_col()
```

3.1.2.9 bandhic.band_hic_matrix.clear_mask

`band_hic_matrix.clear_mask()`

Clear all masks (both entry-level and row/column-level).

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.clear_mask()
```

Return type

None

3.1.2.10 bandhic.band_hic_matrix.count_masked

`band_hic_matrix.count_masked()`

Count the number of masked entries in the banded matrix.

This counts the number of entries in the upper triangular part of the matrix, excluding the diagonal and valid entries.

Returns

Number of valid entries in the banded matrix.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_masked()
0
```

3.1.2.11 bandhic.band_hic_matrix.count_unmasked

`band_hic_matrix.count_unmasked()`

Count the number of unmasked entries in the banded matrix.

Returns

Number of unmasked entries in the banded matrix.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_unmasked()
16
```

3.1.2.12 bandhic.band_hic_matrix.count_in_band_masked

`band_hic_matrix.count_in_band_masked()`

Count the number of masked entries in the in-band region.

Returns

Number of masked entries in the in-band region.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_in_band_masked()
0
```

3.1.2.13 bandhic.band_hic_matrix.count_out_band_masked

`band_hic_matrix.count_out_band_masked()`

Count the number of masked entries in the out-of-band region.

Returns

Number of masked entries in the out-of-band region.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_out_band_masked()
0
```

3.1.2.14 bandhic.band_hic_matrix.count_in_band

`band_hic_matrix.count_in_band()`

Count the number of valid entries in the in-band region.

Returns

Number of valid entries in the in-band region.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_in_band()
10
```

3.1.2.15 bandhic.band_hic_matrix.count_out_band

`band_hic_matrix.count_out_band()`

Count the number of valid entries in the out-of-band region.

Returns

Number of valid entries in the out-of-band region.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2)
>>> mat.count_out_band()
6
```

3.1.3 Data Indexing and Modification

The following methods provide functionality to access, modify, and index the matrix data. These are essential for manipulating individual elements or subsets of the matrix.

<code>band_hic_matrix.__getitem__(index)</code>	Retrieve matrix entries or submatrix using NumPy-like indexing.
<code>band_hic_matrix.__setitem__(index, values)</code>	Assign values to matrix entries using NumPy-like indexing.
<code>band_hic_matrix.get_values(row_idx, col_idx)</code>	Retrieve values considering mask.
<code>band_hic_matrix.set_values(row_idx, col_idx, ...)</code>	Set values at specified row and column indices.
<code>band_hic_matrix.diag(k)</code>	Retrieve the k-th diagonal from the matrix.
<code>band_hic_matrix.set_diag(k, values)</code>	Set values in the k-th diagonal of the matrix.
<code>band_hic_matrix.extract_row(idx[, ...])</code>	Extract stored, unmasked band values for a given row or column.
<code>band_hic_matrix.__iter__()</code>	Iterate over diagonals of the matrix.
<code>band_hic_matrix.iterwindows(width[, step])</code>	Iterate over the diagonals of the matrix with a specified window size.
<code>band_hic_matrix.iterrows()</code>	Iterate over the rows of the band_hic_matrix object.
<code>band_hic_matrix.itercols()</code>	Iterate over the columns of the band_hic_matrix object.
<code>band_hic_matrix.filled([fill_value, copy])</code>	Fill masked entries in data with default value.
<code>band_hic_matrix.clip(min_val, max_val)</code>	Clip data values to given range.

3.1.3.1 `bandhic.band_hic_matrix.__getitem__`

`band_hic_matrix.__getitem__(index)`

Retrieve matrix entries or submatrix using NumPy-like indexing.

Supports:

- Integer indexing: `mat[i, j]` returns a single value.
- Slice indexing: `mat[i:j, i:j]` returns a `band_hic_matrix` for square slices.
- Single-axis slice: `mat[i:j]` returns a `band_hic_matrix` same as `mat[i:j, i:j]`.
- Fancy (array) indexing: `mat[[i1, i2], [j1, j2]]` returns an ndarray or MaskedArray according to *mask*.
- Mixed indexing: combinations of integer, slice, and array-like indices.
- Boolean indexing: ‘`band_hic_matrix`’ object with dtype *bool* can be used to index entries.

When both row and column indices specify the same slice (or a single slice is provided), a new `band_hic_matrix` representing that square submatrix is returned. New submatrix is the view of the original matrix, sharing the same data and mask. If the mask or data is altered in the submatrix, the original matrix will reflect those changes as well.

- If a single integer index is provided for both row and column, a scalar value is returned.
- If a mask is set, masked entries will return as *numpy.ma.masked* for scalars, or as a *numpy.ma.MaskedArray* for arrays.
- If a mask is not set, the scalar value is returned directly, or a *numpy.ndarray* for arrays.
- If a square slice is provided, a new `band_hic_matrix` is returned with the same diagonal number and shape as the original matrix.
- If a single slice is provided, it returns a `band_hic_matrix` with the same diagonal number and shape as the original matrix.
- If fancy indexing is used, it returns a *numpy.ndarray* or *numpy.ma.MaskedArray* depending on whether the mask is set.
- In all other cases, a *numpy.ndarray* (if no mask) or *numpy.ma.MaskedArray* (if mask present) is returned.

Parameters

index (*int*, *slice*, *band_hic_matrix*, *array-like of int*, or *tuple of these*)

– index expression for rows and columns. May be:

- A pair (*row_idx*, *col_idx*) of ints, slices, or array-like for mixed indexing.
- A single slice selecting a square region.
- A *band_hic_matrix* object with dtype of *bool* for boolean indexing.

Returns

- scalar : when both row and column are integer indices.
- *numpy.ndarray* : for fancy or mixed indexing without mask.
- *numpy.ma.MaskedArray* : for fancy or mixed indexing when mask is set.
- `band_hic_matrix` : for square slice results.

Return type

scalar or ndarray or MaskedArray or *band_hic_matrix*

Raises

ValueError – If a slice step is not 1, or if indices are out of bounds.

Examples

```
>>> import numpy as np
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(16).reshape(4,4), diag_num=2)
```

Single-element access (scalar)

```
>>> mat[1, 2]
6
```

Masked element returns masked

```
>>> mat2 = bh.band_hic_matrix(np.eye(4), dtype=int, diag_num=2, mask=([0],[1]))
>>> mat2[0, 1]
masked
```

Square submatrix via two-slice indexing returns band_hic_matrix

```
>>> sub = mat[1:3, 1:3]
>>> isinstance(sub, bh.band_hic_matrix)
True
```

Single-axis slice returns band_hic_matrix for square region

```
>>> sub2 = mat[0:2] # equivalent to mat[0:2, 0:2]
>>> isinstance(sub2, bh.band_hic_matrix)
True
```

Fancy indexing returns ndarray or MaskedArray

```
>>> arr = mat[[0,2,3], [1,2,0]]
>>> isinstance(arr, np.ndarray)
True
```

```
>>> mat.add_mask([0,1],[1,2]) # Add mask to some entries
>>> masked_arr = mat[[0,1], [1,2]]
>>> isinstance(masked_arr, np.ma.MaskedArray)
True
```

Boolean indexing with band_hic_matrix

```
>>> mat3 = bh.band_hic_matrix(np.eye(4), diag_num=2, mask=([0,1],[1,2]))
>>> bool_mask = mat3 > 0 # Create a boolean mask
>>> result = mat3[bool_mask] # Use boolean mask for indexing
>>> isinstance(result, np.ma.MaskedArray)
True
```

```
>>> result
masked_array(data=[1.0, 1.0, 1.0, 1.0],
```

(continues on next page)

```
mask=[False, False, False, False],
fill_value=0.0)
```

3.1.3.2 bandhic.band_hic_matrix.__setitem__

`band_hic_matrix.__setitem__(index, values)`

Assign values to matrix entries using NumPy-like indexing.

Parameters

- **index** (*int, tuple of (row_idx, col_idx), slice, or band_hic_matrix*) – Index expression for rows and columns. May be:
- **column.** (*- A single integer for both row and*) –
- **int** (*- A tuple of row and column indices (can be)*) –
- **slice** –
- **array-like).** (*or*) –
- **region.** (*- A single slice selecting a square*) –
- **indexing.** (*- A band_hic_matrix object with dtype of bool for boolean*) –
- **values** (*scalar or array-like*) – Values to assign. Can be a single scalar or an array-like object.

Raises

- **ValueError** – If index is a slice with step not equal to 1, or if indices exceed matrix dimensions.
- **TypeError** – If *values* is not a scalar or array-like object.
- **Supports:** –
 - - **Integer indexing** – `mat[i, j] = value` assigns to a single element.:
 - - **Slice indexing** – `mat[i:j, i:j] = array or scalar` assigns to a square submatrix.:
 - - **Single-axis slice** – `mat[i:j] = ...` is equivalent to `mat[i:j, i:j].:`
 - - **Fancy (array) indexing** – `mat[[i1, i2], [j1, j2]] = array or scalar` for scattered assignments.:
 - - **Mixed indexing** – combinations of integer, slice, and array-like indices.:
 - - **Boolean indexing** – boolean mask (another `band_hic_matrix` with `dtype=bool`) selects entries to set.:

Return type

None

Examples

```
>>> import bandhic as bh
>>> import numpy as np
>>> mat = bh.band_hic_matrix(np.zeros((4,4)), diag_num=2, dtype=int)
```

Single element assignment

```
>>> mat[1, 2] = 5
>>> mat[1, 2]
5
```

Slice assignment to square submatrix

```
>>> mat[0:2, 0:2] = [[1, 2], [2, 4]]
>>> mat[0:2, 0:2].todense()
array([[1, 2],
       [2, 4]])
```

Single-axis slice assignment (equivalent square slice)

```
>>> mat[2:4] = 0
>>> mat[2:4].todense()
array([[0, 0],
       [0, 0]])
```

Fancy indexing for scattered assignments

```
>>> mat[[0, 3], [1, 2]] = [7, 8]
>>> mat[0, 1], mat[3, 2]
(7, 8)
```

Boolean mask assignment

```
>>> mat2 = bh.band_hic_matrix(np.eye(4), diag_num=2, dtype=int)
>>> bool_mask = mat2 > 0
>>> mat2[bool_mask] = 9
>>> mat2.todense()
array([[9, 0, 0, 0],
       [0, 9, 0, 0],
       [0, 0, 9, 0],
       [0, 0, 0, 9]])
```

Notes

- Assigning to masked entries updates underlying data but does not automatically unmask.
- For multidimensional assignments, scalar values broadcast to all selected positions, while array values must match the number of targeted elements.
- If a boolean mask is used, it must be a *band_hic_matrix* with dtype *bool* and the same shape as the original matrix.
- If a single slice is provided, it behaves like `mat[i:j, i:j]` for square submatrices.

Return type

None

Parameters

- **index** (*Union[Tuple[Union[int, slice, ndarray, list], Union[int, slice, ndarray, list]], slice, band_hic_matrix*]) –
- **values** (*Union[Number, ndarray, list]*) –

3.1.3.3 bandhic.band_hic_matrix.get_values

`band_hic_matrix.get_values(row_idx, col_idx)`

Retrieve values considering mask.

Parameters

- **row_idx** (*array-like of int*) – Row indices.
- **col_idx** (*array-like of int*) – Column indices.

Returns

Retrieved values; masked entries yield masked results.

Return type

ndarray or MaskedArray

Raises

ValueError – If indices exceed matrix dimensions.

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat.get_values([0,1],[1,2])
array([1., 1.]
```

3.1.3.4 bandhic.band_hic_matrix.set_values

`band_hic_matrix.set_values(row_idx, col_idx, values)`

Set values at specified row and column indices.

Parameters

- **row_idx** (*array-like of int*) – Row indices where values will be set.
- **col_idx** (*array-like of int*) – Column indices where values will be set.
- **values** (*scalar or array-like*) – Values to assign.

Return type

None

Examples

```
>>> import bandhic as bh
>>> mat = bh.zeros((3,3), diag_num=2, dtype=int)
>>> mat.set_values([0,1], [1,2], [4,5])
>>> mat[0,1]
4
```

Notes

Writing to masked positions will update the underlying data but will not clear the mask.

Return type

None

Parameters

- **row_idx** (*ndarray*) –
- **col_idx** (*ndarray*) –
- **values** (*Union[Number, ndarray]*) –

3.1.3.5 bandhic.band_hic_matrix.diag

`band_hic_matrix.diag(k)`

Retrieve the *k*-th diagonal from the matrix.

Parameters

k (*int*) – The diagonal index to retrieve.

Returns

The *k*-th diagonal values; masked if mask is set.

Return type

ndarray or *MaskedArray*

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat.diag(1)
array([1., 1.])
```

3.1.3.6 bandhic.band_hic_matrix.set_diag

`band_hic_matrix.set_diag(k, values)`

Set values in the k-th diagonal of the matrix.

Parameters

- **k** (*int*) – The diagonal index to set.
- **values** (*array-like*) – The values to set in the diagonal.

Raises

ValueError – If k is out of range or values length mismatch.

Return type

None

Examples

```
>>> import bandhic as bh
>>> mat = bh.zeros((4,4), diag_num=3)
>>> mat.set_diag(1, [9,9,9])
>>> mat.diag(1)
array([9., 9., 9.]
```

Return type

None

Parameters

- **k** (*int*) –
- **values** (*Iterable[Any]*) –

3.1.3.7 bandhic.band_hic_matrix.extract_row

`band_hic_matrix.extract_row(idx, extract_out_of_band=True)`

Extract stored, unmasked band values for a given row or column.

Parameters

- **idx** (*int*) – Row (or column, due to symmetry) index for which to extract band values.
- **extract_out_of_band** (*bool, optional*) – If True, include out-of-band entries filled with *default_value* and masked if appropriate. If False (default), return only the stored band values.

Returns

If *extract_out_of_band=False*, a 1D array of length up to *diag_num* containing band values. If *extract_out_of_band=True*, a 1D array of length *bin_num* with all row/column values.

Return type

ndarray or MaskedArray

Raises

ValueError – If *idx* is outside the range [0, bin_num-1].

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.extract_row(0, extract_out_of_band=False)
array([0, 1])
>>> mat.extract_row(0)
array([0, 1, 0])
```

3.1.3.8 bandhic.band_hic_matrix.__iter__

`band_hic_matrix.__iter__()`

Iterate over diagonals of the matrix.

Yields

ndarray – Values of each diagonal.

Return type

Iterator[ndarray]

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> for band in mat:
...     print(band)
[1. 1. 1.]
[1. 1.]
```

Return type

Iterator[ndarray]

3.1.3.9 bandhic.band_hic_matrix.iterwindows

`band_hic_matrix.iterwindows(width, step=1)`

Iterate over the diagonals of the matrix with a specified window size.

Parameters

- **width** (*int*) – The size of the window to iterate over.
- **step** (*int, optional*) – Step size between windows. Default is 1.

Yields

band_hic_matrix – The values in the current window.

Return type

Iterator[band_hic_matrix]

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> for win in mat.iterwindows(2):
...     print(win)
band_hic_matrix(shape=(2, 2), diag_num=2, dtype=<class 'numpy.float64'>)
band_hic_matrix(shape=(2, 2), diag_num=2, dtype=<class 'numpy.float64'>)
```

Return type

Iterator[[band_hic_matrix](#)]

Parameters

- **width** (*int*) –
- **step** (*int*) –

3.1.3.10 bandhic.band_hic_matrix.iterrows

`band_hic_matrix.iterrows()`

Iterate over the rows of the `band_hic_matrix` object.

Yields

ndarray – The values in the current row.

Return type

Iterator[*ndarray*]

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> for row in mat.iterrows():
...     print(row)
[1.  1.  1.]
[1.  1.  1.]
[1.  1.  1.]
```

Return type

Iterator[*ndarray*]

3.1.3.11 bandhic.band_hic_matrix.itercols

`band_hic_matrix.itercols()`

Iterate over the columns of the `band_hic_matrix` object.

Yields

ndarray – The values in the current column.

Return type

Iterator[*ndarray*]

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> for col in mat.itercols():
...     print(col)
[1. 1. 1.]
[1. 1. 1.]
[1. 1. 1.]
```

Return type

Iterator[ndarray]

3.1.3.12 bandhic.band_hic_matrix.filled

`band_hic_matrix.filled(fill_value=None, copy=True)`

Fill masked entries in data with default value.

Parameters

- **fill_value** (*scalar*) – Value to assign to masked entries.
- **copy** (*bool*) –

Raises

ValueError – If no mask is initialized.

Return type

`band_hic_matrix`

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(4), diag_num=2, mask = ([0,1],[1,2]))
>>> mat.filled()
band_hic_matrix(shape=(4, 4), diag_num=2, dtype=float64)
```

Return type

`band_hic_matrix`

Parameters

- **fill_value** (*Optional[Union[int, float]]*) –
- **copy** (*bool*) –

3.1.3.13 bandhic.band_hic_matrix.clip

`band_hic_matrix.clip(min_val, max_val)`

Clip data values to given range.

Parameters

- **min_val** (*scalar*) –
- **max_val** (*scalar*) –

Return type

None

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat = mat.clip(0, 10)
```

Return type

None

Parameters

- **min_val** (*Number*) –
- **max_val** (*Number*) –

3.1.4 Data Reduction and Normalization

These methods enable various data reduction operations, such as summing, averaging, or aggregating matrix values along specific axes or dimensions.

<code>band_hic_matrix.min([axis])</code>	Compute the minimum value in the matrix or along a given axis.
<code>band_hic_matrix.max([axis])</code>	Compute the maximum value in the matrix or along a given axis.
<code>band_hic_matrix.sum([axis])</code>	Compute the sum of the values in the matrix or along a given axis.
<code>band_hic_matrix.mean([axis])</code>	Compute the mean value of the matrix or along a given axis.
<code>band_hic_matrix.std([axis])</code>	Compute the standard deviation of the values in the matrix or along a given axis.
<code>band_hic_matrix.var([axis])</code>	Compute the variance of the values in the matrix or along a given axis.
<code>band_hic_matrix.prod([axis])</code>	Compute the product of the values in the matrix or along a given axis.
<code>band_hic_matrix.ptp([axis])</code>	Compute the peak-to-peak (maximum - minimum) value of the matrix or along a given axis.
<code>band_hic_matrix.all([axis, banded_only])</code>	Test whether all (or any) array elements along a given axis evaluate to True.
<code>band_hic_matrix.any([axis, banded_only])</code>	Test whether all (or any) array elements along a given axis evaluate to True.
<code>band_hic_matrix.normalize([inplace])</code>	Normalize each diagonal of the matrix to have zero mean and unit variance.

3.1.4.1 bandhic.band_hic_matrix.min

`band_hic_matrix.min(axis=None)`

Compute the minimum value in the matrix or along a given axis.

Parameters

axis (*None, int, or {'row', 'col', 'diag'}, optional*) – Axis along which to compute the minimum:

- None: compute over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Minimum value(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.min() # global minimum
0
>>> mat.min(axis='row')
array([0, 1, 0])
```

3.1.4.2 bandhic.band_hic_matrix.max

`band_hic_matrix.max(axis=None)`

Compute the maximum value in the matrix or along a given axis.

Parameters

axis (*None*, *int*, or *{'row','col','diag'}*, optional) – Axis along which to compute the maximum:

- *None*: compute over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is *None*.

Returns

Maximum value(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.max() # global maximum
8
>>> mat.max(axis='row')
array([1, 5, 8])
```

3.1.4.3 bandhic.band_hic_matrix.sum

`band_hic_matrix.sum(axis=None)`

Compute the sum of the values in the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the sum:

- None: sum over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Sum(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.sum() # sum of all elements
24
>>> mat.sum(axis='row')
array([ 1, 10, 13])
```

3.1.4.4 bandhic.band_hic_matrix.mean

`band_hic_matrix.mean(axis=None)`

Compute the mean value of the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the mean:

- None: mean over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Mean value(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.mean() # mean of all elements
2.6666666666666665
>>> mat.mean(axis='diag')
array([4., 3.] )
```

3.1.4.5 bandhic.band_hic_matrix.std

`band_hic_matrix.std(axis=None)`

Compute the standard deviation of the values in the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the standard deviation:

- None: std over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Standard deviation(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.std() # std of all elements
2.748737083745107
>>> mat.std(axis='diag')
array([3.26598632, 2.        ] )
```

3.1.4.6 bandhic.band_hic_matrix.var

`band_hic_matrix.var(axis=None)`

Compute the variance of the values in the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the variance:

- None: variance over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Variance(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.var() # variance of all elements
7.555555555555555
>>> mat.var(axis='row')
array([ 0.22222222,  2.88888889, 10.88888889])
```

3.1.4.7 bandhic.band_hic_matrix.prod

`band_hic_matrix.prod(axis=None)`

Compute the product of the values in the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the product:

- None: product over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Product(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(1, 10).reshape(3,3), diag_num=2)
>>> mat.prod() # product of all elements
0
>>> mat.prod(axis='row')
array([ 0, 60, 0])
```

3.1.4.8 bandhic.band_hic_matrix.ptp

`band_hic_matrix.ptp(axis=None)`

Compute the peak-to-peak (maximum - minimum) value of the matrix or along a given axis.

Parameters

axis (*None, int, or {'row','col','diag'}, optional*) – Axis along which to compute the peak-to-peak value:

- None: ptp over all stored values (and default for missing).
- 0 or 'row': per-row reduction.
- 1 or 'col': per-column reduction.
- 'diag': per-diagonal reduction.

Default is None.

Returns

Peak-to-peak value(s) along the specified axis.

Return type

scalar or ndarray

Raises

ValueError – If axis is not one of the supported values.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat.ptp() # ptp of all elements
8
>>> mat.ptp(axis='row')
array([1, 4, 8])
```

3.1.4.9 bandhic.band_hic_matrix.all

`band_hic_matrix.all(axis=None, banded_only=False)`

Test whether all (or any) array elements along a given axis evaluate to True.

Parameters

- **axis** (*None, int, or {'row','col','diag'}, optional*) – Axis along which to test.
 - None: test all stored values (and default for missing).
 - 0 or 'row': per-row reduction.
 - 1 or 'col': per-column reduction.
 - 'diag': per-diagonal reduction.
- **banded_only** (*bool, optional*) – If True, only consider stored band elements; ignore out-of-band values. Default is False.

Returns

Boolean result(s) of the test.

Return type

bool or ndarray

Raises

ValueError – If axis is not supported.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> mat.all()
False
>>> mat.any(axis='diag', banded_only=True)
array([ True, False])
```

3.1.4.10 bandhic.band_hic_matrix.any

`band_hic_matrix.any(axis=None, banded_only=False)`

Test whether all (or any) array elements along a given axis evaluate to True.

Parameters

- **axis** (*None, int, or {'row','col','diag'}, optional*) – Axis along which to test:
 - None: test all stored values (and default for missing).
 - 0 or 'row': per-row reduction.
 - 1 or 'col': per-column reduction.
 - 'diag': per-diagonal reduction.
- **banded_only** (*bool, optional*) – If True, only consider stored band elements; ignore out-of-band values. Default is False.

Returns

Boolean result(s) of the test.

Return type

bool or ndarray

Raises

ValueError – If axis is not supported.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> mat.all()
False
>>> mat.any(axis='diag', banded_only=True)
array([ True, False])
```

3.1.4.11 bandhic.band_hic_matrix.normalize

`band_hic_matrix.normalize(inplace=False)`

Normalize each diagonal of the matrix to have zero mean and unit variance. This modifies the matrix in place.
:raises UserWarning: If any diagonal has zero standard deviation, it will be set to zero.

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.arange(9).reshape(3,3), diag_num=2)
>>> mat = mat.normalize()
```

Return type

None

Parameters

inplace (*bool*) –

3.1.5 Vectorized Computation Methods

These methods allow for the application of universal functions (ufuncs) to the matrix, enabling element-wise operations similar to those in NumPy.

<code>band_hic_matrix.absolute(self, *args, **kwargs)</code>	Perform element-wise 'absolute' operation.
<code>band_hic_matrix.add(self, other, *args, **kwargs)</code>	Perform element-wise 'add' operation with two inputs.
<code>band_hic_matrix.arccos(self, *args, **kwargs)</code>	Perform element-wise 'arccos' operation.
<code>band_hic_matrix.arccosh(self, *args, **kwargs)</code>	Perform element-wise 'arccosh' operation.
<code>band_hic_matrix.arcsin(self, *args, **kwargs)</code>	Perform element-wise 'arcsin' operation.
<code>band_hic_matrix.arcsinh(self, *args, **kwargs)</code>	Perform element-wise 'arcsinh' operation.
<code>band_hic_matrix.arctan(self, *args, **kwargs)</code>	Perform element-wise 'arctan' operation.
<code>band_hic_matrix.arctan2(self, other, *args, ...)</code>	Perform element-wise 'arctan2' operation with two inputs.
<code>band_hic_matrix.arctanh(self, *args, **kwargs)</code>	Perform element-wise 'arctanh' operation.

continues on next page

Table 3.1 – continued from previous page

<code>band_hic_matrix.bitwise_and(self, other, ...)</code>	Perform element-wise 'bitwise_and' operation with two inputs.
<code>band_hic_matrix.bitwise_or(self, other, ...)</code>	Perform element-wise 'bitwise_or' operation with two inputs.
<code>band_hic_matrix.bitwise_xor(self, other, ...)</code>	Perform element-wise 'bitwise_xor' operation with two inputs.
<code>band_hic_matrix.cbrt(self, *args, **kwargs)</code>	Perform element-wise 'cbrt' operation.
<code>band_hic_matrix.conj(self, *args, **kwargs)</code>	Perform element-wise 'conj' operation.
<code>band_hic_matrix.conjugate(self, *args, **kwargs)</code>	Perform element-wise 'conjugate' operation.
<code>band_hic_matrix.cos(self, *args, **kwargs)</code>	Perform element-wise 'cos' operation.
<code>band_hic_matrix.cosh(self, *args, **kwargs)</code>	Perform element-wise 'cosh' operation.
<code>band_hic_matrix.deg2rad(self, *args, **kwargs)</code>	Perform element-wise 'deg2rad' operation.
<code>band_hic_matrix.degrees(self, *args, **kwargs)</code>	Perform element-wise 'degrees' operation.
<code>band_hic_matrix.divide(self, other, *args, ...)</code>	Perform element-wise 'divide' operation with two inputs.
<code>band_hic_matrix.divmod(self, other, *args, ...)</code>	Perform element-wise 'divmod' operation with two inputs.
<code>band_hic_matrix.equal(self, other, *args, ...)</code>	Perform element-wise 'equal' operation with two inputs.
<code>band_hic_matrix.exp(self, *args, **kwargs)</code>	Perform element-wise 'exp' operation.
<code>band_hic_matrix.exp2(self, *args, **kwargs)</code>	Perform element-wise 'exp2' operation.
<code>band_hic_matrix.expml(self, *args, **kwargs)</code>	Perform element-wise 'expml' operation.
<code>band_hic_matrix.fabs(self, *args, **kwargs)</code>	Perform element-wise 'fabs' operation.
<code>band_hic_matrix.float_power(self, other, ...)</code>	Perform element-wise 'float_power' operation with two inputs.
<code>band_hic_matrix.floor_divide(self, other, ...)</code>	Perform element-wise 'floor_divide' operation with two inputs.
<code>band_hic_matrix.fmod(self, other, *args, ...)</code>	Perform element-wise 'fmod' operation with two inputs.
<code>band_hic_matrix.gcd(self, other, *args, **kwargs)</code>	Perform element-wise 'gcd' operation with two inputs.
<code>band_hic_matrix.greater(self, other, *args, ...)</code>	Perform element-wise 'greater' operation with two inputs.
<code>band_hic_matrix.greater_equal(self, other, ...)</code>	Perform element-wise 'greater_equal' operation with two inputs.
<code>band_hic_matrix.heaviside(self, other, ...)</code>	Perform element-wise 'heaviside' operation with two inputs.
<code>band_hic_matrix.hypot(self, other, *args, ...)</code>	Perform element-wise 'hypot' operation with two inputs.
<code>band_hic_matrix.invert(self, *args, **kwargs)</code>	Perform element-wise 'invert' operation.
<code>band_hic_matrix.lcm(self, other, *args, **kwargs)</code>	Perform element-wise 'lcm' operation with two inputs.
<code>band_hic_matrix.left_shift(self, other, ...)</code>	Perform element-wise 'left_shift' operation with two inputs.
<code>band_hic_matrix.less(self, other, *args, ...)</code>	Perform element-wise 'less' operation with two inputs.
<code>band_hic_matrix.less_equal(self, other, ...)</code>	Perform element-wise 'less_equal' operation with two inputs.
<code>band_hic_matrix.log(self, *args, **kwargs)</code>	Perform element-wise 'log' operation.
<code>band_hic_matrix.log1p(self, *args, **kwargs)</code>	Perform element-wise 'log1p' operation.
<code>band_hic_matrix.log2(self, *args, **kwargs)</code>	Perform element-wise 'log2' operation.
<code>band_hic_matrix.log10(self, *args, **kwargs)</code>	Perform element-wise 'log10' operation.
<code>band_hic_matrix.logaddexp(self, other, ...)</code>	Perform element-wise 'logaddexp' operation with two inputs.
<code>band_hic_matrix.logaddexp2(self, other, ...)</code>	Perform element-wise 'logaddexp2' operation with two inputs.
<code>band_hic_matrix.logical_and(self, other, ...)</code>	Perform element-wise 'logical_and' operation with two inputs.

continues on next page

Table 3.1 – continued from previous page

<code>band_hic_matrix.logical_or(self, other, ...)</code>	Perform element-wise 'logical_or' operation with two inputs.
<code>band_hic_matrix.logical_xor(self, other, ...)</code>	Perform element-wise 'logical_xor' operation with two inputs.
<code>band_hic_matrix.maximum(self, other, *args, ...)</code>	Perform element-wise 'maximum' operation with two inputs.
<code>band_hic_matrix.minimum(self, other, *args, ...)</code>	Perform element-wise 'minimum' operation with two inputs.
<code>band_hic_matrix.mod(self, other, *args, **kwargs)</code>	Perform element-wise 'mod' operation with two inputs.
<code>band_hic_matrix.multiply(self, other, *args, ...)</code>	Perform element-wise 'multiply' operation with two inputs.
<code>band_hic_matrix.negative(self, *args, **kwargs)</code>	Perform element-wise 'negative' operation.
<code>band_hic_matrix.not_equal(self, other, ...)</code>	Perform element-wise 'not_equal' operation with two inputs.
<code>band_hic_matrix.positive(self, *args, **kwargs)</code>	Perform element-wise 'positive' operation.
<code>band_hic_matrix.power(self, other, *args, ...)</code>	Perform element-wise 'power' operation with two inputs.
<code>band_hic_matrix.rad2deg(self, *args, **kwargs)</code>	Perform element-wise 'rad2deg' operation.
<code>band_hic_matrix.radians(self, *args, **kwargs)</code>	Perform element-wise 'radians' operation.
<code>band_hic_matrix.reciprocal(self, *args, **kwargs)</code>	Perform element-wise 'reciprocal' operation.
<code>band_hic_matrix.remainder(self, other, ...)</code>	Perform element-wise 'remainder' operation with two inputs.
<code>band_hic_matrix.right_shift(self, other, ...)</code>	Perform element-wise 'right_shift' operation with two inputs.
<code>band_hic_matrix rint(self, *args, **kwargs)</code>	Perform element-wise 'rint' operation.
<code>band_hic_matrix.sign(self, *args, **kwargs)</code>	Perform element-wise 'sign' operation.
<code>band_hic_matrix.sin(self, *args, **kwargs)</code>	Perform element-wise 'sin' operation.
<code>band_hic_matrix.sinh(self, *args, **kwargs)</code>	Perform element-wise 'sinh' operation.
<code>band_hic_matrix.sqrt(self, *args, **kwargs)</code>	Perform element-wise 'sqrt' operation.
<code>band_hic_matrix.square(self, *args, **kwargs)</code>	Perform element-wise 'square' operation.
<code>band_hic_matrix.subtract(self, other, *args, ...)</code>	Perform element-wise 'subtract' operation with two inputs.
<code>band_hic_matrix.tan(self, *args, **kwargs)</code>	Perform element-wise 'tan' operation.
<code>band_hic_matrix.tanh(self, *args, **kwargs)</code>	Perform element-wise 'tanh' operation.
<code>band_hic_matrix.true_divide(self, other, ...)</code>	Perform element-wise 'true_divide' operation with two inputs.

3.1.5.1 bandhic.band_hic_matrix.absolute

`band_hic_matrix.absolute(self, *args, **kwargs)`

Perform element-wise 'absolute' operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.absolute`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.absolute`.

Returns

Result of element-wise 'absolute' operation.

Return type

band_hic_matrix

See also:

`numpy.absolute`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.absolute()
```

3.1.5.2 bandhic.band_hic_matrix.add

`band_hic_matrix.add(self, other, *args, **kwargs)`

Perform element-wise ‘add’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.add`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.add`.

Returns

Result of element-wise ‘add’ operation.

Return type

band_hic_matrix

See also:

`numpy.add`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.add(other)
```

3.1.5.3 bandhic.band_hic_matrix.arccos

`band_hic_matrix.arccos(self, *args, **kwargs)`

Perform element-wise ‘arccos’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arccos`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arccos`.

Returns

Result of element-wise ‘arccos’ operation.

Return type

band_hic_matrix

See also:

`numpy.arccos`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arccos()
```

3.1.5.4 bandhic.band_hic_matrix.arccosh

`band_hic_matrix.arccosh(self, *args, **kwargs)`

Perform element-wise ‘arccosh’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arccosh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arccosh`.

Returns

Result of element-wise ‘arccosh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arccosh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arccosh()
```

3.1.5.5 bandhic.band_hic_matrix.arcsin

`band_hic_matrix.arcsin(self, *args, **kwargs)`

Perform element-wise ‘arcsin’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arcsin`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arcsin`.

Returns

Result of element-wise ‘arcsin’ operation.

Return type

band_hic_matrix

See also:

`numpy.arcsin`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arcsin()
```

3.1.5.6 bandhic.band_hic_matrix.arcsinh

`band_hic_matrix.arcsinh(self, *args, **kwargs)`

Perform element-wise ‘arcsinh’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arcsinh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arcsinh`.

Returns

Result of element-wise ‘arcsinh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arcsinh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arcsinh()
```

3.1.5.7 bandhic.band_hic_matrix.arctan

`band_hic_matrix.arctan(self, *args, **kwargs)`

Perform element-wise ‘arctan’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arctan`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arctan`.

Returns

Result of element-wise ‘arctan’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctan`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arctan()
```

3.1.5.8 bandhic.band_hic_matrix.arctan2

`band_hic_matrix.arctan2(self, other, *args, **kwargs)`

Perform element-wise ‘arctan2’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arctan2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arctan2`.

Returns

Result of element-wise ‘arctan2’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctan2`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.arctan2(other)
```

3.1.5.9 bandhic.band_hic_matrix.arctanh

`band_hic_matrix.arctanh(self, *args, **kwargs)`

Perform element-wise ‘arctanh’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.arctanh`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.arctanh`.

Returns

Result of element-wise ‘arctanh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctanh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.arctanh()
```

3.1.5.10 bandhic.band_hic_matrix.bitwise_and

`band_hic_matrix.bitwise_and(self, other, *args, **kwargs)`

Perform element-wise ‘bitwise_and’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.bitwise_and`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.bitwise_and`.

Returns

Result of element-wise ‘bitwise_and’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_and`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.bitwise_and(other)
```

3.1.5.11 bandhic.band_hic_matrix.bitwise_or

`band_hic_matrix.bitwise_or(self, other, *args, **kwargs)`

Perform element-wise ‘bitwise_or’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.bitwise_or`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.bitwise_or`.

Returns

Result of element-wise ‘bitwise_or’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_or`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.bitwise_or(other)
```

3.1.5.12 bandhic.band_hic_matrix.bitwise_xor

`band_hic_matrix.bitwise_xor(self, other, *args, **kwargs)`

Perform element-wise ‘bitwise_xor’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.bitwise_xor`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.bitwise_xor`.

Returns

Result of element-wise ‘bitwise_xor’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_xor`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.bitwise_xor(other)
```

3.1.5.13 `bandhic.band_hic_matrix.cbrt`

`band_hic_matrix.cbrt(self, *args, **kwargs)`

Perform element-wise ‘cbrt’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cbrt`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cbrt`.

Returns

Result of element-wise ‘cbrt’ operation.

Return type

band_hic_matrix

See also:

`numpy.cbrt`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.cbrt()
```

3.1.5.14 `bandhic.band_hic_matrix.conj`

`band_hic_matrix.conj(self, *args, **kwargs)`

Perform element-wise ‘conj’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.conj`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.conj`.

Returns

Result of element-wise ‘conj’ operation.

Return type

band_hic_matrix

See also:

`numpy.conj`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.conj()
```

3.1.5.15 bandhic.band_hic_matrix.conjugate

`band_hic_matrix.conjugate(self, *args, **kwargs)`

Perform element-wise ‘conjugate’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.conjugate`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.conjugate`.

Returns

Result of element-wise ‘conjugate’ operation.

Return type

band_hic_matrix

See also:

`numpy.conjugate`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.conjugate()
```

3.1.5.16 bandhic.band_hic_matrix.cos

`band_hic_matrix.cos(self, *args, **kwargs)`

Perform element-wise ‘cos’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cos`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cos`.

Returns

Result of element-wise ‘cos’ operation.

Return type

band_hic_matrix

See also:

`numpy.cos`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.cos()
```

3.1.5.17 bandhic.band_hic_matrix.cosh

`band_hic_matrix.cosh(self, *args, **kwargs)`

Perform element-wise ‘cosh’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cosh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cosh`.

Returns

Result of element-wise ‘cosh’ operation.

Return type

band_hic_matrix

See also:

`numpy.cosh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.cosh()
```

3.1.5.18 bandhic.band_hic_matrix.deg2rad

`band_hic_matrix.deg2rad(self, *args, **kwargs)`

Perform element-wise ‘deg2rad’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.deg2rad`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.deg2rad`.

Returns

Result of element-wise ‘deg2rad’ operation.

Return type

band_hic_matrix

See also:

`numpy.deg2rad`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.deg2rad()
```

3.1.5.19 bandhic.band_hic_matrix.degrees

`band_hic_matrix.degrees(self, *args, **kwargs)`

Perform element-wise ‘degrees’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.degrees`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.degrees`.

Returns

Result of element-wise ‘degrees’ operation.

Return type

band_hic_matrix

See also:

`numpy.degrees`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.degrees()
```

3.1.5.20 bandhic.band_hic_matrix.divide

`band_hic_matrix.divide(self, other, *args, **kwargs)`

Perform element-wise ‘divide’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.divide`.

-
- ****kwargs** (*dict*) – Keyword arguments for `numpy.divide`.

Returns

Result of element-wise ‘divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.divide`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.divide(other)
```

3.1.5.21 `bandhic.band_hic_matrix.divmod`

`band_hic_matrix.divmod(self, other, *args, **kwargs)`

Perform element-wise ‘divmod’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.divmod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.divmod`.

Returns

Result of element-wise ‘divmod’ operation.

Return type

band_hic_matrix

See also:

`numpy.divmod`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.divmod(other)
```

3.1.5.22 `bandhic.band_hic_matrix.equal`

`band_hic_matrix.equal(self, other, *args, **kwargs)`

Perform element-wise ‘equal’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.equal`.

Returns

Result of element-wise ‘equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.equal`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.equal(other)
```

3.1.5.23 `bandhic.band_hic_matrix.exp`

`band_hic_matrix.exp(self, *args, **kwargs)`

Perform element-wise ‘exp’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.exp`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.exp`.

Returns

Result of element-wise ‘exp’ operation.

Return type

band_hic_matrix

See also:

`numpy.exp`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.exp()
```

3.1.5.24 bandhic.band_hic_matrix.exp2

`band_hic_matrix.exp2(self, *args, **kwargs)`

Perform element-wise ‘exp2’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.exp2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.exp2`.

Returns

Result of element-wise ‘exp2’ operation.

Return type

band_hic_matrix

See also:

`numpy.exp2`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.exp2()
```

3.1.5.25 bandhic.band_hic_matrix.expm1

`band_hic_matrix.expm1(self, *args, **kwargs)`

Perform element-wise ‘expm1’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.expm1`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.expm1`.

Returns

Result of element-wise ‘expm1’ operation.

Return type

band_hic_matrix

See also:

`numpy.expm1`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.expm1()
```

3.1.5.26 bandhic.band_hic_matrix.fabs

`band_hic_matrix.fabs(self, *args, **kwargs)`

Perform element-wise ‘fabs’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.fabs`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.fabs`.

Returns

Result of element-wise ‘fabs’ operation.

Return type

band_hic_matrix

See also:

`numpy.fabs`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.fabs()
```

3.1.5.27 bandhic.band_hic_matrix.float_power

`band_hic_matrix.float_power(self, other, *args, **kwargs)`

Perform element-wise ‘float_power’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.float_power`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.float_power`.

Returns

Result of element-wise ‘float_power’ operation.

Return type

band_hic_matrix

See also:

`numpy.float_power`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.float_power(other)
```

3.1.5.28 bandhic.band_hic_matrix.floor_divide

`band_hic_matrix.floor_divide(self, other, *args, **kwargs)`

Perform element-wise ‘floor_divide’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.floor_divide`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.floor_divide`.

Returns

Result of element-wise ‘floor_divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.floor_divide`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.floor_divide(other)
```

3.1.5.29 bandhic.band_hic_matrix.fmod

`band_hic_matrix.fmod(self, other, *args, **kwargs)`

Perform element-wise ‘fmod’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.fmod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.fmod`.

Returns

Result of element-wise ‘fmod’ operation.

Return type

band_hic_matrix

See also:

`numpy.fmod`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.fmod(other)
```

3.1.5.30 bandhic.band_hic_matrix.gcd

`band_hic_matrix.gcd(self, other, *args, **kwargs)`

Perform element-wise ‘gcd’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix or array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.gcd`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.gcd`.

Returns

Result of element-wise ‘gcd’ operation.

Return type

band_hic_matrix

See also:

`numpy.gcd`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.gcd(other)
```

3.1.5.31 `bandhic.band_hic_matrix.greater`

`band_hic_matrix.greater(self, other, *args, **kwargs)`

Perform element-wise ‘greater’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.greater`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.greater`.

Returns

Result of element-wise ‘greater’ operation.

Return type

band_hic_matrix

See also:

`numpy.greater`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.greater(other)
```

3.1.5.32 `bandhic.band_hic_matrix.greater_equal`

`band_hic_matrix.greater_equal(self, other, *args, **kwargs)`

Perform element-wise ‘greater_equal’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.greater_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.greater_equal`.

Returns

Result of element-wise ‘greater_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.greater_equal`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.greater_equal(other)
```

3.1.5.33 bandhic.band_hic_matrix.heaviside

`band_hic_matrix.heaviside(self, other, *args, **kwargs)`

Perform element-wise ‘heaviside’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.heaviside`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.heaviside`.

Returns

Result of element-wise ‘heaviside’ operation.

Return type

band_hic_matrix

See also:

`numpy.heaviside`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.heaviside(other)
```

3.1.5.34 bandhic.band_hic_matrix.hypot

`band_hic_matrix.hypot(self, other, *args, **kwargs)`

Perform element-wise ‘hypot’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.hypot`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.hypot`.

Returns

Result of element-wise ‘hypot’ operation.

Return type

band_hic_matrix

See also:

`numpy.hypot`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.hypot(other)
```

3.1.5.35 bandhic.band_hic_matrix.invert

`band_hic_matrix.invert(self, *args, **kwargs)`

Perform element-wise ‘invert’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.invert`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.invert`.

Returns

Result of element-wise ‘invert’ operation.

Return type

band_hic_matrix

See also:

`numpy.invert`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.invert()
```

3.1.5.36 bandhic.band_hic_matrix.lcm

`band_hic_matrix.lcm(self, other, *args, **kwargs)`

Perform element-wise ‘lcm’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.lcm`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.lcm`.

Returns

Result of element-wise ‘lcm’ operation.

Return type

band_hic_matrix

See also:

`numpy.lcm`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.lcm(other)
```

3.1.5.37 bandhic.band_hic_matrix.left_shift

`band_hic_matrix.left_shift(self, other, *args, **kwargs)`

Perform element-wise ‘left_shift’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.left_shift`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.left_shift`.

Returns

Result of element-wise ‘left_shift’ operation.

Return type

band_hic_matrix

See also:

`numpy.left_shift`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.left_shift(other)
```

3.1.5.38 bandhic.band_hic_matrix.less

`band_hic_matrix.less(self, other, *args, **kwargs)`

Perform element-wise ‘less’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.less`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.less`.

Returns

Result of element-wise ‘less’ operation.

Return type

band_hic_matrix

See also:

`numpy.less`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.less(other)
```

3.1.5.39 bandhic.band_hic_matrix.less_equal

`band_hic_matrix.less_equal(self, other, *args, **kwargs)`

Perform element-wise ‘less_equal’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.less_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.less_equal`.

Returns

Result of element-wise ‘less_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.less_equal`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.less_equal(other)
```

3.1.5.40 bandhic.band_hic_matrix.log

`band_hic_matrix.log(self, *args, **kwargs)`

Perform element-wise ‘log’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log`.

Returns

Result of element-wise ‘log’ operation.

Return type

band_hic_matrix

See also:

`numpy.log`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.log()
```

3.1.5.41 bandhic.band_hic_matrix.log1p

`band_hic_matrix.log1p(self, *args, **kwargs)`

Perform element-wise ‘log1p’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log1p`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log1p`.

Returns

Result of element-wise ‘log1p’ operation.

Return type

band_hic_matrix

See also:

`numpy.log1p`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.loglp()
```

3.1.5.42 bandhic.band_hic_matrix.log2

`band_hic_matrix.log2(self, *args, **kwargs)`

Perform element-wise ‘log2’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log2`.

Returns

Result of element-wise ‘log2’ operation.

Return type

band_hic_matrix

See also:

`numpy.log2`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.log2()
```

3.1.5.43 bandhic.band_hic_matrix.log10

`band_hic_matrix.log10(self, *args, **kwargs)`

Perform element-wise ‘log10’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log10`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log10`.

Returns

Result of element-wise ‘log10’ operation.

Return type

band_hic_matrix

See also:

`numpy.log10`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.log10()
```

3.1.5.44 bandhic.band_hic_matrix.logaddexp

`band_hic_matrix.logaddexp(self, other, *args, **kwargs)`

Perform element-wise ‘logaddexp’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logaddexp`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logaddexp`.

Returns

Result of element-wise ‘logaddexp’ operation.

Return type

band_hic_matrix

See also:

`numpy.logaddexp`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.logaddexp(other)
```

3.1.5.45 bandhic.band_hic_matrix.logaddexp2

`band_hic_matrix.logaddexp2(self, other, *args, **kwargs)`

Perform element-wise ‘logaddexp2’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logaddexp2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logaddexp2`.

Returns

Result of element-wise ‘logaddexp2’ operation.

Return type

band_hic_matrix

See also:

`numpy.logaddexp2`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.logaddexp2(other)
```

3.1.5.46 `bandhic.band_hic_matrix.logical_and`

`band_hic_matrix.logical_and(self, other, *args, **kwargs)`

Perform element-wise ‘logical_and’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_and`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_and`.

Returns

Result of element-wise ‘logical_and’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_and`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.logical_and(other)
```

3.1.5.47 `bandhic.band_hic_matrix.logical_or`

`band_hic_matrix.logical_or(self, other, *args, **kwargs)`

Perform element-wise ‘logical_or’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_or`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_or`.

Returns

Result of element-wise ‘logical_or’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_or`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.logical_or(other)
```

3.1.5.48 bandhic.band_hic_matrix.logical_xor

`band_hic_matrix.logical_xor(self, other, *args, **kwargs)`

Perform element-wise ‘logical_xor’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_xor`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_xor`.

Returns

Result of element-wise ‘logical_xor’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_xor`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.logical_xor(other)
```

3.1.5.49 bandhic.band_hic_matrix.maximum

`band_hic_matrix.maximum(self, other, *args, **kwargs)`

Perform element-wise ‘maximum’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.maximum`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.maximum`.

Returns

Result of element-wise ‘maximum’ operation.

Return type

band_hic_matrix

See also:

`numpy.maximum`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.maximum(other)
```

3.1.5.50 bandhic.band_hic_matrix.minimum

`band_hic_matrix.minimum(self, other, *args, **kwargs)`

Perform element-wise ‘minimum’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.minimum`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.minimum`.

Returns

Result of element-wise ‘minimum’ operation.

Return type

band_hic_matrix

See also:

`numpy.minimum`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.minimum(other)
```

3.1.5.51 bandhic.band_hic_matrix.mod

`band_hic_matrix.mod(self, other, *args, **kwargs)`

Perform element-wise ‘mod’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.mod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.mod`.

Returns

Result of element-wise ‘mod’ operation.

Return type

band_hic_matrix

See also:

`numpy.mod`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.mod(other)
```

3.1.5.52 bandhic.band_hic_matrix.multiply

`band_hic_matrix.multiply(self, other, *args, **kwargs)`

Perform element-wise ‘multiply’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.multiply`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.multiply`.

Returns

Result of element-wise ‘multiply’ operation.

Return type

band_hic_matrix

See also:

`numpy.multiply`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.multiply(other)
```

3.1.5.53 bandhic.band_hic_matrix.negative

`band_hic_matrix.negative(self, *args, **kwargs)`

Perform element-wise ‘negative’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.negative`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.negative`.

Returns

Result of element-wise ‘negative’ operation.

Return type

band_hic_matrix

See also:

`numpy.negative`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.negative()
```

3.1.5.54 bandhic.band_hic_matrix.not_equal

`band_hic_matrix.not_equal(self, other, *args, **kwargs)`

Perform element-wise ‘not_equal’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.not_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.not_equal`.

Returns

Result of element-wise ‘not_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.not_equal`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.not_equal(other)
```

3.1.5.55 bandhic.band_hic_matrix.positive

`band_hic_matrix.positive(self, *args, **kwargs)`

Perform element-wise ‘positive’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.positive`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.positive`.

Returns

Result of element-wise ‘positive’ operation.

Return type

band_hic_matrix

See also:

`numpy.positive`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.positive()
```

3.1.5.56 `bandhic.band_hic_matrix.power`

`band_hic_matrix.power(self, other, *args, **kwargs)`

Perform element-wise ‘power’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.power`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.power`.

Returns

Result of element-wise ‘power’ operation.

Return type

band_hic_matrix

See also:

`numpy.power`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.power(other)
```

3.1.5.57 `bandhic.band_hic_matrix.rad2deg`

`band_hic_matrix.rad2deg(self, *args, **kwargs)`

Perform element-wise ‘rad2deg’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.rad2deg`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.rad2deg`.

Returns

Result of element-wise ‘rad2deg’ operation.

Return type

band_hic_matrix

See also:

`numpy.rad2deg`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.rad2deg()
```

3.1.5.58 bandhic.band_hic_matrix.radians

`band_hic_matrix.radians(self, *args, **kwargs)`

Perform element-wise ‘radians’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.radians`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.radians`.

Returns

Result of element-wise ‘radians’ operation.

Return type

band_hic_matrix

See also:

`numpy.radians`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.radians()
```

3.1.5.59 bandhic.band_hic_matrix.reciprocal

`band_hic_matrix.reciprocal(self, *args, **kwargs)`

Perform element-wise ‘reciprocal’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.reciprocal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.reciprocal`.

Returns

Result of element-wise ‘reciprocal’ operation.

Return type

band_hic_matrix

See also:

`numpy.reciprocal`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.reciprocal()
```

3.1.5.60 bandhic.band_hic_matrix.remainder

`band_hic_matrix.remainder(self, other, *args, **kwargs)`

Perform element-wise ‘remainder’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.remainder`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.remainder`.

Returns

Result of element-wise ‘remainder’ operation.

Return type

band_hic_matrix

See also:

`numpy.remainder`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.remainder(other)
```

3.1.5.61 bandhic.band_hic_matrix.right_shift

`band_hic_matrix.right_shift(self, other, *args, **kwargs)`

Perform element-wise ‘right_shift’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.right_shift`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.right_shift`.

Returns

Result of element-wise ‘right_shift’ operation.

Return type

band_hic_matrix

See also:

`numpy.right_shift`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.right_shift(other)
```

3.1.5.62 `bandhic.band_hic_matrix.rint`

`band_hic_matrix.rint(self, *args, **kwargs)`

Perform element-wise ‘rint’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.rint`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.rint`.

Returns

Result of element-wise ‘rint’ operation.

Return type

band_hic_matrix

See also:

`numpy.rint`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.rint()
```

3.1.5.63 `bandhic.band_hic_matrix.sign`

`band_hic_matrix.sign(self, *args, **kwargs)`

Perform element-wise ‘sign’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sign`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sign`.

Returns

Result of element-wise ‘sign’ operation.

Return type

band_hic_matrix

See also:

`numpy.sign`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.sign()
```

3.1.5.64 bandhic.band_hic_matrix.sin

`band_hic_matrix.sin(self, *args, **kwargs)`

Perform element-wise ‘sin’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sin`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sin`.

Returns

Result of element-wise ‘sin’ operation.

Return type

band_hic_matrix

See also:

`numpy.sin`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.sin()
```

3.1.5.65 bandhic.band_hic_matrix.sinh

`band_hic_matrix.sinh(self, *args, **kwargs)`

Perform element-wise ‘sinh’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sinh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sinh`.

Returns

Result of element-wise ‘sinh’ operation.

Return type

band_hic_matrix

See also:

`numpy.sinh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.sinh()
```

3.1.5.66 bandhic.band_hic_matrix.sqrt

`band_hic_matrix.sqrt(self, *args, **kwargs)`

Perform element-wise ‘sqrt’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sqrt`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sqrt`.

Returns

Result of element-wise ‘sqrt’ operation.

Return type

band_hic_matrix

See also:

`numpy.sqrt`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.sqrt()
```

3.1.5.67 bandhic.band_hic_matrix.square

`band_hic_matrix.square(self, *args, **kwargs)`

Perform element-wise ‘square’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.square`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.square`.

Returns

Result of element-wise ‘square’ operation.

Return type

band_hic_matrix

See also:

`numpy.square`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.square()
```

3.1.5.68 bandhic.band_hic_matrix.subtract

`band_hic_matrix.subtract(self, other, *args, **kwargs)`

Perform element-wise ‘subtract’ operation with two inputs.

Parameters

- **self** (*band_hic_matrix*) – First input matrix.
- **other** (*band_hic_matrix* or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.subtract`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.subtract`.

Returns

Result of element-wise ‘subtract’ operation.

Return type

band_hic_matrix

See also:

`numpy.subtract`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.subtract(other)
```

3.1.5.69 bandhic.band_hic_matrix.tan

`band_hic_matrix.tan(self, *args, **kwargs)`

Perform element-wise ‘tan’ operation.

Parameters

- **self** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.tan`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.tan`.

Returns

Result of element-wise ‘tan’ operation.

Return type

band_hic_matrix

See also:

`numpy.tan`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.tan()
```

3.1.5.70 `bandhic.band_hic_matrix.tanh`

`band_hic_matrix.tanh(self, *args, **kwargs)`

Perform element-wise ‘tanh’ operation.

Parameters

- **self** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.tanh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.tanh`.

Returns

Result of element-wise ‘tanh’ operation.

Return type

band_hic_matrix

See also:

`numpy.tanh`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = mat.tanh()
```

3.1.5.71 `bandhic.band_hic_matrix.true_divide`

`band_hic_matrix.true_divide(self, other, *args, **kwargs)`

Perform element-wise ‘true_divide’ operation with two inputs.

Parameters

- **self** (`band_hic_matrix`) – First input matrix.
- **other** (`band_hic_matrix` or *array-like*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.true_divide`.

- ****kwargs** (*dict*) – Keyword arguments for `numpy.true_divide`.

Returns

Result of element-wise ‘true_divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.true_divide`

Examples

```
>>> from bandhic import band_hic_matrix
>>> mat = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> other = mat.copy()
>>> result = mat.true_divide(other)
```

3.1.6 Data Type Conversion and Representation

This section includes methods for converting the matrix to different data types or representations, such as dense, sparse, or masked arrays.

<code>band_hic_matrix.todense()</code>	Convert the band matrix to a dense format.
<code>band_hic_matrix.tocoo()</code>	Convert the matrix to COO format.
<code>band_hic_matrix.tocsr()</code>	Convert the matrix to CSR format.
<code>band_hic_matrix.copy()</code>	Deep copy the object.
<code>band_hic_matrix.astype(dtype[, copy])</code>	Cast data to new dtype.
<code>band_hic_matrix.__repr__()</code>	Return a string representation of the <code>band_hic_matrix</code> object.
<code>band_hic_matrix.__str__()</code>	Return a string representation of the <code>band_hic_matrix</code> object.
<code>band_hic_matrix.__array__([copy])</code>	Return the data as a NumPy array.
<code>band_hic_matrix.__array_priority__()</code>	Return the priority for array operations.

3.1.6.1 `bandhic.band_hic_matrix.todense`

`band_hic_matrix.todense()`

Convert the band matrix to a dense format.

Returns

The dense (square) matrix. Masked if mask is set.

Return type

`ndarray` or `MaskedArray`

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> dense = mat.todense()
>>> dense.shape
(3, 3)
```

3.1.6.2 bandhic.band_hic_matrix.tocoo

`band_hic_matrix.tocoo()`

Convert the matrix to COO format.

Returns

The matrix in scipy COO sparse format.

Return type

coo_array

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> coo = mat.tocoo()
>>> coo.shape
(3, 3)
```

3.1.6.3 bandhic.band_hic_matrix.tocsr

`band_hic_matrix.tocsr()`

Convert the matrix to CSR format.

Returns

The matrix in scipy CSR sparse format.

Return type

csr_array

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> csr = mat.tocsr()
>>> csr.shape
(3, 3)
```

3.1.6.4 bandhic.band_hic_matrix.copy

`band_hic_matrix.copy()`

Deep copy the object.

Returns

A deep copy.

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat2 = mat.copy()
```

3.1.6.5 bandhic.band_hic_matrix.astype

`band_hic_matrix.astype(dtype, copy=False)`

Cast data to new dtype.

Parameters

- **type** (*data-type*) – Target dtype.
- **copy** (*bool*) – If True, the operation is performed in place. Default is False.
- **dtype** (*type*) –

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat = mat.astype(np.float32)
```

Return type

band_hic_matrix

Parameters

- **dtype** (*type*) –
- **copy** (*bool*) –

3.1.6.6 bandhic.band_hic_matrix.__repr__

`band_hic_matrix.__repr__()`

Return a string representation of the `band_hic_matrix` object.

Returns

A string representation of the object.

Return type

str

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> repr(mat)
"band_hic_matrix(shape=(3, 3), diag_num=2, dtype=<class 'numpy.float64'>)"
```

3.1.6.7 bandhic.band_hic_matrix.__str__

`band_hic_matrix.__str__()`

Return a string representation of the `band_hic_matrix` object.

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> print(mat)
band_hic_matrix(shape=(3, 3), diag_num=2, dtype=<class 'numpy.float64'>)
```

3.1.6.8 bandhic.band_hic_matrix.__array__

`band_hic_matrix.__array__(copy=False)`

Return the data as a NumPy array.

Parameters

copy (*bool*, *optional*) – If True, returns a copy. Default is False.

Returns

Underlying band data array.

Return type

ndarray

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> arr = np.array(mat)
```

3.1.6.9 bandhic.band_hic_matrix.__array_priority__

`band_hic_matrix.__array_priority__()`

Return the priority for array operations.

Returns

Priority value.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> mat.__array_priority__()
100
```

3.1.7 Other Methods

This section includes additional methods that do not fall into the categories above but provide other useful operations for *band_hic_matrix*.

<code>band_hic_matrix.memory_usage()</code>	Compute memory usage of <i>band_hic_matrix</i> object.
<code>band_hic_matrix.__len__()</code>	Return the number of rows in the <i>band_hic_matrix</i> object.
<code>band_hic_matrix.__hash__()</code>	Return a hash value for the <i>band_hic_matrix</i> object.
<code>band_hic_matrix.__bool__()</code>	Truth value of the <i>band_hic_matrix</i> , following NumPy semantics.
<code>band_hic_matrix.dump(filename)</code>	Save the <i>band_hic_matrix</i> object to a file.

3.1.7.1 bandhic.band_hic_matrix.memory_usage

`band_hic_matrix.memory_usage()`

Compute memory usage of *band_hic_matrix* object.

Returns

Size in bytes.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat.memory_usage()
772
```

3.1.7.2 bandhic.band_hic_matrix.__len__

`band_hic_matrix.__len__()`

Return the number of rows in the `band_hic_matrix` object.

Returns

Number of rows.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> len(mat)
3
```

3.1.7.3 bandhic.band_hic_matrix.__hash__

`band_hic_matrix.__hash__()`

Return a hash value for the `band_hic_matrix` object.

Returns

Hash value.

Return type

int

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(3), diag_num=2)
>>> hashed=hash(mat)
```

3.1.7.4 bandhic.band_hic_matrix.__bool__

`band_hic_matrix.__bool__()`

Truth value of the `band_hic_matrix`, following NumPy semantics.

Returns

If the matrix has exactly one element (shape (1,1)), returns its truth value; otherwise raises a `ValueError`.

Return type

`bool`

Raises

ValueError – If the matrix contains more than one element.

3.1.7.5 bandhic.band_hic_matrix.dump

`band_hic_matrix.dump(filename)`

Save the `band_hic_matrix` object to a file.

Parameters

filename (*str*) – The name of the file to save the object to.

Return type

`None`

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((3,3), diag_num=2)
>>> mat.dump('myfile.npz')
```

Return type

`None`

Parameters

filename (*str*) –

3.2 Creation Functions

These functions create BandHiC matrices with specific properties.

<code>bandhic.ones(shape[, diag_num, dtype])</code>	Create a <code>band_hic_matrix</code> object filled with ones.
<code>bandhic.zeros(shape[, diag_num, dtype])</code>	Create a <code>band_hic_matrix</code> object filled with zeros.
<code>bandhic.eye(shape[, diag_num, dtype])</code>	Create a <code>band_hic_matrix</code> object filled as an identity matrix.
<code>bandhic.full(shape, fill_value[, diag_num, ...])</code>	Create a <code>band_hic_matrix</code> object filled with a specified value.
<code>bandhic.ones_like(other[, dtype])</code>	Create a <code>band_hic_matrix</code> object matching another matrix, filled with ones.
<code>bandhic.zeros_like(other[, dtype])</code>	Create a <code>band_hic_matrix</code> object matching another matrix, filled with zeros.
<code>bandhic.eye_like(other[, dtype])</code>	Create a <code>band_hic_matrix</code> object matching another matrix, filled as an identity matrix.
<code>bandhic.full_like(other, fill_value[, dtype])</code>	Create a <code>band_hic_matrix</code> object matching another matrix, filled with a specified value.

3.2.1 bandhic.ones

`bandhic.ones(shape, diag_num=1, dtype=<class 'numpy.float64'>)`

Create a `band_hic_matrix` object filled with ones.

Parameters

- **shape** (*tuple of int*) – Matrix shape as (bins, bins).
- **diag_num** (*int, optional*) – Number of diagonals to consider. Default is 1.
- **dtype** (*data-type, optional*) – The data type of the matrix. Default is `np.float64`.

Returns

A `band_hic_matrix` object with all entries filled with ones.

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.ones((5, 5), diag_num=3)
>>> print(mat)
band_hic_matrix(shape=(5, 5), diag_num=3, dtype=<class 'numpy.float64'>)
```

3.2.2 bandhic.zeros

`bandhic.zeros(shape, diag_num=1, dtype=<class 'numpy.float64'>)`

Create a `band_hic_matrix` object filled with zeros.

Parameters

- **shape** (*tuple of int*) – Matrix shape as (bins, bins).
- **diag_num** (*int, optional*) – Number of diagonals to consider. Default is 1.
- **dtype** (*data-type, optional*) – The data type of the matrix. Default is `np.float64`.

Returns

A `band_hic_matrix` object with all entries filled with zeros.

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.zeros((5, 5), diag_num=3)
>>> print(mat)
band_hic_matrix(shape=(5, 5), diag_num=3, dtype=<class 'numpy.float64'>)
```

3.2.3 bandhic.eye

`bandhic.eye(shape, diag_num=1, dtype=<class 'numpy.float64'>)`

Create a `band_hic_matrix` object filled as an identity matrix.

Parameters

- **shape** (*tuple of int*) – Matrix shape as (bins, bins).
- **diag_num** (*int, optional*) – Number of diagonals to consider. Default is 1.
- **dtype** (*data-type, optional*) – The data type of the matrix. Default is `np.float64`.

Returns

A `band_hic_matrix` object with ones on the main diagonal and zeros elsewhere.

Return type

band_hic_matrix

Examples

```
>>> mat = eye((5, 5), diag_num=3)
>>> print(mat)
band_hic_matrix(shape=(5, 5), diag_num=3, dtype=<class 'numpy.float64'>)
```

3.2.4 bandhic.full

`bandhic.full(shape, fill_value, diag_num=1, dtype=<class 'numpy.float64'>)`

Create a `band_hic_matrix` object filled with a specified value.

Parameters

- **shape** (*tuple of int*) – Matrix shape as (bins, bins).
- **fill_value** (*scalar*) – Value to fill the matrix with.
- **diag_num** (*int, optional*) – Number of diagonals to consider. Default is 1.
- **dtype** (*data-type, optional*) – The data type of the matrix. Default is `np.float64`.

Returns

A `band_hic_matrix` object with all entries filled with *fill_value*.

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.full((5, 5), fill_value=7, diag_num=3)
>>> print(mat)
band_hic_matrix(shape=(5, 5), diag_num=3, dtype=<class 'numpy.float64'>)
```

3.2.5 bandhic.ones_like

`bandhic.ones_like(other, dtype=None)`

Create a `band_hic_matrix` object matching another matrix, filled with ones.

Parameters

other (*band_hic_matrix*) – Reference matrix.

Returns

A `band_hic_matrix` object matching *other*, filled with ones.

Return type

band_hic_matrix

Examples

```
>>> mat_ref = zeros((4, 4), diag_num=2)
>>> mat = ones_like(mat_ref)
>>> isinstance(mat, band_hic_matrix)
True
```

3.2.6 bandhic.zeros_like

`bandhic.zeros_like(other, dtype=None)`

Create a `band_hic_matrix` object matching another matrix, filled with zeros.

Parameters

other (*band_hic_matrix*) – Reference matrix.

Returns

A `band_hic_matrix` object matching *other*, filled with zeros.

Return type

band_hic_matrix

Examples

```
>>> mat_ref = zeros((4, 4), diag_num=2)
>>> mat = zeros_like(mat_ref)
>>> isinstance(mat, band_hic_matrix)
True
```

3.2.7 bandhic.eye_like

`bandhic.eye_like(other, dtype=None)`

Create a `band_hic_matrix` object matching another matrix, filled as an identity matrix.

Parameters

other (`band_hic_matrix`) – Reference matrix.

Returns

A `band_hic_matrix` object matching *other*, filled as an identity matrix.

Return type

band_hic_matrix

Examples

```
>>> mat_ref = zeros((4, 4), diag_num=2)
>>> mat = eye_like(mat_ref)
>>> isinstance(mat, band_hic_matrix)
True
```

3.2.8 bandhic.full_like

`bandhic.full_like(other, fill_value, dtype=None)`

Create a `band_hic_matrix` object matching another matrix, filled with a specified value.

Parameters

- **other** (`band_hic_matrix`) – Reference matrix.
- **fill_value** (*scalar*) – Value to fill the matrix.

Returns

A `band_hic_matrix` object matching *other*, filled with *fill_value*.

Return type

band_hic_matrix

Examples

```
>>> mat_ref = zeros((4, 4), diag_num=2)
>>> mat = full_like(mat_ref, fill_value=9)
>>> isinstance(mat, band_hic_matrix)
True
```

3.3 Input/Output Functions

These functions handle input and output operations for BandHiC matrices, including saving and loading from various formats.

<code>bandhic.save_npz(file_name, mat)</code>	Save a <code>band_hic_matrix</code> to a <code>.npz</code> file.
<code>bandhic.load_npz(file_name)</code>	Load a <code>band_hic_matrix</code> from a <code>.npz</code> file.
<code>bandhic.straw_chr(hic_file, chrom, ...[, ...])</code>	Read Hi-C data from a <code>.hic</code> file and return a <code>band_hic_matrix</code> .
<code>bandhic.straw_all_chrs(hic_file, resolution, ...)</code>	Read Hi-C data from a <code>.hic</code> file for all chromosomes and return a dictionary of <code>band_hic_matrix</code> objects.
<code>bandhic.cooler_chr(file_path, chrom, diag_num)</code>	Read Hi-C data from a <code>.cool</code> or <code>.mcool</code> file and return a <code>band_hic_matrix</code> .
<code>bandhic.cooler_all_chrs(file_path, diag_num)</code>	Read Hi-C data from a <code>.cool</code> or <code>.mcool</code> file for all chromosomes and return a dictionary of <code>band_hic_matrix</code> objects.

3.3.1 bandhic.save_npz

`bandhic.save_npz(file_name, mat)`

Save a `band_hic_matrix` to a `.npz` file.

Parameters

- **file_name** (*str*) – Path to save the `.npz` file.
- **mat** (`band_hic_matrix`) – The `band_hic_matrix` object to save.

Return type

None

Examples

```
>>> import bandhic as bh
>>> mat = bh.band_hic_matrix(np.eye(5), diag_num=3)
>>> save_npz('./test/sample.npz', mat)
```

Return type

None

Parameters

- **file_name** (*str*) –
- **mat** (`band_hic_matrix`) –

3.3.2 bandhic.load_npz

`bandhic.load_npz(file_name)`

Load a `band_hic_matrix` from a `.npz` file.

Parameters

file_name (*str*) – Path to the `.npz` file.

Returns

A `band_hic_matrix` object loaded from the file.

Return type

band_hic_matrix

Examples

```
>>> import bandhic as bh
>>> mat = bh.load_npz('./test/sample.npz')
>>> isinstance(mat, band_hic_matrix)
True
```

3.3.3 bandhic.straw_chr

`bandhic.straw_chr(hic_file, chrom, resolution, diag_num, data_type='observed', normalization='NONE', unit='BP')`

Read Hi-C data from a `.hic` file and return a `band_hic_matrix`.

Parameters

- **hic_file** (*str*) – Path to the `.hic` file. This file should be in the Hi-C format compatible with `hicstraw`. Local or remote paths are supported.
- **chrom** (*str*) – Chromosome name (e.g., `'chr1'`, `'chrX'`). Short names like `'1'`, `'X'` are also accepted.
- **resolution** (*int*) – Resolution of the Hi-C data. Such as 10000 for 10kb resolution.
- **diag_num** (*int*) – Number of diagonals to consider.
- **data_type** (*str*, *optional*) – Type of data to read from the Hi-C file. Default is `'observed'`. Other options include `'expected'`, `'balanced'`, etc. See *hicstraw* documentation for more details.
- **normalization** (*str*, *optional*) – Normalization method to apply. Default is `'NONE'`. Other options include `'VC'`, `'VC_SQRT'`, `'KR'`, `'SCALE'`, etc. See *hicstraw* documentation for more details.
- **unit** (*str*, *optional*) – Unit of measurement for the Hi-C data. Default is `'BP'` (base pairs). Other options include `'FRAG'` (fragments), etc.

Return type

band_hic_matrix

See also:

[hicstraw documentation](#) Python interface to read Hi-C data files using `.hic` format.

Returns

A `band_hic_matrix` object containing the Hi-C data.

Return type

band_hic_matrix

Raises

ValueError – If the file cannot be parsed or parameters are invalid.

Parameters

- **hic_file** (*str*) –
- **chrom** (*str*) –
- **resolution** (*int*) –
- **diag_num** (*int*) –
- **data_type** (*str*) –
- **normalization** (*str*) –
- **unit** (*str*) –

Examples

```
>>> import bandhic as bh
>>> mat = bh.straw_chr('/Users/wwb/Documents/workspace/BandHiC-Master/data/
↳ GSE130275_mESC_WT_combined_1.3B_microc.hic', 'chr1', resolution=10000, diag_
↳ num=200)
>>> isinstance(mat, band_hic_matrix)
True
```

3.3.4 bandhic.straw_all_chrs

`bandhic.straw_all_chrs(hic_file, resolution, diag_num, data_type='observed', normalization='NONE', unit='BP')`

Read Hi-C data from a .hic file for all chromosomes and return a dictionary of `band_hic_matrix` objects.

Parameters

- **hic_file** (*str*) – Path to the .hic file. This file should be in the Hi-C format compatible with hicstraw. Local or remote paths are supported.
- **resolution** (*int*) – Resolution of the Hi-C data. Such as 10000 for 10kb resolution.
- **diag_num** (*int*) – Number of diagonals to consider.
- **data_type** (*str*, *optional*) – Type of data to read from the Hi-C file. Default is 'observed'. Other options include 'expected', 'balanced', etc. See *hicstraw* documentation for more details.
- **normalization** (*str*, *optional*) – Normalization method to apply. Default is 'NONE'. Other options include 'VC', 'VC_SQRT', 'KR', 'SCALE', etc. See *hicstraw* documentation for more details.
- **unit** (*str*, *optional*) – Unit of measurement for the Hi-C data. Default is 'BP' (base pairs). Other options include 'FRAG' (fragments), etc.

Returns

A dictionary mapping chromosome names to `band_hic_matrix` objects containing the Hi-C data.

Return type

`Dict[str, band_hic_matrix]`

Raises

ValueError – If the file cannot be parsed or parameters are invalid.

Examples

```
>>> import bandhic as bh
>>> mats = bh.straw_all_chrs('/Users/wwb/Documents/workspace/BandHiC-Master/data/
↳ GSE130275_mESC_WT_combined_1.3B_microc.hic', resolution=10000, diag_num=200)
>>> isinstance(mats['chr1'], band_hic_matrix)
True
```

3.3.5 bandhic.cooler_chr

`bandhic.cooler_chr(file_path, chrom, diag_num, cell_id=None, resolution=None, balance=True)`

Read Hi-C data from a `.cool` or `.mcool` file and return a `band_hic_matrix`.

Parameters

- **file_path** (*str*) – Path to the `.cool`, `.mcool` or `.scool` file.
- **chrom** (*str*) – Chromosome name.
- **diag_num** (*int*) – Number of diagonals to consider.
- **cell_id** (*str, optional*) – Cell ID for `.scool` files.
- **resolution** (*int, optional*) – Resolution of the Hi-C data.
- **balance** (*bool, optional*) – If True, use balanced data. Default is False. This parameter is specific to cooler files.

Returns

A `band_hic_matrix` object containing the Hi-C data.

Return type

band_hic_matrix

Raises

ValueError – If the cooler file is invalid or parameters are incorrect.

Examples

```
>>> import bandhic as bh
>>> mat = bh.cooler_chr('/Users/wwb/Documents/workspace/BandHiC-Master/data/yeast.
↳ 10kb.cool', 'chrI', resolution=10000, diag_num=10)
>>> isinstance(mat, band_hic_matrix)
True
```

See also:

[cooler documentation](#) Official documentation for the Cooler format and API usage.

3.3.6 bandhic.cooler_all_chrs

`bandhic.cooler_all_chrs(file_path, diag_num, resolution=None, cell_id=None, balance=True)`

Read Hi-C data from a .cool or .mcool file for all chromosomes and return a dictionary of `band_hic_matrix` objects.

Parameters

- **file_path** (*str*) – Path to the .cool, .mcool or .scool file.
- **diag_num** (*int*) – Number of diagonals to consider.
- **resolution** (*int*, *optional*) – Resolution of the Hi-C data.
- **cell_id** (*str*, *optional*) – Cell ID for .scool files.
- **balance** (*bool*, *optional*) – If True, use balanced data. Default is False. This parameter is specific to cooler files.

Returns

A dictionary mapping chromosome names to `band_hic_matrix` objects containing the Hi-C data.

Return type

Dict[str, `band_hic_matrix`]

Raises

ValueError – If the cooler file is invalid or parameters are incorrect.

Examples

```
>>> import bandhic as bh
>>> mats = bh.cooler_all_chrs('/Users/wwb/Documents/workspace/BandHiC-Master/data/
↳ yeast.10kb.cool', diag_num=10, resolution=100000)
>>> isinstance(mats['chrI'], band_hic_matrix)
True
```

3.4 Vectorized operations for BandHiC matrices

These functions perform element-wise operations on BandHiC matrices, allowing for efficient computation across the matrix elements. These functions are wrapped around numpy ufuncs to provide a consistent interface for element-wise operations.

<code>bandhic.absolute(x, *args, **kwargs)</code>	Perform element-wise 'absolute' operation.
<code>bandhic.add(x1, x2, *args, **kwargs)</code>	Perform element-wise 'add' operation with two inputs.
<code>bandhic.arccos(x, *args, **kwargs)</code>	Perform element-wise 'arccos' operation.
<code>bandhic.arccosh(x, *args, **kwargs)</code>	Perform element-wise 'arccosh' operation.
<code>bandhic.arcsin(x, *args, **kwargs)</code>	Perform element-wise 'arcsin' operation.
<code>bandhic.arcsinh(x, *args, **kwargs)</code>	Perform element-wise 'arcsinh' operation.
<code>bandhic.arctan(x, *args, **kwargs)</code>	Perform element-wise 'arctan' operation.
<code>bandhic.arctan2(x1, x2, *args, **kwargs)</code>	Perform element-wise 'arctan2' operation with two inputs.
<code>bandhic.arctanh(x, *args, **kwargs)</code>	Perform element-wise 'arctanh' operation.

continues on next page

Table 3.2 – continued from previous page

<i>bandhic.bitwise_and</i> (x1, x2, *args, **kwargs)	Perform element-wise 'bitwise_and' operation with two inputs.
<i>bandhic.bitwise_or</i> (x1, x2, *args, **kwargs)	Perform element-wise 'bitwise_or' operation with two inputs.
<i>bandhic.bitwise_xor</i> (x1, x2, *args, **kwargs)	Perform element-wise 'bitwise_xor' operation with two inputs.
<i>bandhic.cbrt</i> (x, *args, **kwargs)	Perform element-wise 'cbrt' operation.
<i>bandhic.conj</i> (x, *args, **kwargs)	Perform element-wise 'conj' operation.
<i>bandhic.conjugate</i> (x, *args, **kwargs)	Perform element-wise 'conjugate' operation.
<i>bandhic.cos</i> (x, *args, **kwargs)	Perform element-wise 'cos' operation.
<i>bandhic.cosh</i> (x, *args, **kwargs)	Perform element-wise 'cosh' operation.
<i>bandhic.deg2rad</i> (x, *args, **kwargs)	Perform element-wise 'deg2rad' operation.
<i>bandhic.degrees</i> (x, *args, **kwargs)	Perform element-wise 'degrees' operation.
<i>bandhic.divide</i> (x1, x2, *args, **kwargs)	Perform element-wise 'divide' operation with two inputs.
<i>bandhic.divmod</i> (x1, x2, *args, **kwargs)	Perform element-wise 'divmod' operation with two inputs.
<i>bandhic.equal</i> (x1, x2, *args, **kwargs)	Perform element-wise 'equal' operation with two inputs.
<i>bandhic.exp</i> (x, *args, **kwargs)	Perform element-wise 'exp' operation.
<i>bandhic.exp2</i> (x, *args, **kwargs)	Perform element-wise 'exp2' operation.
<i>bandhic.expml</i> (x, *args, **kwargs)	Perform element-wise 'expml' operation.
<i>bandhic.fabs</i> (x, *args, **kwargs)	Perform element-wise 'fabs' operation.
<i>bandhic.float_power</i> (x1, x2, *args, **kwargs)	Perform element-wise 'float_power' operation with two inputs.
<i>bandhic.floor_divide</i> (x1, x2, *args, **kwargs)	Perform element-wise 'floor_divide' operation with two inputs.
<i>bandhic.fmod</i> (x1, x2, *args, **kwargs)	Perform element-wise 'fmod' operation with two inputs.
<i>bandhic.gcd</i> (x1, x2, *args, **kwargs)	Perform element-wise 'gcd' operation with two inputs.
<i>bandhic.greater</i> (x1, x2, *args, **kwargs)	Perform element-wise 'greater' operation with two inputs.
<i>bandhic.greater_equal</i> (x1, x2, *args, **kwargs)	Perform element-wise 'greater_equal' operation with two inputs.
<i>bandhic.heaviside</i> (x1, x2, *args, **kwargs)	Perform element-wise 'heaviside' operation with two inputs.
<i>bandhic.hypot</i> (x1, x2, *args, **kwargs)	Perform element-wise 'hypot' operation with two inputs.
<i>bandhic.invert</i> (x, *args, **kwargs)	Perform element-wise 'invert' operation.
<i>bandhic.lcm</i> (x1, x2, *args, **kwargs)	Perform element-wise 'lcm' operation with two inputs.
<i>bandhic.left_shift</i> (x1, x2, *args, **kwargs)	Perform element-wise 'left_shift' operation with two inputs.
<i>bandhic.less</i> (x1, x2, *args, **kwargs)	Perform element-wise 'less' operation with two inputs.
<i>bandhic.less_equal</i> (x1, x2, *args, **kwargs)	Perform element-wise 'less_equal' operation with two inputs.
<i>bandhic.log</i> (x, *args, **kwargs)	Perform element-wise 'log' operation.
<i>bandhic.log1p</i> (x, *args, **kwargs)	Perform element-wise 'log1p' operation.
<i>bandhic.log2</i> (x, *args, **kwargs)	Perform element-wise 'log2' operation.
<i>bandhic.log10</i> (x, *args, **kwargs)	Perform element-wise 'log10' operation.
<i>bandhic.logaddexp</i> (x1, x2, *args, **kwargs)	Perform element-wise 'logaddexp' operation with two inputs.
<i>bandhic.logaddexp2</i> (x1, x2, *args, **kwargs)	Perform element-wise 'logaddexp2' operation with two inputs.
<i>bandhic.logical_and</i> (x1, x2, *args, **kwargs)	Perform element-wise 'logical_and' operation with two inputs.

continues on next page

Table 3.2 – continued from previous page

<i>bandhic.logical_or</i> (x1, x2, *args, **kwargs)	Perform element-wise 'logical_or' operation with two inputs.
<i>bandhic.logical_xor</i> (x1, x2, *args, **kwargs)	Perform element-wise 'logical_xor' operation with two inputs.
<i>bandhic.maximum</i> (x1, x2, *args, **kwargs)	Perform element-wise 'maximum' operation with two inputs.
<i>bandhic.minimum</i> (x1, x2, *args, **kwargs)	Perform element-wise 'minimum' operation with two inputs.
<i>bandhic.mod</i> (x1, x2, *args, **kwargs)	Perform element-wise 'mod' operation with two inputs.
<i>bandhic.multiply</i> (x1, x2, *args, **kwargs)	Perform element-wise 'multiply' operation with two inputs.
<i>bandhic.negative</i> (x, *args, **kwargs)	Perform element-wise 'negative' operation.
<i>bandhic.not_equal</i> (x1, x2, *args, **kwargs)	Perform element-wise 'not_equal' operation with two inputs.
<i>bandhic.positive</i> (x, *args, **kwargs)	Perform element-wise 'positive' operation.
<i>bandhic.power</i> (x1, x2, *args, **kwargs)	Perform element-wise 'power' operation with two inputs.
<i>bandhic.rad2deg</i> (x, *args, **kwargs)	Perform element-wise 'rad2deg' operation.
<i>bandhic.radians</i> (x, *args, **kwargs)	Perform element-wise 'radians' operation.
<i>bandhic.reciprocal</i> (x, *args, **kwargs)	Perform element-wise 'reciprocal' operation.
<i>bandhic.remainder</i> (x1, x2, *args, **kwargs)	Perform element-wise 'remainder' operation with two inputs.
<i>bandhic.right_shift</i> (x1, x2, *args, **kwargs)	Perform element-wise 'right_shift' operation with two inputs.
<i>bandhic rint</i> (x, *args, **kwargs)	Perform element-wise 'rint' operation.
<i>bandhic.sign</i> (x, *args, **kwargs)	Perform element-wise 'sign' operation.
<i>bandhic.sin</i> (x, *args, **kwargs)	Perform element-wise 'sin' operation.
<i>bandhic.sinh</i> (x, *args, **kwargs)	Perform element-wise 'sinh' operation.
<i>bandhic.sqrt</i> (x, *args, **kwargs)	Perform element-wise 'sqrt' operation.
<i>bandhic.square</i> (x, *args, **kwargs)	Perform element-wise 'square' operation.
<i>bandhic.subtract</i> (x1, x2, *args, **kwargs)	Perform element-wise 'subtract' operation with two inputs.
<i>bandhic.tan</i> (x, *args, **kwargs)	Perform element-wise 'tan' operation.
<i>bandhic.tanh</i> (x, *args, **kwargs)	Perform element-wise 'tanh' operation.
<i>bandhic.true_divide</i> (x1, x2, *args, **kwargs)	Perform element-wise 'true_divide' operation with two inputs.

3.4.1 bandhic.absolute

bandhic.absolute(x, *args, **kwargs)

Perform element-wise ‘absolute’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.absolute`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.absolute`.

Returns

Result of element-wise ‘absolute’ operation.

Return type

band_hic_matrix

See also:

`numpy.absolute`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.absolute(x1)
```

3.4.2 bandhic.add

`bandhic.add(x1, x2, *args, **kwargs)`

Perform element-wise ‘add’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, `ndarray` or `scalar`) – First input matrix.
- **x2** (`band_hic_matrix`, `ndarray` or `scalar`) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.add`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.add`.

Returns

Result of element-wise ‘add’ operation.

Return type

`band_hic_matrix`

See also:

`numpy.add`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.add(x1, x2)
```

3.4.3 bandhic.arccos

`bandhic.arccos(x, *args, **kwargs)`

Perform element-wise ‘arccos’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.arccos`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.arccos`.

Returns

Result of element-wise ‘arccos’ operation.

Return type

band_hic_matrix

See also:

`numpy.arccos`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arccos(x1)
```

3.4.4 bandhic.arccosh

`bandhic.arccosh(x, *args, **kwargs)`

Perform element-wise ‘arccosh’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arccosh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arccosh`.

Returns

Result of element-wise ‘arccosh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arccosh`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arccosh(x1)
```

3.4.5 bandhic.arcsin

`bandhic.arcsin(x, *args, **kwargs)`

Perform element-wise ‘arcsin’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arcsin`.

-
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arcsin`.

Returns

Result of element-wise ‘arcsin’ operation.

Return type

band_hic_matrix

See also:

`numpy.arcsin`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arcsin(x1)
```

3.4.6 `bandhic.arcsinh`

`bandhic.arcsinh`(*x*, **args*, ***kwargs*)

Perform element-wise ‘arcsinh’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arcsinh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arcsinh`.

Returns

Result of element-wise ‘arcsinh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arcsinh`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arcsinh(x1)
```

3.4.7 bandhic.arctan

`bandhic.arctan(x, *args, **kwargs)`

Perform element-wise ‘arctan’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arctan`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arctan`.

Returns

Result of element-wise ‘arctan’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctan`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arctan(x1)
```

3.4.8 bandhic.arctan2

`bandhic.arctan2(x1, x2, *args, **kwargs)`

Perform element-wise ‘arctan2’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.arctan2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.arctan2`.

Returns

Result of element-wise ‘arctan2’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctan2`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.arctan2(x1, x2)
```

3.4.9 bandhic.arctanh

`bandhic.arctanh(x, *args, **kwargs)`

Perform element-wise ‘arctanh’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.arctanh`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.arctanh`.

Returns

Result of element-wise ‘arctanh’ operation.

Return type

band_hic_matrix

See also:

`numpy.arctanh`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.arctanh(x1)
```

3.4.10 bandhic.bitwise_and

`bandhic.bitwise_and(x1, x2, *args, **kwargs)`

Perform element-wise ‘bitwise_and’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, *ndarray or scalar*) – First input matrix.
- **x2** (`band_hic_matrix`, *ndarray or scalar*) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.bitwise_and`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.bitwise_and`.

Returns

Result of element-wise ‘bitwise_and’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_and`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.bitwise_and(x1, x2)
```

3.4.11 bandhic.bitwise_or

`bandhic.bitwise_or(x1, x2, *args, **kwargs)`

Perform element-wise ‘bitwise_or’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, `ndarray` or `scalar`) – First input matrix.
- **x2** (`band_hic_matrix`, `ndarray` or `scalar`) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.bitwise_or`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.bitwise_or`.

Returns

Result of element-wise ‘bitwise_or’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_or`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.bitwise_or(x1, x2)
```

3.4.12 bandhic.bitwise_xor

`bandhic.bitwise_xor(x1, x2, *args, **kwargs)`

Perform element-wise ‘bitwise_xor’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, `ndarray` or `scalar`) – First input matrix.
- **x2** (`band_hic_matrix`, `ndarray` or `scalar`) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.bitwise_xor`.

-
- ****kwargs** (*dict*) – Keyword arguments for `numpy.bitwise_xor`.

Returns

Result of element-wise ‘bitwise_xor’ operation.

Return type

band_hic_matrix

See also:

`numpy.bitwise_xor`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.bitwise_xor(x1, x2)
```

3.4.13 bandhic.cbrt

`bandhic.cbrt(x, *args, **kwargs)`

Perform element-wise ‘cbrt’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cbrt`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cbrt`.

Returns

Result of element-wise ‘cbrt’ operation.

Return type

band_hic_matrix

See also:

`numpy.cbrt`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.cbrt(x1)
```

3.4.14 bandhic.conj

`bandhic.conj(x, *args, **kwargs)`

Perform element-wise ‘conj’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.conj`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.conj`.

Returns

Result of element-wise ‘conj’ operation.

Return type

band_hic_matrix

See also:

`numpy.conj`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.conj(x1)
```

3.4.15 bandhic.conjugate

`bandhic.conjugate(x, *args, **kwargs)`

Perform element-wise ‘conjugate’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.conjugate`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.conjugate`.

Returns

Result of element-wise ‘conjugate’ operation.

Return type

band_hic_matrix

See also:

`numpy.conjugate`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.conjugate(x1)
```

3.4.16 bandhic.cos

`bandhic.cos(x, *args, **kwargs)`

Perform element-wise ‘cos’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cos`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cos`.

Returns

Result of element-wise ‘cos’ operation.

Return type

band_hic_matrix

See also:

[numpy.cos](#)

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.cos(x1)
```

3.4.17 bandhic.cosh

`bandhic.cosh(x, *args, **kwargs)`

Perform element-wise ‘cosh’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.cosh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.cosh`.

Returns

Result of element-wise ‘cosh’ operation.

Return type

band_hic_matrix

See also:

[numpy.cosh](#)

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.cosh(x1)
```

3.4.18 bandhic.deg2rad

`bandhic.deg2rad(x, *args, **kwargs)`

Perform element-wise ‘deg2rad’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.deg2rad`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.deg2rad`.

Returns

Result of element-wise ‘deg2rad’ operation.

Return type

band_hic_matrix

See also:

`numpy.deg2rad`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.deg2rad(x1)
```

3.4.19 bandhic.degrees

`bandhic.degrees(x, *args, **kwargs)`

Perform element-wise ‘degrees’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.degrees`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.degrees`.

Returns

Result of element-wise ‘degrees’ operation.

Return type

band_hic_matrix

See also:

`numpy.degrees`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.degrees(x1)
```

3.4.20 bandhic.divide

`bandhic.divide(x1, x2, *args, **kwargs)`

Perform element-wise ‘divide’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.divide`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.divide`.

Returns

Result of element-wise ‘divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.divide`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.divide(x1, x2)
```

3.4.21 bandhic.divmod

`bandhic.divmod(x1, x2, *args, **kwargs)`

Perform element-wise ‘divmod’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.divmod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.divmod`.

Returns

Result of element-wise ‘divmod’ operation.

Return type

band_hic_matrix

See also:

`numpy.divmod`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.divmod(x1, x2)
```

3.4.22 bandhic.equal

`bandhic.equal(x1, x2, *args, **kwargs)`

Perform element-wise ‘equal’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.equal`.

Returns

Result of element-wise ‘equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.equal`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.equal(x1, x2)
```

3.4.23 bandhic.exp

`bandhic.exp(x, *args, **kwargs)`

Perform element-wise ‘exp’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.exp`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.exp`.

Returns

Result of element-wise ‘exp’ operation.

Return type

band_hic_matrix

See also:

`numpy.exp`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.exp(x1)
```

3.4.24 bandhic.exp2

`bandhic.exp2(x, *args, **kwargs)`

Perform element-wise ‘exp2’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.exp2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.exp2`.

Returns

Result of element-wise ‘exp2’ operation.

Return type

band_hic_matrix

See also:

`numpy.exp2`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.exp2(x1)
```

3.4.25 bandhic.expm1

`bandhic.expm1(x, *args, **kwargs)`

Perform element-wise ‘expm1’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.expm1`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.expm1`.

Returns

Result of element-wise ‘expm1’ operation.

Return type

band_hic_matrix

See also:

`numpy.expm1`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.expm1(x1)
```

3.4.26 bandhic.fabs

`bandhic.fabs(x, *args, **kwargs)`

Perform element-wise ‘fabs’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.fabs`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.fabs`.

Returns

Result of element-wise ‘fabs’ operation.

Return type

band_hic_matrix

See also:

`numpy.fabs`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.fabs(x1)
```

3.4.27 bandhic.float_power

`bandhic.float_power(x1, x2, *args, **kwargs)`

Perform element-wise ‘float_power’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.float_power`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.float_power`.

Returns

Result of element-wise ‘float_power’ operation.

Return type

band_hic_matrix

See also:

`numpy.float_power`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.float_power(x1, x2)
```

3.4.28 bandhic.floor_divide

`bandhic.floor_divide(x1, x2, *args, **kwargs)`

Perform element-wise ‘floor_divide’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.floor_divide`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.floor_divide`.

Returns

Result of element-wise ‘floor_divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.floor_divide`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.floor_divide(x1, x2)
```

3.4.29 bandhic.fmod

`bandhic.fmod(x1, x2, *args, **kwargs)`

Perform element-wise ‘fmod’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.fmod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.fmod`.

Returns

Result of element-wise ‘fmod’ operation.

Return type

band_hic_matrix

See also:

`numpy.fmod`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.fmod(x1, x2)
```

3.4.30 bandhic.gcd

`bandhic.gcd(x1, x2, *args, **kwargs)`

Perform element-wise ‘gcd’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.gcd`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.gcd`.

Returns

Result of element-wise ‘gcd’ operation.

Return type

band_hic_matrix

See also:

`numpy.gcd`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.gcd(x1, x2)
```

3.4.31 bandhic.greater

`bandhic.greater(x1, x2, *args, **kwargs)`

Perform element-wise ‘greater’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.greater`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.greater`.

Returns

Result of element-wise ‘greater’ operation.

Return type

band_hic_matrix

See also:

`numpy.greater`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.greater(x1, x2)
```

3.4.32 bandhic.greater_equal

`bandhic.greater_equal(x1, x2, *args, **kwargs)`

Perform element-wise ‘greater_equal’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.greater_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.greater_equal`.

Returns

Result of element-wise ‘greater_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.greater_equal`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.greater_equal(x1, x2)
```

3.4.33 bandhic.heaviside

`bandhic.heaviside(x1, x2, *args, **kwargs)`

Perform element-wise ‘heaviside’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.heaviside`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.heaviside`.

Returns

Result of element-wise ‘heaviside’ operation.

Return type

band_hic_matrix

See also:

`numpy.heaviside`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.heaviside(x1, x2)
```

3.4.34 bandhic.hypot

`bandhic.hypot(x1, x2, *args, **kwargs)`

Perform element-wise ‘hypot’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.hypot`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.hypot`.

Returns

Result of element-wise ‘hypot’ operation.

Return type

band_hic_matrix

See also:

`numpy.hypot`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.hypot(x1, x2)
```

3.4.35 bandhic.invert

`bandhic.invert(x, *args, **kwargs)`

Perform element-wise ‘invert’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.invert`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.invert`.

Returns

Result of element-wise ‘invert’ operation.

Return type

band_hic_matrix

See also:

`numpy.invert`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.invert(x1)
```

3.4.36 bandhic.lcm

`bandhic.lcm(x1, x2, *args, **kwargs)`

Perform element-wise ‘lcm’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.lcm`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.lcm`.

Returns

Result of element-wise ‘lcm’ operation.

Return type

band_hic_matrix

See also:

`numpy.lcm`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.lcm(x1, x2)
```

3.4.37 bandhic.left_shift

`bandhic.left_shift(x1, x2, *args, **kwargs)`

Perform element-wise ‘left_shift’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.left_shift`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.left_shift`.

Returns

Result of element-wise ‘left_shift’ operation.

Return type

band_hic_matrix

See also:

`numpy.left_shift`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.left_shift(x1, x2)
```

3.4.38 bandhic.less

`bandhic.less(x1, x2, *args, **kwargs)`

Perform element-wise ‘less’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.less`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.less`.

Returns

Result of element-wise ‘less’ operation.

Return type

band_hic_matrix

See also:

`numpy.less`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.less(x1, x2)
```

3.4.39 bandhic.less_equal

`bandhic.less_equal(x1, x2, *args, **kwargs)`

Perform element-wise ‘less_equal’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.less_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.less_equal`.

Returns

Result of element-wise ‘less_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.less_equal`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.less_equal(x1, x2)
```

3.4.40 bandhic.log

`bandhic.log(x, *args, **kwargs)`

Perform element-wise ‘log’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log`.

Returns

Result of element-wise ‘log’ operation.

Return type

band_hic_matrix

See also:

`numpy.log`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.log(x1)
```

3.4.41 bandhic.log1p

`bandhic.log1p(x, *args, **kwargs)`

Perform element-wise ‘log1p’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log1p`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log1p`.

Returns

Result of element-wise ‘log1p’ operation.

Return type

band_hic_matrix

See also:

`numpy.log1p`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.log1p(x1)
```

3.4.42 bandhic.log2

`bandhic.log2(x, *args, **kwargs)`

Perform element-wise ‘log2’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log2`.

Returns

Result of element-wise ‘log2’ operation.

Return type

band_hic_matrix

See also:

`numpy.log2`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.log2(x1)
```

3.4.43 bandhic.log10

`bandhic.log10(x, *args, **kwargs)`

Perform element-wise ‘log10’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.log10`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.log10`.

Returns

Result of element-wise ‘log10’ operation.

Return type

band_hic_matrix

See also:

`numpy.log10`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.log10(x1)
```

3.4.44 bandhic.logaddexp

`bandhic.logaddexp(x1, x2, *args, **kwargs)`

Perform element-wise ‘logaddexp’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logaddexp`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logaddexp`.

Returns

Result of element-wise ‘logaddexp’ operation.

Return type

band_hic_matrix

See also:

`numpy.logaddexp`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.logaddexp(x1, x2)
```

3.4.45 bandhic.logaddexp2

`bandhic.logaddexp2(x1, x2, *args, **kwargs)`

Perform element-wise ‘logaddexp2’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logaddexp2`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logaddexp2`.

Returns

Result of element-wise ‘logaddexp2’ operation.

Return type

band_hic_matrix

See also:

`numpy.logaddexp2`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.logaddexp2(x1, x2)
```

3.4.46 bandhic.logical_and

`bandhic.logical_and(x1, x2, *args, **kwargs)`

Perform element-wise ‘logical_and’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_and`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_and`.

Returns

Result of element-wise ‘logical_and’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_and`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.logical_and(x1, x2)
```

3.4.47 bandhic.logical_or

`bandhic.logical_or(x1, x2, *args, **kwargs)`

Perform element-wise ‘logical_or’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_or`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_or`.

Returns

Result of element-wise ‘logical_or’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_or`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.logical_or(x1, x2)
```

3.4.48 bandhic.logical_xor

`bandhic.logical_xor(x1, x2, *args, **kwargs)`

Perform element-wise ‘logical_xor’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.logical_xor`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.logical_xor`.

Returns

Result of element-wise ‘logical_xor’ operation.

Return type

band_hic_matrix

See also:

`numpy.logical_xor`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.logical_xor(x1, x2)
```

3.4.49 bandhic.maximum

`bandhic.maximum(x1, x2, *args, **kwargs)`

Perform element-wise ‘maximum’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.maximum`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.maximum`.

Returns

Result of element-wise ‘maximum’ operation.

Return type

band_hic_matrix

See also:

`numpy.maximum`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.maximum(x1, x2)
```

3.4.50 bandhic.minimum

`bandhic.minimum(x1, x2, *args, **kwargs)`

Perform element-wise ‘minimum’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.minimum`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.minimum`.

Returns

Result of element-wise ‘minimum’ operation.

Return type

band_hic_matrix

See also:

`numpy.minimum`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.minimum(x1, x2)
```

3.4.51 bandhic.mod

`bandhic.mod(x1, x2, *args, **kwargs)`

Perform element-wise ‘mod’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.mod`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.mod`.

Returns

Result of element-wise ‘mod’ operation.

Return type

band_hic_matrix

See also:

`numpy.mod`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.mod(x1, x2)
```

3.4.52 bandhic.multiply

`bandhic.multiply(x1, x2, *args, **kwargs)`

Perform element-wise ‘multiply’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.multiply`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.multiply`.

Returns

Result of element-wise ‘multiply’ operation.

Return type

band_hic_matrix

See also:

`numpy.multiply`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.multiply(x1, x2)
```

3.4.53 bandhic.negative

`bandhic.negative(x, *args, **kwargs)`

Perform element-wise ‘negative’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.negative`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.negative`.

Returns

Result of element-wise ‘negative’ operation.

Return type

band_hic_matrix

See also:

`numpy.negative`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.negative(x1)
```

3.4.54 bandhic.not_equal

`bandhic.not_equal(x1, x2, *args, **kwargs)`

Perform element-wise ‘not_equal’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.not_equal`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.not_equal`.

Returns

Result of element-wise ‘not_equal’ operation.

Return type

band_hic_matrix

See also:

`numpy.not_equal`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.not_equal(x1, x2)
```

3.4.55 bandhic.positive

`bandhic.positive(x, *args, **kwargs)`

Perform element-wise ‘positive’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.positive`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.positive`.

Returns

Result of element-wise ‘positive’ operation.

Return type

band_hic_matrix

See also:

`numpy.positive`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.positive(x1)
```

3.4.56 bandhic.power

`bandhic.power(x1, x2, *args, **kwargs)`

Perform element-wise ‘power’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, `ndarray` or `scalar`) – First input matrix.
- **x2** (`band_hic_matrix`, `ndarray` or `scalar`) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.power`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.power`.

Returns

Result of element-wise ‘power’ operation.

Return type

band_hic_matrix

See also:

`numpy.power`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.power(x1, x2)
```

3.4.57 bandhic.rad2deg

`bandhic.rad2deg(x, *args, **kwargs)`

Perform element-wise ‘rad2deg’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.rad2deg`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.rad2deg`.

Returns

Result of element-wise ‘rad2deg’ operation.

Return type

band_hic_matrix

See also:

`numpy.rad2deg`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.rad2deg(x1)
```

3.4.58 bandhic.radians

`bandhic.radians(x, *args, **kwargs)`

Perform element-wise ‘radians’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.radians`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.radians`.

Returns

Result of element-wise ‘radians’ operation.

Return type

band_hic_matrix

See also:

`numpy.radians`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.radians(x1)
```

3.4.59 bandhic.reciprocal

`bandhic.reciprocal(x, *args, **kwargs)`

Perform element-wise ‘reciprocal’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.reciprocal`.

-
- ****kwargs** (*dict*) – Keyword arguments for `numpy.reciprocal`.

Returns

Result of element-wise ‘reciprocal’ operation.

Return type

band_hic_matrix

See also:

`numpy.reciprocal`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.reciprocal(x1)
```

3.4.60 `bandhic.remainer`

`bandhic.remainer(x1, x2, *args, **kwargs)`

Perform element-wise ‘remainder’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix, ndarray or scalar*) – First input matrix.
- **x2** (*band_hic_matrix, ndarray or scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.remainder`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.remainder`.

Returns

Result of element-wise ‘remainder’ operation.

Return type

band_hic_matrix

See also:

`numpy.remainder`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.remainder(x1, x2)
```

3.4.61 bandhic.right_shift

`bandhic.right_shift(x1, x2, *args, **kwargs)`

Perform element-wise ‘right_shift’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.right_shift`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.right_shift`.

Returns

Result of element-wise ‘right_shift’ operation.

Return type

band_hic_matrix

See also:

`numpy.right_shift`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.right_shift(x1, x2)
```

3.4.62 bandhic.rint

`bandhic.rint(x, *args, **kwargs)`

Perform element-wise ‘rint’ operation.

Parameters

- **x** (*band_hic_matrix*) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.rint`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.rint`.

Returns

Result of element-wise ‘rint’ operation.

Return type

band_hic_matrix

See also:

`numpy.rint`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.rint(x1)
```

3.4.63 bandhic.sign

`bandhic.sign(x, *args, **kwargs)`

Perform element-wise ‘sign’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sign`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sign`.

Returns

Result of element-wise ‘sign’ operation.

Return type

band_hic_matrix

See also:

`numpy.sign`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.sign(x1)
```

3.4.64 bandhic.sin

`bandhic.sin(x, *args, **kwargs)`

Perform element-wise ‘sin’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sin`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sin`.

Returns

Result of element-wise ‘sin’ operation.

Return type

band_hic_matrix

See also:

`numpy.sin`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.sin(x1)
```

3.4.65 bandhic.sinh

`bandhic.sinh(x, *args, **kwargs)`

Perform element-wise ‘sinh’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sinh`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sinh`.

Returns

Result of element-wise ‘sinh’ operation.

Return type

band_hic_matrix

See also:

`numpy.sinh`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.sinh(x1)
```

3.4.66 bandhic.sqrt

`bandhic.sqrt(x, *args, **kwargs)`

Perform element-wise ‘sqrt’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (*tuple*) – Additional positional arguments for `numpy.sqrt`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.sqrt`.

Returns

Result of element-wise ‘sqrt’ operation.

Return type

band_hic_matrix

See also:

`numpy.sqrt`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.sqrt(x1)
```

3.4.67 bandhic.square

`bandhic.square(x, *args, **kwargs)`

Perform element-wise ‘square’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.square`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.square`.

Returns

Result of element-wise ‘square’ operation.

Return type

band_hic_matrix

See also:

`numpy.square`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.square(x1)
```

3.4.68 bandhic.subtract

`bandhic.subtract(x1, x2, *args, **kwargs)`

Perform element-wise ‘subtract’ operation with two inputs.

Parameters

- **x1** (`band_hic_matrix`, *ndarray or scalar*) – First input matrix.
- **x2** (`band_hic_matrix`, *ndarray or scalar*) – Second input for the operation.
- ***args** (`tuple`) – Additional positional arguments for `numpy.subtract`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.subtract`.

Returns

Result of element-wise ‘subtract’ operation.

Return type

band_hic_matrix

See also:

`numpy.subtract`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.subtract(x1, x2)
```

3.4.69 bandhic.tan

`bandhic.tan(x, *args, **kwargs)`

Perform element-wise ‘tan’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.tan`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.tan`.

Returns

Result of element-wise ‘tan’ operation.

Return type

band_hic_matrix

See also:

`numpy.tan`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.tan(x1)
```

3.4.70 bandhic.tanh

`bandhic.tanh(x, *args, **kwargs)`

Perform element-wise ‘tanh’ operation.

Parameters

- **x** (`band_hic_matrix`) – Input matrix.
- ***args** (`tuple`) – Additional positional arguments for `numpy.tanh`.
- ****kwargs** (`dict`) – Keyword arguments for `numpy.tanh`.

Returns

Result of element-wise ‘tanh’ operation.

Return type

band_hic_matrix

See also:

`numpy.tanh`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> result = bh.tanh(x1)
```

3.4.71 bandhic.true_divide

`bandhic.true_divide(x1, x2, *args, **kwargs)`

Perform element-wise ‘true_divide’ operation with two inputs.

Parameters

- **x1** (*band_hic_matrix*, *ndarray* or *scalar*) – First input matrix.
- **x2** (*band_hic_matrix*, *ndarray* or *scalar*) – Second input for the operation.
- ***args** (*tuple*) – Additional positional arguments for `numpy.true_divide`.
- ****kwargs** (*dict*) – Keyword arguments for `numpy.true_divide`.

Returns

Result of element-wise ‘true_divide’ operation.

Return type

band_hic_matrix

See also:

`numpy.true_divide`

Examples

```
>>> import bandhic as bh
>>> x1 = band_hic_matrix(np.eye(3), diag_num=2, dtype=int)
>>> x2 = x1.copy()
>>> result = bh.true_divide(x1, x2)
```

3.5 Data Reduction and Normalization

These functions perform data reduction and normalization on BandHiC matrices, allowing for efficient analysis of Hi-C data. These functions are wrapped around `band_hic_matrix` methods to provide a consistent interface for data reduction and normalization.

<code>bandhic.min(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.min</code>
<code>bandhic.max(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.max</code>
<code>bandhic.sum(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.sum</code>
<code>bandhic.mean(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.mean</code>
<code>bandhic.std(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.std</code>
<code>bandhic.var(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.var</code>
<code>bandhic.prod(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.prod</code>
<code>bandhic.ptp(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.ptp</code>
<code>bandhic.all(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.all</code>
<code>bandhic.any(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.any</code>
<code>bandhic.clip(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.clip</code>
<code>bandhic.normalize(*args, **kwargs)</code>	Wrapped from <code>band_hic_matrix.normalize</code>

3.5.1 bandhic.min

`bandhic.min(*args, **kwargs)`

Wrapped from `band_hic_matrix.min`

Refer to the documentation: `bandhic.band_hic_matrix.min()`

3.5.2 bandhic.max

`bandhic.max(*args, **kwargs)`

Wrapped from `band_hic_matrix.max`

Refer to the documentation: `bandhic.band_hic_matrix.max()`

3.5.3 bandhic.sum

`bandhic.sum(*args, **kwargs)`

Wrapped from `band_hic_matrix.sum`

Refer to the documentation: `bandhic.band_hic_matrix.sum()`

3.5.4 bandhic.mean

`bandhic.mean(*args, **kwargs)`

Wrapped from `band_hic_matrix.mean`

Refer to the documentation: `bandhic.band_hic_matrix.mean()`

3.5.5 bandhic.std

`bandhic.std(*args, **kwargs)`

Wrapped from *band_hic_matrix.std*

Refer to the documentation: [*bandhic.band_hic_matrix.std\(\)*](#)

3.5.6 bandhic.var

`bandhic.var(*args, **kwargs)`

Wrapped from *band_hic_matrix.var*

Refer to the documentation: [*bandhic.band_hic_matrix.var\(\)*](#)

3.5.7 bandhic.prod

`bandhic.prod(*args, **kwargs)`

Wrapped from *band_hic_matrix.prod*

Refer to the documentation: [*bandhic.band_hic_matrix.prod\(\)*](#)

3.5.8 bandhic.ptp

`bandhic.ptp(*args, **kwargs)`

Wrapped from *band_hic_matrix.ptp*

Refer to the documentation: [*bandhic.band_hic_matrix.ptp\(\)*](#)

3.5.9 bandhic.all

`bandhic.all(*args, **kwargs)`

Wrapped from *band_hic_matrix.all*

Refer to the documentation: [*bandhic.band_hic_matrix.all\(\)*](#)

3.5.10 bandhic.any

`bandhic.any(*args, **kwargs)`

Wrapped from *band_hic_matrix.any*

Refer to the documentation: [*bandhic.band_hic_matrix.any\(\)*](#)

3.5.11 bandhic.clip

`bandhic.clip(*args, **kwargs)`

Wrapped from `band_hic_matrix.clip`

Refer to the documentation: `bandhic.band_hic_matrix.clip()`

3.5.12 bandhic.normalize

`bandhic.normalize(*args, **kwargs)`

Wrapped from `band_hic_matrix.normalize`

Refer to the documentation: `bandhic.band_hic_matrix.normalize()`

3.6 Other Functions

These functions provide additional utilities for BandHiC matrices, including matrix comparison, bias computation, and TAD calling.

<code>bandhic.matrix_equal(a, b)</code>	Check if two <code>band_hic_matrix</code> objects are equal.
<code>bandhic.assert_band_matrix_equal(a, b)</code>	Assert that two <code>band_hic_matrix</code> objects are equal.
<code>bandhic.compute_bin_bias(hic_coo[, verbose, ...])</code>	Compute bias values for Hi-C contact matrices using the Knight-Ruiz normalization algorithm.
<code>bandhic.call_tad(hic_matrix, resolution, ...)</code>	Detect TADs from a Hi-C matrix using the TopDom algorithm.
<code>bandhic.topdom(hic_matrix, bins, window_size)</code>	Detect TADs using TopDom algorithm.
<code>bandhic.apa(hic_path, resolution, loops_df)</code>	Compute Aggregate Peak Analysis (APA) around a set of loop anchors.
<code>bandhic.hiccups(hic_file, chroms, resolutions)</code>	Run the HiCCUPS loop-calling algorithm on Hi-C data using the BandHiC data structure.
<code>bandhic.load_norm_vector_from_hic(hic_file, ...)</code>	Load a normalization vector from a .hic file for a given chromosome and resolution.
<code>bandhic.load_norm_vector_from_cooler(...)</code>	Load a normalization vector from a .cool or .mcool file for a given chromosome and resolution.
<code>bandhic.scc(A, B[, max_k, min_n, method])</code>	Stratified correlation coefficient (SCC) for Hi-C using BandHiC.

3.6.1 bandhic.matrix_equal

`bandhic.matrix_equal(a, b)`

Check if two `band_hic_matrix` objects are equal.

Parameters

- **a** (`band_hic_matrix`) – First `band_hic_matrix` object.
- **b** (`band_hic_matrix`) – Second `band_hic_matrix` object.

Returns

True if the matrices are equal, False otherwise.

Return type
bool

3.6.2 bandhic.assert_band_matrix_equal

`bandhic.assert_band_matrix_equal(a, b)`

Assert that two `band_hic_matrix` objects are equal.

Parameters

- **a** (`band_hic_matrix`) – First `band_hic_matrix` object.
- **b** (`band_hic_matrix`) – Second `band_hic_matrix` object.

Raises

AssertionError – If the two matrices are not equal.

Return type
bool

3.6.3 bandhic.compute_bin_bias

`bandhic.compute_bin_bias(hic_coo, verbose=False, bias_lowerbound=0.5, bias_upperbound=2)`

Compute bias values for Hi-C contact matrices using the Knight-Ruiz normalization algorithm.

Parameters

- **hic_coo** (`scipy.sparse.coo_array`) – A sparse COO matrix representing Hi-C contact data.
- **verbose** (`bool`, *optional*) – If True, print detailed information during processing. Default is False.

Returns

- **bias** (`numpy.ndarray`) – A 1D array containing the bias values for each bin in the Hi-C matrix.
- **is_valid** (`bool`) – A boolean indicating whether the bias vector is valid (mean and median within typical range).

Notes

This function removes a specified percentage of the most sparse bins from the Hi-C matrix before computing the bias values. The Knight-Ruiz normalization algorithm is applied to the modified matrix to compute the bias. The function iteratively removes bins with low interaction counts until a valid bias vector is obtained. The bias vector is expected to have a mean and median close to 1, indicating balanced interaction frequencies across bins.

3.6.4 bandhic.call_tad

`bandhic.call_tad(hic_matrix, resolution, chrom_short, window_size_bp=200000, min_TAD_size=None, stat_filter=True, verbose=False)`

Detect TADs from a Hi-C matrix using the TopDom algorithm. Different from the *TopDom* function, this function accepts a Hi-C matrix in either *band_hic_matrix* format or as a dense numpy array. This function is designed to be used with the BandHiC package and provides a convenient interface for TAD detection.

Parameters

- **hic_matrix** (*band_hic_matrix* or *np.ndarray*) – The Hi-C matrix, either as a *band_hic_matrix* object or a dense numpy array.
- **resolution** (*int*) – The resolution of the Hi-C matrix.
- **chrom_short** (*str*) – The chromosome name without ‘chr’ prefix.
- **window_size_bp** (*int, optional*) – The size of the window to consider for detecting TADs, in base pairs. Default is 200000.
- **min_TAD_size** (*int, optional*) – The minimum size of a TAD to be considered valid, in base pairs. Default is None.
- **stat_filter** (*bool, optional*) – Whether to apply statistical filtering to remove false positives. Default is True.
- **verbose** (*bool, optional*) – Whether to print detailed information during processing. Default is False.

Returns

- **domains** (*pd.DataFrame*) – DataFrame containing detected TADs with columns ‘chr’, ‘from.id’, ‘from.coord’, ‘to.id’, ‘to.coord’, ‘tag’.
- **bins** (*pd.DataFrame*) – DataFrame containing bin information columns ‘id’, ‘chr’, ‘from.coord’, ‘to.coord’, ‘local.ext’, ‘mean.cf’, ‘pvalue’.

3.6.5 bandhic.topdom

`bandhic.topdom(hic_matrix, bins, window_size, stat_filter=True, verbose=False)`

Detect TADs using TopDom algorithm.

Parameters

- **hic_matrix** (*band_hic_matrix* or *np.ndarray*) – The Hi-C matrix, either as a *band_hic_matrix* object or a dense numpy array.
- **bins** (*pd.DataFrame*) – DataFrame containing bin information with columns ‘chr’, ‘from.coord’, ‘to.coord’.
- **window_size** (*int*) – Size of the window to consider for detecting TADs.
- **stat_filter** (*bool, optional*) – Whether to apply statistical filtering to remove false positives. Default is True.
- **verbose** (*bool, optional*) – Whether to print detailed information during processing. Default is False.

Returns

- **domains** (*pd.DataFrame*) – DataFrame containing detected TADs with columns ‘chr’, ‘from.id’, ‘from.coord’, ‘to.id’, ‘to.coord’, ‘tag’.

- **bins** (*pd.DataFrame*) – Updated DataFrame containing bin information with additional columns 'local.ext', 'mean.cf', 'pvalue'.

3.6.6 bandhic.apa

```
bandhic.apa(hic_path, resolution, loops_df, window=10, region_width=6, min_peak_dist=0.0,
            max_peak_dist=8000000, njobs=-1)
```

Compute Aggregate Peak Analysis (APA) around a set of loop anchors.

This is a lightweight Python port of the Juicer/juicebox APA workflow. For each loop (x, y), we extract a (2*window+1)×(2*window+1) cutout centered at (x, y), accumulate cutouts across loops, and report common APA normalizations and region-based summary statistics.

Notes

- Loops are processed per chromosome. For each chromosome, a contact map is loaded from `hic_path` at the requested `resolution` using `bandhic.straw_chr` (with `normalization='KR'` in the current implementation).
- Loop distance filtering is applied in **bin units** after converting loop coordinates to bins. By default, `max_peak_dist` is interpreted as a genomic distance in bp and converted to bins via `resolution`.

Parameters

- **hic_path** (str) – Path to an input .hic file.
- **resolution** (int) – Hi-C bin size in base pairs.
- **loops_df** (DataFrame) – Loop list as a DataFrame (e.g., BEDPE). The current implementation expects at least the columns '#chr1', 'chr2', 'x1', and 'y1' (coordinates in bp). Only intra-chromosomal loops (#chr1 == chr2) are used.
- **window** (int) – Number of bins to include on each side of the loop center; the final cutout size is 2*window+1.
- **region_width** (int) – Corner box size (in bins) used for APA region statistics.
- **min_peak_dist** (float) – Minimum loop distance from the diagonal (in bins, after binning).
- **max_peak_dist** (float) – Maximum loop distance from the diagonal (in bp; converted to bins as `max_peak_dist // resolution` for filtering and matrix loading).
- **njobs** (Optional[int]) – Number of parallel worker processes for loop cutout extraction. -1 uses up to `os.cpu_count()` workers (capped by the number of loops).

Returns

Aggregated APA matrices (raw and normalized), enhancement scores, peak counts, and region-based summary statistics.

Return type

APAResult

3.6.7 bandhic.hiccups

```
bandhic.hiccups(hic_file, chroms, resolutions, fdr=None, peak_width=None, window=None, thresholds=(0.02,
1.5, 1.75, 2.0), centroid_radius=None, max_loop_dist_bp=2000000, kr_neighborhood=5,
matrix_size=512, norm='KR', out_path=None, n_jobs=-1)
```

Run the HiCCUPS loop-calling algorithm on Hi-C data using the BandHiC data structure.

This function provides a high-level interface to a BandHiC-based reimplement of the HiCCUPS algorithm. It supports single- or multi-resolution loop detection across one or more chromosomes and internally applies multiprocessing to accelerate computation on large, high-resolution Hi-C matrices.

Parameters

- **hic_file** (*str*) – Path to the input Hi-C file. Supported formats include .hic, .cool, and .mcool.
- **chroms** (*str or list of str*) – Chromosome name or list of chromosome names (e.g., "chr1" or ["chr1", "chr2"]).
- **resolutions** (*list of int*) – List of bin resolutions (in base pairs) at which HiCCUPS will be executed.
- **fdr** (*list of float or float, optional*) – Target false discovery rate (FDR) for loop detection at each resolution. If a single value is provided, it is applied to all resolutions.
- **peak_width** (*list of int or int, optional*) – Peak half-width (in bins) for each resolution. Defaults follow Juicer recommendations if not specified.
- **window** (*list of int or int, optional*) – Donut window size (in bins) for each resolution. Defaults follow Juicer recommendations if not specified.
- **thresholds** (*list of float, optional*) – Threshold parameters [fdrsum, oe1, oe2, oe3] used for HiCCUPS filtering and cross-resolution merging.
- **centroid_radius** (*list of int or int, optional*) – Radius (in base pairs) for clustering nearby loop pixels into centroids at each resolution.
- **max_loop_dist_bp** (*int, optional*) – Maximum genomic distance (in base pairs) for loop search. Default is 2,000,000 bp.
- **kr_neighborhood** (*int, optional*) – Radius (in bins) used to mask low-quality bins based on the KR normalization vector.
- **matrix_size** (*int, optional*) – Reserved parameter for compatibility; not used in the current implementation.
- **norm** (*str, optional*) – Normalization method to use (e.g., "KR", "VC"). Default is "KR".
- **out_path** (*str, optional*) – Path to write the output loops in BEDPE format. If None, results are not written to disk.
- **n_jobs** (*int, optional*) – Number of parallel worker processes to use. -1 uses all available CPUs.

Returns

loops – List of detected chromatin loops after multi-resolution merging.

Return type

list of Feature2D

3.6.8 bandhic.load_norm_vector_from_hic

`bandhic.load_norm_vector_from_hic(hic_file, chrom, resolution, norm)`

Load a normalization vector from a .hic file for a given chromosome and resolution.

Parameters

- **hic_file** (*str*) – Path to the .hic file.
- **chrom** (*str*) – Chromosome name, e.g., 'chr1' or '1'.
- **resolution** (*int*) – Bin size in base pairs.
- **norm** (*str*) – Normalization method, e.g., 'KR', 'VC', etc.

Returns

Normalization vector for the specified chromosome and resolution.

Return type

np.ndarray

Raises

RuntimeError – If the normalization vector cannot be found for the specified parameters.

3.6.9 bandhic.load_norm_vector_from_cooler

`bandhic.load_norm_vector_from_cooler(cool_path, chrom, resolution, norm)`

Load a normalization vector from a .cool or .mcool file for a given chromosome and resolution.

Parameters

- **cool_path** (*str*) – Path to the .cool or .mcool file.
- **chrom** (*str*) – Chromosome name, e.g., 'chr1'.
- **resolution** (*int*) – Bin size in base pairs.
- **norm** (*str*) – Normalization method, e.g., 'KR', 'VC', etc.

Returns

Normalization vector for the specified chromosome and resolution.

Return type

np.ndarray

Raises

RuntimeError – If the normalization vector cannot be found for the specified parameters.

3.6.10 bandhic.scc

`bandhic.scc(A, B, max_k=None, min_n=10, method='pearson')`

Stratified correlation coefficient (SCC) for Hi-C using BandHiC.

Parameters

- **A** (*band_hic_matrix*) – Two BandHiC matrices (same shape, same diag_num)
- **B** (*band_hic_matrix*) – Two BandHiC matrices (same shape, same diag_num)
- **max_k** (*int*) – Max diagonal (distance bin) to consider
- **min_n** (*int*) – Minimum number of valid pixels per stratum

-
- `method` (`{ "pearson", "spearman" }`) –

Returns

- `scc` (*float*)
- `per_diag` (*dict {k: rho_k}*)

Examples

```
>>> from bandhic import band_hic_matrix
>>> from bandhic import scc
>>> A = band_hic_matrix.straw_chr("example1.hic", "chr1", 10000, diag_num=200)
>>> B = band_hic_matrix.straw_chr("example2.hic", "chr1", 10000, diag_num=200)
>>> scc, per_diag = scc(A, B)
```

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

Symbols

`__array__()` (*bandhic.band_hic_matrix* method), 97
`__array_priority__()` (*bandhic.band_hic_matrix* method), 98
`__bool__()` (*bandhic.band_hic_matrix* method), 100
`__getitem__()` (*bandhic.band_hic_matrix* method), 35
`__hash__()` (*bandhic.band_hic_matrix* method), 99
`__init__()` (*bandhic.band_hic_matrix* method), 25
`__iter__()` (*bandhic.band_hic_matrix* method), 42
`__len__()` (*bandhic.band_hic_matrix* method), 99
`__repr__()` (*bandhic.band_hic_matrix* method), 97
`__setitem__()` (*bandhic.band_hic_matrix* method), 37
`__str__()` (*bandhic.band_hic_matrix* method), 97

A

`absolute()` (*bandhic.band_hic_matrix* method), 55
`absolute()` (*in module bandhic*), 111
`add()` (*bandhic.band_hic_matrix* method), 56
`add()` (*in module bandhic*), 112
`add_mask()` (*bandhic.band_hic_matrix* method), 28
`add_mask_row_col()` (*bandhic.band_hic_matrix* method), 30
`all()` (*bandhic.band_hic_matrix* method), 52
`all()` (*in module bandhic*), 153
`any()` (*bandhic.band_hic_matrix* method), 52
`any()` (*in module bandhic*), 153
`apa()` (*in module bandhic*), 157
`arccos()` (*bandhic.band_hic_matrix* method), 56
`arccos()` (*in module bandhic*), 112
`arccosh()` (*bandhic.band_hic_matrix* method), 57
`arccosh()` (*in module bandhic*), 113
`arcsin()` (*bandhic.band_hic_matrix* method), 57
`arcsin()` (*in module bandhic*), 113
`arcsinh()` (*bandhic.band_hic_matrix* method), 58
`arcsinh()` (*in module bandhic*), 114
`arctan()` (*bandhic.band_hic_matrix* method), 58
`arctan()` (*in module bandhic*), 115
`arctan2()` (*bandhic.band_hic_matrix* method), 59
`arctan2()` (*in module bandhic*), 115
`arctanh()` (*bandhic.band_hic_matrix* method), 60
`arctanh()` (*in module bandhic*), 116

`assert_band_matrix_equal()` (*in module bandhic*), 155
`astype()` (*bandhic.band_hic_matrix* method), 96

B

`band_hic_matrix` (*class in bandhic*), 24
`bin_num` (*bandhic.band_hic_matrix* attribute), 24
`bitwise_and()` (*bandhic.band_hic_matrix* method), 60
`bitwise_and()` (*in module bandhic*), 116
`bitwise_or()` (*bandhic.band_hic_matrix* method), 61
`bitwise_or()` (*in module bandhic*), 117
`bitwise_xor()` (*bandhic.band_hic_matrix* method), 61
`bitwise_xor()` (*in module bandhic*), 117

C

`call_tad()` (*in module bandhic*), 156
`cbrt()` (*bandhic.band_hic_matrix* method), 62
`cbrt()` (*in module bandhic*), 118
`clear_mask()` (*bandhic.band_hic_matrix* method), 31
`clip()` (*bandhic.band_hic_matrix* method), 45
`clip()` (*in module bandhic*), 154
`compute_bin_bias()` (*in module bandhic*), 155
`conj()` (*bandhic.band_hic_matrix* method), 62
`conj()` (*in module bandhic*), 119
`conjugate()` (*bandhic.band_hic_matrix* method), 63
`conjugate()` (*in module bandhic*), 119
`cooler_all_chrs()` (*in module bandhic*), 109
`cooler_chr()` (*in module bandhic*), 108
`copy()` (*bandhic.band_hic_matrix* method), 96
`cos()` (*bandhic.band_hic_matrix* method), 63
`cos()` (*in module bandhic*), 120
`cosh()` (*bandhic.band_hic_matrix* method), 64
`cosh()` (*in module bandhic*), 120
`count_in_band()` (*bandhic.band_hic_matrix* method), 33
`count_in_band_masked()` (*bandhic.band_hic_matrix* method), 32
`count_masked()` (*bandhic.band_hic_matrix* method), 32
`count_out_band()` (*bandhic.band_hic_matrix* method), 34

`count_out_band_masked()` (*bandhic.band_hic_matrix method*), 33
`count_unmasked()` (*bandhic.band_hic_matrix method*), 32

D

`data` (*bandhic.band_hic_matrix attribute*), 24
`default_value` (*bandhic.band_hic_matrix attribute*), 25
`deg2rad()` (*bandhic.band_hic_matrix method*), 64
`deg2rad()` (*in module bandhic*), 121
`degrees()` (*bandhic.band_hic_matrix method*), 65
`degrees()` (*in module bandhic*), 121
`diag()` (*bandhic.band_hic_matrix method*), 40
`diag_num` (*bandhic.band_hic_matrix attribute*), 24
`divide()` (*bandhic.band_hic_matrix method*), 65
`divide()` (*in module bandhic*), 122
`divmod()` (*bandhic.band_hic_matrix method*), 66
`divmod()` (*in module bandhic*), 122
`drop_mask()` (*bandhic.band_hic_matrix method*), 29
`drop_mask_row_col()` (*bandhic.band_hic_matrix method*), 31
`dtype` (*bandhic.band_hic_matrix attribute*), 24
`dump()` (*bandhic.band_hic_matrix method*), 100

E

`equal()` (*bandhic.band_hic_matrix method*), 67
`equal()` (*in module bandhic*), 123
`exp()` (*bandhic.band_hic_matrix method*), 67
`exp()` (*in module bandhic*), 124
`exp2()` (*bandhic.band_hic_matrix method*), 68
`exp2()` (*in module bandhic*), 124
`expm1()` (*bandhic.band_hic_matrix method*), 68
`expm1()` (*in module bandhic*), 125
`extract_row()` (*bandhic.band_hic_matrix method*), 41
`eye()` (*in module bandhic*), 102
`eye_like()` (*in module bandhic*), 104

F

`fabs()` (*bandhic.band_hic_matrix method*), 69
`fabs()` (*in module bandhic*), 125
`filled()` (*bandhic.band_hic_matrix method*), 44
`float_power()` (*bandhic.band_hic_matrix method*), 69
`float_power()` (*in module bandhic*), 126
`floor_divide()` (*bandhic.band_hic_matrix method*), 70
`floor_divide()` (*in module bandhic*), 126
`fmod()` (*bandhic.band_hic_matrix method*), 70
`fmod()` (*in module bandhic*), 127
`full()` (*in module bandhic*), 102
`full_like()` (*in module bandhic*), 104

G

`gcd()` (*bandhic.band_hic_matrix method*), 71

`gcd()` (*in module bandhic*), 128
`get_mask()` (*bandhic.band_hic_matrix method*), 28
`get_mask_row_col()` (*bandhic.band_hic_matrix method*), 31
`get_values()` (*bandhic.band_hic_matrix method*), 39
`greater()` (*bandhic.band_hic_matrix method*), 72
`greater()` (*in module bandhic*), 128
`greater_equal()` (*bandhic.band_hic_matrix method*), 72
`greater_equal()` (*in module bandhic*), 129

H

`heaviside()` (*bandhic.band_hic_matrix method*), 73
`heaviside()` (*in module bandhic*), 129
`hiccups()` (*in module bandhic*), 158
`hypot()` (*bandhic.band_hic_matrix method*), 73
`hypot()` (*in module bandhic*), 130

I

`init_mask()` (*bandhic.band_hic_matrix method*), 27
`invert()` (*bandhic.band_hic_matrix method*), 74
`invert()` (*in module bandhic*), 131
`itercols()` (*bandhic.band_hic_matrix method*), 43
`iterrows()` (*bandhic.band_hic_matrix method*), 43
`iterwindows()` (*bandhic.band_hic_matrix method*), 42

L

`lcm()` (*bandhic.band_hic_matrix method*), 74
`lcm()` (*in module bandhic*), 131
`left_shift()` (*bandhic.band_hic_matrix method*), 75
`left_shift()` (*in module bandhic*), 132
`less()` (*bandhic.band_hic_matrix method*), 76
`less()` (*in module bandhic*), 132
`less_equal()` (*bandhic.band_hic_matrix method*), 76
`less_equal()` (*in module bandhic*), 133
`load_norm_vector_from_cooler()` (*in module bandhic*), 159
`load_norm_vector_from_hic()` (*in module bandhic*), 159
`load_npz()` (*in module bandhic*), 106
`log()` (*bandhic.band_hic_matrix method*), 77
`log()` (*in module bandhic*), 134
`log10()` (*bandhic.band_hic_matrix method*), 78
`log10()` (*in module bandhic*), 135
`log1p()` (*bandhic.band_hic_matrix method*), 77
`log1p()` (*in module bandhic*), 134
`log2()` (*bandhic.band_hic_matrix method*), 78
`log2()` (*in module bandhic*), 135
`logaddexp()` (*bandhic.band_hic_matrix method*), 79
`logaddexp()` (*in module bandhic*), 136
`logaddexp2()` (*bandhic.band_hic_matrix method*), 79
`logaddexp2()` (*in module bandhic*), 136
`logical_and()` (*bandhic.band_hic_matrix method*), 80
`logical_and()` (*in module bandhic*), 137

`logical_or()` (*bandhic.band_hic_matrix* method), 80
`logical_or()` (in module *bandhic*), 138
`logical_xor()` (*bandhic.band_hic_matrix* method), 81
`logical_xor()` (in module *bandhic*), 138

M

`mask` (*bandhic.band_hic_matrix* attribute), 25
`mask_row_col` (*bandhic.band_hic_matrix* attribute), 25
`matrix_equal()` (in module *bandhic*), 154
`max()` (*bandhic.band_hic_matrix* method), 47
`max()` (in module *bandhic*), 152
`maximum()` (*bandhic.band_hic_matrix* method), 82
`maximum()` (in module *bandhic*), 139
`mean()` (*bandhic.band_hic_matrix* method), 48
`mean()` (in module *bandhic*), 152
`memory_usage()` (*bandhic.band_hic_matrix* method), 98
`min()` (*bandhic.band_hic_matrix* method), 46
`min()` (in module *bandhic*), 152
`minimum()` (*bandhic.band_hic_matrix* method), 82
`minimum()` (in module *bandhic*), 139
`mod()` (*bandhic.band_hic_matrix* method), 83
`mod()` (in module *bandhic*), 140
`multiply()` (*bandhic.band_hic_matrix* method), 83
`multiply()` (in module *bandhic*), 141

N

`negative()` (*bandhic.band_hic_matrix* method), 84
`negative()` (in module *bandhic*), 141
`normalize()` (*bandhic.band_hic_matrix* method), 53
`normalize()` (in module *bandhic*), 154
`not_equal()` (*bandhic.band_hic_matrix* method), 84
`not_equal()` (in module *bandhic*), 142

O

`ones()` (in module *bandhic*), 101
`ones_like()` (in module *bandhic*), 103

P

`positive()` (*bandhic.band_hic_matrix* method), 85
`positive()` (in module *bandhic*), 142
`power()` (*bandhic.band_hic_matrix* method), 86
`power()` (in module *bandhic*), 143
`prod()` (*bandhic.band_hic_matrix* method), 50
`prod()` (in module *bandhic*), 153
`ptp()` (*bandhic.band_hic_matrix* method), 51
`ptp()` (in module *bandhic*), 153

R

`rad2deg()` (*bandhic.band_hic_matrix* method), 86
`rad2deg()` (in module *bandhic*), 143
`radians()` (*bandhic.band_hic_matrix* method), 87
`radians()` (in module *bandhic*), 144

`reciprocal()` (*bandhic.band_hic_matrix* method), 87
`reciprocal()` (in module *bandhic*), 144
`remainder()` (*bandhic.band_hic_matrix* method), 88
`remainder()` (in module *bandhic*), 145
`right_shift()` (*bandhic.band_hic_matrix* method), 88
`right_shift()` (in module *bandhic*), 146
`rint()` (*bandhic.band_hic_matrix* method), 89
`rint()` (in module *bandhic*), 146

S

`save_npz()` (in module *bandhic*), 105
`scc()` (in module *bandhic*), 159
`set_diag()` (*bandhic.band_hic_matrix* method), 41
`set_values()` (*bandhic.band_hic_matrix* method), 39
`shape` (*bandhic.band_hic_matrix* attribute), 24
`sign()` (*bandhic.band_hic_matrix* method), 89
`sign()` (in module *bandhic*), 147
`sin()` (*bandhic.band_hic_matrix* method), 90
`sin()` (in module *bandhic*), 147
`sinh()` (*bandhic.band_hic_matrix* method), 90
`sinh()` (in module *bandhic*), 148
`sqrt()` (*bandhic.band_hic_matrix* method), 91
`sqrt()` (in module *bandhic*), 148
`square()` (*bandhic.band_hic_matrix* method), 91
`square()` (in module *bandhic*), 149
`std()` (*bandhic.band_hic_matrix* method), 49
`std()` (in module *bandhic*), 153
`straw_all_chrs()` (in module *bandhic*), 107
`straw_chr()` (in module *bandhic*), 106
`subtract()` (*bandhic.band_hic_matrix* method), 92
`subtract()` (in module *bandhic*), 149
`sum()` (*bandhic.band_hic_matrix* method), 48
`sum()` (in module *bandhic*), 152

T

`tan()` (*bandhic.band_hic_matrix* method), 92
`tan()` (in module *bandhic*), 150
`tanh()` (*bandhic.band_hic_matrix* method), 93
`tanh()` (in module *bandhic*), 150
`tocoo()` (*bandhic.band_hic_matrix* method), 95
`tocsr()` (*bandhic.band_hic_matrix* method), 95
`todense()` (*bandhic.band_hic_matrix* method), 94
`topdom()` (in module *bandhic*), 156
`true_divide()` (*bandhic.band_hic_matrix* method), 93
`true_divide()` (in module *bandhic*), 151

U

`unmask()` (*bandhic.band_hic_matrix* method), 29

V

`var()` (*bandhic.band_hic_matrix* method), 50
`var()` (in module *bandhic*), 153

Z

`zeros()` (*in module bandhic*), [101](#)

`zeros_like()` (*in module bandhic*), [103](#)