



133 views Dec 18, 2025

Introduction to Computer Vision (2025-2)

Korea University

Prof. Gyeongsik Moon

Lecture slides: <https://drive.google.com/drive/folder...>

References: <https://drive.google.com/drive/folder...>

INTRODUCTION TO COMPUTER VISION

Lecture 19 – Vision-Language-Action (VLA) Models

Gyeongsik Moon

Visual Computing and AI Lab

Korea University


Robot Training with RL



`sim_output = []`

1. In the physics-based simulator run below loop: for t in $\text{range}(T)$
 1. Forward state (robot's current position/rotation and target position) to the policy network
 2. The policy network outputs an action from the input state
 3. `sim_output.append({'state': input_state, 'action': action})`
 4. Apply the action using a PD controller
 5. Obtain updated robot's current state
2. Compute reward (high much close to the target) for all elements in `sim_output`
3. For some elements in `sim_output`, increase probability of the output action with high reward

Robot Training with RL



`sim_output = []`

Roll out

1. In the physics-based simulator run below loop: for t in $\text{range}(T)$
 1. Forward state (robot's current position/rotation and target position) to the policy network
 2. The policy network outputs an action from the input state
 3. `sim_output.append({'state': input_state, 'action': action})`
 4. Apply the action using a PD controller
 5. Obtain updated robot's current state
2. Compute reward (high much close to the target) for all elements in `sim_output`
3. For some elements in `sim_output`, increase probability of the output action with high reward

Robot Training with RL

`sim_output = []`

1. In the physics-based simulator run below loop: for t in range(T)
 1. Forward state (robot's current position/rotation and target position) to the policy network
 2. The policy network outputs an action from the input state
 3. `sim_output.append({'state': input_state, 'action': action})`
 4. Apply the action using a PD controller
 5. Obtain updated robot's current state
2. Compute reward (high much close to the target) for all elements in `sim_output`
3. For some elements in `sim_output`, increase probability of the output action with high reward **Loss function**

Robot Training with RL


- There are two problems
1. Roll out
 - Too slow
 - We need to run for loop in physics simulator
 - That makes the training really slow
 2. Loss function
 - No explicit target for the output action
 - RL: "do the estimated action with high reward again!"
 - Supervised learning: "do the 'target' action instead of the estimated action!"

Why Reinforcement Learning?

- If you're in the two situations, you can try RL
 - Infeasible data collection
 - Non-differentiable output function
- Representative examples are agents in video game and robots

Vision-language-action (VLA) models

- The good points of RL becomes limitations of RL at the same time
- How to solve this?
 - Vision-language-action (VLA) models




Vision-language-action (VLA) models

- Use supervised learning instead of RL for the robot training
- How to get data?

Real robot data (teleoperations)




RL in physics simulators (we've learned so far)



Teleoperations

- Use real robots to collect data
- Humans control robots to get robot trajectories
- Costly and hard to scale up




Teleoperations

- Use real robots to collect data
- Humans control robots to get robot trajectories
- Costly and hard to scale up



RL in Physics Simulators

- Use RL for each task instead of building a universal policy network
- For example, train a policy network with RL only for hand-obj grasp
- In this way, we can avoid scale-up issue of RL
- Sim2Real gap: Gap between simulation environments and real worlds




Vision-language-action (VLA) models

- Use supervised learning instead of RL for the robot training
- *Now, we have data (pairs of (state, action))*
- $\text{Loss} = \text{distance}(\text{net}(\text{state}) - \text{action_target})$
- No roll out
- With explicit target

This is also called **behavior cloning** for **imitation learning**.

Vision-language-action (VLA) models



processed into a sequence of tokens, OpenVLA is trained with a standard next-token prediction objective, evaluating the cross-entropy loss on the predicted action tokens only. We discuss key design decisions for implementing this training procedure in Section 3.4. Next, we describe the robot dataset we use for OpenVLA training.

I guess he's Korean...? He's a Ph.D. candidate in Stanford!

[1] Kim, Moo Jin, et al. "OpenVLA: An open-source vision-language-action model." CoRL. 2024.


OpenVLA has no diffusion or generative modeling

Vision-language-action (VLA) models

π_0 : A Vision-Language-Action Flow Model for General Robot Control

Physical Intelligence

Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Lucy Xiaoyang Shi, James Tanner, Quan Vuong, Anna Walling, Haohuan Wang, Ury Zhilinsky
<https://physicalintelligence.company/blog/pi0>




- Combination of VLA model and diffusion generative models
- Denoise action conditioned on image, language, and robot state

Robotic Foundation Models (fancy name of VLA)




RT-1 (Dec. 2022)




RT-X (Oct. 2023)



Pi-Zero (Oct. 2024)



RT-2 (Jul. 2023)




OpenVLA (Jun. 2024)

Helix (Figure)
Hi-Robot (PI)
Gemini Robotics
Pi-0.5 (PI)
GR00T (Nvidia)


Robotic Foundation Models (fancy name of VLA)




RT-1 (Dec. 2022)




RT-X (Oct. 2023)



Pi-Zero (Oct. 2024)



RT-2 (Jul. 2023)



OpenVLA (Jun. 2024)


Helix (Figure)
Hi-Robot (PI)
Gemini Robotics
Pi-0.5 (PI)
GR00T (Nvidia)
DYNA-1
...

Pi-Zero by Physical Intelligence

<https://www.physicalintelligence.company/blog/pi0>




Pi-Zero by Physical Intelligence



Pi-Zero by Physical Intelligence




Pi-Zero by Physical Intelligence




Pi-Zero by Physical Intelligence

문경식




Pi-Zero by Physical Intelligence

문경식



Pi-Zero by Physical Intelligence



Pi-Zero by Physical Intelligence

Physical Intelligence (π)

Open Sourcing π_0

Published February 4, 2025
 Email research@physicalintelligence.company
 Repo [Physical-Intelligence/openpi](https://github.com/Physical-Intelligence/openpi)

README
Apache-2.0 license

openpi

openpi holds open-source models and packages for robotics, published by the [Physical Intelligence team](#).

Currently, this repo contains two types of models:

- the [π₀ model](#), a flow-based diffusion vision-language-action model (VLA)
- the [π₀-FAST model](#), an autoregressive VLA, based on the FAST action tokenizer.

For both models, we provide *base model* checkpoints, pre-trained on 10k+ hours of robot data, and examples for using them out of the box or fine-tuning them to your own datasets.

This is an experiment: π_0 was developed for our own robots, which differ from the widely used platforms such as [ALOHA](#) and [DROID](#), and though we are optimistic that researchers and practitioners will be able to run creative new experiments adapting π_0 to their own platforms, we do not expect every such attempt to be successful. All this is to say: π_0 may or may not work for you, but you are welcome to try it and see!


Evaluation of the Robot Learning Models

문경식

- Evaluation is primarily conducted in the real world
- Real-world evaluation is costly and noisy
 - "We have large enough budget such that we can still make progress."
- Weak correlation between training loss and real-world success rate.
 - Training objectives vs task-specific metrics, training vs testing horizons



ALOHA 2



Evaluation of the Robot Learning Models

문경식

What about evaluation in simulation?


- Sim-to-real gap: rigid / deformable / cloth
- Efficient asset generation
- Digitalization of the real world
- Procedural generation of realistic and diverse scenes
- Correlation between sim and real

Imagenet in
Embodied AI?



Habitat 3.0


Robotic Foundation Model + World Models




World Models



1X World Models




DayDreamer



Nvidia Cosmos - World Foundation Model

- ☐ 3D?
- ☐ Structural Prior?
- ☐ Learning + Physics?



Foundation Models for Embodied Agents



- Current foundation models are not tailored for embodied agents
 - LLM/VLM can fail in embodied-related tasks
 - Limited understanding of geometric / embodied / physical interactions
 - Reinforcement learning (RL) from human feedback → RL from [Embodied Feedback](#)




GPT



Segment Anything



DINO




Adaptation / Life-Long Learning

- Adapt to new scenarios
- Adapt to human preferences
- Self improve / life-long learning



Adapt to new scenarios



Adapt to human preferences



Improve