

GraphRAG methods to create optimized LLM context windows for Retrieval – Jonathan Larson, Microsoft



AI Engineer
243K subscribers

Subscribe

59



Share

Ask

Download



1,665 views Jun 27, 2025 [AIEWF 2025 Complete Playlist](#)

Jonathan Larson is a Senior Principal Data Architect at Microsoft Research working in Special Projects. He currently leads a research team focused on the intersection of graph machine learning, LLM memory representations, and LLM orchestration.

His research has led to shipping new features in Bing, Viva, PowerBI. He also shipped new tools to combat tech fraud. Many of the supporting libraries have been open sourced in collaboration on GitHub. Prior to joining Microsoft, Jonathan was Chief Scientist and Technical Fellow at Sotera Defense Solutions on assignment to DARPA, and led a variety of research across several programs. Jonathan has also led large-scale data science efforts at Google, Zillow, and the US Army. Early in his career, he also worked several startups and incubators.

About Jonathan Larson

Jonathan Larson is a Senior Principal Data Architect at Microsoft Research working in Special Projects. He currently leads a research team focused on the intersection of graph machine learning, LLM memory representations, and LLM orchestration.

GraphRAG

LLM-Derived Knowledge Graphs for Retrieval
Augmented Generation

June 4th, 2025

Jonathan Larson

Microsoft Research

b.com/microsoft/graphrag

From Local to Global: A GraphRAG Approach to Query-Focused Summarization

Darren Edge^{1†} Ha Trinh^{1†} Newman Cheng² Joshua Bradley² Alex Chao³

Apurva Mody³ Steven Truitt² Dasha Metropolitanansky¹ Robert Osazuwa Ness¹

Jonathan Larson¹

¹Microsoft Research

²Microsoft Strategic Missions and Technologies

³Microsoft Office of the CTO

{daedge,trinhha,newmancheng,joshbradley,achao,moapurva,
steventruitt,dasham,robertness,jolarso}@microsoft.com

[†]These authors contributed equally to this work

Abstract

The use of retrieval-augmented generation (RAG) to retrieve relevant information from an external knowledge source enables large language models (LLMs) to answer questions over private and/or previously unseen document collections. However, RAG fails on global questions directed at an entire text corpus, such as “What are the main themes in the dataset?”, since this is inherently a query-focused summarization (QFS) task, rather than an explicit retrieval task. Prior QFS methods, meanwhile, do not scale to the quantities of text indexed by typical RAG systems. To combine the strengths of these contrasting methods, we propose *GraphRAG*, a graph-based approach to question answering over private

main 35 Branches 25 Tags

Go to file

Code

About

A modular graph-based Retrieval-Augmented Generation (RAG) system

microsoft.github.io/graphrag/

gpt rag gpt-4 gpt4 llm llms graphrag

Readme MIT license Code of conduct Security policy Activity Custom properties 25.5k stars 175 watching 2.6k forks Report repository

Releases 25

v2.3.0 Latest 5 days ago

+ 24 releases

Packages

No packages published

Inspired many other offerings, books, and games

- [Neo4j-graphrag-python](#)
- [Llamaindex graphrag](#)
- [Graphrag-lite](#)
- [Nano-graphrag](#)
- [Fast-graphrag](#)
- [Langchain-graphrag](#)
- [Tiny-graphrag](#)
- [LightRAG](#)
- [GraphRAG Local UI](#)
- [infiniflow/ragflow](#)

Microsoft Supercharges RAG with Knowledge Graphs



GraphRAG - The Card Game

ChrisOwen, Director of Engineering, Microsoft



New Horizons!

LLM memory with structure is a key enabler

- New Vertical: GraphRAG for Code
- **New OSS Release Today: BenchmarkQED**
- LazyGraphRAG Results
 - New Benchmarks
 - Azure Local
 - LazyGraphRAG for Science

GraphRAG for Code - Repo Understanding *An Example*


Terminal based Python game where the player earns points by avoiding obstacles and loses points if they collide.

- LLM has never seen this code before
- Small enough for human to know holistically for ground truth
- Complex enough that the LLM couldn't reason well over it
- ~200 lines of code across 7 files



Regular RAG – Q&A


“Describe what the application is and how it works.”



The application is designed as a game that is configured and initiated through a main function. The game leverages a configuration file and has its main components, such as the game screen and game logic, encapsulated in separate classes and functions.



GraphRAG for Code – Q&A

“Describe what the application is and how it works.”



GraphRAG for Code - Translation

- Simply including all code directly in the context window fails
- Python -> Rust
 - Involved language specific libraries (E.g. curses)
 - Game codebase uses abstract classes
 - Rust has highly different semantics than Python
- Building Rust codebase generated **complete working code out of the box**



```
EXPLORER
├── .venv
├── terminal_jumper
│   ├── __pycache__
│   ├── __init__.py
│   ├── __main__.py
│   ├── background.py
│   ├── config.py
│   ├── game.py
│   ├── obstacle.py
│   ├── player.py
│   ├── ui_element.py
│   ├── __init__.py
│   ├── .coverage
│   ├── .gitignore
│   ├── Dockerfile
│   ├── poetry.lock
│   ├── pyproject.toml
│   └── README.md
├── ui_element.py
├── player.py
├── obstacle.py
└── game.py

terminal_jumper > player.py > ...
6 class Player(UIElement):
31 def jump(self) -> None:
35     self._jump_offset = 0
36
37 def update(self):
38     x, y = self.positions_to_render[0]
39
40     if self._is_jumping:
41         self._jump_offset += self._jump_direction
42
43         if self._jump_offset == -1 * self._player_config.max_jump_height:
44             self._jump_direction = 1
45         elif self._jump_offset == 0:
46             self._is_jumping = False
47             self._jump_direction = -1
48
49         y = self._base_y + self._jump_offset
50     else:
51         y = self._base_y
52
53     self.positions_to_render[0] = (x, y)
54
55
56
```

```
EXPLORER
├── .venv
├── terminal_jumper
│   ├── __pycache__
│   ├── __init__.py
│   ├── __main__.py
│   ├── background.py
│   ├── config.py
│   ├── game.py
│   ├── obstacle.py
│   ├── player.py
│   ├── ui_element.py
│   ├── __init__.py
│   ├── .coverage
│   ├── .gitignore
│   ├── Dockerfile
│   ├── poetry.lock
│   ├── pyproject.toml
│   └── README.md
├── ui_element.py
├── player.py
├── obstacle.py
└── game.py

terminal_jumper > obstacle.py > ...
3
4 from .config import ObstaclesConfig, ScreenConfig
5 from .ui_element import UIElement
6
7
8 class Obstacle(UIElement):
9     def __init__(
10         self, *, screen_config: ScreenConfig, obstacle_config: ObstaclesConfig
11     ) -> None:
12         self._obstacle_config = obstacle_config
13
14         self._base_x = screen_config.max_x
15         self._base_y = screen_config.max_y
16         self.x_width = random.randint(1, obstacle_config.max_width)
17         self.y_width = random.randint(1, obstacle_config.max_height)
18
19         self.screen_config = screen_config
20         self.render_character = obstacle_config.render_character
21         self.positions_to_render = self._create_positions_to_render()
22
23     def _create_positions_to_render(self) -> list[tuple[int, int]]:
24         return [
25             (x, y)
26             for x in range(self._base_x, self._base_x + self.x_width)
27             for y in range(self._base_y - self.y_width, self._base_y)
28         ]
29
30     def update(self) -> None:
31         self._base_x -= self._obstacle_config.speed
32         self.positions_to_render = self._create_positions_to_render()
33
```

```
EXPLORER
├── .venv
├── terminal_jumper
│   ├── __pycache__
│   ├── __init__.py
│   ├── __main__.py
│   ├── background.py
│   ├── config.py
│   ├── game.py
│   ├── obstacle.py
│   ├── player.py
│   ├── ui_element.py
│   ├── __init__.py
│   ├── .coverage
│   ├── .gitignore
│   ├── Dockerfile
│   ├── poetry.lock
│   ├── pyproject.toml
│   └── README.md
├── ui_element.py
├── player.py
├── obstacle.py
└── game.py

terminal_jumper > game.py > ...
1 # Copyright (c) 2024 Microsoft Corporation.
2 import curses
3 import random
4 import time
5
6 from .background import Background
7 from .config import GameConfig, ScreenConfig
8 from .obstacle import Obstacle
9 from .player import Player
10 from .ui_element import check_collision
11
12
13 class Game:
14     def __init__(self, screen: curses.window, *, config: GameConfig):
15         self._config = config
16         self._screen = screen
17
18         self._background = Background(
19             screen_config=config.screen,
20             background_config=config.background,
21         )
22
23         self._player = Player(
24             screen_config=config.screen,
25             player_config=config.player,
26         )
27
28         self._obstacles: list[Obstacle] = []
29
30         self._score = 0
31
32     def run(self):
33         try:
34             while True:
35                 self._handle_input()
36                 self._update()
37                 self._render()
38
```

09:12:12

```
docker docker build -t terminal_jumper_python . && docker run --rm -it terminal_jumper_python
[+] Building 0.3s (1/2)
=> [internal] load build definition from Dockerfile
=> transferring dockerfile: 331B
=> [internal] load metadata for docker.io/library/python:3.10-slim
```



prompt.txt X

Users > rracnicol > Desktop > prompt.txt

```
1 You are a coding expert, and your job is to translate code from a Python project into the Rust version of
2 that project.
3 In this code translation task, you are presented with the original source code, and you need to translate it
4 respecting the following rules:
5 1. Output only the raw code; we should be able to directly copy and paste the output to a Python file.
6 3. Add comments in the output code to explain it.
7 3. Try to follow the implementation in the source code, but make adjustments as needed as the change in
8 language, dependencies, and specifications require.
9 Also, follow this specification to perform the translation:
10 1. Translate a Python terminal game using curses into Rust utilizing the crossterm library. 2. Ensure the
11 functionality remains intact while conforming to Rust idioms.
12 3. Replace the Python curses library with Rust's crossterm library, adapting the code accordingly.
13 4. Employ the latest version of the crossterm API.
14 All these rules and specifications should be used to rewrite and adapt the code into a new Rust
15 implementation, according to the given specification.
16
17 The code to be translated is:
18
19 '''python
20 import curses
21 import random
22 import time
23 from abc import ABC, abstractmethod
24 from dataclasses import dataclass, field
25
26 @dataclass
27 class ScreenConfig:
28     width: int = 80
29     height: int = 30
30     margin: int = 2
```

Chat playground

Start with a sample prompt

- Recipe creation**
Need a recipe for a dish that combines
Roses from two different cuisines.
- Historical fiction**
Write a scene set in ancient Rome,
focusing on the daily life of a common
citizen.
- Poetry generation**
Compose a poem about the beauty of
nature in autumn.

prompt.txt X

Users > rracnicol > Desktop > prompt.txt

```
217 class Game:
218     def __render__(self):
219         self._player.render(self._screen)
220         for obstacle in self._obstacles:
221             obstacle.render(self._screen)
222         self._screen.addstr(0, 0, f"Score: {self._score}")
223         self._screen.refresh()
224
225 def main():
226     config = GameConfig()
227
228     def run(screen: curses.window) -> curses.window:
229         curses.curs_set(0)
230         screen.nodelay(True)
231         screen.resize(config.screen.height, config.screen.width)
232         game = Game(screen, config=GameConfig())
233         game.run()
234         curses.wrapper(run)
235
236 if __name__ == "__main__":
237     main()
238
239 Now output the translated code to rust.
```

Chat playground

```
'''python
import curses
import random
import time
from abc import ABC, abstractmethod
from dataclasses import dataclass, field

@dataclass
class ScreenConfig:
    width: int = 80
    height: int = 30
    margin: int = 2

class Game:
    def __render__(self):
        self._player.render(self._screen)
        for obstacle in self._obstacles:
            obstacle.render(self._screen)
        self._screen.addstr(0, 0, f"Score: {self._score}")
        self._screen.refresh()

def main():
    config = GameConfig()

    def run(screen: curses.window) -> curses.window:
        curses.curs_set(0)
        screen.nodelay(True)
        screen.resize(config.screen.height, config.screen.width)
        game = Game(screen, config=GameConfig())
        game.run()
        curses.wrapper(run)

if __name__ == "__main__":
    main()

Now output the translated code to rust.'''
```

```
main.rs 9+ X
src > main.rs > ...
327 impl<W: Write> Game<W> {
383     fn render(&mut self) {
396         } Result<(), Error>
397         .unwrap();
398
399         self.stdout.flush().unwrap();
400     }
401 } impl Game<W>
402
▶ Run | Debug
403 fn main() {
404     let config: GameConfig = GameConfig::new();
405     let stdout: Stdout = stdout();
406     let mut stdout: StdoutLock<'static> = stdout.lock();
407     execute!(stdout, terminal::EnterAlternateScreen).unwrap();
408     terminal::enable_raw_mode().unwrap();
409
410     let mut game: Game<StdoutLock<'static>> = Game::new(stdout, config);
411
412     game.run();
413
414     execute!(
415         game.stdout,
416         terminal::LeaveAlternateScreen,
417         cursor::Show
418     ) Result<(), Error>
419     .unwrap();
420     terminal::disable_raw_mode().unwrap();
```

Code	Message	File	Source
rustc[Click for full co...	use of moved value: `player_config` value used here after move	src/main.rs [Ln 197, Col 31]	rustc
rustc[Click for full co...	use of moved value: `obstacle_config` value used here after move	src/main.rs [Ln 273, Col 31]	rustc
rustc[Click for full co...	no field `positions_to_render` on type `&impl UIElement` unknown field	src/main.rs [Ln 310, Col 33]	rustc
rustc[Click for full co...	no field `positions_to_render` on type `&impl UIElement` unknown field	src/main.rs [Ln 311, Col 22]	rustc
rustc[Click for full co...	no method named `clone` found for struct `ScreenConfig` in the current scope items from tra...	src/main.rs [Ln 332, Col 55]	rustc
rustc[Click for full co...	no method named `clone` found for struct `BackgroundConfig` in the current scope items fro...	src/main.rs [Ln 332, Col 82]	rustc
rustc[Click for full co...	no method named `clone` found for struct `ScreenConfig` in the current scope items from tra...	src/main.rs [Ln 333, Col 47]	rustc
rustc[Click for full co...	no method named `clone` found for struct `PlayerConfig` in the current scope items from trail...	src/main.rs [Ln 333, Col 70]	rustc
rustc[Click for full co...	no method named `clone` found for mutable reference `&mut Obstacle` in the current scope i...	src/main.rs [Ln 370, Col 45]	rustc
rustc[Click for full co...	no method named `clone` found for struct `ScreenConfig` in the current scope items from tra...	src/main.rs [Ln 377, Col 36]	rustc
rustc[Click for full co...	no method named `clone` found for struct `ObstaclesConfig` in the current scope items from...	src/main.rs [Ln 378, Col 39]	rustc
rustc[Click for full co...	unused import: `ExecutableCommand` `#[warn(unused_imports)]` on by default	src/main.rs [Ln 6, Col 5]	rustc

```
terminal_jumper  .dingcode4llm  _l_jumper_rust
+ code4llm git:(feature/unit-test-generation) x uv run poe translate --code ./tests/integration/terminal_jumper --source pyt
hon --target rust --output ../terminal_jumper_rust/src --index output/terminal_jumper_index_structured _
```

```
terminal_jumper  python -m uv run poe translate --code ./tests/integration/terminal_jumper --source python --target rust --output ../term
inal_jumper_rust/src --index output/terminal_jumper_index_structured
+ code4llm git:(feature/unit-test-generation) x uv run poe translate --code ./tests/integration/terminal_jumper --source pyt
hon --target rust --output ../terminal_jumper_rust/src --index output/terminal_jumper_index_structured
Poe => python -m code4llm.translate --code ./tests/integration/terminal_jumper --source python --target rust --output ../term
inal_jumper_rust/src --index output/terminal_jumper_index_structured
```



```

namespace",
"import",
"preprocessor",
"error"
}
},
"debug": {
"verbose": false,
"generate_astred_digest": true
}
}
creating llm client with azure=True, key=0, base=https://resilience-aoai-brazilsouth.openai.azure.com/, version=2024-05-01-pr
view, model=gpt-4o, deployment=gpt-4o
No environment configuration found.
ManagedIdentityCredential will use IMDS
Translating code from python to rust, target path=/Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src
Writing files to /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src: 0%|          | 0/7 [00:00<?, ?it/s]
[1/7] translating terminal_jumper/config.py (python) to terminal_jumper/config.rs (rust): dependencies=[]
[1/7] translation of terminal_jumper/config.py [python] to terminal_jumper/config.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/config.rs
[2/7] translating terminal_jumper/ui_element.py (python) to terminal_jumper/ui_element.rs (rust): dependencies=['terminal_jum
per/config.py']
[2/7] translation of terminal_jumper/ui_element.py [python] to terminal_jumper/ui_element.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/ui_element.rs
[3/7] translating terminal_jumper/obstacle.py (python) to terminal_jumper/obstacle.rs (rust): dependencies=['terminal_jumper/
ui_element.py', 'terminal_jumper/config.py']
[3/7] translation of terminal_jumper/obstacle.py [python] to terminal_jumper/obstacle.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/obstacle.rs
[4/7] translating terminal_jumper/player.py (python) to terminal_jumper/player.rs (rust): dependencies=['terminal_jumper/ui_e
lement.py', 'terminal_jumper/config.py']
[4/7] translation of terminal_jumper/player.py [python] to terminal_jumper/player.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/player.rs
[5/7] translating terminal_jumper/background.py (python) to terminal_jumper/background.rs (rust): dependencies=['terminal_jum
per/ui_element.py', 'terminal_jumper/config.py']
[5/7] translation of terminal_jumper/background.py [python] to terminal_jumper/background.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/background.rs
[6/7] translating terminal_jumper/game.py (python) to terminal_jumper/game.rs (rust): dependencies=['terminal_jumper/config.p
y', 'terminal_jumper/background.py', 'terminal_jumper/player.py', 'terminal_jumper/obstacle.py', 'terminal_jumper/ui_element.
py']
[6/7] translation of terminal_jumper/game.py [python] to terminal_jumper/game.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/game.rs
[7/7] translating terminal_jumper/__main__.py (python) to terminal_jumper/main.rs (rust): dependencies=['terminal_jumper/conf
ig.py', 'terminal_jumper/game.py']
[7/7] translation of terminal_jumper/__main__.py [python] to terminal_jumper/main.rs [rust] DONE
Writing /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src/main.rs
Writing files to /Users/rracanizzi/Coding/recording/code4llm/./terminal_jumper_rust/src: 100%|█| 7/7 [00:00:00.000 272.15it/

```

EXPLORER

... ui_element.rs X


TERMINAL_JUMPER_RUST

- src
 - background.rs
 - config.rs
 - game.rs
 - main.rs
 - obstacle.rs
 - player.rs
 - ui_element.rs
- target
- .gitignore
- Cargo.lock
- Cargo.toml
- Dockerfile


```

1 // Import local dependencies from config module
2 use crate::config::ScreenConfig;
3 use std::io::{Stdout, Write};
4 use crossterm::{ExecutableCommand, terminal, cursor};
5
6 // Define a public trait UIElement to emulate abstract class behavior in Python
7 pub trait UIElement {
8     // Abstract methods to be implemented by structs
9     fn screen_config(&self) -> ScreenConfig;
10    fn render_character(&self) -> char;
11    fn positions_to_render(&self) -> &Vec<(usize, usize)>;
12    fn update(&mut self);
13
14    // Default render method
15    fn render(&self, stdout: &mut Stdout) {
16        let screen_config = self.screen_config().clone();
17        let render_character = self.render_character();
18        for &(x, y) in self.positions_to_render() {
19            if x >= 0 && x < screen_config.width && y >= 0 && y < screen_config.height {
20                stdout.execute(cursor::MoveTo(x as u16, y as u16)).unwrap();
21                write!(stdout, "{}", render_character).unwrap();
22            }
23        }
24    }
25 }
26
27 // Function to check collision between two UIElements
28 pub fn check_collision(element_0: &dyn UIElement, element_1: &dyn UIElement) -> bool {
29     for &(x0, y0) in element_0.positions_to_render() {
30         if element_1.positions_to_render().iter().any(|&(x1, y1)| x1 == x0 && y1 == y0) {
31             return true;
32         }
33     }
34     false
35 }

```

```
25 impl Game {
98 }
99
100 // Method to render game elements
101 fn render(&mut self) {
102     self.stdout.execute(terminal::Clear(terminal::ClearType::All)).unwrap();
103
104     self.background.render(&mut self.stdout);
105     self.player.render(&mut self.stdout);
106
107     for obstacle in &self.obstacles {
108         obstacle.render(&mut self.stdout);
109     }
110
111     self.stdout.execute(cursor::MoveTo(0, 0)).unwrap();
112     write!(self.stdout, "Score: {}", self.score).unwrap();
113     self.stdout.flush().unwrap();
114 }
115
116 // Public function to create the screen
117 pub fn create_screen(screen_config: ScreenConfig) -> Stdout {
118     let mut stdout = std::io::stdout();
119     stdout.execute(terminal::EnterAlternateScreen).unwrap();
120     stdout.execute(cursor::Hide).unwrap();
121     terminal::disable_raw_mode().unwrap();
122     stdout
123 }
```




```
+ terminal_jumper_rust docker build -t terminal_jumper_rust . && docker run --rm -it terminal_jumper_rust
[+] Building 0.5s (1/2)
=> [internal] load build definition from Dockerfile
=> => transferring dockerfile: 404B
=> [internal] load metadata for docker.io/library/rust:latest
docker:desktop-linux
0.0s
0.0s
0.5s
```



Chocolate Doom

Original 30+ year old Doom Source updated to run on modern OS

- Doom codebase is
 - 96K+ lines of code
 - 231 files
 - 800K+ tokens



GraphRAG for Code - Automated Documentation

Doom Documentation

Home

API

Documentation

Table of Contents

- Introduction
- The Doom Project
- User Experience
- Chapter 1: Introduction to the System
- Chapter 2: Community-Driven Enhancements
 - Section 2.1: Processing Community Input
 - Section 2.2: Applying Modifications
- Chapter 3: Network Client Functionality
 - Section 3.1: Initialization and Connection
 - Section 3.2: Game State Management
- Chapter 4: GUI Operations Pre-Launch
 - Section 4.1: Initialization
 - Section 4.2: Updating GUI Elements

Search

Table of contents

Table of Contents

Introduction

The Doom Project

User Experience

Chapter 1: Introduction to the System

Chapter 2: Community-Driven Enhancements

- Section 2.1: Processing Community Input
- Section 2.2: Applying Modifications

Chapter 3: Network Client Functionality

- Section 3.1: Initialization and Connection
- Section 3.2: Game State Management

Chapter 4: GUI Operations Pre-Launch

- Section 4.1: Initialization
- Section 4.2: Updating GUI Elements

GraphRAG for Code - Automated Documentation

Doom Documentation

Home

API

Introduction

The Doom Project

The Doom Project generates a comprehensive first-person shooter game environment. It provides a framework for various gameplay mechanics, including player movements, animations, line-of-sight calculations, and collision detection. By integrating these features, the system creates an interactive and immersive gaming experience.

The project outputs visually rich and dynamic environments that include floors, ceilings, and dynamic elements such as moving objects and sprites. It also manages the initialization of interactive game levels, provides a save system for player progress, and includes a playable demo mode to showcase underlying game mechanics.

User Experience

Players running the Doom Project can expect a structured gaming experience involving: - Game initialization - Demo playback - Level transitions - Single-player and multiplayer modes (with dynamic sound effects, music, and interactive menus)

Additional features like player spawning, game state management, real-time rendering, special effects, and a finale sequence ensure an engaging and immersive gameplay atmosphere.

Search

Table of contents

Table of Contents

Introduction

The Doom Project

User Experience

Chapter 1: Introduction to the System

Chapter 2: Community-Driven Enhancements

- Section 2.1: Processing Community Input
- Section 2.2: Applying Modifications

Chapter 3: Network Client Functionality

- Section 3.1: Initialization and Connection
- Section 3.2: Game State Management

Chapter 4: GUI Operations Pre-Launch

- Section 4.1: Initialization
- Section 4.2: Updating GUI Elements

GraphRAG for Code - Automated Documentation

Doom Documentation

Home

API

Chapter 1: Introduction to the System

The system's architecture is built with a modular design, enabling scalability and flexibility. Key components include: - A graphical rendering engine responsible for real-time graphics, spatial data handling, and clipping geometries. - Network client and server modules for managing client-server interactions and synchronization in multiplayer environments. - A sound system that processes and plays sound effects and music in coordination with game events. - User interface management components that facilitate navigation and interactions.

Each module focuses on tasks such as rendering graphics, managing network connections, processing sound, and orchestrating user interactions. This approach allows independent maintenance and easier upgrades for each subsystem.

Chapter 2: Community-Driven Enhancements

Community-driven enhancements leverage user-generated content—custom levels, mods, or gameplay mechanics—to expand a system's capabilities. This collaborative model promotes deeper engagement and a sense of ownership among community members.

Section 2.1: Processing Community Input

When users contribute content, the system must parse, validate, and integrate the input safely. Typical approaches include: - Using structured formats (JSON, XML) to define configurations or assets. - Parsing these data formats with specialized libraries (e.g., "json-c" for C, "Jackson" for Java, "ElementTree" for Python). - Validating the data to confirm correctness of format, data types, and acceptable value ranges. - Handling parsing errors gracefully, logging any issues, and preventing malformed or malicious data from affecting the system's stability.

Section 2.2: Applying Modifications

Search

Table of contents

Section 3.2: Game State Management

Chapter 4: GUI Operations Pre-Launch

- Section 4.1: Initialization
- Section 4.2: Updating GUI Elements

Chapter 5: Dedicated Server Management

- Section 5.1: Command-Line Parameter Validation
- Section 5.2: Server Operations Loop

Chapter 6: System Interface

- Section 6.1: Sound Initialization and Shutdown
- Section 6.2: Sound Effects and Music Control

Chapter 7: Video Operations and Management

- Section 7.1: Basic Video Setup
- Section 7.2: Drawing and Buffer Manipulation

Chapter 8: Networking and Query Operations

- Section 8.1: Query Initialization
- Section 8.2: Secure Network Operations


Chapter 9: Command-Line




Code Feature Development




Feature: Add ability for players to jump in Doom



- Existing agents fail on complex tasks
 - Multi-file modifications cause problems
 - Lack of understanding of how everything fits together

This is where **GraphRAG** can actually help










```


263 + {
264 +     // Set initial jump velocity (experiment with this value)
265 +     mobj->momz = BFRACUNIT;
266 +     player->jumping = true;
267 +     player->jump_time = 0;
268 + }
269 +
270 + // Update jump state
271 + if (player->jumping)
272 + {
273 +     player->jump_time++;
274 +     // Check if we've landed
275 +     if (momz <= mobj->floorz)
276 +     {
277 +         player->jumping = false;
278 +     }
279 + }
280 + }
281 +
282 + // check for smooth step up
283 + if (mobj->player && mobj->z < mobj->floorz)
284 + {
285 +     // ...
286 + }
287 + }
288 +
289 + // Check for jumping
290 + if (cmd->jump && mobj->floorz > player->jump_time)
291 + {
292 +     player->momz = BFRACUNIT; // Initial jump velocity
293 +     player->jumping = true;
294 + }
295 +
296 + if (cmd->forwardmove || cmd->sidemove)
297 + {
298 +     if (player->state == SSTATES[PLAY])
299 +     {
300 +         // ...
301 +     }
302 + }

```




BenchmarkQED: Automated RAG Benchmarking


Available now at <https://github.com/microsoft/benchmark-qed>



AutoQ: Synthetic queries with variable data scope




AutoQ: Synthetic queries with variable data scope



AutoE: Evaluation by query class & quality metric

Composite score of (Comprehensiveness, Diversity, Empowerment, and Relevance)



Evaluation insights

LazyGraphRAG significantly beat VectorRAG

- long context (1M tokens) makes little difference to VectorRAG performance
- LazyGraphRAG excels for queries spanning the local-global spectrum
- LazyGraphRAG was ~10% the cost of 1M token Vector RAG

above the 50% line represent a win for LazyGraphRAG (LGR).
the score, the more LGR wins.

Azure Local

Azure Arc Blog

Search this community



Discovering the Advanced Capabilities of RAG on Azure Local

- Support for **Hybrid Search**, and soon **Lazy Graph RAG**, allowing robust, fast, low-cost indexing and providing quality and relevant answers regardless of query type.

Azure Arc Blog · 5 MIN READ

Transforming On-Premises Data with RAG Capabilities on Azure Local

sanjanamohan  May 19, 2023

Authored by: Sanjana Mohan, General Manager, Sales, and Meena, Lead, Data RAG, Product Management

Announcing

Microsoft Discovery

Graph-based scientific
co-reasoning




Specialized discovery agents
for conducting research

Extensible and
enterprise-ready

Transforming the scientific method with Agentic AI



Video Demonstration



Video Demonstration

Based on internal knowledge and literature, I've found several promising coolant types.

Key properties to calculate include:

1. **High Thermal Conductivity:** Ensures efficient heat transfer.
2. **Dielectric Strength:** Prevents electrical short circuits.
3. **Low Toxicity:** Ensures safety and environmental compatibility.
4. **Chemical Stability:** Maintains performance under operational conditions.
5. **Low Global Warming Potential (GWP):** Reduces climate impact.

I'll start compiling a comprehensive report on the latest research in this domain. While I'm researching, feel free to leave this chat. I'll let you know as soon as I'm done.

Reasoning ▾

the latest reports

Focus on our AI operations

Deep reasoning over graph-based scientific knowledge

Video Demonstration

Based on internal knowledge and literature, I've found several promising coolant types.

Key properties to calculate include:

1. **High Thermal Conductivity:** Ensures efficient heat transfer.
2. **Dielectric Strength:** Prevents electrical short circuits.
3. **Low Toxicity:** Ensures safety and environmental compatibility.
4. **Chemical Stability:** Maintains performance under operational conditions.
5. **Low Global Warming Potential (GWP):** Reduces climate impact.

I'll start compiling a comprehensive report on the latest research in this domain. While I'm researching, feel free to leave this chat. I'll let you know as soon as I'm done.

Reasoning completed ▾

Activity Sources

- > Searching internal R&D for non-PFAS coolant alternatives
- > Reviewing recent literature on thermal fluid efficiency
- > Extracting boiling point, density, solubility, and heat of formation data
- > Filtering by regulatory criteria (PFAS bans, GWP < 100)
- > Compiling citations from internal reports and public sources
- > Generating a structured summary for Copilot report delivery

the latest reports

Focus on our AI operations

Deep reasoning over graph-based scientific knowledge

Video Demonstration

- 3. **Low Toxicity:** Ensures safety and environmental compatibility.
- 4. **Chemical Stability:** Maintains performance under operational conditions.
- 5. **Low Global Warming Potential (GWP):** Reduces climate impact.

I'll start compiling a comprehensive report on the latest research in this domain. While I'm researching, feel free to leave this chat. I'll let you know as soon as I'm done.

Reasoning ▾

Activity Sources

- | Activity | Sources |
|---|---------|
| > Searching internal R&D for non-PFAS coolant alternatives | ✓ |
| > Reviewing recent literature on thermal fluid efficiency | ✓ |
| > Extracting boiling point, density, solubility, and heat of formation data | ✓ |
| > Filtering by regulatory criteria (PFAS bans, GWP < 100) | ✓ |
| > Compiling citations from internal reports and public sources | ✓ |
| > Generating a structured summary for Copilot report delivery | ✓ |

Takeaways:

1. *LLM memory with structure is a key enabler*
2. *Agents can massively amplify this power*