

# AWS re:INVENT

## Best Practices for Amazon S3 with Special Guest Human Longevity Inc.

Rob Wilson, Sr. Product Manager—Amazon S3

Katie Lamkin, Software Engineer—Human Longevity, Inc.

November 27, 2017

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



This is a company that is using data to deliver health intelligence.

## Agenda

- Overview of Amazon S3
- **Managing** your cloud storage
- **Securing access** to your cloud storage
- Adding **layers of protection** to retain your data
- Achieving **high levels of performance**
- **HLI** is using data to deliver health intelligence

# The AWS Storage Portfolio



Amazon EBS  
(persistent)



Amazon EC2  
Instance Store  
(ephemeral)

## Block



Amazon EFS

## File



Amazon S3



Amazon Glacier

## Object



AWS  
Snow Family



AWS Storage  
Gateway



EFS  
File Sync



Third-Party  
Connectors



AWS Direct  
Connect



S3 Transfer  
Acceleration



Amazon  
Kinesis

## Data Transfer

aws  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Benefits of Amazon S3 & Amazon Glacier



Durable, Available, and  
Scalable



Security and Compliance



Query In Place



Flexible Management



Ecosystem

aws  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.




Amazon S3 is designed to be a durable object store with 11 nines of availability, you can also scale to Petabytes and Exabytes using S3. You have 3 different ways to encrypt your objects in S3, you can use server side managed by you the customer where you provide the key, or use the AWS KMS service to encrypt your objects. We also have compliance offerings like Federand, HIPAA, or PCI compliance using S3 storage. For Query In Place, we have Amazon Athena and Amazon Redshift Spectrum that both allow you to analyze data using SQL across S3 and taking in data from your data warehouse without requiring you to extract or load that data in any other service. We also have **Flexible Mgt tools** for better storage visibility, monitor, set alarms. Our Ecosystem consists of 3<sup>rd</sup> party services and in-house services.


# Choice of Storage Classes



Amazon S3 Standard



Amazon S3 Standard-  
Infrequent Access



Amazon Glacier

Active data

Milliseconds

From 2.1¢-GB/mo.

Infrequently accessed data

Milliseconds

1.25¢-GB/mo.

Archive data

Minutes to hours

0.4¢-GB/mo.

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.




# Durability and Availability

## Regional services:

- Data written across three physical availability zones (AZs)
- Data remains durable even in the event of an entire AZ failure

## Designed for:

- Durability: 99.999999999%
- Availability:
  - Amazon S3 Standard: 99.99%
  - Amazon S3-IA: 99.9%



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.





# Storage Management

Object Tags

Lifecycle Management

Storage Class Analysis

Amazon S3 Inventory

**AWS**  
**re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Storage Management



Cross-Region  
Replication



Lifecycle Policies



Event  
Notifications



Object Tags



Amazon CloudWatch  
Request Metrics



Amazon S3  
Inventory



Storage Class  
Analysis



AWS CloudTrail  
Data Events

**AWS**  
**re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Object Tags

Easily manage and control access for Amazon S3 objects



Access Control



Lifecycle Policies



Analysis

- Tag your objects with key-value pairs
- Classify your data with tags that can be edited at any time
- Filter objects for storage class analysis and CloudWatch request metrics
- Define access and lifecycle policies based on tags

You can add up to 10 tags per object stored in S3, this can be used for several analytics use cases like changing the tags to the S3 objects to control access over time without changing the data. Bucket policies allows you to set access policies and IAM User Roles policies based on the 'what tagged objects should this user have access to?'. You can write Lifecycle policies (to transition or expire storage) per bucket or prefix level depending on how granular you want to control your lifecycle policies. You can now also use tags for this as well by attaching tags to objects with a specific lifecycle policy so that only those tagged objects will be affected.

## Lifecycle Policies

Create rules to automatically *transition* or *expire* your storage




Lifecycle rules take action based on object age

Example policy:

- Move all objects older than 30 days to Standard–Infrequent Access
- Move all objects older than 90 days to Amazon Glacier



S3 Standard



S3 Standard –  
Infrequent Access



Amazon Glacier

**AlertLogic** is using tags on S3 objects in a very clever way, they have a number of N customers stored in a single S3 bucket. They can have 950 customers worth of data stored in a single S3 bucket, they then use tags to keep track of which customer data is a particular object and when was that data originally created. They used the **creationDate** and **lastSeenDate** as tags on objects and have policies that move the data to long term storage options when it hasn't been accessed in say '3 months'.

# Storage Class Analysis

Data-driven storage management and cost optimization for Amazon S3



Daily Storage  
Class Analysis



Export Storage Class  
Analysis to your S3 Bucket



Filter by Bucket,  
Prefix, or Object  
Tags

- Monitors access patterns to understand your storage usage
- After 30 days, recommends when to move objects to Standard–Infrequent Access
- Export file includes a daily report of storage, retrieved bytes, and GETs by object age


AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



How do we know that 30 days is the number of days to move to infrequent access and 90 days is the number of days to move to longer term storage like Athena for S3 objects?

# Storage Class Analysis



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



This is what you will see in the S3 console when you set this up.

# Amazon S3 Inventory

Low cost alternative to the LIST API delivered into your bucket



Saves Time



Daily or Weekly Delivery



CSV or ORC Format

- Includes encryption status of each object *New*
- Amazon S3 Inventory files can be encrypted *New*
- Available in ORC file format *New*
- Compatible with Amazon Athena and Amazon Redshift Spectrum *New*

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



This is a way to list out all the objects in an S3 bucket or an S3 prefix. This is a feature that you configure to have a list of S3 buckets and their associated metadata delivered to you, you can then do advanced analytics on the list.

## Security

Data Encryption

Access Controls

AWS CloudTrail Data Events

Amazon Macie


AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.





# Encrypting Your Data



## Server-Side Encryption

SSE-S3  
SSE-C  
SSE-KMS



## Client-Side Encryption

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



**Client-Side encryption** is when you encrypt the data object before uploading it into S3, but you can also let AWS do the data object encryption for you on the **Server-Side** before storing it in S3.

**SSE-S3** means that AWS manages the data and master keys, you just specify whether you want the data encrypted when they are uploaded. This is encryption at REST so keep in mind that when an authorized request comes in to read your object, AWS is going to decrypt the object and then deliver it to the requesting party.

**SSE-C** is server-side encryption customer, it refers to you providing and managing the customer key, so with your request for retrieval you will have to specify the encryption key and AWS will use the key that you provide to encrypt or decrypt the object depending on if it is a PUT or a GET.

**SSE-KMS** is the Key Management Service, with KMS there is a data key used in S3 to encrypt your data and there is a master key that is retained in the KMS service. Customers need approval and authorization before they can read the objects from S3, they also need the permissions from the KMS service before they can get access to the master key they need to decrypt the object when they get it.






## Encryption by Default *New*

Automatically encrypts all objects written to your Amazon S3 bucket

- Choose SSE-S3 or SSE-KMS
- Makes it easy to satisfy compliance needs



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



## Security



### Resource-based

- Object Access Control Lists (ACLs)
- Bucket Access Control Lists (ACLs)
- Bucket policies



### User-based


- Identity and Access Management (IAM) policies

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Above are the few different options and levels that you can manage for doing security on your S3 buckets. Let us now see how to use these options and how a request to your S3 bucket is authorized. **Bucket ACLs** are best recommended to be used for a S3 bucket logging group like for log delivery from Amazon S3 to write those logs.



When you add a prefix to your object key name like a '/' for organizing your folder, it will look like a folder as above.

Layers of Security

How does Amazon S3 authorize a request?

Bucket operations:

- User context—IAM user permissions
- Bucket context—bucket policy, bucket ACL

AWS re:Invent  
© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

aws

If the IAM Role trying to access your S3 bucket does not have access to S3 or does not have access to your account, then the request is denied immediately. If an account is trying to access your S3 bucket, then we will look at the Bucket context's policy and bucket ACL to determine access.

# Layers of Security



How does Amazon S3 authorize a request?

Object operations:

User context—IAM user permissions

Bucket context—bucket policy, bucket ACL

Object context—object ACL



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



There is an additional layer when using the Object level, we will look at the object context and the object ACL.

## Permission Checks *New*



Amazon S3 console interface showing a list of buckets. The interface includes a search bar, buttons for 'Create bucket', 'Delete bucket', and 'Empty bucket', and summary statistics: 42 Buckets, 3 Public, and 6 Regions. The table lists buckets with their names, access status, region, and creation date.

Bucket name	Access	Region	Date created
jbarr-public	Public	US East (N. Virginia)	Sep 10, 2014 6:01:05 PM
jbarr-edge	Public	US East (N. Virginia)	Nov 23, 2016 6:40:14 AM
awsroadtrip.com	Public	US East (N. Virginia)	Apr 30, 2013 7:46:50 AM
www.awsroadtrip.com	Not public *	US East (N. Virginia)	Apr 30, 2013 7:49:34 AM

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Layers of Security



How does Amazon S3 authorize a request?

Object operations:

Prefixes—allow you to grant permissions for many objects in one policy statement



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



When you add a prefix to an object, it gets stored in a folder with other objects that have that prefix as above. We can then create and write S3 bucket policies for the folder as a whole and then for individual subfolders if needed.

## User Policy Example

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:PutObject",
        "s3:GetObject",
        "s3:GetObjectVersion",
        "s3:DeleteObject",
        "s3:DeleteObjectVersion"
      ],
      "Resource": "arn:aws:s3:::examplebucket/Alice/*"
    }
  ]
}
```

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



To manage a user at the **Prefix level**, in this case the prefix **examplebucket/Alice**. This User policy will grant PUT, GET, DELETE permissions to a particular user called Alice. The S3 Resource allowed is for the objects within the folder in **examplebucket/Alice/\***, the user Alice can now interact with that particular subset of S3 objects.




# Manage Access with Object Tags

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetObject"
      ],
      "Resource": "arn:aws:s3:::EXAMPLE-BUCKET-NAME/*"
      "Condition": {"StringEquals": {"s3:RequestObjectTag/Project": "Delta"}}
    }
  ]
}
```


Next, we will talk about **Object Tags** on your S3 objects level. Here we are adding a **Condition** attribute to the policy, we want a user to be able to get all the Objects that are associated with the Project called **Delta**. Project delta might start very small and grow over time to a very large project, we just continue to tag all the S3 objects associated with the project so that permitted users can see and use them. When Project Delta ends, we can go ahead and just simply delete all the tags on the objects or even delete all the objects themselves in addition to all the user permissions associated to Project Delta.

## Amazon S3 Data Events in CloudTrail


Perform security analysis, meet your IT auditing and compliance needs, and take immediate action on object-level activity to immediately improve security posture




Log Object Level Operations




Monitor Changes to Bucket Configurations



SNS Notification for Log Delivery




© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.




Data Events in CloudTrail can be turned on to start looking at object level activity and recording the GET, PUT, DELETE events to the buckets. You can automate alerts using this approach. We can set up lambda functions to revert unwanted events back to their intended state.

# Amazon Macie *New*



A security service that uses machine learning to automatically discover, classify, and protect sensitive data in AWS

- Recognizes sensitive data
- Continuously monitors data access
- Provides dashboards and alerts



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



## Data Protection

Cross-Region Replication

Versioning


Multi-Factor Authentication

## Cross-Region Replication

Automatically replicate data to any other AWS Region



- Replicate by object, bucket, or prefix
- Support for SSE-KMS encrypted objects *New*
- Ownership overwrite *New*
  - Change the object owner in the destination region



AWS  
re:Invent


© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Versioning

Protect your data from accidental deletion

- New version with every upload
- Protects from unintended user deletes
- Easy retrieval of deleted objects



**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



**Versioning** protects your data from accidental deletion, by creating new versions of your object every time you overwrite a particular object key like the version number. You can then go back and use the particular object key name you want to get that particular version.


# Multi-Factor Authentication (MFA)

Adds another layer of protection for deleting objects or changing the versioning state of the bucket

Requires two forms of authentication:



Your security  
credentials



Unique code from an approved  
authentication device

**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# Performance

Tips for Object Key-Naming

Amazon S3 Transfer Acceleration

Additional Best Practices

## Getting High Throughput with Amazon S3

Amazon S3 automatically scales to thousands of requests per second per prefix based on your steady state traffic

- Amazon S3 automatically partitions your prefixes within hours adjusting to increases in request rates
- Consider using a three- or four-character hash

## Using a Three- or Four-Character Hash

Due to recent Amazon S3 performance enhancements, most customers no longer need to worry about introducing entropy in key names

examplebucket/**232a**-2017-26-05-15-00-00/cust1234234/photo1.jpg  
examplebucket/**7b54**-2017-26-05-15-00-00/cust3857422/photo2.jpg  
examplebucket/**921c**-2017-26-05-15-00-00/cust1248473/photo2.jpg



### A bit more LIST friendly:

examplebucket/**animations/232a**-2017-26-05-15-00-00/cust1234234/animation1.obj  
examplebucket/**videos/ba65**-2017-26-05-15-00-00/cust8474937/video2.mpg  
examplebucket/**photos/8761**-2017-26-05-15-00-00/cust1248473/photo3.jpg



Random hash should come before patterns such as dates and sequential IDs  
Always first ensure that your application can accommodate

aws  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.


aws

This is how you can add the hash to your buckets. Object keys are stored in an index in an AWS region, and if you are constantly writing the same object keys repeatedly like for a year 2017 or a day 12, this will place all those objects close together within the same partition or index. So, if you are also doing a lot of reads on those objects, you might start to see some performance slowdowns. You can make this better by putting a **hash** in front of your object key names as above to add some randomness and spread the data around better. You can also add prefixes like the **/animations/<hash>** for specific buckets that might get a high traffic.



# Faster Uploads Over Long Distances with Amazon S3 Transfer Acceleration

- No firewall changes or client software
- Longer distances, more benefit
- Faster or no additional charge
- 101 global edge locations




**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



You can specify that you want to use this feature for your S3 bucket

## How fast is Amazon S3 Transfer Acceleration?



500 GB upload from these edge locations to a bucket in Singapore

**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

Try it at [s3speedtest.com](https://s3speedtest.com)



# More Ways to Improve Performance



Amazon CloudFront



Multipart Uploads




Range GETs

## Human Longevity Inc.

Katie Lamkin, Software Engineer

### The Premier Health Intelligence Provider Extending the quality and longevity of life



**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Human longevity is a human genomics company founded by Craig Venter in 2013, it gathers quality genomic data as well as Phenotypic data at petabyte scale. They perform a whole genomic sequencing in order to make discoveries in part of the genome in addition with phenotypic data like a full body MRI, brain scan, CT scans, height weight, etc. This provides preventive healthcare.

## Our Mission

Human Longevity, Inc. (HLI), was founded by leaders in genomics with the ultimate goal of giving everyone access to the power of data-driven health intelligence.

HLI combines state-of-the-art DNA sequencing and expert analysis with machine learning, to help change medicine to a more data-driven science. With a multidisciplinary team of research scientists, computing experts and physicians, we are empowering every part of the healthcare system to work more efficiently.


# BRINGING HEALTH INTELLIGENCE TO LIFE.

**AWS  
re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



## Merging Genomics with Phenotype Data to Deliver Health Intelligence




**AWS  
re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



We then sequence their genome and do analysis on it that are given back to them in their 'health intelligence' report containing potential cancer or neurological risks, ancestry, etc.

# HLI Sequencing Laboratory




AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Microbiomes are the bacteria in the gut that also get sequenced. This adds up to about 6Pb of data in S3 and 10Pb in Glacier.

## Analysis Output



To get the data, we put the samples into our sequencer and it dumps the data in our local aspire storage that will upload that data into S3. Those files can be up to 400,000 BCL files that all get compressed into a file that is about 600GB in size. When this 600GB file gets dropped into S3, it triggers our primary analysis platform that takes those 400,000 BCL files and turns them into the overall genome file which is about 200GB. After the primary analysis is done, a lambda gets triggered checks what is the next workflow that needs to be run like a secondary analysis step that then gets triggered. After all required workflow gets completed, all the analysis data again gets dumped into S3.

We then have professionals that map the phenomic data into specific ontologies and the result of their work again gets dumped into S3 as well. S3 is the merging ground for both genomic and phenotypic data.



# Business Needs

Default Business Case	Rule
Patient or partner allows access to data	Not restricted

Edge Business Case	Rule
Patient or partner denies access to data	Completely restricted
Partner only allows our research team access to data	Restricted to all but our research team
Partner allows HLI ownership of data after an allotted period of time	Restricted to all, but after that allotted time period, data is not restricted

AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



There are 4 main business needs to securing our data.

## Amazon S3 Object Tags and IAM Managed Policies

Translated the business need into using Amazon S3 object tags and IAM managed policies to allow access to specific data

The screenshot shows the AWS 'Tags' console. It has a title bar 'Tags' with a close button. Below is a table with two columns: 'Key' and 'Value'. There are three rows of tags: 'rights' with value 'true', 'restriction' with value 'true', and 'project-id' with value 'pj-1234'. Each row has a delete icon (X) to its right. Below the table is an 'Add Tag' button. At the bottom, there is a 'Cancel' button and a 'Save' button. A note at the bottom states: 'To enable replication of object tags IAM policies used for Cross-Region Replication must be updated if they were created prior to the introduction of Object tagging.'


AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



The 3 tags we use on the S3 buckets for access management that we use are *rights*, *restriction*, *project-id*.

# Serverless Solution




AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



We needed an automatic solution for tagging the millions of files as appropriate, we used a serverless solution for doing this tagging as above. Once a workflow completes and has uploaded its files to S3, an SMS message gets sent off and that triggers a Step Function that has a series controlled parallel lambdas that gets triggered to go to their respective S3 buckets and tag all the files. Each of the individual lambdas will hit our own API to gather the list of files that they need to tag and what to tag them with, then they will go out and get the files, unpack them, and tag all the files in S3.

## IAM Managed Policy: Flow Chart



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



We have 2 different types of IAM policies, Implicit Allow and Implicit Deny.

# IAM Managed Policy: Implicit Allow

- Deny read access:
  - Rights tag = false AND Restriction tag = true
- Override rule:
  - Project-id tag = pj-1234

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "S3RestrictedRead",
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:GetObjectVersion"
      ],
      "Resource": [
        "arn:aws:s3:::hli-bucket/*"
      ],
      "Condition": {
        "StringNotEquals": {
          "s3:ExistingObjectTag/rights": "false",
          "s3:ExistingObjectTag/restriction": "true"
        },
        "StringEquals": {
          "s3:ExistingObjectTag/project-id": "pj-1234"
        }
      }
    }
  ]
}
```

**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# IAM Managed Policy: Implicit Deny

- Allow read access:
  - Rights tag = true AND Restriction tag = false
- Override rule:
  - Project-id tag = pj-1234


```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "S3RestrictedRead",
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:GetObjectVersion"
      ],
      "Resource": [
        "arn:aws:s3:::hli-bucket/*"
      ],
      "Condition": {
        "StringEquals": {
          "s3:ExistingObjectTag/rights": "true",
          "s3:ExistingObjectTag/restriction": "false"
        }
      }
    },
    {
      "Sid": "S3ProjectRead",
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:GetObjectVersion"
      ],
      "Resource": [
        "arn:aws:s3:::hli-bucket/*"
      ],
      "Condition": {
        "StringEquals": {
          "s3:ExistingObjectTag/project-id": "pj-1234"
        }
      }
    }
  ]
}
```

**AWS re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



# HLI Achievements: Algorithms, Tools, and Methods



We have done a lot with the data so far, we have created an open search tool that aggregates all the files that we have been granted open access to and built a search tool on top of them to allow easy insights and querying both the genomic and phenotypic data. we can also do queries based on demographics, age, genome variants to build graphs and insights.

## Learn more...

**STG401** – This Is My Architecture – Storage Lightning Round – Tues, 12:15PM

**STG301** – Deep Dive on Amazon S3 & Amazon Glacier Infrastructure – Tues, 4:00 PM

**STG201** – Storage State of the Union – Wed, 11:30 AM

**STG313** – Big Data Breakthroughs – Wed, 12:15 PM OR 7:00 PM

**STG312** – Best Practices for Building a Data Lake in Amazon S3 & Amazon Glacier – Thurs, 3:15 PM



AWS  
re:Invent  
Thank you!



AWS  
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

