



SaaS presents developers with a unique blend of architectural challenges. While the concepts of multi-tenancy are straightforward, the reality of making all the moving parts work together can be daunting. In this session, we move beyond the conceptual bits of SaaS and look under the hood of an SaaS application. Our goal is to examine the fundamentals of identity, data partitioning, and tenant isolation through the lens of a working solution and to highlight the challenges and strategies associated with building a next generation SaaS application on AWS. We look at the full lifecycle of registering new tenants, applying security policies to prevent cross-tenant access, and leveraging tenant profiles to effectively distribute and partition tenant data. We intend to connect many of the conceptual dots of an SaaS implementation, highlighting the tradeoffs and considerations that can shape your approach to SaaS architecture.



All the tenant data is shared in this architecture since this is a polled environment. Onboarding includes sign up and other things that have to be provisioned, spun up, the policies that need to be created for the tenant

The SaaS architecture landscape

Tenant 1

Onboarding

Tenant 2

Authentication

We then need to set up authentication, what does SaaS do to authentication? Identity is a fundamental part of SaaS since it affects the app services, partitioning, etc

The SaaS architecture landscape

Tenant 1

Onboarding

Tenant 2

Authentication

Application
services

Service

Service

What does it mean to be a developer and write the services as separate microservices in a multi-tenant SaaS environment?

The SaaS architecture landscape

Tenant 1

Tenant 2

Onboarding

Authentication

Application services

Service

Service

Storage partitioning



We look at storage partitioning, how we represent pooled, multi-tenant data, how do we encapsulate storage in this SaaS environment

The SaaS architecture landscape

Tenant 1

Tenant 2

Onboarding

Authentication

Application services

Service

Service

Storage partitioning




Tenant isolation



Tenant isolation

How do we do tenant isolation in a SaaS environment? You really need to keep tight boundaries between tenant resources, what strategies can we have besides authentication to enforce tenant isolation?

The SaaS architecture landscape




AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

aws

We then have the operational bits of the SaaS applications like health, metrics, management, billing, etc

The conceptual architecture




AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

aws


The stack we build this reference SaaS application with is shown above, we use the custom authorizer for an added layer of security, then we have NodeJS services working as separate microservices, we use cognito as the identity management solution and use a lot of its part.

Provisioned environment




This is the provisioned environment that you will get when you deploy the code, this is an HA architecture

Start with tenant onboarding




This is the onboarding experience, tell it a little bit about our SaaS configuration, all the code behind this is being done by Cognito for you

Onboarding under the hood




This Tenant registration service is going to be the orchestrator for all what we have to create for this tenant onboarding after they have successfully registered using Cognito. There are 3 major parts of this service.

Onboarding under the hood




First, we have to create the user and the identity footprint of the app. We have to provision all the mechanics for all the users of the system that will need identity profiles. It uses cognito to create the identity for the user, we are using cognito as an openID connect. It provisions the user pool that lets you configure policies like password policy, MFA. We are provisioning a user pool per tenant.

Onboarding under the hood



We also have to provision all the policies that will be needed for all the types of users. We then create some mapping between a user and a user pool.

Onboarding under the hood



AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



We then create one entry in the DynamoDB table that will have the TenantID, plan, status like active/inactive. Once this is all in place, we will have 1 tenant.

Provisioning custom attributes

Type	Name	Min length	Max length	Mutable
string	custom:tenant_id	1	256	<input type="checkbox"/>
string	custom:tier	1	256	<input checked="" type="checkbox"/>
string	custom:company_name	1	256	<input checked="" type="checkbox"/>
string	custom:role	1	256	<input checked="" type="checkbox"/>


AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Then we have to set up and configure the tenant itself,

Provisioning a billing account




AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.




Then we have to set up the actual billing interface for this tenant and provision their billing process and setup.

Authentication with SaaS context




The encrypted JWT token contains the data we need as a UserID and a Tenant ID that we will use with in the header of all calls to all the downstream SaaS services

Invoking application services




We don't know who you are as a tenant and what IAM credentials to use for access to scope you to within the SaaS services,

Invoking application services



We then have a Token manager that gets the Tenant ID out from the JWT token,

Invoking application services




We then get IAM credentials that will give back what the user with the Tenant ID can get/see from the services.

JWT decoding & credential lookup

```
module.exports.getCredentialsFromToken = function(req, updateCredentials) {  
  var bearerToken = req.get('Authorization');  
  if (bearerToken) {  
    var tokenValue = bearerToken.substring(bearerToken.indexOf(' ') + 1);  
    var decodedIdToken = jwtDecode(tokenValue);  
    async.waterfall([  
      function(callback) {  
        getUserPoolWithParams(userName, callback)  
      },  
      function(userPool, callback) {  
        authenticateUserInPool(userPool, tokenValue, callback)  
      }  
    ], function(error, results) {  
      if (!error)  
        updateCredentials(results)  
    });  
  }  
};
```

Token validation with Amazon API Gateway



We add a custom authorizer to the API Gateway to add more security by taking the JWT token and inspecting it to determine which API endpoints the user is allowed to call or not

AWS Lambda validator function

```
verifiedJwt = nJwt.verify(event.authorizationToken, key);


// parse the ARN from the incoming event
// if the token is invalid, deny access immediately
...

policy = new AuthPolicy(verifiedJwt.body.sub, awsAccountId, apiOptions);

if (verifiedJwt.body.scope.indexOf("admins") > -1) {
    policy.allowAllMethods();
} else {
    policy.allowMethod(AuthPolicy.HttpVerb.GET, "*");
    policy.allowMethod(AuthPolicy.HttpVerb.POST, "/users/" +
verifiedJwt.body.sub);
}
context.succeed(policy.build());
```

The policy we create and return is then used by the API Gateway to allow access to an endpoint or not

Data partitioning & encapsulation



AWS re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.




Object tags can also be used to partition data in S3.

Accessing tenant scoped data

```
tokenManager.getCredentialsFromToken(req, function(credentials) {  
  var searchParams = {  
    TableName: productSchema.TableName,  
    KeyConditionExpression: "tenantId = :tenantId",  
    ExpressionAttributeValues: {  
      ":tenantId": tenantId  
    }  
  };  
  
  var dynamoHelper = new DynamoDBHelper(productSchema,  
    credentials, configuration);  
  
  dynamoHelper.query(searchParams, credentials, function (error, products) {  
    res.status(200).send(products);  
  });  
});
```

Adding in tenant isolation



Provisioning policies for roles

Tenant admin
role

Tenant user
role

System admin
role

```
{
  "sid": "TenantReadOnlyOrderTable",
  "Effect": "Allow",
  "Action": [
    "dynamodb:GetItem",
    "dynamodb:BatchGetItem",
    "dynamodb:Query",
    "dynamodb:DescribeTable"
  ],
  "Resource": [
    "arn:aws:dynamodb:us-east-1:000000000000:table/order"
  ],
  "Condition": {
    "ForAllValues:StringEquals": {
      "dynamodb:LeadingKeys": [
        "5bd24c40d66c4755819d28ceab9f0826"
      ]
    }
  }
}
```

AWS
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



This is one of the IAM policies that were provisioned for a tenant when they register, the LeadingKeys value contains the tenant ID that we want to use this specific policy

Binding custom roles to users



Cognito user pool

- User pool ID
- Application ID



Cognito federated
identity

Custom attributes
custom:tenantId
custom:role
custom:tier

Auth role matching rules
custom:role = TenantAdmin
custom:role = TenantUser


Configuring role-matching

```
Rules: [  
  {  
    Claim: 'custom:role',  
    MatchType: 'Equals',  
    RoleARN: identityPoolRoleParams.rolesystem,  
    Value: identityPoolRoleParams.adminRoleName  
  },  
  {  
    Claim: 'custom:role',  
    MatchType: 'Equals',  
    RoleARN: identityPoolRoleParams.rolesupportOnly,  
    Value: identityPoolRoleParams.userRoleName  
  },  
]
```


Acquiring a token with role context

```
function getCredentialsForIdentity(event, callback){  
  var cognitoidentity = new AWS.CognitoIdentity({...});  
  var params = {  
    IdentityId: event.IdentityId, ← Identity Pool Id  
    Logins: {  
      [event.provider]: event.token, ← ID Token  
    }  
  };  
  cognitoidentity.getCredentialsForIdentity(params, function (err, data){  
    if (err) {  
      callback(err);  
    }  
    else {  
      callback(data);  
    }  
  });  
};
```

Connecting identity and isolation



Role-based application flows



Applying roles to application view

Start by extracting the tenant role during login

```
$rootScope.currentUser = $scope.username;
$rootScope.bearerToken = response.data.token;
var decodedToken = jwtHelper.decodeToken($rootScope.bearerToken);
$rootScope.userDisplayName = decodedToken['given_name'] + ' ' +
    decodedToken['family_name'];
$rootScope.userRole = decodedToken['custom:role'];
```

Add helper to centralize access policies

```
$rootScope.isLinkEnabled = function (viewLocation) {
    var enabled = false;
    if ($rootScope.isUserLoggedIn) {
        if ($.inArray(viewLocation, ['/login', '/']) >= 0)
            enabled = true;
        else if (viewLocation === '/tenants') {
            enabled = $rootScope.isSystemUser();
        }
        else if (viewLocation === '/users') {
            enabled = $rootScope.isAdminUser();
        }
        else if ($.inArray(viewLocation, ['/products', '/orders']) >= 0) {
            enabled = $rootScope.isTenantUser();
        }
    }
    return enabled;
};
```

Applying role the application views

```
<li ng-if="isLinkEnabled('/users')"
    ng-class="{active:isActiveLink('/users')}">
  <a ng-href="#!/users">Users</a>
</li>
```

Extract role from token

Define view access policies

Show/hide views based on policies


Enabling client access \neq enabling resource access

AWS
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Metering consumption




AWS
re:Invent

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.



Centralized system health



- Client polls services for system health
- Real-time view of microservice availability
- View of key activity metrics
- Services expose health endpoint
- Illustrates system vs. tenant flows

Takeaways

- Identity is foundational to SaaS application architecture
- IAM adds depth and power to your isolation model
- Limit developer awareness of security/tenant context
- Consider the impact of system *and* tenant roles
- Make metering and analytics an early priority
- Work the multitenant problem from end-to-end

AWS SaaS resources

Quick start: SaaS Identity and Isolation with Amazon Cognito

<https://aws.amazon.com/quickstart/saas/identity-with-cognito/>

Source repository

<https://github.com/aws-quickstart/saas-identity-cognito>

SaaS On AWS content

<https://aws.amazon.com/partners/saas-on-aws/>

**AWS
re:Invent**

Thank you!

**AWS
re:Invent**

© 2017, Amazon Web Services, Inc. or its Affiliates. All rights reserved.

