

GTU Department of Computer Engineering
CSE 222/505 - Spring 2023
Homework 6 Report

BERRU LAFCI
1901042681

myMap

While building the map:

- After process the string, it initializes a variable wordCounter to keep track of the current word index and splits the preprocessedStr into an array of words using the space (" ") as the delimiter.

```
if(key.equals(" ")) {  
    wordCounter++;  
    continue;  
}
```

It traverse through the string. If the map already contains the current key, it adds the current word to the list of words and increase the count in the **info** object.

```
if (map.containsKey(key)) {    // if the key already exists  
    info value = map.get(key); // get the value of the key  
    value.setCount(value.getCount() + 1); // increment the count  
    value.getWords().add(words[wordCounter]);  
}
```

If the map does not contain the current key, it creates a new **info** object with a count of 1 and the current list of word.

```
else {    // if the key does not exist  
    info value = new info(count:1, words[wordCounter]);  
    map.put(key, value); // add the key and value to the map  
    mapSize++;  
}
```

mergeSort

The `merge_sort()` method is called with the values array, aux array, and the indices representing the leftmost and rightmost elements of the array. It recursively divides the array into smaller halves until the left index is less than the right index.

The `merge_sort()` method then calls itself twice, once for the left half of the array (from left to mid) and once for the right half of the array (from mid + 1 to right).

```
merge_sort(values, aux, left, mid); // left half
merge_sort(values, aux, mid + 1, right); // right half
merge(values, aux, left, mid, right); // merge the two halves
```

The actual mergeSort algorithm of the two sorted subarrays is performed by the `merge()` method:

The `merge()` method creates a temporary array (temp) to store the merged values and a temporary ArrayList to store the corresponding keys. It compares the values from the left and right subarrays and copies them to the temp array and tempKeys ArrayList in **sorted order**. If there are any remaining elements in either the left or right subarray, they are copied to the temp array and tempKeys ArrayList.

Once the merging process is completed, the `sortMap()` method creates a new sortedMap and copies the sorted values and corresponding keys from the original map to the sortedMap.

In summary, the merge sort algorithm is implemented by recursively dividing the array into smaller halves, sorting them separately, and then merging the sorted halves back together. This process continues until the entire array is sorted.

The time complexity of the `merge_sort` method:

The function divides the array in half each time it is called, resulting in a **binary tree of recursive calls**. Therefore, the depth of the recursion tree is logarithmic to the size of the input array, given by $\log(n)$, where n is the number of elements in the array.

At each level of the recursion, the function performs a merge operation, which takes linear time proportional to the size of the merged subarray. Since the size of the merged subarray doubles at each level, the total time complexity of merging all subarrays is also linear to the size of the input array.

Therefore, the overall time complexity of the `merge_sort` function is **$O(n \log(n))$** , where n is the number of elements in the input array.

Test Cases:

```
110 static void main(String[] args) {  
    String str = "'Hush, hush!' whispered the rushing wind.";
```

```
berry@DESKTOP-092GAB6:/mnt/c/Users/lafci/Desktop/3. Sınıf/3. sınıf 2. dönem/Data Structure/HW/  
p/3. Sınıf/3. sınıf 2. dönem/Data Structure/HW/  
● HW6$ javac Main.java  
berry@DESKTOP-092GAB6:/mnt/c/Users/lafci/Desktop/3. Sınıf/3. sınıf 2. dönem/Data Structure/HW/HW6$ java Main  
Original string: 'Hush, hush!' whispered the rushing wind.  
Preprocessed string: hush hush whispered the rushing wind  
Original (unsorted) Map:  
Letter: h - Count: 7 - Words:[hush, hush, hush, hush, whispered, the, rushing]  
Letter: u - Count: 3 - Words:[hush, hush, rushing]  
Letter: s - Count: 4 - Words:[hush, hush, whispered, rushing]  
Letter: w - Count: 2 - Words:[whispered, wind]  
Letter: i - Count: 3 - Words:[whispered, rushing, wind]  
Letter: p - Count: 1 - Words:[whispered]  
Letter: e - Count: 3 - Words:[whispered, whispered, the]  
Letter: r - Count: 2 - Words:[whispered, rushing]  
Letter: d - Count: 2 - Words:[whispered, wind]  
Letter: t - Count: 1 - Words:[the]  
Letter: n - Count: 2 - Words:[rushing, wind]  
Letter: g - Count: 1 - Words:[rushing]  
Sorted Map:  
Letter: p - Count: 1 - Words:[whispered]  
Letter: t - Count: 1 - Words:[the]  
Letter: g - Count: 1 - Words:[rushing]  
Letter: w - Count: 2 - Words:[whispered, wind]  
Letter: r - Count: 2 - Words:[whispered, rushing]  
Letter: d - Count: 2 - Words:[whispered, wind]  
Letter: n - Count: 2 - Words:[rushing, wind]  
Letter: u - Count: 3 - Words:[hush, hush, rushing]  
Letter: i - Count: 3 - Words:[whispered, rushing, wind]  
Letter: e - Count: 3 - Words:[whispered, whispered, the]  
Letter: s - Count: 4 - Words:[hush, hush, whispered, rushing]  
Letter: h - Count: 7 - Words:[hush, hush, hush, hush, whispered, the, rushing]  
berry@DESKTOP-092GAB6:/mnt/c/Users/lafci/Desktop/3. Sınıf/3.
```

```

• sınıf 2. dönem/Data Structure/HW/HW6$ javac Main.java
berry@DESKTOP-092GAB6:/mnt/c/Users/lafci/Desktop/3. Sınıf/3. sınıf 2. dönem/Da
• 6$ java Main
Original string: Buzzing bees buzz.
Preprocessed string: buzzing bees buzz
Original (unsorted) Map:
Letter: b - Count: 3 - Words:[buzzing, bees, buzz]
Letter: u - Count: 2 - Words:[buzzing, buzz]
Letter: z - Count: 4 - Words:[buzzing, buzzing, buzz, buzz]
Letter: i - Count: 1 - Words:[buzzing]
Letter: n - Count: 1 - Words:[buzzing]
Letter: g - Count: 1 - Words:[buzzing]
Letter: e - Count: 2 - Words:[bees, bees]
Letter: s - Count: 1 - Words:[bees]
Sorted Map:
Letter: i - Count: 1 - Words:[buzzing]
Letter: n - Count: 1 - Words:[buzzing]
Letter: g - Count: 1 - Words:[buzzing]
Letter: s - Count: 1 - Words:[bees]
Letter: u - Count: 2 - Words:[buzzing, buzz]
Letter: e - Count: 2 - Words:[bees, bees]
Letter: b - Count: 3 - Words:[buzzing, bees, buzz]
Letter: z - Count: 4 - Words:[buzzing, buzzing, buzz, buzz]
berry@DESKTOP-092GAB6:/mnt/c/Users/lafci/Desktop/3. Sınıf/3. sınıf 2. dönem/Da
○ 6$

```

Empty input (with exception in myMap constructor):

```

public static void main
    String str = "";

berry@DESKTOP-092GAB6:/
⊗ 6$ java Main
Input is empty.
berry@DESKTOP-092GAB6:/
○ 6$

```