

Telco Customer Churn Analysis Report

Berru Lafcı | 1901042681

I. INTRODUCTION

In the competitive landscape of telecommunications, understanding and predicting customer churn is crucial for retaining a stable customer base and ensuring business sustainability. This code aims to conduct a comprehensive analysis of customer churn for a telecommunications company and build predictive models to identify potential churners. The dataset utilized in this analysis contains a rich set of information about customers, covering attributes, subscribed services, account details, and demographic information.

II. DATASET OVERVIEW

The dataset includes 7,043 rows representing individual customers and 21 columns encompassing various features. These features include customer attributes, details about subscribed services (phone, internet, security, streaming, etc.), account information (tenure, contract, billing method, charges), and demographic details (gender, age range, dependents, etc.). The primary target variable is "Churn," indicating whether a customer has left within the last month.

III. LIBRARIES AND DATA IMPORT

To facilitate the analysis and machine learning tasks, essential libraries such as NumPy, Pandas, Matplotlib, Seaborn, scikit-learn, and others are imported. The dataset is loaded from a CSV file named "Telco-Customer-Churn.csv."

IV. DATA ANALYSIS

A. General Information about Dataset

Using df.dtypes, it was observed that the TotalCharges feature has object type. That's why the to_numeric function was implemented. Additionally, binary encoding was applied to Churn, which is the target value. Using the df.isnull().sum() function, it was analyzed how many missing values were in each feature.

customerID	gender	SeniorCitizen	Partner	Dependents	tenure	PhoneService	MultipleLines	InternetService	OnlineSecurity	OnlineBackup	DeviceProtection	TechSupport
0	Female	0	Yes	No	1	No	No phone service	DSL	No	No	No	No
1	5575-0808	Male	0	No	No	34	Yes	No	DSL	Yes	No	Yes
2	3568-CPWR	Male	0	No	No	2	Yes	No	DSL	Yes	No	No
3	7265-COCB	Male	0	No	No	45	No	No phone service	DSL	Yes	No	Yes
4	9237-HQIU	Female	0	No	No	2	Yes	No	Fiber optic	No	No	No

StreamingTV	StreamingMovies	Contract	PaperlessBilling	PaymentMethod	MonthlyCharges	TotalCharges	Churn
0	No	Month-to-month	Yes	Electronic check	29.850	29.850	0
1	No	One year	No	Auto bill check	56.950	1066.500	0
2	No	Month-to-month	Yes	Auto bill check	51.850	130.150	1
3	No	One year	No	Bank transfer (automatic)	42.300	1346.750	0
4	No	Month-to-month	Yes	Electronic check	70.700	101.600	1

customerID	0
gender	0
SeniorCitizen	0
Partner	0
Dependents	0
tenure	0
PhoneService	0
MultipleLines	0
InternetService	0
OnlineSecurity	0
OnlineBackup	0
DeviceProtection	0
TechSupport	0
StreamingTV	0
StreamingMovies	0
Contract	0
PaperlessBilling	0
PaymentMethod	0
MonthlyCharges	0
TotalCharges	11
Churn	0

There are 11 missing values in TotalCharges feature.

B. Handling categorical and numerical variables

Categorical features are identified by examining columns with object data types. Binary numerical features, characterized by having less than 10 unique values and not being of object data type, are also extracted. Similarly, cardinal features, defined by having more than 20 unique values and being of object data type, are identified. The final set of categorical features is formed by combining traditional categorical features, binary numerical features, and excluding cardinal features. Numeric features and numeric features excluding binary ones are also identified separately. The outcome is presented through printed statements, showcasing the categorized features for further analysis.


```
Categorical features: ['gender', 'Partner', 'Dependents', 'PhoneService', 'MultipleLines', 'InternetService', 'OnlineSecurity', 'OnlineBackup', 'DeviceProtection', 'TechSupport', 'StreamingTV', 'StreamingMovies', 'Contract', 'PaperlessBilling', 'PaymentMethod', 'SeniorCitizen', 'Churn']

Numerical features: ['tenure', 'MonthlyCharges', 'TotalCharges']

Binary numerical features: ['SeniorCitizen', 'Churn']
```


C. Analyzing Categorical Features

Analyzing by churn with using countplot. For example,




D. Analyzing Numerical Features

Analyzing with using boxplot. Also observing outliers. For example,



There are exactly 5 outliers in TotalCharges as it can be seen with the dots on the plot.



V. PREPROCESSING

A. Detecting and handling potential outliers in numerical columns

The interquartile range (IQR) method is employed to identify potential outliers. First and third quartiles (Q1 and Q3) are calculated, and the IQR is obtained by subtracting Q1 from Q3. The lower and upper bounds for potential outliers are then defined as values falling below $Q1 - 1.5 \times \text{IQR}$ and above $Q3 + 1.5 \times \text{IQR}$.


Subsequently, potential outliers are identified by comparing each value in the column against the defined bounds. The identified outliers are printed for examination:

Potential outliers:				
	customerID	gender	TotalCharges	Churn
0	7590-VHVEG	Female	111111111.850	0
17	9959-WOFKT	Male	111111111.250	0
28	5248-YGIJN	Male	333333333.450	0
32	6827-IEAUQ	Female	22222.450	0
39	8168-UQWVF	Female	333333333.400	1

To address the outliers, a filtered version of the dataset is created by excluding rows where the column values fall outside the determined bounds:

```
df = df[~((df[col] < lower_bound) | (df[col] > upper_bound))]
```

This process is repeated for each numerical column. Finally, a boxplot is generated for each column after outlier removal to visually inspect the impact on the distribution.



B. Analyzing and Handling Missing Values

The code calculates the number of missing values (n_miss) and the missing ratio (ratio) for each column in the na_columns list.

	n_miss	ratio
TotalCharges	11	0.160


Then, the code captures the columns with missing values in the "TotalCharges" column because we found the missing values only in this feature. Subsequently, it fills the missing values in the "TotalCharges" column with the median value of the available non-missing entries. This approach is a common technique for handling missing data, providing a summary of missing value statistics.

customerID	0
gender	0
SeniorCitizen	0
Partner	0
Dependents	0
tenure	0
PhoneService	0
MultipleLines	0
InternetService	0
OnlineSecurity	0
OnlineBackup	0
DeviceProtection	0
TechSupport	0
StreamingTV	0
StreamingMovies	0
Contract	0
PaperlessBilling	0
PaymentMethod	0
MonthlyCharges	0
TotalCharges	0
Churn	0


VI. CORRELATION

This part is focused on visualizing the correlation between numerical features in the dataset. The correlation matrix provides information about the linear relationship between pairs of numerical features.

As we see from matrix, all numerical features have positive correlation with each other which means they affect each other in the same way. Here this is correlation matrix with outliers:



And here is correlation matrix without outliers:



Outliers can inflate the covariance between variables, leading to higher correlation coefficients. By eliminating outliers, the covariance and correlation values may decrease, reflecting a more accurate representation of the relationships between variables in the absence of extreme data points.

The correlation matrix is calculated using the .corr() method in Pandas, which computes the Pearson correlation coefficients between pairs of numerical columns in the dataframe. The

Pearson correlation coefficient (r) is a measure of linear correlation between two variables and ranges from -1 to 1.

$$r = \frac{\sum (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum (x_i - \bar{x})^2 \sum (y_i - \bar{y})^2}}$$

VII. IMPLEMENTING FIRST MODEL



I chose to use the GradientBoosting algorithm for the first modeling. Gradient Boosting is an ensemble learning method that builds a sequence of weak learners (typically decision trees) to create a strong learner. It combines the predictions of individual models to improve overall performance. Since the target variable is "Churn" which is a binary classification task, Gradient Boosting is a suitable algorithm for such predictive modeling tasks.

Gradient Boosting and many other machine learning algorithms require numerical input, and they may struggle with categorical variables. One-Hot Encoding is employed to convert categorical variables into a format that is compatible with these algorithms. The "one_hot_encoder" function returns the dataframe with the original categorical columns replaced by their one-hot encoded counterparts.

The encoded "dff" is then used to define the target variable (y) as the "Churn" column, and the feature matrix (X) by dropping the "Churn" column and the "customerID" column. The dataset is split into training and testing sets using the "train_test_split" function.

Here is the first model evaluation values:


```
Accuracy: 0.8101
Recall: 0.6494
Precision: 0.5412
F1: 0.5904
Auc: 0.7512
```



VIII. FEATURE IMPORTANCE

The model assigns importance scores to each feature, indicating their contribution to the model's predictive performance. The feature names are obtained from the columns of the training set (X_train).

In my analysis, I saw that tenure, InternetService_FiberOptic and TotalCharges features are the most important ones that effects the model's performance.



IX. FEATURE SELECTION

The goal of feature selection is to identify and retain the most relevant features while discarding less influential ones, which can enhance model interpretability, reduce overfitting, and potentially improve model generalization to new data.

I firstly tried 0.1 as threshold but, it eliminate so much feature. Then I used 0.001 as threshold to determine the importance level. Features with importance scores equal or greater than this threshold are then selected and stored in the selected_features list. Subsequently, the training and testing datasets, denoted as X_train and X_test, are updated to exclusively include the chosen features. Following this, the model employs these chosen features to make predictions on the test set (X_test_selected).

