

# Metaprogramming with Macros

Eugene Burmako

École Polytechnique Fédérale de Lausanne  
<http://scalamacros.org/>

10 September 2012

# Macros

# Macros

Macros realize the notion of textual abstraction.

# Macros

Macros realize the notion of textual abstraction.

Textual abstraction:

- ▶ Recognize pieces of text that match a specification
- ▶ Replace them according to a procedure

## Example

```
(let (x 42) (print x))
```

```
((lambda (x) (print x)) 42)
```

## Example

```
(let (x 42) (print x))
```

```
(defmacro let args
```

```
((lambda (x) (print x)) 42)
```

## Example

```
(let (x 42) (print x))
```

```
(defmacro let args
  (cons
    (cons 'lambda
      (cons (list (caar args))
            (cdr args))))
    (cdar args)))
```

```
((lambda (x) (print x)) 42)
```

## Example

```
(let (x 42) (print x))
```

```
(defmacro let args  
  (cons  
    (cons 'lambda  
          (cons (list (caar args))  
                  (cdr args)))  
    (cdar args)))
```

```
((lambda (x) (print x)) 42)
```



# Why macros?

- ▶ Deeply embedded DSLs (database access, testing)
- ▶ Optimization (programmable inlining, fusion)
- ▶ Analysis (integrated proof-checker)
- ▶ Effects (effect containment and propagation)
- ▶ ...

# Today's talk

Macrology is vast:

- ▶ Notation
- ▶ Variable capture
- ▶ Typechecking meta-programs
- ▶ Syntax extensibility
- ▶ ...

# Today's talk

Macrology is vast:

- ▶ Notation
- ▶ Variable capture
- ▶ Typechecking meta-programs
- ▶ Syntax extensibility
- ▶ ...

Surveyed papers are versatile as well.

# Today's talk

Going into all the details is a genuine pleasure

But instead let me tell you a story

# Alexandre Dumas



# Outline

The story of bindings

## Anaphoric if

```
(aif (calculate)
      (print it)
      (error "does not compute"))
```

## Anaphoric if

```
(aif (calculate)
      (print it)
      (error "does not compute"))
```

```
(let* ((temp (calculate))
        (it temp))
      (if temp
          (print it)
          (error "does not compute")))
```



## The aif macro

```
(aif (calculate)
     (print it)
     (error "does not compute"))
```

```
(defmacro aif args
```

```
(let* ((temp (calculate))
        (it temp))
  (if temp
      (print it)
      (error "does not compute"))))
```

## Start with a template

```
(aif (calculate)
      (print it)
      (error "does not compute"))
```

```
(defmacro aif args
  (let* ((temp (car args))
         (it temp))
    (if temp
        (cadr args)
        (caddr args))))
```

```
(let* ((temp (calculate))
       (it temp))
  (if temp
      (print it)
      (error "does not compute")))
```

## Surround with parentheses

```
(aif (calculate)
  (print it)
  (error "does not compute"))
```

```
(defmacro aif args
  (list 'let* (list (list 'temp (car args))
                    (list 'it 'temp))
    (list 'if 'temp
          (cadr args)
          (caddr args))))
```

```
(let* ((temp (calculate))
      (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

## Quasiquote

```
(aif (calculate)
  (print it)
  (error "does not compute"))
```

```
(defmacro aif args
  '(let* ((temp .....))
    (it temp))
  (if temp
    .....
    .....)))
```

```
(let* ((temp (calculate))
  (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

## Unquote

```
(aif (calculate)
  (print it)
  (error "does not compute"))
```

```
(defmacro aif args
  '(let* ((temp ,(car args))
          (it temp))
    (if temp
      ,(cadr args)
      ,(caddr args))))
```

```
(let* ((temp (calculate))
      (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```