Metaprogramming with Macros

Eugene Burmako

École Polytechnique Fédérale de Lausanne http://scalamacros.org/

10 September 2012

Macros

2

Macros

Macros realize the notion of textual abstraction.

3

Macros

Macros realize the notion of textual abstraction.

Textual abstraction:

- Recognize pieces of text that match a specification
- ▶ Replace them according to a procedure

Example

```
(let (x 42) (print x))
```

Example

```
(let (x 42) (print x))
```

```
((lambda (x) (print x)) 42)
```

Step 1. Recognize pieces of text

```
(let (x 42) (print x))
(defmacro let args
```

```
((lambda (x) (print x)) 42)
```

Step 1. Recognize pieces of text

```
(let (x 42) (print x))
(defmacro let args
((lambda (x) (print x)) 42)
```

Step 2. Replace them according to a procedure

```
(let (x 42) (print x))
(defmacro let args
  (cons
   (cons 'lambda
         (cons (list (caar args))
               (cdr args)))
   (cdar args)))
((lambda (x) (print x)) 42)
```

Step 2. Replace them according to a procedure

```
(let (x 42) (print x))
(defmacro let args
  (cons
   (cons 'lambda
         (cons (list (caar args))
               (cdr args)))
   (cdar args)))
((lambda (x) (print x)) 42)
```

The essence of macros

- ▶ Recognize pieces of text that match a specification
- ▶ Replace them according to a procedure

Why macros?

- ► Deeply embedded DSLs (database access, testing)
- Optimization (programmable inlining, fusion)
- Analysis (integrated proof-checker)
- Effects (effect containment and propagation)
- **.**..

Today's talk

Macrology is vast:

- Notation
- ► Variable capture
- ► Typechecking meta-programs
- Syntax extensibility
- **.**..

Surveyed papers are versatile as well.

Today's talk

Going into all the details would be a genuine pleasure.

But instead let me tell you a story.

The prelude of macros

The tale of bindings

The trilogy of tongues

Anaphoric if

```
(aif (calculate)
  (print it)
  (error "does not compute"))
```

Anaphoric if

```
(aif (calculate)
  (print it)
  (error "does not compute"))
```

```
(let* ((temp (calculate))
        (it temp))
(if temp
        (print it)
        (error "does not compute")))
```

The aif macro

```
(aif (calculate)
  (print it)
  (error "does not compute"))
(defmacro aif args
```

```
(let* ((temp (calculate))
          (it temp))
  (if temp
          (print it)
          (error "does not compute")))
```

Start with a notation

```
(aif (calculate)
 (print it)
  (error "does not compute"))
(defmacro aif args
        (let*
                          ((temp (car args))
                           (it temp))
          (if temp
             (cadr args)
             (caddr args))))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

Surround it with parentheses

```
(aif (calculate)
 (print it)
  (error "does not compute"))
(defmacro aif args
  (list 'let* (list (list 'temp (car args))
                    (list 'it 'temp))
    (list 'if 'temp
             (cadr args)
             (caddr args))))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

Quasiquote

```
(aif (calculate)
  (print it)
  (error "does not compute"))
(defmacro aif args
       '(let*
                          ((temp ....)
                           (it temp))
          (if
               temp
             . . . . . . . . . . . .
             .....)))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

Unquote

```
(aif (calculate)
  (print it)
  (error "does not compute"))
(defmacro aif args
       '(let*
                          ((temp ,(car args))
                           (it temp))
          (if temp
            ,(cadr args)
            ,(caddr args))))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

```
Unquote
(aif (calculate)
  (print it)
  (error "does not compute"))
(defmacro aif args
    '(let* ((temp ,(car args))
            (it temp))
       (if temp
            ,(cadr args)
            (caddr args))))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

```
Macro by example (MBE)
(aif (calculate)
  (print it)
  (error "does not compute"))
(define-syntax aif
  (syntax-rules ()
    ((aif cond then else)
     (let* ((temp cond)
             (it temp))
       (if temp
           then
           else)))))
(let* ((temp (calculate))
       (it temp))
  (if temp
    (print it)
    (error "does not compute")))
```

Interlude

- ▶ Macros are regular functions that happen to work with syntax objects
- Quasiquotes = static templates + dynamic holes

The prelude of macros

The tale of bindings

The trilogy of tongues

The prelude of macros

The tale of bindings

The trilogy of tongues

The prelude of macros

The tale of bindings

The trilogy of tongues