



G2 FLOOR PLAN - DIMENSIONED
SCALE: 1/8" = 1'-0"
PLAN NORTH
TRUE NORTH

A2 FLOOR PLAN - NOTED
SCALE: 1/8" = 1'-0"
PLAN NORTH
TRUE NORTH

GENERAL NOTES - FLOOR PLAN

1. REFER TO G-SERIES SHEETS FOR ACCESSIBILITY REQUIREMENT STANDARDS. CONTACT ARCHITECT FOR DIRECTION IF ANY FIELD CONDITIONS CONFLICT WITH THESE REQUIREMENTS.
2. DIMENSIONS ARE TO FACE OF WALL UNO. DIMENSIONS IDENTIFIED AS "CLEAR", "MIN", OR "MAX" MUST BE MAINTAINED FROM FINISH. NOTIFY ARCHITECT IN WRITING OF ANY CONFLICTS.
3. SEE ENLARGED PLANS AND DETAILS FOR DIMENSIONS NOT INCLUDED ON THIS SHEET.
4. INTERIOR WALLS SHALL BE CONSTRUCTED AT 90 DEGREE ANGLES UNO.
5. REFER TO DOOR SCHEDULE FOR DOORS AND HARDWARE. PROVIDE STOPS AT ALL DOOR LOCATIONS UNO.
6. SET NEW DOOR FRAMES 8" MIN FROM PERPENDICULAR CMU WALL UNO.
7. LOOSE FURNITURE SHOWN FOR REFERENCE. GC TO INCLUDE ALLOWANCE FOR FURNITURE. SEE PROJECT MANUAL FOR ADDITIONAL INFO.
8. CONTRACTOR TO VERIFY ALL OFCI EQUIPMENT / MILLWORK MEETS ACCESSIBILITY STANDARDS.
9. MECHANICAL, PLUMBING, AND ELECTRICAL EQUIPMENT SHOWN FOR REFERENCE ONLY ON ARCHITECTURAL PLANS. COORDINATE ALL EQUIPMENT WITH CONSULTANT DRAWINGS.
10. REFER TO FINISH LEGEND FOR PAINT COLORS CALLED OUT ON REFLECTED CEILING PLANS AND FINISH PLANS.
11. UNLESS OTHERWISE NOTED, ALL FLOOR TILE SHALL BE CENTERED IN ROOM.
12. REFER TO RCP LEGEND ON OVERALL REFLECTED CEILING PLANS FOR RCP ABBREVIATIONS AND FINISHES.
13. WALL TILE AND BASE GROUT LINES SHALL ALIGN WITH FLOOR TILE.
14. INSULATED CONCRETE MASONRY UNIT TYPES VARY; VERIFY BLOCK TYPES AND LAYOUT WITH MANUFACTURER PRIOR TO COMMENCING MASONRY WORK.
15. COORDINATE ALL IN-WALL PLUMBING AND ELECTRICAL REQUIREMENTS WITH PLUMBING AND ELECTRICAL DRAWINGS PRIOR TO COMMENCING MASONRY WORK.
16. ALL PLUMBING AND ELECTRICAL INFRASTRUCTURE TO BE CONCEALED IN BLOCK CAVITY PER BLOCK MANUFACTURER DETAILS.
17. ALL WALL COVER PLATES TO BE BRUSHED STAINLESS STEEL.
18. DO NOT SCALE DRAWINGS. ANY DISCREPANCIES WITH DRAWINGS CONTACT DESIGNER.
19. VERIFY DIMENSIONS AND REQUIRED CLEARANCES FOR ALL ACCESSIBLE PLUMBING FIXTURES PRIOR TO UTILITY ROUGH-IN. LOCATE ROUGH-IN TO PROVIDE CLEARANCES AS REQUIRED BY GOVERNING ACCESSIBILITY STANDARDS. SEE SHEETS G1.11 AND G1.12.
20. LOW VOLTAGE CABLING AND DEVICES TO BE PROVIDED BY OWNER, NOT IN CONTRACT. GC TO COORD. ROUGH-IN REQUIREMENTS WITH OWNER'S VENDOR.

KEYNOTES

KEY	KEYNOTE
03 13	CONC FILLED STL BOLLARD, SEE SITE DETAILS
06 07	SECURE BASE & UPPER CABINETS W/ SS WORK SURFACE
07 13	PREFINISHED METAL DOWNSPOUT, COLOR TO BE SELECTED BY ARCHITECT
07 19	EXTENT OF ROOF / SOFFIT ABOVE, SEE CEILING PLAN AND ROOF PLAN
10 01	SS1 WIRE MESH KENNEL GATE ASSEMBLY
11 01	INCINERATOR, OFCI
11 02	FUEL STORAGE TANK, OFCI
11 03	CAT CAGES, OFCI
12 02	OFFICE DESK, OFCI - SEE PROJECT MANUAL FOR FURNITURE ALLOWANCE
12 04	OFFICE SECURE STORAGE CABINET, OFCI - SEE PROJECT MANUAL FOR FURNITURE ALLOWANCE
23 00	EXPOSED PAINTED DUCTWORK INTERNALLY INSULATED, SEE MECHANICAL
23 03	HEAT PUMP, SEE MECHANICAL
23 04	DEDICATED OUTDOOR AIR UNIT, SEE MECHANICAL
32 01	FENCING 4 GATES, SEE CIVIL
32 06	CONCRETE SIDEWALK, SEE CIVIL
32 08	PARKING SPACE WITH WHEEL STOP, SEE CIVIL
32 09	SITE UTILITY EQUIP, SEE CIVIL
32 14	ALUMINUM SHED, OFCI
32 17	GRAVEL FILLED DRAINAGE TRENCH, SEE CIVIL

WALL TYPE LEGEND

- 4" CMU WALL
- 8" CMU WALL
- 8" INSULATED CMU WALL
- 8" INSULATED CMU WALL (2 HOUR FIRE RATING)

FRANKLIN CO. ANIMAL CONTROL FACILITY
GEORGE FRALEY PARKWAY
WINCHESTER, TN 37398

FLOOR PLANS

ISSUE DATE

PERMIT DOCUMENTS 12-12-2023

Goodwyn Mills Cawood, LLC
3310 West End Avenue, Suite 420
Nashville, TN 37203
T 615.333.7200
GMCNETWORK.COM

DRAWN BY:

CHECKED BY:

GMC # ANAS230037



A1.01