
# in minimizing magnetic field gradients for the nEDM search

Aritra Biswas
Filippone Group, Kellogg Radiation Laboratory


August 7, 2014

# nEDM = neutron electric dipole moment

- up quark:  $\frac{2}{3}e$
- ► each down quark:  $-\frac{1}{3}e$
- electric dipole moment:
   vector measuring separation
   between + and charges
   and their orientation



#### why does the nEDM matter?



- $\triangleright$   $C: q \mapsto -q$
- $P:(t,x,y,z)\mapsto(t,x,-y,z)$
- $ightharpoonup T: (t, x, y, z) \mapsto (-t, x, y, z)$
- CPT symmetry
  - + P violation
  - + T violation
  - $\Rightarrow$  *CP* violation
- reformulations of Standard Model
- matter-antimatter asymmetry

#### how do we measure the nEDM?

- put ultra-cold neutrons (UCN) in E and B fields
- lacktriangleright neutron will precess at frequency  $\omega$


$$\omega_{\uparrow\uparrow} = -\frac{\mu_n B + d_n E}{J\hbar}, \quad \omega_{\uparrow\downarrow} = -\frac{\mu_n B - d_n E}{J\hbar}$$
 (1)

$$\Delta\omega = \pm \frac{2d_n E}{J\hbar} \pm \Delta\omega_{geo} \tag{2}$$

- ▶  $\frac{\partial \mathbf{B}}{\partial (x,y,z)} \neq 0 \Rightarrow \frac{\partial \mathbf{B}}{\partial t} \neq 0 \Rightarrow \text{effect of } \mathbf{E} \text{ field } \Rightarrow \Delta \omega_{geo}$
- ▶ geometric phase ⇒ false measurement!


Pendlebury et. al. Geometric-phase-induced false electric dipole moment signals for particles in traps. Phys. Rev. A. 70, 032102 (2004).

# creating an uniform magnetic field




- ▶  $B_0$  coil:  $\cos \theta$  coil geometry, emulates sheet current
- ► ferromagnetic Metglas shield
- superconducting axial shield
- superconducting upper endcap

### original comparison, warm




# Metglas thickness

Field slice in [m]: x = -0.1, y = 0.0, z = nan




### Metglas 10 cm longer on top


Field slice in [m]: x = -0.1, y = 0.0, z = nan




# correction 1: probe measurement time




#### correction 2: x centering



# correction 2: x centering, superconducting




#### correction 2: x centering, superconducting, 1.4 cm offset




### comparison, superconducting

Field slice in [m]: x = 0.086, y = 0.0, z = nan




#### correction 3: probe axis offset



- 3 separate 1-axis probes
- incomplete vector map
- need to store z-axis offset vector along with z array
- OffsetAxis class to return proper spatial axis array based on desired vector component


#### comparison, superconducting, no offsets

Field slice in [m]: x = 0.1, y = 0.0, z = nan




#### comparison, superconducting, x-centering and axis offset

Field slice in [m]: x = 0.086, y = 0.0, z = nan



# correction 4: probe tilt



$$B_x = B_x' \cos \theta - B_z' \sin \theta, \quad B_z = B_z' \cos \theta + B_x' \sin \theta \tag{3}$$

1.  $\theta$  is small:

$$B_x = B_x' - B_z'\theta, \quad B_z = B_z' + B_x'\theta$$

2.  $B_z = 0$  at center:

$$\theta = -\frac{B_z'}{B_x'}$$

# comparison, superconducting

