

MY LEETCODE

REVISION HANDBOOK

Patterns • Complexity • Solutions • Recall

40 problems

Built for active recall before interviews — understand the pattern, then rebuild the code.

SMALL STEPS. REPEATED RECALL. STRONGER DSA.

Revision Index

Find a problem by number, pattern, or difficulty.

NO.	PROBLEM	PATTERN	LEVEL
0001	1. Two Sum	Hashing / Set	Easy
0002	2. Add Two Numbers	Linked List	Medium
0003	3. Longest Substring Without Repeating Characters	Hashing / Set	Medium
0004	4. Median of Two Sorted Arrays	Sorting	Hard
0007	7. Reverse Integer	Math / Simulation	Medium
0009	9. Palindrome Number	Math / Simulation	Easy
0011	11. Container With Most Water	Two Pointers	Medium
0014	14. Longest Common Prefix	Arrays / Implementation	Easy
0019	19. Remove Nth Node From End of List	Linked List	Medium
0021	21. Merge Two Sorted Lists	Linked List	Easy
0024	24. Swap Nodes in Pairs	Linked List	Medium
0033	33. Search in Rotated Sorted Array	Arrays / Implementation	Medium
0034	34. Find First and Last Position of Element in Sorted Array	Binary Search	Medium
0035	35. Search Insert Position	Binary Search	Easy
0041	41. First Missing Positive	Hashing / Set	Hard
0049	49. Group Anagrams	Hashing / Set	Medium
0053	53. Maximum Subarray	Greedy / Kadane	Medium
0076	76. Minimum Window Substring	Hashing / Set	Hard
0081	81. Search in Rotated Sorted Array II	Binary Search	Medium
0094	94. Binary Tree Inorder Traversal	Binary Search	Easy
0098	98. Validate Binary Search Tree	Binary Search	Medium
0100	100. Same Tree	Binary Search	Easy
0101	101. Symmetric Tree	Binary Search	Easy
0121	121. Best Time to Buy and Sell Stock	Greedy / Kadane	Easy
0122	122. Best Time to Buy and Sell Stock II	Greedy / Kadane	Medium
0128	128. Longest Consecutive Sequence	Hashing / Set	Medium
0135	135. Candy	Arrays / Implementation	Hard
0189	189. Rotate Array	Math / Simulation	Medium
0209	209. Minimum Size Subarray Sum	Arrays / Implementation	Medium
0215	215. Kth Largest Element in an Array	Arrays / Implementation	Medium
0239	239. Sliding Window Maximum	Two Pointers	Hard
0342	342. Power of Four	Arrays / Implementation	Easy

NO.	PROBLEM	PATTERN	LEVEL
0455	455. Assign Cookies	Sorting	Easy
0628	628. Maximum Product of Three Numbers	Sorting	Easy
0701	784. Insert into a Binary Search Tree	Binary Search	Medium
0896	932. Monotonic Array	Arrays / Implementation	Easy
1438	1549. Longest Continuous Subarray With Absolute Diff Less Than or Equal to Limit	Sliding Window	Medium
2426	2513. Number of Pairs Satisfying Inequality	Binary Search	Hard
3718	4080. Smallest Missing Multiple of K	Hashing / Set	Easy
3867	4242. Sum of GCD of Formed Pairs	Sorting	Medium

#0001

PROBLEM

1. Two Sum

DIFFICULTY

Easy

PATTERN

Hashing / Set

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0001

1. Two Sum

Easy

Hashing / Set

C++

QUESTION



Given an array of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`.



Example

Input: `nums = [2,7,11,15]`, `target = 9` Output: `[0,1]` Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$ avg.



SPACE COMPLEXITY

$O(n)$



PATTERN

Hashing / Set

</> Solution (C++)

Problem 0001

```
class Solution {
public:
    vector<int> twoSum(vector<int>& nums, int target) {
        unordered_map<int, int> mp;
        for (int i = 0; i < nums.size(); i++) {
            int x = target - nums[i];
            if (mp.find(x) != mp.end()) {
                return {mp[x], i};
            }
            mp[nums[i]] = i;
        }
        return {};
    }
};
```

#0002

PROBLEM

2. Add Two Numbers

DIFFICULTY

Medium

PATTERN

Linked List

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0002

2. Add Two Numbers

Medium

Linked List

C++

QUESTION

- ✓ You are given two non-empty linked lists representing two non-negative integers. The digits are stored in reverse order, and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list.

Example

Input: l1 = [2,4,3], l2 = [5,6,4] Output: [7,0,8] Explanation: 342 + 465 = 807.

Visual Representation



pattern → nodes → result

✓ TIME COMPLEXITY
O(n)

✓ SPACE COMPLEXITY
O(1)

✓ PATTERN
Linked List

</> Solution (C++)

Problem 0002

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     ListNode *next;
 *     ListNode() : val(0), next(nullptr) {}
 *     ListNode(int x) : val(x), next(nullptr) {}
 *     ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    ListNode* addTwoNumbers(ListNode* l1, ListNode* l2) {
        ListNode* dummy = new ListNode(0);
        ListNode* temp = dummy;
        int carry = 0;
        while (l1 != NULL || l2 != NULL || carry != 0) {
            int sum = carry;
            if (l1 != NULL) {
                sum += l1->val;
                l1 = l1->next;
            }
            if (l2 != NULL) {
                sum += l2->val;
                l2 = l2->next;
            }
            carry = sum / 10;
            temp->next = new ListNode(sum % 10);
            temp = temp->next;
        }
        return dummy->next;
    }
};
```

PROBLEM 0003

#0003

PROBLEM

3. Longest Substring Without Repeating Characters

DIFFICULTY

Medium

PATTERN

Hashing / Set

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

3. Longest Substring Without Repeating Characters

Medium

Hashing / Set

C++

QUESTION



Given a string s , find the length of the longest substring without duplicate characters.



Example

Input: $s = \text{"abcabcbb"}$ Output: 3 Explanation: The answer is "abc", with the length of 3. Note that "bca" and "cab" are also correct answers.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ avg.

SPACE COMPLEXITY

 $O(n)$ 

PATTERN

Hashing / Set

</> Solution (C++)

Problem 0003

```
class Solution {
public:
    int lengthOfLongestSubstring(string s) {
        unordered_set<char> st;
        int left = 0;
        int maxi = 0;
        for (int right = 0; right < s.size(); right++) {
            while (st.find(s[right]) != st.end()) {
                st.erase(s[left]);
                left++;
            }
            st.insert(s[right]);
            maxi = max(maxi, right - left + 1);
        }
        return maxi;
    }
};
```

#0004

PROBLEM

4. Median of Two Sorted Arrays

DIFFICULTY

Hard

PATTERN

Sorting

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0004

4. Median of Two Sorted Arrays

Hard

Sorting

C++

QUESTION



Given two sorted arrays `nums1` and `nums2` of size `m` and `n` respectively, return the median of the two sorted arrays.



Example

Input: `nums1 = [1,3]`, `nums2 = [2]` Output: 2.00000
Explanation: merged array = `[1,2,3]` and median is 2.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n \log n)$



SPACE COMPLEXITY

$O(n) / O(1)$



PATTERN

Sorting

</> Solution (C++)

Problem 0004

```
class Solution {
public:
    double findMedianSortedArrays(vector<int>& nums1, vector<int>& nums2) {
        nums1.insert(nums1.end(), nums2.begin(), nums2.end());
        sort(nums1.begin(), nums1.end());
        if(nums1.size()%2==0){
            return (nums1[(nums1.size()/2)-1]+nums1[nums1.size()/2])/2.0;
        }
        else{
            return nums1[nums1.size()/2.0];
        }
        return{};
    }
};
```

PROBLEM 0007

#0007

PROBLEM

7. Reverse Integer

DIFFICULTY

Medium

PATTERN

Math / Simulation

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

7. Reverse Integer

Medium

Math / Simulation

C++

QUESTION



Given a signed 32-bit integer x , return x with its digits reversed. If reversing x causes the value to go outside the signed 32-bit integer range $[-2^{31}, 2^{31} - 1]$, then return 0.



Example

Input: $x = 123$ Output: 321



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Math / Simulation

</> Solution (C++)

Problem 0007

```
class Solution {
public:
    int reverse(int x) {
        int rev = 0;

        while(x!=0){
            int d = x%10;
            if(rev > INT_MAX/10 || rev < INT_MIN/10)
                return 0;
            rev = rev*10 + d;
            x=x/10;
        }
        return rev;
    }
};
```

PROBLEM 0009

#0009

PROBLEM

9. Palindrome Number

DIFFICULTY

Easy

PATTERN

Math / Simulation

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

9. Palindrome Number

Easy

Math / Simulation

C++

QUESTION



Given an integer x , return true if x is a palindrome, and false otherwise.



Example

Input: $x = 121$ Output: true Explanation: 121 reads as 121 from left to right and from right to left.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Math / Simulation

</> Solution (C++)

Problem 0009

```
class Solution {
public:
    bool isPalindrome(int x){
        if (x < 0)
            return false;
        if (x != 0 && x % 10 == 0)
            return false;
        int rev = 0;
        while (x > rev) {
            rev = rev * 10 + x % 10;
            x /= 10;
        }
        if(x==rev || x==rev/10)
            return true;
        else
            return false;
    }
};
```

PROBLEM 0011

#0011

PROBLEM

11. Container With Most Water

DIFFICULTY

Medium

PATTERN

Two Pointers

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

11. Container With Most Water

Medium

Two Pointers

C++

QUESTION



You are given an integer array height of length n. There are n vertical lines drawn such that the two endpoints of the ith line are (i, 0) and (i, height[i]).



Example

Input: height = [1,8,6,2,5,4,8,3,7] Output: 49
Explanation: The above vertical lines are represented by array [1,8,6,2,5,4,8,3,7]. In this case, the max area of water (blue section) the container can contain is 49.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Two Pointers

</> Solution (C++)

Problem 0011

```
class Solution {
public:
    int maxArea(vector<int>& height) {
        int left = 0;
        int right = height.size()-1;
        int area = 0;
        while(left<right){
            int h = min(height[left],height[right]);
            int a = h*(right-left);
            area = max(a,area);
            if(height[left]<height[right]){
                left++;
            }
            else{
                right--;
            }
        }
        return area;
    }
};
```

#0014

PROBLEM

14. Longest Common Prefix

DIFFICULTY

Easy

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0014

14. Longest Common Prefix

Easy

Arrays / Implementation

C++

QUESTION



Write a function to find the longest common prefix string amongst an array of strings.



Example

Input: strs = ["flower","flow","flight"]
Output: "fl"



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)



SPACE COMPLEXITY

O(1)



PATTERN

Arrays / Implementation

</> Solution (C++)

Problem 0014

```
class Solution {
public:
    string longestCommonPrefix(vector<string>& strs) {

        string prefix = strs[0];

        for(int i = 1; i < strs.size(); i++) {

            int j = 0;

            while(j < prefix.size() &&
                  j < strs[i].size() &&
                  prefix[j] == strs[i][j]) {
                j++;
            }

            prefix = prefix.substr(0, j);

            if(prefix == "")
                return "";
        }

        return prefix;
    }
};
```

#0019

PROBLEM

19. Remove Nth Node From End of List

DIFFICULTY

Medium

PATTERN

Linked List

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0019

19. Remove Nth Node From End of List

Medium

Linked List

C++

QUESTION



Given the head of a linked list, remove the nth node from the end of the list and return its head.



Example

Input: head = [1,2,3,4,5], n = 2 Output: [1,2,3,5]



Visual Representation



pattern → nodes → result



TIME COMPLEXITY

O(n)



SPACE COMPLEXITY

O(1)



PATTERN

Linked List

</> Solution (C++)

Problem 0019

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     ListNode *next;
 *     ListNode() : val(0), next(nullptr) {}
 *     ListNode(int x) : val(x), next(nullptr) {}
 *     ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    ListNode* removeNthFromEnd(ListNode* head, int n) {
        ListNode *dummy = new ListNode(0);
        dummy->next = head;
        ListNode *temp=head;
        int count = 0;
        while(temp!=NULL){
            temp = temp->next;
            count++;
        }
        int k=count-n;
        temp = dummy;
        while(k>0){
            temp=temp->next;
            k--;
        }
        ListNode *temp1=temp->next;
        temp->next=temp1->next;
        delete temp1;
        ListNode* newHead = dummy->next;
        delete dummy;
        return newHead;
    }
};
```

#0021

PROBLEM

21. Merge Two Sorted Lists

DIFFICULTY

Easy

PATTERN

Linked List

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0021

21. Merge Two Sorted Lists

Easy

Linked List

C++

QUESTION

✓ You are given the heads of two sorted linked lists list1 and list2.

Example

Input: list1 = [1,2,4], list2 = [1,3,4] Output: [1,1,2,3,4,4]

Visual Representation



pattern → nodes → result

✓ TIME COMPLEXITY
O(n)

✓ SPACE COMPLEXITY
O(1)

✓ PATTERN
Linked List

</> Solution (C++)

Problem 0021

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     ListNode *next;
 *     ListNode() : val(0), next(nullptr) {}
 *     ListNode(int x) : val(x), next(nullptr) {}
 *     ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    ListNode* mergeTwoLists(ListNode* list1, ListNode* list2) {
        if(list1==NULL){return list2;}
        if(list2==NULL){return list1;}
        ListNode* dummy=new ListNode(-1);
        ListNode* temp = dummy;
        while(list1!=NULL && list2!=NULL){
            if(list1->val<=list2->val){
                temp->next=list1;
                list1=list1->next;
            }
            else{
                temp->next=list2;
                list2=list2->next;
            }
            temp=temp->next;
        }
        if(list1!=NULL){
            temp->next=list1;
        }
        else{
            temp->next=list2;
        }
        return dummy->next;
    }
};
```

#0024

PROBLEM

24. Swap Nodes in Pairs

DIFFICULTY

Medium

PATTERN

Linked List

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

24. Swap Nodes in Pairs

Medium

Linked List

C++

QUESTION



Given a linked list, swap every two adjacent nodes and return its head. You must solve the problem without modifying the values in the list's nodes (i.e., only nodes themselves may be changed.)



Example

Input → Output



Visual Representation



pattern → nodes → result



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Linked List

</> Solution (C++)

Problem 0024

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     ListNode *next;
 *     ListNode() : val(0), next(nullptr) {}
 *     ListNode(int x) : val(x), next(nullptr) {}
 *     ListNode(int x, ListNode *next) : val(x), next(next) {}
 * };
 */
class Solution {
public:
    ListNode* swapPairs(ListNode* head) {
        ListNode* dummy = new ListNode(0);
        dummy->next = head;
        ListNode* temp = dummy;
        while(temp->next != NULL && temp->next->next != NULL) {
            ListNode* first = temp->next;
            ListNode* second = first->next;
            first->next = second->next;
            second->next = first;
            temp->next = second;
            temp = first;
        }
        ListNode* newHead = dummy->next;
        delete dummy;
        return newHead;
    }
};

```

PROBLEM 0033

33. Search in Rotated Sorted Array

Medium

Arrays / Implementation

C++

QUESTION

✓ There is an integer array `nums` sorted in ascending order (with distinct values).

Example

Input: `nums = [4,5,6,7,0,1,2]`, `target = 0`
Output: 4

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Arrays / Implementation

</> Solution (C++)

Problem 0033

```
class Solution {
public:
    int search(vector<int>& nums, int target) {
        for(int i=0;i<nums.size();i++){
            if(nums[i]==target){
                return i;
            }
        }
        return -1;
    }
};
```

#0033

PROBLEM

33. Search in Rotated Sorted Array

DIFFICULTY

Medium

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

#0034

PROBLEM

34. Find First and Last Position of Element in Sorted Array

DIFFICULTY

Medium

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0034

34. Find First and Last Position of Element in Sorted Array

Medium

Binary Search

C++

QUESTION

- ✓ Given an array of integers `nums` sorted in non-decreasing order, find the starting and ending position of a given target value.

Example

Input: `nums = [5,7,7,8,8,10]`, `target = 8`
Output: `[3,4]`

Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$



SPACE COMPLEXITY

$O(1)$



PATTERN

Binary Search

</> Solution (C++)

Problem 0034

```
class Solution {
public:
    vector<int> searchRange(vector<int>& nums, int target) {
        int first = -1;
        int last = -1;
        // Find first occurrence
        int left = 0;
        int right = nums.size() - 1;
        while (left <= right) {
            int mid = left + (right - left) / 2;
            if (nums[mid] == target) {
                first = mid;
                right = mid - 1; // search left
            }
            else if (target > nums[mid]) {
                left = mid + 1;
            }
            else {
                right = mid - 1;
            }
        }
        // Find last occurrence
        left = 0;
        right = nums.size() - 1;
        while (left <= right) {
            int mid = left + (right - left) / 2;
            if (nums[mid] == target) {
                last = mid;
                left = mid + 1; // search right
            }
            else if (target > nums[mid]) {
                left = mid + 1;
            }
            else {
                right = mid - 1;
            }
        }
        return {first, last};
    }
};
```

#0035

PROBLEM

35. Search Insert Position

DIFFICULTY

Easy

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0035

35. Search Insert Position

Easy

Binary Search

C++

QUESTION

- ✓ Given a sorted array of distinct integers and a target value, return the index if the target is found. If not, return the index where it would be if it were inserted in order.

Example

Input: nums = [1,3,5,6], target = 5 Output: 2

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Binary Search

</> Solution (C++)

Problem 0035

```
class Solution {
public:
    int searchInsert(vector<int>& nums, int target) {
        int left = 0;
        int right = nums.size()-1;
        while(left<=right){
            int mid = left + (right - left)/2;
            if(nums[mid]==target){
                return mid;
            }
            if(target>nums[mid]){
                left=mid+1;
            }
            else{
                right=mid-1;
            }
        }
        return left;
    }
};
```

#0041

PROBLEM

41. First Missing Positive

DIFFICULTY

Hard

PATTERN

Hashing / Set

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0041

41. First Missing Positive

Hard

Hashing / Set

C++

QUESTION



Given an unsorted integer array `nums`. Return the smallest positive integer that is not present in `nums`.



Example

Input: `nums = [1,2,0]` Output: 3 Explanation: The numbers in the range `[1,2]` are all in the array.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$ avg.



SPACE COMPLEXITY

$O(n)$



PATTERN

Hashing / Set

`</>` **Solution (C++)**

Problem 0041

```
class Solution {
public:
    int firstMissingPositive(vector<int>& nums) {
        unordered_set<int> st;
        for(int x:nums){
            st.insert(x);
        }
        for(int i =1;i<=nums.size();i++){
            if(st.find(i)==st.end()){
                return i;
            }
        }
        return nums.size()+1;
    }
};
```

PROBLEM 0049

#0049

PROBLEM

49. Group Anagrams

DIFFICULTY

Medium

PATTERN

Hashing / Set

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

49. Group Anagrams

Medium

Hashing / Set

C++

QUESTION



Given an array of strings `strs`, group the anagrams together. You can return the answer in any order.



Example

Input → Output



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n \log n)$ 

SPACE COMPLEXITY

 $O(n) / O(1)$ 

PATTERN

Hashing / Set

</> Solution (C++)

Problem 0049

```
class Solution {
public:
    vector<vector<string>> groupAnagrams(vector<string>& strs) {
        unordered_map<string, vector<string>> mp;
        for(string s: strs){
            string key = s;
            sort(key.begin(), key.end());
            mp[key].push_back(s);
        }
        vector<vector<string>> ans;
        for(auto x: mp){
            ans.push_back(x.second);
        }
        return ans;
    }
};
```

PROBLEM 0053

#0053

PROBLEM

53. Maximum Subarray

DIFFICULTY

Medium

PATTERN

Greedy / Kadane

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

53. Maximum Subarray

Medium

Greedy / Kadane

C++

QUESTION



Given an integer array `nums`, find the subarray with the largest sum, and return its sum.



Example

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]` Output: 6
 Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Greedy / Kadane

</> Solution (C++)

Problem 0053

```
class Solution {
public:
    int maxSubArray(vector<int>& nums) {
        int sum = 0;
        int maxsum = INT_MIN;
        for(int i = 0; i < nums.size(); i++){
            sum += nums[i];
            maxsum = max(maxsum, sum);
            if(sum < 0){
                sum = 0;
            }
        }
        return maxsum;
    }
};
```

#0076

PROBLEM

76. Minimum Window Substring

DIFFICULTY

Hard

PATTERN

Hashing / Set

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0076

76. Minimum Window Substring

Hard

Hashing / Set

C++

QUESTION

- ✓ Given two strings s and t of lengths m and n respectively, return the minimum window substring of s such that every character in t (including duplicates) is included in the window. If there is no such substring, return the empty string $""$.

Example

Input: $s = \text{"ADOBECODEBANC"} , t = \text{"ABC"}$ Output: "BANC" Explanation: The minimum window substring "BANC" includes 'A', 'B', and 'C' from string t .

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n)$ avg.

✓ SPACE COMPLEXITY
 $O(n)$

✓ PATTERN
Hashing / Set

</> Solution (C++)

Problem 0076

```
class Solution {
public:
    string minWindow(string s, string t) {
        unordered_map<char,int> n,w;
        for(char c:t) n[c]++;
        int l = 0,start=0;
        int req = n.size();
        int have = 0;
        int len = INT_MAX ;
        for(int r = 0; r<s.size(); r++){
            w[s[r]]++;
            if(n.count(s[r]) && w[s[r]]==n[s[r]]){
                have++;
            }
            while(have == req){
                if(r-l+1 < len){
                    len = r-l+1;
                    start = l;
                }
                w[s[l]]--;
                if(n.count(s[l])&&w[s[l]]<n[s[l]]){
                    have--;
                }
                l++;
            }
        }
        if(len == INT_MAX) return "";
        return s.substr(start,len);
    }
};
```

#0081

PROBLEM

81. Search in Rotated Sorted Array II

DIFFICULTY

Medium

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

PROBLEM 0081

81. Search in Rotated Sorted Array II

Medium

Binary Search

C++

QUESTION



There is an integer array `nums` sorted in non-decreasing order (not necessarily with distinct values).



Example

Input: `nums = [2,5,6,0,0,1,2]`, `target = 0`
Output: `true`



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$



SPACE COMPLEXITY

$O(1)$



PATTERN

Binary Search

</> Solution (C++)

Problem 0081

```
class Solution {
public:
    bool search(vector<int>& nums, int target) {
        int left = 0;
        int right = nums.size() - 1;
        while (left <= right) {
            int mid = left + (right - left) / 2;
            if (nums[mid] == target)
                return true;
            // Duplicates: cannot determine which half is sorted
            if (nums[left] == nums[mid] && nums[mid] == nums[right]) {
                left++;
                right--;
            }
            // Left half is sorted
            else if (nums[left] <= nums[mid]) {
                if (nums[left] <= target && target < nums[mid])
                    right = mid - 1;
                else
                    left = mid + 1;
            }
            // Right half is sorted
            else {
                if (nums[mid] < target && target <= nums[right])
                    left = mid + 1;
                else
                    right = mid - 1;
            }
        }
        return false;
    }
};
```

PROBLEM 0094

#0094

PROBLEM

94. Binary Tree Inorder Traversal

DIFFICULTY

Easy

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

94. Binary Tree Inorder Traversal

Easy

Binary Search

C++

QUESTION



Given the root of a binary tree, return the inorder traversal of its nodes' values.



Example

Input → Output



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Binary Search

</> Solution (C++)

Problem 0094

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
 * };
 */
class Solution {
public:
    vector<int> ans;
    vector<int> inorderTraversal(TreeNode* root) {
        if(root == NULL)
            return ans;
        inorderTraversal(root->left);
        ans.push_back(root->val);
        inorderTraversal(root->right);
        return ans;
    }
};
```

#0098

PROBLEM

98. Validate Binary Search Tree

DIFFICULTY

Medium

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

PROBLEM 0098

98. Validate Binary Search Tree

Medium

Binary Search

C++

QUESTION

- ✓ Given the root of a binary tree, determine if it is a valid binary search tree (BST).

Example

Input: root = [2,1,3] Output: true

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Binary Search

</> Solution (C++)

Problem 0098

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
 * };
 */
class Solution {
public:
    bool check(TreeNode* root, long long low, long long high){
        if(root == NULL) return true;
        if (root->val <= low || root->val >= high)
            return false;
        return check(root->left, low, root->val)&&check(root->right, root->val, high);
    }
    bool isValidBST(TreeNode* root) {
        return check(root, LLONG_MIN, LLONG_MAX);
    }
};
```

#0100

PROBLEM

100. Same Tree

DIFFICULTY

Easy

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

PROBLEM 0100

100. Same Tree

Easy

Binary Search

C++

QUESTION



Given the roots of two binary trees p and q , write a function to check if they are the same or not.



Example

Input: $p = [1,2,3]$, $q = [1,2,3]$ Output: true



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$



SPACE COMPLEXITY

$O(1)$



PATTERN

Binary Search

</> Solution (C++)

Problem 0100

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
 * };
 */
class Solution {
public:
    bool isSameTree(TreeNode* p, TreeNode* q) {
        if(p==NULL && q==NULL) return true;
        if(p==NULL || q==NULL) return false;
        if(p->val!=q->val) return false;
        return isSameTree(p->left,q->left)&&isSameTree(p->right,q->right);
    }
};
```

#0101

PROBLEM

101. Symmetric Tree

DIFFICULTY

Easy

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

PROBLEM 0101

101. Symmetric Tree

Easy

Binary Search

C++

QUESTION



Given the root of a binary tree, check whether it is a mirror of itself (i.e., symmetric around its center).



Example

Input: root = [1,2,2,3,4,4,3] Output: true



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)



SPACE COMPLEXITY

O(1)



PATTERN

Binary Search

</> Solution (C++)

Problem 0101

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
 * };
 */
class Solution {
public:
    bool mirror(TreeNode* left, TreeNode* right) {
        if (left == NULL && right == NULL)
            return true;
        if (left == NULL || right == NULL)
            return false;
        if (left->val != right->val)
            return false;
        return mirror(left->left, right->right) &&
            mirror(left->right, right->left);
    }
    bool isSymmetric(TreeNode* root) {
        if (root == NULL)
            return true;
        return mirror(root->left, root->right);
    }
};
```

PROBLEM 0121

#0121

PROBLEM

121. Best Time to Buy and Sell Stock

DIFFICULTY

Easy

PATTERN

Greedy / Kadane

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

[Pattern](#) → [recall](#) → [re-implement](#)

121. Best Time to Buy and Sell Stock

Easy

Greedy / Kadane

C++

QUESTION



You are given an array prices where prices[i] is the price of a given stock on the ith day.



Example

Input: prices = [7,1,5,3,6,4] Output: 5
Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6-1 = 5. Note that buying on day 2 and selling on day 1 is not allowed because you must buy before you sell.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Greedy / Kadane

</> Solution (C++)

Problem 0121

```
class Solution {
public:
    int maxProfit(vector<int>& prices) {
        int minprice = prices[0];
        int profit = 0;
        for(int i =1;i<prices.size();i++){
            minprice= min(minprice,prices[i]);
            profit = max(profit,prices[i]-minprice);
        }
        return profit;
    }
};
```

PROBLEM 0122

#0122

PROBLEM

122. Best Time to Buy and Sell Stock II

DIFFICULTY

Medium

PATTERN

Greedy / Kadane

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

122. Best Time to Buy and Sell Stock II

Medium

Greedy / Kadane

C++

QUESTION



You are given an integer array prices where prices[i] is the price of a given stock on the ith day.



Example

Input: prices = [7,1,5,3,6,4] Output: 7
 Explanation: Buy on day 2 (price = 1) and sell on day 3 (price = 5), profit = 5-1 = 4. Then buy on day 4 (price = 3) and sell on day 5 (price = 6), profit = 6-3 = 3. Total profit is 4 + 3 = 7.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Greedy / Kadane

</> Solution (C++)

Problem 0122

```
class Solution {
public:
    int maxProfit(vector<int>& prices) {
        int profit=0;
        for(int i = 1;i<prices.size();i++){
            if(prices[i]>prices[i-1]){
                profit = profit + prices[i] - prices[i-1];
            }
        }
        return profit;
    }
};
```

PROBLEM 0128

#0128

PROBLEM

128. Longest Consecutive Sequence

DIFFICULTY

Medium

PATTERN

Hashing / Set

LANGUAGE

C++

128. Longest Consecutive Sequence

Medium

Hashing / Set

C++

QUESTION



Given an unsorted array of integers `nums`, return the length of the longest consecutive elements sequence.



Example

Input: `nums = [100,4,200,1,3,2]` Output: 4
Explanation: The longest consecutive elements sequence is `[1, 2, 3, 4]`. Therefore its length is 4.



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ avg.

SPACE COMPLEXITY

 $O(n)$ 

PATTERN

Hashing / Set

</> Solution (C++)

Problem 0128

```
class Solution {
public:
    int longestConsecutive(vector<int>& nums) {
        unordered_set<int> st(nums.begin(), nums.end());
        int ans = 0;
        for(int x:st){
            if(st.find(x-1) == st.end()){
                int current = x;
                int count = 1;
                while(st.find(current+1) != st.end()){
                    current++;
                    count++;
                }
                ans = max(ans, count);
            }
        }
        return ans;
    }
};
```

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

#0135

PROBLEM

135. Candy

DIFFICULTY

Hard

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0135

135. Candy

Hard

Arrays / Implementation

C++

QUESTION

- ✓ There are n children standing in a line.

Example

Input: ratings = [1,0,2] Output: 5 Explanation: You can allocate to the first, second and third child with 2, 1, 2 candies respectively.

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n^2)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Arrays / Implementation

</> Solution (C++)

Problem 0135

```
class Solution {
public:
    int candy(vector<int>& ratings) {
        int n = ratings.size();
        vector<int> candy(n, 1);
        for(int i = 1; i < n; i++) {
            if(ratings[i] > ratings[i-1])
                candy[i] = candy[i-1] + 1;
        }
        for(int i = n-2; i >= 0; i--) {
            if(ratings[i] > ratings[i+1])
                candy[i] = max(candy[i], candy[i+1] + 1);
        }
        int count = 0;
        for(int x : candy)
            count += x;
        return count;
    }
};
```

PROBLEM 0189

#0189

PROBLEM

189. Rotate Array

DIFFICULTY

Medium

PATTERN

Math / Simulation

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

189. Rotate Array

Medium

Math / Simulation

C++

QUESTION



Given an integer array `nums`, rotate the array to the right by `k` steps, where `k` is non-negative.



Example

Input: `nums = [1,2,3,4,5,6,7]`, `k = 3` Output: `[5,6,7,1,2,3,4]` Explanation: rotate 1 steps to the right: `[7,1,2,3,4,5,6]` rotate 2 steps to the right: `[6,7,1,2,3,4,5]` rotate 3 steps to the right: `[5,6,7,1,2,3,4]`



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Math / Simulation

</> Solution (C++)

Problem 0189

```
class Solution {
public:
    void rotate(vector<int>& nums, int k) {
        k = k % nums.size();
        reverse(nums.begin(), nums.end());
        reverse(nums.begin(), nums.begin() + k);
        reverse(nums.begin() + k, nums.end());
    }
};
```

PROBLEM 0209

#0209

PROBLEM

209. Minimum Size Subarray Sum

DIFFICULTY

Medium

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

209. Minimum Size Subarray Sum

Medium

Arrays / Implementation

C++

QUESTION

- ✓ Given an array of positive integers `nums` and a positive integer `target`, return the minimal length of a subarray whose sum is greater than or equal to `target`. If there is no such subarray, return 0 instead.

Example

Input: `target = 7, nums = [2,3,1,2,4,3]` Output: 2
 Explanation: The subarray `[4,3]` has the minimal length under the problem constraint.

Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ 

SPACE COMPLEXITY

 $O(1)$ 

PATTERN

Arrays / Implementation

</> Solution (C++)

Problem 0209

```
class Solution {
public:
    int minSubArrayLen(int target, vector<int>& nums) {
        int l=0;
        int sum=0;
        int len = INT_MAX;
        for(int r=0;r<nums.size();++r){
            sum += nums[r];
            while(sum>=target){
                len = min(r-l+1,len);
                sum-=nums[l];
                ++l;
            }
        }
        if(len == INT_MAX) return 0;
        return len;
    }
};
```

#0215

PROBLEM

215. Kth Largest Element in an Array

DIFFICULTY

Medium

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0215

215. Kth Largest Element in an Array

Medium

Arrays / Implementation

C++

QUESTION



Given an integer array `nums` and an integer `k`, return the `k`th largest element in the array.



Example

Input: `nums = [3,2,1,5,6,4]`, `k = 2` Output: 5



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$



SPACE COMPLEXITY

$O(1)$



PATTERN

Arrays / Implementation

</> Solution (C++)

Problem 0215

```
class Solution {
public:
    int findKthLargest(vector<int>& nums, int k) {
        priority_queue<int, vector<int>, greater<int>> pq;
        for(int x:nums){
            pq.push(x);
            if(pq.size()>k){
                pq.pop();
            }
        }
        return pq.top();
    }
};
```

#0239

PROBLEM

239. Sliding Window Maximum

DIFFICULTY

Hard

PATTERN

Two Pointers

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 0239

239. Sliding Window Maximum

Hard

Two Pointers

C++

QUESTION

- ✓ You are given an array of integers `nums`, there is a sliding window of size `k` which is moving from the very left of the array to the very right. You can only see the `k` numbers in the window. Each time the sliding window moves right by one position.

Example

Input: `nums = [1,3,-1,-3,5,3,6,7]`, `k = 3`
Output: `[3,3,5,5,6,7]` Explanation: Window
position Max ----- [1 3 -1] -3
5 3 6 7 3 1 [3 -1 -3] 5 3 6 7 3 1 3 [-1 -3 5] 3
6 7 5 1 3 -1 [-3 5 3] 6 7 5 1 3 -1 -3 [5 3 6] 7
6 1 3 -1 -3 5 [3 6 7] 7

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Two Pointers

</> Solution (C++)

Problem 0239

```
class Solution {
public:
    vector<int> maxSlidingWindow(vector<int>& nums, int k) {
        deque<int> dq;
        vector<int> ans;
        for (int r = 0; r < nums.size(); r++) {
            // Remove elements outside the window
            while (!dq.empty() && dq.front() <= r - k) {
                dq.pop_front();
            }
            // Remove smaller elements
            while (!dq.empty() && nums[dq.back()] <= nums[r]) {
                dq.pop_back();
            }
            // Add current index
            dq.push_back(r);
            // Window size is k
            if (r >= k - 1) {
                ans.push_back(nums[dq.front()]);
            }
        }
        return ans;
    }
};
```

PROBLEM 0342

#0342

PROBLEM

342. Power of Four

DIFFICULTY

Easy

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

342. Power of Four

Easy

Arrays / Implementation

C++

QUESTION



Given an integer n , return true if it is a power of four. Otherwise, return false.



Example

Input: $n = 16$ Output: true



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

$O(n)$



SPACE COMPLEXITY

$O(1)$



PATTERN

Arrays / Implementation

</> Solution (C++)

Problem 0342

```
class Solution {
public:
    bool isPowerOfFour(int n) {
        if(n<=0) return false;
        while(n%4==0){
            n/=4;
        }
        return n==1;
    }
};
```

PROBLEM 0455

#0455

PROBLEM

455. Assign Cookies

DIFFICULTY

Easy

PATTERN

Sorting

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

455. Assign Cookies

Easy

Sorting

C++

QUESTION



Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.



Example

Input: $g = [1, 2, 3]$, $s = [1, 1]$ Output: 1
 Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3. And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content. You need to



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n \log n)$ 

SPACE COMPLEXITY

 $O(n) / O(1)$ 

PATTERN

Sorting

</> Solution (C++)

Problem 0455

```
class Solution {
public:
    int findContentChildren(vector<int>& g, vector<int>& s) {
        sort(g.begin(), g.end());
        sort(s.begin(), s.end());
        int i = 0;
        int j = 0;
        int count = 0;
        while (i < g.size() && j < s.size()) {
            if (s[j] >= g[i]) {
                count++;
                i++;
                j++;
            }
            else {
                j++;
            }
        }
        return count;
    }
};
```

PROBLEM 0628

#0628

PROBLEM

628. Maximum Product of Three Numbers

DIFFICULTY

Easy

PATTERN

Sorting

LANGUAGE

C++

628. Maximum Product of Three Numbers

Easy

Sorting

C++

QUESTION

✓ You are given an integer array `nums`.

Example

Input → Output

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n \log n)$

✓ SPACE COMPLEXITY
 $O(n) / O(1)$

✓ PATTERN
Sorting

</> Solution (C++)

Problem 0628

```
class Solution {
public:
    int maximumProduct(vector<int>& nums) {
        sort(nums.begin(), nums.end());
        int n = nums.size();
        int a = nums[n-1] * nums[n-2] * nums[n-3];
        int b = nums[0] * nums[1] * nums[n-1];
        return max(a, b);
    }
};
```

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

#0701

PROBLEM

784. Insert into a Binary Search Tree

DIFFICULTY

Medium

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

784. Insert into a Binary Search Tree

Medium

Binary Search

C++

QUESTION



You are given the root node of a binary search tree (BST) and a value to insert into the tree. Return the root node of the BST after the insertion. It is guaranteed that the new value does not exist in the original BST.



Example

Input: root = [4,2,7,1,3], val = 5 Output: [4,2,7,1,3,5] Explanation: Another accepted tree is:



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Binary Search

</> Solution (C++)

Problem 0701

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode() : val(0), left(nullptr), right(nullptr) {}
 *     TreeNode(int x) : val(x), left(nullptr), right(nullptr) {}
 *     TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {}
 * };
 */
class Solution {
public:
    TreeNode* insertIntoBST(TreeNode* root, int val) {
        // Empty position found
        if(root == NULL) {
            return new TreeNode(val);
        }
        // Go right
        if(val > root->val) {
            root->right = insertIntoBST(root->right, val);
        }
        // Go left
        else {
            root->left = insertIntoBST(root->left, val);
        }
        return root;
    }
};
```

PROBLEM 0896

#0896

PROBLEM

932. Monotonic Array

DIFFICULTY

Easy

PATTERN

Arrays / Implementa...

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

932. Monotonic Array

Easy

Arrays / Implementation

C++

QUESTION



An array is monotonic if it is either monotone increasing or monotone decreasing.



Example

Input: nums = [1,2,2,3] Output: true



Visual Representation

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

O(n)

SPACE COMPLEXITY

O(1)

PATTERN

Arrays / Implementa...

</> Solution (C++)

Problem 0896

```
class Solution {
public:
    bool isMonotonic(vector<int>& nums) {
        bool increasing = true;
        bool decreasing = true;
        for(int i = 0; i < nums.size() - 1; i++) {
            if(nums[i] > nums[i+1])
                increasing = false;
            if(nums[i] < nums[i+1])
                decreasing = false;
        }
        return increasing || decreasing;
    }
};
```

#1438

PROBLEM

1549. Longest Continuous Subarray With Absolute Diff Less Than or Equal to Limit

DIFFICULTY

Medium

PATTERN

Sliding Window

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

1549. Longest Continuous Subarray With Absolute Diff Less Than or Equal to Limit

Medium

Sliding Window

C++

QUESTION

- Given an array of integers `nums` and an integer `limit`, return the size of the longest non-empty subarray such that the absolute difference between any two elements of this subarray is less than or equal to `limit`.

Example

Input: `nums = [8,2,4,7]`, `limit = 4` Output: 2
 Explanation: All subarrays are: `[8]` with maximum absolute diff $|8-8| = 0 \leq 4$. `[8,2]` with maximum absolute diff $|8-2| = 6 > 4$. `[8,2,4]` with maximum absolute diff $|8-2| = 6 > 4$. `[8,2,4,7]` with maximum absolute diff $|8-2| = 6 > 4$.

Visual Representation

INPUT

PATTERN

OUTPUT

TIME COMPLEXITY
 $O(n)$

SPACE COMPLEXITY
 $O(1)$

PATTERN
Sliding Window

Solution (C++)

Problem 1438

```
class Solution {
public:
    int longestSubarray(vector<int>& nums, int limit) {
        deque<int> maxi;
        deque<int> mini;
        int l = 0;
        int ans = 0;
        for (int r = 0; r < nums.size(); r++) {
            // Maintain decreasing deque for maximum
            while (!maxi.empty() && nums[maxi.back()] < nums[r]) {
                maxi.pop_back();
            }
            maxi.push_back(r);
            // Maintain increasing deque for minimum
            while (!mini.empty() && nums[mini.back()] > nums[r]) {
                mini.pop_back();
            }
            mini.push_back(r);
            // Window invalid
            while (nums[maxi.front()] - nums[mini.front()] > limit) {
                if (maxi.front() == l)
                    maxi.pop_front();
                if (mini.front() == l)
                    mini.pop_front();
                l++;
            }
            ans = max(ans, r - l + 1);
        }
        return ans;
    }
};
```

#2426

PROBLEM

2513. Number of Pairs Satisfying Inequality

DIFFICULTY

Hard

PATTERN

Binary Search

LANGUAGE

C++

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 2426

2513. Number of Pairs Satisfying Inequality

Hard

Binary Search

C++

QUESTION

- ✓ You are given two 0-indexed integer arrays `nums1` and `nums2`, each of size `n`, and an integer `diff`. Find the number of pairs (i, j) such that:

Example

Input: `nums1 = [3,2,5]`, `nums2 = [2,2,1]`, `diff = 1` Output: 3 Explanation: There are 3 pairs that satisfy the conditions: 1. $i = 0, j = 1: 3 - 2 \leq 2 - 2 + 1$. Since $i < j$ and $1 \leq 1$, this pair satisfies the conditions. 2. $i = 0, j = 2: 3 - 5 \leq 2 - 1 + 1$. Since $i < j$ and $-2 \leq 2$, this

Visual Representation

INPUT

PATTERN

OUTPUT

✓ TIME COMPLEXITY
 $O(n^2)$

✓ SPACE COMPLEXITY
 $O(1)$

✓ PATTERN
Binary Search

</> Solution (C++)

Problem 2426

```
class Solution {
public:
    long long mergeSort(vector<long long>& a, int l, int r, int diff) {
        if(l >= r) return 0;
        int mid = l + (r - l) / 2;
        long long count = 0;
        count += mergeSort(a, l, mid, diff);
        count += mergeSort(a, mid + 1, r, diff);
        // Count pairs: i in left, j in right
        int j = mid + 1;
        for(int i = l; i <= mid; i++) {
            while(j <= r && a[i] > a[j] + diff)
                j++;
            count += r - j + 1;
        }
        // Normal merge
        vector<long long> temp;
        int i = l;
        j = mid + 1;
        while(i <= mid && j <= r) {
            if(a[i] <= a[j])
                temp.push_back(a[i++]);
            else
                temp.push_back(a[j++]);
        }
        while(i <= mid)
            temp.push_back(a[i++]);
        while(j <= r)
            temp.push_back(a[j++]);
        for(int k = l; k <= r; k++)
            a[k] = temp[k - l];
        return count;
    }
    long long numberOfPairs(vector<int>& nums1, vector<int>& nums2, int diff) {
        int n = nums1.size();
        vector<long long> a(n);
        for(int i = 0; i < n; i++)
            a[i] = (long long)nums1[i] - nums2[i];
        return mergeSort(a, 0, n - 1, diff);
    }
};
```

PROBLEM 3718

#3718

PROBLEM

4080. Smallest Missing Multiple of K

DIFFICULTY

Easy

PATTERN

Hashing / Set

LANGUAGE

C++

4080. Smallest Missing Multiple of K

Easy

Hashing / Set

C++

QUESTION

Given an integer array `nums` and an integer `k`, return the smallest positive multiple of `k` that is missing from `nums`.

**Example**

Input → Output

**Visual Representation**

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n)$ avg.

SPACE COMPLEXITY

 $O(n)$ 

PATTERN

Hashing / Set</> **Solution (C++)**

Problem 3718

```
class Solution {
public:
    int missingMultiple(vector<int>& nums, int k) {
        unordered_set<int> st;
        for(int x : nums){
            st.insert(x);
        }
        for(int i=1;i<=nums.size()+1;i++){
            int x = k*i;
            if(st.find(x)==st.end()){
                return x;
            }
        }
        return -1;
    }
};
```

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement

PROBLEM 3867

#3867

PROBLEM

4242. Sum of GCD of Formed Pairs

DIFFICULTY

Medium

PATTERN

Sorting

LANGUAGE

C++

4242. Sum of GCD of Formed Pairs

Medium

Sorting

C++

QUESTIONYou are given an integer array `nums` of length `n`.**Example**

Input → Output

**Visual Representation**

INPUT

PATTERN

OUTPUT



TIME COMPLEXITY

 $O(n \log n)$ 

SPACE COMPLEXITY

 $O(n) / O(1)$ 

PATTERN

Sorting**</> Solution (C++)**

Problem 3867

```

class Solution {
public:
    long long gcdSum(vector<int>& nums) {
        vector<int> g;
        int m = 0;
        int a = 0;
        for(int i = 0; i < nums.size(); i++){
            m = max(m, nums[i]);
            a = gcd(nums[i], m);
            g.push_back(a);
        }
        long long sum = 0;
        int b = 0;
        sort(g.begin(), g.end());
        for(int i = 0; i < g.size()/2; i++){
            b = gcd(g[i], g[g.size()-1-i]);
            sum += b;
        }
        return sum;
    }
};

```

QUICK LINKS

- [LeetCode](#)
- [Notes](#)
- [Similar Problems](#)

Last revised

27 Sep 2026

Pattern → recall → re-implement