



**Mondragon
Unibertsitatea**

Faculty of
Engineering

AdaBoost

Xabier Etxezarreta

AdaBoost

1

Internals

2

Scikit-Learn

3

Example (Jupyter Notebook)

4

References


1

AdaBoost Internals

Internals - What is AdaBoost?

- **AdaBoost** is a machine learning **meta-algorithm**
- **Boosting** originated from the question of whether a set of **weak classifiers** could be converted to a **strong classifier**.
- AdaBoost stands for '**Adaptive Boosting**' which transforms weak learners or predictors to **strong predictors** in order to solve problems of classification.
- Improves the **performance** of machine learning algorithms.

Internals - How AdaBoost works?




- Classification problem
- 10 instances
 - 5 positive
 - 5 negative

Internals - How AdaBoost works?

AdaBoost first iteration

- Blue zone (positive zone)
- Red zone (negative zone)

Incorrectly classified instances will have a **greater importance** in the next iteration.




Internals - How AdaBoost works?

AdaBoost second iteration

- Blue zone (positive zone)
- Red zone (negative zone)


Incorrectly classified instances will have a **greater importance** in the next iteration.




Internals - How AdaBoost works?

AdaBoost third iteration

- Blue zone (positive zone)
- Red zone (negative zone)



Internals - How AdaBoost works?



Internals - AdaBoost Pros and Cons

- **Pros**
 - Fast, simple and easy to program.
 - Flexibility to be combined with any algorithm.
- **Cons**
 - Boosting increases the overall complexity of your system
 - Weak classifiers being too weak can lead to low margins and overfitting.

2

AdaBoost

Scikit-Learn

Internals - AdaBoost Pros and Cons

`sklearn.ensemble`.AdaBoostClassifier

```
class sklearn.ensemble. AdaBoostClassifier (base_estimator=None, n_estimators=50, learning_rate=1.0,  
algorithm='SAMME.R', random_state=None) \[source\]
```

base_estimator

- The base estimator from which the boosted ensemble is built.
- Base estimator → *DecisionTreeClassifier(max_depth=1)*

n_estimators

- The maximum number of estimators at which boosting is terminated.
- The number of weak learners is controlled by this parameter.
- In case of perfect fit, the learning procedure is stopped early.

The **main parameters to tune** to obtain good results are **n_estimators** and the **complexity of the base estimators** (e.g., its depth `max_depth` or minimum required number of samples to consider a split `min_samples_split`).

3

AdaBoost Example

Example - AdaBoost



https://github.com/xetxezarreta/Aprendizaje_Automatico/blob/master/02_classification_adaboost/adaboost.ipynb

4

References

References

- <https://www.educba.com/adaboost-algorithm/>
- <https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.AdaBoostClassifier.html>
- <https://medium.com/soldai/ensamble-de-clasificadores-usando-adaboost-50bc2ca47640>
- <https://machinelearningmastery.com/boosting-and-adaboost-for-machine-learning/>
- <http://rob.schapire.net/papers/explaining-adaboost.pdf>



**Mondragon
Unibertsitatea**

Faculty of
Engineering

Eskerrik asko
Muchas gracias
Thank you

Xabier Etxezarreta

xabier.etxezarreta@alumni.mondragon.edu