

coop-writing v1.0

Geraldo Xexéo

Sunday 30th May, 2021 - 01:44

Contents

1	Introduction	2
1.1	A bit of context	3
1.2	The Brazilian origin	3
2	How to use coop-writing	3
2.1	Using from Overleaf	3
3	Package Options	4
3.1	Command oriented options	5
3.2	State oriented options	5
3.3	General behavior	5
4	Version	6
5	Editorial comments	6
5.1	Creating authors	6
5.2	Available commands	7
5.2.1	Comments	7
5.3	Striked-throught comments	8
5.4	Text Modification - Suggestions	8
5.5	Putting more warning in text	9
5.6	A tip for using comments	9
6	Draft environment	10
7	Subjects	11
8	Lists	11
9	To dos	11
10	Warnings	12

11 The commands in Portuguese	12
11.1 Opções em Português	13
12 Comparision with other packages	13
13 Implementation	13
13.1 Access to the current version	13
13.2 Option Processing	14
13.2.1 Creating Options Variables	14
13.2.2 Portuguese Options	14
13.2.3 English Options, from ed package	14
13.2.4 Original English Options	14
13.2.5 Fixing the Super Options	15
13.3 Required Packages	15
13.4 Optional Packages	16
13.5 Color related variables	16
13.6 I18N Almost Using Babel	17
13.7 ed inspired code	18
13.8 More for the footnote	18
13.9 The margin note	19
13.10Anonimization	20
13.11Subjects	21
13.12Editorial Comments	21
13.13Suggestions, Removes and Changes	23
13.14Citations Needed	23
13.15Draft	24
13.16Powerful command to create editors and authors	24
13.17To do notes	25
13.18Portuguese/English, or inverse translation table	26

1 Introduction

This package supports editorial comments and gives some extra support for writing papers, or any document that involves more than one author or editor.

Usually, a final version of a document would be printed with the `publish` option turned one, and no editorial comment would appear. In this document `the reader will see some uses`¹ of the package, since it is distributted with the `editing` option turned on. This is done because I must provide the examples of use. A version using `publish` is available to be used as a comparision.

¹XEXÉO:This is an exemple of using this package to make a comment with highlighted text

1.1 A bit of context

`coop-writing` was written to support my way of working, and received suggestions from my students. The starting goal was to build only a front-end to put together other packages, but with time, and the difficulty to make different packages with commands that have the same name work together, it grew in scope.

It picks ideas from different packages, such as `ed`[Koh11], `color-edits`[Kem20], and `todonotes`[Mid21], and from my practice writing papers and supervising thesis. As it is my first package, \LaTeX and \LaTeX programming is sometimes naive. However, due to the large amount of available code, and sites as StackExchange, this is not a rule.

1.2 The Brazilian origin

Originally, `coop-writing` was written in Portuguese. The Portuguese commands are still available.

2 How to use coop-writing

`coop-writing` is available as open source at <https://github.com/xexeo/coop-writing>. The stable distribution is in the folder `dist`, while the latest, and unstable, will be in the root folder.

The only file you really need, besides this manual, is `coop-writing.sty`. This should be in your \LaTeX path, such as in the same folder that your main `.tex` file.

If you are new to \LaTeX , just put one of these 3 lines in the preamble part of your document, i.e., before `\begin{document}`:

```
\usepackage[editing]{coop-writing}
\usepackage[submit]{coop-writing}
\usepackage[publish]{coop-writing}
```

After that, you can use `\cwauthor` or `\cweditor` to make commentaries, but you must look at the many options available that are described in section 5. You will probably want to define authors as described in subsection 5.1.

You can make suggestions, complain about bugs, and request features using GitHub’s “Issues” feature, in <https://github.com/xexeo/coop-writing/issues> (you must be signed in).

2.1 Using from Overleaf

The best way to use `coop-writing` inside Overleaf is to link the distributed style file through its URL. To do that, inside your project, select first “Up-

load”. An “Add files” window will appear, then select “From External URL” and enter `https://raw.githubusercontent.com/xexeo/coop-writing/main/dist/coop-writing.sty` as “URL to fetch the file from” and “coop-writing” as “File Name in This Project”, as in Figure 1.




Figure 1: How to link a `coop-writing.sty` file in your project folder in Overleaf to the official distribution.

3 Package Options

Using the package allows the use of all macros and environments described in this manual, however, **if the options are not turned on, there will be no effect on the generated pdf**, since, by default, all options are false.

There are two types of options. The first type enables the visualization of the result of specific macros or environments, such as the `cwdraft` environment. They are named *command oriented options*. You can use many of them in the same time.

The second type represent a state of the text, which can be editing, submit, or publish, and some minor variations. They are named *state oriented options*.

If they appear together, state oriented commands have precedence over the others. However, the user should avoid mixing command and state oriented options. Also, most of the time, you should **use only one of the state oriented options**.

It should be clear that the options have no impact on the availability of the macros and environments, they will be there for you to use, but they deeply affect their behavior. A macro that is very complex, such as `\cwauthor`, if one of options `comments` or `editing` is selected, is replaced by a simple version that does almost nothing.

3.1 Command oriented options

- | | |
|--------------------------|---|
| <code>subjects</code> | • <code>subjects</code> , enables the use of <code>\subject</code> , which is proposed as a paragraph heading describing its subject; |
| <code>comments</code> | • <code>comments</code> , enables all editorial comments and the command <code>\pleasecite</code> ; |
| <code>drafts</code> | • <code>drafts</code> , enables the <code>\cwdraft</code> command; |
| <code>suggestions</code> | • <code>suggestions</code> , enables the comments defined in the suggestion section of this text. |
| <code>anonymize</code> | • <code>anonymize</code> , enables anonymization commands, and |
| <code>todos</code> | • <code>todos</code> , enables the to do family of commands. |

3.2 State oriented options

- | | |
|-------------------------------|---|
| <code>submit</code> | • <code>submit</code> , enables the submit state. Anonimization is on, subjects, comments, drafts and suggestions are off |
| <code>noanonymize</code> | • <code>noanonymize</code> , disables anonymizations even in <code>submit</code> and <code>editing</code> options |
| <code>publish</code> | • <code>publish</code> , disables all command oriented options, ignore suggestions. |
| <code>acceptingpublish</code> | • <code>acceptingpublish</code> , disables all command oriented options, accept suggestions |
| <code>editing</code> | • <code>editing</code> , enables subjects, comments, drafts and suggestions. |

3.3 General behavior

The general behavior of this package is to provide different ways of marking your text, for example with comments or to do notes, that can be totally suppressed when desired. Mostly, this can be easily done using one of the 3 main option states: `editing`, `submit`, and `publish`.

Users should use the `editing` state most of the time. In this state, all markings will appear and the anonymization will be off.

When submitting, the `submit` state will provide a clean article, without any markings. Most of the times the article should be anonymized, but if this is not enforced, it is possible to use the options `submit` and `noanonymize` together. `publish` will never anonymize.

The goal is to make the `submit` and `publish` documents states minimally invasive, to avoid any clash with publishers' styles. A clash will be considered a bug, and should be reported to the authors.

If you use comments, there will be a lot of "Marginpar moved" warnings. This is normal behavior, caused by the margin notes.

4 Version

It is possible that the user wants to know the version being used. We provide two commands for it.

<code>\coopwritingversion</code>	Provides the current version
<code>\printcoopwritingversion</code>	Provides name and version

`\coopwritingversion` was used in the title of this article. The current version is v1.0.

If needed, the second macro prints also the name of the package:

`\printcoopwritingversion`

will result in:

coop-writing v. v1.0

Please state the version when reporting bugs.

5 Editorial comments

This is the main reason of this package.

The idea is that not only users can make editorial comments on the text they are writing, but they can also establish a dialog through those comments. In this package an editorial comment has 3 visual parts: an intervention in the text, a margin note indicating this intervention, and a footnote explaining it². Figure 2 illustrate this behavior.

Xexéo:2




Figure 2: How comments appear in the document when `editing` option is on.

5.1 Creating authors

`\cwnamedef` This macro creates a series of commands based on a desired base command name. The command name is, usually, the name of the author, of the editor, or a function in the work being done.

²XEXÉO:This is the simplest form of an editorial note.

It must be given in the preamble of the \LaTeX document, i.e., before the `\begin{document}` declaration. It is usually done just after the `\usepackage{coop-writing}` line. Its syntax is:

```
\cwnamedef {<name>}{<color>}{<author-name>}
```

Where $\langle name \rangle$ will be the base command name, which generates different commands by receiving suffixes, $\langle color \rangle$ is the color to be used by all comments and suggestions made by this author, and $\langle author-name \rangle$ is the string to be used to represent the author.

As an example, I usually declare myself as:

```
\cwnamedef{xexeo}{red}{Xexéo}
```

And, among other commands, `\xexeo` will be defined in such a way that it generates a footnote written in red, with a indicative margin note in the same color. Both will be identified with “Xexéo”³.

The $\langle name \rangle$ and $\langle author-name \rangle$ are different to support short command names and characters not supported in \LaTeX macros. Therefore, if your name is *Gutenberg* you can create a family of commenting macros based on `\gut`, but use “Gutenberg” as your identifier.

`\cwaauthor` Two authors are pre-defined in the style, `cwaauthor` and `cweditor`, to represent an author and an editor.

5.2 Available commands

For each user created with command name $\langle name \rangle$, such as `cwaauthor` and `cweditor`, used as example, the following commands are available.

5.2.1 Comments

```
\<name>      \<name> [<selection>]{<footnote comment>}
\cwaauthor   \cwaauthor [<selection>]{<footnote comment>}
\cweditor    \cweditor  [<selection>]{<footnote comment>}
```

These are the simplest commands, and will make a comment in the form of a identified footnote⁴. They can also be used to highlight some text⁵.

```
\<name>r      \<name>r [<selection>]{<footnote comment>}{<label>}
\cwaauthorr   \cwaauthorr [<selection>]{<footnote comment>}{<label>}
\cweditorr    \cweditorr  [<selection>]{<footnote comment>}{<label>}
```

³XEXÉO: This is the example of the minimal use of an editorial command

⁴AUTHOR: Simplest footnote comment

⁵EDITOR: Comment with highlighting

Author:6
Author:7

This command will make a comment in the form of a labeled footnote⁶. It can also be used to **highlight some text**⁷. The label must be unique, since it is used as a L^AT_EX label too.

5.3 Striked-throught comments

After using the editorial comments for a time we started to delete the old ones that represented fixed problems. However, we notice that some comments should be kept, even if solved. The solution was to create the striked-throught comments. They are easy to use, just put an x after the command name.

```
\<name>x      \<name>x [<selection>]{<footnote comment>}  
\cworthorx    \cworthorx [<selection>]{<footnote comment>}  
\cworthorx    \cworthorx [<selection>]{<footnote comment>}
```

Editor:8
Author:9

This command will make a comment in the form of a footnote⁸, however the comment is striked through. It can also be used to **highlight some text**⁹.

```
\<name>rx      \<name>rx [<selection>]{<footnote comment>}{<label>}  
\cworthorrx    \cworthorrx [<selection>]{<footnote comment>}{<label>}  
\cworthorrx    \cworthorrx [<selection>]{<footnote comment>}{<label>}
```

Author:10
Author:11

This command will make a comment in the form of a labeled footnote¹⁰, however the comment is striked through. It can also be used to **highlight some text**¹¹. The label must be unique, since it is used as a L^AT_EX label too.

5.4 Text Modification - Suggestions

Sometimes one of the authors wants to insert, remove or edit some text, but he or she is not sure that every one will agree, therefore he or she can make a suggestion, that will appear with his or her color.

```
\<name>sug      \<name>sug [<comment>]{<suggested text>}  
\cworthorsug    \cworthorsug [<comment>]{<suggested text>}  
\cworthorsug    \cworthorsug [<comment>]{<suggested text>}
```

This macro supports making a suggestion. It inserts text, using the color chosen by the author. It is also possible to make a comment, but in this command the command is the optional argument.

⁶ AUTHOR[FIRST LABEL]:labeled footnote comment

⁷ AUTHOR[YET ANOTHER LABEL]:labeled comment with highlighting

⁸ EDITOR:Simplest footnote comment

⁹ AUTHOR:Comment with highlighting

¹⁰ AUTHOR[SECOND LABEL]:labeled footnote comment

¹¹ AUTHOR[NEW LABEL]:labeled comment with highlighting

Editor:12

As example, in this paragraph the **inserted text** will appears in the red, and it is possible to **use a comment**¹².

```
\<name>rem      \<name>rem[<comment>]{<suggested removal>}
\cworthorrem    \cworthorrem[<comment>]{<suggested removal>}
\cweditorrem    \cweditorrem[<comment>]{<suggested removal>}
```

This macro is used to suggest removals.

Author:13

This is an example ~~that is quite good~~. Again, it is also possible to comment the ~~the removal~~¹³ removal.

```
\<name>swap      \<name>swap[<comment>]{<suggested removal>}{<suggested insertion>}
\cworthorswap    \cworthorswap[<comment>]{<suggested removal>}{<suggested insertion>}
\cweditorswap    \cweditorswap[<comment>]{<suggested removal>}{<suggested insertion>}
```

This will work as the union of a removal and a suggestion. Actually, both are simplified forms of this command.

~~This should work like this~~. This is an example of how the command should work.

5.5 Putting more warning in text

It is possible to define a symbol, or any other thing, to appear before the superscript number that indicates the comment.

`\cwsetcommwarn` This is done using the following command and syntax:

```
\cwsetcommwarn{<symbol>}
```

Using package `marvosym`, the example:

```
\cwsetcommwarn{\Lightning}
```

Xexéo:14

will change the behavior of editorial¹⁴ comments to include the `ℑ` symbol.

You can remove the symbol by simply using `\cwsetcommwarn{}`

It should be clear that `coop-writing` does not provide any font. If the user wants to use one font, like `marvosym`, he or she must import it with `\usepackage`.

5.6 A tip for using comments

A student asked me to give a priority to my demands. This would make me add yet another set of commands, with more arguments. labels don't work because they must be unique to allow for being used as references.

¹²EDITOR:I want to insert this

¹³AUTHOR:Repeated words

¹⁴XEXÉO:This comment superscript number should be preceded by a `ℑ`

The solution, however, is simple, special characters, such as `*`, `$_star$` can be used and are highly efficient to communicate priority¹⁵.

Using other fonts, more can be accomplished. For example, package `marvosym` offers `\HollowBox`, `□`, `\Checkedbox`, `☑`, `\CrossedBox`, `☒`, which can be used to indicate that something should be done, is done or will not be done.

6 Draft environment

`cwdraft` The `cwdraft` environment aims to allow writers to include text that is marked somehow as a draft¹

This environment is evolving, looking for a good way to signal the draft status, due to the different interactions with the packages it uses and user's packages. It has one optional parameter that names the draft. Its default value is “Draft” If the `draft` option is not enabled, the text inside the title and the text inside the environment will not appear. The user should remember that some options will automatically turn on the `draft` option, such as the option `edicao`.

`\cssetdraftcolor` The color of the title highlight can be changed with

`\cssetdraftcolor{<color>}`

The example:

```
\begin{cwdraft}[A draft title]
This is the example of a draft.
The title must be highlighted
There must be a box around it.
\end{cwdraft}
```

```
\cwsetdraftcolor{blue}
\begin{cwdraft}
This draft has the default title.
\end{cwdraft}
```

generates:

A draft title

This is the example of a draft.

The title must be highlighted

¹⁵ XEXÉO:★★ Two stars are still low priority

¹This was motivated because my students liked to hide text from me because “it was only a draft”, but I need to have some way to measure if they were advancing. Marking text as a draft allowed them to be free of the fear of showing errors to me. I see it most as a psychological support to writing without fear of making mistakes. And, yes, you can still use footnotes and they will be correctly numbered

There must be a box around it.

Draft

This draft has the default title.

7 Subjects

`\cwssubject` `\cwssubject[<color>]{<text>}`

These are supposed to help organizing a text by giving a “title” for each paragraph.

The idea here is that each paragraph should be about one and only one subject, and that reading these paragraph title will allow the authors to better understand what is being written and in which sequence.

This feature was inspired by Minto [Min09].

The example:

```
\cwssubject{Example of a subject}
A subject is the main subject of a paragraph
```

```
\cwssubject[pink]{A pink colored subject}
You can use other colors, such as pink.%
```

generates:

Example of a subject

A subject is the main subject of a paragraph

A pink colored subject

You can use other colors, such as pink.

8 Lists

`\listofcomment` Comments, citation demands and subjects can be list with these commands.

`\listofcomment` The lists will only appear if their commands are enable (or in the all-enabling
`\listofsubject` editing option).

They are usually put in the end of the file.

9 To dos

`\todo` The `todo` command is a much simpler version than the one available in

Xexéo:¹⁶

`todonotes`¹⁶. Its syntax is:

```
\todo[inline]{\text}
```

To do:¹⁷

A `todo` without a `inline` option is equivalent to a comment of author “To do”¹⁷. With the option, the text will appear inside an orange box, as in the example below.

The example:

```
\todo[inline]{This command can have other options,  
based on other implementations of to do in different packages.}
```

generates:

This command can have other options, based on other implementations of to do in different packages

.

`\cwdefinetodocolor`

It is possible to change the background color of the box using `.`. The idea, however, is that all to-dos should have the same color.

```
\cwdefinetodocolor{\color}.
```

The example:

```
\cwdefinetodocolor{yellow}  
\todo[inline]{This command can have other options,  
based on other implementations of to do in different packages.}
```

generates:

This command can have other options, based on other implementations of to do in different packages.

10 Warnings

This package uses another package that changes L^AT_EX’s standard behavior for summary and lists. When you use it, you must explicitly change pages with `\newpage` before `\tableofcontents` or similar commands.

11 The commands in Portuguese

This section is in Brazilian Portuguese.

A Tabela 1 Mostra o mapeamento em inglês e português.

¹⁶XEXÉO:But it will grow in power with time

¹⁷TO DO:This is how it works without the inline option

Tabela 1: Tradução dos comandos para português.

Tipo	Inglês	Português
environment	<code>cwdraft</code>	<code>rascunho</code>
macro	<code>\cwnamedef</code>	<code>\cwautor</code>
macro	<code>\cwsubject</code>	<code>\cwassunto</code>
macro	<code>\listofcomment</code>	<code>\listofcomentario</code>
macro	<code>\listofsubject</code>	<code>\listofassunto</code>
macro	<code>\listofcitationneeds</code>	<code>\listofcomentarioref</code>
macro	<code>\todo</code>	<code>\todo</code>

11.1 Opções em Português

As seguintes opções são aceitas em português, todas sem acentos ou cedilha: anonimizar, naoanonimizar, rascunhos, assuntos, comentarios, edicao, submeter, publicar, sugestoes, publicaraceitando.

12 Comparision with other packages

It is interesting to compare this package with other 3:

- `ed` has more features for commenting, and is more configurable, however it does not have colors.
- `todonotes` it does not have the identification of the commentator, which must be put by hand. It has more options too.
- `color-edits` does not support to do notes and drafts.

13 Implementation

This package was initially written in Portuguese. As it become more useful, it was translated to English. There are still some signs of this in the code.

13.1 Access to the current version

We provide some macros for the user to know the version being used.

`\coopwritingversion` Provides current version of coop-writing

```
1 \newcommand{\coopwritingversion}{\cw@version}%
```

`\printcoopwritingversion` Provides package name and version

```
2 \newcommand{\printcoopwritingversion}{coop-writing v. \coopwritingversion}%
```

13.2 Option Processing

13.2.1 Creating Options Variables

```
3 \newif\ifshowednotes\showednotesttrue%
4 \newif\ifmargins\marginstrue%
5 \newif\ifmarginnote\marginnotefalse%
6 \newif\ifednotebookmarks\ednotebookmarksfalse%
7 \newif\if@showcomentario\@showcomentariofalse%
8 \newif\if@naoanonimizar\@naoanonimizarfalse%
9 \newif\if@showdraft\@showdraftfalse%
10 \newif\if@showsubjects\@showsubjectsfalse%
11 \newif\if@showsgestao\@showsgestaofalse%
12 \newif\if@beanonymous\@beanonymousfalse%
13 \newif\if@showtodo\@showtodofalse%
14 \newif\if@modoedicao\@modoedicaofalse%
15 \newif\if@modosubmeter\@modosubmeterfalse%
16 \newif\if@modopublicar\@modopublicarfalse%
17 \newif\if@modopublicaraceitando\@modopublicaraceitandofalse%
```

13.2.2 Portuguese Options

```
18 \DeclareOption{rascunhos}{\@showdrafttrue}
19 \DeclareOption{comentarios}{\@showcomentariottrue}
20 \DeclareOption{anonimizar}{\@beanonymoustrue}
21 \DeclareOption{naoanonimizar}{\@naoanonimizartrue}
22 \DeclareOption{sugestoes}{\@showsgestaottrue}
23 \DeclareOption{assuntos}{\@showsubjectstrue}
24 \DeclareOption{edicao}{\@modoedicaottrue}
25 \DeclareOption{submeter}{\@modosubmetertrue}
26 \DeclareOption{publicar}{\@modopublicartrue}
27 \DeclareOption{publicaraceitando}{
28     \@modopublicartrue
29     \@modopublicaraceitandottrue
30 }
```

13.2.3 English Options, from ed package

```
31 \DeclareOption{show}{\showednotesttrue\message{ed.sty: showing ednotes}}
32 \DeclareOption{hide}{\showednotesfalse\message{ed.sty: hiding ednotes}}
33 \DeclareOption{draft}{\showednotesttrue\message{ed.sty: showing ednotes}}
34 \DeclareOption{final}{\showednotesfalse\message{ed.sty: hiding ednotes}}
35 \DeclareOption{nomargins}{\marginsfalse}
36 \DeclareOption{marginnote}{\marginnotetrue}
37 \DeclareOption{pdfbookmarks}{\ednotebookmarkstrue}
```

13.2.4 Original English Options

```
38 \DeclareOption{comments}{\@showcomentariottrue}
39 \DeclareOption{anonimize}{\@beanonymoustrue}
40 \DeclareOption{noanonimize}{\@naoanonimizartrue}
```

```

41 \DeclareOption{suggestions}{\@showsugestaottrue}
42 \DeclareOption{subjects}{\@showssubjectstrue}
43 \DeclareOption{drafts}{\@showdrafttrue}
44 \DeclareOption{todos}{\@showtodottrue}
45 \DeclareOption{editing}{\@modoedicaottrue}
46 \DeclareOption{submit}{\@modosubmetertrue}
47 \DeclareOption{publish}{\@modopublicartrue}
48 \DeclareOption{acceptingpublish}{
49     \@modopublicartrue
50     \@modopublicaraceitandottrue
51 }
52 \ProcessOptions\relax

```

13.2.5 Fixing the Super Options

```

53 \if@modoedicao
54 \@showssubjectstrue
55 \@showdrafttrue
56 \@showcomentariottrue
57 \@showsugestaottrue
58 \@beanonymoustrue
59 \@showtodottrue
60 \fi
61 \if@modosubmeter
62 \@showssubjectsfalse
63 \@showdraftfalse
64 \@showcomentariofalse
65 \@showsugestaofalse
66 \@beanonymoustrue
67 \@showtodofalse
68 \fi
69 \if@naoanonimizar
70 \@beanonymousfalse
71 \fi
72 \if@modopublicar
73 \@showssubjectsfalse
74 \@showsugestaofalse
75 \@showdraftfalse
76 \@showcomentariofalse
77 \@beanonymousfalse
78 \@showtodofalse
79 \fi%
80 \if@showtodo
81 \@showcomentariottrue
82 \fi

```

13.3 Required Packages

Packages that are always required

To do:¹⁸

- xcolor - used to support colors
- soulutf8 - this is a variation of soul, used for highlighting
- ulem - used to support strikethrough¹⁸
- tocloft - used to support modifications in lists and tocs
- mdframed - used to support boxes for todos and drafts
- iflang - used to check if language is loaded and define new words not in Babel

```
83 \RequirePackage{xcolor}
84 \RequirePackage{soulutf8}
85 \RequirePackage[normalem]{ulem}
86 \RequirePackage{tocloft}
87 \RequirePackage{etoolbox}
88 \RequirePackage{environ}
89 \RequirePackage{xstring}
90 \RequirePackage{csquotes}
91 \RequirePackage{mdframed}
```

13.4 Optional Packages

Package that are required only sometimes

```
92 \ifshowednotes%
93 \ifmarginnote%
94 \RequirePackage{marginnote}%
95 \fi%
96 \else%
97 \RequirePackage{verbatim}%
98 \fi%
```

Checking if babel is loaded, use iflang

```
99 \@ifpackageloaded{babel}%
100 {% \message{Babel Loaded!}%
101   \RequirePackage{iflang}%
102 }{%
103   \message{Babel not detected!}%
104 }%

105 % |hyperref| must always be the last
106 \ifednotebookmarks\RequirePackage{hyperref}\fi
```

13.5 Color related variables

```
107 \newcommand{\cor@prof}{red}%
108 \newcommand{\cor@cand}{blue}%
109 \newcommand{\cor@subject}{green}%
110 \newcommand{\cor@citar}{purple}%
```

¹⁸To do:I must complete this explanation list


```
111 \newcommand{\cor@hldraft}{yellow}%
```

13.6 I18N Almost Using Babel

We can detect if babel is enable and allow for some languages. If you want to use another language, you must set new values for the command `\cwdrafttitle`. I really thought that it was possible to do something smarter with babel, for example using `\setlocalecaption`, but no attempt worked out was I wanted.

There are some packages, as `translator` that can be useful but up to now this seems to be the easiest way of doing it.

The advantage of this way is that any user can `\renewcommand{\cwdrafttitle}{some text}`.

```
112 \def\cwdrafttitle{Standard Draft}%
113 \def\cwcommentstitle{Standard List of Comments}%
114 \def\cwsubjtitle{Standard List of Subjects}%
115 \def\cwcitationstitle{Standard List of Citation Needs}%
116 \def\cwpleasecitetext{Plese cite}
117 \def\cwpleasecitemessage{something to support this information}
118 \def\cwpleasecitemarginnote{Cite}%
119 %
120 \@ifpackageloaded{babel}%
121 {%
122     \IfLanguageName{brazilian}%
123     {%
124         \def\cwdrafttitle{draft}%
125         \def\cwcommentstitle{Lista de Comentários}%
126         \def\cwsubjtitle{Lista de Assuntos}%
127         \def\cwcitationstitle{Necessidades de Citação}%
128         \def\cwpleasecitetext{Favor citar}%
129         \def\cwpleasecitemessage{alguma coisa que suporte este texto}%
130         \def\cwpleasecitemarginnote{Citar}%
131     }{}%
132 %
133     \IfLanguageName{portuguese}%
134     {%
135         \def\cwdrafttitle{draft}%
136         \def\cwcommentstitle{Lista de Comentários}%
137         \def\cwsubjtitle{Lista de Assuntos}%
138         \def\cwcitationstitle{Necessidades de Citação}%
139         \def\cwpleasecitetext{Favor citar}%
140         \def\cwpleasecitemessage{alguma coisa que suporte este texto}%
141         \def\cwpleasecitemarginnote{Citar}%
142     }{}%
143 %
144     \IfLanguageName{english}%
145     {%
146         \def\cwdrafttitle{Draft}%
147         \def\cwcommentstitle{List of Comments}%
```

```

148      \def\cwsubjtitle{List of Subjects}%
149      \def\cwcitationstitle{List of Citation Needs}%
150      \def\cwpleasecitetext{Plese cite}
151      \def\cwpleasecitemessage{something to support this information}
152      \def\cwpleasecitemarginnote{Cite}%
153  }{}%
154 }%
155 {}%

```

13.7 ed inspired code

This code, inspired in the `ed` package, makes the basic mechanism for inserting comments as footnotes with an observation in the margin. As an addition to `ed`, it support colors.

Setting up the counter

```
156 \newcounter{cwnote}%
```

Format for the text

```
157 \newcommand\cw@noteshape{\sffamily}%
```

Defining the variable that holds the color to be printed. `soul` made it quite complex, global variable is not the best programming technique, but it works.

footnote indicador e rótulo

`\cw@foot` This macro really creates a footnote. It uses counter `cwnote` in arabic. It prints the footnote using the currently defined color (That is a global variable, setted up elsewhere. This is not good programming practice, but it turned out to be the easiest way of doing it in \LaTeX without more and more arguments.)

Syntax: `\cw@foot{<footnote-text>}{<author-name>}{<label>}`

```

158 \newcommand\cw@foot[3]%
159 {\def\@test{#3}\footnotetext[\arabic{cwnote}]}%
160 {\scshape\textcolor{\cw@currentcolor}{#2}}%
161 \if\@test\@empty\else\label{ed:#3}\textcolor{\cw@currentcolor}{[#3]}%
162 \fi\textcolor{\cw@currentcolor}{:}}%
163 \cw@noteshape\textcolor{\cw@currentcolor}{#1}}}%

```

13.8 More for the footnote

`\cw@mark` This puts the footnote mark in the text

```

164 \def\cw@mark@style#1{#1}%
165 \newcommand\cw@mark[1]{\cw@mark@style{\footnotemark[#1]}}%

```

`\cw@footnote` This macro actually makes the footnote mark and text

```
166 \newcommand{\cw@beforemarksymbol}{}%
167 \newcommand{\cwsetcommwarn}[1]{\def\cw@beforemarksymbol{#1}}%
168 \newcommand\cw@footnote[3]{%
169 \textcolor{\cw@currentcolor}{\cw@beforemarksymbol\cw@mark{\arabic{cwnote}}}%
170 %%%\cw@mark{\arabic{cwnote}}
171 \cw@foot{#1}{#2}{#3}%
172 }%
```

13.9 The margin note

```
173 \newcommand\cw@margin[1]{%
174 \ifmargins%
175 \ifmarginnote%
176 \marginnote{%
177 \textcolor{\cw@currentcolor}{#1}}%
178 \else%
179 \marginpar{\textcolor{\cw@currentcolor}{#1}}%
180 \fi%
181 \fi}%

```

`\Cw@note` Basic function to build the note

```
182 \newcommand\Cw@note[3]% text, type, label
183 {\addtocounter{cwnote}{1}%
184 \ifshowednotes%
185 \cw@footnote{#1}{#2}{#3}%
186 \ifednotebookmarks%
187 \belowpdfbookmark{#2: #1}{#2.\thecwnote}%
188 \fi
189 \fi}%

```

More functions for doing the editorial note

```
190 \newcommand\cw@note[4]% text, type, label, margin
191 {\Cw@note{#1}{#2}{#3}%
192 \ifshowednotes\cw@margin{#4:\arabic{cwnote}}%
193 \fi}%
194 \newcommand\cwnote@label{Editor}%
195 \newcommand\cwnote@margin{Ed}%
196 \newcommand\cwnotelabel[1]{\def\cwnote@label{#1}}%
197 \newcommand\cwnotemargin[1]{\def\cwnote@margin{#1}}%
198 \newcommand{\Cw@note}[2][ ]{\Cw@note{#2}\cwnote@label{#1}}%
199 %
200 \newcommand{\cwnote}[3][ ]{%
201 \def\cw@currentcolor{#3}%
202 \cw@note{#2}%
203 \cwnote@label{#1}%
204 \cwnote@margin%

```

```

205 }%
206 %%https://tex.stackexchange.com/questions/30483/how-can-i-check-in-latex-
    or-plain-tex-whether-a-command-exists-by-name
207 %% as opções comentario, assuntos e anonimizar
208 %% CORES

\corleve Make a color lighter for later use in highlightings This code is more complex than it
    shuould be because o soulutf8's package \hl behavior. Solution found in: https:
    //tex.stackexchange.com/questions/410295/soul-color-transparency

209 \newcommand{\cor@suavizacao}{40}%
210 \newcommand{\corleve}[1]{#1!\cor@suavizacao!white}

\cw@hl1 Light highlight makes a \hl that is lighter

211 \newcommand{\cw@hl1}[2] % Depedendo do soulutf8
212 {\colorlet{x@coraqui}{\corleve{#1}}}%
213 \sethlcolor{x@coraqui}%
214 \hl{#2}%
215 }%

Isolating cwnote

216 %% rótulo texto cor indicador
217 \newcommand{\cw@cwnote}[4] []{%
218 \cwnotelabel{#4}%
219 \cwnotemargin{#4}%
220 \cwnote[#1]{#2}{#3}%
221 }%

```

13.10 Anonimization

Will write anonymous or cite anonymous. The user has a way to configure the citation as he or she wants.

```

\cw@anoncitetext Default values for anonymous citation.
\cw@anonciteptext
\cw@anoncitetttext 222 \newcommand{\cw@anoncitetext}{(Anonymous, Year)}%
223 \newcommand{\cw@anonciteptext}{(Anonymous, Year)}%
224 \newcommand{\cw@anoncitetttext}{Anonymous (Year)}%

\cwdefanoncitetext These macros allow to define how anonymous citations will appear is anonymous
\cwdefanonciteptext mode is activated. For exemplo, one can change all the citation formats to [0].
\cwdefanoncitetttext
225 \newcommand{\cwdefanoncitetext}[1]{\renewcommand{\cw@anoncitetext}{#1}}%
226 \newcommand{\cwdefanonciteptext}[1]{\renewcommand{\cw@anonciteptext}{#1}}
227 \newcommand{\cwdefanoncitetttext}[1]{\renewcommand{\cw@anoncitetttext}{#1}}%

```

```

228 \if@beanonymous
229 \newcommand{\cwanon}[1]{Anonymous}%
230 \newcommand{\cwanoncite}[2][]{\cw@anoncitetext}%
231 \newcommand{\cwanoncitep}[2][]{\cw@anonciteptext}%
232 \newcommand{\cwanoncitet}[2][]{\cw@anoncitetttext}%
233 \else
234 \newcommand{\cwanon}[1]{#1}%
235 \newcommand{\cwanoncite}[2][]{\cite[#1]{#2}}%
236 \ifdef{\citep}{\newcommand{\cwanoncitep}[2][]{\citep[#1]{#2}}}{\newcommand{\cwanoncitep}[2][]{\
237 \ifdef{\citet}{\newcommand{\cwanoncitet}[2][]{\citet[#1]{#2}}}{\newcommand{\cwanoncitet}[2][]{\
238 \fi}|
239 %% retrocompatibilidade
240 \newcommand{\xanon}[2][]{\cwanon[#1]{#2}}%
241 \newcommand{\xanoncitep}[2][]{\cwanoncitep[#1]{#2}}%
242 \newcommand{\xanoncitet}[2][]{\cwanoncitet[#1]{#2}}%

```

13.11 Subjects

The idea of subjects is to have one subject for each paragraph. Currently is just a list of subjects and a highlight.

```

243 \if@showsubjects
244 \newcommand{\listsubject}{\cwsbjtitle}%
245 %% cria a lista, depende do pacote tcloft
246 \ifundefined{chapter}
247 {\newlistof[section]{subject}{aaa}{\listsubject}}
248 {\newlistof[chapter]{subject}{aaa}{\listsubject}}%
249 %%
250 \newcommand{\cwsbjct}[2][\cor@subject]{%
251 \refstepcounter{subject}%
252 \sethlcolor{#1}%
253 \hl{#2}%
254 \par%
255 \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}{#2}}%
256 }%
257 \setlength{\cftsubjectnumwidth}{2.5em}%
258 \else%
259 \newcommand{\listofsubject}{}%
260 \newcommand{\cwsbjct}[2]{}%
261 \fi%

```

13.12 Editorial Comments

The main subject of this package

```

262 \if@showcomentario
263 %% Resolve a lista de comentários
264 \newcommand{\listcomentario}{\cwcommentstitle}%

```

```

265 %% cria a lista
266 \@ifundefined{chapter}
267 {\newlistof[section]{comentario}{ccc}{\listcomentario}}
268 {\newlistof[chapter]{comentario}{ccc}{\listcomentario}}}%
269 %%
270 %% Comentador genérico - parte I
271 %% faz o cwnote e soma na lista
272 %% [rótulo], texto , cor, indicador
273 \newcommand{\cw@comentar}[4][{}]{%
274 \ifstrempy{#4}{%
275 % rótulo texto cor indicador
276 \cw@cwnote[#1]{#2}{#3}{Comentário}% faz a nota de rodapé do ed
277 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}}%
278 }%
279 {%
280 \cw@cwnote[#1]{#2}{#3}{#4}%
281 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}}%
282 }%
283 }%
284 %% comentador genérico, parte II
285 %% faz o highlight , soma o step e comenta
286 %% [texto hl] footnote cor indicator
287 \newcommand{\cw@comment}[4][{}]{%
288 \refstepcounter{comentario}% soma um ao contador
289 \cw@hll{#3}{#1}% ver subfunção de impressão com hl
290 \cw@comentar{#2}{#3}{#4}%
291 }%
292 %%
293 %%
294 \newcommand{\cw@xcomment}[4][{}]{%
295 \refstepcounter{comentario}% soma um ao contador
296 \cw@hll{#3}{#1}% ver subfunção de impressão com hl
297 \cw@comentar{\sout{#2}}{#3}{#4}%
298 }%
299 %%
300 %%
301 %% comentador genérico com rótulo
302 %% [texto hl] footnote cor indicator rótulo
303 \newcommand{\cw@commentLabeled}[5][{}]{%
304 \refstepcounter{comentario}%
305 \cw@hll{#3}{#1}%
306 \cw@comentar[#5]{#2}{#3}{#4}%
307 }%
308 %%
309 %% [texto hl] footnote cor indicator rótulo
310 \newcommand{\cw@xcommentLabeled}[5][{}]{%
311 \refstepcounter{comentario}%
312 \cw@hll{#3}{#1}%
313 \cw@comentar[#5]{\sout{#2}}{#3}{#4}%
314 }%

```

```

315 %%
316 \setlength{\cftcomentarionumwidth}{2.5em}
317 \else
318 \newcommand{\cw@comentar}[4] [] {}%
319 \newcommand{\listofcomentario}{}%
320 %% não pode perder o texto comentado
321 \newcommand{\cw@comment}[4] [] {#1}%
322 \newcommand{\cw@commentLabeled}[5] [] {#1}%
323 \fi%

```

13.13 Suggestions, Removes and Changes

```

324 %% comentário, cor, indicador, textovelho, cor velho, textonovo, cor novo
325 %% Em modo publicar coloca o textovelho
326 \if@showsgestao
327 \newcommand{\cw@gensug}[7] [Uma proposta]{%
328 \textcolor{#5}{\sout{#4}}% CORRIGINDO AQUI
329 \textcolor{#7}{#6}%
330 \if@showcomentario%
331 \ifstrepty{#1}{}%
332 {\refstepcounter{comentario}%
333 \cw@comentar{#1}{#2}{#3}% [rótulo], cor , footnote , indicador
334 }%
335 \fi%
336 }%% [rótulo], cor , footnote , indicador
337 \else%
338 \if@modopublicaraceitando
339 \newcommand{\cw@gensug}[7] [] {#6}%
340 \else%
341 \newcommand{\cw@gensug}[7] [] {#4}%
342 \fi%
343 \fi%

```

13.14 Citations Needed

One common error of students is not to cite correctly. Citation errors are so common that I decided to provide the option to have an optional list just for them. They are enable together with commentaries, users can use them or not.

```

344 \if@showcomentario%
345 \newcommand{\listcomentarioref}{\cw@citationstitle}%
346 \@ifundefined{chapter}{\newlistof[section]{comentarioref}{ccr}{\listcomentarioref}}{\newlistof
347 \else%
348 \newcommand{\listofcomentarioref}{}%
349 \fi%
350 \if@showcomentario%
351 \newcommand{\cw@commentref}[3] [] {%
352 \refstepcounter{comentarioref}%
353 \cw@hll{#3}{#1}%

```

```

354 \cw@cwnote{#2}{#3}{\cwpleasecitmarginnote}%
355 \addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}%
356 }%
357 \setlength{\cftcomentariorefnwidth}{2.5em}%
358 \else%
359 \newcommand{\cw@commentref}[3]{}%
360 \fi%
361 \if@showcomentario
362 \newcommand{\favorcitar}[1][\cwpleasecitmessage]{%
363 \cw@commentref{\cwpleasecittext\ #1}{\cor@citar}}%
364 \else%
365 \newcommand{\favorcitar}[1]{}{}%
366 \fi%

```

13.15 Draft

cwdraft This environment creates a boxed text, with title used as a first parameter. It uses package **mdframed** to create the frame. If draft is turned off as an option, it suppresses everything inside the body. Due to problems with **soul** accepting **\cwdrafttitle** we use **\colorbox** to support multiple languages if default title is used

```

367 \if@showdraft%
368 \NewEnviron{cwdraft}[1]{}%
369 \ifstrempy{#1}%
370 {\colorbox{\cor@leve{\cor@hldraft}}{\textbf{\cwdrafttitle}}}%
371 {\cw@hll{\cor@hldraft}{\textbf{#1}}}%
372 \newline%
373 \BODY%
374 }%
375 {}%
376 \surroundwithmdframed{cwdraft}%
377 \else%
378 \NewEnviron{draft}[1]{}{}%
379 \fi%

```

\cwsetdraftcolor Sets the color that highlights the draft title

```

380 %
381 \newcommand{\cwsetdraftcolor}[1]{\def\cor@hldraft{#1}}
382 %

```

13.16 Powerful command to create editors and authors

This allows for many types of comments. This was the reason I started using a front-end to **ed**, and later decided to use colors, that **ed** does not support. If I had known of **color-edits**, maybe this package was never done. I actually implemented the same functionalities without knowing about that package. One day,

looking for other editorial packages that used editorial symbols, I found `color-edits`, but it was too late, I was already hooked on L^AT_EX programming addiction. nome do autor, cor, identificador

`\cwautor`

```

383 \newcommand{\cwautor}[3]{%
384 %% cwcomment - texto a hl, cor, comentário, indicador de pessoa
385 \expandafter\newcommand\csname#1\endcsname[2] []%
386 {%
387 \cw@comment{##1}{##2}{#2}{#3}}%
388 % [texto a marcar], cor , comentário, palavra, rótulo
389 \expandafter\newcommand\csname#1r\endcsname[3] []%
390 {\cw@commentLabeled{##1}{##2}{#2}{#3}{##3}}%
391 %% cortados
392 \expandafter\newcommand\csname#1x\endcsname[2] []%
393 {%
394 %% Comentários
395 \cw@xcomment{##1}{##2}{#2}{#3}}%
396 % [texto a marcar], cor , comentário, palavra, rótulo
397 \expandafter\newcommand\csname#1rx\endcsname[3] []%
398 {\cw@xcommentLabeled{##1}{##2}{#2}{#3}{##3}}%
399 %% sugestões
400 \expandafter\newcommand\csname#1sug\endcsname[2] []%
401 {\cw@gensug{##1}{#2}{#3}{#2}{##2}{#2}}%
402 \expandafter\newcommand\csname#1rem\endcsname[2] []%
403 {\cw@gensug{##1}{#2}{#3}{##2}{#2}{#2}}%
404 \expandafter\newcommand\csname#1troca\endcsname[3] []%
405 {\cw@gensug{##1}{#2}{#3}{##2}{#2}{##3}{#2}}%
406 \expandafter\newcommand\csname#1swap\endcsname[3] []%
407 {\cw@gensug{##1}{#2}{#3}{##2}{#2}{##3}{#2}}%
408 }%

```

`\cwauthor` These are the two standard users.

`\cweditor`

```

409 \cwautor{cwauthor}{red}{Author}
410 \cwautor{cweditor}{blue}{Editor}

```

13.17 To do notes

This was developed because some of my students started a text using `todonotes`, before being aware of my package, therefore I need to have some compatibility to make de change. With time it became useful and I will try to make something better in the future.

`\todo` If option inline is not used, it is only a front-end to an editorial comment for a user called “To do”. If it is used, it tries to simulate the simplest behavior of `todonotes` package. In the future this can be enhanced, since package `mdframe`

is very powerful. If the non-inline version is used, the to do note will not appear in the List of Commentaries.¹⁹

```

411 \newcommand{\cw@todobackgroundcolor}{orange}%
412 \cwautor{\cw@todoauthor}{orange}{To do}%
413 \if@showtodo%
414 \newcommand{\todo}[2][comentar]{%
415 \IfEq{inline}{#1}%
416 {%
417 \begin{mdframed}[backgroundcolor=\cw@todobackgroundcolor]
418 #2%
419 \end{mdframed}%
420 }%
421 {%
422 \cw@todoauthor{#2}%
423 }%
424 }%
425 \else%
426 \newcommand{\todo}[2]{}%
427 \fi%
```

`\cwdefinetodocolor` Allows the definition of a background color for todo notes.

```

428 \newcommand{\cwdefinetodocolor}[1]{\renewcommand{\cw@todobackgroundcolor}{#1}}%
```

13.18 Portuguese/English, or inverse translation table

These next lines of code made easy to convert this package to English, because it was written in Portuguese, for Brazilian researchers. Some commands were rewritten in English with time, such as `rascunho`, but the Portuguese version will always be maintained, while other were translated using only his mechanism.

```

429 \let\rascunho=\cwdraft%
430 \let\cwassunto=\cwsubject%
431 \let\pleasecite=\favorcitar%
432 \let\cwnamedef=\cwautor%
433 \let\listofcomments=\listofcomentario%
434 \let\listofcitationneeds=\listofcomentarioref%
435 \let\listofassunto=\listofsubject%
```

End of Code

¹⁹XEXÉO:It would be nice to check if `todonotes` is load and just use it

References

- [Kem20] David Kempe. *The Color-edits package. Colorful edits for multiple authors of a shared document.* Version 1.1. Sept. 19, 2020. URL: <http://www.ctan.org/pkg/color-edits> (visited on 05/29/2021).
- [Koh11] Michael Kohlhase. *The Ed package. Editorial Notes for LaTeX documents.* Version 1.8. July 1, 2011. URL: <https://gl.kwarc.info/kwarc/macros/tree/master/ed> (visited on 05/29/2021).
- [Mid21] Henrik Skov Midtiby. *The todonotes package.* Apr. 26, 2021. URL: <http://www.ctan.org/pkg/todonote> (visited on 05/29/2021).
- [Min09] B. Minto. *The Pyramid Principle: Logic in Writing and Thinking.* Financial Times Series. Financial Times Prentice Hall, 2009. ISBN: 9780273710516.

Change History

v1.0

General: First version 1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	<code>\showtodot</code> true .. 44, 59	<code>\cw@anoncitetttext</code> ..
<code>\@beanonymousfalse</code> ..	<code>\@test</code> 159, 161 222, 227, 232
..... 12, 70, 77		<code>\cw@beforemarksymbol</code>
<code>\@beanonymoustrue</code> ..	<code>_</code> 363 166, 167, 169
.... 20, 39, 58, 66	A	<code>\cw@commentar</code>
<code>\@empty</code> 161	<code>\addcontentsline</code> ..	. 273, 290, 297,
<code>\@ifpackageloaded</code> ..	. 255, 277, 281, 355	306, 313, 318, 333
..... 99, 120	<code>\addtocounter</code> 183	<code>\cw@comment</code> 287, 321, 387
<code>\@ifundefined</code>	B	<code>\cw@commentLabeled</code> ..
.... 246, 266, 346	<code>\belowpdfbookmark</code> .. 187 303, 322, 390
<code>\@modoedicaofalse</code> .. 14	<code>\BODY</code> 373	<code>\cw@commentref</code>
<code>\@modoedicaotru</code> 24, 45	 351, 359, 363
<code>\@modopublicaraceitandofalse</code>	C	<code>\cw@currentcolor</code> ..
..... 17	<code>\cftcomentarionumwidth</code> 160–163,
<code>\@modopublicaraceitandotru</code> 316	169, 177, 179, 201
..... 29, 50	<code>\cftcomentariorefnwidth</code>	<code>\cw@cwnote</code>
<code>\@modopublicarf</code> 16 357	. 217, 276, 280, 354
<code>\@modopublicartrue</code> ..	<code>\cftsubjectnumwidth</code> 257	<code>\cw@foot</code> <u>158</u> , 171
.... 26, 28, 47, 49	<code>\cite</code> 235–237	<code>\cw@footnote</code> .. <u>166</u> , 185
<code>\@modosubmeterfalse</code> 15	<code>\citep</code> 236	<code>\cw@gensug</code>
<code>\@modosubmetertrue</code> ..	<code>\citet</code> 237	. 327, 339, 341,
..... 25, 46	<code>\colorbox</code> 370	401, 403, 405, 407
<code>\@naoanonimizarfalse</code> 8	<code>\colorlet</code> 212	<code>\cw@hll</code> <u>211</u> , 289, 296,
<code>\@naoanonimizartrue</code>	<code>\coopwritingversion</code>	305, 312, 353, 371
..... 21, 40 <u>1</u> , 2	<code>\cw@margin</code> ... 173, 192
<code>\@showcomentariofalse</code>	<code>\cor@cand</code> 108	<code>\cw@mark</code> .. <u>164</u> , 169, 170
..... 7, 64, 76	<code>\cor@citar</code> ... 110, 363	<code>\cw@mark@style</code> 164, 165
<code>\@showcomentariotru</code>	<code>\cor@hldraft</code>	<code>\Cw@note</code> .. <u>182</u> , 191, 198
.... 19, 38, 56, 81	. 111, 370, 371, 381	<code>\cw@note</code> 190, 202
<code>\@showdraftfalse</code> ..	<code>\cor@prof</code> 107	<code>\cw@noteshape</code> . 157, 163
..... 9, 63, 75	<code>\cor@suavizacao</code> 209, 210	<code>\cw@todoauthor</code> 422
<code>\@showdrafttrue</code> ...	<code>\cor@subject</code> .. 109, 250	<code>\cw@todobackgroundcolor</code>
..... 18, 43, 55	<code>\cor@leve</code> .. <u>209</u> , 212, 370 411, 417, 428
<code>\@showssubjectsfalse</code>	<code>\csname</code> 385,	<code>\cw@version</code> 1
..... 10, 62, 73	389, 392, 397,	<code>\cw@xcomment</code> .. 294, 395
<code>\@showssubjectstrue</code> ..	400, 402, 404, 406	<code>\cw@xcommentLabeled</code>
..... 23, 42, 54	<code>\cw@anonciteptext</code> 310, 398
<code>\@showsugestaofalse</code> <u>222</u> , 226, 231	<code>\cwanon</code> ... 229, 234, 240
..... 11, 65, 74	<code>\cw@anoncitetttext</code> ..	<code>\cwanoncite</code> ... 230, 235
<code>\@showsugestaotru</code> <u>222</u> , 225, 230	<code>\cwanoncitep</code>
..... 22, 41, 57	 231, 236, 241
<code>\@showtodofalse</code> ...		<code>\cwanoncitett</code>
..... 13, 67, 78	 232, 237, 242

<code>\cwassunto</code>	430	<code>\else</code> ..	96, 161, 178,	<code>\IfLanguageName</code> ...	
<code>\cwauthor</code>	409		233, 258, 317,	122, 133, 144
<code>\cwautor</code>	383,		337, 340, 347,	<code>\ifmarginnote</code>	5, 93, 175
	409, 410, 412, 432		358, 364, 377, 425	<code>\ifmargins</code>	4, 174
<code>\cwcitationstyle</code> .		<code>\end</code>	419	<code>\ifshowednotes</code>	
	115,	<code>\endcsname</code> ...	385,	...	3, 92, 184, 192
	127, 138, 149, 345		389, 392, 397,	<code>\ifstrempy</code>	274, 331, 369
<code>\cwcommentstyle</code>	113,		400, 402, 404, 406		
	125, 136, 147, 264	environments:		L	
<code>\cwdefanoniciteptext</code>	225	<code> cwdraft</code>	367	<code>\label</code>	161
<code>\cwdefanonicitetext</code>	225	<code>\expandafter</code> ..	385,	<code>\listcomentario</code> ...	
<code>\cwdefanonicitettext</code>	225		389, 392, 397,	264, 267, 268
<code>\cwdefinetodocolor</code>	428		400, 402, 404, 406	<code>\listcomentarioref</code> .	
<code>\cwdraft</code>	429			345, 346
<code> cwdraft (environment)</code>	367	F		<code>\listofassunto</code>	435
<code>\cwdrafttitle</code> .	112,	<code>\favorcitar</code>	362, 365, 431	<code>\listofcitationneeds</code>	
	124, 135, 146, 370	<code>\fi</code>	60, 68, 71, 79, 82,	434
<code>\cweditor</code>	409		95, 98, 106, 162,	<code>\listofcomentario</code> .	
<code>\cwnamedef</code>	432		180, 181, 188,	319, 433
<code>\Cwnote</code>	198		189, 193, 238,	<code>\listofcomentarioref</code>	
<code>\cwnote</code>	200, 220		261, 323, 335,	348, 434
<code>\cwnote@label</code>			342, 343, 349,	<code>\listofcomments</code> ...	433
	194, 196, 198, 203		360, 366, 379, 427	<code>\listofsubject</code>	259, 435
<code>\cwnote@margin</code>		<code>\footnotemark</code>	165	<code>\listsubject</code>	
	195, 197, 204	<code>\footnotetext</code>	159	244, 247, 248
<code>\cwnotelabel</code> ..	196, 218	H		M	
<code>\cwnotemargin</code> .	197, 219	<code>\hl</code>	214, 253	<code>\marginnote</code>	176
<code>\cwpleassecitemarginnote</code>		I		<code>\marginnotefalse</code> ...	5
	118,	<code>\if</code>	161	<code>\marginnotetrue</code> ...	36
	130, 141, 152, 354	<code>\if@beanonymous</code>	12, 228	<code>\marginpar</code>	179
<code>\cwpleassecitemessage</code>		<code>\if@modoedicao</code> ..	14, 53	<code>\marginsfalse</code>	35
	117,	<code>\if@modopublicar</code>	16, 72	<code>\marginstrue</code>	4
	129, 140, 151, 362	<code>\if@modopublicaraceitando</code>		N	
<code>\cwpleassecitetext</code>	17, 338	<code>\NewEnviron</code> ...	368, 378
	116,	<code>\if@modosubmeter</code>	15, 61	<code>\newif</code>	3-17
	128, 139, 150, 363	<code>\if@naoanonimizar</code>	8, 69	<code>\newline</code>	372
<code>\cwsetcommwarn</code>	167	<code>\if@showcomentario</code> .		<code>\newlistof</code> ...	247,
<code>\cwsetdraftcolor</code> ..	380	7, 262,	248, 267, 268, 346	
<code>\cwsubject</code>	250, 260, 430		330, 344, 350, 361	<code>\numberline</code>	
<code>\cwsubjtitle</code> ..	114,	<code>\if@showdraft</code> ...	9, 367	. 255, 277, 281, 355	
	126, 137, 148, 244	<code>\if@showsubjects</code>	10, 243	P	
D		<code>\if@showsgestao</code>	11, 326	<code>\par</code>	254
<code>\DeclareOption</code>		<code>\if@showtodo</code>	13, 80, 413	<code>\pleascite</code>	431
....	18-27, 31-48	<code>\ifdef</code>	236, 237	<code>\printcoopwritingversion</code>	
E		<code>\ifednotebookmarks</code>	2
<code>\ednotebookmarksfalse</code>		6, 106, 186	<code>\ProcessOptions</code> ...	52
.....	6	<code>\IfEq</code>	415		
<code>\ednotebookmarkstrue</code>	37				

<code>\protect</code>	S	<code>\textcolor</code>
. 255, 277, 281, 355	<code>\sethlcolor</code> . . . 213, 252	. 160–163, 169,
R	<code>\setlength</code> 257, 316, 357	177, 179, 328, 329
<code>\rascunho</code> 429	<code>\sffamily</code> 157	<code>\thecomentario</code> 277, 281
<code>\refstepcounter</code> . . .	<code>\showednotesfalse</code> 32, 34	<code>\thecomentarioref</code> . 355
. 251, 288, 295,	<code>\showednotetrue</code> . .	<code>\thecwnote</code> 187
304, 311, 332, 352 3, 31, 33	<code>\thesubject</code> 255
<code>\relax</code> 52	<code>\sout</code> 297, 313, 328	<code>\todo</code> 411
<code>\renewcommand</code>	<code>\surroundwithmdframed</code>	X
. 225–227, 428 376	<code>\xanon</code> 240
<code>\RequirePackage</code> . . .	T	<code>\xanoncitep</code> 241
. 83–91,	<code>\textbf</code> 370, 371	<code>\xanoncitet</code> 242
94, 97, 101, 106		

List of Comments

1.1	Xexéo: This is an exemple of using this package to make a comment with highlighted text	2
5.1	Xexéo: This is the simplest form of an editorial note.	6
5.2	Xexéo: This is the example of the minimal use of an editorial command	7
5.3	Author: Simplest footnote comment	7
5.4	Editor: Comment with highlighting	7
5.5	Author: labeled footnote comment	8
5.6	Author: labeled comment with highlighting	8
5.7	Editor: Simplest footnote comment	8
5.8	Author: Comment with highlighting	8
5.9	Author: labeled footnote comment	8
5.10	Author: labeled comment with highlighting	8
5.11	Editor: I want to insert this	9
5.12	Author: Repeated words	9
5.13	Xexéo: This comment superscript number should be preceeded by a £	9
5.14	Xexéo: ★★ Two stars are still low priority	10
9.1	Xexéo: But it will grow in power with time	12
9.2	To do: This is how it works without the inline option	12
13.1	To do: I must complete this explanation list	16
13.2	Xexéo: It would be nice to check if todonotes is load and just use it .	26

List of Citation Needs

List of Subjects

7.1	Example of a subject	11
7.2	A pink colored subject	11