

coop-writing v1.5.2

Geraldo Xexéo

Monday 18th November, 2024 - 12:09

Contents

1	Introduction	3
1.1	A bit of context	3
1.2	The Brazilian origin	3
2	How to use coop-writing	3
2.1	How to complain or make suggestions	4
2.2	Using from Overleaf	4
3	Package Options	4
3.1	Command oriented options	5
3.2	State oriented options	5
3.3	Behavior oriented options	5
3.4	General behavior	6
4	Version	6
5	Editorial comments	6
5.1	Creating authors	7
5.2	Available commands	7
5.2.1	Comments	8
5.2.2	Labeled Comments	8
5.3	Striked-throught comments	8
5.4	Text Modification - Suggestions	9
5.5	Putting more warning in text	10
5.6	A tip for using comments	10
6	Anonymization	10
7	Draft environment	11
8	Subjects	12
8.1	Reconfiguring the behavior of <code>cwmain</code>	13
9	Lists	14
10	To dos	14

11 Coloring Text	15
12 Language Support	15
13 Optional Files (input and include)	16
14 Warnings	16
15 The commands in Portuguese	16
15.1 Opções em Português	16
16 Comparision with other packages	17
17 Useful packages that work together with coop-writing	17
18 Interaction with other packages	17
19 Implementation	18
19.1 Access to the current version	18
19.2 Option Processing	18
19.2.1 Creating Options Variables used in ed	18
19.2.2 Portuguese Options	18
19.2.3 English Options, inspired on ed package	19
19.2.4 Original English Options	19
19.2.5 Fixing the Super Options	19
19.3 Required Packages	20
19.4 Optional Packages	20
19.5 CoppeTeX problems	21
19.6 Solving problems with other packages	21
19.6.1 Problems with <code>abntex2</code> and <code>memoir</code>	21
19.7 Color related variables	22
19.8 I18N Almost Using Babel	22
19.9 ed inspired code	23
19.9.1 The footnote	23
19.9.2 The margin note	25
19.10Anonymization	26
19.11Subjects	29
19.12Editorial Comments	30
19.13Suggestions, Removes and Changes	32
19.14File Control	32
19.15Citations Needed	33
19.16Draft	34
19.17Powerful command to create editors and authors	34
19.18To do notes	35
19.19Text Color	36
19.20Portuguese/English, or inverse translation table	36

1 Introduction

This package supports editorial comments and gives some extra support for writing papers, or any document that involves more than one author or editor.

Usually, a final version of a document would be printed with the `publish` option turned on, and no editorial comments would appear. In this document `the reader will see some uses`¹ of the package, since it is distributed with the `editing` option turned on. This is done to provide the examples of use.

1.1 A bit of context

I wrote `coop-writing` to support my way of writing papers in collaboration with my students, and also to comment on theses and dissertations I supervise. It received many suggestions from my students.

The starting goal was to build a front-end that would put together other packages, with the best behavior of each package, mostly `ed` and `todonotes`, but with time, and the difficulty to make different packages with commands that have the same name to coexist, it grew in scope.

It picks ideas from different packages, such as `ed`[Koh11], `color-edits`[Kem20], and `todonotes`[Mid21]. As it is my first package, \TeX and \LaTeX programming is sometimes naive. However, due to the large amount of available code, and sites as StackExchange, this is not a rule.

1.2 The Brazilian origin

Originally, `coop-writing` was written in Portuguese. The Portuguese commands are still available. Typos and others errors can appear in this text, please use GitHub issues to warn me any errors that you find.

2 How to use coop-writing

`coop-writing` is available as open source at <https://github.com/xexeo/coop-writing>, using a MIT License. The stable distribution is in the folder `dist`, while the latest, and unstable, will be in the root folder. A CTAN folder now contains the current submitted CTAN distribution.

The only file you really need, apart from this manual, is `coop-writing.sty`. This should be in your \LaTeX path, such as in the same folder that your main `.tex` file.

If you are new to \LaTeX , just put **one** of these 3 lines in the preamble part of your document, i.e., before `\begin{document}`:

```
\usepackage[editing]{coop-writing}
\usepackage[submit]{coop-writing}
```

¹XEXÉO: This is an example of using this package to make a comment with highlighted text

```
\usepackage[publish]{coop-writing}
```

After that, you can use `\cwauthor` or `\cweditor` to make commentaries, but you should look at the many options available that are described in section 5. You will probably want to define authors as described in subsection 5.1.

2.1 How to complain or make suggestions

You can make suggestions, complain about bugs, and request features using GitHub’s “Issues” feature, in <https://github.com/xexeo/coop-writing/issues>.

2.2 Using from Overleaf

The best way to use `coop-writing` inside Overleaf is to link the distributed style file through its URL. To do that, inside your project, select first “Upload”. An “Add files” window will appear, then select “From External URL” and enter <https://raw.githubusercontent.com/xexeo/coop-writing/main/dist/coop-writing.sty> as “URL to fetch the file from” and “coop-writing” as “File Name in This Project”, as in Figure 1.




Figure 1: How to link a `coop-writing.sty` file in your project folder in Overleaf to the official distribution.

3 Package Options

"Using the package allows the use of all macros and environments described in this manual. However, if the options are not turned on, there will be no effect on the generated PDF because, by default, all options are false.

There are three types of options. The first type enables the visualization of the result of specific macros or environments, such as the `cwdraft` environment. They are named *command oriented options*. You can use many of them in the same time.

The second type represents a state of the text, which can be `editing`, `submit`, or `publish`, and some minor variations. They are named *state oriented options*.

They turn on and off different commands, according to the need described by the state.

The third type control other behaviors. They are named *behavior oriented options*

If they appear together, state oriented commands have precedence over the others. However, the user should avoid mixing command and state oriented options. Also, you should **use only one of the state oriented options**.

It should be clear that the options have no impact on the availability of the macros and environments, they will be there for you to use, but they deeply affect their behavior. A macro that is very complex, such as `\cwauthor`, if one of the options `comments` or `editing` is selected, is replaced by a simple version that does almost nothing.

3.1 Command oriented options

<code>subjects</code>	• <code>subjects</code> , enables the use of <code>\subject</code> , which is proposed as a paragraph heading describing its subject;
<code>comments</code>	• <code>comments</code> , enables all editorial comments and the command <code>\pleasecite</code> ;
<code>drafts</code>	• <code>drafts</code> , enables the <code>\cwdraft</code> command;
<code>suggestions</code>	• <code>suggestions</code> , enables the comments defined in the suggestion section of this text.
<code>anonymize</code>	• <code>anonymize</code> , enables anonymization commands, and
<code>todos</code>	• <code>todos</code> , enables the to do family of commands.
<code>changecolor</code>	• <code>changecolor</code> , enable the <code>cwcolor</code> family of commands

3.2 State oriented options

<code>submit</code>	• <code>submit</code> , enables the <code>submit</code> state. <code>anonymize</code> is on, <code>subjects</code> , <code>comments</code> , <code>drafts</code> , <code>changecolor</code> and <code>suggestions</code> are off.
<code>noanonymize</code>	• <code>noanonymize</code> , disables <code>anonymize</code> even in <code>submit</code> and <code>editing</code> options.
<code>publish</code>	• <code>publish</code> , disables all command oriented options, ignore suggestions.
<code>acceptingpublish</code>	• <code>acceptingpublish</code> , disables all command oriented options, accept suggestions
<code>editing</code>	• <code>editing</code> , enables <code>subjects</code> , <code>comments</code> , <code>drafts</code> , <code>changecolor</code> and <code>suggestions</code> ; since version 1.3 it disables <code>anonymize</code> .

3.3 Behavior oriented options

Some of these options are inherited from `ed`.

- `nopdfbookmarks` will avoid adding bookmarks in the `pdf` file for all comments. The default behavior of `coop-writing` is adding them.
- `toclofttitles` toggles the option `titles` in `tocloft`, that avoid the redefinition of `\listoffigures` and `\listoftables`. This fixes the bug with the CoppeTeX package, identified as `coppe`.

3.4 General behavior

The general behavior of this package is to provide various ways of marking your text, such as with comments or 'to-do' notes, which can be completely suppressed if desired.. Mostly, this can be easily done using one the the 3 main option states: **editing**, **submit**, and **publish**.

Users should use the **editing** state most of the time. In this state, all markings will appear and the anonymization will be off.

When submitting, the **submit** state will provide a clean article, without any markings. Most of the times the article should be anonymized, but if this is not enforced by a conference or journal, it is possible to use the options **submit** and **noanonymize** together. **publish** will never anonymize.

The goal is to make the **submit** and **publish** documents states minimally invasive, to avoid any clash with publishers' styles. A clash will be considered a bug, and should be reported to the authors. Most of the time, using these options will simply create dummy commands.

If you use **comments**, there will be a lot of "Marginpar moved" warnings. This is normal behavior, caused by the margin notes. It will not happen when **submit** or **publish** is active.

4 Version

It is possible that the user wants to know the version being used. We provide two commands for it.

<code>\coopwritingversion</code>	Provides the current version
<code>\printcoopwritingversion</code>	Provides name and version
	<code>\coopwritingversion</code> was used in the title of this article. The current version is v1.5.2.

If needed, the second macro prints also the name of the package:

`\printcoopwritingversion`

will result in:

coop-writing v. v1.5.2

Please state the version when reporting bugs.

5 Editorial comments

This is the main purpose of this package.

The idea is that users not only can make editorial comments on the text they are writing, but they can also establish a dialog through those comments. In this package an editorial comment has 3 visual parts: an intervention in the text, a

Xexéo:2 margin note indicating this intervention, and a footnote explaining it². Figure 2 illustrate this behavior.




Figure 2: How comments appear in the document when `editing` option is on.

5.1 Creating authors

`\cwnamedef` This macro creates a series of commands based on a desired base command name. The command name is, usually, the name of the author, of the editor, or a function in the work being done.

This macro must be used in the preamble of the L^AT_EX document, i.e., before the `\begin{document}` declaration. It is usually done just after the `\usepackage{coop-writing}` line. Its syntax is:

```
\cwnamedef {<name>}{<color>}{<author-name>}
```

Where `<name>` will be the base command name, which generates different commands, by receiving suffixes, `<color>` is the color to be used by all comments and suggestions made by this author, and `<author-name>` is the string to be used to represent the collaborator.

As an example, I usually declare myself as:

```
\cwnamedef{xexeo}{red}{Xexéo}
```

And, among other commands, `\xexeo` will be defined in such a way that it generates a footnote written in red, with a indicative margin note in the same color. Both will be identified with “Xexéo”³.

The `<name>` and `<author-name>` are different to support short command names and characters not supported in L^AT_EX macros. Therefore, if you name is *Gutenberg* you can create a family of commenting macros based on `\gut`, but use “Gutenberg” as your identifier.

`\cwauthor` Two authors are pre-defined in the style, `cwauthor` and `cweditor`, to represent an author and an editor. They can be freely used.

5.2 Available commands

For each user created with command name `<name>`, such as `cwauthor` and `cweditor`, used as example, the following commands are available.

²XEXÉO: This is the simplest form of an editorial note.
³XEXÉO: This is the example of the minimal use of an editorial command

5.2.1 Comments

```

\<name>      \<name> [\<selection>]{\<footnote comment>}
\cauthor     \cauthor [\<selection>]{\<footnote comment>}
\ceditor     \ceditor [\<selection>]{\<footnote comment>}

```

These are the simplest commands, and will make a comment in the form of a identified footnote⁴. The optional *<selection>* parameter allows to highlight some text⁵.

5.2.2 Labeled Comments

```

\<name>r      \<name>r [\<selection>]{\<footnote comment>}{\<label>}
\cauthorrr   \cauthorrr [\<selection>]{\<footnote comment>}{\<label>}
\ceditorrr   \ceditorrr [\<selection>]{\<footnote comment>}{\<label>}

```

This command will make a comment in the form of a labeled footnote⁶. It can also be used to highlight some text⁷. The label must be unique, and usually a single word, since it is used as a L^AT_EX `\label` too. You can refer to this command using `\ref{cw:<label>}`. For example, the comment 6 would be referenced as `\ref{cw:FirstLabel}`, as in here Comment 6.

5.3 Striked-through comments

After using the editorial comments for a time, we started to delete the old ones that represented fixed problems. However, we notice that some comments should be kept, even if solved. The solution was to create the striked-trought comments. They are easy to use, just put an x after the command name.

```

\<name>x      \<name>x [\<selection>]{\<footnote comment>}
\cauthorrx   \cauthorrx [\<selection>]{\<footnote comment>}
\ceditorrx   \ceditorrx [\<selection>]{\<footnote comment>}

```

This command will make a comment in the form of a footnote⁸, however the comment is striked through. It can also be used to highlight some text⁹.

```

\<name>rx     \<name>rx [\<selection>]{\<footnote comment>}{\<label>}
\cauthorrrx  \cauthorrrx [\<selection>]{\<footnote comment>}{\<label>}
\ceditorrrx  \ceditorrrx [\<selection>]{\<footnote comment>}{\<label>}

```

This command will make a comment in the form of a labeled footnote¹⁰, however the comment is striked through. It can also be used to highlight some text¹¹.

⁴ AUTHOR:Simplest footnote comment

⁵ EDITOR:Comment with highlighting

⁶ AUTHOR[FIRSTLABEL]:labeled footnote comment

⁷ AUTHOR[OTHERLABEL]:labeled comment with highlighting

⁸ EDITOR:Simplest footnote comment

⁹ AUTHOR:Comment with highlighting

¹⁰ AUTHOR[SECOND LABEL]:labeled footnote comment

¹¹ AUTHOR[NEW LABEL]:labeled comment with highlighting

The label must be unique, since it is used as a L^AT_EX label too.

5.4 Text Modification - Suggestions

Sometimes, an author may want to insert, remove, or edit some text. If they are unsure whether everyone will agree, they can make a suggestion, which will appear in their chosen color.

<code>\<name>sug</code>	<code>\<name>sug[<i><comment></i>]{<i><suggested text></i>}</code>
<code>\cauthorsug</code>	<code>\cauthorsug[<i><comment></i>]{<i><suggested text></i>}</code>
<code>\ceditorsug</code>	<code>\ceditorsug[<i><comment></i>]{<i><suggested text></i>}</code>

This macro supports making a suggestion. It inserts text, using the color chosen by the author. It is also possible to make a comment, but in this command the command is the optional argument.

As example, in this paragraph the following text:

`\cauthorsug{inserted text}` will appears in the red, and it is possible to `\ceditorsug[I want to insert this]{use a comment}`.

generates:

inserted text¹² will appears in the red, and it is possible to use a comment¹³.

<code>\<name>rem</code>	<code>\<name>rem[<i><comment></i>]{<i><suggested removal></i>}</code>
<code>\cauthorrem</code>	<code>\cauthorrem[<i><comment></i>]{<i><suggested removal></i>}</code>
<code>\ceditorrem</code>	<code>\ceditorrem[<i><comment></i>]{<i><suggested removal></i>}</code>

This macro is used to suggest removals.

For example:

This is an example `\cauthorrem{that is quite good}`.
Again, it is also possible to comment
the `\cauthorrem[Repeated words]{the removal}` removal.

generates:

This is an example ~~that is quite good~~¹⁴. Again, it is also possible to comment
the ~~the removal~~¹⁵ removal.

<code>\<name>swap</code>	<code>\<name>swap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>
<code>\cauthorswap</code>	<code>\cauthorswap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>
<code>\ceditorswap</code>	<code>\ceditorwap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>

This will work as the union of a removal and a suggestion. Actually, both are simplified forms of this command.

¹² AUTHOR:Attention

¹³ EDITOR:I want to insert this

¹⁴ AUTHOR:Attention

¹⁵ AUTHOR:Repeated words

For example:

```
\cwauthorswap{This should work like this.}%  
{This is an example of how the command should work.}%  
The following text is not a suggestion.
```

generates:

~~This should work like this.~~This is an example of how the command should work.¹⁶ The following text is not a suggestion.

Author:16

5.5 Putting more warning in text

It is possible to define a symbol, or any other character or text, to appear before the superscript number that indicates the comment

`\cwsetcommwarn` This is done using the following command and syntax:

```
\cwsetcommwarn{\symbol}
```

Using package `marvosym`, the example:

```
\cwsetcommwarn{\Lightning}
```

Xexéo:17

will change the behavior of editorial¹⁷ comments to include the ⚡ symbol.

You can remove the symbol by simply using `\cwsetcommwarn{}`

It should be clear that `coop-writing` does not provide any font for these symbols. If users want to use a certain font, like `marvosym`, they import it with `\usepackage`.

5.6 A tip for using comments

A student asked me to give a priority to my demands. This would make me add yet another set of commands, with more arguments. labels don't work because they must be unique to allow for being used as references.

Xexéo:18

The solution, however, is simple, special characters, such as ★, `\star` can be used and are highly efficient to communicate priority¹⁸.

Using other fonts, more can be accomplished. For example, package `marvosym` offers `\HollowBox`, ☐, `\Checkedbox`, ☑, `\CrossedBox`, ☒, which can be used to indicate that something should be done, is done or will not be done.

6 Anonymization

Anonymization provide commands to replace names and references by anonymous names and references. It, by default, is enabled only in the `submit` option

There are 5 anonymization commands:

¹⁶AUTHOR:Attention

¹⁷XEXÉO:This comment superscript number should be preceeded by a ⚡

¹⁸XEXÉO:★★ Two stars are still low priority

<code>\cwanon</code>	• <code>\cwanon{⟨text⟩}</code>
<code>\cwanoncite</code>	• <code>\cwanoncite[⟨cite-compatible-oarg⟩]{⟨cite-compatible-arg⟩}</code>
<code>\cwanoncitet</code>	• <code>\cwanoncitet[⟨citet-compatible-oarg⟩]{⟨citet-compatible-arg⟩}</code>
<code>\cwanoncitep</code>	• <code>\cwanoncitep[⟨citep-compatible-oarg⟩]{⟨citep-compatible-arg⟩}</code>
<code>\cwblind</code>	• <code>\cwblind{⟨command⟩}{⟨open text⟩}{⟨blind text⟩}</code>

The alternative text used by anonymization commands can be configured with other commands:

<code>\cwdefanontext</code>	• <code>\cwdefanontext{⟨replacement-text⟩}</code>
<code>\cwdefanoncitetext</code>	• <code>\cwdefanoncitetext{⟨replacement-text⟩}</code>
<code>\cwdefanoncitetttext</code>	• <code>\cwdefanoncitetttext{⟨replacement-text⟩}</code>
<code>\cwdefanonciteptext</code>	• <code>\cwdefanonciteptext{⟨replacement-text⟩}</code>

The example:

```
My name is \cwanon{Geraldo Xexéo}, and I read \cwanoncite{ed},
\cwanoncitep[pags 1]{todonotes}, % \cwanoncitet{xcolor}.
```

generates:

My name is [Geraldo Xexéo](#), and I read [\[Koh11\]](#), [\[Mid21, pags 1\]](#), Kern [\[Ker16\]](#).

Changing values, as in:

```
\cwdefanontext{Can't say}
\cwdefanoncitetext{[0]}
\cwdefanonciteptext{[X]}
\cwdefanoncitetttext{[Anon]}
My name is \cwanon{Geraldo Xexéo}, and I read \cwanoncite{ed},
\cwanoncitep[pags 1]{todonotes}, % \cwanoncitet{xcolor}.
```

generates:

My name is [Geraldo Xexéo](#), and I read [\[Koh11\]](#), [\[Mid21, pags 1\]](#), Kern [\[Ker16\]](#).

`\cwblind` is a command that appeared in version 1.3. It works as a `\newcommand` with two different definitions, the first for when anonymization is turned off, the second for when it is turned on.

When in editing mode, text to be anonymized will be printed in blue. This color can be changed with the command `\cwsetanoncolor`.

7 Draft environment

`\cwdraft` (*env.*) The `\cwdraft` environment aims to allow writers to include text that is marked somehow as a draft¹

¹This was motivated because my students liked to hide text from me because “it was only a draft”, but I needed to have some way to measure if they were advancing. Marking text as a draft allowed them to be free of the fear of showing errors to me. I see it most as a psychological support to writing without fear of making mistakes. And, yes, you can still use footnotes and they will be correctly numbered

This environment is evolving, looking for a good way to signal the draft status, due to the different interactions with the packages it uses and user's packages. It has one optional parameter that names the draft. Its default value is "Draft". If the `draft` option is not enabled, the text inside the title and the text inside the environment will not appear. The user should remember that some options will automatically turn on the `draft` option, such as the option `editing`.

`\cssetdraftcolor` The color of the title highlight can be changed with

`\cssetdraftcolor{<color>}`

The example:

```
\begin{cwdraft}[A draft title]
This is the example of a draft.
The title must be highlighted
There must be a box around it.
\end{cwdraft}

\cwsetdraftcolor{blue}
\begin{cwdraft}
This draft has the default title.
\end{cwdraft}
```

generates:

A draft title

This is the example of a draft.

The title must be highlighted

There must be a box around it.

Draft

This draft has the default title.

8 Subjects

`\cwsubject`
`\cwmain` `\cwsubject[<color>]{<text>}`

These are alternatives supposed to help organizing a text.

`\cwsubject` provides a header or title for a paragraph.

`\cwmain` provides an emphasis (yellow highlight by default) for any text. It should be used in the main message of the paragraph

The idea here is that each paragraph should be about one and only one subject, and that reading these paragraph title will allow the authors to better understand what is being written and in which sequence.

This feature was inspired by Minto [Min09].

The example:

```
\cwsubject{Example of a subject}
A subject is the main subject of a paragraph

\cwsubject[pink]{A pink colored subject}
You can use other colors, such as pink.

\cwsetsubjectcolor{cyan}
\cwsubject{All subjects will be cyan.}
You can use other colors, such as pink.
```

generates:

Example of a subject
A subject is the main subject of a paragraph
A pink colored subject
You can use other colors, such as pink.
All subjects will be cyan.
You can use other colors, such as pink.
While the example:

```
\cwmain{This is the main idea}. This is the explanation. These are examples.

\cwmain[pink]{This is another main idea}. This is the explanation. These are examples.

\cwsetmaincolor{cyan}
\cwmain{This is the main idea}. This is the explanation. These are examples.
```

generates:

This is the main idea. This is the explanation. These are examples.
This is another main idea. This is the explanation. These are examples.
This is the main idea. This is the explanation. These are examples.

Intentionally, entries in `\cwsubject` and `\cwmain` go both for the list of subjects, since users should use one or another for each paragraph.

8.1 Reconfiguring the behavior of `cwmain`

It is possible to reconfigure partially the behavior of `\cwmain` by using the standard \LaTeX macro `\renewcommand` on the command `\cwmainemphasis`.

Its standard definition is:

```
\newcommand{\cwmainemphasis}[1]{\hl{#1}}
```

And this will highlight it with the current highlight color, which can be easily defined with `\cwsetmaincolor`.

However, suppose if you want the text to be in bold, you must redefine this command, like in:

```
\renewcommand{\cwmainemphasis}[1]{\textbf{#1}}
```

This is easy to do, but an error can always cause mayhem.

Therefore, the example:

```
\renewcommand{\cwmainemphasis}[1]{\textbf{#1}}
\cwmain{This is the main idea}. This is the explanation. These are examples.
```

generates.

This is the main idea. This is the explanation. These are examples.

9 Lists

<code>\listofcomments</code>	Comments, citation demands and subjects can be list with these commands.
<code>\listofcitationneeds</code>	The lists will only appear if their commands are enable (or in the all-enabling
<code>\listofsubjects</code>	editing option).

They are usually put in the end of the file.

10 To dos

`\todo` The `todo` command is a much simpler version than the one available in `todonotes`¹⁹. It's syntax is:

```
\todo[inline]{\textit{text}}
```

A `todo` without a `inline` option is equivalent to a comment of author "To do"²⁰. With the option, the text will appear inside an orange box, as in the example below.

The example:

```
\todo[inline]{This command can have other options,
based on other implementations of to do in different packages.}
```

generates:

This command can have other options, based on other implementations of to do in different packages

`\cwdefinetedocolor` It is possible to change the background color of the box using this macro . The idea, however, is that all to-dos should have the same color.

¹⁹XEXÉO:But it will grow in power with time

²⁰TO DO:This is how it works without the inline option

```
\cwdefinetodocolor{<color>}.
```

The example:

```
\cwdefinetodocolor{yellow}
\todo[inline]{This command can have other options,
based on other implementations of to do in different packages.}
```

generates:

This command can have other options, based on other implementations of to do in different packages.

11 Coloring Text

Sometimes we want to color text. As for version 1.5 we have the new `\cwcolor` and `\cwrestore` color commands.

`\cwcolor` Sets the current default text color to a new color, save the current default start color as color to restored with `restorecolor`.

```
\cwcolor{<color>}.
```

`\cwrestorecolor` Restore the last default text color.

```
Text is in the default text color.
\cwcolor{red}
This text in red
\cwrestorecolor
This text back to default color
```

Text is in the default text color. This text in red This text back to default color

12 Language Support

This style supports the following `babel` defined languages:

- brazil,
- brazilian,
- portuguese, and
- english.

<code>\cwcommentstitle</code>	To use other language, or to use other texts instead of the standard ones, you
<code>\cwdrafttitle</code>	should define these macros, as in:
<code>\cwsubjtitle</code>	<code>\def\cwdrafttitle{Draft}</code>
<code>\cwcitationtitle</code>	<code>\def\cwcommentstitle{List of Comments}</code>
<code>\cwpleasecitetext</code>	<code>\def\cwsubjtitle{List of Subjects}</code>
<code>\cwpleasecitemessage</code>	
<code>\cwpleasecitemarginnote</code>	

```

\def\cwcitationstitle{List of Citation Needs}
\def\cwpleasecitetext{Plese cite}
\def\cwpleasecitemessage{something to support this information}
\def\cwpleasecitemarginnote{Cite}

```

13 Optional Files (input and include)

Since version 1.4, it is possible to insert optional files accordingly to the current mode

<code>\cwinput</code> <code>\cwinclude</code> <code>\cwinputediting</code> <code>\cwincludeediting</code> <code>\cwinputsubmit</code> <code>\cwincludesubmit</code> <code>\cwinputpublish</code> <code>\cwincludepublish</code>	<p>This first to commands allow to select which file will be displayed in each mode.</p> <pre> \cwinput{\file-editing-mode}\{file-submit-mode}\{file-publish-mode} \cwinclude{\file-editing-mode}\{file-submit-mode}\{file-publish-mode} </pre> <p>The next six commands work only in their specific mode.</p> <pre> \cwinputediting{\file-if-editing-mode} \cwincludeediting{\file-if-editing-mode} \cwinputsubmit{\file-if-submit-mode} \cwincludesubmit{\file-if-submit-mode} \cwinputpublish{\file-if-publish-mode} \cwincludepublish{\file-if-publish-mode} </pre>
--	---

14 Warnings

This package uses another package that changes L^AT_EX's standard behavior for summary and lists. When you use it, you must explicitly change pages with `\newpage` before `\tableofcontents` or similar commands.

15 The commands in Portuguese

This section is in Brazilian Portuguese.

A Tabela 1 Mostra o mapeamento em inglês e português.

15.1 Opções em Português

As seguintes opções são aceitas em português, todas sem acentos ou cedilha: anonimizar, naoanonimizar, rascunhos, assuntos, comentarios, edicao, submeter, publicar, sugestoes, publicaraceitando.

Tabela 1: Tradução dos comandos para português.

Tipo	Inglês	Português
environment	<code>cwdraft</code>	<code>rascunho</code>
macro	<code>\cwnamedef</code>	<code>\cwautor</code>
macro	<code>\cwssubject</code>	<code>\cwassunto</code>
macro	<code>\listofcomments</code>	<code>\listofcomentario</code>
macro	<code>\listofsubjects</code>	<code>\listofassunto</code>
macro	<code>\listofcitationneeds</code>	<code>\listofcomentarioref</code>
macro	<code>\todo</code>	<code>\todo</code>

16 Comparision with other packages

It is interesting to compare this package with other 3:

- `ed` has more features for commenting, and is more configurable, however it does not have colors.
- `todonotes` it does not have the identification of the commentator, which must be put by hand. It has more options too.
- `color-edits` does not support to do notes and drafts.

17 Useful packages that work together with coop-writing

`lineno` is useful in editing mode, and works together with `coop-writing`, as our tests show.

18 Interaction with other packages

This packages uses other packages, and this can cause interaction with them and even other packages. \LaTeX is a harsh mistress.

`tocloft` seems to be the main agressor and it is a candidate to be removed, since its function in the code is mostly secondary, generate lists of the comments, etc.

`tocloft` interacts with `memoir`. At this point, I blame `memoir`, since it **emulates** `tocloft`, but change syntax and behavior. This is a crazy idea for me, and show the need for namespaces in \LaTeX .

`tocloft` also interacts with `coppe`, the class for the CoppeTeX package, which I am one of the maintainers, both redefine `LoF` and `LoT`. More IFs, that detect `coppe` and turn on `titles` option in `tocloft`, and a new option `toclofttitles` to solve the general problem of `tocloft` changing `LoF` and `LoT` definitions.

19 Implementation

This package was initially written in Portuguese. As it become more useful, it was translated to English. There are still some signs of this in the code.

19.1 Access to the current version

We provide some macros for the user to know the version being used.

`\coopwritingversion` Provides current version of coop-writing

```
1 \newcommand{\coopwritingversion}{\cw@version}%
```

`\printcoopwritingversion` Provides package name and version

```
2 \newcommand{\printcoopwritingversion}{coop-writing v. \coopwritingversion}%
```

19.2 Option Processing

19.2.1 Creating Options Variables used in ed

Some come from ed code and are being cleaned

```
3 \newif\ifshowednotes\showednotesttrue%
4 \newif\ifmargins\marginstrue%
5 \newif\ifednotebookmarks\ednotebookmarkstrue%
6 % \subsubsection{Creating Original Options Variables}
7 \newif\if@showcomentario\@showcomentariofalse%
8 % as próximas duas variáveis controlam o \@beanonymous, por isso tem que ser duas
9 % porque só são mexidas se chamadas, não pode chamar uma porque vai mudar sempre
10 % a \@beanonymous
11 \newif\if@anonimizar\@anonimizarfalse% o default é não anonimizar
12 \newif\if@naoanonimizar\@naoanonimizarfalse% o default dessa variavel é anonimizar
13 \newif\if@beanonymous\@beanonymousfalse%
14 \newif\if@showdraft\@showdraftfalse%
15 \newif\if@showsubjects\@showsubjectsfalse%
16 \newif\if@showsgestao\@showsgestaofalse%
17 \newif\if@showtodo\@showtodofalse%
18 \newif\if@modoedicao\@modoedicaofalse%
19 \newif\if@modosubmeter\@modosubmeterfalse%
20 \newif\if@modopublicar\@modopublicarfalse%
21 \newif\if@modopublicaraceitando\@modopublicaraceitandofalse%
22 \newif\if@cwtoclofttitles\@cwtoclofttitlesfalse
23 \newif\if@changecolor\@changecolorfalse
```

19.2.2 Portuguese Options

```
24 \DeclareOption{rascunhos}{\@showdrafttrue}
25 \DeclareOption{comentarios}{\@showcomentariottrue}
26 \DeclareOption{anonimizar}{\@anonimizartrue} % isso vai se perder nos modos
27 \DeclareOption{naoanonimizar}{\@naoanonimizartrue}
```

```

28 \DeclareOption{sugestoes}{\@showsugestaottrue}
29 \DeclareOption{assuntos}{\@showsobjecttrue}
30 \DeclareOption{edicao}{\@modoedicaottrue}
31 \DeclareOption{submeter}{\@modosubmetertrue}
32 \DeclareOption{publicar}{\@modopublicartrue}
33 \DeclareOption{publicaraceitando}{\@modopublicartrue
34     \@modopublicartrue
35     \@modopublicaraceitandottrue}
36 }

```

19.2.3 English Options, inspired on ed package

```

37 \DeclareOption{nopdfbookmarks}{\ednotebookmarksfalse}

```

19.2.4 Original English Options

```

38 \DeclareOption{comments}{\@showcomentariottrue}
39 \DeclareOption{anonymize}{\@anonimizartrue}
40 \DeclareOption{noanonymize}{\@naoanonimizartrue}
41 \DeclareOption{suggestions}{\@showsugestaottrue}
42 \DeclareOption{subjects}{\@showsobjecttrue}
43 \DeclareOption{drafts}{\@showdrafttrue}
44 \DeclareOption{todos}{\@showtodottrue}
45 \DeclareOption{change color}{\@change colortrue}
46 \DeclareOption{editing}{\@modoedicaottrue}
47 \DeclareOption{submit}{\@modosubmetertrue}
48 \DeclareOption{publish}{\@modopublicartrue}
49 \DeclareOption{accepting publish}{\@modopublicartrue
50     \@modopublicartrue
51     \@modopublicaraceitandottrue}
52 }

```

New option to titles in tocloft

```

53 \DeclareOption{tocloft titles}{\@cwtoclofttitletrue}
54 \ProcessOptions\relax

```

19.2.5 Fixing the Super Options

```

55 \if@modoedicao
56 \@showsobjecttrue
57 \@showdrafttrue
58 \@showcomentariottrue
59 \@showsugestaottrue
60 \@beanonymousfalse
61 \@showtodottrue
62 \@change colortrue
63 \fi
64 \if@modosubmeter
65 \@showsobjectfalse
66 \@showdraftfalse
67 \@showcomentariofalse
68 \@showsugestaofalse
69 \@beanonymoustrue
70 \@showtodofalse
71 \@change colorfalse

```

```

72 \fi
73 \if@modopublicar
74 \@showssubjectsfalse
75 \@showsugestaofalse
76 \@showdraftfalse
77 \@showcomentariofalse
78 \@beanonymousfalse
79 \@showtodofalse
80 \@changecolorfalse
81 \fi%
82 % is explicitilly set, changes beanonymous
83 \if@naoanonimizar
84 \@beanonymousfalse
85 \fi
86 % is explicitilly set, changes beanonymous
87 \if@anonimizar
88 \@beanonymoustrue
89 \fi
90 \if@showtodo
91 \@showcomentariottrue
92 \fi

```

19.3 Required Packages

Packages that are always required

- xcolor - used to support colors
- soul - substituted its now obsolete variation in 1.4.4, used for highlighting.
- ulem - used to support strikethrought²¹
- tocloft - used to support modifications in lists and tocs
- mdframed - used to support boxes for todos and drafts
- iflang - used to check if language is loaded and define new words not in Babel

```

93 \RequirePackage{xcolor}
94 \RequirePackage{soul}
95 \RequirePackage[normalem]{ulem}
96 \RequirePackage{etoolbox} % \ifdef comes from here
97 \RequirePackage{environ}
98 \RequirePackage{xstring}
99 \RequirePackage{csquotes}
100 \RequirePackage{mdframed}

```

19.4 Optional Packages

Package that are required only sometimes

```

101 \ifshowednotes%
102 \else%
103 \RequirePackage{verbatim}%
104 \fi%

```

²¹To do: I must complete this explanation list

19.5 CoppeTeX problems

tocloft and CoppeTeX have different assumptions whether LoF, LoT and etc... appears in ToC. In default Book, they do not appear

```
105 \@ifclassloaded{coppe}%  
106 {%  
107 \RequirePackage[titles]{tocloft}%  
108 }%  
109 {%  
110 \if@cwtoctlofttitles%  
111 \RequirePackage[titles]{tocloft}%  
112 \else%  
113 \RequirePackage{tocloft}%  
114 \fi%  
115 }%
```

Checking if babel is loaded, use iflang

```
116 \@ifpackageloaded{babel}%  
117 {% \message{Babel Loaded!}%  
118 \RequirePackage{iflang}%  
119 }{%  
120 \message{Babel not detected!}%  
121 }%
```

hyperref must always be the last

```
122 \ifednotebookmarks\RequirePackage{hyperref}\fi
```

19.6 Solving problems with other packages

19.6.1 Problems with abntex2 and memoir

abntex2 causes error in \newlistof, you can't refer to chapter, section or other counter as optional argument

Cite:22

This error is actually memoir fault²², since it emulates tocloft (and other packages). I can't imagine why...

Therefore, we will avoid using the command with option when the class is present

```
123 \@ifclassloaded{memoir}%  
124 {% TRUE  
125 \newif\if@cwmemoirdefense\@cwmemoirdefensetrue%  
126 }%  
127 {% FALSE  
128 \newif\if@cwmemoirdefense\@cwmemoirdefensefalse%  
129 }%  
130 %
```

²²CITE:Please cite memoir package

19.7 Color related variables

```
131 \newcommand{\cor@prof}{red}%
132 \newcommand{\cor@cand}{blue}%
133 \newcommand{\cor@subject}{green}%
134 \newcommand{\cor@main}{yellow}%
135 \newcommand{\cor@citar}{purple}%
136 \newcommand{\cor@hldraft}{yellow}%
137 \newcommand{\cw@cftnumwidth}{20pt}
```

19.8 I18N Almost Using Babel

We can detect if babel is enable and allow for some languages. If you want to use another language, you must set new values for the command `\cwdrafttitle`. I really thought that it was possible to do something smarter with babel, for example using `\setlocalecaption`, but no attempt worked out as I wanted.

There are some packages, as `translator` that can be useful but up to now this seems to be the easiest way of doing it.

The advantage of this way is that any user can `\renewcommand{\cwdrafttitle}{some text}`.

```
138 \def\cwdrafttitle{Standard Draft}%
139 \def\cwcommentstitle{Standard List of Comments}%
140 \def\cwsubjtitle{Standard List of Subjects}%
141 \def\cwcitationstitle{Standard List of Citation Needs}%
142 \def\cwpleasecitetext{Plese cite}%
143 \def\cwpleasecitemessage{something to support this information}%
144 \def\cwpleasecitemarginnote{Cite}%
145 \def\cw@attentiontext{Attention}%
146 %
147 \@ifpackageloaded{babel}%
148 {%
149     \IfLanguageName{brazil}%
150     {%
151         \def\cwdrafttitle{Rascunho}%
152         \def\cwcommentstitle{Lista de Comentários}%
153         \def\cwsubjtitle{Lista de Assuntos}%
154         \def\cwcitationstitle{Necessidades de Citação}%
155         \def\cwpleasecitetext{Favor citar}%
156         \def\cwpleasecitemessage{alguma coisa que suporte este texto}%
157         \def\cwpleasecitemarginnote{Citar}%
158         \def\cw@attentiontext{Atenção}%
159     }{%
160         \IfLanguageName{brazilian}%
161         {%
162             \def\cwdrafttitle{Rascunho}%
163             \def\cwcommentstitle{Lista de Comentários}%
164             \def\cwsubjtitle{Lista de Assuntos}%
165             \def\cwcitationstitle{Necessidades de Citação}%
166             \def\cwpleasecitetext{Favor citar}%
167             \def\cwpleasecitemessage{alguma coisa que suporte este texto}%
168             \def\cwpleasecitemarginnote{Citar}%
169             \def\cw@attentiontext{Atenção}%
170         }{%
171             \def\cwdrafttitle{Standard Draft}%
172             \def\cwcommentstitle{Standard List of Comments}%
173             \def\cwsubjtitle{Standard List of Subjects}%
174             \def\cwcitationstitle{Standard List of Citation Needs}%
175             \def\cwpleasecitetext{Plese cite}%
176             \def\cwpleasecitemessage{something to support this information}%
177             \def\cwpleasecitemarginnote{Cite}%
178             \def\cw@attentiontext{Attention}%
179         }%
180     }%
181 }
```

```

171 %
172 \IfLanguageName{portuguese}%
173 {%
174     \def\cwdrafttitle{Rascunho}%
175     \def\cwcommentstitle{Lista de Comentários}%
176     \def\cwsubjtitle{Lista de Assuntos}%
177     \def\cwcitationstitle{Necessidades de Citação}%
178     \def\cwpleasecitetext{Favor citar}%
179     \def\cwpleasecitemessage{alguma coisa que suporte este texto}%
180     \def\cwpleasecitemarginnote{Citar}%
181     \def\cw@attentiontext{Atenção}%
182 }{}%
183 %
184 \IfLanguageName{english}%
185 {%
186     \def\cwdrafttitle{Draft}%
187     \def\cwcommentstitle{List of Comments}%
188     \def\cwsubjtitle{List of Subjects}%
189     \def\cwcitationstitle{List of Citation Needs}%
190     \def\cwpleasecitetext{Plese cite}%
191     \def\cwpleasecitemessage{something to support this information}%
192     \def\cwpleasecitemarginnote{Cite}%
193     \def\cw@attentiontext{Attention}%
194 }{}%
195 }%
196 {}%

```

19.9 ed inspired code

This code, inspired in the `ed` package²³, makes the basic mechanism for inserting comments as footnotes with an observation in the margin. As an addition to `ed`, it support colors and some text before the superscript number in the text

`cwnotecounter` Setting up the counter that gives the number of the footnote

```
197 \newcounter{cwnotecounter}%
```

19.9.1 The footnote

Format for the text

```
198 \newcommand\cw@noteshape{\sffamily}%
```

Defining the variable that holds the color to be printed. `soul` made it quite complex, global variable is not the best programming technique, but it works.

```
199 \def\cw@currentcolor{black}%
```

footnote indicador e rótulo

`\cw@foot` This macro write the text in the footnote using with standard L^AT_EX `\footnotetext`

²³CITE:Plese cite ed package

It uses counter `cwnotecounter` in arabic. It prints the footnote using the currently defined color (That is a global variable, setted up elsewehre. This is not good programming practice, but it turned out to be the easiest way of doing it in L^AT_EX without more and more arguments.)

Syntax: `\cw@foot{<footnote-text>}{<author-name>}{<label>}`

If this is a labeled note, it will create a L^AT_EX label on the format

`cw:<label>`

That can be used in a `\ref` command.

```
200 \newcommand\cw@foot[3]%
201 {%
202 \def\@test{#3}% @test just checks if argument #3 exists
203 \footnotetext[\arabic{cwnotecounter}]{%
204 {%
205 {\scshape{\textcolor{\cw@currentcolor}{#2}}}%
206 \if\@test%
207 \@empty%
208 \else%
209 \label{cw:#3}%
210 \textcolor{\cw@currentcolor}{[#3]}% if \meta{label} is not empty
211 \fi%
212 \textcolor{\cw@currentcolor}{:}}}%
213 \cw@noteshape\textcolor{\cw@currentcolor}{#1}}%
214 }%
```

`\cw@mark` This macro generates the footnote mark with standard L^AT_EX `\footnotemark`

```
215 \def\cw@mark@style#1{#1}%
216 \newcommand\cw@mark[1]{\cw@mark@style{\footnotemark[#1]}}%
```

`\cw@beforemarksymbol` These macros control the symbol (or any text) that can appear before the footnote mark
`\cwsetcommwarn` notemark

`\cwsetcommwarn{<symbol>}`

`<symbol>` can be of any length, but we suggest only one character. It can be empty, what is the default option, and will print nothing at that point.

```
217 \newcommand{\cw@beforemarksymbol}{}%
218 \newcommand{\cwsetcommwarn}[1]{\def\cw@beforemarksymbol{#1}}%
```

`\cw@footnote` This macro actually makes the footnote symbol, mark and text

Syntax is:

`\cw@footnote{<text>}{<name>}{<label>}`

`<label>` can be empty, but must be present

It is in this macro that symbol, number and footnote mark end up in the document.

This command also changes the color of footnote mark WARNING: it does that by redefining `\@makefnmark`, however this interferes with normal L^AT_EX operation. Therefore we save and restore the original value.

When we change the `\@makefnmark` to a slightly different version that includes color, that is controlled by a “global” is a variable of coop-writing, even if it is not global in the `\gdef` sense.

It is possible that this cause, in a style that changes the footnote, some difference between coop-writing footnotes and normal (style) footnotes. This is not bad necessarily, it can even be good.

```
219 \newcommand\cw@footnote[3]{%
220 \let\@temp@makefnmark\@makefnmark%
221 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\color{\cw@currentcolor}\@thefnmark}}}%
222 \textcolor{\cw@currentcolor}{\cw@beforemarksymbol\cw@mark{\arabic{cwnotecounter}}}%
223 \cw@foot{#1}{#2}{#3}%
224 \let\@makefnmark\@temp@makefnmark%
225 }%
```

19.9.2 The margin note

This macro builds the margin note.

```
226 \newcommand\cw@margin[1]{%
227 \ifmargins%
228 \marginpar{\textcolor{\cw@currentcolor}{#1}}%
229 \fi%
230 }%
```

`\Cw@note` Basic function to build the comment

`\Cw@note{<text>}{<name>}{<label>}`

If not label, it must be empty

```
231 \newcommand\Cw@note[3]% text, name, label
232 {%
233 \addtocounter{cwnotecounter}{1}%
234 \ifshowednotes%
235 \cw@footnote{#1}{#2}{#3}%
236 \ifednotebookmarks%
237 \belowpdfbookmark{#2: #1}{cwnotepdfbm.\thecwnotecounter}%
238 \fi%
239 \fi}%

```

More functions for doing the editorial note

```
240 \newcommand\cw@note[4]% text, type, label, margin
241 {\Cw@note{#1}{#2}{#3}%
242 \ifshowednotes%
243 \cw@margin{#4:\arabic{cwnotecounter}}}%
244 \fi}%
245 \newcommand\cwnote@label{Editor}%
246 \newcommand\cwnote@margin{Ed}%
247 \newcommand\cwnotelabel[1]{\def\cwnote@label{#1}}%
248 \newcommand\cwnotemargin[1]{\def\cwnote@margin{#1}}%
249 \newcommand{\Cw@note}[2][ ]{\Cw@note{#2}\cwnote@label{#1}}%
```

`\cwnote` It writes the footnote, the symbol and the margin.

To avoid problems we keep `\cw@currentcolor`

WARNING: will this use a lot of memory? Every creation will keep the old value alive?

```
250 \newcommand{\cwnote}[3] [] {%
251 \let\@temp@color\cw@currentcolor%
252 \def\cw@currentcolor{#3}%
253 \cw@note{#2}%
254 \cwnote@label{#1}%
255 \cwnote@margin%
256 \let\cw@currentcolor\@temp@color%
257 }%
```

<https://tex.stackexchange.com/questions/30483/how-can-i-check-in-latex-or-plain-tex-whether-a-command-exists-by-name> as opções comentario, assuntos e anonimizar CORES

`\corleve` Make a color lighter for later use in highlightings This code is more complex than it should be because of `soulutf8`'s package `\hl` behavior. Solution found in: <https://tex.stackexchange.com/questions/410295/soul-color-transparency>

```
258 \newcommand{\cor@suavizacao}{40}%
259 \newcommand{\corleve}[1]{#1!\cor@suavizacao!white}
```

`\cwsetanoncolor` Sets the color used to indicate what will be anonymized

```
260 \newcommand{\cwsetanoncolor}[1]{\def\cw@editAnonColor{#1}}
261 \cwsetanoncolor{blue}
```

`\cw@hl1` Light highlight makes a `\hl` that is lighter

```
262 \newcommand{\cw@hl1}[2] % Dependendo do soulutf8
263 {\colorlet{x@coraqui}{\corleve{#1}}%
264 \sethlcolor{x@coraqui}%
265 \hl{#2}%
266 }%
```

Isolating `cwnote`

```
267 %% rótulo texto cor indicador
268 \newcommand{\cw@cwnote}[4] [] {%
269 \cwnotelabel{#4}%
270 \cwnotemargin{#4}%
271 \cwnote[#1]{#2}{#3}%
272 }%
```

19.10 Anonymization

Will write anonymous or cite anonymous. The user has a way to configure the citation as he or she wants.

```

\cw@anontext Default values for anonymous citation.
\cw@anoncitetext
\cw@anonciteptext 273 %
\cw@anoncitetttext 274 \newcommand{\cw@anontext}{Anonymous}
275 \newcommand{\cw@anoncitetext}{(Anonymous, Year)}%
276 \newcommand{\cw@anonciteptext}{(Anonymous, Year)}%
277 \newcommand{\cw@anoncitetttext}{Anonymous (Year)}%

\cwdefanontext These macros allow to define how anonymous citations will appear is anonymous
\cwdefanoncitetext mode is activated. For exemplo, one can change all the citation formats to [0].
\cwdefanonciteptext
\cwdefanoncitetttext 278 \newcommand{\cwdefanontext}[1]{\renewcommand{\cw@anontext}{#1}}%
279 \newcommand{\cwdefanoncitetext}[1]{\renewcommand{\cw@anoncitetext}{#1}}%
280 \newcommand{\cwdefanonciteptext}[1]{\renewcommand{\cw@anonciteptext}{#1}}%
281 \newcommand{\cwdefanoncitetttext}[1]{\renewcommand{\cw@anoncitetttext}{#1}}%

282 \if@beanonymous
283 \newcommand{\cwanon}[1]{\cw@anontext}%
284 \newcommand{\cwanoncite}[2][]{\cw@anoncitetext}%
285 \newcommand{\cwanoncitep}[2][]{\cw@anonciteptext}%
286 \newcommand{\cwanoncitet}[2][]{\cw@anoncitetttext}%
287 \else% be anonymous
288 \if@modoedicao%
289 \newcommand{\cwanon}[1]{\textcolor{\cw@editAnonColor}{#1}}%
290 \newcommand{\cwanoncite}[2][]{%
291 {%
292 \ifstrempy{#1}%
293 {\textcolor{\cw@editAnonColor}{\cite{#2}}}%
294 {\textcolor{\cw@editAnonColor}{\cite[#1]{#2}}}%
295 }%
296 \else% modo edicao
297 \newcommand{\cwanon}[1]{#1}%
298 \newcommand{\cwanoncite}[2][]{%
299 {%
300 \ifstrempy{#1}%
301 {\cite{#2}}%
302 {\cite[#1]{#2}}%
303 }%
304 \fi% modoedicao
305 %
306 %%%%%%%%%%%
307 % where ifdef comes from?
308 \ifdef{\citep}%
309 {% tem citep
310 \newcommand{\cwanoncitep}[2][]{%
311 {%
312 \if@modoedicao%
313 \ifstrempy{#1}%
314 {\textcolor{\cw@editAnonColor}{\citep{#2}}}%
315 {\textcolor{\cw@editAnonColor}{\citep[#1]{#2}}}%
316 \else% modo edicao
317 \ifstrempy{#1}%
318 {\citep{#2}}%
319 {\citep[#1]{#2}}%

```

```

320 \fi% mode edicao
321 }%
322 }%
323 {% não tem citep
324 \newcommand{\cwanoncitep}[2] []
325 {\ifstrempy{#1}%
326 {\cwanoncite{#2}}}%
327 {\cwanoncite[#1]{#2}}}%
328 }%
329 }%
330 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
331 \ifdef{\citet}%
332 {% tem citet
333 \newcommand{\cwanoncitet}[2] []%
334 {%
335 \if@modoedicao%
336 \ifstrempy{#1}%
337 {\textcolor{\cw@editAnonColor}{\citet{#2}}}%
338 {\textcolor{\cw@editAnonColor}{\citet[#1]{#2}}}%
339 \else% modo edicao
340 \ifstrempy{#1}%
341 {\citet{#2}}}%
342 {\citet[#1]{#2}}}%
343 \fi% modo edicao
344 }%
345 }%
346 {% não tem citet
347 \newcommand{\cwanoncitet}[2] []
348 {%
349 \ifstrempy{#1}%
350 {\cwanoncite{#2}}}%
351 {\cwanoncite[#1]{#2}}}%
352 }%
353 }%
354 \fi% be anonymous
355 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

```

`\cwblind` Defines a new macro for blind review commands `\cwblind{command}{open text}{blind text}`

```

356 \if@beanonymous%
357 \newcommand{\cwblind}[3]{%
358 \newcommand{#1}{#3}%
359 }%
360 \else%
361 \if@modoedicao%
362 \newcommand{\cwblind}[3]{%
363 \newcommand{#1}{\textcolor{\cw@editAnonColor}{#2}}}% AQUI
364 }%
365 \else
366 \newcommand{\cwblind}[3]{%
367 \newcommand{#1}{#2}%
368 }%
369 \fi%

```

370 \fi%

19.11 Subjects

The idea of subjects is to have one subject for each paragraph.

There are two commands to support it: `\cwsubject[⟨highlight-color⟩]{⟨subject⟩}` and `\cwmain[⟨highlight-color⟩]{⟨line-inside-a-paragraph⟩}`

Both are listed with `\listofsubject`.

`\cwsetsubjectcolor` Sets color for all `cwsubject` and `cwmaincolor`

`\cwsetmaincolor`

371 \newcommand{\cwsetsubjectcolor}[1]{\def\cor@subject{#1}}%

372 \newcommand{\cwsetmaincolor}[1]{\def\cor@main{#1}}%

`\cwsubject` Currently is just a list of subjects and and a highlight

This is an use for cwsubject

it is a header for a paragraph.

373 \if@showsubjects

374 \newcommand{\listsubject}{\cwsubjttitle}%

375 %% cria a lista, depende do pacote tclift

Memoir class needs 2 commands to really define a list It also changes the `\newlistof` arguments' meaning

376 \if@cwmemoirdefense%

377 \@ifundefined{chapter}%

378 {\newlistentry[section]{subject}{aaa}{0}}

379 {\newlistentry[chapter]{subject}{aaa}{0}}

380 \newlistof{listofsubject}{aaa}{\listsubject}

381 \else%

382 \@ifundefined{chapter}%

383 {\newlistof[section]{subject}{aaa}{\listsubject}}%

384 {\newlistof[chapter]{subject}{aaa}{\listsubject}}%

385 \fi%

386 %

387 %

388 \newcommand{\cwsubject}[2][\cor@subject]{%

389 \refstepcounter{subject}%

390 \sethlcolor{#1}%

391 \hl{#2}}%

392 \par%

393 % I really can't say why we need to

394 % avoid curly braces in the next command

395 \if@cwmemoirdefense%

396 \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}#2}}%

397 \else%

398 \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}{#2}}%

399 \fi%

400 }%

`\cwmain` This is another way to control the main idea for a paragraph, but using an sentence inside it.

This is a use for cwmain. In the first sentence of a paragraph.

Trying to configure it:

This is a use for cwmain. In the first sentence of a paragraph.

```

401 \newcommand{\cwmainemphasis}[1]{\hl{#1}}
402 %
403 \newcommand{\cwmain}[2][\cor@main]{%
404   \refstepcounter{subject}%
405   \sethlcolor{#1}%
406   \cwmainemphasis{#2}%
407   \if@cwmemoirdefense%
408     \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}#2}%
409   \else%
410     \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}{#2}}%
411   \fi%
412 }%
413 %
414 \if@cwmemoirdefense%
415 \else%
416 \setlength{\cftsubjectnumwidth}{\cw@cftnumwidth}%
417 \fi%
418 \else%
419 \newcommand{\listofsubject}{}%
420 \newcommand{\cwsubject}[2][{}]{%
421 \newcommand{\cwmain}[2][{}]{#2}
422 \fi%
```

19.12 Editorial Comments

The main subject of this package

```

423 \if@showcomentario
424 %% Resolve a lista de comentários
425 \newcommand{\listcomentario}{\cwcommentstitle}%
426 %% cria a lista
427 \if@cwmemoirdefense%
428 \@ifundefined{chapter}%
429 {\newlistentry[section]{comentario}{ccc}{0}}
430 {\newlistentry[chapter]{comentario}{ccc}{0}}
431 \newlistof{listofcomentario}{ccc}{\listcomentario}%
432 \else%
433 \@ifundefined{chapter}
434 {\newlistof[section]{comentario}{ccc}{\listcomentario}}
435 {\newlistof[chapter]{comentario}{ccc}{\listcomentario}}%
436 \fi%
437 %%
438 %% Comentarador genérico - parte I
439 %% faz o cwnote e soma na lista
440 %% [rótulo], texto , cor, indicador
441 \newcommand{\cw@comentar}[4][{}]{%
```

```

442 \ifstrempy{#4}{%
443 % rótulo texto cor indicador
444 \cw@cwnote[#1]{#2}{#3}{Comentário}% faz a nota de rodapé do ed
445 \if@cwmemoirdefense%
446 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}%
447 \else%
448 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}}%
449 \fi%
450 }%
451 {%
452 \cw@cwnote[#1]{#2}{#3}{#4}%
453 \if@cwmemoirdefense%
454 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}%
455 \else%
456 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}}%
457 \fi%
458 }%
459 }%
460 %% comentador genérico, parte II
461 %% faz o highlight , soma o step e comenta
462 %% [texto hl] footnote cor indicador
463 \newcommand{\cw@comment}[4][]{%
464 \refstepcounter{comentario}% soma um ao contador
465 \cw@hll{#3}{#1}% ver subfunção de impressão com hl
466 \cw@comentar{#2}{#3}{#4}%
467 }%
468 %%
469 %%
470 \newcommand{\cw@xcomment}[4][]{%
471 \refstepcounter{comentario}% soma um ao contador
472 \cw@hll{#3}{#1}% ver subfunção de impressão com hl
473 \cw@comentar{\sout{#2}}{#3}{#4}%
474 }%
475 %%
476 %%
477 %% comentador genérico com rótulo
478 %% [texto hl] footnote cor indicador rótulo
479 \newcommand{\cw@commentLabeled}[5][]{%
480 \refstepcounter{comentario}%
481 \cw@hll{#3}{#1}%
482 \cw@comentar[#5]{#2}{#3}{#4}%
483 }%
484 %%
485 %% [texto hl] footnote cor indicador rótulo
486 \newcommand{\cw@xcommentLabeled}[5][]{%
487 \refstepcounter{comentario}%
488 \cw@hll{#3}{#1}%
489 \cw@comentar[#5]{\sout{#2}}{#3}{#4}%
490 }%
491 %%
492 \if@cwmemoirdefense%
493 \else%
494 \setlength{\cftcomentarionumwidth}{\cw@cftnumwidth}%
495 \fi%

```

```

496 \else
497 \newcommand{\cw@comentar}[4][{}]{%
498 \newcommand{\listofcomentario}{}%
499 %% não pode perder o texto comentado
500 \newcommand{\cw@comment}[4][{}]{#1}%
501 \newcommand{\cw@commentLabeled}[5][{}]{#1}%
502 \newcommand{\cw@xcomment}[4][{}]{#1}%
503 \newcommand{\cw@xcommentLabeled}[5][{}]{#1}%
504 \fi%

```

19.13 Suggestions, Removes and Changes

```

505 %% comentário, cor, indicador, textovelho, cor velho, textonovo, cor novo
506 %% Em modo publicar coloca o textovelho
507 \newcommand{\cwdefattentiontext}[1]{\def\cw@attentiontext{#1}}
508 \if@showsuggestao
509 \newcommand{\cw@gensug}[7][Uma proposta]{%
510 \textcolor{#5}{\sout{#4}}}% CORRIGINDO AQUI
511 \textcolor{#7}{#6}%
512 \if@showcomentario%
513 \ifstrempy{#1}{%
514 \cw@comentar{\cw@attentiontext}{#2}{#3}%% [rótulo], cor , footnote , indicador
515 }%
516 {\refstepcounter{comentario}%
517 \cw@comentar{#1}{#2}{#3}%% [rótulo], cor , footnote , indicador
518 }%
519 \fi%
520 }%% [rótulo], cor , footnote , indicador
521 \else%
522 \if@modopublicaraceitando
523 \newcommand{\cw@gensug}[7][{}]{#6}%
524 \else%
525 \newcommand{\cw@gensug}[7][{}]{#4}%
526 \fi%
527 \fi%

```

19.14 File Control

```

\cwinput
\cwinclude
\cwinputediting 528 \newcommand{\cwinput}[3]{ } %% blank commands first
\cwincludeediting 529 \newcommand{\cwinclude}[3]{ }
\cwinputsubmit 530 \newcommand{\cwinputediting}[1]{ }
\cwincludesubmit 531 \newcommand{\cwincludeediting}[1]{ }
\cwinputpublish 532 \newcommand{\cwinputsubmit}[1]{ }
\cwincludepublish 533 \newcommand{\cwincludesubmit}[1]{ }
534 \newcommand{\cwinputpublish}[1]{ }
535 \newcommand{\cwincludepublish}[1]{ }
536 \if@modoedicao %% redefine only the necessary commands
537 \renewcommand{\cwinput}[3]{\input{#1}}
538 \renewcommand{\cwinclude}[3]{\include{#1}}
539 \renewcommand{\cwinputediting}[1]{\input{#1}}
540 \renewcommand{\cwincludeediting}[1]{\include{#1}}
541 \else

```



```

542 \if@modopublicar
543 \renewcommand{\cwininput}[3]{\input{#3}}
544 \renewcommand{\cwininclude}[3]{\include{#3}}
545 \renewcommand{\cwininputpublish}[1]{\input{#1}}
546 \renewcommand{\cwinincludepublish}[1]{\include{#1}}
547 \else
548 \if@modosubmeter
549 \renewcommand{\cwininput}[3]{\input{#2}}
550 \renewcommand{\cwininclude}[3]{\include{#2}}
551 \renewcommand{\cwininputsubmit}[1]{\input{#1}}
552 \renewcommand{\cwinincludesubmit}[1]{\include{#1}}
553 \fi
554 \fi
555 \fi

```

\cwinincludepublish

19.15 Citations Needed

One common error of students is not to cite correctly. Citation errors are so common that I decided to provide the option to have an optional list just for them. They are enable together with commentaries, users can use them or not.

```

556 \if@showcomentario%
557 \newcommand{\listcomentarioref}{\cwcitationstitle}%
558 \if@cwmemoirdefense%
559 \@ifundefined{chapter}%
560 {\newlistentry[section]{comentarioref}{ccr}{0}}
561 {\newlistentry[chapter]{comentarioref}{ccr}{0}}
562 \newlistof{listofcomentarioref}{ccr}{\listcomentarioref}
563 \else%
564 \@ifundefined{chapter}%
565 {\newlistof[section]{comentarioref}{ccr}{\listcomentarioref}}
566 {\newlistof[chapter]{comentarioref}{ccr}{\listcomentarioref}}%
567 \fi%
568 \else%
569 \newcommand{\listofcomentarioref}{}%
570 \fi%
571 \if@showcomentario%
572 \newcommand{\cw@commentref}[3][ ]{%
573 \refstepcounter{comentarioref}%
574 \cw@hll{#3}{#1}%
575 \cw@cwnote{#2}{#3}{\cwpleasecitmarginnote}%
576 \if@cwmemoirdefense%
577 \addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}%
578 \else%
579 \addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}%
580 \fi%
581 }%
582 \if@cwmemoirdefense%
583 \else%
584 \setlength{\cftcomentariorefnumwidth}{\cw@cftnumwidth}%
585 \fi%

```

```

586 \else%
587 \newcommand{\cw@commentref}[3]{}%
588 \fi%
589 \if@showcomentario

```

`\pleasecite` `\pleasecite[(footnote-text)]`

```

590
591 \newcommand{\pleasecite}[1][\cwpleasecitmessage]{%
592 \cw@commentref{\cwpleasecitetext\ #1}{\cor@citar}}%
593 \else%
594 \newcommand{\pleasecite}[1][{}]{}%
595 \fi%

```

19.16 Draft

`cwdraft` (*env.*) This environment creates a boxed text, with title used as a first parameter. It uses package `mdframed` to create the frame. If draft is turned off as an option, it suppresses everything inside the body. Due to problems with `soul` accepting `\cwdrafttitle` we use `\colorbox` to support multiple languages if default title is used

```

596 \if@showdraft%
597 \NewEnviron{cwdraft}[1][{}]{%
598 \ifstrempy{#1}%
599 {\colorbox{\cor@leve{\cor@hldraft}}{\textbf{\cwdrafttitle}}}%
600 {\cw@hll{\cor@hldraft}{\textbf{#1}}}%
601 \newline%
602 \BODY%
603 }%
604 }%
605 \surroundwithmdframed{cwdraft}%
606 \else%
607 \NewEnviron{cwdraft}[1][{}]{}%
608 \fi%

```

`\cwsetdraftcolor` Sets the color that highlights the draft title

```

609 %
610 \newcommand{\cwsetdraftcolor}[1]{\def\cor@hldraft{#1}}
611 %

```

19.17 Powerful command to create editors and authors

This allows for many types of comments. This was the reason I started using a front-end to `ed`, and later decided to use colors, that `ed` does not support. If I had known of `color-edits`, maybe this package was never done. I actually implemented the same functionalities without knowing about that package. One day, looking for other editorial packages that used editorial symbols, I found `color-edits`, but it was too late, I was already hooked on \LaTeX programming addiction. nome do autor, cor, identificador

`\cwnamedef`

```

612 \newcommand{\cwnamedef}[3]{%
613 %% cwcomment - texto a hl, cor, comentário, indicador de pessoa
614 \expandafter\newcommand\csname#1\endcsname[2] []%
615 {%
616 \cw@comment[##1]{##2}{#2}{#3}}%
617 % [texto a marcar], cor , comentário, palavra, rótulo
618 \expandafter\newcommand\csname#1r\endcsname[3] []%
619 {\cw@commentLabeled[##1]{##2}{#2}{#3}{##3}}%
620 %% cortados
621 \expandafter\newcommand\csname#1x\endcsname[2] []%
622 {%
623 %% Comentários
624 \cw@xcomment[##1]{##2}{#2}{#3}}%
625 %% [texto a marcar], cor , comentário, palavra, rótulo
626 \expandafter\newcommand\csname#1rx\endcsname[3] []%
627 {\cw@xcommentLabeled[##1]{##2}{#2}{#3}{##3}}%
628 %% sugestões
629 \expandafter\newcommand\csname#1sug\endcsname[2] []%
630 {\cw@gensug[##1]{#2}{#3}{#2}{##2}{#2}}%
631 \expandafter\newcommand\csname#1rem\endcsname[2] []%
632 {\cw@gensug[##1]{#2}{#3}{##2}{#2}{#2}}%
633 \expandafter\newcommand\csname#1troca\endcsname[3] []%
634 {\cw@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
635 \expandafter\newcommand\csname#1swap\endcsname[3] []%
636 {\cw@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
637 }%

```

`\cwauthor` These are the two standard users.

`\cweditor`

```

638 \cwnamedef{cwauthor}{red}{Author}
639 \cwnamedef{cweditor}{blue}{Editor}

```

19.18 To do notes

This was developed because some of my students started a text using `todonotes`, before being aware of my package, therefore I need to have some compatibility to make de change. With time it became useful and I will try to make something better in the future.

`\todo` If option inline is not used, it is only a front-end to an editorial comment for a user called “To do”. If it is used, it tries to simulate the simplest behavior of `todonotes` package. In the future this can be enhanced, since package `mdframe` is very powerful. If the non-inline version is used, the to do note will not appear in the List of Commentaries.²⁴

```

640 \newcommand{\cw@todobackgroundcolor}{orange}%
641 \cwnamedef{cw@todoauthor}{orange}{To do}%
642 \if@showtodo%
643 \newcommand{\todo}[2][comentar]{%

```

²⁴XEXÉO:It would be nice to check if `todonotes` is load and just use it

```

644 \IfEq{inline}{#1}%
645 {%
646 \begin{mdframed}[backgroundcolor=\cw@todobackgroundcolor]
647 #2%
648 \end{mdframed}%
649 }%
650 {%
651 \cw@todoauthor{#2}%
652 }%
653 }%
654 \else%\if@showtodo
655 \newcommand{\todo}[2][{}]{%
656 \fi%

```

`\cwdefinetodocolor` Allows the definition of a background color for todo notes.

```

657 \newcommand{\cwdefinetodocolor}[1]{\renewcommand{\cw@todobackgroundcolor}{#1}}%

```

19.19 Text Color

This is new in version 1.5. Trying to create a way to change the color of the default text, but it could interact with other commands.

```

658 \if@changeicolor%
659 \newcommand{\cwsavecolor}{\colorlet{savedcolor}{.}}
660 \newcommand{\cwcolor}[1]{\cwsavecolor%
661 \color{#1}
662 }
663 \newcommand{\cwrestorecolor}{\color{savedcolor}}
664 \else%
665 \newcommand{\cwsavecolor}{}
666 \newcommand{\cwcolor}[1]{}
667 \newcommand{\cwrestorecolor}{}
668 \fi%

```

19.20 Portuguese/English, or inverse translation table

These next lines of code made easy to convert this package to English, because it was written in Portuguese, for Brazilian researchers. Some commands were rewritten in English with time, such as `rascunho`, but the Portuguese version will always be maintained, while other were translated using only his mechanism.

```

669 \let\rascunho=\cwdraft%
670 \let\cwassunto=\cwsubject%
671 \let\favorcitar=\pleasecite%
672 \let\cwautor=\cwnamedef%
673 \let\listofcomments=\listofcomentario%
674 \let\listofcitationneeds=\listofcomentarioref%
675 \let\listofassunto=\listofsubject%
676 \let\listofsubjects=\listofsubject%
677 %

```

End of Code

References

- [Kem20] David Kempe. *The Color-edits package. Colorful edits for multiple authors of a shared document.* Version 1.1. Sept. 19, 2020. URL: <http://www.ctan.org/pkg/color-edits> (visited on 05/29/2021).
- [Ker16] Uwe Kern. *The Xcolor package. Driver-independent color extensions for LaTeX and pdfLaTeX.* Version 2.12. May 11, 2016. URL: <http://www.ukern.de/tex/xcolor.html> (visited on 05/29/2021).
- [Koh11] Michael Kohlhase. *The Ed package. Editorial Notes for LaTeX documents.* Version 1.8. July 1, 2011. URL: <https://gl.kwarc.info/kwarc/macros/tree/master/ed> (visited on 05/29/2021).
- [Mid21] Henrik Skov Midtiby. *The todonotes package.* Apr. 26, 2021. URL: <http://www.ctan.org/pkg/todonote> (visited on 05/29/2021).
- [Min09] B. Minto. *The Pyramid Principle: Logic in Writing and Thinking.* Financial Times Series. Financial Times Prentice Hall, 2009. ISBN: 9780273710516.

Change History

1.4.4	General: soul substitutes soulutf8 that is now obsolete	1	department, “emulates” tocloft, but not correctly. Many IFs were necessary	1	
1.5	General: Commands to change text color (and restore)	1	v1.2.3	General: CoppeTex class asks for LoF and etc... to appear in ToC. This is an option in tocloft, but Book does not behave like that	1
1.5.1	General: Coloring should only work in edit mode	1	v1.2.4	General: Corrections for CTAN . . .	1
1.5.2	General: clash with mdpi option submit, make 2 options that should be excludent possible together, solving if nested ifs . . .	1	v1.3	General: New macro cwblind	1
v1.0	General: First version	1	v1.3.1	General: Fix bug on todo and publish	1
v1.1	General: You can put an aditional symbol before the comment superscript number	1	v1.3.2	General: Fix bug on citation anonymous	1
v1.1.1	General: Fix some bugs, anonymization back on manual . . .	1	v1.3.3	General: Fix behavior of anonymize and noanonymize to be stronger than modes	1
v1.1.2	General: PDF bookmarks can’t handle full UTF	1	v1.4	General: Now there are commands to include files in special situations	1
v1.2.0	General: New command cwmain and configuration for it	1	v1.4.1	General: Text that will be anonimized will appear in a different color	1
v1.2.1	General: Fixing problems with footnote mark color and also recovering L ^A T _E X command (at-sign)makefnmark	1	v1.4.2	General: Citation that will be anonimized will appear in a different color	1
v1.2.2	General: Memoir class, used by abnetex2, used by my		v1.4.3	General: Suggestions, removal now have default commentaries	1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\@anonimizarfal ^{se} . 11	\@showdraftfal ^{se} ..	\coopwritingversion
\@anonimizartru ^e 26, 39 14, 66, 76 1, 2
\@beanonymous 8, 10	\@showdrafttru ^e . . .	\cor@cand 132
\@beanonymousfal ^{se} 24, 43, 57	\cor@citar . . . 135, 592
..... 13, 60, 78, 84	\@showsbjectsfal ^{se}	\cor@hldraft
\@beanonymoustru ^e 69, 88 15, 65, 74	. 136, 599, 600, 610
\@change ^{color} fal ^{se} .	\@showsbjectstru ^e .	\cor@main . 134, 372, 403
..... 23, 71, 80 29, 42, 56	\cor@prof 131
\@change ^{color} tru ^e 45, 62	\@showsugestaofal ^{se}	\cor@suavizacao 258, 259
\@cwmemoirdefens ^e fal ^{se} 16, 68, 75	\cor@subject
..... 128	\@showsugestaotru ^e 133, 371, 388
\@cwmemoirdefens ^e tru ^e 28, 41, 59	\corleve . . 258, 263, 599
..... 125	\@showtodofal ^{se} . . .	\csname 614,
\@cwtoclofttitl ^{es} fal ^{se} 17, 70, 79	618, 621, 626,
..... 22	\@showtodotru ^e .. 44, 61	629, 631, 633, 635
\@cwtoclofttitl ^{es} tru ^e	\@temp@color .. 251, 256	\cw@anonciteptext .
..... 53	\@temp@makefnmark 273, 280, 285
\@empty 207 220, 224	\cw@anoncit ^e text . .
\@ifclassload ^{ed} 105, 123	\@test 202, 206 273, 279, 284
\@ifpackageload ^{ed} .	\@textsuperscript . 221	\cw@anoncit ^e ttext .
..... 116, 147	\@thefnmark 221 273, 281, 286
\@ifund ^{efined}	_ 592	\cw@anontext
..... 377, 382,	A 273, 278, 283
428, 433, 559, 564	\addcontentsline ..	\cw@attentiontext .
\@makefnmark 396, 398, 408,	. 145, 158, 169,
..... 220, 221, 224	410, 446, 448,	181, 193, 507, 514
\@modoedicaofal ^{se} . 18	454, 456, 577, 579	\cw@beforemark ^s symbol
\@modoedicaotru ^e 30, 46	\addtocounter 233 217, 222
\@modopublicarac ^e itandofal ^{se}	B	\cw@cftnumwidth . . .
..... 21	\belowpdfbookmark . 237	. 137, 416, 494, 584
\@modopublicarac ^e itandotru ^e	\BODY 602	\cw@comentar . . 441,
..... 35, 51	C	466, 473, 482,
\@modopublicarfal ^{se} 20	\cftcomentarionumwidth	489, 497, 514, 517
\@modopublicartru ^e 494	\cw@comment 463, 500, 616
..... 32, 34, 48, 50	\cftcomentariorefnumwidth	\cw@commentLabeled .
\@modosubmeterfal ^{se} 19 584 479, 501, 619
\@modosubmetertru ^e .	\cftsubjectnumwidth 416	\cw@commentref
..... 31, 47	\cite . 293, 294, 301, 302 572, 587, 592
\@naoanonimizarfal ^{se} 12	\citep 308,	\cw@currentcolor 199,
\@naoanonimizartru ^e	314, 315, 318, 319	205, 210, 212,
..... 27, 40	\cit ^e t 331,	213, 221, 222,
\@showcomentari ^o fal ^{se}	337, 338, 341, 342	228, 251, 252, 256
..... 7, 67, 77	\color 221, 661, 663	\cw@cwnote
\@showcomentari ^o tru ^e	\colorbox 599	. 268, 444, 452, 575
..... 25, 38, 58, 91	\colorlet 263, 659	\cw@editAnonColor .
	 260, 289,

293, 294, 314, 315, 337, 338, 363	\cwinclude 528	\ednotebookmarkstrue 5
\cw@foot 200, 223	\cwincluedeediting . 528	\else 102,
\cw@footnote . . 219, 235	\cwincluedeupload . 528	112, 208, 287,
\cw@gensug	\cwinput 528	296, 316, 339,
. 509, 523, 525,	\cwinputediting . . . 528	360, 365, 381,
630, 632, 634, 636	\cwinputpublish . . . 528	397, 409, 415,
\cw@hll 262, 465, 472,	\cwinputsubmit 528	418, 432, 447,
481, 488, 574, 600	\cwmain 401	455, 493, 496,
\cw@margin . . . 226, 243	\cwmainemphasis 401, 406	521, 524, 541,
\cw@mark 215, 222	\cwnamedef . . . 612,	547, 563, 568,
\cw@mark@style 215, 216	638, 639, 641, 672	578, 583, 586,
\Cw@note . . 231, 241, 249	\Cwnote 249	593, 606, 654, 664
\cw@note 240, 253	\cwnote 250, 271	\end 648
\cw@noteshape . 198, 213	\cwnote@label	\endcsname . . . 614,
\cw@todoauthor 651	. 245, 247, 249, 254	618, 621, 626,
\cw@todobackgroundcolor	\cwnote@margin	629, 631, 633, 635
. 640, 646, 657 246, 248, 255	environments:
\cw@version 1	\cwnotecounter 197	cwdraft 596
\cw@xcomment	\cwnotelabel . . 247, 269	\expandafter . . 614,
. 470, 502, 624	\cwnotemargin . 248, 270	618, 621, 626,
\cw@xcommentLabeled	\cwpleasecitemarginnote	629, 631, 633, 635
. 486, 503, 627 144, 157,	
\cwanon . . . 283, 289, 297	168, 180, 192, 575	F
\cwanoncite	\cwpleasecitemessage	\favorcitar 671
. 284, 290, 298, 143, 156,	\fi . . 63, 72, 81, 85,
326, 327, 350, 351	167, 179, 191, 591	89, 92, 104, 114,
\cwanoncitep	\cwpleasecitetext .	122, 211, 229,
. 285, 310, 324 142, 155,	238, 239, 244,
\cwanoncitett	166, 178, 190, 592	304, 320, 343,
. 286, 333, 347	\cwrestorecolor 663, 667	354, 369, 370,
\cwassunto 670	\cwsavecolor	385, 399, 411,
\cwauthor 638 659, 660, 665	417, 422, 436,
\cwautor 672	\cwsetanoncolor . . . 260	449, 457, 495,
\cwblind 356	\cwsetcommwarn 217	504, 519, 526,
\cwcitationstyle .	\cwsetdraftcolor . . 609	527, 553, 554,
. 141, 154,	\cwsetmaincolor . . . 371	555, 567, 570,
165, 177, 189, 557	\cwsetsubjectcolor . 371	580, 585, 588,
\cwcolor 660, 666	\cwsubject 373, 420, 670	595, 608, 656, 668
\cwcommentstyle . .	\cwsubjtitle 140, 153,	\footnotemark 216
. 139, 152,	164, 176, 188, 374	\footnotetext 203
163, 175, 187, 425		
\cwdefanonciteptext 278	D	H
\cwdefanoncitett . 278	\DeclareOption	\hbox 221
\cwdefanoncitetttext 278 24, 25, 26,	\hl 265, 391, 401
\cwdefanontext 278	27, 28, 29, 30,	
\cwdefattentiontext 507	31, 32, 33, 37,	I
\cwdefinetodocolor . 657	38, 39, 40, 41,	\if 206
\cwdraft 669	42, 43, 44, 45,	\if@animizar . . 11, 87
cwdraft (env.) 596	46, 47, 48, 49, 53	\if@beanonymous . . .
\cwdrafttitle 13, 282, 356
. 138, 151,	E	\if@changecolor 23, 658
162, 174, 186, 599	\ednotebookmarksfalse	\if@cwmemoirdefense
\cweditor 638 37	. 125, 128, 376,
		395, 407, 414,

427, 445, 453, 492, 558, 576, 582	\listofassunto 675	R
\if@cwtoctlofttitles 22, 110	\listofcitationneeds 674	\rascunho 669
\if@modoedicao 18, 55, 288, 312, 335, 361, 536	\listofcomentario 498, 673	\refstepcounter 389, 404, 464, 471, 480, 487, 516, 573
\if@modopublicar 20, 73, 542	\listofcomentarioref 569, 674	\relax 54
\if@modopublicaraceitando 21, 522	\listofcomments ... 673	\renewcommand . 278, 279, 280, 281, 537, 538, 539, 540, 543, 544, 545, 546, 549, 550, 551, 552, 657
\if@modosubmeter 19, 64, 548	\listofsubjects ... 676	\RequirePackage 93, 94, 95, 96, 97, 98, 99, 100, 103, 107, 111, 113, 118, 122
\if@naoanonimizar 12, 83	\listsubject 374, 380, 383, 384	
\if@showcomentario 7, 423, 512, 556, 571, 589	M	
\if@showdraft .. 14, 596	\marginpar 228	
\if@showssubjects 15, 373	\marginstrue 4	
\if@showsugestao 16, 508	\meta 210	
\if@showtodo 17, 90, 642, 654	N	S
\ifdef 96, 308, 331	\NewEnviron ... 597, 607	\sethlcolor 264, 390, 405
\ifednotebookmarks 5, 122, 236	\newif 3, 4, 5, 7, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 125, 128	\setlength 416, 494, 584
\IfEq 644	\newline 601	\sffamily 198
\IfLanguageName 149, 160, 172, 184	\newlistentry 378, 379, 429, 430, 560, 561	\showednotestruel ... 3
\ifmargins 4, 227	\newlistof 380, 383, 384, 431, 434, 435, 562, 565, 566	\sout 473, 489, 510
\ifshowednotes 3, 101, 234, 242	\normalfont 221	\subsubsection 6
\ifstrempty ... 292, 300, 313, 317, 325, 336, 340, 349, 442, 513, 598	\numberline 396, 398, 408, 410, 446, 448, 454, 456, 577, 579	\surroundwithmdframed 605
\include .. 538, 540, 544, 546, 550, 552	P	T
\input 537, 539, 543, 545, 549, 551	\par 392	\textbf 599, 600
L	\pleasecite ... 590, 671	\textcolor 205, 210, 212, 213, 222, 228, 289, 293, 294, 314, 315, 337, 338, 363, 510, 511
\label 209	\printcoopwritingversion 2	\thecomentario 446, 448, 454, 456
\listcomentario 425, 431, 434, 435	\ProcessOptions ... 54	\thecomentarioref 577, 579
\listcomentarioref . . 557, 562, 565, 566	\protect 396, 398, 408, 410, 446, 448, 454, 456, 577, 579	\thecwnotecounter . 237
		\thesubject 396, 398, 408, 410
		\todo 640

List of Comments

1.1 Xexéo: This is an exemple of using this package to make a comment with highlighted text	3
5.1 Xexéo: This is the simplest form of an editorial note.	7
5.2 Xexéo: This is the example of the minimal use of an editorial command	7
5.3 Author: Simplest footnote comment	8
5.4 Editor: Comment with highlighting	8
5.5 Author: labeled footnote comment	8
5.6 Author: labeled comment with highlighting	8
5.7 Editor: Simplest footnote comment	8
5.8 Author: Comment with highlighting	8
5.9 Author: labeled footnote comment	8
5.10 Author: labeled comment with highlighting	8
5.10 Author: Attention	9
5.11 Editor: I want to insert this	9
5.11 Author: Attention	9
5.12 Author: Repeated words	9
5.12 Author: Attention	10
5.13 Xexéo: This comment superscript number should be preceeded by a $\frac{1}{2}$.	10
5.14 Xexéo: ★★ Two stars are still low priority	10
10.1 Xexéo: But it will grow in power with time	14
10.2 To do: This is how it works without the inline option	14
19.1 To do: I must complete this explanation list	20
19.2 Xexéo: It would be nice to check if todonotes is load and just use it . .	35

List of Citation Needs

19.1 Plese cite memoir package	21
19.2 Plese cite ed package	23

List of Subjects

8.1	Example of a subject	13
8.2	A pink colored subject	13
8.3	All subjects will be cyan.	13
8.4	This is the main idea	13
8.5	This is another main idea	13
8.6	This is the main idea	13
8.7	This is the main idea	14
19.1	This is an use for cwsobject	29
19.2	This is a use for cwmain.	30
19.3	This is a use for cwmain.	30