Código do Estilo hacksxexeo v4.3.2

Geraldo Xexéo

Thursday 27^{th} May, 2021 - 16:01

1 Introduction

This package support different forms of comments and editorial marks. It picks ideas from different packages, such as ed, color-edits, todonotes, and others. It was written to support my way of working, and received suggestions from my students. The main goal was to build only a front-end to other packages, but with time, it grow in scope.

As it is my first package, TeXand IATeXprogramming is sometimes naive. I aimed at building it over other packages, but due to the fact that many packages in this subject clash, I rewrote some code. Also, although aiming at minial interference with other packages, some decisions had to be made.

I had to thank Eduardo Mangeli, that did some previous code.

2 Usage

Este pacote usa outro pacote que transforma o comportamento padrão do sumário e das listas no LATEX, que deixam de pular a página automaticamente. Não há por enquanto solução para esse problema, a não ser o óbvio: usar o comando \newpage antes dos comandos \tableofcontents, etc.

Se você usar o pacote hyperref, as listas podem ser clicadas para atingir o local do comentário.

2.1 Informing user about versions

It is possible that the user wants to know the version being used. We provide two commands for it.

 $\verb|\hacksxexeoversion| \\ | printhacksxexeoversion| \\$

Provides the current version Provides name and version

2.2 Draft environment

rascunho

The draft environment aims to allow writers to include text that is marked somehow as a draft. This environment is evolving, looking for a good way to signal the draft status, due to the different interactions with the packages it uses and user's

packages. It has one optional parameter that names the draft. Its default value is "Rascunho" Ir the rascunho option is not enabled, the text inside the title and the text inside the environment will not appear. The user should remember that some options will automatically turn on the rascunho option, such as the option

\begin{rascunho}[A draft title] This is the example of a draft. The title must be highlighted There must be a box around it. \end{rascunho}

\begin{rascunho} This draft has the default title. \end{rascunho}

A draft title

This is the example of a draft. The title must be highlighted There must be a box around it.

Draft

This draft has the default title.

3 Warnings

This package uses another package that changes LATEX's standard behavior for summary and lists. When you use it, you must explicitly change pages with \newpage before \tableofcontents or similar commands.

Implementation 4

Access to the current version

We provide some macros for the user to know the version being used.

\hacksxexeoversion Provides current version of hacksxexeo

1 \newcommand{\hacksxexeoversion}{\hx@version}%

\printhacksxexeoversion Provides package name and version

2 \newcommand{\printhacksxexeoversion}{\hacksxexeo v. \hacksxexeoversion}\%

4.2 Option Processing

```
3 \newif\ifshowednotes\showednotestrue
4 \newif\ifmargins\marginstrue
5 \newif\ifmarginnote\marginnotefalse
6 \newif\ifednotebookmarks\ednotebookmarksfalse
7 \DeclareOption{show}{\showednotestrue\message{ed.sty: showing ednotes}}
8 \DeclareOption{hide}{\showednotesfalse\message{ed.sty: hiding ednotes}}
9 \DeclareOption{draft}{\showednotestrue\message{ed.sty: showing ednotes}}
{\tt 10 \setminus DeclareOption\{final\}\{\setminus showed notesfalse \setminus message\{ed.sty: \ hiding \ ednotes\}\}}
11 \DeclareOption{nomargins}{\marginsfalse}
12 \DeclareOption{marginnote} {\marginnotetrue}
13 \DeclareOption{pdfbookmarks}{\ednotebookmarkstrue}
14 %%%
15 \newif\if@showcomentario\@showcomentariofalse
16 \DeclareOption{comentarios}{\@showcomentariotrue}
17 \newif\if@beanonymous\@beanonymousfalse
18 \DeclareOption{anonimizar}{\@beanonymoustrue}
19 \newif\if@naoanonimizar\@naoanonimizarfalse
20 \DeclareOption{naoanonimizar}{\@naoanonimizartrue}
21 %% As 3 opções a seguir tem comportamento
22 %% dependente de comentarios (colocam ou não)
23 \newif\if@showsugestao\@showsugestaofalse
24 \DeclareOption{sugestoes}{
      \@showsugestaotrue}
26 \newif\if@showassuntos\@showassuntosfalse
27 \DeclareOption{assuntos}{\Qshowassuntostrue}
28 \newif\if@showrascunho\@showrascunhofalse
29 \DeclareOption{rascunhos}{\@showrascunhotrue}
30 \newif\if@showtodo\@showtodofalse
31 \DeclareOption{todos}{\@showtodotrue}
32 \newif\if@modoedicao\@modoedicaofalse
33 \newif\if@modosubmeter\@modosubmeterfalse
34 \neq 0
35 \mbox{ } \mbox{\ licaraceitando} \mbox{\cite{Cmodopublicaraceitandofalse}}
36 \DeclareOption{edicao}{\@modoedicaotrue}
37 \DeclareOption{submeter}{\@modosubmetertrue}
38 \DeclareOption{publicar}{\@modopublicartrue}
39 \DeclareOption{publicaraceitando}{\@modopublicartrue \@modopublicaraceitandotrue }
40 \ProcessOptions\relax
```

5 Super Options

Some options are more general and set other options

```
41 \if@modoedicao
42 \@showassuntostrue
43 \@showrascunhotrue
44 \@showcomentariotrue
45 \@showsugestaotrue
46 \@beanonymoustrue
```

```
47 \@showtodotrue
49 \setminus if@modosubmeter
50 \@showassuntosfalse
51 \@showrascunhofalse
52 \@showcomentariofalse
53 \@showsugestaofalse
54 \@beanonymoustrue
55 \@showtodofalse
56 \fi
57 \setminus if@naoanonimizar
58 \@beanonymousfalse
59 \fi
60 \if@modopublicar
61 \@showassuntosfalse
62 \ \ %showsugestaofalse
63 \ \ %showrascunhofalse
65 \setminus \texttt{Qbeanonymousfalse}
66 \@showtodofalse
67 \fi%
68 \if@showtodo
69 \@showcomentariotrue
70 \fi
```

5.1 Required Packages

```
Packages that are always required
```

6 Optional Packages

Package that are required only sometimes

```
83 \ifshowednotes
84 %%\RequirePackage{paralist}
85 \ifmarginnote\RequirePackage{marginnote}\fi
86 \else
```

```
87 \RequirePackage{verbatim}
88 \fi%
Checking if babel is loaded, use iflang
89 \@ifpackageloaded{babel}%
90 {% \message{Babel Loaded!}%
91 \RequirePackage{iflang}%
92 }{%
93 \message{Babel not detected!}%
94 }%
95 % | hyperref | must always be the last
96 \ifednotebookmarks\RequirePackage{hyperref}\fi
```

6.1 I18N Using Babel

We can detect if babel is enable and allow for some languages. If you want to use another language, just use \setlocalecaption to set the correct value.

\hxdrafttitle

```
97 \@ifpackageloaded{babel}%
 98 {%
 99
       \IfLanguageName{brazilian}{\def\hxdrafttitle{Rascunho}}{}
100
       \IfLanguageName{portuguese}{\def\hxdrafttitle{Rascunho}}{}
       \IfLanguageName{english}{\def\hxdrafttitle{Draft}}{}
101
       \message{Babel detected!}
102
103 }{%
104
       \def\hxdrafttitle{This~is~a~Draft}%
       \message{No Babel!}
105
106 }%
```

6.2 ed inspired code

This code, inspired in the ed package, makes the basic mechanism for inserting comments as footnotes with an observation in the margin. As an adition to ed, it support colors.

```
107 \newcommand\ednoteshape{\sffamily}
108 \newcounter{ednote}
109 \def\hx@currentcolor{black}
a mágica é aqui footnote indicador e rótulo
```

\ed@foot

This macro creates a footnote. It uses counter ednote in arabic. It prints the footnote using the currently defined color (That is a global variable, setted up elsewehre. This is not good programming practice, but it turned out to be the easiest way of doing it in IATEX without more and more arguments.)

```
110 \newcommand\ed@foot[3]% text, type, label
111 {\def\@test{#3}\footnotetext[\arabic{ednote}]%
112 {\scshape{\textcolor{\hx@currentcolor}{#2}}\if\@test\@empty\else\label{ed:#3}\textcolor{\hx@currentcolor}
```

```
113 \def\ed@mark@style#1{#1}%
114 \newcommand\ed@mark[1]{\ed@mark@style{\footnotemark[#1]}}%
\label{locality} $$115 \rightarrow \mathbb{3}\left(\frac{3}{\hat{1}\right)}^2 \left(\frac{3}{\hat{1}}\right)^2 . $$
116 %% a outra mágica é aqui
117 \newcommand\ed@margin[1]{\ifmargins\ifmarginnote\marginnote{\textcolor{\hx@currentcolor}{#1}}\e
119 \newcommand\Ed@note[3]% text, type, label
120 {\addtocounter{ednote}{1}\message{#2!}%
                 \label{lower_showed} $$ \left( \frac{\#1}{\#2}{\#3} \right) ifednotebook marks \elow pdfbook mark{\#2: \#1}{\#2.} the edding of the property of
122 \newcommand\ed@note[4]% text, type, label, margin
124 \newcommand\ednote@label{EdNote}%
125 \newcommand\ednote@margin{EdN}%
126 \newcommand\ednotelabel[1] {\def\ednote@label{#1}}%
127 \newcommand\ednotemargin[1]{\def\ednote@margin{#1}}%
\label{localized} $$128 \rightarrow \mathbb{[2][]_{\endownermand}^{2}\left[2\right][]_{\endownermand}^{2}\endownermand}$
129 \newcommand{\ednote}[3][]{\def\hx@currentcolor{#3}%
130 \ed@note{#2}\ednote@label{#1}\ednote@margin}%
132 %%https://tex.stackexchange.com/questions/30483/how-can-i-check-in-latex-or-plain-tex-whether-
134 %% as opções comentario, assuntos e anonimizar
135 %% CORES
  6.3
                  Variáveis relacionadas a cores
136 \newcommand{\cor@prof}{red}%
137 \newcommand{\cor@cand}{blue}%
138 \newcommand{\cor@assunto}{green}%
139 \newcommand{\cor@citar}{purple}%
140 \newcommand{\cor@hlrascunho}{yellow}%
```

```
136 \newcommand{\cor@prof}{red}%

137 \newcommand{\cor@cand}{blue}%

138 \newcommand{\cor@cand}{blue}%

139 \newcommand{\cor@citar}{purple}%

140 \newcommand{\cor@citar}{purple}%

141 \%Isso \(\delta\) um truque para o \nldo soulutf8 funcionar

142 \%https://tex.stackexchange.com/questions/410295/soul-color-transparency

143 \% comando para suavizar uma cor

\corleve \( \text{Esse comando faz uma cor ficar mais clara para o hilight Isso \(\delta\) um truque para o \( \text{o soulutf8 funcionar https://tex.stackexchange.com/questions/410295/soul-color-transparency

144 \newcommand{\cor@suavizacao}{40}\%

145 \newcommand{\cor@suavizacao}{40}\%

146 \% \text{Problema de dar cor para o soul pode ser resolvido}

147 \% \text{Aqui mudando para o ulem}

148 \newcommand{\hx@hll}[2]\% \text{Depedendo do soulutf8}

149 \{\colorlet{x@coraqui}{\corleve{#1}}\}\%

150 \sethlcolor{x@coraqui}{\corleve{#1}}{#2}

152 \% \colorbox{\corleve{#1}}{#2}

153 \%

154 \% \text{ isolando o ednote}
```

```
155 %% rótulo texto cor indicador
156 \newcommand{\hx@ednote}[4][]{%
157 \ednotelabel{#4}%
158 \ednotemargin{#4}%
159 \ednote[#1]{#2}{#3}%
160 % isso não tem - \hx@ednotepre{#1}{\textcolor{#3}{#2}}{#4}{#4}{#3}
162 %%
163 %%
164 %%
165 %% Anonimização
166 %% Se anonimiza, escreve anonymous
167 %% se não escreve o texto
168 \newcommand{\hx@anoncitetext}{(Anonymous, Year)}%
169 \newcommand{\hx@anonciteptext}{(Anonymous, Year)}%
170 \newcommand{\hx@anoncitettext}{Anonymous (Year)}%
171 \newcommand{\hxdefanoncitetext}[1]{\newcommand{\hxQanoncitetext}} \#1}}\%
172 \newcommand{\hxdefanonciteptext} [1] {\renewcommand{\hx@anonciteptext} {#1}}%
173 \newcommand{\hxdefanoncitettext} [1] {\renewcommand{\hx@anoncitettext} {#1}}%
174
175 \if@beanonymous
176 \newcommand{\hxanon}[1]{Anonymous}%
177 \newcommand{\hxanoncite}[2][]{\hx@anoncitetext}%
178 \newcommand{\hxanoncitep} [2] [] {\hx@anonciteptext}%
179 \newcommand{\hxanoncitet}[2][]{\hx@anoncitettext}%
180 \else
181 \newcommand{\hxanon}[1]{#1}%
182 \newcommand{\hxanoncite}[2][]{\cite[#1]{#2}}%
183 \left\{ \left( 183 \right) \right\} \\
184 \left\{ \left( 12 \right) \right\} \\ \left( 12 \right) \\ \left( 13 \right) \\
185 \fi%
186 %% retrocompatibilidade
187 \newcommand{\xanon} [2] [] {\hxanon [#1] {#2}}%
188 \newcommand{\xanoncitep}[2][]{\hxanoncitep[#1]{#2}}%
189 \newcommand{\xanoncitet}[2][]{\hxanoncitet[#1]{#2}}%
190 %%
191 \% Assuntos colore o texto apenas, pode melhorar
192 %%
193 \if@showassuntos
194 %% Cria a lista
195 %% cria o título
196 \newcommand{\listassunto}{Lista de Assuntos}%
197 %% cria a lista, depende do pacoto tcloft
\label{list-sunt} $$198 \end{chapter}_{\newlist of [section] assunto}_{\aaa}_{\newlist of [chapter] assunto}_{\newlist of [section]}_{\newlist of [s
199 %%
200 \newcommand{\hxassunto}[2][\cor@assunto]{%
201
                             \refstepcounter{assunto}%
202
                             \sethlcolor{#1}%
                             \h1{#2}%
203
                             \par%
204
```

```
\addcontentsline{aaa}{assunto}{\protect\numberline{\theassunto}{#2}}%
205
206 }%
207 \setlength{\cftassuntonumwidth}{2.5em}%
208 \ensuremath{\mbox{\sc lse}\%}
209 %% se não é para mostrar, não faz nada
210 \newcommand{\listofassunto}{}%
211 \mbox{ } \mbox{
212 \fi% | % @showassuntos
213 \newcommand{\xassunto}[2] [\cor@assunto] {\hxassunto [#1] {#2}}
214 %%
215 %%
216 %%
217 \if@showcomentario
218 %% Resolve a lista de comentários
219 \newcommand{\listcomentario}{Lista de Comentários}%
220 %% cria a lista
222 %%
223 %% Comentador genérico - parte I
224 %% faz o ednote e soma na lista
225 %% []rótulo], texto , cor, indicador
226 \newcommand{\hx@comentar} [4] [] {\%}
                \ifstrempty{#4}{%
227
                         % rótulo texto cor indicador
228
                         \hx@ednote[#1]{#2}{#3}{Comentário}% faz a nota de rodapé do ed
229
                         \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}}}
230
               }%
231
                {%
232
                          \hx@ednote[#1]{#2}{#3}{#4}%
233
                         \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}}%
234
               }%
235
236 }%
237 %% comentador genérico, parte II
238 \% faz o highlight , soma o step e comenta
239 %% [texto hl] footnote cor indicator
240 \newcommand{\hx@comment}[4][]{%
                \refstepcounter{comentario}% soma um ao contador
241
                \hx@hll{#3}{#1}% ver subfunção de impressão com hl
^{242}
^{243}
                \hx@comentar{#2}{#3}{#4}%
244 }%
245 %%
246 %%
247 \newcommand{\hx@xcomment} [4] [] {%
                \refstepcounter{comentario}% soma um ao contador
248
249
                \hx@hll{#3}{#1}% ver subfunção de impressão com hl
^{250}
                \t \ \hx@comentar{\sout{#2}}{#3}{#4}%
251 }%
252 %%
253 %%
254 %% comentador genérico com rótulo
```

```
255 %% [texto hl] footnote cor indicator rótulo
256 \newcommand{\hx@commentLabeled}[5][]{%
                  \refstepcounter{comentario}%
257
                  \hx@hl1{#3}{#1}%
258
                  \mbox{hx@comentar}[#5]{#2}{#3}{#4}%
259
260 }%
261 %%
262 %% [texto hl] footnote cor indicator rótulo
263 \newcommand{\hx@xcommentLabeled} [5] [] {%
                  \refstepcounter{comentario}%
264
                  \hx@hll{#3}{#1}%
265
                  \mbox{\normalfont} \mbox{\norm
^{266}
267 }%
268 %%
269 \setlength{\cftcomentarionumwidth}{2.5em}
270 \else
271 \newcommand{\hx@comentar} [4] []{}%
272 \newcommand{\listofcomentario}{}%
273 %% não pode perder o texto comentado
274 \newcommand{\hx@comment}[4][]{#1}%
275 \newcommand{\hx@commentLabeled}[5][]{#1}%
276 \fi%
277 %%%
278 %%
279 \%\% Sugestões e trocas
280 %%
281 %%%
282 %% comentário, cor, indicador, textovelho, cor velho, textonovo, cor novo
283 %% Em modo publicar coloca o textovelho
284 \setminus if@showsugestao
285 \newcommand{\hx@gensug} [7] [Uma proposta] {\%}
                  \verb|\textcolor{#5}{\sout{#4}}|% CORRIGINDO AQUI|
286
287
                  \text{textcolor}\{\#7\}\{\#6\}\%
                  \if@showcomentario%
288
                  \left\{ fstrempty\{\#1\}\{\}\%\right\}
289
                  {\refstepcounter{comentario}%
290
                             291
                  }%
292
293
                  \fi%
294 } % [rótulo], cor , footnote , indicador
295 \else%
296 \if@modopublicaraceitando
297 \newcommand{\hx@gensug} [7] [] \{#6\}\%
298 \else%
299 \newcommand{\hx@gensug} [7] [] {#4}%
300 \fi%
301 \fi%
303 %% Agora o criador
304 %% criando novos autores
```

```
305 %% nome do autor, cor, identificador
306 \newcommand{\hxautor}[3]{%
                                   % hxcomment - texto a hl, cor, comentário, indicador de pessoa
307
                                   \expandafter\newcommand\csname#1\endcsname[2][]%
308
                                   {%
309
310
                                                       %Comentários
311
                                                       \hx@comment[##1]{##2}{#2}{#3}}%
312
                                   % [texto a marcar], cor , comentário, palavra, rótulo
                                   \expandafter\newcommand\csname#1r\endcsname[3][]%
313
                                   {\nx} {\nx} = {\nx} {\
314
                                   % cortados
315
316
                                   \ensuremath{\texttt{\endcsname}}\
317 {%
                                   %Comentários
318
                                   \mbox{\comment}[##1]{##2}{#2}{#3}}%
319
320\ \mbox{\ensuremath{\mbox{\ensuremath{\mbox{\sc N}}}} [texto a marcar], cor , comentário, palavra, rótulo
321 \expandafter\newcommand\csname#1rx\endcsname[3][]%
322 {\hx@xcommentLabeled[##1]{##2}{#2}{#3}{##3}}%
323
324
                                   %sugestões
                                   \expandafter\newcommand\csname#1sug\endcsname[2][]%
325
                                   {\ny 0gensug[\##1]{\#2}{\#3}{}{\#2}{\#2}{\#2}}
326
327
                                   \expandafter\newcommand\csname#1rem\endcsname[2][]%
328
                                   {\ny 0} {\ny
329
330
                                    \expandafter\newcommand\csname#1troca\endcsname[3][]%
                                   {\hx@gensug[##1]{#2}{#3}{##2}{##3}{#2}}%
331
332 }%
333 \hxautor{prof}{red}{Prof}
334 \hxautor{cand}{blue}{Cand}
335 %%
336 %%
337 %%
338 %% reclamações sobre citações
339 %%
340 %%
341 \if@showcomentario%
342 %% cria o título
343 \newcommand{\listcomentarioref}{Necessidades de Citação}%
344 %% cria a lista
345 \end{fined} 
346 \else%
347 %% se não é para mostrar, não faz nada
348 \newcommand{\listofcomentarioref}{}%
349 \fi%
350 \if@showcomentario%
351 \newcommand{\hx@commentref}[3][]{%
352
                                   \refstepcounter{comentarioref}%
353
                                   \hx@hl1{#3}{#1}%
```

354

```
\addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}}%
         356 }%
         357 \setlength{\cftcomentariorefnumwidth}{2.5em}%
         358 \else%
         359 \newcommand{\hx@commentref}[3]{}%
         360 \fi%
         361 \if@showcomentario
         362 \newcommand{\favorcitar}[1][algo que suporte essa afirmação]{%
                \hx@commentref{Por favor citar #1}{\cor@citar}}%
         364 \else%
         365 \newcommand{\favorcitar}[1][]{}%
         366 \fi%
         367 %%
         368 %%
         369 %%
         370\ \mbox{\%}\ \mbox{Marcando} ou esquendo dos rascunhos
         371 %% Changebar foi removido porque é ruim
         372 %%
        This macro creates a boxed text, with title used as a first parameter It uses package
rascunho
          mdframed to create the frame. If rascunho is turned off as an option, it supress
          everything inside the body. Due to problems with soul accepting \hxdrafttitle
          we use \colorbox to support multiple languages if default title is used
         373 \if@showrascunho%
         374 \NewEnviron{rascunho}[1][]{%
                \ifstrempty{#1}
         375
                {\colorbox{\corleve{\cor@hlrascunho}}{\textbf{\hxdrafttitle}}}
         376
                {\normalfont{\normalfont{1}}}% \
         377
         378
                \newline%
         379
                \BODY%
         380 }%
         381 {}%
         382 \surroundwithmdframed{rascunho}%
         383 \else%
         384 \NewEnviron\{rascunho\}[1][]{}{}%
         385 \fi%
         386 %% Futuro \\
         388 %% \newcommand{\namargem}{\ed@margin{Teste}}
         389 %%
         390 %%
         391 %%
         392 %% Fazendo um todo do todonotes simples
         393 %
         394 %%\if@showtodo%
         395 \hxautor{hx@todoauthor}{orange}{TO DO}%
         396 \newcommand{\hx@todobackgroundcolor}{orange}%
         398 \newcommand{\todo}[2][comentar]{%
```

355

```
399 \IfEq{inline}{#1}%
400 {%
401 \begin{mdframed} [backgroundcolor=\hx@todobackgroundcolor]
402 #2%
403 \end{mdframed}%
404 }%
405 {%
406 \hx@todoauthor{#2}%
407 }%
408 }%
409 %%\else%
410 %%\newcommand{\todo}[2][]{}%
411 %%\fi%
412 %
```

End of Code

Change History

v4.0	$\operatorname{dar} \operatorname{problemas} \operatorname{com} \operatorname{o}$
General: Primeira versão com dtx . 1	enumerate e itemize 1
v4.0.3	v4.3.0
General: Consertando o strike	General: Comandos que riscam os
through	comentários, como profx 1
v4.1.0	v4.3.1
General: Publicar aceitando as	General: Tem espaço demais entre
mudan ças introduzidos 1	${ m marginnotes}\ { m tentando}$
v4.2.0	resolver
General: Comando todo 1	v4.3.2
v4.2.1	General: Fixing behavior of
General: Pacote paralist, herdado	rascunho, going for
de código do ed, parece inútil e	internationalization

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

$\mathbf{Symbols}$	\mathbf{A}	\Ed@note 119, 123, 128
$\$ Qbeanonymousfalse .	\addcontentsline	$\ensuremath{\verb{dQnote}}$ $122,130$
	.205,230,234,355	\Ednote 128
\@beanonymoustrue .	\addtocounter 120	\ednote 129, 159
$\dots \dots 18, 46, 54$		\ednote@label
\@empty 112	В	. 124, 126, 128, 130
\@ifpackageloaded 89,97	$\$ belowpdfbookmark . 121	\ednote@margin
\@ifundefined	\BODY 379	125, 127, 130
\dots 198, 221, 345	_	\ednotebookmarksfalse
$\mbox{\tt @modoedicaofalse}$. 32	C	6
\@modoedicaotrue 36	\cftassuntonumwidth 207	\ednotebookmarkstrue 13
\@modoedicaotrue 50 \@modopublicaraceitandofa	1se 1se	\ednotelabel 126, 157
95	111111111 200	\ednotemargin 127, 158
\@modopublicaraceitandotr	uecftcomentariorefnumwidth	\ednoteshape 107, 112
		\else 86, 112, 117,
\c 0modopublicarfalse 34	\cite 182-184	180, 208, 270,
\@modopublicartrue .	\citep 183	295, 298, 346,
	\citet 184	$358, \ 364, \ 383, \ 409$
\c 0modosubmeterfalse 33	\colorbox 152, 376	\end 403
$\mbox{\tt @modosubmetertrue}$. 37	\colorlet 149	\endcsname
\@naoanonimizarfalse 19	\cor@assunto	. 308, 313, 316,
\@naoanonimizartrue 20	138, 200, 213	321, 325, 328, 330
\@showassuntosfalse	\cor@citar 139, 363	\expandafter
$\dots \dots 26, 50, 61$	\cor@hlrascunho	. 308, 313, 316,
\@showassuntostrue .	140, 376, 377	321, 325, 328, 330
$\dots \dots $	\cor@prof 136	
\@showcomentariofalse	\cor@suavizacao 144, 145	${f F}$
	\corleve	\favorcitar 362, 365
\@showcomentariotrue	. <u>144,</u> 149, 152, 376	\fi 48, 56,
$\dots \dots 16, 44, 69$	\csname $308, 313, 316,$	59, 67, 70, 85,
\@showrascunhofalse	321, 325, 328, 330	88, 96, 112, 117,
$\dots \dots 28, 51, 63$	321, 323, 320, 330	121, 123, 185,
$\@$ showrascunhotrue .	D	212, 276, 293,
$\dots \dots 29, 43$	\DeclareOption $7-13$,	300, 301, 349,
$\0$ showsugestaofalse	16, 18, 20, 24,	$360, \ 366, \ 385, \ 411$
$\dots \dots 23, 53, 62$	27, 29, 31, 36–39	\footnotemark 114
$\@$ showsugestaotrue .		\footnotetext 111
25, 45	${f E}$	
\@showtodofalse	$\verb \ed@foot \dots \dots \underline{110}, 115$	H
	$\verb \ed@footnote 115, 121 $	\hacksxexeoversion $\underline{1}, 2$
\@showtodotrue 31, 47	\ed@margin 117, 123, 388	\hl 141, 151, 203
\@test 111, 112	\ed@mark 114, 115	\hx@anonciteptext .
\\	\ed@mark@style 113, 114	\dots 169, 172, 178

\hx@anoncitetext	\if@modopublicaraceitando	\numberline
\dots 168, 171, 177	$\dots \dots 35, 296$	$.\ \ 205,\ 230,\ 234,\ 355$
\hx @anoncitettext .	$\$ \if@modosubmeter $33, 49$	
\dots 170, 173, 179	\if@naoanonimizar 19,57	P
$\hx@comentar \dots$	\if@showassuntos 26, 193	\par 204
226, 243, 250,	\if@showcomentario .	\printhacksxexeoversion
$259, \ \ 266, \ \ 271, \ \ 291$	$\dots \dots 15, 217,$	<u>2</u>
\hx@comment 240, 274, 311	$288,\ 341,\ 350,\ 361$	\ProcessOptions 40
$\hx@commentLabeled$.	\if 0 showrascunho $28,373$	\protect
$\dots 256, 275, 314$	$\$ if Oshowsugestao $23,284$.205,230,234,355
\hx@commentref	$\$ \if \mathbb{G} show to do $30, 68, 394$	
$\dots 351, 359, 363$	\ifdef 183, 184	${f R}$
$\hx@currentcolor$	$\$ if ednote book marks .	\rascunho 373
.109,112,117,129	$\dots \dots 6, 96, 121$	\refstepcounter
$\hx@ednote \dots \dots$	\IfEq 399	$. 201, \ 241, \ 248,$
. 156, 229, 233, 354	$\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $	$257, \ \ 264, \ \ 290, \ \ 352$
\hx@ednotepre 160	\ifmarginnote 5, 85, 117	\relax 40
\hx@gensug 285, 297,	\ifmargins 4, 117	\renewcommand
$299,\ 326,\ 329,\ 331$	\ifshowednotes	$\dots 171-173, 397$
\hx @hll 148, 242, 249,	3, 83, 121, 123	\RequirePackage
$258, \ 265, \ 353, \ 377$	\ifstrempty $227, 289, 375$. 71–73, 75–80,
\hx@todoauthor 406	T	84, 85, 87, 91, 96
\hx @todobackgroundcolor	L	
\dots 396, 397, 401	\label 112 \listassunto 196, 198	${f S}$
\hx @version 1	· · · · · · · · · · · · · · · · · · ·	\sethlcolor $150, 202$
\hx@xcomment 247, 319	\listcomentario 219, 221	\setlength 207, 269, 357
$\hx@xcommentLabeled$	\listcomentarioref 343, 345	\sffamily 107
$\dots \dots 263, 322$		\slash showednotesfalse $8,10$
\hxanon 176, 181, 187	\listofassunto 210 \listofcomentario . 272	\showednotestrue $3, 7, 9$
\hxanoncite 177, 182	\listofcomentarioref	\sout 250, 266, 286
ackslashhxanoncitep	348	$\sl surroundwithmdframed$
178, 183, 188		
\h xanoncitet	M	
179, 184, 189	\marginnote 117	${f T}$
\hxassunto 200, 211, 213	\marginnotefalse 5	\textbf 376, 377
\h xautor	\marginnotetrue 12	\textcolor 112 ,
. 306, 333, 334, 395	\marginpar 117	117, 160, 286, 287
\h xdefanonciteptext 172	\marginsfalse 11	\theassunto 205
\h xdefanoncitetext . 171	\marginstrue 4	\thecomentario $230, 234$
\h xdefanoncitettext 173		\t thecomentarioref . 355
\h xdefinetodocolor . 397	N	$\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $
\hxdrafttitle 97 , 376	\namargem 388	$\verb+\todo+ \dots \dots 398, 410+$
	\NewEnviron $374,384$	
I	\newif 3-	\mathbf{X}
\if	$6,\ 15,\ 17,\ 19,\ 23,$	\xanon 187
$\$ \if@beanonymous $17,\ 175$	26, 28, 30, 32-35	\xanoncitep 188
$\footnote{1}$ \if Qmodoedicao $32,\ 41$	\newline 378	\xanoncitet 189
$\$ \if@modopublicar $34,60$	$\verb \newlistof 198, 221, 345 $	\xassunto 213