

hacksxexeo v4.4.0

Geraldo Xexéo

Saturday 29th May, 2021 - 03:04

Contents

1	Introduction	2
2	Package Options	3
2.1	Command oriented options	3
2.2	State oriented options	3
3	Version	3
4	Editorial comments	4
4.1	Creating authors	4
4.2	Available commands	5
4.2.1	Comments	5
4.3	Striked-thought comments	5
4.4	Text Modification - Suggestions	6
4.5	A tip for using comments	7
5	Draft environment	7
6	Subjects	8
7	Lists	8
8	To dos	8
9	Warnings	9
10	Comparision with other packages	9
11	Implementation	9
11.1	Access to the current version	9
11.2	Option Processing	9
11.2.1	Creating Options Variables	9

11.2.2	Portuguese Options	10
11.2.3	English Options, from ed package	10
11.2.4	Original English Options	10
11.2.5	Fixing the Super Options	11
11.3	Required Packages	11
11.4	Optional Packages	12
11.5	Color related variables	12
11.6	Il8N Almost Using Babel	12
11.7	ed inspired code	14
11.8	More for the footnote	14
11.9	The margin note	14
11.10	Anonimization	16
11.11	Subjects	16
11.12	Editorial Comments	17
11.13	Suggestions, Removes and Changes	18
11.14	Citations Needed	19
11.15	Draft	19
11.16	Powerful command to create editors and authors	20
11.17	To do notes	21
11.18	Portuguese/English, or inverse translation table	21

1 Introduction

This package supports editorial comments and gives some extra support for writing papers. It picks ideas from different packages, such as `ed`, `color-edits`, and `todonotes`, and from my practice writing papers and supervising thesis.

`hacksxexeo` was written to support my way of working, and received suggestions from my students. The starting goal was to build only a front-end to put together other packages, but with time, and the difficulty to make different packages with commands that have the same name work together, it grow in scope.

It is available as open source at <https://github.com/xexeo/hacksxexeo>. You can make suggestions using GitHub’s “Issues” feature.

As it is my first package, \TeX and \LaTeX programming is sometimes naive. However, due to the large amount of available code, and sites as StackExchange, this is not a rule. You can also use GitHub to complain about bugs.

In this document the reader will see some uses¹ of the package, since it is distributed with the `editing` option turned on. A final version, with no comments, would be used with the `publish` option.

¹`XEXÉO`: This is an exemple of using this package to make a comment with highlighted text

2 Package Options

There are two types of options. The first type enable specific commands, such as the `draft` command. They are named *command oriented options*. The second type represent a state of the text, which can be editing (a continuous state), submit, or publish, and some variations. They are named *state oriented options*. If they appear together, state oriented commands have precedence over the others. The user should avoid mixing them.

2.1 Command oriented options

<code>subjects</code>	<ul style="list-style-type: none"> • <code>subjects</code>, enables the use of <code>\subject</code>, which is proposed as a paragraph heading describing its subject;
<code>comments</code>	<ul style="list-style-type: none"> • <code>comments</code>, enables all editorial comments and the command <code>\pleasecite</code>;
<code>drafts</code>	<ul style="list-style-type: none"> • <code>drafts</code>, enables the <code>\draft</code> command;
<code>suggestions</code>	<ul style="list-style-type: none"> • <code>suggestions</code>, enables the comments defined in the suggestion section of this text.
<code>anonymize</code>	<ul style="list-style-type: none"> • <code>anonymize</code>, enables anonymization commands, and
<code>todos</code>	<ul style="list-style-type: none"> • <code>todos</code>, enables the to do family of commands.

2.2 State oriented options

<code>submit</code>	<ul style="list-style-type: none"> • <code>submit</code>, enables the submit state. Anonimization is on, subjects, comments, drafts and suggestions are off
<code>noanonymize</code>	<ul style="list-style-type: none"> • <code>noanonymize</code>, disables anonymizations even in <code>submit</code> and <code>editing</code> options
<code>publish</code>	<ul style="list-style-type: none"> • <code>publish</code>, disables all command oriented options, ignore suggestions.
<code>acceptingpublish</code>	<ul style="list-style-type: none"> • <code>acceptingpublish</code>, disable all command oriented options, accept suggestions
<code>editing</code>	<ul style="list-style-type: none"> • <code>editing</code>, enables subjects, comments, drafts and suggestions.

Users should use the `editing` state most of the time. When submitting, the `submit` state will provide a clean article, without any comments. Most of the times the article should be anonymized, but if this is not enforced, it is possible to use the options `submit` and `noanonymize` together. `publish` will never anonymize.

3 Version

It is possible that the user wants to know the version being used. We provide two commands for it.

<code>\hacksexexeoversion</code>	Provides the current version
<code>\printhacksexexeoversion</code>	Provides name and version

`\hacksxexeoversion` was used in the title of this article. The current version is v4.4.0.

If needed, the second macro prints also the name of the package:

`\printhacksxexeoversion`

will result in:

hacksxexeo v. v4.4.0

4 Editorial comments

This is the main reason of this package.

The idea is that not only users can make editorial comments on the text they are writing, but they can also establish a dialog through those comments. Visually, an editorial comment, in this package, is composed of 3 parts: an intervention in the text, a margin note indicating this intervention, and a footnote explaining it².

Xexéo:2

4.1 Creating authors

`\hxauthor` This macro creates a series of commands based on the desired base command name. The command name is, usually, the name of the author or his/her function in the work being done.

The syntax is:

`\hxautor {\langle name \rangle}{\langle color \rangle}{\langle author-name \rangle}`

Where $\langle name \rangle$ will be the base command name, which generates different commands by receiving suffixes, $\langle color \rangle$ is the color to be used by all comments and suggestions made by this author, and $\langle author-name \rangle$ is the string to be used to represent the author.

As an example, I usually declare myself as:

`\hxauthor{xexeo}{red}{Xexéo}`

And, among other commands, `\xexeo` will be defined in such a way that it generates a footnote written in red, with a indicative margin note in the same color. Both will be identified with “Xexéo”³.

The $\langle name \rangle$ and $\langle author-name \rangle$ are different to support for short command names and characters not supported in L^AT_EX commands. Therefore, if you name is *Gutenberg* you can create a family of commenting comments based on `\gut`, but use “Gutenberg” as your identifier.

²XEXÉO: This is the simplest form of an editorial note.

³XEXÉO: This is the example of the minimal use of an editorial command

Xexéo:3

`prof` Some authors are pre-defined in the style, `prof` and `cand`, to represent the
`cand` professor and the graduate candidate.

4.2 Available commands

For each user created with command name $\langle name \rangle$, such as `prof` and `cand` used as example, the following commands are created.

4.2.1 Comments

```
\<name>      \<name> [<selection>]{<footnote comment>}
\prof        \prof [<selection>]{<footnote comment>}
\cand        \cand [<selection>]{<footnote comment>}
```

These commands will make a comment in the form of a footnote⁴. It can also be used to `highlight some text`⁵.

```
\<name>r      \<name>r [<selection>]{<footnote comment>}{<label>}
\profr       \profr [<selection>]{<footnote comment>}{<label>}
\candr       \candr [<selection>]{<footnote comment>}{<label>}
```

This command will make a comment in the form of a labeled footnote⁶. It can also be used to `highlight some text`⁷. The label must be unique, since it is used as a L^AT_EX `label` too.

4.3 Striked-throught comments

After using the editorial comments for a time we started to delete the old ones that represented fixed problems. However, we notice that some comments should be kept, even if solved. The solution was to create the striked-trought comments. They are easy to use, just put an `x` after the command name.

```
\<name>x      \<name>x [<selection>]{<footnote comment>}
\prof x       \prof x [<selection>]{<footnote comment>}
\cand x       \cand x [<selection>]{<footnote comment>}
```

This command will make a comment in the form of a footnote⁸, however the comment is striked through. It can also be used to `highlight some text`⁹.

⁴~~PROF:Simplest footnote comment~~

⁵~~CAND:Comment with highlighting~~

⁶~~PROF[FIRST LABEL]:labeled footnote comment~~

⁷~~PROF[YET ANOTHER LABEL]:labeled comment with highlighting~~

⁸~~CAND:Simplest footnote comment~~

⁹~~PROF:Comment with highlighting~~

<code>\<name>rx</code>	<code>\<name>rx [<i><selection></i>]{<i><footnote comment></i>}{<i><label></i>}</code>
<code>\profrx</code>	<code>\profrx [<i><selection></i>]{<i><footnote comment></i>}{<i><label></i>}</code>
<code>\candrx</code>	<code>\candrx [<i><selection></i>]{<i><footnote comment></i>}{<i><label></i>}</code>

Prof:10
Prof:11

This command will make a comment in the form of a labeled footnote¹⁰, however the comment is striked through. It can also be used to **highlight some text**¹¹. The label must be unique, since it is used as a L^AT_EX label too.

4.4 Text Modification - Suggestions

Sometimes one of the authors wants to insert, remove or edit some text, but he or she is not sure that every one will agree, therefore he or she can make a suggestion, that will appear with his or her color.

<code>\<name>sug</code>	<code>\<name>sug[<i><comment></i>]{<i><suggested text></i>}</code>
<code>\profsug</code>	<code>\profsug[<i><comment></i>]{<i><suggested text></i>}</code>
<code>\candsug</code>	<code>\candsug[<i><comment></i>]{<i><suggested text></i>}</code>

This macro supports making a suggestion. It inserts text, using the color chosen by the author. It is also possible to make a comment, but in this command the command is the optional argument.

As example, in this paragraph the **inserted text** will appears in the red, and it is possible to **use a comment**¹².

Cand:12

<code>\<name>rem</code>	<code>\<name>rem[<i><comment></i>]{<i><suggested removal></i>}</code>
<code>\profrem</code>	<code>\profrem[<i><comment></i>]{<i><suggested removal></i>}</code>
<code>\candrem</code>	<code>\candrem[<i><comment></i>]{<i><suggested removal></i>}</code>

This macro is used to suggest removals.

This is an example **that is quite good**. Again, it is also possible to comment the **the removal**¹³ removal.

Prof:13

<code>\<name>swap</code>	<code>\<name>swap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>
<code>\profswap</code>	<code>\profswap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>
<code>\candswap</code>	<code>\candswap[<i><comment></i>]{<i><suggested removal></i>}{<i><suggested insertion></i>}</code>

This will work as the union of a removal and a suggestion. Actually, both are simplified forms of this command.

~~This should work like this.~~ This is an example of how the command should work.

¹⁰Prof[SECOND LABEL]:~~labeled footnote comment~~

¹¹Prof[NEW LABEL]:~~labeled comment with highlighting~~

¹²Cand:I want to insert this

¹³Prof:Repeated words

4.5 A tip for using comments

A student asked me to give a priority to my demands. This would make me add yet another set of commands, with more arguments. labels don't work because they must be unique to allow for being used as references.

The solution, however, is simple, special characters, such as \star , \star can be used and are highly efficient to communicate priority¹⁴.

Using other fonts, more can be accomplished. For example, package `marvosym` offers `\HollowBox`, \square , `\Checkedbox`, \boxtimes , `\CrossedBox`, \boxtimes , which can be used to indicate that something should be done, is done or will not be done.

5 Draft environment

`draft` The draft environment aims to allow writers to include text that is marked somehow as a draft. It was motivated because my students liked to hide text from me because “it was only a draft”, but I need to have some way to measure if they were advancing. Marking text as a draft allowed them to be free of the fear of showing errors to me. We could also use it while writing papers, since we are not native language speakers. I see it most as a psychological support to writing without fear of making mistakes.

This environment is evolving, looking for a good way to signal the draft status, due to the different interactions with the packages it uses and user's packages. It has one optional parameter that names the draft. Its default value is “Draft” If the `draft` option is not enabled, the text inside the title and the text inside the environment will not appear. The user should remember that some options will automatically turn on the `draft` option, such as the option `edicao`.

```
\begin{draft}[A draft title]
This is the example of a draft.
The title must be highlighted
There must be a box around it.
\end{draft}
```

```
\begin{draft}
This draft has the default title.
\end{draft}
```

A draft title
This is the example of a draft.

¹⁴`XEXEO:★★` Two stars are still low priority

The title must be highlighted
There must be a box around it.

Draft
This draft has the default title.

6 Subjects

`\hxsubject` `\hxsubject[<color>]{<text>}`

These are supposed to help organizing a text by giving a “title” for each paragraph.

Example of a subject

A subject is the main subject of a paragraph

A pink colored subject

You can use other colors, such as pink.

7 Lists

`\listofcomment` Comments, citation demands and subjects can be list with these commands.
`\listofcomment` The lists will only appear if their commands are enable (or in the all-enabling
`\listofsubject` editing option).
They are usually put in the end of the file.

8 To dos

`\todo` The `todo` command is a much simpler version than the one available in `todonotes`¹⁵. It’s syntax is:

`\todo[inline]{<text>}`

A `todo` without a `inline` option is equivalent to a comment of author “To do”. With the option, the text will appear inside an orange box, as in the example below.

This command can have other options, based on other implementations of `todo` in different packages

¹⁵`XEXEO:But it will grow in power with time`

9 Warnings

This package uses another package that changes L^AT_EX's standard behavior for summary and lists. When you use it, you must explicitly change pages with `\newpage` before `\tableofcontents` or similar commands.

10 Comparision with other packages

It is interesting to compare this package with other 3:

- `ed` has more features for commenting, and is more configurable, however it does not have colors.
- `todonotes` it does not have the identification of the commentator, which must be put by hand. It has more options too.
- `color-edits` does not support to do notes and drafts.

11 Implementation

This package was initially written in Portuguese. As it become more useful, it was translated to English. There are still some signs of this in the code.

11.1 Access to the current version

We provide some macros for the user to know the version being used.

`\hacksxexeoversion` Provides current version of hacksxexeo

```
1 \newcommand{\hacksxexeoversion}{\hx@version}%
```

`\printhacksxexeoversion` Provides package name and version

```
2 \newcommand{\printhacksxexeoversion}{hacksxexeo v. \hacksxexeoversion}%
```

11.2 Option Processing

11.2.1 Creating Options Variables

```
3 \newif\ifshowednotes\showednotestru%
4 \newif\ifmargins\marginstrue%
5 \newif\ifmarginnote\marginnotefalse%
6 \newif\ifednotebookmarks\ednotebookmarksfalse%
7 \newif\if@showcomentario\@showcomentariofalse%
8 \newif\if@naoanonimizar\@naoanonimizarfalse%
```

```

9 \newif\if@showdraft\@showdraftfalse%
10 \newif\if@showsubjects\@showsubjectsfalse%
11 \newif\if@showsgestao\@showsgestaofalse%
12 \newif\if@beanonymous\@beanonymousfalse%
13 \newif\if@showtodo\@showtodofalse%
14 \newif\if@modoedicao\@modoedicaofalse%
15 \newif\if@modosubmeter\@modosubmeterfalse%
16 \newif\if@modopublicar\@modopublicarfalso%
17 \newif\if@modopublicaraceitando\@modopublicaraceitandofalse%

```

11.2.2 Portuguese Options

```

18 \DeclareOption{rascunhos}{\@showdrafttrue}
19 \DeclareOption{comentarios}{\@showcomentariottrue}
20 \DeclareOption{anonimizar}{\@beanonymoustrue}
21 \DeclareOption{naoanonimizar}{\@naoanonimizartrue}
22 \DeclareOption{sugestoes}{\@showsgestaottrue}
23 \DeclareOption{assuntos}{\@showsubjectstrue}
24 \DeclareOption{edicao}{\@modoedicaottrue}
25 \DeclareOption{submeter}{\@modosubmetertrue}
26 \DeclareOption{publicar}{\@modopublicartrue}
27 \DeclareOption{publicaraceitando}{\@modopublicartrue
28     \@modopublicartrue
29     \@modopublicaraceitandottrue
30 }

```

11.2.3 English Options, from ed package

```

31 \DeclareOption{show}{\showednotesttrue\message{ed.sty: showing ednotes}}
32 \DeclareOption{hide}{\showednotesfalse\message{ed.sty: hiding ednotes}}
33 \DeclareOption{draft}{\showednotesttrue\message{ed.sty: showing ednotes}}
34 \DeclareOption{final}{\showednotesfalse\message{ed.sty: hiding ednotes}}
35 \DeclareOption{nomargins}{\marginsfalse}
36 \DeclareOption{marginnote}{\marginnotetrue}
37 \DeclareOption{pdfbookmarks}{\ednotebookmarkstrue}

```

11.2.4 Original English Options

```

38 \DeclareOption{comments}{\@showcomentariottrue}
39 \DeclareOption{anonimize}{\@beanonymoustrue}
40 \DeclareOption{noanonimize}{\@naoanonimizartrue}
41 \DeclareOption{suggestions}{\@showsgestaottrue}
42 \DeclareOption{subjects}{\@showsubjectstrue}
43 \DeclareOption{drafts}{\@showdrafttrue}
44 \DeclareOption{todos}{\@showtodottrue}
45 \DeclareOption{editing}{\@modoedicaottrue}
46 \DeclareOption{submit}{\@modosubmetertrue}
47 \DeclareOption{publish}{\@modopublicartrue}
48 \DeclareOption{acceptingpublish}{\@modopublicartrue
49     \@modopublicartrue
50     \@modopublicaraceitandottrue

```

```

51 }
52 \ProcessOptions\relax

```

11.2.5 Fixing the Super Options

```

53 \if@modoedicao
54 \@showsobjectstrue
55 \@showdrafttrue
56 \@showcomentariottrue
57 \@showsugestaotrue
58 \@beanonymoustrue
59 \@showtodottrue
60 \fi
61 \if@modosubmeter
62 \@showsobjectsfalse
63 \@showdraftfalse
64 \@showcomentariofalse
65 \@showsugestaofalse
66 \@beanonymoustrue
67 \@showtodofalse
68 \fi
69 \if@naoanonimizar
70 \@beanonymousfalse
71 \fi
72 \if@modopublicar
73 \@showsobjectsfalse
74 \@showsugestaofalse
75 \@showdraftfalse
76 \@showcomentariofalse
77 \@beanonymousfalse
78 \@showtodofalse
79 \fi%
80 \if@showtodo
81 \@showcomentariottrue
82 \fi

```

11.3 Required Packages

Packages that are always required

- xcolor - used to support colors
- soulutf8 - this is a variation of soul, used for highlighting
- ulem - used to support strikethrough¹⁶

```

83 \RequirePackage{xcolor}
84 \RequirePackage{soulutf8}
85 \RequirePackage[normalem]{ulem}
86 \RequirePackage{tocloft}

```

¹⁶To do: I must complete this explanation list

```

87 \RequirePackage{etoolbox}
88 \RequirePackage{environ}
89 \RequirePackage{xstring}
90 \RequirePackage{csquotes}
91 \RequirePackage{mdframed}

```

11.4 Optional Packages

Package that are required only sometimes

```

92 \ifshowednotes%
93 \ifmarginnote%
94 \RequirePackage{marginnote}%
95 \fi%
96 \else%
97 \RequirePackage{verbatim}%
98 \fi%

```

Checking if babel is loaded, use iflang

```

99 \@ifpackageloaded{babel}%
100 {% \message{Babel Loaded!}%
101     \RequirePackage{iflang}%
102 }{%
103     \message{Babel not detected!}%
104 }%

105 % |hyperref| must always be the last
106 \ifednotebookmarks\RequirePackage{hyperref}\fi

```

11.5 Color related variables

```

107 \newcommand{\cor@prof}{red}%
108 \newcommand{\cor@cand}{blue}%
109 \newcommand{\cor@subject}{green}%
110 \newcommand{\cor@citar}{purple}%
111 \newcommand{\cor@hldraft}{yellow}%

```

11.6 I18N Almost Using Babel

We can detect if babel is enable and allow for some languages. If you want to use another language, you must set new values for the command `\hxdrafttitle`. I really thought that it was possible to do something smarter with babel, for example using `\setlocalecaption`, but no attempt worked out was I wanted.

There are some packages, as `translator` that can be useful but up to now this seems to be the easiest way of doing it.

The advantage of this way is that any user can `\renewcommand{\hxdrafttitle}{some text}`.

```

112 \def\hxdrafttitle{Standard Draft}%
113 \def\hxcommentstitle{Standard List of Comments}%
114 \def\hxsubjtitle{Standard List of Subjects}%
115 \def\hxcitationstitle{Standard List of Citation Needs}%
116 \def\hxpleasecitetext{Plese cite}
117 \def\hxpleasecitemessage{something to support this information}
118 \def\hxpleasecitemarginnote{Cite}%
119 %
120 \@ifpackageloaded{babel}%
121 {%
122     \IfLanguageName{brazilian}%
123     {%
124         \def\hxdrafttitle{draft}%
125         \def\hxcommentstitle{Lista de Comentários}%
126         \def\hxsubjtitle{Lista de Assuntos}%
127         \def\hxcitationstitle{Necessidades de Citação}%
128         \def\hxpleasecitetext{Favor citar}%
129         \def\hxpleasecitemessage{alguma coisa que suporte este texto}%
130         \def\hxpleasecitemarginnote{Citar}%
131     }{}%
132 %
133     \IfLanguageName{portuguese}%
134     {%
135         \def\hxdrafttitle{draft}%
136         \def\hxcommentstitle{Lista de Comentários}%
137         \def\hxsubjtitle{Lista de Assuntos}%
138         \def\hxcitationstitle{Necessidades de Citação}%
139         \def\hxpleasecitetext{Favor citar}%
140         \def\hxpleasecitemessage{alguma coisa que suporte este texto}%
141         \def\hxpleasecitemarginnote{Citar}%
142     }{}%
143 %
144     \IfLanguageName{english}%
145     {%
146         \def\hxdrafttitle{Draft}%
147         \def\hxcommentstitle{List of Comments}%
148         \def\hxsubjtitle{List of Subjects}%
149         \def\hxcitationstitle{List of Citation Needs}%
150         \def\hxpleasecitetext{Plese cite}
151         \def\hxpleasecitemessage{something to support this information}
152         \def\hxpleasecitemarginnote{Cite}%
153     }{}%
154 }%
155 {}%

```

11.7 ed inspired code

This code, inspired in the `ed` package, makes the basic mechanism for inserting comments as footnotes with an observation in the margin. As an addition to `ed`, it support colors.

Setting up the counter

```
156 \newcounter{hxnote}%
```

Format for the text

```
157 \newcommand\hx@noteshape{\sffamily}%
```

Defining the variable that holds the color to be printed. `soul` made it quite complex, global variable is not the best programming technique, but it works.

footnote indicador e rótulo

`\hx@foot` This macro really creates a footnote. It uses counter `hxnote` in arabic. It prints the footnote using the currently defined color (That is a global variable, setted up elsewhere. This is not good programming practice, but it turned out to be the easiest way of doing it in L^AT_EX without more and more arguments.)

Syntax: `\hx@foot{<footnote-text>}{<author-name>}{<label>}`

```
158 \newcommand\hx@foot[3]%
159 {\def\@test{#3}\footnotetext[\arabic{hxnote}]}%
160 {\scshape\textcolor{\hx@currentcolor}{#2}}%
161 \if\@test\@empty\else\label{ed:#3}\textcolor{\hx@currentcolor}{[#3]}%
162 \fi\textcolor{\hx@currentcolor}{:}}%
163 \hx@noteshape\textcolor{\hx@currentcolor}{#1}}%
```

11.8 More for the footnote

`\hx@footnote` This macro actually makes the footnote mark and text

```
164 \def\hx@mark@style#1{#1}%
165 \newcommand\hx@mark[1]{\hx@mark@style{\footnotemark[#1]}}%
166 \newcommand\hx@footnote[3]{\hx@mark{\arabic{hxnote}}\hx@foot{#1}{#2}{#3}}%
```

11.9 The margin note

```
167 \newcommand\hx@margin[1]{%
168 \ifmargins%
169 \ifmarginnote%
170 \marginnote{%
171 \textcolor{\hx@currentcolor}{#1}}%
172 \else%
```

```

173 \marginpar{\textcolor{\hx@currentcolor}{#1}}%
174 \fi%
175 \fi}%

\Hx@note Basic function to build the note

176 \newcommand\Hx@note[3]% text, type, label
177 {\addtocounter{hxnote}{1}%
178 \ifshowednotes%
179 \hx@footnote{#1}{#2}{#3}%
180 \ifednotebookmarks%
181 \belowpdfbookmark{#2: #1}{#2.\thehxnote}%
182 \fi
183 \fi}%

More functions for doing the editorial note

184 \newcommand\hx@note[4]% text, type, label, margin
185 {\Hx@note{#1}{#2}{#3}%
186 \ifshowednotes\hx@margin{#4:\arabic{hxnote}}}%
187 \fi}%
188 \newcommand\hxnote@label{Editor}%
189 \newcommand\hxnote@margin{Ed}%
190 \newcommand\hxnotelabel[1]{\def\hxnote@label{#1}}%
191 \newcommand\hxnotemargin[1]{\def\hxnote@margin{#1}}%
192 \newcommand{\Hxnote}[2][\def\Hx@note{#2}\hxnote@label{#1}}%
193 %
194 \newcommand{\hxnote}[3][\def%
195 \def\hx@currentcolor{#3}%
196 \hx@note{#2}%
197 \hxnote@label{#1}%
198 \hxnote@margin}%
199}%
200 %%%https://tex.stackexchange.com/questions/30483/how-can-i-check-in-latex-or-plain-tex-whether-
201 %% as opções comentario, assuntos e anonimizar
202 %% CORES

\corleve Make a color lighter for later use in highlightings This code is more complex than it
shuould be because o soulutf8's package \hl behavior. Solution found in: https://tex.stackexchange.com/questions/410295/soul-color-transparency

203 \newcommand{\cor@suavizacao}{40}%
204 \newcommand{\corleve}[1]{#1!\cor@suavizacao!white}

\hx@hl1 Light highlight makes a \hl that is lighter

205 \newcommand{\hx@hl1}[2]% % Depedendo do soulutf8
206 {\colorlet{x@coraqui}{\corleve{#1}}%
207 \sethlcolor{x@coraqui}%
208 \hl{#2}%
209}%

```

Isolating hxnote

```
210 %% rótulo texto cor indicador
211 \newcommand{\hx@hxnote}[4][]{%
212 \hxnotelabel{#4}%
213 \hxnotemargin{#4}%
214 \hxnote[#1]{#2}{#3}%
215 }%
```

11.10 Anonimization

Will write anonymous or cite anonymous. The user has a way to configure the citation as he or she wants.

```
\hx@anoncitetext Default values for anonymous citation.
\hx@anonciteptext
\hx@anoncitetttext 216 \newcommand{\hx@anoncitetext}{(Anonymous, Year)}%
217 \newcommand{\hx@anonciteptext}{(Anonymous, Year)}%
218 \newcommand{\hx@anoncitetttext}{Anonymous (Year)}%

\hxdefanoncitetext These macros allow to define how anonymous citations will appear is anonymous
\hxdefanonciteptext mode is activated. For exemplo, one can change all the citation formats to [0].
\hxdefanoncitetttext 219 \newcommand{\hxdefanoncitetext}[1]{\renewcommand{\hx@anoncitetext}{#1}}%
220 \newcommand{\hxdefanonciteptext}[1]{\renewcommand{\hx@anonciteptext}{#1}}
221 \newcommand{\hxdefanoncitetttext}[1]{\renewcommand{\hx@anoncitetttext}{#1}}%

222 \if@beanonymous
223 \newcommand{\hxanon}[1]{Anonymous}%
224 \newcommand{\hxanoncite}[2][]{\hx@anoncitetext}%
225 \newcommand{\hxanoncitep}[2][]{\hx@anonciteptext}%
226 \newcommand{\hxanoncitet}[2][]{\hx@anoncitetttext}%
227 \else
228 \newcommand{\hxanon}[1]{#1}%
229 \newcommand{\hxanoncite}[2][]{\cite{#1}{#2}}%
230 \ifdef{\citep}{\newcommand{\hxanoncitep}[2][]{\citep{#1}{#2}}{\newcommand{\hxanoncitep}[2][]{\
231 \ifdef{\citet}{\newcommand{\hxanoncitet}[2][]{\citet{#1}{#2}}{\newcommand{\hxanoncitet}[2][]{\
232 \fi|
233 %% retrocompatibilidade
234 \newcommand{\xanon}[2][]{\hxanon{#1}{#2}}%
235 \newcommand{\xanoncitep}[2][]{\hxanoncitep{#1}{#2}}%
236 \newcommand{\xanoncitet}[2][]{\hxanoncitet{#1}{#2}}%
```

11.11 Subjects

The idea of subjects is to have one subject for each paragraph. Currently is just a list of subjects and a highlight.


```

237 \if@showsubjects
238 \newcommand{\listsubject}{\hxsubjtitle}%
239 %% cria a lista, depende do pacote tcloft
240 \@ifundefined{chapter}
241 {\newlistof[section]{subject}{aaa}{\listsubject}}
242 {\newlistof[chapter]{subject}{aaa}{\listsubject}}%
243 %%
244 \newcommand{\hxsubject}[2][\cor@subject]{%
245 \refstepcounter{subject}%
246 \sethlcolor{#1}%
247 \hl{#2}%
248 \par%
249 \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}{#2}}%
250 }%
251 \setlength{\cftsubjectnumwidth}{2.5em}%
252 \else%
253 \newcommand{\listofsubject}{}%
254 \newcommand{\hxsubject}[2][{}]{%
255 \fi%

```

11.12 Editorial Comments

The main subject of this package

```

256 \if@showcomentario
257 %% Resolve a lista de comentários
258 \newcommand{\listcomentario}{\hxcommentstitle}%
259 %% cria a lista
260 \@ifundefined{chapter}
261 {\newlistof[section]{comentario}{ccc}{\listcomentario}}
262 {\newlistof[chapter]{comentario}{ccc}{\listcomentario}}%
263 %%
264 %% Comentador genérico - parte I
265 %% faz o hxnote e soma na lista
266 %% []rótulo], texto , cor, indicador
267 \newcommand{\hx@comentar}[4][{}]{%
268 \ifstrempy{#4}{%
269 % rótulo texto cor indicador
270 \hx@hxnote[#1]{#2}{#3}{Comentário}% faz a nota de rodapé do ed
271 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}}%
272 }%
273 {%
274 \hx@hxnote[#1]{#2}{#3}{#4}%
275 \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}}%
276 }%
277 }%
278 %% comentador genérico, parte II
279 %% faz o highlight , soma o step e comenta
280 %% [texto hl] footnote cor indicator

```

```

281 \newcommand{\hx@comment}[4][]{%
282 \refstepcounter{comentario}% soma um ao contador
283 \hx@hll{#3}{#1}% ver subfunção de impressão com hl
284 \hx@comentar{#2}{#3}{#4}%
285 }%
286 %%
287 %%
288 \newcommand{\hx@xcomment}[4][]{%
289 \refstepcounter{comentario}% soma um ao contador
290 \hx@hll{#3}{#1}% ver subfunção de impressão com hl
291 \hx@comentar{\sout{#2}}{#3}{#4}%
292 }%
293 %%
294 %%
295 %% comentador genérico com rótulo
296 %% [texto hl] footnote cor indicator rótulo
297 \newcommand{\hx@commentLabeled}[5][]{%
298 \refstepcounter{comentario}%
299 \hx@hll{#3}{#1}%
300 \hx@comentar[#5]{#2}{#3}{#4}%
301 }%
302 %%
303 %% [texto hl] footnote cor indicator rótulo
304 \newcommand{\hx@xcommentLabeled}[5][]{%
305 \refstepcounter{comentario}%
306 \hx@hll{#3}{#1}%
307 \hx@comentar[#5]{\sout{#2}}{#3}{#4}%
308 }%
309 %%
310 \setlength{\cftcomentariounumwidth}{2.5em}
311 \else
312 \newcommand{\hx@comentar}[4][]{}%
313 \newcommand{\listofcomentario}{}%
314 %% não pode perder o texto comentado
315 \newcommand{\hx@comment}[4][]{#1}%
316 \newcommand{\hx@commentLabeled}[5][]{#1}%
317 \fi%

```

11.13 Suggestions, Removes and Changes

```

318 %% comentário, cor, indicador, textovelho, cor velho, textonovo, cor novo
319 %% Em modo publicar coloca o textovelho
320 \if@showsgestao
321 \newcommand{\hx@gensug}[7][Uma proposta]{%
322 \textcolor{#5}{\sout{#4}}% CORRIGINDO AQUI
323 \textcolor{#7}{#6}%
324 \if@showcomentario%
325 \ifstrempy{#1}{}%
326 {\refstepcounter{comentario}%

```

```

327 \hx@comentar{#1}{#2}{#3}%% [rótulo], cor , footnote , indicador
328 }%
329 \fi%
330 }%% [rótulo], cor , footnote , indicador
331 \else%
332 \if@modopublicaraceitando
333 \newcommand{\hx@gensug}[7][]{#6}%
334 \else%
335 \newcommand{\hx@gensug}[7][]{#4}%
336 \fi%
337 \fi%

```

11.14 Citations Needed

One common error of students is not to cite correctly. Citation errors are so common that I decided to provide the option to have an optional list just for them. They are enable together with commentaries, users can use them or not.

```

338 \if@showcomentario%
339 \newcommand{\listcomentarioref}{\hxcitationstitle}%
340 \ifundefined{chapter}{\newlistof[section]{comentarioref}{ccr}{\listcomentarioref}}{\newlistof
341 \else%
342 \newcommand{\listofcomentarioref}{}%
343 \fi%
344 \if@showcomentario%
345 \newcommand{\hx@commentref}[3][]{%
346 \refstepcounter{comentarioref}%
347 \hx@hll{#3}{#1}%
348 \hx@hxnote{#2}{#3}{\hxpleasecitmarginnote}%
349 \addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}%
350 }%
351 \setlength{\cftcomentariorefnwidth}{2.5em}%
352 \else%
353 \newcommand{\hx@commentref}[3]{}%
354 \fi%
355 \if@showcomentario
356 \newcommand{\favorcitar}[1]{\hxpleasecitmessage}{%
357 \hx@commentref{\hxpleasecittext\ #1}{\cor@citar}}%
358 \else%
359 \newcommand{\favorcitar}[1]{}%
360 \fi%

```

11.15 Draft

draft This macro creates a boxed text, with title used as a first parameter It uses package `mdframed` to create the frame. If draft is turned off as an option, it supress everything inside the body. Due to problems with soul accepting `\hxdrafttitle` we use `\colorbox` to support multiple languages if default title is used

```

361 \if@showdraft%
362 \NewEnviron{draft}[1][]{%
363 \ifstrempy{#1}%
364 {\colorbox{\corleve{\cor@hldraft}}{\textbf{\hxdrafttitle}}}%
365 {\hx@hll{\cor@hldraft}{\textbf{#1}}}%
366 \newline%
367 \BODY%
368 }%
369 {}%
370 \surroundwithmdframed{draft}%
371 \else%
372 \NewEnviron{draft}[1][]{\{}%
373 \fi%

```

11.16 Powerful command to create editors and authors

This allows for many types of comments. This was the reason I started using a front-end to `ed`, and later decided to use colors, that `ed` does not support. If I had known of `color-edits`, maybe this package was never done. I actually implemented the same functionalities without knowing about that package. One day, looking for other editorial packages that used editorial symbols, I found `color-edits`, but it was too late, I was already hooked on L^AT_EX programming addiction. nome do autor, cor, identificador

`\hxautor`

```

374 \newcommand{\hxautor}[3]{%
375 %% hxcomment - texto a hl, cor, comentário, indicador de pessoa
376 \expandafter\newcommand\csname#1\endcsname[2][]{%
377 {%
378 \hx@comment[##1]{##2}{#2}{#3}}%
379 % [texto a marcar], cor , comentário, palavra, rótulo
380 \expandafter\newcommand\csname#1r\endcsname[3][]{%
381 {\hx@commentLabeled[##1]{##2}{#2}{#3}{##3}}%
382 %% cortados
383 \expandafter\newcommand\csname#1x\endcsname[2][]{%
384 {%
385 %% Comentários
386 \hx@xcomment[##1]{##2}{#2}{#3}}%
387 % [texto a marcar], cor , comentário, palavra, rótulo
388 \expandafter\newcommand\csname#1rx\endcsname[3][]{%
389 {\hx@xcommentLabeled[##1]{##2}{#2}{#3}{##3}}%
390 %% sugestões
391 \expandafter\newcommand\csname#1sug\endcsname[2][]{%
392 {\hx@gensug[##1]{#2}{#3}{#2}{##2}{#2}}%
393 \expandafter\newcommand\csname#1rem\endcsname[2][]{%
394 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{#2}}%
395 \expandafter\newcommand\csname#1troca\endcsname[3][]{%

```

```

396 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
397 \expandafter\newcommand\csname#1swap\endcsname[3][]%
398 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
399 }%
400 \hxautor{prof}{red}{Prof}
401 \hxautor{cand}{blue}{Cand}

```

11.17 To do notes

This was developed because some of my students started a text using `todonotes`, before being aware of my package, therefore I need to have some compatibility to make de change. With time it became useful and I will try to make something better in the future.

`\todo` Fazendo um todo do `todonotes` simples.

If option `inline` is not used, it is only a front-end to an editorial comment for a user called “To do”. If it is used, it tries to simulate the simplest behavior of `todonotes` package. In the future this can be enhanced, since package `mdframe` is very powerful. If the non-inline version is used, the to do note will not appear in the List of Commentaries.

```

402 \hxautor{hx@todoauthor}{orange}{To do}%
403 \newcommand{\hx@todobackgroundcolor}{orange}%
404 \newcommand{\todo}[2][comentar]{%
405 \IfEq{inline}{#1}%
406 {%
407 \begin{mdframed}[backgroundcolor=\hx@todobackgroundcolor]
408 #2%
409 \end{mdframed}%
410 }%
411 {%
412 \hx@todoauthor{#2}%
413 }%
414 }%

```

`\hxdefinetodocolor` Allows the definition of a background color for todo notes.

```

415 \newcommand{\hxdefinetodocolor}[1]{\renewcommand{\hx@todobackgroundcolor}{#1}}%

```

11.18 Portuguese/English, or inverse translation table

These next lines of code made easy to convert this package to English, because it was written in Portuguese, for Brazilian researchers. Some commands were rewritten in English with time, such as `rascunho`, but the Portuguese version will always be maintained, while other were translated using only his mechanism.

```
416 \let\rascunho=\draft%
417 \let\hxassunto=\hxsubject%
418 \let\pleasecite=\favorcitar%
419 \let\hxauthor=\hxautor%
420 \let\listofcomments=\listofcomentario%
421 \let\listofcitationneeds=\listofcomentarioref%
422 \let\listofassunto=\listofsubject%
```

End of Code

Change History

v4.0	dar problemas com o	
General: Primeira versão com dtx .	enumerate e itemize	1
v4.0.3	v4.3.0	
General: Consertando o strike	General: Comandos que riscam os	
through	comentários, como profx	1
v4.1.0	v4.3.1	
General: Publicar aceitando as	General: Tem espaço demais entre	
mudanças introduzidos	marginnotes... tentando	
v4.2.0	resolver	1
General: Comando todo	v4.3.2	
v4.2.1	General: Fixing behavior of draft,	
General: Pacote paralist, herdado	going for internationalization . .	1
de código do ed, parece inútil e	v4.4.0	
	General: First version in English .	1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	<code>\@showtodot</code> true .. 44, 59	E
<code>\@beanonymousfalse</code> 12, 70, 77	<code>\@test</code> 159, 161	<code>\ednotebookmarksfalse</code> 6
<code>\@beanonymoustrue</code> 20, 39, 58, 66	<code>_</code> 357	<code>\ednotebookmarkstrue</code> 37
<code>\@empty</code> 161	A	<code>\else</code> 96, 161, 172, 227, 252, 311, 331, 334, 341, 352, 358, 371
<code>\@ifpackageloaded</code> 99, 120	<code>\addcontentsline</code> 249, 271, 275, 349	<code>\end</code> 409
<code>\@ifundefined</code> 240, 260, 340	<code>\addtocounter</code> 177	<code>\endcsname</code> ... 376, 380, 383, 388, 391, 393, 395, 397
<code>\@modoedicaofalse</code> . 14	B	environments:
<code>\@modoedicaotru</code> 24, 45	<code>\belowpdfbookmark</code> . 181	<code>draft</code> <u>361</u>
<code>\@modopublicaraceitandofalse</code> 17	<code>\BODY</code> 367	<code>\expandafter</code> .. 376, 380, 383, 388, 391, 393, 395, 397
<code>\@modopublicaraceitandotru</code> 29, 50	C	F
<code>\@modopublicarf</code> 16	<code>\cftcomentarionumwidth</code> 310	<code>\favorcitar</code> 356, 359, 418
<code>\@modopublicartr</code> 26, 28, 47, 49	<code>\cftcomentariorefnumwidth</code> 351	<code>\fi</code> .. 60, 68, 71, 79, 82, 95, 98, 106, 162, 174, 175, 182, 183, 187, 232, 255, 317, 329, 336, 337, 343, 354, 360, 373
<code>\@modosubmeterfalse</code> 15	<code>\cftsubjectnumwidth</code> 251	<code>\footnotemark</code> 165
<code>\@modosubmetertr</code> 25, 46	<code>\cite</code> 229–231	<code>\footnotetext</code> 159
<code>\@naoanonimizarf</code> 8	<code>\citep</code> 230	H
<code>\@naoanonimizartr</code> 21, 40	<code>\citet</code> 231	<code>\hacksxexeoversion</code> <u>1</u> , 2
<code>\@showcomentariof</code> 7, 64, 76	<code>\colorbox</code> 364	<code>\hl</code> 208, 247
<code>\@showcomentariotr</code> 19, 38, 56, 81	<code>\colorlet</code> 206	<code>\hx@anonciteptext</code> <u>216</u> , 220, 225
<code>\@showdraftfalse</code> 9, 63, 75	<code>\cor@cand</code> 108	<code>\hx@anoncitetext</code> <u>216</u> , 219, 224
<code>\@showdrafttr</code> 18, 43, 55	<code>\cor@citar</code> ... 110, 357	<code>\hx@anoncitetttext</code> <u>216</u> , 221, 226
<code>\@showsubjectsfalse</code> 10, 62, 73	<code>\cor@hldraft</code> 111, 364, 365	<code>\hx@comentar</code> 267, 284, 291, 300, 307, 312, 327
<code>\@showsubjectstr</code> 23, 42, 54	<code>\cor@prof</code> 107	<code>\hx@comment</code> 281, 315, 378
<code>\@showsugestaofalse</code> 11, 65, 74	<code>\cor@suavizacao</code> 203, 204	
<code>\@showsugestaostr</code> 22, 41, 57	<code>\cor@subject</code> .. 109, 244	
<code>\@showtodofalse</code> 13, 67, 78	<code>\corleve</code> .. <u>203</u> , 206, 364	
	<code>\csname</code> 376, 380, 383, 388, 391, 393, 395, 397	
	D	
	<code>\DeclareOption</code> 18–27, 31–48	
	<code>\draft</code> 416	
	<code>draft (environment)</code> . <u>361</u>	

\hx@commentLabeled .	\hxnote 194, 214	\listcomentario . . .
. 297, 316, 381	\hxnote@label 258, 261, 262
\hx@commentref 188, 190, 192, 197	\listcomentarioref .
. 345, 353, 357	\hxnote@margin 339, 340
\hx@currentcolor 189, 191, 198	\listofassunto 422
. 160–	\hxnotelabel . . 190, 212	\listofcitationneeds
163, 171, 173, 195	\hxnotemargin . 191, 213 421
\hx@foot 158, 166	\hxpleasecitmarginnote	\listofcomentario .
\hx@footnote . . 164, 179 118, 313, 420
\hx@gensug	130, 141, 152, 348	\listofcomentarioref
. 321, 333, 335,	\hxpleasecitmessage 342, 421
392, 394, 396, 398 117,	\listofcomments . . . 420
\hx@hll 205, 283, 290,	129, 140, 151, 356	\listofsubject 253, 422
299, 306, 347, 365	\hxpleasecitetext .	\listsubject
\hx@hxnote 116, 238, 241, 242
. 211, 270, 274, 348	128, 139, 150, 357	
\hx@margin . . . 167, 186	\hxsubject 244, 254, 417	M
\hx@mark 165, 166	\hxsubjtitle . . 114,	\marginnote 170
\hx@mark@style 164, 165	126, 137, 148, 238	\marginnotefalse . . . 5
\Hx@note . . 176, 185, 192		\marginnotetrue . . . 36
\hx@note 184, 196	I	\marginpar 173
\hx@noteshape . 157, 163	\if 161	\marginsfalse 35
\hx@todoauthor 412	\if@beanonymous 12, 222	\marginstrue 4
\hx@todobackgroundcolor	\if@modoedicao . . 14, 53	
. 403, 407, 415	\if@modopublicar 16, 72	N
\hx@version 1	\if@modopublicaraceitando	\NewEnviron . . . 362, 372
\hx@xcomment . . . 288, 386 17, 332	\newif 3–17
\hx@xcommentLabeled	\if@modosubmeter 15, 61	\newline 366
. 304, 389	\if@naoanonimizar 8, 69	\newlistof . . . 241,
\hxanon . . . 223, 228, 234	\if@showcomentario .	242, 261, 262, 340
\hxanoncite . . . 224, 229 7, 256,	\numberline
\hxanoncitep	324, 338, 344, 355 249, 271, 275, 349
. 225, 230, 235	\if@showdraft . . . 9, 361	
\hxanoncitet	\if@showsubjects 10, 237	P
. 226, 231, 236	\if@showsgestao 11, 320	\par 248
\hxassunto 417	\if@showtodo . . . 13, 80	\pleasecite 418
\hxauthor 419	\ifdef 230, 231	\printhacksxeover
\hxautor . . 374, 402, 419	\ifednotebookmarks 2
\hxcitationstitle 6, 106, 180	\ProcessOptions . . . 52
. 115,	\IfEq 405	\protect
127, 138, 149, 339	\IfLanguageName 249, 271, 275, 349
\hxcommentstitle 113, 122, 133, 144	
125, 136, 147, 258	\ifmarginnote 5, 93, 169	R
\hxdefanonciteptext 219	\ifmargins 4, 168	\rascunho 416
\hxdefanoncitetext . 219	\ifshowednotes	\refstepcounter . . .
\hxdefanoncitetttext 219 3, 92, 178, 186 245, 282, 289,
\hxdefinetodocolor . 415	\ifstrempty 268, 325, 363	298, 305, 326, 346
\hxdrafttitle . 112,		\relax 52
124, 135, 146, 364	L	\renewcommand
\Hxnote 192	\label 161 219–221, 415

<code>\RequirePackage</code>	83–	<code>\sout</code>	291, 307, 322	<code>\thecomentarioref</code>	349
	91, 94, 97, 101, 106	<code>\surroundwithmdframed</code>		<code>\thehxnote</code>	181
S			370	<code>\thesubject</code>	249
<code>\sethlcolor</code>	207, 246	T		<code>\todo</code>	<u>402</u>
<code>\setlength</code>	251, 310, 351				
<code>\sffamily</code>	157	<code>\textbf</code>	364, 365	X	
<code>\showednotesfalse</code>	32, 34	<code>\textcolor</code>	160–163,	<code>\xanon</code>	234
<code>\showednotestru</code>	..		171, 173, 322, 323	<code>\xanonicitep</code>	235
	3, 31, 33	<code>\thecomentario</code>	271, 275	<code>\xanonicitet</code>	236

List of Comments

1.1	Xexéo: This is an exemple of using this package to make a comment with highlighted text	2
4.1	Xexéo: This is the simplest form of an editorial note.	4
4.2	Xexéo: This is the example of the minimal use of an editorial command	4
4.3	Prof: Simplest footnote comment	5
4.4	Cand: Comment with highlighting	5
4.5	Prof: labeled footnote comment	5
4.6	Prof: labeled comment with highlighting	5
4.7	Cand: Simplest footnote comment	5
4.8	Prof: Comment with highlighting	5
4.9	Prof: labeled footnote comment	6
4.10	Prof: labeled comment with highlighting	6
4.11	Cand: I want to insert this	6
4.12	Prof: Repeated words	6
4.13	Xexéo: ★★ Two stars are still low priority	7
8.1	Xexéo: But it will grow in power with time	8
11.1	To do: I must complete this explanation list	11

List of Citation Needs

List of Subjects

6.1	Example of a subject	8
6.2	A pink colored subject	8