

# hacksxexeo v4.4.0

Geraldo Xexéo

Friday 28<sup>th</sup> May, 2021 - 22:39

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Package Options</b>	<b>3</b>
2.1	Command oriented options . . . . .	3
2.2	State oriented options . . . . .	3
<b>3</b>	<b>Version</b>	<b>3</b>
<b>4</b>	<b>Editorial comments</b>	<b>4</b>
4.1	Creating authors . . . . .	4
4.2	Available commands . . . . .	5
4.2.1	Comments . . . . .	5
4.3	Striked-throught comments . . . . .	5
4.4	Text Modification - Suggestions . . . . .	6
4.5	A tip for using comments . . . . .	7
<b>5</b>	<b>Draft environment</b>	<b>7</b>
<b>6</b>	<b>Subjects</b>	<b>8</b>
<b>7</b>	<b>Lists</b>	<b>8</b>
<b>8</b>	<b>Warnings</b>	<b>8</b>
<b>9</b>	<b>Comparision with other packages</b>	<b>8</b>
<b>10</b>	<b>Implementation</b>	<b>9</b>
10.1	Access to the current version . . . . .	9
10.2	Option Processing . . . . .	9
10.2.1	Creating Options Variables . . . . .	9
10.2.2	Portuguese Options . . . . .	9
10.2.3	English Options, from ed package . . . . .	10

10.2.4	Original English Options . . . . .	10
10.2.5	Fixing the Super Options . . . . .	10
10.3	Required Packages . . . . .	11
10.4	Optional Packages . . . . .	11
10.5	Color related variables . . . . .	12
10.6	Il8N Almost Using Babel . . . . .	12
10.7	ed inspired code . . . . .	13
10.8	More for the footnote . . . . .	14
10.9	The margin note . . . . .	14
10.10	Anonimization . . . . .	15
10.11	Subjects . . . . .	16
10.12	Editorial Comments . . . . .	16
10.13	Suggestions, Removes and Changes . . . . .	17
10.14	Citations Needed . . . . .	18
10.15	Draft . . . . .	19
10.16	Powerful command to create editors and authors . . . . .	19
10.17	To do notes . . . . .	20
10.18	Portuguese/English, or inverse translation table . . . . .	21

## 1 Introduction

This package supports editorial comments and gives some extra support for writing papers. It picks ideas from different packages, such as `ed`, `color-edits`, and `todonotes`, and from my practice writing papers and supervising thesis.

`hacksxexeo` was written to support my way of working, and received suggestions from my students. The starting goal was to build only a front-end to put together other packages, but with time, and the difficulty to make different packages with commands that have the same name work together, it grew in scope.

It is available as open source at <https://github.com/xexeo/hacksxexeo>. You can make suggestions using GitHub’s “Issues” feature.

As it is my first package,  $\text{\TeX}$  and  $\text{\LaTeX}$  programming is sometimes naive. However, due to the large amount of available code, and sites as StackExchange, this is not a rule. You can also use GitHub to complain about bugs.

In this document `the reader will see some uses`<sup>1</sup> of the package, since it is distributed with the `editing` option turned on. A final version, with no comments, would be used with the `publish` option.

---

<sup>1</sup>`XEXÉO: This is an example of using this package to make a comment with highlighted text`

## 2 Package Options

There are two types of options. The first type enable specific commands, such as the `draft` command. They are named *command oriented options*. The second type represent a state of the text, which can be editing (a continuous state), submit, or publish, and some variations. They are named *state oriented options*. If they appear together, state oriented commands have precedence over the others. The user should avoid mixing them.

### 2.1 Command oriented options

<code>subjects</code>	• <code>subjects</code> , enables the use of <code>\subject</code> , which is proposed as a paragraph heading describing its subject;
<code>comments</code>	• <code>comments</code> , enables all editorial comments and the command <code>\pleasecite</code> ;
<code>drafts</code>	• <code>drafts</code> , enables the <code>\draft</code> command;
<code>suggestions</code>	• <code>suggestions</code> , enables the comments defined in the suggestion section of this text.
<code>anonymize</code>	• <code>anonymize</code> , enables anonymization commands, and
<code>todos</code>	• <code>todos</code> , enables the to do family of commands.

### 2.2 State oriented options

<code>submit</code>	• <code>submit</code> , enables the submit state. Anonimization is on, subjects, comments, drafts and suggestions are off
<code>noanonymize</code>	• <code>noanonymize</code> , disables anonymizations even in <code>submit</code> and <code>editing</code> options
<code>publish</code>	• <code>publish</code> , disables all command oriented options, ignore suggestions.
<code>acceptingpublish</code>	• <code>acceptingpublish</code> , disable all command oriented options, accept suggestions
<code>editing</code>	• <code>editing</code> , enables subjects, comments, drafts and suggestions.

Users should use the `editing` state most of the time. When submitting, the `submit` state will provide a clean article, without any comments. Most of the times the article should be anonymized, but if this is not enforced, it is possible to use the options `submit` and `noanonymize` together. `publish` will never anonymize.

## 3 Version

It is possible that the user wants to know the version being used. We provide two commands for it.

<code>\hacksexexeoversion</code>	Provides the current version
<code>\printhacksexexeoversion</code>	Provides name and version

`\hacksxexeoversion` was used in the title of this article. The current version is v4.4.0.

If needed, the second macro prints also the name of the package:

`\printhacksxexeoversion`

will result in:

hacksxexeo v. v4.4.0

## 4 Editorial comments

This is the main reason of this package.

The idea is that not only users can make editorial comments on the text they are writing, but they can also establish a dialog through those comments. Visually, an editorial comment, in this package, is composed of 3 parts: an intervention in the text, a margin note indicating this intervention, and a footnote explaining it <sup>2</sup>.

Xexéo:2

### 4.1 Creating authors

`\hxauthor` This macro creates a series of commands based on the desired base command name. The command name is, usually, the name of the author or his/her function in the work being done.

The syntax is:

`\hxautor {\langle name \rangle}{\langle color \rangle}{\langle author-name \rangle}`

Where  $\langle name \rangle$  will be the base command name, which generates different commands by receiving suffixes,  $\langle color \rangle$  is the color to be used by all comments and suggestions made by this author, and  $\langle author-name \rangle$  is the string to be used to represent the author.

As an example, I usually declare myself as:

`\hxauthor{xexeo}{red}{Xexéo}`

And, among other commands, `\xexeo` will be defined in such a way that it generates a footnote written in red, with a indicative margin note in the same color. Both will be identified with “Xexéo” <sup>3</sup>.

Xexéo:3

The  $\langle name \rangle$  and  $\langle author-name \rangle$  are different to support for short command names and characters not supported in L<sup>A</sup>T<sub>E</sub>X commands. Therefore, if you name is *Gutenberg* you can create a family of commenting comments based on `\gut`, but use “Gutenberg” as your identifier.

---

<sup>2</sup>XEXÉO: This is the simplest form of an editorial note.

<sup>3</sup>XEXÉO: This is the example of the minimal use of an editorial command

`prof`      Some authors are pre-defined in the style, `prof` and `cand`, to represent the  
`cand`      professor and the graduate candidate.

## 4.2 Available commands

For each user created with command name  $\langle name \rangle$ , such as `prof` and `cand` used as example, the following commands are created.

### 4.2.1 Comments

```
\<name>      \<name> [<selection>]{<footnote comment>}
\prof        \prof [<selection>]{<footnote comment>}
\cand        \cand [<selection>]{<footnote comment>}
```

These commands will make a comment in the form of a footnote <sup>4</sup>. It can also be used to **highlight some text** <sup>5</sup>.

```
\<name>r      \<name>r [<selection>]{<footnote comment>}{<tag>}
\profr       \profr [<selection>]{<footnote comment>}{<tag>}
\candr       \candr [<selection>]{<footnote comment>}{<tag>}
```

This command will make a comment in the form of a tagged footnote <sup>6</sup>. It can also be used to **highlight some text** <sup>7</sup>. The tag must be unique, since it is used as a L<sup>A</sup>T<sub>E</sub>X label too.

## 4.3 Striked-throught comments

After using the editorial comments for a time we started to delete the old ones that represented fixed problems. However, we notice that some comments should be kept, even if solved. The solution was to create the striked-throught comments. They are easy to use, just put an `x` after the command name.

```
\<name>x      \<name>x [<selection>]{<footnote comment>}
\profx       \profx [<selection>]{<footnote comment>}
\candx       \candx [<selection>]{<footnote comment>}
```

This command will make a comment in the form of a footnote <sup>8</sup>, however the comment is striked through. It can also be used to **highlight some text** <sup>9</sup>.

<sup>4</sup>~~PROF:Simplest footnote comment~~

<sup>5</sup>~~CAND:Comment with highlighting~~

<sup>6</sup>~~PROF[FIRST TAG]:Tagged footnote comment~~

<sup>7</sup>~~PROF[YET ANOTHER TAG]:Tagged comment with highlighting~~

<sup>8</sup>~~CAND:Simplest footnote comment~~

<sup>9</sup>~~PROF:Comment with highlighting~~

```

\<name>rx      \<name>rx [\<selection>]{\footnote comment}{\<tag>}
\profrx       \profrx [\<selection>]{\footnote comment}{\<tag>}
\candrx       \candrx [\<selection>]{\footnote comment}{\<tag>}

```

Prof:10

This command will make a comment in the form of a tagged footnote <sup>10</sup>, however the comment is striked through. It can also be used to highlight some text <sup>11</sup>. The tag must be unique, since it is used as a L<sup>A</sup>T<sub>E</sub>X label too.

Prof:11

## 4.4 Text Modification - Suggestions

Sometimes one of the authors wants to insert, remove or edit some text, but he or she is not sure that every one will agree, therefore he or she can make a suggestion, that will appear with his or her color.

```

\<name>sug      \<name>sug[\<comment>]{\suggested text}
\profsug       \profsug[\<comment>]{\suggested text}
\candsug       \candsug[\<comment>]{\suggested text}

```

This macro supports making a suggestion. It inserts text, using the color chosen by the author. It is also possible to make a comment, but in this command the command is the optional argument.

As example, in this paragraph the inserted text will appears in the red, and it is possible to use a comment <sup>12</sup>.

Cand:12

```

\<name>rem      \<name>rem[\<comment>]{\suggested removal}
\profrem       \profrem[\<comment>]{\suggested removal}
\candrem       \candrem[\<comment>]{\suggested removal}

```

This macro is used to suggest removals.

This is an example that is quite good. Again, it is also possible to comment the the removal <sup>13</sup> removal.

Prof:13

```

\<name>swap     \<name>swap[\<comment>]{\suggested removal}{\suggested insertion}
\profswap      \profswap[\<comment>]{\suggested removal}{\suggested insertion}
\candswap      \candswap[\<comment>]{\suggested removal}{\suggested insertion}

```

This will work as the union of a removal and a suggestion. Actually, both are simplified forms of this command.

~~This should work like this.~~ This is an example of how the command should work.

<sup>10</sup> PROF[SECOND TAG]:Tagged footnote comment

<sup>11</sup> PROF[NEW TAG]:Tagged comment with highlighting

<sup>12</sup> CAND:I want to insert this

<sup>13</sup> PROF:Repeated words

## 4.5 A tip for using comments

A student asked me to give a priority to my commands. This would make me add yet another set of commands, with more arguments. Tags don't work because they must be unique to allow for being used as references.

The solution, however, is simple, special characters, such as ★ can be used and are highly efficient to communicate priority <sup>14</sup>.

Using other fonts, more can be accomplished. For example, package `marvosym` offers `\HollowBox`, `\Checkedbox`, `\CrossedBox`, `\X`, which can be used to indicate that something should be done, is done or will not be done.

## 5 Draft environment

`draft` The draft environment aims to allow writers to include text that is marked somehow as a draft. It was motivated because my students liked to hide text from me because “it was only a draft”, but I need to have some way to measure if they were advancing. Marking text as a draft allowed them to be free of the fear of showing errors to me. We could also use it while writing papers, since we are not native language speakers. I see it most as a psychological support to writing without fear of making mistakes.

This environment is evolving, looking for a good way to signal the draft status, due to the different interactions with the packages it uses and user's packages. It has one optional parameter that names the draft. Its default value is “Draft” If the `draft` option is not enabled, the text inside the title and the text inside the environment will not appear. The user should remember that some options will automatically turn on the `draft` option, such as the option `edicao`.

```
\begin{draft}[A draft title]
This is the example of a draft.
The title must be highlighted
There must be a box around it.
\end{draft}
```

```
\begin{draft}
This draft has the default title.
\end{draft}
```

**A draft title**  
This is the example of a draft.

---

<sup>14</sup> `XEXEO:★★` Two stars are still low priority

The title must be highlighted

There must be a box around it.

**Draft**

This draft has the default title.

## 6 Subjects

`\hxsubject`      `\hxsubject[<color>]{<text>}`

These are supposed to help organizing a text by giving a “title” for each paragraph.

**Example of a subject**

A subject is the main subject of a paragraph

**A pink colored subject**

You can use other colors, such as pink.

## 7 Lists

`\listofcomment`      Comments, citation demands and subjects can be list with these commands.  
`\listofcomment`      The lists will only appear if their commands are enable (or in the all-enabling  
`\listofsubject`      editing option).  
They are usually put in the end of the file.

## 8 Warnings

This package uses another package that changes L<sup>A</sup>T<sub>E</sub>X’s standard behavior for summary and lists. When you use it, you must explicitly change pages with `\newpage` before `\tableofcontents` or similar commands.

## 9 Comparision with other packages

It is interesting to compare this package with other 3:

- **ed** has more features for commenting, and is more configurable, however it does not have colors.



- `todonotes` it does not have the identification of the commentator, which must be put by hand. It has more options too.
- `color-edits` does not support to do notes and drafts.

## 10 Implementation

This package was initially written in Portuguese. As it become more useful, it was translated to English. There are still some signs of this in the code.

### 10.1 Access to the current version

We provide some macros for the user to know the version being used.

```
\hacksxexeoversion Provides current version of hacksxexeo
1 \newcommand{\hacksxexeoversion}{\hx@version}%

\printhacksxexeoversion Provides package name and version
2 \newcommand{\printhacksxexeoversion}{hacksxexeo v. \hacksxexeoversion}%
```

### 10.2 Option Processing

#### 10.2.1 Creating Options Variables

```
3 \newif\ifshowednotes\showednotesttrue
4 \newif\ifmargins\marginstrue
5 \newif\ifmarginnote\marginnotefalse
6 \newif\ifednotebookmarks\ednotebookmarksfalse
7 \newif\if@showcomentario\@showcomentariofalse
8 \newif\if@naoanonimizar\@naoanonimizarfale
9 \newif\if@showdraft\@showdraftfalse
10 \newif\if@showsubjects\@showsubjectsfalse
11 \newif\if@showsgestao\@showsgestaofalse
12 \newif\if@beanonymous\@beanonymousfalse
13 \newif\if@showtodo\@showtodofalse
14 \newif\if@modoedicao\@modoedicaofalse
15 \newif\if@modosubmeter\@modosubmeterfalse
16 \newif\if@modopublicar\@modopublicarfale
17 \newif\if@modopublicaraceitando\@modopublicaraceitandofalse
```

#### 10.2.2 Portuguese Options

```
18 \DeclareOption{rascunhos}{\@showdrafttrue}
19 \DeclareOption{comentarios}{\@showcomentariottrue}
20 \DeclareOption{anonimizar}{\@beanonymoustrue}
```

```

21 \DeclareOption{naoanonimizar}{\@naoanonimizartrue}
22 \DeclareOption{sugestoes}{\@showsugestaottrue}
23 \DeclareOption{assuntos}{\@showssubjectstrue}
24 \DeclareOption{edicao}{\@modoedicaottrue}
25 \DeclareOption{submeter}{\@modosubmetertrue}
26 \DeclareOption{publicar}{\@modopublicartrue}
27 \DeclareOption{publicaraceitando}{\@modopublicartrue
28     \@modopublicartrue
29     \@modopublicaraceitandottrue}
30 }

```

### 10.2.3 English Options, from ed package

```

31 \DeclareOption{show}{\showednotesttrue\message{ed.sty: showing ednotes}}
32 \DeclareOption{hide}{\showednotestfalse\message{ed.sty: hiding ednotes}}
33 \DeclareOption{draft}{\showednotesttrue\message{ed.sty: showing ednotes}}
34 \DeclareOption{final}{\showednotestfalse\message{ed.sty: hiding ednotes}}
35 \DeclareOption{nomargins}{\marginfalse}
36 \DeclareOption{marginnote}{\marginnotetrue}
37 \DeclareOption{pdfbookmarks}{\ednotebookmarkstrue}

```

### 10.2.4 Original English Options

```

38 \DeclareOption{comments}{\@showcomentariottrue}
39 \DeclareOption{anonimize}{\@beanonymoustrue}
40 \DeclareOption{noanonimize}{\@naoanonimizartrue}
41 \DeclareOption{suggestions}{\@showsugestaottrue}
42 \DeclareOption{subjects}{\@showssubjectstrue}
43 \DeclareOption{drafts}{\@showdrafttrue}
44 \DeclareOption{todos}{\@showtodottrue}
45 \DeclareOption{editing}{\@modoedicaottrue}
46 \DeclareOption{submit}{\@modosubmetertrue}
47 \DeclareOption{publish}{\@modopublicartrue}
48 \DeclareOption{acceptingpublish}{\@modopublicartrue
49     \@modopublicartrue
50     \@modopublicaraceitandottrue}
51 }
52 \ProcessOptions\relax

```

### 10.2.5 Fixing the Super Options

```

53 \if@modoedicao
54 \@showssubjectstrue
55 \@showdrafttrue
56 \@showcomentariottrue
57 \@showsugestaottrue
58 \@beanonymoustrue
59 \@showtodottrue
60 \fi
61 \if@modosubmeter
62 \@showssubjectsfalse

```

```

63 \@showdraftfalse
64 \@showcomentariofalse
65 \@showsugestaofalse
66 \@beanonymoustrue
67 \@showtodofalse
68 \fi
69 \if@naoanonimizar
70 \@beanonymousfalse
71 \fi
72 \if@modopublicar
73 \@showssubjectsfalse
74 \@showsugestaofalse
75 \@showdraftfalse
76 \@showcomentariofalse
77 \@beanonymousfalse
78 \@showtodofalse
79 \fi%
80 \if@showtodo
81 \@showcomentariottrue
82 \fi

```

### 10.3 Required Packages

Packages that are always required

- xcolor - used to support colors
- soulutf8 - this is a variation of soul, used for highlighting
- ulem - used to support strikethrough<sup>15</sup>

```

83 \RequirePackage{xcolor}
84 \RequirePackage{soulutf8}
85 \RequirePackage[normalem]{ulem}
86 \RequirePackage{tocloft}
87 \RequirePackage{etoolbox}
88 \RequirePackage{environ}
89 \RequirePackage{xstring}
90 \RequirePackage{csquotes}
91 \RequirePackage{mdframed}

```

### 10.4 Optional Packages

Package that are required only sometimes

```

92 \ifshowednotes
93 %\RequirePackage{paralist}
94 \ifmarginnote\RequirePackage{marginnote}\fi
95 \else

```

---

<sup>15</sup>To do: I must complete this explanation list

```

96 \RequirePackage{verbatim}
97 \fi%

Checking if babel is loaded, use iflang

98 \@ifpackageloaded{babel}%
99 {% \message{Babel Loaded!}%
100 \RequirePackage{iflang}%
101 }{%
102 \message{Babel not detected!}%
103 }%

104 % |hyperref| must always be the last
105 \ifednotebookmarks\RequirePackage{hyperref}\fi

```

## 10.5 Color related variables

```

106 \newcommand{\cor@prof}{red}%
107 \newcommand{\cor@cand}{blue}%
108 \newcommand{\cor@subject}{green}%
109 \newcommand{\cor@citar}{purple}%
110 \newcommand{\cor@hldraft}{yellow}%

```

## 10.6 I18N Almost Using Babel

We can detect if babel is enable and allow for some languages. If you want to use another language, you must set new values for the command `\hxdrafttitle`. I really thought that it was possible to do something smarter with babel, for example using `\setlocalecaption`, but no attempt worked out was I wanted.

There are some packages, as `translator` that can be useful but up to now this seems to be the easiest way of doing it.

The advantage of this way is that any user can `\renewcommand{\hxdrafttitle}{some text}`.

```

111 \def\hxdrafttitle{Standard Draft}%
112 \def\hxcommentstitle{Standard List of Comments}%
113 \def\hxsubjttitle{Standard List of Subjects}%
114 \def\hxcitationstitle{Standard List of Citation Needs}%
115 \def\hxpleasecitetext{Plese cite}
116 \def\hxpleasecitemessage{something to support this information}
117 \def\hxpleasecitemarginnote{Cite}%
118 %
119 \@ifpackageloaded{babel}%
120 {%
121 \IfLanguageName{brazilian}%
122 {%
123 \def\hxdrafttitle{draft}%
124 \def\hxcommentstitle{Lista de Comentários}%
125 \def\hxsubjttitle{Lista de Assuntos}%

```

```

126         \def\hxcitationstitle{Necessidades de Citação}%
127         \def\hxpleasecitetext{Favor citar}%
128         \def\hxpleasecitmessage{alguma coisa que suporte este texto}%
129         \def\hxpleasecitmarginnote{Citar}%
130     }{}%
131 %
132     \IfLanguageName{portuguese}%
133     {%
134         \def\hxdrafttitle{draft}%
135         \def\hxcommentstitle{Lista de Comentários}%
136         \def\hxsubjtitle{Lista de Assuntos}%
137         \def\hxcitationstitle{Necessidades de Citação}%
138         \def\hxpleasecitetext{Favor citar}%
139         \def\hxpleasecitmessage{alguma coisa que suporte este texto}%
140         \def\hxpleasecitmarginnote{Citar}%
141     }{}%
142 %
143     \IfLanguageName{english}%
144     {%
145         \def\hxdrafttitle{Draft}%
146         \def\hxcommentstitle{List of Comments}%
147         \def\hxsubjtitle{List of Subjects}%
148         \def\hxcitationstitle{List of Citation Needs}%
149         \def\hxpleasecitetext{Plese cite}
150         \def\hxpleasecitmessage{something to support this information}
151         \def\hxpleasecitmarginnote{Cite}%
152     }{}%
153 }%
154 {}%

```

## 10.7 ed inspired code

This code, inspired in the `ed` package, makes the basic mechanism for inserting comments as footnotes with an observation in the margin. As an addition to `ed`, it support colors.

Setting up the counter

```
155 \newcounter{hxnote}
```

Format for the text

```
156 \newcommand\hx@noteshape{\sffamily}
```

```
157 %
```

```
158 % Defining the variable that holds the color to be printed.
```

```
159 % |soul| made it quite complex, global variable is not the best programming technique, but it w
```

```
160 \def\hx@currentcolor{black}
```

footnote indicador e rótulo

`\ed@foot` This macro really creates a footnote. It uses counter `hxnote` in arabic. It prints the footnote using the currently defined color (That is a global variable, setted up elsewhehre. This is not good programming practice, but it turned out to be the easiest way of doing it in L<sup>A</sup>T<sub>E</sub>X without more and more arguments.)

```
161 \newcommand\ed@foot[3]% text, type, label
162 {\def\@test{#3}\footnotetext[\arabic{hxnote}]}%
163 {\scshape\textcolor{hx@currentcolor}{#2}}\if\@test\empty\else\label{ed:#3}\textcolor{hx@cu
```

## 10.8 More for the footnote

```
164 \def\ed@mark@style#1{#1}%
165 \newcommand\ed@mark[1]{\ed@mark@style{\footnotemark[#1]}}%
166 %
167 \newcommand\ed@footnote[3]{\ed@mark{\arabic{hxnote}}\ed@foot{#1}{#2}{#3}}%
```

## 10.9 The margin note

```
168 \newcommand\ed@margin[1]{\ifmargins\ifmarginnote\marginnote{\textcolor{hx@currentcolor}{#1}}\e
```

`\Hx@note` Basic function to hold build the note

```
169 \newcommand\Hx@note[3]% text, type, label
170 {\addtocounter{hxnote}{1}\message{#2!}}%
171 \ifshowednotes\ed@footnote{#1}{#2}{#3}\ifednotebookmarks\belowpdfbookmark{#2: #1}{#2.\thehx
```

More functions for doing the editorial note

```
172 \newcommand\hx@note[4]% text, type, label, margin
173 {\Hx@note{#1}{#2}{#3}\ifshowednotes\ed@margin{#4:\arabic{hxnote}}\fi}%
174 \newcommand\hxnote@label{Editor}%
175 \newcommand\hxnote@margin{Ed}%
176 \newcommand\hxnote@label[1]{\def\hxnote@label{#1}}%
177 \newcommand\hxnote@margin[1]{\def\hxnote@margin{#1}}%
178 \newcommand{\Hxnote}[2] [] {\Hx@note{#2}\hxnote@label{#1}}%
179 \newcommand{\hxnote}[3] [] {\def\hx@currentcolor{#3}%
180 \hx@note{#2}\hxnote@label{#1}\hxnote@margin}%
181 %%https://tex.stackexchange.com/questions/30483/how-can-i-check-in-latex-or-plain-tex-whether-
182 %% as opções comentario, assuntos e anonimizar
183 %% CORES
```

`\corleve` Make a color lighter for later use in highlightings This code is more complex than it shuould be because o soulutf8's package `\hl` behavior. Solution found in: <https://tex.stackexchange.com/questions/410295/soul-color-transparency>

```
184 \newcommand{\cor@suavizacao}{40}%
185 \newcommand{\corleve}[1]{#1!\cor@suavizacao!white}
```

`\hx@hl` Light highlight makes a `\hl` that is lighter

```

186 \newcommand{\hx@hll}[2] % Depedendo do soulutf8
187 {\colorlet{x@coraqui}{\corleve{#1}}}%
188 \sethlcolor{x@coraqui}%
189 \hl{#2}
190 }%

```

Isolating hxnote

```

191 %% rótulo texto cor indicador
192 \newcommand{\hx@hxnote}[4] [] {%
193 \hxnotelabel{#4}%
194 \hxnotemargin{#4}%
195 \hxnote{#1}{#2}{#3}%
196 % isso não tem - \hx@hxnotepre{#1}{\textcolor{#3}{#2}}{#4}{#4}{#3}
197 }%

```

## 10.10 Anonimization

Will write anonymous or cite anonymous. The user has a way to configure the citation as he or she wants.

```

\hx@anoncitertext Default values for anonymous citation.
\hx@anonciteptext
\hx@anoncitetttext 198 \newcommand{\hx@anoncitertext}{(Anonymous, Year)}%
199 \newcommand{\hx@anonciteptext}{(Anonymous, Year)}%
200 \newcommand{\hx@anoncitetttext}{Anonymous (Year)}%

```

```

\hxdefanoncitertext These macros allow to define how anonymous citations will appear is anonymous
\hxdefanonciteptext mode is activated. For exemplo, one can change all the citation formats to [0].
\hxdefanoncitetttext

```

```

201 \newcommand{\hxdefanoncitertext}[1]{\renewcommand{\hx@anoncitertext}{#1}}%
202 \newcommand{\hxdefanonciteptext}[1]{\renewcommand{\hx@anonciteptext}{#1}}%
203 \newcommand{\hxdefanoncitetttext}[1]{\renewcommand{\hx@anoncitetttext}{#1}}%

```

```

204 \if@beanonymous
205 \newcommand{\hxanon}[1]{Anonymous}%
206 \newcommand{\hxanoncite}[2] [] {\hx@anoncitertext}%
207 \newcommand{\hxanoncitep}[2] [] {\hx@anonciteptext}%
208 \newcommand{\hxanoncitet}[2] [] {\hx@anoncitetttext}%
209 \else
210 \newcommand{\hxanon}[1]{#1}%
211 \newcommand{\hxanoncite}[2] [] {\cite{#1}{#2}}%
212 \ifdef{\citep}{\newcommand{\hxanoncitep}[2] [] {\citep{#1}{#2}}}{\newcommand{\hxanoncitep}[2] [] {\
213 \ifdef{\citet}{\newcommand{\hxanoncitet}[2] [] {\citet{#1}{#2}}}{\newcommand{\hxanoncitet}[2] [] {\
214 \fi}%
215 %% retrocompatibilidade
216 \newcommand{\xanon}[2] [] {\hxanon{#1}{#2}}%
217 \newcommand{\xanoncitep}[2] [] {\hxanoncitep{#1}{#2}}%
218 \newcommand{\xanoncitet}[2] [] {\hxanoncitet{#1}{#2}}%

```

## 10.11 Subjects

The idea of subjects is to have one subject for each paragraph. Currently is just a list of subjects and a highlight.

```
219 \if@showsubjects
220 \newcommand{\listsubject}{\hxsubjtitle}%
221 %% cria a lista, depende do pacote tclift
222 \@ifundefined{chapter}
223 {\newlistof[section]{subject}{aaa}{\listsubject}}
224 {\newlistof[chapter]{subject}{aaa}{\listsubject}}%
225 %%
226 \newcommand{\hxsubject}[2][\cor@subject]{%
227   \refstepcounter{subject}%
228   \sethlcolor{#1}%
229   \hl{#2}%
230   \par%
231   \addcontentsline{aaa}{subject}{\protect\numberline{\thesubject}{#2}}%
232 }%
233 \setlength{\cftsubjectnumwidth}{2.5em}%
234 \else%
235 \newcommand{\listofsubject}{}%
236 \newcommand{\hxsubject}[2][{}]{%
237 \fi%
```

## 10.12 Editorial Comments

The main subject of this package

```
238 \if@showcomentario
239 %% Resolve a lista de comentários
240 \newcommand{\listcomentario}{\hxcommentstitle}%
241 %% cria a lista
242 \@ifundefined{chapter}
243 {\newlistof[section]{comentario}{ccc}{\listcomentario}}
244 {\newlistof[chapter]{comentario}{ccc}{\listcomentario}}%
245 %%
246 %% Comentador genérico - parte I
247 %% faz o hxnote e soma na lista
248 %% []rótulo, texto , cor, indicador
249 \newcommand{\hx@comentar}[4][{}]{%
250   \ifstrempy{#4}{%
251     % rótulo texto cor indicador
252     \hx@hxnote[#1]{#2}{#3}{Comentário}% faz a nota de rodapé do ed
253     \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#2}}%
254   }%
255   {%
256     \hx@hxnote[#1]{#2}{#3}{#4}%
257     \addcontentsline{ccc}{comentario}{\protect\numberline{\thecomentario}{#4: #2}}%
```



```

258     }%
259 }%
260 %% comentador genérico, parte II
261 %% faz o highlight , soma o step e comenta
262 %% [texto hl] footnote cor indicator
263 \newcommand{\hx@comment}[4][{}]{%
264     \refstepcounter{comentario}% soma um ao contador
265     \hx@hll{#3}{#1}% ver subfunção de impressão com hl
266     \hx@comentar{#2}{#3}{#4}%
267 }%
268 %%
269 %%
270 \newcommand{\hx@xcomment}[4][{}]{%
271     \refstepcounter{comentario}% soma um ao contador
272     \hx@hll{#3}{#1}% ver subfunção de impressão com hl
273     \hx@comentar{\sout{#2}}{#3}{#4}%
274 }%
275 %%
276 %%
277 %% comentador genérico com rótulo
278 %% [texto hl] footnote cor indicator rótulo
279 \newcommand{\hx@commentLabeled}[5][{}]{%
280     \refstepcounter{comentario}%
281     \hx@hll{#3}{#1}%
282     \hx@comentar[#5]{#2}{#3}{#4}%
283 }%
284 %%
285 %% [texto hl] footnote cor indicator rótulo
286 \newcommand{\hx@xcommentLabeled}[5][{}]{%
287     \refstepcounter{comentario}%
288     \hx@hll{#3}{#1}%
289     \hx@comentar[#5]{\sout{#2}}{#3}{#4}%
290 }%
291 %%
292 \setlength{\cftcomentariounumwidth}{2.5em}
293 \else
294 \newcommand{\hx@comentar}[4][{}]{%
295 \newcommand{\listofcomentario}{}%
296 %% não pode perder o texto comentado
297 \newcommand{\hx@comment}[4][{}]{#1}%
298 \newcommand{\hx@commentLabeled}[5][{}]{#1}%
299 \fi%|

```

### 10.13 Suggestions, Removes and Changes

```

300 %% comentário, cor, indicador, textovelho, cor velho, textonovo, cor novo
301 %% Em modo publicar coloca o textovelho
302 \if@showsuggestao
303 \newcommand{\hx@gensug}[7][Uma proposta]{%

```

```

304 \textcolor{#5}{\sout{#4}}% CORRIGINDO AQUI
305 \textcolor{#7}{#6}%
306 \if@showcomentario%
307 \ifstrempy{#1}{}%
308 {\refstepcounter{comentario}%
309 \hx@comentar{#1}{#2}{#3}% [rótulo], cor , footnote , indicador
310 }%
311 \fi%
312 }% [rótulo], cor , footnote , indicador
313 \else%
314 \if@modopublicaraceitando
315 \newcommand{\hx@gensug}[7][{}]{#6}%
316 \else%
317 \newcommand{\hx@gensug}[7][{}]{#4}%
318 \fi%
319 \fi%

```

## 10.14 Citations Needed

One common error of students is not to cite correctly. Citation errors are so common that I decided to provide the option to have an optional list just for them. They are enable together with commentaries, users can use them or not.

```

320 \if@showcomentario%
321 \newcommand{\listcomentarioref}{\hxcitationstitle}%
322 \@ifundefined{chapter}{ \newlistof[section]{comentarioref}{ccr}{\listcomentarioref}}{\newlistof
323 \else%
324 \newcommand{\listofcomentarioref}{}}%
325 \fi%
326 \if@showcomentario%
327 \newcommand{\hx@commentref}[3][{}]{%
328 \refstepcounter{comentarioref}%
329 \hx@hll{#3}{#1}%
330 \hx@hxnote{#2}{#3}{\hxpleasecitmarginnote}%
331 \addcontentsline{ccr}{comentarioref}{\protect\numberline{\thecomentarioref}{#2}}%
332 }%
333 \setlength{\cftcomentariorefnumwidth}{2.5em}%
334 \else%
335 \newcommand{\hx@commentref}[3][{}]{%
336 \fi%
337 \if@showcomentario
338 \newcommand{\favorcitar}[1][\hxpleasecitmessage]{%
339 \hx@commentref{\hxpleasecitertext \ #1}{\cor@citar}}%
340 \else%
341 \newcommand{\favorcitar}[1][{}]{%
342 \fi%

```

## 10.15 Draft

**draft** This macro creates a boxed text, with title used as a first parameter. It uses package `mdframed` to create the frame. If `draft` is turned off as an option, it suppresses everything inside the body. Due to problems with `soul` accepting `\hxdrafttitle` we use `\colorbox` to support multiple languages if default title is used

```

343 \if@showdraft%
344 \NewEnviron{draft}[1][]{%
345   \ifstrempy{#1}
346   {\colorbox{\corleve{\cor@hldraft}}{\textbf{\hxdrafttitle}}}
347   {\hx@hll{\cor@hldraft}{\textbf{#1}}}%
348   \newline%
349   \BODY%
350 }%
351 {}%
352 \surroundwithmdframed{draft}%
353 \else%
354 \NewEnviron{draft}[1][]{\{}{}%
355 \fi%
```

## 10.16 Powerful command to create editors and authors

This allows for many types of comments. This was the reason I started using a front-end to `ed`, and later decided to use colors, that `ed` does not support. If I had known of `color-edits`, maybe this package was never done. I actually implemented the same functionalities without knowing about that package. One day, looking for other editorial packages that used editorial symbols, I found `color-edits`, but it was too late, I was already hooked on L<sup>A</sup>T<sub>E</sub>X programming addiction. nome do autor, cor, identificador

`\hxautor`

```

356 \newcommand{\hxautor}[3]{%
357 %% hxcomment - texto a hl, cor, comentário, indicador de pessoa
358 \expandafter\newcommand\csname#1\endcsname[2][]{%
359 {%
360 \hx@comment[##1]{##2}{#2}{#3}}%
361 % [texto a marcar], cor , comentário, palavra, rótulo
362 \expandafter\newcommand\csname#1r\endcsname[3][]{%
363 {\hx@commentLabeled[##1]{##2}{#2}{#3}{##3}}%
364 %% cortados
365 \expandafter\newcommand\csname#1x\endcsname[2][]{%
366 {%
367 %% Comentários
368 \hx@xcomment[##1]{##2}{#2}{#3}}%
369 %% [texto a marcar], cor , comentário, palavra, rótulo
370 \expandafter\newcommand\csname#1rx\endcsname[3][]{%
```

```

371 {\hx@xcommentLabeled[##1]{##2}{#2}{#3}{##3}}%
372 %% sugestões
373 \expandafter\newcommand\csname#1sug\endcsname[2][]{%
374 {\hx@gensug[##1]{#2}{#3}{#2}{##2}{#2}}%
375 \expandafter\newcommand\csname#1rem\endcsname[2][]{%
376 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{#2}}%
377 \expandafter\newcommand\csname#1troca\endcsname[3][]{%
378 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
379 \expandafter\newcommand\csname#1swap\endcsname[3][]{%
380 {\hx@gensug[##1]{#2}{#3}{##2}{#2}{##3}{#2}}%
381 }%
382 \hxautor{prof}{red}{Prof}
383 \hxautor{cand}{blue}{Cand}

```

## 10.17 To do notes

This was developed because some of my students started a text using `todonotes`, before being aware of my package, therefore I need to have some compatibility to make de change. With time it became useful and I will try to make something better in the future.

`\todo` Fazendo um todo do `todonotes` simples.

If option `inline` is not used, it is only a front-end to an editorial comment for a user called “To do”. If it is used, it tries to simulate the simplest behavior of `todonotes` package. In the future this can be enhanced, since package `mdframe` is very powerful. If the non-inline version is used, the to do note will not appear in the List of Commentaries.

```

384 \hxautor{hx@todoauthor}{orange}{To do}%
385 \newcommand{\hx@todobackgroundcolor}{orange}%
386 \newcommand{\todo}[2][comentar]{%
387 \IfEq{inline}{#1}%
388 {%
389 \begin{mdframed}[backgroundcolor=\hx@todobackgroundcolor]
390 #2%
391 \end{mdframed}%
392 }%
393 {%
394 \hx@todoauthor{#2}%
395 }%
396 }%

```

`\hxdefinetodocolor` Allows the definition of a background color for todo notes.

```

397 \newcommand{\hxdefinetodocolor}[1]{\renewcommand{\hx@todobackgroundcolor}{#1}}%

```

## 10.18 Portuguese/English, or inverse translation table

These next lines of code made easy to convert this package to English, because it was written in Portuguese, for Brazilian researchers. Some commands were rewritten in English with time, such as `rascunho`, but the Portuguese version will always be maintained, while other were translated using only his mechanism.

```
398 \let\rascunho=\draft%
399 \let\hxassunto=\hxsubject
400 \let\pleasecite=\favorcitar%
401 \let\hxauthor=\hxautor%
402 \let\listofcomments=\listofcomentario
403 \let\listofcitationneeds=\listofcomentarioref
404 \let\listofassunto=\listofsubject
```

End of Code

## Change History

v4.0		dar problemas com o	
General: Primeira versão com dtx .	1	enumerate e itemize . . . . .	1
v4.0.3		v4.3.0	
General: Consertando o strike		General: Comandos que riscam os	
through . . . . .	1	comentários, como profx . . . . .	1
v4.1.0		v4.3.1	
General: Publicar aceitando as		General: Tem espaço demais entre	
mudanças introduzidos . . . . .	1	marginnotes... tentando	
v4.2.0		resolver . . . . .	1
General: Comando todo . . . . .	1	v4.3.2	
v4.2.1		General: Fixing behavior of draft,	
General: Pacote paralist, herdado		going for internationalization . .	1
de código do ed, parece inútil e		v4.4.0	
		General: First version in English .	1

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

<b>Symbols</b>	<code>\@showtodot</code> true .. 44, 59	<b>E</b>
<code>\@beanonymousfalse</code> .. ..... 12, 70, 77	<code>\@test</code> ..... 162, 163	<code>\ed@foot</code> ..... <u>161</u> , 167
<code>\@beanonymoustrue</code> .. .... 20, 39, 58, 66	<code>\_</code> ..... 339	<code>\ed@footnote</code> .. 167, 171
<code>\@empty</code> ..... 163	<b>A</b>	<code>\ed@margin</code> ... 168, 173
<code>\@ifpackageloaded</code> .. ..... 98, 119	<code>\addcontentsline</code> .. ..... 231, 253, 257, 331	<code>\ed@mark</code> ..... 165, 167
<code>\@ifundefined</code> ..... .... 222, 242, 322	<code>\addtocounter</code> ..... 170	<code>\ed@mark@style</code> 164, 165
<code>\@modoedicaofalse</code> .. 14	<b>B</b>	<code>\ednotebookmarksfalse</code> ..... 6
<code>\@modoedicaotru</code> 24, 45	<code>\belowpdfbookmark</code> .. 171	<code>\ednotebookmarkstrue</code> 37
<code>\@modopublicaraceitandofalse</code> ..... 17	<code>\BODY</code> ..... 349	<code>\else</code> ..... 95, 163, 168, 209, 234, 293, 313, 316, 323, 334, 340, 353
<code>\@modopublicaraceitandotru</code> ..... 29, 50	<b>C</b>	<code>\end</code> ..... 391
<code>\@modopublicarf</code> 16	<code>\cftcomentarionumwidth</code> ..... 292	<code>\endcsname</code> ... 358, 362, 365, 370, 373, 375, 377, 379
<code>\@modopublicartrue</code> .. .... 26, 28, 47, 49	<code>\cftcomentariorefnwidth</code> ..... 333	environments: <code>draft</code> ..... <u>343</u>
<code>\@modosubmeterfalse</code> 15	<code>\cftsubjectnumwidth</code> 233	<code>\expandafter</code> .. 358, 362, 365, 370, 373, 375, 377, 379
<code>\@modosubmetertrue</code> .. ..... 25, 46	<code>\cite</code> ..... 211–213	<b>F</b>
<code>\@naoanonimizarfalse</code> 8	<code>\citep</code> ..... 212	<code>\favorcitar</code> 338, 341, 400
<code>\@naoanonimizartrue</code> ..... 21, 40	<code>\citet</code> ..... 213	<code>\fi</code> 60, 68, 71, 79, 82, 94, 97, 105, 163, 168, 171, 173, 214, 237, 299, 311, 318, 319, 325, 336, 342, 355
<code>\@showcomentariofalse</code> ..... 7, 64, 76	<code>\colorbox</code> ..... 346	<code>\footnotemark</code> ..... 165
<code>\@showcomentariotru</code> .... 19, 38, 56, 81	<code>\colorlet</code> ..... 187	<code>\footnotetext</code> ..... 162
<code>\@showdraftfalse</code> .. ..... 9, 63, 75	<code>\cor@cand</code> ..... 107	<b>H</b>
<code>\@showdrafttrue</code> ... ..... 18, 43, 55	<code>\cor@citar</code> ... 109, 339	<code>\hacksxexeoversion</code> <u>1</u> , 2
<code>\@showsubjectfalse</code> ..... 10, 62, 73	<code>\cor@hldraft</code> ..... ..... 110, 346, 347	<code>\hl</code> ..... 189, 229
<code>\@showsubjecttrue</code> .. ..... 23, 42, 54	<code>\cor@prof</code> ..... 106	<code>\hx@anonciteptext</code> .. .... <u>198</u> , 202, 207
<code>\@showsugestaofalse</code> ..... 11, 65, 74	<code>\cor@suavizacao</code> 184, 185	<code>\hx@anoncitetext</code> .. .... <u>198</u> , 201, 206
<code>\@showsugestaotrue</code> .. ..... 22, 41, 57	<code>\cor@subject</code> .. 108, 226	<code>\hx@anoncitetttext</code> .. .... <u>198</u> , 203, 208
<code>\@showtodofalse</code> ... ..... 13, 67, 78	<code>\corleve</code> .. <u>184</u> , 187, 346	
	<code>\csname</code> ..... 358, 362, 365, 370, 373, 375, 377, 379	
	<b>D</b>	
	<code>\DeclareOption</code> .... ..... 18–27, 31–48	
	<code>\draft</code> ..... 398	
	<code>draft (environment)</code> . <u>343</u>	

<code>\hx@comentar</code> . . . . .	<code>\hxnote@label</code> . . . . .	<code>\listcomentario</code> . . .
. 249, 266, 273,	. 174, 176, 178, 180	. . . . 240, 243, 244
282, 289, 294, 309	<code>\hxnote@margin</code> . . . .	<code>\listcomentarioref</code> .
<code>\hx@comment</code> 263, 297, 360	. . . . 175, 177, 180	. . . . . 321, 322
<code>\hx@commentLabeled</code> .	<code>\hxnotelabel</code> . . 176, 193	<code>\listofassunto</code> . . . 404
. . . . 279, 298, 363	<code>\hxnotemargin</code> . 177, 194	<code>\listofcitationneeds</code>
<code>\hx@commentref</code> . . . .	<code>\hxpleasecitmarginnote</code>	. . . . . 403
. . . . 327, 335, 339	. . . . . 117,	<code>\listofcomentario</code> .
<code>\hx@currentcolor</code> . .	129, 140, 151, 330	. . . . . 295, 402
. 160, 163, 168, 179	<code>\hxpleasecitmessage</code>	<code>\listofcomentarioref</code>
<code>\hx@gensug</code> . . . . .	. . . . . 116,	. . . . . 324, 403
. 303, 315, 317,	128, 139, 150, 338	<code>\listofcomments</code> . . 402
374, 376, 378, 380	<code>\hxpleasecitetext</code> .	<code>\listofsubject</code> 235, 404
<code>\hx@hll</code> 186, 265, 272,	. . . . . 115,	<code>\listsubject</code> . . . . .
281, 288, 329, 347	127, 138, 149, 339	. . . . 220, 223, 224
<code>\hx@hxnote</code> . . . . .	<code>\hxsubject</code> 226, 236, 399	
. 192, 252, 256, 330	<code>\hxsubjtitle</code> . . 113,	<b>M</b>
<code>\hx@hxnotepre</code> . . . . 196	125, 136, 147, 220	<code>\marginnote</code> . . . . . 168
<code>\Hx@note</code> . . 169, 173, 178		<code>\marginnotefalse</code> . . . 5
<code>\hx@note</code> . . . . . 172, 180	<b>I</b>	<code>\marginnotetrue</code> . . . 36
<code>\hx@noteshape</code> . 156, 163	<code>\if</code> . . . . . 163	<code>\marginpar</code> . . . . . 168
<code>\hx@todoauthor</code> . . . 394	<code>\if@beanonymous</code> 12, 204	<code>\marginsfalse</code> . . . . 35
<code>\hx@todobackgroundcolor</code>	<code>\if@modoedicao</code> . . 14, 53	<code>\marginstrue</code> . . . . . 4
. . . . 385, 389, 397	<code>\if@modopublicar</code> 16, 72	
<code>\hx@version</code> . . . . . 1	<code>\if@modopublicaraceitando</code>	<b>N</b>
<code>\hx@xcomment</code> . . 270, 368	. . . . . 17, 314	<code>\NewEnviron</code> . . . 344, 354
<code>\hx@xcommentLabeled</code>	<code>\if@modosubmeter</code> 15, 61	<code>\newif</code> . . . . . 3–17
. . . . . 286, 371	<code>\if@naoanonimizar</code> 8, 69	<code>\newline</code> . . . . . 348
<code>\hxanon</code> . . . 205, 210, 216	<code>\if@showcomentario</code> .	<code>\newlistof</code> . . . 223,
<code>\hxanoncite</code> . . . 206, 211	. . . . . 7, 238,	224, 243, 244, 322
<code>\hxanoncitep</code> . . . . .	306, 320, 326, 337	<code>\numberline</code> . . . . .
. . . . 207, 212, 217	<code>\if@showdraft</code> . . . 9, 343	. 231, 253, 257, 331
<code>\hxanoncitet</code> . . . . .	<code>\if@showsubjects</code> 10, 219	<b>P</b>
. . . . 208, 213, 218	<code>\if@showsgestao</code> 11, 302	<code>\par</code> . . . . . 230
<code>\hxassunto</code> . . . . . 399	<code>\if@showtodo</code> . . . 13, 80	<code>\pleasecite</code> . . . . . 400
<code>\hxauthor</code> . . . . . 401	<code>\ifdef</code> . . . . . 212, 213	<code>\printhacksxexeoversion</code>
<code>\hxautor</code> . . 356, 384, 401	<code>\ifednotebookmarks</code> .	. . . . . 2
<code>\hxcitationstyle</code> .	. . . . . 6, 105, 171	<code>\ProcessOptions</code> . . . 52
. . . . . 114,	<code>\IfEq</code> . . . . . 387	<code>\protect</code> . . . . .
126, 137, 148, 321	<code>\IfLanguageName</code> . . .	. 231, 253, 257, 331
<code>\hxcommentstyle</code> 112,	. . . . 121, 132, 143	
. . . . 124, 135, 146, 240	<code>\ifmarginnote</code> 5, 94, 168	<b>R</b>
<code>\hxdefanonciteptext</code> 201	<code>\ifmargins</code> . . . . 4, 168	<code>\rascunho</code> . . . . . 398
<code>\hxdefanoncitetext</code> . 201	<code>\ifshowednotes</code> . . .	<code>\refstepcounter</code> . . .
<code>\hxdefanoncitettext</code> 201	. . . 3, 92, 171, 173	. 227, 264, 271,
<code>\hxdefinetodocolor</code> . 397	<code>\ifstrempy</code> 250, 307, 345	280, 287, 308, 328
<code>\hxdrafttitle</code> . 111,		<code>\relax</code> . . . . . 52
123, 134, 145, 346	<b>L</b>	<code>\renewcommand</code> . . . .
<code>\Hxnote</code> . . . . . 178	<code>\label</code> . . . . . 163	. . . . 201–203, 397
<code>\hxnote</code> . . . . . 179, 195		



<code>\RequirePackage</code> . . .	<code>\showednotesttrue</code> . .	<code>\thecomentario</code> 253, 257
. . . . . 83–91,	. . . . . 3, 31, 33	<code>\thecomentarioref</code> . 331
93, 94, 96, 100, 105	<code>\sout</code> . . . . . 273, 289, 304	<code>\thehxnote</code> . . . . . 171
	<code>\surroundwithmdframed</code>	<code>\thesubject</code> . . . . . 231
	. . . . . 352	<code>\todo</code> . . . . . 384
<b>S</b>		
<code>\sethlcolor</code> . . . 188, 228		
<code>\setlength</code> 233, 292, 333	<b>T</b>	<b>X</b>
<code>\sffamily</code> . . . . . 156	<code>\textbf</code> . . . . . 346, 347	<code>\xanon</code> . . . . . 216
<code>\showednotesfalse</code> 32, 34	<code>\textcolor</code> . . . 163,	<code>\xanoncitep</code> . . . . . 217
	168, 196, 304, 305	<code>\xanoncitet</code> . . . . . 218

## List of Comments

1.1	Xexéo: This is an exemple of using this package to make a comment with highlighted text . . . . .	2
4.1	Xexéo: This is the simplest form of an editorial note. . . . .	4
4.2	Xexéo: This is the example of the minimal use of an editorial command	4
4.3	Prof: Simplest footnote comment . . . . .	5
4.4	Cand: Comment with highlighting . . . . .	5
4.5	Prof: Tagged footnote comment . . . . .	5
4.6	Prof: Tagged comment with highlighting . . . . .	5
4.7	Cand: <del>Simplest footnote comment</del> . . . . .	5
4.8	Prof: <del>Comment with highlighting</del> . . . . .	5
4.9	Prof: <del>Tagged footnote comment</del> . . . . .	6
4.10	Prof: <del>Tagged comment with highlighting</del> . . . . .	6
4.11	Cand: I want to insert this . . . . .	6
4.12	Prof: Repeated words . . . . .	6
4.13	Xexéo: ★★ Two stars are still low priority . . . . .	7
10.1	To do: I must complete this explanation list . . . . .	11

## List of Citation Needs

## List of Subjects

6.1	Example of a subject . . . . .	8
6.2	A pink colored subject . . . . .	8