

# Elements Of Data Science - F2020

## **Week 6: Intro to Machine Learning Models Continued**

10/18/2020

# TODOs

- Readings:
  - Recommended: [https://scikit-learn.org/stable/supervised\\_learning.html](https://scikit-learn.org/stable/supervised_learning.html)
  - Reference: PML Chapter Chap 3
- HW1, Due **Thurs Oct 22nd, 11:59pm ET**
- Answer and submit Quiz 6, **Sunday Oct 25th, 11:59pm ET**
- Midterm
  - Release Monday night 10/26
  - Due **Saturday Oct 31st, 11:59pm ET**
  - Have 24hrs after starting exam to finish
  - 30-40 questions (fill in the blank/multiple choice/short answer)
  - Online via Gradescope
  - Questions asked/answered **privately** via Piazza
  - Open-book, open-note, open-python

# Today

- Finish Linear Models
- One Vs. Rest For Multiclass/Multilabel Classification
- Distance Based: kNN
- Tree Based: Decision Tree
- Ensembles: Bagging, Boosting, Stacking

# Questions?

# Linear Models

- Linear Regression
- Logistic Regression
- SVM

# Wine as Multi-Class Classification

# Wine as Multi-Class Classification

```
In [2]: df_wine = pd.read_csv('../data/wine_dataset.csv', usecols=['alcohol', 'ash', 'proline', 'hue', 'class'])

X = df_wine[['proline', 'hue']]
y = df_wine['class']

zscore = lambda x: (x-x.mean()) / x.std()

X_zscore = X.apply(zscore, axis=0)
alcohol_zscore = zscore(df_wine.alcohol)

y.value_counts().sort_index()
```

```
Out[2]: 0    59
        1    71
        2    48
        Name: class, dtype: int64
```

# One Vs. Rest (OvR) Classification For Multiclass, Multilabel



# One Vs. Rest (OvR) Classification For Multiclass, Multilabel

- Can use any binary classifier for Multiclass/Multilabel classification by training multiple models:
  - model 1 : class 1 vs (class 2 and class 3)
  - model 2 : class 2 vs (class 1 and class 3)
  - model 3 : class 3 vs (class 1 and class 2)
- For Multiclass
  - Predict  $\hat{y}$  using the model with highest  $P(y = \hat{y} \mid x)$ , or distance from boundary, or ...
- For Multilabel
  - Predict  $\hat{y}$  for any model that predicts a value above some threshold

See [sklearn](#) for more info and other methods

# OvR For Logistic Regression

# OvR For Logistic Regression

```
In [3]: from sklearn.linear_model import LogisticRegression
logr = LogisticRegression(multi_class='ovr', # default
                          max_iter=1000     # to avoid errors
                          )
logr.fit(X_zscore,y)

print(logr.predict(X_zscore.iloc[[15,82,166]]))
print(logr.predict_proba(X_zscore.iloc[[15,82,166]]))
```

```
[0 1 2]
[[9.67392098e-01 3.14881014e-02 1.11980048e-03]
 [1.46331313e-01 8.53010324e-01 6.58362811e-04]
 [1.75637296e-01 3.44369368e-01 4.79993336e-01]]
```

# OvR For Logistic Regression


```
In [3]: from sklearn.linear_model import LogisticRegression
logr = LogisticRegression(multi_class='ovr', # default
                          max_iter=1000     # to avoid errors
                          )
logr.fit(X_zscore,y)

print(logr.predict(X_zscore.iloc[[15,82,166]]))
print(logr.predict_proba(X_zscore.iloc[[15,82,166]]))
```

```
[0 1 2]
[[9.67392098e-01 3.14881014e-02 1.11980048e-03]
 [1.46331313e-01 8.53010324e-01 6.58362811e-04]
 [1.75637296e-01 3.44369368e-01 4.79993336e-01]]
```


```
In [4]: fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X_zscore.values,y.values,logr)
ax.set_xlabel(X.columns[0]); ax.set_ylabel(X.columns[1])
```

Out[4]: Text(0, 0.5, 'hue')



# Distance Based: k-Nearest Neighbor (kNN)

- What category do most of the  $k$  nearest neighbors belong to?



From PML


# KNN in sklearn

# KNN in sklearn

```
In [5]: from sklearn.neighbors import KNeighborsClassifier

knn = KNeighborsClassifier(n_neighbors=5)
knn.fit(X,y)

fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X.values, y.values, clf=knn);
ax.set_xlabel(X.columns[0]); ax.set_ylabel(X.columns[1]);
```




# Effects of Standardization on Distance Based Methods



# Effects of Standardization on Distance Based Methods

```
In [6]: knn = KNeighborsClassifier(n_neighbors=5)
knn.fit(X_zscore,y)

fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X_zscore.values, y.values, clf=knn);
plt.xlabel(X.columns[0]); plt.ylabel(X.columns[1]);
```



# Curse of Dimensionality

The more dimensions, the further away things can be.

# Curse of Dimensionality

The more dimensions, the further away things can be.

```
In [7]: x1 = np.array([0,0])  
        x2 = np.array([1,1])  
        ((x1 - x2)**2).sum()**.5
```

```
Out[7]: 1.4142135623730951
```

# Curse of Dimensionality

The more dimensions, the further away things can be.

```
In [7]: x1 = np.array([0,0])  
x2 = np.array([1,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[7]: 1.4142135623730951
```

```
In [8]: x1 = np.array([0,0])  
x2 = np.array([0,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[8]: 1.0
```

# Curse of Dimensionality

The more dimensions, the further away things can be.

```
In [7]: x1 = np.array([0,0])  
x2 = np.array([1,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[7]: 1.4142135623730951
```

```
In [8]: x1 = np.array([0,0])  
x2 = np.array([0,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[8]: 1.0
```

```
In [9]: x1,x2 = np.zeros(1000),np.ones(1000)  
(((x1 - x2)**2).sum())**.5
```

```
Out[9]: 31.622776601683793
```

# Curse of Dimensionality

The more dimensions, the further away things can be.

```
In [7]: x1 = np.array([0,0])  
x2 = np.array([1,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[7]: 1.4142135623730951
```

```
In [8]: x1 = np.array([0,0])  
x2 = np.array([0,1])  
(((x1 - x2)**2).sum())**.5
```

```
Out[8]: 1.0
```

```
In [9]: x1,x2 = np.zeros(1000),np.ones(1000)  
(((x1 - x2)**2).sum())**.5
```

```
Out[9]: 31.622776601683793
```

```
In [10]: x2[0] = 0  
(((x1 - x2)**2).sum())**.5
```

```
Out[10]: 31.606961258558215
```


# Regression with kNN

# Regression with kNN

```
In [11]: from sklearn.neighbors import KNeighborsRegressor

knnr = KNeighborsRegressor(n_neighbors=5)
knnr.fit(X_zscore.proline.values.reshape(-1,1), alcohol_zscore)
X_test = np.linspace(-2,4,1000).reshape(-1,1)
y_hat = knnr.predict(X_test)


fig,ax = plt.subplots(1,1,figsize=(6,6))
ax.scatter(X_zscore.proline, alcohol_zscore, s=20, edgecolor="black",
           c="darkorange", label="data")
ax.plot(X_test, y_hat, color="cornflowerblue",
        label="n_neighbors=5", linewidth=2)
ax.set_xlabel('proline'); ax.set_ylabel('alcohol'); ax.legend();
```





# Decision Tree

- What answer does a series of yes/no questions lead us to?



From PML


# Decision Tree Classifier in sklearn

# Decision Tree Classifier in sklearn

```
In [12]: from sklearn.tree import DecisionTreeClassifier

dtc = DecisionTreeClassifier(max_depth=10)
dtc.fit(X,y)

fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X.values, y.values, clf=dtc);
plt.xlabel(X.columns[0]); plt.ylabel(X.columns[1]);
```




# Building a Decision Tree

- How to decide which question to choose? **Reduce Impurity**

# Building a Decision Tree

- How to decide which question to choose? **Reduce Impurity**



From PML

# Plot Learned Decision Tree Using sklearn


```
# Note: there is a conflict between plot_tree and seaborn.set_style in sklearn < .24  
from sklearn.tree import plot_tree  
# for tree with maxdepth=10  
plot_tree(dtc, ax=ax, fontsize=8, feature_names=X.columns, filled=True);
```

# Decision Tree: Limit Maximum Depth

# Decision Tree: Limit Maximum Depth

```
In [14]: dtc_md3 = DecisionTreeClassifier(max_depth=3)
dtc_md3.fit(X,y)

fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X.values, y.values, clf=dtc_md3);
plt.xlabel(X.columns[0]); plt.ylabel(X.columns[1]);
```





# Plot Learned Decision Tree Using sklearn

- For tree with max\_depth=3


# Regression with Decision Trees

# Regression with Decision Trees

```
In [15]: from sklearn.tree import DecisionTreeRegressor

dtr = DecisionTreeRegressor(max_depth=3)
dtr.fit(X.proline.values.reshape(-1,1), df_wine.alcohol)
X_test = np.linspace(300,1700,1000)[: , np.newaxis]
y_hat = dtr.predict(X_test)

fig, ax = plt.subplots(1,1, figsize=(6,6))
ax.scatter(X.proline, df_wine.alcohol, s=20, edgecolor="black",
           c="darkorange", label="data")
ax.plot(X_test, y_hat, color="cornflowerblue",
        label="max_depth=3", linewidth=2)
ax.set_xlabel('proline'); ax.set_ylabel('alcohol'); plt.legend();
```



# Ensemble Methods

- "Wisdom of the crowd"
- Can often achieve better performance with collection of learners
- Often use shallow trees as base learners


# Ensemble Methods

- "Wisdom of the crowd"
- Can often achieve better performance with collection of learners
- Often use shallow trees as base learners

Common methods for generating ensembles:

- **Bagging** (Bootstrap Aggregation)
  - Random Forest
- **Boosting**
  - Gradient Boosting
- **Stacking**

# Random Forest and Gradient Boosted Trees




From <https://www.researchgate.net/publication/301638643> Electromyographic Patterns during Golf Swing Activation Sequence Profiling and Prediction of Shot Effectiveness

# Bagging with Random Forests

- Trees built with bootstrap samples and subsets of features
- Achieve variation with random selection of observations and features

Sample indices	Bagging round 1	Bagging round 2	...
1	2	7	...
2	2	3	...
3	1	2	...
4	3	1	...
5	7	1	...
6	2	7	...
7	4	7	...

 $C_1$  $C_2$  $C_m$

# Random Forests with sklearn




# Random Forests with sklearn

```
In [16]: from sklearn.ensemble import RandomForestClassifier

rfc = RandomForestClassifier(n_estimators=10, # number of trees in ensemble
                             n_jobs=-1,     # parallelize using all available cores
                             random_state=0  # for demonstration only
                             )

rfc.fit(X,y)

fig,ax = plt.subplots(1,1,figsize=(6,6))
plot_decision_regions(X.values, y.values, clf=rfc);
plt.xlabel(X.columns[0]); plt.ylabel(X.columns[1]);
```




# Regression with RandomForest

# Regression with RandomForest

```
In [17]: from sklearn.ensemble import RandomForestRegressor


rfr = RandomForestRegressor(n_estimators=3, n_jobs=-1)
rfr.fit(df_wine.proline.values.reshape(-1,1), df_wine.alcohol)
X_test = np.linspace(300,1700,1000)[: , np.newaxis]
y_hat = rfr.predict(X_test)

fig, ax = plt.subplots(1,1, figsize=(6,6))
ax.scatter(df_wine.proline, df_wine.alcohol, s=20, edgecolor="black",
           c="darkorange", label="data")
ax.plot(X_test, y_hat, color="cornflowerblue",
        label="n_estimators=3", linewidth=2)
ax.set_xlabel('proline'); ax.set_ylabel('alcohol'); plt.legend();
```



# Gradient Boosted Trees

- Trees built by adding weight to mis-classification
- Achieve variation due to changes in weights on observations



From PML


# Regression with Gradient Boosted Trees

# Regression with Gradient Boosted Trees


```
In [19]: from sklearn.ensemble import GradientBoostingRegressor

gbr = GradientBoostingRegressor(n_estimators=10)
gbr.fit(df_wine.proline.values.reshape(-1,1), df_wine.alcohol)
X_test = np.linspace(300,1700,1000)[: , np.newaxis]
y_hat = gbr.predict(X_test)

fig, ax = plt.subplots(1,1, figsize=(6,6))
ax.scatter(df_wine.proline, df_wine.alcohol, s=20, edgecolor="black",
          c="darkorange", label="data")
ax.plot(X_test, y_hat, color="cornflowerblue",
        label="n_estimators=10", linewidth=2)
ax.set_xlabel('proline'); ax.set_ylabel('alcohol'); plt.legend();
```



# Stacking



From <https://blogs.sas.com/content/subconsciousmusings/2017/05/18/stacked-ensemble-models-win-data-science-competitions/>

# Stacking with mlxtend for Classification




# Stacking with mlxtend for Classification

```
In [20]: from mlxtend.classifier import StackingClassifier

ensemble = [LogisticRegression(max_iter=1000),
             DecisionTreeClassifier(max_depth=3),
             KNeighborsClassifier(n_neighbors=3)]

stc = StackingClassifier(ensemble, LogisticRegression())
stc.fit(X_zscore, y)

fig, ax = plt.subplots(1, 1, figsize=(6, 6))
plot_decision_regions(X_zscore.values, y.values, clf=stc);
plt.xlabel(X.columns[0]); plt.ylabel(X.columns[1]);
```



# Stacking with mlxtend for Regression

# Stacking with mlxtend for Regression

```
In [21]: from mlxtend.regressor import StackingRegressor

ensemble = [LinearRegression(),
            DecisionTreeRegressor(max_depth=3),
            KNeighborsRegressor(n_neighbors=6)]

stackr = StackingRegressor(ensemble, LinearRegression())
stackr.fit(X_zscore.proline.values.reshape(-1,1), df_wine.alcohol)
X_test = np.linspace(-2,4,1000)[:,:np.newaxis]
y_hat = stackr.predict(X_test)


fig,ax = plt.subplots(1,1,figsize=(6,6))
ax.scatter(X_zscore.proline.values.reshape(-1,1), df_wine.alcohol, s=20, edgecolor="black",
          c="darkorange", label="data")
ax.plot(X_test, y_hat, color="cornflowerblue",
        label="stacking_ensemble", linewidth=2)
ax.set_xlabel('proline'); ax.set_ylabel('alcohol');
plt.legend();
```



# Review of Models


# Model Review: Simple/Multiple Linear Regression

- Use for: Regression
- Pros:
  - fast to train
  - interpretable coefficients
- Cons:
  - assumes linear relationship
  - depends on removing colinear features



# Model Review: Logistic Regression


- Use for: Classification
- Pros:
  - fast to train
  - interpretable coefficients (log odds)
- Cons:
  - assumes linear boundary
  - depends on removing colinear features



from PML


# Model Review: Support Vector Machine (SVM)

- Use for: Classification and Regression
- Pros:
  - fast to evaluate
  - can use kernel trick to learn non-linear functions
- Cons:
  - slow to train
  - can fail to converge on very large datasets



# Model Review: k Nearest Neighbor (kNN)


- Use for: Classification or Regression
- Pros:
  - fast to train
  - non-linear boundary
- Cons:
  - potentially slow to predict
  - curse of dimensionality





# Model Review: Decision Tree


- Use for: Classification or Regression
- Pros:
  - very interpretable
  - quick to predict
  - can handle numeric and categorical variables without transformation
- Cons:
  - tendency to overfit (learn training set too well, more next class!)



From PML

# Model Review: Random Forest (Ensemble via Bagging)

- Use for: Classification or Regression
- Pros:
  - less likely to overfit than decision tree
  - quick to train (through parallelization, quick to predict)
- Cons:
  - less interpretable, though still possible



From [https://www.researchgate.net/publication/301638643\\_Electromyographic\\_Patterns\\_during\\_Golf\\_Swing\\_Activation\\_Sequence\\_Profiling\\_and\\_Prediction\\_of\\_Shot\\_Effectiveness](https://www.researchgate.net/publication/301638643_Electromyographic_Patterns_during_Golf_Swing_Activation_Sequence_Profiling_and_Prediction_of_Shot_Effectiveness)

# Model Review: Gradient Boosted Trees (Ensemble via Boosting)


- Use for: Classification or Regression
- Pros:
  - pays more attention to difficult decision regions
  - quick to predict
  - tends to work well on difficult tasks
- Cons:
  - slow to train (parallelization not possible)
  - less interpretable, though still possible

# Model Review: Ensemble via Stacking

- Use for: Classification (or Regression)
- Pros:
  - combines benefits of multiple learning types
  - easy to implement
  - tends to win competitions
- Cons:
  - difficult to interpret
  - training/prediction time depends on component models

# Neural Networks (aka Deep Learning)

- Pros and Cons of Deep Learning
  - sensitive to initialization and structure
  - high complexity -> needs more data
  - low interpretability
  - can learn complex interactions
  - performs well on tasks involving complex signals (ex images, sound, etc)



# Questions?