Agent Harnesses Need a Pattern Discipline — Scaling Alone Cannot Absorb Their System Responsibilities

Haoyi Xiong

Abstract

An agent is a model embedded in an executable harness that mediates context, tools, permissions, state, verification, and termination. Some of what a harness does compensates for the model and may be absorbed as models improve. Other responsibilities are obligations to parties outside the model: who may authorize an action, what counts as acceptance, which evidence is kept, and how execution stops or recovers. These are assigned at the system level, whatever the model's scale, yet recurring harness decisions are usually recorded only as component names, code, or prompt recipes. We argue that agent harnesses need *pattern discipline*: contextual, revisable records of protected contracts, permitted variation, authority, evidence, consequences, and lifecycle conditions. The paper develops this position in four parts. First, a normative minimum: consequential responsibilities stay identifiable, authorized, and auditable through change. Second, the A^2 (Activities $\times$ Assets) taxonomy, which carries the protected-contract and permitted-variation distinction of software design patterns through design, verification, and evolution. Third, nine analytical cases and three structural drifts between software and harness engineering, which show what the taxonomy distinguishes; closed-loop self-improvement is a particularly demanding case. Fourth, a research agenda: two prospective protocols with predeclared three-way decision rules and simulated operating characteristics make the value of external enforcement and of complete records falsifiable. As exploratory support, a lexical-cue audit of 52 literature-sourced candidate records in 41 repositories shows that the candidate vocabulary is readily retrieved from real harness code and walks 16 structurally exact candidates up an evidence ladder from cue to model-coded pointcut and contract. The audit supplies an instrument, worked examples, and a sampling frame; it does not estimate how common patterns or contracts are.

2012 ACM Subject Classification Computing methodologies → Artificial intelligence

Keywords and phrases agent harnesses, software design patterns, system responsibilities, software evolution, agent evaluation

1 Introduction

An agent's behavior is produced by a model embedded in a *harness*: the executable runtime that assembles context, exposes tools, enforces permissions, maintains state, invokes evaluators, and decides when to stop. ReAct made the reasoning–action loop explicit [57]; SWE-agent showed that the agent–computer interface changes outcomes [56]. A benchmark result is therefore a property of model $\times$ harness under a task, evaluator, and budget—not of the model in isolation [26, 1]. Building and maintaining this runtime is now an engineering activity in its own right, with official guides, reference implementations, and surveys [2, 36, 28, 19, 31].

As harnesses grow, their builders reach for object-oriented design (OOD) to keep them changeable. OO-Harness specializes related harnesses through inheritance and routes tasks among subclasses polymorphically [25]. HarnessX constructs and evolves reusable harness components [13], and natural-language harness documents turn run-level policy, handoffs, and validation gates into explicit artifacts [37]. Each design exposes a seam: a place where behavior may change while an interface is meant to hold.

These seams are increasingly edited by agents. Harness^2 improves a harness with

contrastive probes and carries adaptation experience across iterations [55]; RRSI regularizes repeated harness improvement [53]; Harmony Harness searches among competing functionality and security objectives [59]; and observability-driven evolution uses traces to guide candidate changes [26]. Harness engineering is thereby becoming closed-loop: the system that is evaluated also proposes its successor. We use *recursive self-improvement* (RSI) for this system-level loop, which is distinct from training model weights.

Empirical studies of harnesses have taken three forms. Source studies read implementations: an audit of eleven coding agents reports recurring mechanisms [6]. Literature studies mine publications: Cai et al. extract quality attributes and 16 design patterns from 94 papers on LLM-based multi-agent systems for software engineering [11]. Outcome studies vary the runtime and measure task results, cost, or ablated modules [1, 26, 37]. Together they show that mechanisms recur and that harness choices matter. What most of them record is a mechanism name or an end-to-end score.

The missing object is the responsibility that must survive change. Harnesses are repeatedly modified as models, tools, interfaces, and tasks change, and a rewrite can alter what the model observes, which actions require approval, what counts as acceptance, or which traces remain auditable. Four challenges follow.

- *Names are not contracts.* A component name such as "memory," "router," or "evaluator" identifies a mechanism. It does not state which behavior is protected, what may vary, who may change it, or what evidence admits the change.
- *Recurrence is not evidence.* A lexical cue, a source instance, a matched pointcut, a tested contract, and a measured outcome are different evidence levels, and catalogs rarely keep them apart.
- *The maintainer is becoming an agent.* A closed-loop candidate can rewrite its own checks, permissions, or provenance; ordinary migration and maintenance face the same risk at lower speed.
- *Utility is model-conditional.* A mechanism that helps one model snapshot may be unnecessary for the next, while the obligation it enforced remains.

Software engineering met a similar problem when systems outgrew their first designs, and it answered with design patterns. We read that literature as two streams. The *assets* stream says what a design keeps stable and where it may vary: contracts, frozen points, hot spots, and variation mechanisms [16, 8, 38]. The *activities* stream says how those assets are used over a lifecycle: in design and implementation, in testing and verification, and in maintenance and evolution [15, 24]. Our intuition is that harness engineering should inherit both streams and extend them for model–runtime interaction, stochastic behavior, model-conditional utility, and components that can change their own evaluator, permission boundary, or evidence trail. We cross the two streams into the A^2 (Activities $\times$ Assets) taxonomy (Figure 1). The assets axis states what a harness mechanism protects, its *protected contract*, and where it may change, its *permitted variation*. The activities axis states when that obligation is specified (A1, design and implementation), tested (A2, testing and verification), and maintained or reopened (A3, maintenance and evolution). Ordinary customization stays inside the declared variation seam; changing the protected contract itself returns from A3 to A1 and requires explicit authority. Every candidate pattern in this paper is placed on these coordinates. Table 1 crosses the two streams and shows, cell by cell, how each software concern extends to a harness responsibility.

Position. Agent harnesses need explicit, revisable responsibility records. Each record states a protected contract, permitted variation, authority, acceptance evidence, failure consequences, and lifecycle conditions. We call the practice of recording and testing these




Figure 1 The proposed A^2 (Activities × Assets) taxonomy. The Activities axis comprises design and implementation (A1), testing and verification (A2), and maintenance and evolution (A3). The merged Assets header groups generalized contracts and customization seams: frozen points state scoped invariants, while hot spots and variation mechanisms expose permitted changes. Cell contents illustrate our proposed harness interpretation and are not an exhaustive catalog. Solid arrows indicate the lifecycle relationship, which is not a mandatory sequential workflow. The dashed A3-to-A1 return applies when an asset's protected contract must change; ordinary customization stays within the documented variation seam. Redesign requires explicit authority, and retirement does not remove external obligations. Paradigm, quality, and human/agent factors are cross-cutting lenses and not additional axes.

obligations *pattern discipline*. Its normative minimum is that consequential responsibilities remain identifiable, authorized, and auditable through change. The specific record schema we propose is a separate, empirical claim, and we make it testable.

Two clarifications fix the scope of the position. First, the *system responsibilities* of the title are obligations whose violation has consequences outside the model: permissions, external side effects, acceptance authority, audit evidence, recovery, and termination. A stronger model can absorb cognitive scaffolding such as decomposition or planning aids, and we expect it to. It cannot, by improving, assign authority or preserve an external audit trail. The position concerns the second kind. Second, a record is not enforcement. A record makes a responsibility identifiable; keeping it authorized and auditable also takes runtime mechanisms. We therefore treat the two separately throughout: one hypothesis concerns external enforcement and the other concerns records.

The ingredients of this position exist. Source studies and literature studies already catalog harness patterns [6, 11], and natural-language harness documents already make run-level policy and artifact contracts explicit [37]. What we add is the synthesis that connects them: a record that attaches authority, acceptance evidence, violation consequences, and lifecycle conditions to a mechanism description; a taxonomy that follows the record through design, verification, and evolution; an evidence ladder that keeps a retrieval cue, a pointcut, a

Table 1 Software-to-harness transitions under the proposed A^2 lens. Read down an activity or across from its protected contract to its permitted variation. Each cell pairs a software-engineering focus with our proposed harness-engineering extension as an analytical mapping. Coding-agent mechanisms attributed to Barbaste et al. [6] carry source locators in the appendix, and named evolution methods are research mechanisms. Appendix A.1 supplies the detailed harness inventory and provenance.

Activities	Assets	
	Protected contract	Permitted variation
A1 *Design and implementation*	*Software engineering:* keeps interfaces and control rules stable across software components [16, 8, 42]. *Harness engineering:* keeps rules for what models and tools can see, do, return, and control stable while they work together [6, 57, 40, 2].	*Software engineering:* changes behavior through code hooks and replaceable components [16, 42]. *Harness engineering:* extends these change points to model providers, processing steps, tools loaded when needed, work routing, parallel tasks, and control handoffs [6, 3, 36, 40].
A2 *Testing and verification*	*Software engineering:* exposes dependencies so tests can control inputs and check outputs [15, 16, 42]. *Harness engineering:* also protects stopping rules, minimum permissions, isolated execution, and time or work limits from agent bypass [6].	*Software engineering:* swaps settings or components to test different cases [15]. *Harness engineering:* makes task rules, reviewers, memory, and improvement goals replaceable while keeping required safeguards fixed [6, 2, 43, 53, 59].
A3 *Maintenance and evolution*	*Software engineering:* stores component state and records changes so a system can be inspected or restored [16, 42, 14]. *Harness engineering:* also preserves event history, alternative session paths, the origin of changes, and evidence needed after context or model updates [6].	*Software engineering:* updates or replaces configurable parts as requirements change [42, 16, 22]. *Harness engineering:* also updates memory, task routing, policies, and the harness itself, using observed failures while preserving permissions, checks, records, and recovery duties [6, 25, 55, 13, 12, 26].

contract, and an outcome apart; and prospective protocols that test the two empirical claims the position leaves open.

An exploratory repository audit supports the argument. From the literature we collect 52 candidate records in five source families and search for their vocabulary in 41 frozen repositories from 36 repository families. The vocabulary is readily retrieved: 1,265 of the 2,132 candidate–repository cells carry a lexical cue. For 16 structurally exact candidates we then walk the same cells up an evidence ladder. Under the coding of one model with 200 prompt profiles, six gain majority support for the pointcut and four keep support for a complete contract under every profile. The audit is purposive and model-assisted. We use it for three things: an instrument with a frozen expression, specification, and negative control for every record; worked examples of detection and tracking; and a sampling frame for independent adjudication. It is not an estimate of how common patterns or contracts are.

This paper makes four contributions and adds one body of supporting material.

- *A position with a normative minimum.* Consequential harness responsibilities stay identifiable, authorized, and auditable through change (Sections 1 and 3.3.3).

- *The A^2 taxonomy and the responsibility record.* Activities × Assets locates each record's protected contract and permitted variation across design, verification, and evolution, and the record adds authority, evidence, and lifecycle conditions (Section 3.3).
- *Nine analytical cases and three structural drifts.* The cases show which obligations superficially similar mechanisms protect. The drifts show where harness engineering departs from software engineering: closed-loop evolution, agent factors, and model-conditional utility (Sections 3.4 and 4).
- *A research agenda that can falsify the position's empirical claims.* Two prospective protocols with predeclared three-way decision rules and simulated operating characteristics test external enforcement and record utility (Section 5).
- *Supporting material.* A 52-record seed inventory with the detection and matching rule for every record, representative UML class views of proposed contracts, and an exploratory lexical-cue audit of 41 repositories that exercises the evidence ladder on real code (Sections 3.1 and 3.2; Appendices A, A.4, and B).

The first three contributions are argued, the fourth is specified and awaits execution, and the supporting material is exploratory. Each claim therefore carries its own evidence level (Table 18).

Section 2 reviews harness engineering, the repository panel, software design patterns, and empirical methods, and states the open problems. Section 3 presents the candidate inventory, the exploratory audit with its coverage, candidate, and trajectory results, and the A^2 taxonomy with its case studies. Section 4 analyzes three structural drifts. Sections 5–8 state what would falsify the position, answer alternative views, issue a call to action, and conclude. Appendix A lists the complete inventory with the matching rule, Appendix A.4 draws representative UML class views, and Appendix B gives the audit protocol, statistics, and reproducibility record.

2 Background and Related Work

2.1 Harness Engineering and Representative Repositories

Let M be a fixed model, $t \sim \mathcal{T}$ a task, $s_0(t)$ its initial state, and B a budget. A harness H is the executable runtime and configuration that mediates interactions among M, tools, and an environment [19, 31]. Together they induce a trajectory distribution $\tau \sim P_H(\tau \mid t, M, s_0, B)$. An evaluator E maps a trajectory and resulting state to outcomes. Holding M, t, s_0, B, and E fixed while changing H defines a harness contrast rather than a model contrast. Estimating a causal harness effect additionally requires randomized or matched repeated runs, version-pinned components, and run-level uncertainty.

Model reports document the model side of this boundary [34, 17], including distinct context regimes [18]. Model-level system cards characterize model risks [35]; a harness's enforcement is validated at the system level. Functionally, H assembles instructions and context, exposes tool schemas, executes actions under permissions, maintains state, and controls retries or termination. Tool use, feedback, and external environment state show why these are operational rather than purely model-level choices [41, 43, 54]. The boundary admits learned components: a learned router or model-based reviewer is inside H when it is part of the system under study.

Motivated by agent-evaluation and harness-cost analyses [58, 1], we propose a minimal reproducibility record: model and decoding configuration; instructions and context assembly; tool and environment versions; state and memory policy; permission and stopping rules;

evaluator; and resource budget. It must separate task-time actions from development-time changes. Section 4.1 operationalizes this record and its lifecycle use.

Engineering practice has converged on a small vocabulary of runtime structures. Anthropic's guide and reference implementations describe prompt chaining, routing, parallelization, orchestrator–workers, and evaluator–optimizer workflows [2, 3]. OpenAI's guide adds manager coordination and decentralized handoffs [36]. The Model Context Protocol literature reuses Mediator, Observer, publish–subscribe, and Broker for agent communication [40]. Coding agents add execution loops, tool registries, permission layers, durable session state, and stop-time verification [6]. Section 3.1 turns this vocabulary into a source-indexed inventory.

Object-oriented design gives this practice a structure for change. OO-Harness places shared behavior in a base harness, specializes it in subclasses, and dispatches tasks through a polymorphic router [25]. Composition is the alternative: HarnessX builds harnesses from reusable components [13]. HarnessForge adapts runtime structure and policy together [12]. The design question is classical—inheritance versus composition around a stable interface [16]—but the author of the subclass or component may now be an agent. In our panel, cues for inheritance and polymorphic routing (record E01) appear in 33 of 36 repository families. The study protocol located no official OO-Harness repository, so these cues reflect inheritance in public harness classes and not the OO-Harness system itself.

To see how this practice appears in code, we study 41 open-source repositories grouped into 36 repository families (Table 2). A *family* groups repositories from one lineage—a fork, a successor, or a split of one project—so that shared ancestry counts once. Four families hold more than one repository: OpenHands (three), Cline and Roo Code, OpenAI Swarm and the Agents SDK, and AutoGen and Agent Framework. The panel spans Python (25 repositories), TypeScript (13), Rust (2), and JavaScript (1). It covers coding agents (19), general assistants (17), and browser, research, embodied, and mixed-domain systems (5), with single-agent (10), multi-agent (15), mixed (10), and research-specific (6) architectures.

Repository selection followed a frozen protocol. A repository is eligible when it contains executable source for an LLM-based agent runtime or harness that mediates at least one responsibility: model invocation, tool execution, state, permission, delegation, evaluation, recovery, context, or termination. Documentation-only, prompt-only, benchmark-only, generated-scaffold, and simple API-client repositories are excluded; archived repositories remain eligible as a boundary condition. Candidates came from declared search queries and a curated channel seeded by this paper's source index. They were deduplicated by repository identity and clustered into families before selection. Discovery prioritized architecture and evolution signals, and star count was recorded only as descriptive metadata. The core frame holds 24 families (29 repositories), stratified for diversity across core runtimes, orchestration frameworks, and configuration-driven harnesses; across Python and TypeScript; and across single- and multi-agent architectures. The protocol records that pattern outcome counts were not used to add, remove, or replace non-pilot families. The frame keeps families with a visible architecture event—a runtime-boundary change in OpenHands, the Cline and Roo Code fork divergence, the Swarm successor, the AutoGen migration, and configuration shifts in ECC and Langflow—because such events carry lifecycle evidence. Two purposive supplements were added after the frame was frozen: six official research repositories for evolution mechanisms named in the literature, and six repositories chosen for implementation variation and lineage comparison, including a fork ecosystem, a simplified successor, and a cross-language variant. The 36-family panel is therefore purposive. Every count in this paper describes the panel and is not a prevalence estimate for agent software.

Table 2 Repository panel: 41 repositories in 36 repository families. Parentheses group the repositories of one family, which share a lineage and count once in family-level statistics. The core frame was frozen first; the two supplements were added purposively afterwards. Research-supplement repositories are the official code named by the cited paper or its project page.

Pool and stratum	Fam.	Repos.	Repositories
Core frame (24 families, 29 repositories)			
Python core runtimes	4	6	(OpenHands, OpenHands software-agent-sdk, OpenHands automation), SWE-agent, Aider, browser-use
TypeScript core runtimes	7	8	(Cline, Roo Code), OpenCode, Gemini CLI, pi, deepseek-harness, OpenClaw, Orca
Python orchestration	10	12	(OpenAI Swarm, OpenAI Agents SDK), LangGraph, (AutoGen, Agent Framework), CrewAI, MetaGPT, Google ADK, smolagents, Pydantic AI, Agno, DeerFlow
TypeScript orchestration	1	1	Mastra
Configuration-driven and visual	2	2	ECC, Langflow
Research supplement (6 families, 6 repositories)			
Evolution mechanisms	5	5	Harness^2 [55], RRSI [53], HarnessX [13], HarnessForge [12], Agentic Harness Engineering [26]
Embodied assistance	1	1	CarryOn [49]
Implementation supplement (6 families, 6 repositories)			
Implementation and lineage variants	6	6	Codex, Goose, Continue, Qwen Code, mini-SWE-agent, OpenAI Agents JS
Total	36	41	

2.2 Design Patterns in Software Engineering: Assets and Activities

A design pattern names a recurring problem in a context, a solution structure, and its consequences [16, 8]. We sort the software-engineering literature into two streams, because the taxonomy of Section 3.3 crosses them. The *assets stream* asks what a design keeps stable and what it leaves open. The *activities stream* asks how engineers use that distinction when they design and implement, test and verify, and maintain and evolve a system. Table 3 sorts the works we build on.

In the assets stream, the first asset is the *protected contract*. Parnas's criterion decomposes a system so that each module hides a design decision that is likely to change behind an interface that is not [38]. The Gang-of-Four and POSA catalogs make the stable part explicit as participant roles and collaboration rules [16, 8, 42]. Domain-driven design protects a model's language and boundaries [14], and resource-management patterns state acquisition and release obligations [22]. In each case the reusable asset is a contract: an interface together with the invariants that its clients may rely on.

The second asset is the *permitted variation*. The same catalogs name where change is welcome. Strategy, Template Method, Adapter, and Observer expose hooks, and interceptors and component configurators extend a running system [16, 42]. The aspect-oriented tradition that began with Kiczales et al. [21] contributes the vocabulary we use for detection: a *join point* is a place in execution where behavior can attach, and a *pointcut* selects the join points to which a concern applies. Multi-dimensional separation of concerns generalizes the idea that one system can be decomposed along several concerns at once [44], and pattern

Table 3 Software-engineering foundations sorted into the assets and activities streams. The assets stream states what a design protects and where it may vary; the activities stream states how that distinction is used across the lifecycle and how it is studied empirically. The last column names what each stream leaves open for harnesses. The assignment of works to streams is our reading.

Stream and coordinate	Representative works	Contribution used here	Left open for harnesses
Assets stream: what is protected and what may vary			
Protected contract	Modular decomposition [38]; GoF and POSA catalogs [16, 8, 42]; domain-driven design [14]; resource management [22]	An interface and its invariants hide the decisions that are likely to change.	Contracts over what a model may observe, do, and approve; authority to revise them.
Permitted variation	GoF hooks and POSA interceptors [16, 42]; aspects and concerns [21, 44]; pattern languages [10, 9]	Hot spots, join points, and connections among patterns name where change is welcome.	Variation chosen at run time by a stochastic model or edited by an agent.
Activities stream: how the assets are used and studied			
A1 Design and implementation	Pattern catalogs [16, 8]; modular criteria [38]	A shared vocabulary and a default decomposition before code exists.	Designs that assign context, tools, and control to agent roles.
A2 Testing and verification	Test seams [15]	A variation point doubles as a control point for tests.	Checks that the tested system can bypass or rewrite.
A3 Maintenance and evolution	Laws of software evolution [24]; resource lifecycles [22]	Continuing change is expected; patterns localize it.	Change proposed by the system itself; value that ends when the model changes.
Empirical study of assets and activities	Pattern detection [46]; repository mining [20]; study design and sampling [39, 5, 30, 23]	Recover assets from artifacts; observe activities in histories; bound claims by sample and evidence level.	Evidence levels that separate a cue from a contract and a contract from an outcome.

languages connect individual patterns into sequences and alternatives [10, 9].

The activities stream follows the lifecycle. In *design and implementation* (A1), patterns give designers a shared vocabulary and a default decomposition: fix the contract, expose the variation point, and name the consequences before code exists [16, 8]. In *testing and verification* (A2), Feathers defines a seam as a place where behavior can be altered without editing in that place [15]. A seam lets a test substitute a dependency, control inputs, and observe outputs. The variation point of design thus becomes the control point of verification. In *maintenance and evolution* (A3), Lehman's laws observe that a system in use must be continually adapted and that its complexity grows unless work is done to contain it [24]. Patterns localize that adaptation. A change that fits a declared variation point is routine; a change that does not fit signals that the contract must be redesigned.

Pattern thinking has already reached agents (Table 4). Read through the two streams, this work is strongest on assets: it catalogs what recurs and how patterns connect. Its treatment of activities is partial. Individual studies address pattern evolution, lifecycle framing for one concern, or validation gates, and to our knowledge none carries one record through design, verification, and evolution. Recent harness surveys organize the domain by components, control–agency–runtime boundaries, or interfaces and mechanisms [28, 19, 31].

We take what these lines establish as given. Pattern catalogs for agents exist, and natural-language harness documents already state run-level policy, validation gates, and artifact contracts [37]. Explicit patterns and explicit contracts are therefore not our claim. Our contribution is the synthesis that connects them: a responsibility record that adds authority, acceptance evidence, violation consequences, and lifecycle conditions to a mechanism description; the A^2 organization that follows a record through design, verification, and evolution; an evidence ladder that keeps retrieval, exemplars, pointcuts, contracts, trajectories, and outcomes apart; and prospective protocols that separate the value of enforcement from the value of records.

2.3 Empirical Methods in Software Engineering and Repository Mining

The exploratory audit in Section 3.2 and the protocols in Section 5 take their method from empirical software engineering. The two streams apply here as well: some methods recover *assets* from artifacts, and others observe *activities* in histories.

In the assets stream, design-pattern detection recovers pattern instances from source structure, for example by scoring the similarity between a system's class graph and a pattern's role graph [46]. Its lesson for harnesses is that a detector returns *candidates*: a structural or lexical match must still be adjudicated against the pattern's intent. We therefore separate a retrieval cue from a pointcut match, and a pointcut match from a supported contract.

In the activities stream, repository mining treats version control, releases, and project metadata as data about how software is built and changed. Kalliamvakou et al. document its perils on GitHub: many repositories are not engineered projects, and forks duplicate history [20]. Our eligibility rule and family clustering respond to both. Lehman's laws motivate following a record across releases instead of reading it at one snapshot [24].

For study design, case-study guidelines ask for a protocol, multiple sources of evidence, and a chain from data to claim [39]. Sampling guidance distinguishes probability samples from purposive ones and cautions against generalizing from the latter [5], and the diversity of a sample can be reported explicitly [30]. Evidence-based software engineering asks that practice rest on critically appraised evidence [23]. We adopt a frozen protocol, a diversity-oriented purposive panel, and an explicit evidence ladder, and we report the audit as exploratory.

Table 5 orders the evidence used in this paper: a retrieval cue, a canonical source exemplar, a pointcut and contract specification against which an implementation can be adjudicated, a lifecycle trajectory, and a causal experiment. A level never implies the one above it. The exploratory audit of Section 3.2 reaches the lower levels for one purposive panel, with model-assisted coding at the pointcut and contract level. Independent adjudication and the causal level are specified as next steps (Sections 7.4 and 5). Appendix B.1 gives the audit's evidence model, unit of analysis, and statistics.

2.4 Open Problems

The background leaves five problems open. Each sits in one of the two streams, and each motivates one part of this paper.

Table 4 Positioning this engineering synthesis against direct prior work. The distinctions state complementary scopes. "Explicit" means the feature is central to the cited work rather than merely compatible with it.

Work	Primary object and connection	Lifecycle / validation	Distinction relevant here
Taylor et al. [45]; Weyns [51]	Agent-based and self-adaptive multi-agent architectures; interrelated architectural patterns.	Pattern mining, use, and evolution; case illustrations.	Prior agent-architecture precedents on which harness-level records build.
Cai et al. [11]	Quality attributes, 16 design patterns, and rationale mined from 94 LLM-based multi-agent software-engineering papers.	Systematic descriptive study; no connected harness lifecycle proposed.	Establishes a stronger empirical catalog baseline than isolated records.
Yu [60]	Twelve connected NFR patterns for security, reliability, observability, and cost, including agent-specific aspects.	Goal-to-aspect method and an open-source framework case study.	Relevant agentic quality-attribute work with complementary scope.
Milošević and Rabhi [29]	Design patterns for governed agentic communities, roles, protocols, and human–agent accountability.	Formal framework and clinical-trial-matching case study.	Centers organizational governance; our unit is the executable harness contract and its permitted variation.
Billiris and Gill [7]	A federated observability architecture pattern for changing telemetry.	AI-SDLC framing and a controlled proof of concept.	Provides lifecycle depth for one concern; our proposal supplies a common record schema across multiple harness responsibilities.
Pan et al. [37]	Executable natural-language documents for run-level harness policy, modules, handoffs, state updates, validation gates, and artifact contracts.	Shared-runtime comparisons, module ablations, and results across coding, terminal-use, and computer-use benchmarks.	Direct harness-representation neighbor with empirical evidence; it motivates our emphasis on authority, evidence, and lifecycle controls.
This paper	A pattern-discipline position: responsibility records, the A^2 taxonomy, nine analytical cases, and three structural drifts.	Promotion obligations spanning pointcut, contract, variation, evidence, and lifecycle; A1 design, A2 verification, and A3 evolution/retirement.	Adds authority, acceptance evidence, and lifecycle conditions to mechanism descriptions, with an exploratory audit and two prospective protocols.

Table 5 Evidence ladder, and how far the exploratory audit climbs it. Each level answers its own question and never implies the level below it in the table. The audit results describe one purposive panel.

Level	Unit	Status in this paper	What the level shows
Repository retrieval	Repository–pattern cell	1,265 of 2,132 cells carry a lexical cue; 1,246 in the current snapshot	The vocabulary of a candidate is present in the code; pattern presence is a later level
Canonical exemplar	Pattern	Source-backed exemplar for 51/52 patterns	At least one concrete source location anchors each supported pattern in the atlas
Pointcut/contract specification	Pattern definition	52/52 specifications with context, trigger, structure, effect, and contract fields	The comparison instrument is complete enough to adjudicate implementations
Model-coded pointcut and contract	Exact structural candidate cell	16 matcher-selected cells coded by one model under 200 prompt profiles: six majority-supported pointcuts, four with a complete contract under every profile	The coding step can be carried out and is stable to prompt wording in most cells; its correctness awaits independent adjudication
Independently adjudicated pointcut and contract	Stratified sample of cells	Specified as the next study (Section 7.4)	Cue-to-pointcut precision and recall, and contract support, with human agreement
Lifecycle trajectory	Candidate–repository trajectory	621/1,272 trajectories have at least two observed checkpoints	Large source-path changes and movement are observable in sampled histories; cue gaps are tracked as detector gaps
Causal experiment	Matched task or participant	H1/H2 designs with decision rules; outcome data to be collected	The external-enforcement and pattern-record-value hypotheses are specified for execution

1. *From mechanism names to responsibility records (assets).* Catalogs and guides name what recurs. They seldom state the protected contract, the permitted variation, and the authority to change either (Section 3.3).
2. *From retrieval to contract evidence (assets).* No shared ladder separates a cue from an instance, a pointcut match, a supported contract, and a measured outcome, so recurrence is easily read as validation (Sections 3.1 and 3.2).
3. *One record across the lifecycle (activities).* Design, verification, and evolution are studied separately. A record is rarely followed from its declaration to its tests and on to its revision or retirement (Sections 3.3 and 3.4).
4. *Self-modification and model change (activities).* Software patterns assume a human maintainer and a stable execution substrate. A harness may be maintained by an agent, and its mechanisms can lose value when only the model changes (Section 4).

5. *Causal value (both streams).* Whether external enforcement and complete records improve outcomes over simpler alternatives has not been tested (Section 5).

3 Harness Design Patterns and the A^2 Taxonomy

This section addresses the first three open problems. Section 3.1 shows that the literature already supplies candidate harness patterns. Section 3.2 reports an exploratory audit of where their vocabulary appears in repositories and how its location changes. Section 3.3 defines the A^2 taxonomy and the responsibility record, which are the core of the section. Section 3.4 uses them to map, detect, track, and analyze patterns through case studies.

3.1 Candidate Patterns Already Exist: Families and Representative Records

Candidate harness patterns do not need to be invented. The literature already names them, and we take each definition from the source that reports it. We call the entries *records*, because they differ in standing: some are recurring patterns in the classical sense, the coding-agent labels are anchored to a source-code study of eleven harnesses, and the evolution entries are mechanisms instantiated by one research system each. Our inventory holds 52 records in five source families: 29 coding-agent mechanisms (P), seven official-guide workflows and coordination patterns (W), four communication patterns (C), two reasoning and feedback patterns (R), and ten evolution mechanisms (E). Table 6 lists representative records with their source descriptions, and Appendix A gives all 52 by category.

The P family covers the runtime core of coding agents: execution loops, tool handling, permission and sandbox layers, durable state, and stop-time checks. The W family holds the five workflows of Anthropic's guide and the two coordination forms of OpenAI's guide. The C family holds the four classical communication patterns that the Model Context Protocol literature applies to agents. The R family holds the reason–act loop and verbal reflection. The E family holds research mechanisms for harness evolution, from inheritance-based specialization to regularized and multi-objective search. The families record where a description comes from; they do not add an axis to the taxonomy.

This is a scoped, argument-driven inventory: the union of named patterns, official-guide workflows, communication patterns, reasoning mechanisms, and evolution mechanisms used in the paper's comparisons. These five provenance families organize the inventory; they do not add an axis to A^2. Activity and asset coordinates are assigned across families as part of the paper's analysis. We include a record when a cited source names a recurring solution or workflow, or when a research system instantiates a mechanism needed for the evolution analysis. We exclude generic component names without a recurring decision, uncited examples, and additional relabelings introduced only to increase coverage. Records remain separate when their authority, state, or variation contracts differ, even if their surface structures overlap. The record count describes this inventory; frequency estimates come from the audit.

P01–P29 are anchored to the eleven-system source-code study of Barbaste et al. [6], whose catalog reports 29 recurring patterns. We checked each record against that paper (arXiv:2609.00006v1): Appendix A.1 gives a section and page locator for every record. Seventeen records use the source's label or a shortened form of it, and eight adapt or merge neighboring source mechanisms. P03 generalizes one system's loop, P10 is our synthesis of the paper's edit-error and output-truncation findings, P11 recasts its "disappearing boundary between tool and workflow" as a boundary to declare, and P29 joins harness mimicry with




Figure 2 Observed candidate cues, evidence provenance, and lifecycle signals in the selected panel. (A) Candidate-cue richness across 36 repository families. (B) Mean family cue coverage by record family; "Primitive" denotes the coding-agent (P) records. (C) Composition of the complete pattern–repository matrix; unobserved cells remain explicit. (D) Row-conditional next states after a candidate trajectory's first observation, with 95% repository-cluster bootstrap intervals. Family, rather than cell, is the independent unit. All results are descriptive for the selected frozen panel.

harness hosting. These readings are ours. W01–W05 follow Anthropic's guide and official reference implementations [2, 3]; W06–W07 follow OpenAI's manager and handoff guidance [36]. C01–C04 are classical communication patterns discussed in the MCP survey [40]. R and E records cite the corresponding papers. E records are instantiated research mechanisms, not claims of independently established recurring patterns; E08–E09 are adjacent embodied settings. Google's architectural components [52], surveys, and benchmarks are not relabeled as additional patterns merely to increase the count.

The records vary in granularity and evidence level, and some describe the same idea at different granularities. Completeness here means coverage of this declared inventory. The inventory is the source-indexed basis for the audit below and the seed for the registry requested in Section 7.

3.2 Exploratory Support: Candidate Cues in Repositories and How Their Locations Change

The inventory comes from the literature. To see how it meets real code, we audited the 52 records across the 41 repositories (36 families) of Section 2.1, at the current snapshot and at sampled historical releases. This subsection reports what we observed (Figure 2, Table 7). How the audit was run and checked is in Appendix B: the retrieval and matching procedure, the sensitivity analyses, the model-assisted coding, and the statistics. The observations describe this panel of repositories.

3.2.1 Cue Coverage: The Candidate Vocabulary Is Readily Retrieved

The vocabulary of the inventory is widely present in harness code. A lexical cue appears in 1,265 of the 2,132 candidate–repository cells, 1,246 of them in the current snapshot, and a curated exemplar anchors seven more. The median family holds cues for 35 of the 52 records (IQR 28.2–37.0), and six records drew current cues in all 36 families: P02, P10, P12, P23, P25, and W02. These six are concurrency, delegation, sandbox, scope, and routing

Table 6 Representative records from the five source families of the 52-record inventory. The mechanism column paraphrases the cited source and is the definition used in this paper. "Fam." counts the 36 repository families with a retrieval cue for the record (Section 3.2); it is not pointcut or contract support. Appendix A lists all 52 records by category.

ID	Record	Source-reported mechanism	Source	Fam.
Coding-agent mechanisms (P; 29 records; Barbaste et al.; source-located labels)				
P01	Minimal linear loop	Alternate model turns and action execution.	[6]	35
P04	Middleware-pipeline loop	Layer behavior around model/tool calls.	[6]	34
P14	Event-sourced conversation engine	Reconstruct state from recorded events.	[6]	31
P17	Verify-on-stop guards	Check artifacts before accepting completion.	[6]	8
P18	Hybrid loop detection	Detect stalled or repetitive behavior.	[6]	8
P21	Syntax-aware command permissioning	Inspect command structure before execution.	[6]	2
P23	Layered permission and sandbox	Combine policy decisions with execution isolation.	[6]	36
P26	Session-tree version control	Branch or revisit execution history.	[6]	30
P27	Lineage and threshold compaction	Bound history while retaining useful state.	[6]	35
Official-guide workflows and coordination (W; 7 records; Anthropic and OpenAI guides)				
W02	Routing	Select a specialized path for an input.	[2, 3]	36
W04	Orchestrator–workers	Generate and delegate subtasks dynamically.	[2, 3]	30
W05	Evaluator–optimizer	Revise an artifact using iterative feedback.	[2, 3]	17
W07	Decentralized handoffs	Transfer control to another specialized agent.	[36]	29
Communication patterns (C; 4 records; Sarkar and Sarkar)				
C01	Mediator	Coordinate interactions through an intermediary.	[40]	5
C02	Observer	Notify registered dependents of changes.	[40]	29
C03	Publish–subscribe	Decouple producers from consumers.	[40]	24
C04	Broker	Mediate discovery and invocation across boundaries.	[40]	22
Reasoning and feedback (R; 2 records; Yao et al. and Shinn et al.)				
R01	Reason–act–observe (ReAct)	Interleave reasoning and external actions.	[57]	35
R02	Verbal reflection memory	Reuse feedback across attempts.	[43]	1
Instantiated evolution mechanisms (E; 10 records; one research system each)				
E01	Inheritance and polymorphic routing	Specialize related harnesses.	[25]	33
E02	Propose–Probe–Compose	Improve a harness using contrastive probes.	[55]	6
E03	Regularized harness improvement	Limit overfitting during repeated edits.	[53]	12
E04	Multi-objective evolution and composition	Search among competing objectives.	[59]	8
E05	Composable harness foundry	Construct and evolve reusable harness components.	[13]	2
E10	Observability-driven harness evolution	Use traces to guide candidate changes.	[26]	1

Table 7 Key descriptive results from the frozen repository audit. Counts and intervals describe the selected panel. Current cues are retrieval signals, canonical locators are one atlas exemplar per pattern by design, and support locators point to tests, documentation, or a specification. S/R/U denotes supported, rejected, and unresolved candidate pointcuts under the indicated rule. All quantities are descriptive.

Measurement	Result
Repositories / independent families	41 / 36
Current-cue cells	1,246 / 2,132
Retrieval-cue cells (current or historical)	1,265 / 2,132
Canonical-locator-only cells	7 / 2,132
Cells with any evidence layer	1,272 / 2,132
Patterns with canonical exemplar	51 of 52
Atlas support: test / docs / spec.	44 / 7 / 1
Pointcuts: majority / invariant (S/R/U)	6/8/2 / 4/8/4
Median family coverage	35 of 52 (IQR 28.2–37.0)
Exploratory co-occurrence flags	22 of 1,326
Multi-checkpoint realizations	621 of 1,272 (48.8%)
Large path change after first observation [95% CI]	35.2% [23.3–47.3]

Table 8 Retrieval coverage by corpus stratum. Counts are pattern–repository cells with any current, historical, or canonical evidence. They are descriptive retrieval yields, not pointcut prevalence; repository families remain the independent unit.

Stratum	Value	Observed cells	Share
record family	Communication	86/164	52.4%
	Evolution	74/410	18.0%
	Primitive	886/1189	74.5%
	Reasoning	40/82	48.8%
	Workflow	186/287	64.8%
source pool	frozen	905/1508	60.0%
	implementation supplement	200/312	64.1%
	research supplement	167/312	53.5%
language	JavaScript	41/52	78.8%
	Python	699/1300	53.8%
	Rust	73/104	70.2%
	TypeScript	459/676	67.9%

mechanisms, the shared vocabulary of harness code. A cue marks where a pattern may be; whether the pattern is there is the next question (Section 3.2.2).

Coverage follows a clear gradient across record families (Figures 3 and 4). Mean family cue coverage is 76.9% for coding-agent records and 67.1% for workflow records, 55.6% for communication, 50.0% for reasoning, and 19.2% for evolution records. The mechanisms that run a session are named in nearly every harness, while the mechanisms that change a harness over time are named in few.

The same contrast appears across strata (Table 8). Evolution records have current or historical cues in 18.0% of cells, against 74.5% for primitive records. Python repositories yield 53.8%, TypeScript 67.9%, and Rust 70.2%; source pools differ less (53.5%–64.1%).

Organized by the activity coordinates of Appendix A (Table 9), records with a design coordinate are the most widely cued (74.6%) and records with a verification coordinate the least (44.1%). The verification records split sharply. Layered permission and sandbox (P23) and scope-based authorization (P25) draw cues in all 36 families. Verify-on-stop guards




Figure 3 Coverage and diversity in the selected panel. (A) Family-level coverage for all 52 candidates with 95% Wilson intervals; colour denotes record family. Horizontal rules separate pattern families. (B) Distribution of observed-pattern richness across 36 families; the vertical line marks the median. (C) Evidence-layer composition across the complete 2,132-cell matrix. (D) Mean and 95% envelope from 5,000 random family orders. The unit is the repository family. Unobserved cells remain explicit and are not classified as absent mechanisms.

(P17), hybrid loop detection (P18), and the policy floor (P22) draw cues in 8 each, and syntax-aware command permissioning (P21) in 2. Harnesses widely name the boundaries of what an agent may do and far less often name checks on whether the agent's work is done.




Figure 4 Pattern coverage by repository family and evidence layer. The 52 candidate rows are shared across two panels that continue through the 36 repository-family columns. Cell shade records the number of independent evidence layers available in a family: current cue, historical cue, and canonical source locator. Thin white rules separate cells; horizontal black rules separate pattern families, and vertical black rules separate the frozen, research, and implementation-supplement repository pools. Complete pattern names and values are provided in Appendix A.2.

3.2.2 From Cues to Structural Candidates: Retrieval, Pointcut, and Contract Separate

Most observed cells rest on a current lexical cue (1,246 of 1,272). With a stricter rule of at least two current code paths plus support, 857 cells remain. Exact symbol-level matching narrows the set to 16 structural candidates, and coding these against their pointcut and contract fields separates them further. The pointcut held in six cells: hybrid loop detection (P18) in Pydantic AI and Roo Code, syntax-aware command permissioning (P21) in Qwen Code, OpenCode, and OpenClaw, and R02 in CarryOn. It did not hold in eight and stayed unresolved in two, P17 in DeerFlow and P21 in Gemini CLI. Five of the six held cells recorded all four contract fields: requires, ensures, invariant, and violation behavior. Context and trigger were clear in every cell; the open question was effect, that is, whether the mechanism actually changes control flow.

Table 9 Family cue coverage by activity coordinate. A record is counted under every activity in its inventory coordinate, so the three activity rows overlap. Mean coverage is the mean share of the 36 repository families with a retrieval cue; the median is in families. The values are re-tabulated from the coverage records in Appendix A.2.

Activity coordinate	Records	Mean coverage	Median families
A1 Design and implementation	31	74.6%	30
A2 Testing and verification	16	44.1%	10
A3 Maintenance and evolution	22	48.2%	19.5
All records	52	61.8%	27.5

Table 10 Observed transitions after a candidate trajectory's first checkpoint. Probabilities are conditional on `first_observed`. Intervals use 2,000 repository-cluster bootstrap resamples.

Next state	Count	Probability [95% CI]
Large path change	113	0.352 [0.233, 0.473]
Moved / renamed	83	0.259 [0.140, 0.418]
Persisted	72	0.224 [0.058, 0.400]
Expanded	28	0.087 [0.045, 0.132]
Contracted	23	0.072 [0.024, 0.123]
Signal gap	2	0.006 [0.000, 0.015]

Retrieval, structural match, pointcut, and contract are thus different questions that receive different answers on the same code. A keyword shows where to look. A pointcut shows that a mechanism intercepts the right join point. A contract shows what the mechanism promises when it fires. A responsibility record makes this distinction explicit. The six held cells, P21 in particular, are concrete exemplars of fully specified records. Appendix B.3 gives the per-cell evidence and its robustness.

3.2.3 Co-occurrence and Cue Trajectories: Cue Locations Move

Records co-occur in structured ways. Twenty-two of 1,326 candidate pairs were flagged at $q < 0.05$. The strongest pair, event-sourced conversation state with observer notifications, appears together in 29 of 36 families ($\phi = 0.817$). Shared architecture and repository lineage are plausible sources of such pairings.

Cue locations change often across releases. Across 1,272 trajectories and 2,611 frozen observations, 321 transitions followed a first observed cue (Table 10): 35.2% were large cue-path changes (95% family-cluster interval [21.3%, 47.3%]), 25.9% moves or renames, and 22.4% persistence. They come from 20 repositories in 16 families.

At least 398 trajectories (31.3%) contain a move, large path change, expansion, or contraction. Once a cue persists, it tends to keep persisting ($67/75 = 89.3\%$). Contracted cue paths often expand again ($16/33 = 48.5\%$), so cue locations do not change monotonically. No explicit retirement record was observed. The practical reading is that the code a record points to is reorganized often, which is why a record carries a lifecycle field.

3.2.4 How the Paper Uses the Audit

Taken together, the observations support cue-level recurrence as a descriptive premise. Every canonical candidate except E08 has a source locator, and the median family holds cues for




Figure 5 Candidate lifecycle trajectory structure. (A) Number of observed checkpoints per candidate–repository trajectory. (B) Most frequent normalized state sequences after removing leading `not_yet_observed` states. (C) Multi-checkpoint share and modeled-change share by record family. (D) Normalized Shannon entropy of the next observed state; higher values indicate more diverse observed transitions. A missing cue is a detector gap, not evidence of retirement. Sequence counts are descriptive for this checkpoint panel and are not probabilities for unseen repositories.

35 of the 52 records. On the 16 exact candidates, retrieval, pointcut, and contract separate. Records co-occur in structured ways, and the code they point to moves often across releases. How such movement affects task quality, safety, cost, or reliability is an outcome question.

The paper uses the audit in three ways. It supplies an instrument: 52 specifications with expressions, aliases, exemplars, and negative controls (Appendix A). It supplies worked examples for the detection and tracking case studies of Section 3.4. And it supplies a sampling frame for the next evidence step, an independently adjudicated, stratified sample that estimates cue-to-pointcut precision and recall (Section 7.4). The argument of this paper does not rest on the size of any gap between cues and contracts, and we do not claim to have measured one.

Because the instrument bounds what the audit can support, we also audited the cue path and made it reproducible (Appendix B.5). A deterministic runner emits cues sorted by stable identifier with no generation timestamp and records observability and truncation ledgers; repeated runs on the same inputs are byte-identical. A gated loop on labeled development fixtures verified three implementation defects—missed `checkpoint_` identifiers, a bare `route` alternative that matches configuration strings, and cues produced by comment-only mentions—and retained a combined candidate only because no positive regressed, every near miss stayed unmatched, and every frozen output hash was unchanged. That candidate is not applied to the frozen scan. Fixture checks are non-generalizing, and independent human adjudication of both the fixtures and the 16 coded candidates remains open, so these limits bound every observation in this section.

3.3 The A^2 Taxonomy of Harness Design Patterns

The inventory says which patterns exist, and the audit says where their cues appear. Neither says what a pattern protects, or when that protection is defined, tested, and revised. The A^2 (Activities $\times$ Assets) taxonomy supplies both coordinates (Figure 1). It crosses the two streams of Section 2.2. The activities axis indexes *when* an obligation is defined, tested, and reconsidered. The assets axis states *what* must remain stable and what may change. Its

foundations are classical patterns, modular decomposition, and test seams [16, 8, 38, 15]. A^2 is a proposed coordinate system for organizing records, and Section 5.4 states how its value as a lens can be tested.

3.3.1 The Activities Axis

The axis has three activities, taken from the activities stream: design and implementation (A1), testing and verification (A2), and maintenance and evolution (A3). A1 declares authority, state ownership, boundaries, and anticipated change points. A2 exercises those declarations under malformed results, partial failure, adversarial instructions, and task variation. A3 uses operational or repeated-run evidence to decide whether the existing seam still absorbs required change. If it does not, the A3-to-A1 return is *re-generalization*—redesign of the contract, a step beyond routine tuning. The axis is an evidence cycle that any record can re-enter.

3.3.2 The Assets Axis

The axis has two assets, taken from the assets stream. The *protected contract* is the behavior that clients, operators, and auditors may rely on: an interface together with its authority, state, and acceptance semantics. The *permitted variation* is the set of changes that preserve that contract, reached through a named variation mechanism such as an adapter, hook, policy profile, or router. Two probes locate the boundary between them. A *substitution probe* changes an adapter, routing policy, evaluator rubric, or context projection while holding the declared invocation, authority, state, and acceptance semantics fixed. If the replacement remains admissible, it lies inside the variation seam. A *violation probe* asks which change would invalidate the design: altering an error meaning, lowering a permission floor, discarding required provenance, or letting a component approve its own output usually changes the protected contract. The contract is therefore a semantic commitment, often broader than an API, and permitted variation is the configuration that preserves it.

The boundary is also setting-dependent. A sandbox provider may vary while the execution-isolation guarantee remains fixed; an evaluator rubric may vary while independent acceptance remains fixed; a memory projection may vary while event identity and ordering remain fixed. In another setting, one of those mechanisms may itself be protected. A record must therefore state the actor allowed to vary the asset, the evidence used to check the invariant, and the response to a violation. Ambiguity is resolved by competing contract hypotheses and tests. Paradigm, quality, and human/agent factors qualify these judgments without adding new record fields [14].

3.3.3 From Coordinates to Pattern Records

Pattern discipline governs how a recurring mechanism becomes revisable engineering knowledge. It extends cataloging with a decision: whether a recurring mechanism should be reused, revised, or retired. Five obligations define a pattern record. *Boundary:* state the context, trigger, structure, effect, and a negative case outside the pointcut. *Contract:* name authority, precondition, invariant, postcondition, and violation behavior. *Variation:* separate the frozen point from the hot spot and identify their connecting mechanism [16, 8, 15]. *Evidence:* distinguish retrieval cues, source instances, pointcut matches, contract tests, and measured outcomes. *Lifecycle:* version the record and state retest, migration, and retirement conditions. A candidate is promoted once every obligation is verified. The records are catalog-agnostic:

Table 11 What a disciplined pattern record adds to a mechanism description. The example context is replacing a tool provider or adapter.

Question	Mechanism description	Disciplined pattern record
When does it apply?	Names an adapter, authorization check, or confinement mechanism.	States the recurring problem, context, assumptions, and provenance.
What remains, and what may vary?	Describes an implementation or interface.	Separates the protected contract from the permitted provider, schema, or adapter variation.
How should the change be tested?	May supply local examples or component tests.	Names authority boundaries, consequences, and tests for bypass, interference, or invalid combinations.
What happens after later updates?	Leaves lifecycle decisions to the implementer.	States re-evaluation evidence and keep–adapt–retire conditions across A1–A3.

they let a familiar label, repeated token, or single implementation carry exactly the evidence it has. Table 11 contrasts a record with a mechanism description.

Three properties of this schema bound what we claim for it. The five obligations are one candidate field set. The normative minimum of Section 1 holds whichever field set a community adopts, and the value of this one is the subject of Hypothesis 2. A record also has a cost; whether its benefit repays that cost is part of what the record-utility study measures. Finally, a record documents an obligation and does not enforce it. Authorization and auditability need runtime mechanisms, which Hypothesis 1 tests separately.

The distinction applies throughout the harness lifecycle. A mechanism list answers "what components or behaviors have been seen?" Pattern discipline adds "in what context does it apply, which contract does it protect, what may vary, who has authority, what evidence checks it, and when should it be retested or retired?" The first supports retrieval; the second supports design comparison, verification, migration, and maintenance.

A concrete example makes the comparison explicit. Suppose a team replaces a tool provider or adapter. A mechanism list can identify adapters, authorization, and isolation, but it need not state the contexts in which each applies or the obligations that survive replacement. Table 11 states what a disciplined pattern record would add. The comparison is an illustration evaluated by the falsification tests in Section 5, not an established empirical advantage.

3.4 Using the Taxonomy: Mapping, Detection, Tracking, and Analysis

The taxonomy supports four uses. It *maps* a record to activity and asset coordinates. It tells a detector what to look for when it *detects* the record in a repository. It gives a history something to follow when it *tracks* the record across versions. And it supports the *analysis* of relations among records. We illustrate each use with case studies drawn from the inventory and the audit.

3.4.1 Mapping Records to Coordinates: Nine Analytical Cases

Appendix A assigns every record an activity coordinate, a proposed protected contract, and a proposed permitted variation. Section 3.2.1 re-tabulates the exploratory cue coverage by




Figure 6 Analytical coverage of the declared inventory. Dark segments show records selected for the nine analytical cases; light segments show the remaining records in each source family. The cases include 22 of 52 records and all five families, but selection is uneven and argument-driven. Counts describe this paper's declared inventory, not field prevalence or pattern effectiveness.

those coordinates.

Table 12 selects nine analytical cases spanning 22 inventory records across design, verification, and evolution (Figure 6). They were selected to expose alternatives, dependencies, complementary obligations, and conflicts. Each case separates three evidence statuses: the cited source reports a mechanism; the protected contract and consequence are our interpretation; and the discriminating test is a proposal. Section 5.4 specifies how independent analysts could test the reliability and coverage of those annotations.

1. Delegation is not handoff. Anthropic's orchestrator–workers workflow delegates dynamically generated subtasks [2], whereas OpenAI's handoff guidance transfers control to a specialized agent [36]. Both customize who performs work, but their frozen contracts differ: a worker returns a result to a coordinator; a handoff must specify what state and authority move with control. A2 therefore needs different probes for missing worker results and circular or overprivileged handoffs. The organizational drawing alone does not capture this distinction.

2. An extension interface does not fix execution semantics. Consider the middleware, provider-adapter, and deferred-loading entries P04/P08/P09 [6]. An adapter translates an invocation; an interceptor can also reorder, reject, or repeat it; a lazy registry changes when a capability becomes visible. All may preserve a nominal tool schema while changing observable behavior. Their A1 commonality is an extension seam, not interchangeability. A2 should test error translation, retry side effects, and authorization after loading. Retiring a wrapper after a model upgrade must preserve its external obligations, not just its score.

3. Communication patterns supply contracts, not only labels. The MCP survey covers Mediator, Observer, publish–subscribe, and Broker in agent communication [40]. Our reading separates the participant/message contract from routing and subscription policies. Replacing a mediator with a topic bus changes who receives evidence, who can invoke whom, and where ordering is enforced; it is not merely renaming coordination. A3 also matters: stale observers, schema changes, and revoked participants can invalidate an A1 contract. This case acknowledges classical pattern reuse while exposing lifecycle questions that a communication topology alone leaves unanswered.

4. Authorization and confinement are separate seams. The policy-floor, sandbox, and scoped-profile mechanisms provide an illustrative case [6]. A task-specific profile may tighten

Table 12 Nine analytical cases located with the same A^2 grammar. The case names and cited mechanisms are source-reported; the contract, variation, and consequence columns are our proposed interpretation, and Section 3.4.1 gives the corresponding discriminating tests. The cases are analytical illustrations selected for contrast. Complete records, sources, and provenance qualifications are in Appendix A.1.

Case / activity	Assets: proposed interpretation		Proposed consequence
	Protected contract	Permitted variation	
1. Delegation vs. handoff *A1 · Design*	Task/result envelope; explicit control ownership.	Assign workers by dispatch; transfer roles by handoff.	Both distribute work, but transfer different authority and context.
2. Tool extension *A1 · Design*	Invocation/result schema; error semantics.	Swap adapters; intercept middleware; load tool registries lazily.	Compatibility need not preserve order, permissions, or side effects.
3. Message topology *A1/A3 · Design and evolution* [40]	Message schema; delivery semantics; participant authority.	Mediate or broker messages; register observers or topics.	Decoupling creates ordering, trust, and subscription obligations.
4. Permission layers *A2 · Verification*	Minimum authorization; execution-isolation boundary.	Compose scoped profiles; swap sandbox adapters.	A correct policy decision does not prove execution confinement.
5. Feedback vs. acceptance *A2 · Verification*	Feedback interface; protected acceptance/exit rule.	Vary rubrics in evaluator loops; vary checks at exit hooks.	Improvement is not authorization; both may share faulty checks.
6. Durable state *A1/A3 · Design and evolution*	Event identity; ordering; branch provenance.	Swap context projectors and recovery policies through event/branch APIs.	History enables inspection, not reversal of external effects.
7. Context revision *A2/A3 · Verification and evolution* [43]	Retained-evidence contract; memory-update contract.	Change projections by compaction; add feedback memories by reflection.	Both alter later observations and may lose evidence or retain bad advice.
8. OO-Harness *A1/A3 · Design and evolution* [25]	Base interfaces; specified inherited behavior.	Override by inheritance; specialize tasks by router dispatch.	A narrow edit seam may hide parent coupling; dispatch does not enforce invariants.
9. Evolution constraints *A2/A3 · Verification and evolution* [53, 59]	Evaluation access; objectives; acceptance protocol.	Bound edits and compose candidates within a controlled search space.	Local gains may overfit selection feedback or hide objective trade-offs.

a protected authorization floor, but a correct approval decision says little about an execution adapter that permits additional effects. Conversely, an isolated environment does not decide whether an action is authorized. The A^2 analysis requires both contracts and tests the seam between them: scope inheritance, revocation, and enforcement after tool substitution. Policy-floor redesign is privileged re-generalization, not ordinary agent customization.

5. Feedback is not acceptance authority. Evaluator–optimizers give revision feedback [2]; a verify-on-stop design intercepts termination before accepting the artifact. These functions can coexist, but neither a persuasive critique nor a passing checker proves that the acceptance path is protected. The intended frozen point is the acceptance protocol, while project checks are hot spots reached through an exit hook. A2 must test bypasses, solver edits to checks, flaky failures, and budget exhaustion. Changing a rubric and changing who may approve that rubric are different operations.

6. Durable history is not reversible execution. The log-as-queue, event-sourcing, and session-tree entries P13/P14/P26 connect A1 execution to A3 recovery [6]. Stable identities and ancestry can support multiple context projections and branch policies, but a replayed tool call may repeat an external action. A maintenance change that prunes history can also remove evidence required by A2. The seam therefore needs an explicit retained-evidence and side-effect contract; an append-only log or a rollback command is not sufficient. Recovery tests should inspect both restored local state and duplicated external effects.

7. Compaction and reflection alter evidence differently. P27 compaction changes what history is projected into context [6]; Reflexion uses verbal feedback across attempts [43]. One can discard a necessary fact, while the other can preserve mistaken advice. Their shared activity is context revision, not an identical memory mechanism. The A1 interface should state provenance and update authority; A2 should test retained facts and contaminated feedback; A3 should specify when a summary or reflection is revised or removed. A token-saving policy is not successful if it invalidates a later check.

8. Inheritance localizes edits but does not freeze behavior. OO-Harness supplies a concrete inheritance-based mechanism and polymorphic task routing [25]. A base interface can make permitted edits visible, but overrides may still violate assumptions elsewhere in the hierarchy. Our proposed frozen point is therefore the specified inherited contract, not the mere existence of a parent class [16]. The case motivates regression tests across subclasses and routes, and a comparison with composition under matched changes. Section 4.1 examines how agent-driven editing closes the A3-to-A1 loop within this space.

9. The mutation seam and the acceptance rule are different assets. RRSI regularizes repeated harness improvement; Harmony considers multi-objective evolution and composition [53, 59]. These are not a head-to-head mechanism comparison. Together they motivate separating what a candidate may edit from what evidence admits it. Edit budgets and composition policies can vary within an experiment, while evaluation access and declared objectives must remain controlled. Repeated selection feedback cannot double as an untouched final test. An A3 gain that changes its own acceptance criterion does not validate the A1 generalization.

Across the cases, one question recurs: what change can the asset absorb, and what evidence would force contract renegotiation? In every case the consequence column names the failure that would be hidden by a catalog entry that records only the mechanism. Each case thus contributes a contract and a proposed rejection test, and the protocols in Section 5 turn the cases into comparative experiments.

The cases establish expressiveness: the taxonomy can state distinctions that a mechanism name leaves implicit. They are argued from the cited sources and from the semantics of the

mechanisms. Whether independent analysts assign the same coordinates, and whether A^2 covers more or costs less than an existing scheme, are empirical questions with a stated test (Section 5.4).

3.4.2 Detecting a Pattern in a Repository: Pointcuts and Contracts

A coordinate becomes detectable once it is written as a specification. The *pointcut* states context, trigger, structure, and effect: where in execution the pattern applies and what it changes. The *contract* states what the mechanism requires and ensures, the invariant it protects, and its behavior on violation. A *negative control* names a look-alike that lies outside the pointcut. Table 13 gives the specifications for three verification records.

The specifications make the model-coded dispositions of the exploratory audit readable (Section 3.2.2; per-cell votes in Table 23). The dispositions are one model's coding under 200 prompt profiles, so we use them as worked examples of how a specification is applied, not as verified findings about the repositories. For syntax-aware command permissioning (P21), the matcher selected seven repositories. Three gained majority support (Qwen Code, OpenCode, and OpenClaw), where parsed commands feed a permission decision. Three were rejected under every profile (DeerFlow, Codex, and Orca), because the declared effect or boundary was absent. Gemini CLI stayed unresolved: parsed commands feed its confirmation policy, but a coarse fallback remains disputed. For hybrid loop detection (P18), Pydantic AI and Roo Code were supported under every profile and Mastra was rejected. For verify-on-stop (P17), the one selected cell, DeerFlow, stayed unresolved. A post-completion acceptance verdict exists, but checker exceptions do not change the completed status and no enforced stop gate is shown. The negative control addresses exactly this case: a check that runs after completion is feedback, and only an intercepted stop is acceptance. Across all 16 cells, the profiles agreed on every context and trigger judgment and varied on four effect judgments. In these cells and under these prompts, variation therefore concentrates at the effect, which is where the contract begins. Whether effect is the hard step in general is a question for independently adjudicated samples.

A matched pointcut is still short of a complete record. The Verify-on-Stop record below states what a detected instance must supply; it instantiates Case 5. Figure 7 draws the same record as an analytical UML class view: who proposes completion, who verifies, and which gate alone may accept. Appendix A.4 draws three further class views, and Appendix A.1 gives the complete record inventory. Each view reconstructs a proposed contract, not an execution observed in a repository.

An A2 record: Verify-on-Stop.

Context and problem. A tool-using agent can claim completion without checking the resulting artifact. A guard should prevent premature acceptance while making failures actionable. *Frozen point and hot spot.* The termination interception and evaluator access boundary are protected contracts. Project-specific tests, check selection, and diagnostic formatting are customizable. Test changes have a separate approval process from ordinary solver changes.

Variation mechanism. A controlled exit hook runs the checker and returns a structured verdict. A failure can reopen the rollout with diagnostics, subject to retry and resource bounds. Budget exhaustion or an unavailable evaluator must be distinguishable from acceptance.

Consequences. Verification adds latency and can reject correct work when tests are flaky or incomplete. Model-based checks can be correlated with the solver. The guard does not protect a writable test suite merely because it is outside the solver's prompt.

Table 13 Pointcut and contract specifications for three verification records. The pointcut (context, trigger, structure, effect) states where a record applies and what it changes; the contract (requires, ensures, invariant, violation) states what it protects; the negative control names a look-alike outside the pointcut. The text is taken from the study's frozen pattern specification, which holds one such entry for each of the 52 records.

Field	P17 Verify-on-stop guards	P18 Hybrid loop detection	P21 Syntax-aware command permissioning
Pointcut			
Context	The agent proposes completion after producing an artifact.	Successive agent observations or actions can repeat without progress.	An agent proposes a shell command with security-relevant structure.
Trigger	A stop or finish action is requested.	A loop signal crosses a configured threshold or composite condition.	The command is about to be parsed, classified, or executed.
Structure	Exit interception, verifier execution, and accept-or-continue result.	Repetition signals, thresholds, and an intervention interface.	Shell parser, normalized command tree, policy evaluator, and execution handoff.
Effect	The stop is accepted only after the verifier reports sufficient evidence.	The harness diagnoses a loop and stops, redirects, or escalates.	Authorization uses parsed operations and a parse failure cannot fall through to execution.
Contract			
Requires	Stop can be intercepted and at least one verification is available.	Action or observation history is available in comparable form.	The command is representable by a parser or rejected before execution.
Ensures	Failed verification returns actionable feedback or blocks completion.	Intervention is attributed to explicit evidence and recorded in the trace.	Every subcommand and redirection is covered by a policy decision.
Invariant	The same acceptance gate cannot be bypassed by another stop path.	A detector cannot block all exploration solely because outputs are similar.	Parsed intent and executed command refer to the same normalized operation.
Violation	Unavailable or flaky verifier yields explicit unknown or failure, not silent success.	Detector error, disabled mode, or false positive has a recoverable path.	Unsupported syntax fails closed or requests explicit review.
Negative control	Tests run by the user after the run are not verify-on-stop.	A recursion depth limit alone is not semantic loop detection.	A substring denylist is not syntax-aware permissioning.




Figure 7 The Verify-on-Stop record (P17) as an analytical UML class view. Each class box is a proposed participant role; its operation compartment lists the calls that role receives. Numbered dashed arrows are call dependencies, and brown arrows are returns or failures. The relationship panel restates every call; the lower panels restate the record's pointcut, contract, variation, test obligation, and negative control from its frozen specification. The view is an analytical reconstruction of the proposed contract, not an observed execution trace or a repository class declaration. The invariant is the point of the record: the acceptance gate cannot be bypassed by another stop path.

Evidence and retirement. Compare otherwise matched runs with and without the hook, recording incorrect acceptances, incorrect rejections, cost, and escalation. A faster or stronger model is not sufficient reason to remove enforcement; removal must preserve the acceptance contract through another evaluated mechanism.




Figure 8 Representative calendar-time pattern trajectories. Each row is a pattern–repository trajectory. The horizontal axis gives the frozen commit or release date, not a normalized lineage time. Marker shape and colour encode the detector-derived lifecycle state, and marker area indicates the number of detector cues at that checkpoint. The selection covers six trajectories and 24 checkpoints with stable, changing, lineage-crossing, and gap/recovery states; it is illustrative rather than a probability sample. A detector gap is not interpreted as retirement, and the lines do not establish source-level architectural redesign.

3.4.3 Tracking a Pattern across Versions

The A3 activity asks whether a record persists, moves, or is replaced. Tracking follows one record–repository pair across frozen releases and labels each checkpoint with a detector-derived state. Figure 8 shows six illustrative pattern–repository trajectories on a calendar-time axis. The selected 24 checkpoints span stable continuity, cue-intensity and path changes, cross-repository lineage persistence, name or location movement, and detector gap recovery. Lines connect sampled observations only; they do not interpolate unobserved change or establish retirement.

The six trajectories cover four situations. *Persistence across a lineage:* cues for the minimal linear loop (P01) and the reason–act loop (R01) appear in SWE-agent from v0.1.0 (April 2024) and persist into its simplified successor mini-SWE-agent through v2.4.6 (July 2026); cues for the coordinator–worker spawn flow (P12) persist across the migration from AutoGen to Agent Framework. *Reorganization within a repository:* cues for layered permission and sandbox (P23) in OpenHands show large cue-path changes at both later checkpoints between 0.3.0 and v1.37.0, and routing (W02) in OpenAI Agents JS changes paths once and then persists. *Detector gap and recovery:* Observer (C02) has no cue at the two earliest Cline and Roo Code checkpoints and becomes visible at the later ones, which is recorded as a gap and not as absence.

A cue path that moves shows that code was reorganized. It does not show whether the contract survived the move. Each specification therefore carries an evolution question that a source review must answer. For P23 it asks whether one policy surface evolved into layered cross-platform enforcement; for P12, whether delegation gained nested history, approvals,

and a background lifecycle; for P17, whether completion verification became mandatory instead of advisory. Answering these questions requires commit-level adjudication, which the present audit leaves to the next study (Section 7.4). The Session-Tree Recovery record states what such tracking must preserve; it instantiates Case 6.

An A3 record: Session-Tree Recovery.

Context and problem. Long tasks can require revisiting a decision without discarding the entire execution history.

Frozen point and hot spot. Stable identifiers, branch relationships, and provenance form the record contract. Branch selection, checkpoints, and summarization are variable policies. Their interface must state what happens to pending actions and external side effects.

Variation mechanism. A branch/checkpoint API separates task-specific recovery from the representation of durable state.

Consequences. Branching retains more data and may expose sensitive history. A summary can omit a fact needed by a later verifier. A rollback of the local record cannot undo an irreversible external action.

Evidence and retirement. Inject interruptions at defined points and check recovery, duplicate side effects, and provenance retention. State migration is privileged re-generalization if it breaks the old contract, not a routine pruning policy.

3.4.4 Analyzing Relations among Patterns

Relations among mechanisms are optional metadata that extend the contribution. This subsection provides a notation for machine-readable catalogs, graph representations, or annotation studies; validating the proposed types for completeness and consistent annotation is future work.

Let m_i and m_j be mechanism records. We write

$$m_i \xrightarrow[\phi]{\rho} m_j,$$

where ρ names the connection and ϕ states the context or precondition under which it is claimed. No edge is context-free. The provisional connection types are:

- *requires:* m_i's stated contract is valid only if m_j supplies a named obligation;
- *complements:* the records address distinct obligations of the same problem, and neither is presented as sufficient;
- *specializes:* m_i narrows m_j's context, invariants, or permitted variation without contradicting them;
- *alternates with:* the records address the same problem but make different trade-offs or authority assignments; and
- *conflicts with:* their stated assumptions or invariants cannot hold together in the named context.

Activity order supplies a separate lifecycle connection: a pattern can be introduced in A1, probed in A2, adapted or retired in A3, and returned to A1 when its protected contract must change. These annotations are proposals to document and test, not universal laws or observed causal effects.

As a worked fragment, a tool adapter requires an authorization boundary because schema compatibility does not grant permission. A sandbox complements that boundary because approval and execution confinement address different obligations. A workspace profile

specializes the authorization policy; delegation alternates with handoff because it retains rather than transfers control; and an evaluator–optimizer conflicts with protected acceptance when it can rewrite the evidence that authorizes termination. Adding a sandbox therefore does not repair a missing authorization decision.

The nine cases in Table 12 can be encoded as follows; the inventory IDs retain their meanings from Appendix A.1.

1. Delegation → handoff:
   $\rho =$*alternates with*, $\phi =$*control owner* (A1: W04/W07).
2. Deferred loading → tool extension:
   $\rho =$*specializes*, $\phi =$*on-demand visibility* (A1: P04/P08/P09).
3. Mediation → publish–subscribe:
   $\rho =$*alternates with*, $\phi =$*routing topology* (A1/A3: C01–C04).
4. Sandbox → policy floor:
   $\rho =$*complements*, $\phi =$*decision vs. confinement*
   (A2: P22/P23/P25).
5. Evaluator–optimizer → verify-on-stop:
   $\rho =$*conflicts with*, $\phi =$*reviewer can edit checks* (A2: W05/P17).
6. Session branching → event history:
   $\rho =$*requires*, $\phi =$*recoverable ancestry* (A1/A3: P13/P14/P26).
7. Compaction → reflection memory:
   $\rho =$*alternates with* or *complements*, $\phi =$*context-revision method*
   (A2/A3: P27/R02).
8. Task subclass → base harness:
   $\rho =$*specializes*, $\phi =$*inherited contract preserved* (A1/A3: E01).
9. Regularized search → multi-objective evolution:
   $\rho =$*complements*, $\phi =$*different risks* (A2/A3: E03/E04).

4 Structural Drift: Software versus Harness Engineering

Harness engineering inherits the assets and activities of software engineering, but three of their assumptions drift (Table 14). In software engineering a human team typically closes the maintenance loop, people read and apply the patterns, and an asset's value changes mainly with requirements or dependencies. In harness engineering the loop can close through the system itself, agents consume and revise the patterns, and a mechanism's value also depends on the model. These are shifts of emphasis and not a clean dichotomy: software engineering has automated maintenance and self-adaptive systems [51], and its assets age for many reasons. The drifts name what becomes the default case for harnesses. Each is an analytical claim. For each we state the difference, the risk or confound, and a rejecting test, and we note where the exploratory audit of Section 3.2 bears on it.

4.1 Evolution Should Be Closed-Loop Self-Improvement

Difference. In ordinary software maintenance, developers propose changes and a separately administered process admits a release. A closed-loop harness can instead use its own traces to propose, probe, select, and reuse successor logic. OO-Harness evolves subclasses and routes tasks among them [25]; Harness^2 carries adaptation experience across iterations [55]; and RRSI and Harmony Harness constrain repeated search or expose functionality–security trade-offs [53, 59]. These systems demonstrate the mechanism; safe autonomous maintenance

Table 14 Structural drift from software engineering to harness engineering. Each row names an assumption that software patterns make, how it shifts for harnesses, and what a responsibility record must add. The rows are proposed shifts of emphasis; each carries a rejection test in the text.

Dimension	Software engineering	Harness engineering	What the record must add
Evolution loop (Section 4.1)	Developers typically propose changes; a separately administered process admits a release.	The harness can use its own traces to propose, probe, select, and reuse successor logic.	An evolution envelope: variation searched within an epoch, the contract revised only across epochs under separate authority.
Pattern consumer (Section 4.2)	Human designers, testers, and maintainers read patterns and apply judgment.	Agents design, verify, and evolve the harness; humans hold the named authority.	Machine-checkable pointcuts and tests, stated authority, context visibility, and control ownership.
Utility lifetime (Section 4.3)	An asset's value changes mainly with requirements, dependencies, or implementations.	A mechanism may also gain or lose value when only the model changes.	A boundary between replaceable implementations and protected obligations, with a controlled removal test.

in general is the open question our test addresses. The adaptation is system-level, distinct from model training with AI feedback [4].

We take the position that harness evolution should be closed-loop. A harness is modified repeatedly as models, tools, and tasks change, and its own traces are direct evidence about where it fails. Using that evidence systematically is preferable to ad hoc manual re-tuning, provided that the loop is bounded. The question is then not whether an agent may edit the harness. It is which part the agent may edit, and on what evidence.

Design patterns supply the bound. A record separates the two assets, so that the loop can search the permitted variation while the protected contract is held fixed. For closed-loop self-improvement, the same record defines an evolution envelope $\mathcal{D} = (C, \mathcal{V}, \mathcal{A}, \mathcal{E}, \mathcal{L})$: protected contract, permitted variation, authority, acceptance evidence, and lifecycle rule. A change is admissible only inside $\mathcal{V}$, under $\mathcal{A}$, while preserving C and satisfying $\mathcal{E}$; otherwise it returns to A1 for contract redesign. This specialization shows the general record at work in a particularly demanding setting.

The invariant part is not immutable. "Frozen" means protected within a stated scope and authority. We therefore distinguish two epochs. Within a *variation epoch*, the loop proposes and admits changes inside $\mathcal{V}$ at the pace of its own feedback, while C, $\mathcal{A}$, and $\mathcal{E}$ stay fixed. At an *epoch boundary*, accumulated evidence may show that the declared variation no longer absorbs the required change. The contract itself is then redesigned through the A3-to-A1 return, under a separate authority and with evidence that the candidate could not influence, and the record is re-versioned. Invariants thus evolve as well, but on a longer epoch and through a different gate. This is separation of concerns [38, 44] applied to rates of change: fast change and slow change are assigned to different assets, authorities, and evidence.

The exploratory audit is consistent with this being an open design space. Evolution

records have the thinnest cue coverage of the five families, 19.2% mean family coverage against 76.9% for coding-agent records, and the four evolution-record cells that the exact matcher selected were not supported under any prompt profile (Section 3.2.2). These are retrieval results and four matcher-selected, model-coded cells, so they do not characterize the panel. They do suggest that an evolution envelope is not something a lexical instrument retrieves from source today, which is one reason to state it in a record.

Risk or confound. The proposer, selection data, and acceptance rule can become statistically or operationally coupled. A candidate may memorize selection tasks, rewrite the checks that admit it, or improve task success by weakening another objective. Isolating those causes takes more than inheritance, a required `super()` call, an edit budget, or a strong aggregate score. Published system configurations also vary models, search budgets, and routing, which motivates a controlled comparison.

Rejecting test. Treat one predeclared sequence of maintenance changes as the experimental unit. Randomize matched sequences to bounded agent adaptation or human-maintained/no-adaptation controls; hold the initial harness, model, tools, edit budget, and selection feedback fixed. Evaluate each promoted version on inaccessible task and safety cases. Reject the claim that closed-loop evolution is a reliable general advantage if it fails a prespecified held-out benefit margin or causes more protected-contract violations than the controls. The run record and the data separation are defined below.

For every run, record model and decoding configuration; instructions and context assembly; tool and environment versions; state policy; permissions and stopping rules; evaluator; and resource budget. Also record role-level context visibility, control ownership, messages, routing, and aggregation. This identifies the treatment behind a system label and permits reconstruction of correlated or conflicting failures.

For the closed-loop test, the experimental unit is a complete, predeclared maintenance sequence, not a candidate patch or a catalog record. Give bounded adaptation, human-maintained, and no-adaptation arms the same initial harness, model, tools, change requests, selection cases, feedback, and edit budget. Record the protected core, permitted edits, every proposal and promotion, fallback behavior, and acceptance authority. Score promoted versions only on final task and safety cases unavailable during proposal and selection. Pilot the maintenance sequences for feasibility without exposing final cases, then power the confirmatory study over multiple independent sequences rather than treating candidate patches as replicates. This design tests system-level adaptation; it does not turn a class hierarchy, `super()` call, or aggregate score into a safety boundary.

A lifecycle record needs only a transition, its evidence, and its authority: introduce, retain/adapt, or retire the asset, with contract redesign marked separately. Age and agent preference are not evidence. Practitioner discussion provides context for this proposed reporting field [50]; it is not evidence that the transitions are autonomously reliable.

For acceptance, assign development, selection, and final evaluation to disjoint data and record who can read or write each set. Any case whose outcome informs a proposal or promotion belongs to selection, regardless of a "holdout" label. The final evaluator returns no candidate-specific feedback before the experiment ends. Preregister task and safety outcomes plus escalation for missing or conflicting evidence. Record evaluator versions, blinded scoring, inter-rater reliability where judgments are subjective, and every excluded or aborted run. A task gain cannot compensate for crossing a protected permission or security threshold. RRSI and multi-objective evolution motivate this separation [53, 59]; neither establishes universal convergence.

4.2 Human Factors Become Agent Factors

Software design patterns were written for people. They guide human designers when they design and implement a system, human testers when they test and verify it, and human maintainers when they maintain and evolve it. Their prose form, with intent, forces, and consequences, assumes a reader who exercises judgment. In harness engineering the same three activities are increasingly carried out by agents: one agent composes a workflow, another reviews its output, and a self-improvement loop revises the harness. A harness design pattern must therefore drive agentic evolution as well as inform human practice, and this changes what a pattern has to contain. A human reader often infers who is allowed to change a component; an automated proposer works more reliably when the authority is stated. A human tester can often recognize a look-alike; a detector needs a pointcut and a negative control. A human maintainer can judge when a design is exhausted; a loop needs an acceptance rule and an epoch boundary. The contrast is one of degree. People also misread authority, and agents can infer context that is left implicit. The defensible claim is that machine-actionable processes benefit from explicit, checkable semantics, and that people benefit from them as well. The record fields of Section 3.3.3 are these semantics written down. People do not leave the loop: they hold the authority that the record names.

Difference. Conventional human factors asks whether people and teams can understand, coordinate, and maintain a design. A harness must also specify the observable rollout: which agent role receives which context and tools, who owns control after delegation or handoff, how trajectories are aggregated, and what feedback reaches later attempts. Centralized, decentralized, hierarchical, and adaptive topologies make these runtime assignments part of the treatment rather than merely an organization chart [61].

Risk or confound. Shared context or feedback can correlate errors; parallel workers can conflict; and a hierarchy can hide routing failures behind an aggregate score. Differences attributed to a mechanism may instead come from unequal context, authority, token allocation, or review evidence. Topology also changes latency, cost, and reconstructability after failure [61, 1]. Identifying the claimed mechanism therefore requires role-level evidence beyond task success [58].

Rejecting test. Use matched task–seed pairs as experimental units in a factorial intervention on topology and context/authority visibility. Keep model, tools, prompts, total budget, and acceptance checks fixed; record role-level trajectories rather than only final answers. Make contract violations and blinded failure-attribution accuracy primary; treat task, cost, latency, correlation, and provenance measures as secondary. Reject the claim that agent-factor annotations are necessary explanatory variables if topology and visibility interventions neither change these outcomes within prespecified equivalence margins nor improve failure attribution over an ordinary team-level record.

In the exploratory audit, the vocabulary of coordination is widely retrieved: cues for routing (W02) and the coordinator–worker spawn flow (P12) appear in all 36 families, and cues for orchestrator–workers (W04) and decentralized handoffs (W07) in 30 and 29. Whether the corresponding context visibility and control ownership are declared is a contract-level question that cue coverage does not answer; it is what the role-level record is for.

4.3 Mechanisms Have Model-Conditional Utility Lifetimes

Difference. Conventional assets usually change value when requirements, dependencies, or implementations change. A harness component can also gain or lose value when only the underlying model changes: a model may absorb decomposition while permissions, acceptance,

Table 15 Proposed scope-relative deletion boundary. Replaceable components still require a controlled removal test; protected contracts require authorized revision.

Protect within scope	Keep replaceable
Evaluator access and acceptance protocol	Task tests and model-based rubrics
Enforced permission floor	Tool adapters and policy profiles
Durable audit and provenance contract	History projections and summaries
Resource and termination bounds	Planners, routing heuristics, and prompts

and audit remain external obligations. We call the setting-specific decay of measured benefit or assumptions a *model-conditional utility lifetime*: the range of model snapshots over which a mechanism exceeds a prespecified benefit threshold. The construct is agnostic to the shape of decay. A documented tool-removal case shows a team retiring most of an agent's tools [47]. That case redesigns the architecture and is not a controlled model-only contrast, so it motivates the construct without demonstrating it. Demonstration takes the factorial design below, which crosses model snapshot with mechanism.

Risk or confound. A before/after model comparison can mistake model improvement for successful harness deletion, or retain scaffolding whose cost now exceeds its benefit. Worse, deleting an apparently absorbed cognitive aid can silently remove an enforcement contract. Table 15 therefore separates replaceable implementations from scope-relative obligations; it is our proposed boundary, to be checked by the removal test below.

Rejecting test. For each model snapshot, randomize matched task–seed pairs to the pattern or a simpler contract-preserving baseline, under equal tool and cost budgets. Measure task and safety outcomes, cost, and interactions between model snapshot and pattern. Estimate the first snapshot at which the prespecified net-benefit contrast falls below its threshold, without requiring monotone decay. Reject the model-sensitive lifetime account if sufficiently precise estimates show neither threshold crossing nor model–pattern interaction across the precommitted snapshot range. Do not retire an enforcement mechanism unless its replacement separately preserves the protected outcome. The measurement protocol at the end of this section specifies the design.

The exploratory audit cannot estimate a utility lifetime, because cue paths carry no measurement of utility. What it adds is narrower: 51.2% of trajectories have no second checkpoint, and the instrument found no explicit retirement record in any trajectory. Removal decisions are thus not something the sampled evidence makes visible, which is why the lifetime has to be measured by the protocol below.

In the lifetime measurement, the experimental unit is a matched task–seed pair within a model snapshot. Before observing outcomes, choose snapshots, held-out task families, a simpler contract-preserving baseline, cost envelope, safety floor, and practical-benefit threshold. Within each snapshot randomize pairs to the pattern or baseline while holding tools, permissions, and evaluator fixed. Define net benefit before observation, including task and safety outcomes, cost, and any non-compensable safety floor. Estimate the pattern contrast and its interaction with model snapshot using simultaneous intervals or another predeclared multiplicity procedure. The first snapshot at which the contrast falls below the threshold gives a setting-specific lifetime bound; censor it if observation ends first, and allow later snapshots to cross back above the threshold. Reject the model-sensitive lifetime account if precise estimates show neither threshold crossing nor interaction over the declared snapshot range. This test does not authorize removal when the baseline fails the safety floor.

5 What Would Falsify This Position

Section 4 states three proposed differences and their local rejection conditions. This section makes two bounded empirical claims falsifiable: the value of external enforcement and the utility of the proposed record schema. They complement the normative minimum, which rests on accountability rather than on outcome data. The exploratory audit in Section 3.2 motivates these tests, and the protocols specify the causal evidence. Every test preregisters units, primary estimands, practical margins, exclusions, budgets, power, missing-run rules, and multiplicity control. Equivalence is claimed only against explicit margins.

The two studies below supply the complementary causal evidence on enforcement and pattern records, using interventions assigned independently of observed task outcomes. Their current status is *design only*; no arm in either study has been executed, so this section reports prospective decision rules and design simulations rather than hypothesis-test results. Each rule has three outcomes: supported, rejected, or inconclusive. A study that fails to support a hypothesis has not thereby rejected it.

5.1 Hypothesis 1: External Enforcement versus Minimal Runtime

Question and arms. Hypothesis 1 compares an instruction-only runtime (I), a capability-matched minimal runtime (M), and a full external-enforcement runtime (E) under the same task and threat model. All arms expose the same tools, files, context budget, token budget, wall-clock budget, and final evaluator. In I and M, protected permissions, acceptance, recovery, and audit are delegated to instructions; in E they are implemented outside model control. The primary causal contrast is E versus M. I is a measurement control for the cost of supplying an executable runtime, and four optional leave-one-control-out arms remove the permission floor, independent acceptance, recoverable checkpoints, or tamper-evident audit in turn. The primary contrast estimates the effect of the enforcement bundle. The controls can interact, so a leave-one-out difference describes the bundle without that control and is not the independent effect of the control.

Task bank and randomization. The planning schedule specifies 120 task slots in six families: basic patches, permission boundaries, acceptance gates, interrupted recovery, tool migration, and environment change. Final task content and hidden tests must be frozen before preregistration. Each task is crossed with three frozen model snapshots, two execution environments, and three independent seeds. Within every task–seed pair, the primary arms run in seeded random order with concealed allocation. Development tasks used to construct a harness cannot enter this bank. Hidden tests and a scripted adversarial suite remain inaccessible during a run. Manipulation checks verify that E actually blocks prohibited calls, that M and I expose the same capabilities, that bypass attempts are detected, and that the evaluator can return both accepted and rejected outcomes.

Primary estimands. *Contract-preserving success* is correct task completion with no unauthorized state change, incorrect acceptance, recovery failure, or missing required audit evidence. *Unauthorized effect* is a binary violation of the frozen permission contract. Task success, incorrect acceptance, recovery failure, audit completeness, latency, tokens, and tool calls are reported separately as secondary outcomes. Missing or aborted runs count as non-success and remain in the assigned arm.

Inference and rejection rule. Tasks, not runs, are the independent clusters. We average paired run differences within task, resample tasks 2,000 times, and use simultaneous 97.5% intervals for the two co-primary outcomes. The provisional practical margins are five percentage points for contract-preserving success and five percentage points for the absolute

risk of unauthorized effects. These are planning inputs, not empirical findings; the security owner must approve or replace them before preregistration. Hypothesis 1 is *rejected* within the tested scope when the lower bound for M minus E contract-preserving success exceeds minus five percentage points *and* the upper bound for M minus E unauthorized effects stays below five percentage points: the minimal runtime is then non-inferior on both outcomes. Hypothesis 1 is *supported* when both intervals lie wholly beyond their margins in favor of E. Any other result is *inconclusive*: Hypothesis 1 is retained as not rejected and the imprecision is reported. Interactions with model snapshot and environment are mandatory, and success cannot compensate for a safety-bound violation.

5.2 Hypothesis 2: Complete Pattern Records versus Mechanism-Only Descriptions

Hypothesis 2 tests whether explicit pattern records improve engineering decisions. It uses a three-arm matched design: complete lifecycle-aware pattern records (A), descriptions of the same mechanisms with authority, contract, evidence, negative-case, and lifecycle fields removed and with length and presentation matched to A (B), and ordinary documentation (C). The human planning study uses 60 participants. The separate agent study uses 60 seeded agent units formed from three fixed model snapshots, 20 units per snapshot, with two decoding seeds per task. Human and agent results are analyzed separately. Agent inference is conditional on these snapshots: seeded units estimate run-level variation and are not independent samples from a population of models.

Allocation and carryover. Each participant or agent unit completes six tasks, one from each task family, two under each arm. Arms are assigned in Latin-square blocks of three units by three tasks, and task order is randomized within unit. A unit therefore meets all three arms, and learning can carry over from one task to the next. Three features address this. Every task has its own materials, and no material is shown under two arms. Arm order is balanced by the Latin square and enters the analysis as a heterogeneity term. And the contrast on each unit's first task, which is a between-unit comparison free of carryover, is reported as a sensitivity analysis.

Outcomes and inference. Blinded raters score accepted designs and changes on a 0–100 rubric frozen before data collection, with inter-rater agreement reported; hidden tests measure violations of protected contracts. The human participant is the independent cluster in the human study; the seeded agent unit is clustered within a fixed model snapshot in the agent study. A crossed analysis reports task and snapshot interactions and does not generalize beyond the three snapshots. The two A-versus-control quality contrasts and the corresponding violation contrasts use simultaneous 97.5% intervals. The provisional margins are five points on the 0–100 rubric and two percentage points of violation risk. Both are planning inputs. The quality margin in particular needs a substantive justification from pilot rubric data before preregistration.

Decision rule. Hypothesis 2 is *supported* within scope when the lower bounds of both quality contrasts exceed the five-point margin and the upper bounds of both violation contrasts stay below two points. It is *rejected* within scope when the upper bound of the A-minus-B quality contrast lies below the margin, so that any benefit of the record fields is smaller than the smallest benefit of interest, or when a violation contrast lies wholly above its margin. Any other result is *inconclusive*. The A-versus-B contrast is the one that isolates the record fields, because B holds mechanism content and presentation constant. The A-versus-C contrast estimates the broader effect of a documentation package and is read that way. Support does not imply field-wide benefit or that every record field is necessary.




Figure 9 Confirmatory designs for the two hypotheses. Left: matched task–seed pairs compare instruction-only, minimal-runtime, and fully enforced harnesses. Right: blocked tasks compare complete pattern records, mechanism-only descriptions, and ordinary documentation. The figure specifies allocation structure only; neither study has been executed.

The human and agent studies both hold the initial harness, model, tools, time, and token budget fixed and keep final tests inaccessible during the task. Rejected proposals, rollback, provenance, effort, and cost are diagnostic outcomes. Neither a rejection nor an inconclusive result removes the normative duty to make consequential responsibilities explicit; they bear on this schema's utility.

5.3 Designs, Decision Rules, and Operating Characteristics

Figure 9 shows the allocation structure of both studies, and Table 16 states their decision rules. Figure 10 and Table 17 report simulated operating characteristics at the planning unit counts. All of these are planning quantities under explicitly stated illustrative scenarios; none is an empirical result.

The accompanying experiment package contains the machine-readable protocol, seeded allocation schedules, task manifest schema, result-analysis code, synthetic pipeline checks, and PDF-only planning figures. It does not contain model runs for these studies. Execution requires frozen model access, a task bank with hidden tests, separated development and final evaluators, and documentation of any approved protocol amendment.

5.4 Scope Extensions

Separate clustered studies compare variation mechanisms over a tenth change and automated evolution against human-maintained and no-adaptation controls. Both use held-out tasks and matched budgets; failure to isolate a mechanism effect retains only problem-specific guidance. The closed-loop comparison is specified in Section 4.1. The other two extensions follow.

For the mechanism test, each of several predeclared ten-change sequences is a clustered experimental unit. Vary tool schemas, capability availability, permissions, requirements, and model snapshots; include changes inside declared hot spots and changes that challenge

Table 16 Pre-specified three-way decisions for the two causal hypotheses. Bounds are those of simultaneous 97.5% intervals. Margins are provisional planning inputs and require approval before outcomes are observed. E, M, A, B, and C are the study arms defined in the text.

	Independent unit	Supported when	Rejected when	Otherwise
H1	Task; task–seed pairs are repeated within model and environment strata.	M is worse than E beyond both margins: contract-preserving success by more than five points and unauthorized-effect risk by more than five points.	M is non-inferior to E on both outcomes: success within five points and unauthorized-effect risk within five points.	Inconclusive. Retain H1 as not rejected; report imprecision, interactions, and every failed obligation.
H2	Human participant, or seeded agent unit nested in one of three fixed snapshots; six tasks repeat within the unit.	A exceeds B and C on accepted-design quality by more than five rubric points and adds less than two points of hidden violation risk against both.	The quality benefit of A over B is below five rubric points, or A adds more than two points of violation risk against B or C.	Inconclusive. Report scope-specific estimates; never pool human and agent units.




Figure 10 Prospective operating characteristics, not empirical results. Monte Carlo simulations use explicitly stated illustrative outcome rates and between-unit variation to show how the probability of the intended decision changes with the number of independent tasks (H1) or participant and seeded-agent units (H2). The intended decision is to reject a hypothesis in the scenario where it is false and to support it in the scenario where it is true. For H1, the scenarios are a minimal runtime that is genuinely within both margins and external controls that genuinely exceed both margins. For H2, they are no record advantage and a complete-record advantage. The bands are 95% Monte Carlo intervals, the dashed line marks 0.8, and the dotted lines mark the planning counts of 120 tasks and 60 units. The illustrative rates are not observed effects. Changing any assumed rate, variance, margin, or multiplicity rule changes the required sample size.

the protected contract. Randomize matched sequences across mechanisms, match exposed capabilities and edit budgets, and keep final evaluation tasks unavailable during adaptation. Define regression and permission-failure rates as primary estimands; treat effort, runtime, provenance loss, deletion effort, and forced contract redesign as prespecified secondary outcomes. Model sequence and task-family heterogeneity, report missing or aborted changes, and control multiplicity. Pilot reference implementations against a common conformance

Table 17 Prospective operating characteristics at the planning unit counts. Entries are Monte Carlo decision rates (%) over 2,000 replicates under explicit illustrative scenarios, split by the three-way rules of Table 16. H1 uses 120 independent tasks; H2 uses 60 participants or 60 seeded agent units per separately analyzed study, and agent results are conditional on three fixed snapshots. The last column is the 95% Monte Carlo interval of the intended decision's rate. All values are design-planning quantities.

Planning scenario	Intended	Supported	Rejected	Inconclusive	95% interval
H1: minimal runtime within margins	Reject H1	0.0	89.2	10.8	87.9–90.6
H1: external-enforcement advantage	Support H1	100.0	0.0	0.0	100.0–100.0
H2: no record advantage	Reject H2	0.0	>99.9	<0.1	99.9–100.0
H2: record advantage	Support H2	86.0	0.0	14.0	84.5–87.5

suite before randomization; if capability matching is infeasible, report a descriptive case comparison rather than a confirmatory mechanism effect. Report unmatched implementation differences; if they preclude attribution, the general comparison fails rather than becoming a leaderboard claim.

To validate the inventory and the A^2 lens, freeze source snapshots, search terms, inclusion and exclusion decisions, and deduplication rules before annotation. At least two analysts should independently code whether each source reports a mechanism, which A1/A2/A3 activities it informs, its protected contract and permitted variation, and any proposed connection type. Report agreement for each field, adjudicate disagreements without deleting them, and publish uncodable or negative cases. The source-reported mechanism must remain separate from the analysts' contract, consequence, and test interpretations.

To test the value of A^2 as an organizing lens, apply it and at least one prior architecture, quality-attribute, or agent-pattern scheme to the same held-out systems. Preregister coverage, unresolved cases, annotation time, agreement, and decision errors as outcomes. Failure to improve any prespecified outcome would retain A^2 only as descriptive vocabulary.

6 Alternative Views

6.1 Scaling Will Absorb Harnesses

The strongest objection is that stronger models will internalize planning, tool choice, and memory. Tool removal and the simplification of classical patterns by dynamic languages make this credible [47, 32]; cognitive-compensatory scaffolding should disappear when a model reliably absorbs it. Hypothesis 1 instead asks whether instruction-only self-policing matches external enforcement. Hold tasks and threat models fixed, then compare a minimal runtime with enforced controls on task quality, bypass, incorrect acceptance, cost, and recovery. If it meets prespecified task non-inferiority and security margins, reject the hypothesis for that scope; otherwise scaling moved the boundary rather than removing it.

6.2 Harness Diversity Is a Feature

Different domains, users, and risk tolerances legitimately need different harnesses, so no stack or mechanism should be canonical. We agree: pattern discipline is designed to preserve responsibilities while implementations differ [6]. Compare complete pattern records with mechanism-only and ordinary documentation on matched design and migration tasks. If

complete records do not improve responsibility identification or reduce contract violations without suppressing valid diversity, reject the bounded utility claim for that scope; the normative requirement to make consequential duties explicit stands on its own.

6.3 This Is Software Engineering, Not ML

A critic may accept these practices as software engineering while denying that they are an ML problem. Harness architecture complements learning algorithms: measured capability can depend on model–runtime interactions [26, 1]. AgentBench and later evaluation work make environment and system configuration material [27, 58]. A factorial model–harness study should test interaction while reporting tokens, tool calls, time, and engineering effort; no ML claim remains if interactions are negligible on held-out tasks.

7 Call to Action

7.1 Build an Open Harness-Responsibility Registry

Create a public, versioned registry with explicit states: proposed, source-located, pointcut-confirmed, contract-supported, outcome-tested, and retired. Each record should state responsibility, pointcut, invariant, permitted variation, authority, acceptance evidence, failure modes, costs, and retirement triggers. Appendix A.1 offers a 52-record seed. Freeze sources and decisions; require independent review before promotion (Section 5.4).

7.2 Benchmark Variation Mechanisms and Records

Publish negative cases, matched design tasks, and first- and *tenth*-change sequences with reference implementations, evaluator splits, cost/threat models, and outcome schemas. OO-Harness, HarnessX, and HarnessForge are candidate baselines [25, 13, 12]. Conceal final tasks, preregister margins, and report margin-based contrasts beyond a leaderboard (Section 5.4).

7.3 Agree on Evidence and Protected Responsibilities

Use cross-laboratory review with public proposals, conflicts, appeals, and retirement reviews. Name each invariant's authority, failure behavior, and bypass test. Promote after independent replication, and standardize evidence obligations so that stacks can stay diverse (Section 4.1).

7.4 Extend the Audit

The exploratory audit supplies the sampling frame for a confirmatory study. The first priority is independent adjudication. Draw a stratified sample of cells that covers observed and unobserved cells, the five record families, the source pools, and the implementation languages. Have at least two human reviewers decide the four pointcut dimensions separately for each cell, map test evidence to each contract obligation, apply the negative control, and adjudicate disagreements. This yields cue-to-pointcut precision, a false-negative rate for unobserved cells, and contract support on a common denominator, so that the drop from retrieval to pointcut to contract can be quantified on the same cells. Only reviewed cells should enter a confirmatory pointcut or contract matrix. The same review should check the names and attributions of the P records against the primary study before the registry is seeded.

The second priority is complete lineage-aware history. Commit- and release-level events should distinguish introduction, movement or rename, authority redesign, split, merge,

Table 18 Claims of this paper and their standing. The position rests on C1–C3, which are argued. C4 and C5 are specified and await execution. C6 and C7 are exploratory observations on one purposive panel and serve as supporting material.

Claim	Type and standing
C1. Consequential harness responsibilities must stay identifiable, authorized, and auditable through change.	Normative; argued from accountability for obligations that lie outside the model (Sections 1 and 3.3.3).
C2. Responsibility records and the A^2 taxonomy organize obligations across design, verification, and evolution.	Conceptual; expressiveness shown by nine analytical cases and a 52-record seed inventory. Annotation reliability and comparative value have a stated test (Sections 3.3 and 3.4).
C3. Harness engineering drifts from software engineering in closed-loop evolution, agent factors, and model-conditional utility lifetimes.	Analytical; each drift carries a rejection test (Section 4).
C4 (H1). External enforcement protects contracts beyond a capability-matched minimal runtime.	Prospective; 120-task protocol with a three-way decision rule (Section 5).
C5 (H2). Complete pattern records improve design and migration decisions over mechanism-only and ordinary documentation.	Prospective; protocols with 60 participants and 60 seeded agent units and a three-way decision rule (Section 5).
C6. The vocabulary of the candidate inventory is readily retrieved from harness code, and the levels of the evidence ladder separate on the same cells.	Exploratory; a lexical cue in 1,265 of 2,132 cells, and 16 matcher-selected cells coded by one model with 6/8/2 majority and 4/8/4 all-profile dispositions (Section 3.2).
C7. Retrieved cue locations change across sampled releases.	Exploratory; 321 transitions after a first observed cue, 35.2% with a large cue-path change (Section 3.2.3).

removal, replacement, and explicit retirement. Repository-family clustering and time-to-event or multistate models should be used when event times are observable. The current checkpoint gaps remain detector gaps and cannot be converted into retirement evidence.

The third priority is provenance-balanced sampling. The panel should cover coding, browser, research, embodied, and enterprise agents; multiple implementation languages; open and closed development contexts; and successor lineages. Pattern-specific alias induction can prioritize unobserved cells, but new lexical hits require source review before promotion. Finally, contract presence should be connected to actual failures and to the matched H1/H2 experiments rather than treated as an outcome.

8 Discussion and Conclusion

The paper's claims have different standings, and Table 18 keeps them apart. The normative minimum, the A^2 taxonomy, the nine cases, and the three drifts are argued. They can be examined now, by checking whether the distinctions hold for a given harness. The two hypotheses are specified with decision rules that can reject them. The repository audit is exploratory. It shows that the candidate vocabulary is present in real harness code and that cue, structural match, pointcut, and contract can be told apart on the same cells. It was built with one model's assistance on a purposive panel, so it supplies an instrument, worked

examples, and a sampling frame, and leaves prevalence to later work.

Three steps would strengthen the evidence. An independently adjudicated, stratified sample of cells, with at least two human reviewers, would turn cue coverage into estimates of pointcut precision and recall. Executing the two protocols would settle whether external enforcement and complete records earn their cost. Measuring transfer and utility lifetimes across model snapshots would show which mechanisms can be retired and which obligations must be re-homed. The security of self-evolving harnesses remains an open risk [53, 59], and it is the setting where these steps matter most.

Agent harnesses carry system responsibilities at every model scale. Stronger models will absorb much of the scaffolding around them. The obligations to parties outside the model stay with the system: who authorizes, what is accepted, what is recorded, and how execution stops. Pattern discipline makes those obligations explicit as contracts, permitted variation, authority, evidence, consequences, and lifecycle conditions, across design, verification, and evolution. This paper contributes the position and its normative minimum, the A^2 taxonomy that organizes responsibility records, nine cases and three drifts that show what the taxonomy distinguishes, and two protocols that make the remaining empirical claims testable. Self-improvement makes the discipline urgent, and every harness that changes can use it.

References

1 Muayad Sayed Ali, Aliaksandra Novik, Anji Boddupally, et al. The harness effect: How orchestration design sets the token economics of enterprise agentic ai. *arXiv preprint arXiv:2607.06906*, 2026. URL: https://arxiv.org/abs/2607.06906.

2 Anthropic. Building effective agents. Anthropic practitioner guide, 2024. URL: https://www.anthropic.com/research/building-effective-agents.

3 Anthropic. Building effective agents cookbook. Official reference implementations, GitHub repository, n.d. Prompt chaining, routing, parallelization, orchestrator–workers, and evaluator–optimizer workflows. URL: https://github.com/anthropics/anthropic-cookbook/tree/main/patterns/agents.

4 Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022. URL: https://arxiv.org/abs/2212.08073.

5 Sebastian Baltes and Paul Ralph. Sampling in software engineering research: A critical review and guidelines. *Empirical Software Engineering*, 27(4):94, 2022. doi:10.1007/s10664-021-10072-8.

6 Paul Barbaste, Tristan Darrigol, Germain Vu, and Tom Wiltberger. Harness engineering: Anatomy, architecture, and evolution of coding agents — a source-code study of eleven systems. *arXiv preprint arXiv:2609.00006*, 2026. URL: https://arxiv.org/abs/2609.00006.

7 Grace Victoria Billiris and Asif Qumer Gill. A federated observability architecture pattern for reliable agentic AI software systems across the AI software development lifecycle. *Information and Software Technology*, 2026. doi:10.1016/j.infsof.2026.108260.

8 Frank Buschmann et al. *Pattern-Oriented Software Architecture: A System of Patterns*, volume 1. Wiley, 1996. URL: https://openlibrary.org/books/OL602786M.

9 Frank Buschmann, Kevlin Henney, and Douglas C. Schmidt. *Pattern-Oriented Software Architecture: A Pattern Language for Distributed Computing*, volume 4. Wiley, 2007. URL: https://openlibrary.org/books/OL7595514M.

10 Frank Buschmann, Kevlin Henney, and Douglas C. Schmidt. *Pattern-Oriented Software Architecture: On Patterns and Pattern Languages*, volume 5. Wiley, 2007. URL: https://openlibrary.org/books/OL7618027M.

11 Yangxiao Cai, Ruiyin Li, Peng Liang, Mojtaba Shahin, and Zengyang Li. Designing LLM-based multi-agent systems for software engineering tasks: Quality attributes, design patterns and

rationale. arXiv preprint arXiv:2511.08475, 2025. URL: https://arxiv.org/abs/2511.08475, doi:10.48550/arXiv.2511.08475.

12 Mingju Chen, Can Lv, Guibin Zhang, Heng Chang, and Shiji Zhou. HarnessForge: Joint harness and policy evolution for adaptive agent systems. In *Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing*, pages 43130–43155. Association for Computational Linguistics, 2026. URL: https://aclanthology.org/2026.emnlp-main.1893/, doi:10.18653/2026.emnlp-main.1893.

13 Tingyang Chen, Shuo Lu, Kang Zhao, Weicheng Meng, Hanlin Teng, Tianhao Li, Chao Li, Xule Liu, Jian Liang, Zhizhong Zhang, Yuan Xie, Heng Qu, Kun Shao, and Jian Luan. HarnessX: A composable, adaptive, and evolvable agent harness foundry. arXiv preprint arXiv:2606.14249, 2026. URL: https://arxiv.org/abs/2606.14249.

14 Eric Evans. *Domain-Driven Design: Tackling Complexity in the Heart of Software*. Addison-Wesley, 2004. Copyright year; first published August 2003. URL: https://www.informit.com/store/domain-driven-design-tackling-complexity-in-the-heart-9780321125217.

15 Michael Feathers. *Working Effectively with Legacy Code*. Pearson, 2004. URL: https://www.informit.com/store/working-effectively-with-legacy-code-9780131177055.

16 Erich Gamma, Richard Helm, Ralph Johnson, and John Vlissides. *Design Patterns: Elements of Reusable Object-Oriented Software*. Addison-Wesley, 1995. Copyright year; first published October 1994. URL: https://www.informit.com/store/design-patterns-elements-of-reusable-object-oriented-9780201633610.

17 Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, et al. Gemini: A family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023. URL: https://arxiv.org/abs/2312.11805.

18 Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*, 2024. URL: https://arxiv.org/abs/2403.05530.

19 Chaoyue He, Xin Zhou, Di Wang, Hong Xu, Wei Liu, and Chunyan Miao. Harness engineering for language agents: The harness layer as control, agency, and runtime. Preprints.org, version 2, 2026. Preprint, not peer reviewed. doi:10.20944/preprints202603.1756.v2.

20 Eirini Kalliamvakou, Georgios Gousios, Kelly Blincoe, Leif Singer, Daniel M. German, and Daniela Damian. The promises and perils of mining GitHub. In *Proceedings of the 11th Working Conference on Mining Software Repositories*, pages 92–101. ACM, 2014. doi:10.1145/2597073.2597074.

21 Gregor Kiczales, John Lamping, Anurag Mendhekar, Chris Maeda, Cristina Lopes, Jean-Marc Loingtier, and John Irwin. Aspect-oriented programming. In *ECOOP '97—Object-Oriented Programming*, pages 220–242. Springer, 1997. doi:10.1007/BFb0053381.

22 Michael Kircher and Prashant Jain. *Pattern-Oriented Software Architecture: Patterns for Resource Management*, volume 3. Wiley, 2004. URL: https://openlibrary.org/books/OL7597837M.

23 Barbara A. Kitchenham, Tore Dybå, and Magne Jørgensen. Evidence-based software engineering. In *Proceedings of the 26th International Conference on Software Engineering*, pages 273–281. IEEE, 2004. doi:10.1109/ICSE.2004.1317449.

24 Meir M. Lehman. Programs, life cycles, and laws of software evolution. *Proceedings of the IEEE*, 68(9):1060–1076, 1980. doi:10.1109/PROC.1980.11805.

25 Gaotang Li, Bhavana Dalvi Mishra, Yifei Ming, Yanfei Chen, Zhongying CuiZhu, Lesly Miculicich, Long T. Le, Rui Meng, Chun-Liang Li, Hanghang Tong, Chen-Yu Lee, and Tomas Pfister. Object-oriented harness: Evolving agent harnesses through object-oriented design. *arXiv preprint arXiv:2610.28380*, 2026. URL: https://arxiv.org/abs/2610.28380.

26 Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shihan Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, and Yu-Gang Jiang. Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses. *arXiv preprint arXiv:2604.25850*, 2026. URL: https://arxiv.org/abs/2604.25850.

27 Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, et al. Agentbench: Evaluating llms as agents. In *International Conference on Learning Representations*, 2024. URL: https://arxiv.org/abs/2308.03688.

28 Qianyu Meng, Yanan Wang, Liyi Chen, Yihang Li, Wei Wu, Wenyuan Jiang, Qimeng Wang, Chengqiang Lu, Yan Gao, Yi Wu, and Yao Hu. Agent harness for large language model agents: A survey. Preprints.org, version 3, 2026. Preprint, not peer reviewed. doi:10.20944/preprints202604.0428.v3.

29 Zoran Milošević and Fethi Rabhi. Architecting agentic communities using design patterns. arXiv preprint arXiv:2601.03624, 2026. URL: https://arxiv.org/abs/2601.03624, doi:10.48550/arXiv.2601.03624.

30 Meiyappan Nagappan, Thomas Zimmermann, and Christian Bird. Diversity in software engineering research. In *Proceedings of the 9th Joint Meeting on Foundations of Software Engineering*, pages 466–476. ACM, 2013. doi:10.1145/2491411.2491415.

31 Xuying Ning, Katherine Tieu, Dongqi Fu, Tianxin Wei, Zihao Li, Yuanchen Bei, Jiaru Zou, Mengting Ai, et al. Code as agent harness. arXiv preprint arXiv:2605.18747, 2026. URL: https://arxiv.org/abs/2605.18747.

32 Peter Norvig. Design patterns in dynamic programming. Online document, n.d. URL: https://www.norvig.com/design-patterns/design-patterns.pdf.

33 Alexander Novikov, Ngân Vũ, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, et al. Alphaevolve: A coding agent for scientific and algorithmic discovery. *arXiv preprint arXiv:2506.13131*, 2025. URL: https://arxiv.org/abs/2506.13131.

34 OpenAI. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. URL: https://arxiv.org/abs/2303.08774.

35 OpenAI. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024. URL: https://arxiv.org/abs/2410.21276.

36 OpenAI. A practical guide to building agents. OpenAI practitioner guide, 2025. URL: https://cdn.openai.com/business-guides-and-resources/a-practical-guide-to-building-agents.pdf.

37 Linyue Pan, Lexiao Zou, Shuo Guo, Jingchen Ni, and Hai-Tao Zheng. Natural-language agent harnesses. arXiv preprint arXiv:2603.25723, 2026. URL: https://arxiv.org/abs/2603.25723, doi:10.48550/arXiv.2603.25723.

38 D. L. Parnas. On the criteria to be used in decomposing systems into modules. *Communications of the ACM*, 15(12):1053–1058, 1972. doi:10.1145/361598.361623.

39 Per Runeson and Martin Höst. Guidelines for conducting and reporting case study research in software engineering. *Empirical Software Engineering*, 14(2):131–164, 2009. doi:10.1007/s10664-008-9102-8.

40 Anjana Sarkar and Soumyendu Sarkar. Survey of LLM agent communication with MCP: A software design pattern centric review. arXiv preprint arXiv:2506.05364, 2025. URL: https://arxiv.org/abs/2506.05364.

41 Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, 2023. URL: https://arxiv.org/abs/2302.04761.

42 Douglas C. Schmidt, Michael Stal, Hans Rohnert, and Frank Buschmann. *Pattern-Oriented Software Architecture: Patterns for Concurrent and Networked Objects*, volume 2. Wiley, 2000. URL: https://www.dre.vanderbilt.edu/~schmidt/POSA/POSA2/.

43 Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, 2023. URL: https://arxiv.org/abs/2303.11366.

44 Peri Tarr, Harold Ossher, William Harrison, and Stanley M. Sutton, Jr. *n* degrees of separation: Multi-dimensional separation of concerns. In *Proceedings of the 21st International Conference on Software Engineering*, pages 107–119. ACM, 1999. doi:10.1145/302405.302457.

45 Paul Taylor, Peter Evans-Greenwood, and James Odell. The genesis of a pattern language for agent-based enterprise systems. In *Sixth International Conference on Quality Software*, 2006. doi:10.1109/QSIC.2005.65.

46 Nikolaos Tsantalis, Alexander Chatzigeorgiou, George Stephanides, and Spyros T. Halkidis. Design pattern detection using similarity scoring. *IEEE Transactions on Software Engineering*, 32(11):896–909, 2006. doi:10.1109/TSE.2006.112.

47 Vercel. We removed 80% of our agent's tools. Vercel blog, n.d. URL: https://vercel.com/blog/we-removed-80-percent-of-our-agents-tools.

48 Peidong Wang, Ying Chang, Zhiming Ma, Xiaocui Yang, Shi Feng, Daqi Liu, Yuzhe Yang, Xu Cao, Chuang Wang, Jian Su, and Daling Wang. AdaRSI: On-demand recursive self-improvement for embodied agents. arXiv preprint arXiv:2610.20474, 2026. URL: https://arxiv.org/abs/2610.20474.

49 Zixuan Wang, Yuqi Liu, Yuxin Chen, Sengqiao Yang, Jinhui Ye, Pengguang Chen, Changsheng Lu, Shu Liu, Bei Yu, and Jiaya Jia. CarryOn: A dual-loop harness for personalized and reliable robot assistance. arXiv preprint arXiv:2610.21453, 2026. URL: https://arxiv.org/abs/2610.21453.

50 Lilian Weng. Harness engineering for self-improvement. Practitioner blog, 2026. URL: https://lilianweng.github.io/posts/2026-07-04-harness/.

51 Danny Weyns. A pattern language for multi-agent systems. In *2009 Joint Working IEEE/IFIP Conference on Software Architecture and European Conference on Software Architecture*, 2009. doi:10.1109/WICSA.2009.5290805.

52 Julia Wiesinger, Patrick Marlow, and Vladimir Vuskovic. Agents. Google/Kaggle whitepaper, n.d. URL: https://www.kaggle.com/whitepaper-agents.

53 Peng Xia, Rujun Han, Zifeng Wang, Yanfei Chen, Yufan Zhuang, Yoonho Lee, Chengsong Huang, Han Yu, Zhongying CuiZhu, Yifei Ming, Huaxiu Yao, Burak Gokturk, Tomas Pfister, and Chen-Yu Lee. RRSI: Regularized recursive self-improvement of agent harnesses. arXiv preprint arXiv:2609.24972, version 3, 2026. URL: https://arxiv.org/abs/2609.24972v3.

54 Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. In *Advances in Neural Information Processing Systems*, 2024. URL: https://arxiv.org/abs/2404.07972.

55 Ruiyao Xu, Yanfei Chen, Zhongying CuiZhu, Bhavana Dalvi Mishra, Yifei Ming, Han Yu, Rujun Han, Chen-Yu Lee, and Tomas Pfister. Harness^2: Recursive agent harnessing for an open world. arXiv preprint arXiv:2610.14224, 2026. URL: https://arxiv.org/abs/2610.14224.

56 John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering. *Advances in Neural Information Processing Systems*, 2024. URL: https://arxiv.org/abs/2405.15793.

57 Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *International Conference on Learning Representations*, 2023. URL: https://arxiv.org/abs/2210.03629.

58 Asaf Yehudai, Lilach Eden, Alan Li, Guy Uziel, Yilun Zhao, Roy Bar-Haim, Arman Cohan, and Michal Shmueli-Scheuer. A survey on evaluation of LLM-based agents. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 26690–26714. Association for Computational Linguistics, 2026. URL: https://aclanthology.org/2026.findings-acl.1330/, doi:10.18653/v1/2026.findings-acl.1330.

59 Weichen Yu, Lesly Miculicich, Bhavana Dalvi Mishra, Jiefeng Chen, Shuo Li, Matt Fredrikson, Tomas Pfister, and Long T. Le. Harmony harness: Multi-objective self-evolution of agent harnesses. *arXiv preprint arXiv:2610.15150*, 2026. URL: https://arxiv.org/abs/2610.15150.

60 Yijun Yu. From goals to aspects, revisited: An NFR pattern language for agentic AI systems. arXiv preprint arXiv:2603.00472, 2026. URL: https://arxiv.org/abs/2603.00472, doi:10.48550/arXiv.2603.00472.

61 Yiwen Zhu, Lihe Liu, Jiaqian Yu, and Di Zhang. LLM-based multi-agent orchestration: A survey of frameworks, communication protocols, and emerging patterns. *Future Internet*, 18(6):326, 2026. doi:10.3390/fi18060326.

A Complete Pattern Inventory by Category

This appendix lists all 52 records of the inventory introduced in Section 3.1, grouped into its five source categories: coding-agent mechanisms (P01–P29), official-guide workflows and coordination patterns (W01–W07), communication patterns (C01–C04), reasoning and feedback patterns (R01–R02), and instantiated evolution mechanisms (E01–E10). Each record gives its A^2 activity coordinate, the source-reported mechanism, our proposed protected contract and permitted variation, a consequence or validation question, and its source. Each record is followed by a code box that states how it is detected and matched in a repository: its regular expression, aliases, canonical exemplar, and negative control. Appendix A.4 draws three representative UML class views of proposed records. Appendix A.2 reports family and repository cue coverage for every record, and Appendix A.3 qualifies the sources. Section 3.2 reports the exploratory audit that produced the coverage values, and Appendix B documents its protocol.

Identifiers are inventory traceability aids. Each combines a source-family prefix with a serial number; a slash lists separate records and a double hyphen spans a contiguous range. For example, `W04/W07` resolves to *Orchestrator–workers* and *Decentralized handoffs*, while `C01-C04` resolves to the four communication rows listed under C. Prefixes record source families; they do not assert equal evidentiary status within or across families.

Activity assignments, frozen points, hot spots, variation mechanisms, and consequence questions are our proposed A^2 analysis, not quotations or reported comparative results. "Frozen" means protected within a stated scope and authority, not technically immutable. A1/A2/A3 indicate analysis focus, not exclusive bins. Enforcement, independence, recovery, and performance must be tested in the actual implementation. The table therefore distinguishes a mechanism's intended contract from evidence that the contract holds. Every row has a Reference cell. For P records it gives the section and page in Barbaste et al. [6] (arXiv:2609.00006v1) and states whether the label is the source's, adapted, merged, or our synthesis; for other records it identifies the guide, paper, or system reporting the mechanism. These references do not attribute our proposed asset boundaries or consequence questions to the source authors. Official guides and implementation documentation are cited through BibTeX `@misc` entries, without treating them as peer-reviewed evidence.

A.1 Record-by-Record Inventory with Detection and Matching

Each record below is followed by a code box that states how the record is detected and matched in a repository. All records pass through the same pipeline, summarized in Table 19; what differs by record is the rule in its box. The box contents are taken verbatim from the study's frozen protocol files. A long expression is wrapped after an alternation bar; the line break and the indentation are not part of the expression.

Detection. The `regex` line is the record's lexical cue. It is run with `ripgrep` in case-insensitive mode over code files (`.py`, `.ts`, `.tsx`, `.js`, `.jsx`, `.mjs`, `.cjs`, `.cs`, `.rs`), test files, and supporting files (`.yaml`, `.yml`, `.toml`, `.json`, `.md`, `.mdx`). Dependency, virtual-

Table 19 Detection and matching methods used in the audit. Each step produces a different evidence level (Table 5); no step implies the next. "Records" is the number of the 52 records to which the step applies, and "Box field" names the line of the code box that carries the record-specific rule.

Step	Method	How it is applied	Box field	Records
Lexical cue	Regular expression	One frozen expression per record, run case-insensitively over code, test, and supporting files of the current snapshot and of sampled historical releases.	`regex`	52
Structural symbol	Code analysis	Symbols extracted from a Python syntax tree or from declaration syntax in 14 other languages are normalized and replayed against the record's expression.	`regex`	52
Compound alias	Normalized string match	Record-specific aliases of at least eight characters, matched inside the compacted symbol name.	`aliases`	15
Canonical exemplar	Curated source reading	One implementation locator (file and line) with a supporting test, documentation, or configuration artifact; E08 has a specification only.	`exemplar`, `support`	51
Pointcut and contract coding	Model-assisted review	Exact structural candidates are coded against the record's pointcut, contract, and negative control under 200 prompt profiles of one model.	`joinpoint`, `negative`, `coded`	7

environment, build, coverage, recording, fixture, generated, and vendored paths are excluded, and at most 40 hits are kept per repository and record. A hit is a retrieval cue. The same expressions are run on the sampled historical releases to obtain historical cues.

Matching. The layered matcher extracts symbols from code. For Python it walks the abstract syntax tree and records class and function definitions, imports, call names, and assignment targets. For TypeScript, JavaScript, Rust, Go, Java, Kotlin, Ruby, PHP, Swift, Scala, C, C++, C#, and Lua it records the names introduced by the declaration expression `(?:^|\b)(?:class|interface|type|enum|struct|trait|impl|function|fn|def)\s+([A-Za-z_$][\w$]*)`. Each symbol is normalized to snake case and replayed against the record's `regex`. The `aliases` line lists the compound aliases that fifteen records carry because their vocabulary differs across ecosystems; an alias matches when it occurs inside the symbol name after lower-casing and removal of non-alphanumeric characters. An earlier pass that scored generic pointcut terms overmatched common words and was rejected, so those terms are not used.

Anchoring and review. The `joinpoint` line names where in execution the record applies. The `exemplar` and `support` lines give the canonical exemplar: one implementation file and line located by reading the repositories, with a supporting artifact. The exemplar is one instance by construction and says nothing about other repositories. A cell with an exact symbol or alias match enters the review queue and is coded against the record's specification: the four pointcut fields, the four contract fields, and the `negative` control, which names a look-alike that must not count (Section 3.4.2). The `coded` line gives the number of exact

candidate cells coded for the record in Table 23. That coding was done by one model under 200 role-conditioned prompt profiles; it is not human adjudication.

Representative class views. Appendix A.4 draws three representative UML class views (P01, P11, and E08), and Figure 7 in the main text draws P17. Each class box is a proposed participant role, its operation compartment lists the calls it receives, and the numbered dashed arrows are call dependencies. A relationship panel restates every call, so the drawing never depends on following a crossing arrow. The views are analytical reconstructions of proposed contracts, not observed execution traces or repository class declarations.

P. Coding-agent mechanisms: locators in Barbaste et al. (arXiv:2609.00006v1)

P01 / A1. Minimal linear loop. Alternate model turns and action execution. *Protected contract:* Turn/result protocol and termination interface. *Permitted variation:* Prompts, tools, and stopping policy through explicit callbacks or configuration. *Consequence / validation:* Simple to inspect; test premature stops and runaway retries. *Source:* Barbaste et al. [6], §6.2, p. 14 (Mini-SWE-Agent, "Minimal Linear Loop); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bwhile\s+(?:true|not\s+done)|\bmax_(?:turns|steps|iterations)\b|
            \brun_(?:loop|until)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : agent_turn_execution
exemplar  : openai/openai-agents-python src/agents/run_internal/run_loop.py:987
support   : tests/test_agent_runner.py:1 (test)
negative  : A one-shot model call with no action cycle does not satisfy the
            pointcut.
```

P02 / A1. Streaming concurrent batch loop. Overlap output and independent work. *Protected contract:* Result correlation and event-ordering contract. *Permitted variation:* Batch size and scheduling through concurrent executors. *Consequence / validation:* Latency gains can introduce races; test ordering and cancellation. *Source:* Barbaste et al. [6], §6.2, p. 13 (Claude Code, "Streaming Loop with Concurrent Tool Batching); shortened label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:concurrent|parallel(?:ism)?|batch(?:ed|ing)?|Promise\.all|
            asyncio\.gather)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : parallel_invocation_batch
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/agent/parallel_executor.py:51
support   : tests/sdk/agent/test_parallel_tool_span_context.py:1 (test)
negative  : Generic concurrency in an unrelated subsystem does not count.
```

P03 / A1. Asynchronous state machine. Make waiting and resumption explicit. *Protected contract:* Legal states, transitions, and completion rules. *Permitted variation:* Handlers and recovery policies through transition dispatch. *Consequence / validation:* More states to maintain; test interrupted and duplicate events. *Source:* Barbaste et al. [6], §6.2, p. 14 (Codex, "Tokio Async State Machine); generalized label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bstate[_-]?machine\b|\b(?:transition|transitions|legal_states)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : asynchronous_wait_and_resume
exemplar  : langchain-ai/langgraph libs/langgraph/langgraph/graph/state.py:131
support   : libs/langgraph/tests/test_subgraph_persistence_async.py:63 (test)
negative  : An enum without transition enforcement is not sufficient.
```

P04 / A1. Middleware-pipeline loop. Layer behavior around model/tool calls. *Protected contract:* Invocation order and continuation interface. *Permitted variation:* Logging, policy, and retry layers through middleware composition. *Consequence / validation:* Ordering changes semantics; test short circuits and repeated side effects. *Source:* Barbaste et al. [6], §6.2, p. 14 (Mistral Vibe, "Middleware-Pipeline Loop); Table 11, p. 52; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bmiddleware\b|\badd_middleware\b|\bon_[a-z_]+\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : model_or_tool_call_boundary
exemplar  : microsoft/agent-framework
            python/packages/core/agent_framework/_middleware.py:860
support   : python/packages/core/tests/core/test_middleware_context_result.py:46 (test)
negative  : A hard-coded helper call is not a middleware pipeline.
```

P05 / A1. Asynchronous-generator loop. Expose incremental execution events. *Protected contract:* Yield/resume, cancellation, and cleanup protocol. *Permitted variation:* Consumers and interceptors through generator interfaces. *Consequence / validation:* Backpressure and abandoned consumers can leak work. *Source:* Barbaste et al. [6], §6.2, p. 15 (Gemini CLI, "Async-Generator Loop); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\basync\s+def\s+\w+\([^\n]*\).*?yield\b|\basync\s+function\s*\*|
            \bAsyncGenerator\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : incremental_event_stream
exemplar  : openai/openai-agents-python
            src/agents/models/chatcmpl_stream_handler.py:603
support   : tests/test_stream_events.py:1 (test)
negative  : A synchronous list returned at the end is not the streaming pointcut.
```

P06 / A1. Functional core and steering queues. Separate transitions from live control. *Protected contract:* State-transition and steering-message schemas. *Permitted variation:* Effects and steering policies through queues and effect handlers. *Consequence / validation:* Clarify when steering takes effect; test replay and ordering. *Source:* Barbaste et al. [6], §6.2, p. 15 (Pi, "Functional Core with Steering Queues); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bsteering\b|\beffect\s+handler\b|\bfunctional\s+core\b|
            \bsteering_queue\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : transition_core_with_live_input
exemplar  : anomalyco/opencode packages/core/src/session/inbox.ts:54
support   : packages/core/test/session-runner.test.ts:1 (test)
negative  : A mutable global message list without transition semantics is
            insufficient.
```

P07 / A1. Cache-dialect fanout. Adapt caching to provider-specific interfaces. *Protected contract:* Cache identity and response-association rules. *Permitted variation:* Provider hints and encodings through dialect adapters. *Consequence / validation:* Test invalidation, privacy boundaries, and unsupported hints. *Source:* Barbaste et al. [6], Table 12, p. 53 (OpenCode, "Cache-Dialect Fanout); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:prompt[_-]?cache|cache[_-]?control|cache[_-]?key|
            cache[_-]?hint|dialect)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
```

```
joinpoint : provider_request_construction
exemplar  : openai/openai-agents-python
            src/agents/run_internal/prompt_cache_key.py:17
support   : tests/test_prompt_cache_key.py:1 (test)
negative  : A generic response cache is not provider-dialect cache control.
```

P08 / A1. Multi-provider transport abstraction. Swap model backends. *Protected contract:* Common request, response, and error interface. *Permitted variation:* Provider transports through adapters and configuration. *Consequence / validation:* Shared schemas can hide differences in tools, usage, or retries. *Source:* Barbaste et al. [6], §7.1, p. 18 ("Provider Abstraction Spectrum: multi-provider via an abstraction layer or owned transports); merged label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:model[_-]?provider|provider[_-]?model|model[_-]?adapter|
            LLMClient|ModelClient)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : model_backend_resolution
exemplar  : openai/openai-agents-python src/agents/models/interface.py:150
support   : tests/models/test_reasoning_content.py:25 (test)
negative  : A single hard-coded vendor client is not the abstraction.
```

P09 / A1. Deferred tool loading. Discover capabilities only when needed. *Protected contract:* Discovery, authorization, and invocation contract. *Permitted variation:* Tool descriptions and implementations through lazy registries. *Consequence / validation:* Smaller context adds discovery latency; test permission checks after loading. *Source:* Barbaste et al. [6], §8.3, p. 27 ("Deferred Tool Loading); Table 11, p. 52; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bdeferred(?:[_-]?\w+)?\b|\blazy[_-]?(?:tool|load)|
            \btool[_-]?search\b|\bdiscover[_-]?tools\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : tool_discovery_to_invocation
exemplar  : openai/openai-agents-python src/agents/tool.py:1641
support   : tests/test_run_internal_items.py:279 (test)
negative  : A large static tool list does not satisfy deferred loading.
```

P10 / A1/A2. Capped output and remediation errors. Bound observations while enabling recovery. *Protected contract:* Output limits and explicit error/truncation status. *Permitted variation:* Limits, summaries, and repair hints through result adapters. *Consequence / validation:* Truncation can hide evidence; retain access to complete artifacts. *Source:* Barbaste et al. [6], §8.4, p. 28 (edit-error recovery) and Recommendation 3, §16.3, p. 68 (output truncation); our synthesis, not a named source pattern

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:max_output|output[_-]?limit|truncat(?:e|ed|ion)|remediat(?:e|
            ion))\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : observation_boundary
exemplar  : openai/openai-agents-python
            src/agents/sandbox/util/token_truncation.py:73
support   : tests/sandbox/test_token_truncation.py:1 (test)
negative  : A logging length limit unrelated to agent observations does not count.
```

P11 / A1. Tool–workflow boundary. Distinguish an operation from an orchestration. *Protected contract:* Tool effect/result contract and workflow ownership. *Permitted variation:* Multi-step procedures through workflow composition. *Consequence / validation:* Avoid hidden loops, duplicate retries, and ambiguous cost accounting. *Source:* Barbaste et al. [6], §14.1, p. 59 (Signal 3, "The disappearing boundary between tool and workflow); our reframing as a boundary to declare

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:tool[_-]?workflow|workflow[_-]?tool|workflow)\b.*\b(?:tool|
            agent)\b|\b(?:tool|agent)\b.*\bworkflow\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : operation_versus_orchestration
exemplar  : OpenHands/software-agent-sdk
            openhands-tools/openhands/tools/workflow/definition.py:1
support   : tests/tools/workflow/test_workflow_tool.py:1 (test)
negative  : A single function that happens to call another function is not enough.
```

P12 / A1. Coordinator–worker spawn flow. Delegate bounded subtasks. *Protected contract:* Task envelope, identity, and result-return protocol. *Permitted variation:* Worker roles and allocation through spawning and dispatch. *Consequence / validation:* Check delegated authority, budgets, and loss of shared context. *Source:* Barbaste et al. [6], §6.4, p. 16 (“Coordinator-Worker Pattern); Table 11 “Recursive Composition, p. 52; adapted label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:spawn(?:ed|ing)?|sub[_-]?agent|worker[_-]?agent|delegate(?:d|s|
            ion)?)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : delegated_task_spawn
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/subagent/schema.py:202
support   : tests/sdk/subagent/test_subagent_registry.py:1 (test)
negative  : Sequential calls to independent agents without delegation do not count.
```

P13 / A1/A3. Log-as-queue loops. Drive work from a durable execution record. *Protected contract:* Event identity and append/consume semantics. *Permitted variation:* History projection and consumption through log adapters. *Consequence / validation:* Replay must not repeat irreversible external effects. *Source:* Barbaste et al. [6], §6.2, p. 15 (OpenCode, “Log-as-Queue Loop); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:event[_-]?log|append[_-]?(?:event|item)|event[_-]?queue|
            log[_-]?as[_-]?queue)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : durable_work_consumption
exemplar  : OpenHands/automation openhands/automation/models.py:222
support   : tests/test_scheduler.py:703 (test)
negative  : An in-memory queue is not log-as-queue.
```

P14 / A1/A3. Event-sourced conversation engine. Reconstruct state from recorded events. *Protected contract:* Event schema, ordering, and projection rules. *Permitted variation:* Views and migrations through versioned projectors. *Consequence / validation:* Test schema evolution and incomplete or sensitive histories. *Source:* Barbaste et al. [6], §6.2, p. 13 (OpenHands, “Event-Sourced Conversation Engine); Table 11 “Event Sourcing, p. 52; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:event[_-]?sourc(?:e|ed|ing)|conversation[_-]?events|
            append[_-]?event|projection)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : conversation_state_projection
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/conversation/state.py:342
support   : tests/sdk/conversation/local/test_state_serialization.py:234 (test)
negative  : A mutable message array without projection semantics is insufficient.
```

P15 / A1/A3. Declarative skills. Package reusable task procedures. *Protected contract:* Skill discovery/loading and execution boundaries. *Permitted variation:* Instructions and resources through manifests or skill files. *Consequence / validation:* Check provenance, staleness, and authority of loaded instructions. *Source:* Barbaste et al. [6], §14.1, p. 59 (Signal 1, "Skills as declarative programs); §12.5; Table 11, p. 52; adapted label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:skills?[_-]?(?:loader|registry|catalog|service)|
            load[_-]?skills?|SKILL\.md)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : reusable_procedure_loading
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/skills/skill.py:179
support   : tests/sdk/skills/test_skill_md_convention.py:1 (test)
negative  : A prompt template string without discovery or resource boundaries is
            not enough.
```

P16 / A1/A3. Hooks and event bus. Extend behavior at named events. *Protected contract:* Event vocabulary, ordering, and interception semantics. *Permitted variation:* Handlers through registration and subscription. *Consequence / validation:* Test reentrancy, hidden dependencies, and conflicting handlers. *Source:* Barbaste et al. [6], §14.1, p. 59 (Signal 2, "Hooks and event buses as the extension substrate); adapted label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:event[_-]?bus|hooks?[_-]?(?:manager|registry|system)|
            register[_-]?hook|subscribe)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : named_lifecycle_event
exemplar  : microsoft/agent-framework
            python/packages/core/agent_framework/_agent_hooks.py:3
support   : python/packages/core/tests/core/test_agent_hooks.py:189 (test)
negative  : A direct logging statement is not an extensible hook.
```

P17 / A2. Verify-on-stop guards. Check artifacts before accepting completion. *Protected contract:* Exit interception and acceptance interface. *Permitted variation:* Project tests through controlled verification hooks. *Consequence / validation:* Test bypasses, flaky checks, and unavailable evaluators. *Source:* Barbaste et al. [6], §6.2, p. 15 (Hermes stop-guards); Table 12 "Outer Verification Loop, p. 53; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:verify[_-]?on[_-]?stop|before[_-]?stop|stop[_-]?verif|
            completion[_-]?check|acceptance[_-]?check)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : verifyonstop, beforestop, stopverify, completioncheck, acceptancecheck
# anchoring and review
joinpoint : terminal_acceptance_interception
exemplar  : Darwin-Agent/HarnessX harnessx/processors/control/self_verify.py:95
support   : tests/unit/test_processor_triggers.py:336 (test)
negative  : Tests run by the user after the run are not verify-on-stop.
coded     : 1 exact candidate cell under 200 prompt profiles
```

P18 / A2. Hybrid loop detection. Detect stalled or repetitive behavior. *Protected contract:* Observation and intervention interface. *Permitted variation:* Signals and thresholds through detector composition. *Consequence / validation:* False positives can stop useful exploration; measure both error types. *Source:* Barbaste et al. [6], §6.2, p. 15 (Gemini CLI, "Hybrid Loop Detection); Table 11 "Stuck Detection, p. 52; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:loop[_-]?detect(?:ion|or)?|doom[_-]?loop|repetition[_-]?detect|
            stuck[_-]?(?:detect|loop))\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
```

```
aliases   : loopdetect, doomloop, repetitiondetect, stuckloop
# anchoring and review
joinpoint : repetitive_behavior_observation
exemplar  : Darwin-Agent/HarnessX harnessx/processors/control/loop_detection.py:38
support   : tests/unit/test_processor_triggers.py:135 (test)
negative  : A recursion depth limit alone is not semantic loop detection.
coded     : 3 exact candidate cells under 200 prompt profiles
```

P19 / A2. Budgeted loop with caps. Bound execution resources. *Protected contract:* Accounting and exhaustion semantics. *Permitted variation:* Allowances and escalation through budget policies. *Consequence / validation:* Exhaustion is not success; account for parallel and delegated work. *Source:* Barbaste et al. [6], §6.2, p. 15 (Hermes, "Budgeted Loop with Stop-Guards); adapted label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:max_(?:turns|steps|iterations)|step[_-]?limit|
            budget[_-]?(?:policy|limit)|token[_-]?budget)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : resource_accounting_cycle
exemplar  : anomalyco/opencode packages/core/src/session/runner/max-steps.ts:1
support   : packages/core/test/session-runner.test.ts:1 (test)
negative  : A constant limit in an unrelated library does not meet the pointcut.
```

P20 / A2/A3. Reflection-augmented loop. Use feedback to revise attempts. *Protected contract:* Attempt/feedback record and retry limits. *Permitted variation:* Critique prompts and memory through feedback injection. *Consequence / validation:* Self-critique may share solver errors; revalidate independently. *Source:* Barbaste et al. [6], §6.3, p. 16 ("Reflection-Augmented Loop); Table 11 "Reflection Loop, p. 52; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:reflection|self[_-]?critique|critique|reflexion)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : failed_attempt_feedback
exemplar  : OpenHands/software-agent-sdk
            examples/01_standalone_sdk/31_iterative_refinement.py:370
support   : tests/sdk/agent/test_iterative_refinement.py:111 (test)
negative  : A static system prompt asking the model to reflect is not enough.
```

P21 / A2. Syntax-aware command permissioning. Inspect command structure before execution. *Protected contract:* Parse / authorize / execute boundary. *Permitted variation:* Rules through syntax-aware policy handlers. *Consequence / validation:* Parsing alone does not establish intent or prevent execution bypasses. *Source:* Barbaste et al. [6], §10.9, p. 39 (OpenCode); Table 12 "Syntax-Aware Command Permissioning, p. 53; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:shell[_-]?pars|command[_-]?pars|bash[_-]?pars|syntax[_-]?aware|
            authorize[_-]?command)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : shellparse, commandparse, syntaxaware, authorizecommand
# anchoring and review
joinpoint : command_authorization_boundary
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/security/shell_parser.py:58
support   : tests/sdk/security/test_shell_parser.py:1 (test)
negative  : A substring denylist is not syntax-aware permissioning.
coded     : 7 exact candidate cells under 200 prompt profiles
```

P22 / A2. Policy floor. Preserve minimum restrictions across customization. *Protected contract:* Minimum authorization contract and privileged change process. *Permitted variation:* Stricter project rules through policy composition. *Consequence / validation:* Test precedence and attempts to weaken inherited restrictions. *Source:* Barbaste et al. [6], §10.7, p. 38 (Hermes, "A Policy Floor

That Survives YOLO); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:policy[_-]?floor|minimum[_-]?policy|deny[_-]?rules?|
            policy[_-]?composition)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : policyfloor, minimumpolicy, denyrules, policycomposition
# anchoring and review
joinpoint : policy_composition
exemplar  : anomalyco/opencode packages/core/src/permission.ts:20
support   : packages/core/test/permission.test.ts:1 (test)
negative  : A single configurable allowlist has no composition floor.
```

P23 / A2. Layered permission and sandbox. Combine policy decisions with execution isolation. *Protected contract:* Authorization and environment-enforcement boundaries. *Permitted variation:* Profiles and adapters through explicit policy/sandbox interfaces. *Consequence / validation:* Check gaps between approved intent and actual side effects. *Source:* Barbaste et al. [6], §10.1, p. 35 (Claude Code, "Three-Layered Permission System); §10.2, p. 36 (Codex permission stack with native sandboxing); merged label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:sandbox|container|permission[_-]?profile|policy[_-]?engine)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : authorized_action_environment
exemplar  : openai/openai-agents-python src/agents/sandbox/sandbox_agent.py:31
support   : tests/sandbox/test_mount_security.py:1 (test)
negative  : A prompt warning without execution enforcement is not a sandbox.
```

P24 / A2. Guardian approval reviewer. Review risky proposed actions. *Protected contract:* Review/escalation protocol and reviewer access boundary. *Permitted variation:* Rubrics and review models through a separate role. *Consequence / validation:* Independence is not automatic; test shared-context contamination and bypasses. *Source:* Barbaste et al. [6], §10.2, p. 36 (Codex, "Guardian, an LLM Approval Reviewer); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:guardian|approval[_-]?(?:request|callback|handler)|
            review[_-]?action|human[_-]?approval)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : risky_action_escalation
exemplar  : openai/openai-agents-python src/agents/tool.py:1498
support   : tests/test_function_tool_approval_arguments.py:1 (test)
negative  : A post-hoc warning after execution is not an approval gate.
```

P25 / A2. Scope-based authorization and profiles. Bind capabilities to explicit scopes. *Protected contract:* Scope identity and authorization-resolution rules. *Permitted variation:* Profiles through scoped capability configuration. *Consequence / validation:* Test privilege inheritance, revocation, and cross-scope access. *Source:* Barbaste et al. [6], §10.4, p. 37 (OpenClaw, "Scope-Based Authorization); §10.6, p. 38 (Mistral Vibe agent-profile gates); merged label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:scope[sd]?|capabilit(?:y|ies)|authorization[_-]?profile|
            permission[_-]?scope)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : capability_resolution
exemplar  : openclaw/openclaw src/gateway/method-scopes.ts:215
support   : src/shared/operator-scope-compat.test.ts:64 (test)
negative  : A boolean admin flag is not a scope model.
```

P26 / A3. Session-tree version control. Branch or revisit execution history. *Protected contract:*

Node identity, ancestry, and provenance. *Permitted variation:* Forking/pruning through branch and checkpoint interfaces. *Consequence / validation:* Local rollback cannot undo external side effects. *Source:* Barbaste et al. [6], Table 12, p. 53 (Pi; OpenHands conversation tree, "Session-Tree Version Control); source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:checkpoint|session[_-]?tree|fork[_-]?(?:session|conversation|
            thread)|branch[_-]?(?:session|conversation))\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : conversation_history_branch
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/conversation/impl/local_conversation.py:861
support   : tests/sdk/conversation/local/test_conversation_tree.py:1 (test)
negative  : Workspace checkpoint without conversation branching is only partial.
```

P27 / A3. Lineage and threshold compaction. Bound history while retaining useful state. *Protected contract:* Lineage links and retained-evidence contract. *Permitted variation:* Thresholds and summaries through compaction policies. *Consequence / validation:* Measure lost facts and later verification failures, not only tokens saved. *Source:* Barbaste et al. [6], §9.5, p. 32 ("Threshold Compaction); §9.5, p. 33 (Hermes, "Lineage Compaction); merged label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:compact(?:ion|ed|or)?|summari[sz](?:e|ation)|
            truncate[_-]?history|token[_-]?limited[_-]?history)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : context_projection
exemplar  : anomalyco/opencode packages/core/src/session/compaction.ts:298
support   : packages/core/test/session-native-compaction.test.ts:213 (test)
negative  : A generic text truncate utility is not compaction without lineage.
```

P28 / A3. Agent-maintained memory pipelines. Update reusable task memory. *Protected contract:* Memory provenance, access, and revision interface. *Permitted variation:* Selection and consolidation through memory-update stages. *Consequence / validation:* Test stale or poisoned memory and self-reinforcing errors. *Source:* Barbaste et al. [6], §9.6, p. 33 ("Persistent Memory Pipelines); Table 12 "Agent-Maintained Memory, p. 53; source label

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:memory[_-]?(?:pipeline|store|update|manager)|remember|
            memories)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : reusable_memory_update
exemplar  : mastra-ai/mastra
            packages/memory/src/processors/observational-memory/observational-memory.ts
             :423
support   : packages/memory/src/processors/observational-memory/__tests__/observational-
             memory.test.ts:1 (test)
negative  : A chat transcript retained in memory is not an update pipeline.
```

P29 / A1/A3. Harness mimicry and service hosting. Preserve an interface while changing its implementation or host. *Protected contract:* Compatibility and service-boundary contract. *Permitted variation:* Backends through emulation or service adapters. *Consequence / validation:* Matching an interface does not guarantee equivalent effects or permissions. *Source:* Barbaste et al. [6], Table 12, p. 53 (Pi, "Harness Mimicry); §13.3, p. 58 (ACP harness hosting); merged label, interface-preservation reading ours

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:mimic(?:ry)?|emulat(?:e|ion)|ACP[_-]?client|
            agent[_-]?client[_-]?protocol)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
```

```
aliases   : none
# anchoring and review
joinpoint : external_harness_compatibility
exemplar  : OpenHands/software-agent-sdk
            openhands-sdk/openhands/sdk/agent/acp_agent.py:1815
support   : tests/sdk/agent/test_acp_agent.py:1 (test)
negative  : A similar function signature without protocol compatibility is
            insufficient.
```

W. Official-guide workflows and coordination patterns

W01 / A1. Prompt chaining. Pass intermediate results through planned stages. *Protected contract:* Stage order and input/output contract. *Permitted variation:* Stage prompts and checks through sequential composition. *Consequence / validation:* Intermediate errors propagate; compare with a simpler single call. *Source:* Anthropic [2, 3]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:prompt[_-]?chain(?:ing)?|chain[_-]?(?:prompt|agent)|
            sequential[_-]?(?:workflow|pipeline))\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : promptchain, sequentialagent, sequentialpipeline
# anchoring and review
joinpoint : sequential_stage_composition
exemplar  : google/adk-python src/google/adk/agents/sequential_agent.py:91
support   : tests/unittests/agents/test_sequential_agent.py:80 (test)
negative  : Independent prompts with no intermediate-result dependency do not count.
```

W02 / A1. Routing. Select a specialized path for an input. *Protected contract:* Route schema and dispatch interface. *Permitted variation:* Classifier and route implementations through conditional dispatch. *Consequence / validation:* Test misrouting and unsupported inputs; expose selection cost. *Source:* Anthropic [2, 3]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:route(?:r|s|d|ing)?|dispatch[_-]?route|handoff[_-]?route)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : input_dispatch
exemplar  : openai/openai-agents-python examples/agent_patterns/routing.py:10
support   : examples/agent_patterns/README.md:21 (documentation)
negative  : An if statement inside one prompt is not an observable routing contract.
```

W03 / A1. Parallelization. Run independent work or alternative judgments concurrently. *Protected contract:* Fan-out/fan-in and aggregation contract. *Permitted variation:* Partitions, voters, and reducers through parallel composition. *Consequence / validation:* Correlated errors can defeat voting; account for all workers. *Source:* Anthropic [2, 3]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:fan[_-]?out|fan[_-]?in|parallel[_-]?(?:run|agent|workflow)|
            Promise\.all|asyncio\.gather)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : fan_out_fan_in
exemplar  : openai/openai-agents-python examples/agent_patterns/parallelization.py:7
support   : examples/agent_patterns/README.md:45 (documentation)
negative  : Bare Promise.all without a fan-in contract is only a cue.
```

W04 / A1. Orchestrator–workers. Generate and delegate subtasks dynamically. *Protected contract:* Delegation and result-synthesis protocol. *Permitted variation:* Task decomposition and workers through dynamic dispatch. *Consequence / validation:* Test decomposition quality, delegated authority, and duplicate effort. *Source:* Anthropic [2, 3]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:orchestrator|orchestrate|task[_-]?decomposition|
```

```
            worker[_-]?agent|dynamic[_-]?dispatch)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : dynamic_task_decomposition
exemplar  : OpenHands/software-agent-sdk
            examples/01_standalone_sdk/42_file_based_subagents.py:24
support   : tests/sdk/subagent/test_subagent_registry.py:1 (test)
negative  : A fixed sequence of sub-agents is W01 rather than dynamic W04.
```

W05 / A2/A3. Evaluator–optimizer. Revise an artifact using iterative feedback. *Protected contract:* Evaluation/revision interface and stopping rules. *Permitted variation:* Rubrics and revisions through an explicit feedback loop. *Consequence / validation:* Do not confuse repeated selection feedback with independent final evaluation. *Source:* Anthropic [2, 3]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:evaluator[_-]?optimizer|optimizer|evaluation[_-]?feedback|
            revision[_-]?loop)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : generate_evaluate_revise
exemplar  : openai/openai-agents-python examples/agent_patterns/llm_as_a_judge.py:47
support   : examples/agent_patterns/README.md:1 (documentation)
negative  : One model call that says it improved itself is not enough.
```

W06 / A1. Manager coordination. Keep a coordinating agent in control of specialists. *Protected contract:* Manager-owned delegation and result integration. *Permitted variation:* Specialist agents through callable agent interfaces. *Consequence / validation:* The manager can bottleneck or distort evidence from specialists. *Source:* OpenAI [36]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:manager[_-]?agent|supervisor|coordinator[_-]?agent|
            manager[_-]?coordination)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : manager_owned_specialist_work
exemplar  : crewAIInc/crewAI lib/crewai/src/crewai/crew.py:1533
support   : lib/crewai/tests/test_crew.py:1 (test)
negative  : A coordinator that merely launches tasks without integration is W04.
```

W07 / A1. Decentralized handoffs. Transfer control to another specialized agent. *Protected contract:* Control-transfer, state, and authority contract. *Permitted variation:* Handoff targets and criteria through explicit transitions. *Consequence / validation:* Check lost context, circular handoffs, and privilege transfer. *Source:* OpenAI [36]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:hand[_-]?offs?|transfer[_-]?to|transfer[_-]?agent|
            decentrali[sz]ed[_-]?handoff)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : peer_control_transfer
exemplar  : openai/openai-agents-python src/agents/handoffs/__init__.py:127
support   : tests/test_handoff_tool.py:1 (test)
negative  : A normal function call that returns to the caller is not a handoff.
```

C. Communication patterns discussed in agent literature

C01 / A1. Mediator. Coordinate interactions through an intermediary. *Protected contract:* Participant/message and coordination interface. *Permitted variation:* Participants and policies through mediated dispatch. *Consequence / validation:* Central coordination can become a bottleneck or failure point. *Source:* Sarkar and Sarkar [40]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:mediator|message[_-]?mediator|coordination[_-]?interface)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : mediator, messagecoordinator, coordinationinterface
# anchoring and review
joinpoint : participant_interaction_coordination
exemplar  : microsoft/autogen
            python/packages/autogen-agentchat/src/autogen_agentchat/teams/_group_chat/
             _base_group_chat_manager.py:25
support   : python/packages/autogen-agentchat/tests/test_group_chat.py:1 (test)
negative  : A shared global object is not necessarily a mediator.
```

C02 / A1. Observer. Notify registered dependents of changes. *Protected contract:* Subscription and notification contract. *Permitted variation:* Observers through registration callbacks. *Consequence / validation:* Check ordering, stale subscriptions, and notification cascades. *Source:* Sarkar and Sarkar [40]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:Observer|observer|add[_-]?listener|register[_-]?(?:listener|
            observer))\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : subject_change_notification
exemplar  : mastra-ai/mastra packages/core/src/events/event-emitter/index.ts:21
support   : packages/core/src/events/unix-socket-pubsub-solo.test.ts:54 (test)
negative  : Polling the subject rather than notification is not the observer
            pointcut.
```

C03 / A1/A3. Publish–subscribe. Decouple producers from consumers. *Protected contract:* Topic/event schema and delivery semantics. *Permitted variation:* Subscribers and filters through a topic bus. *Consequence / validation:* Define duplication, ordering, durability, and subscriber authorization. *Source:* Sarkar and Sarkar [40]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:pub(?:lish)?[_-]?sub(?:scribe)?|topic[_-]?bus|event[_-]?bus|
            subscriber)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : topic_based_event_delivery
exemplar  : mastra-ai/mastra packages/core/src/events/pubsub.ts:19
support   : packages/core/src/events/subscribe-start-position.test.ts:25 (test)
negative  : Directly invoking known listeners is C02 rather than C03.
```

C04 / A1. Broker. Mediate discovery and invocation across boundaries. *Protected contract:* Service-description and request/reply contract. *Permitted variation:* Providers and transports through broker registration. *Consequence / validation:* Check schema mismatch, trust, and broker availability. *Source:* Sarkar and Sarkar [40]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:broker|provider[_-]?registry|tool[_-]?registry|
            service[_-]?registry)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : service_discovery_invocation
exemplar  : mastra-ai/mastra packages/core/src/events/unix-socket-pubsub.ts:325
support   : packages/core/src/events/unix-socket-pubsub-codec.test.ts:62 (test)
negative  : A local factory returning implementations is only a registry cue.
```

R. Reasoning and feedback patterns

R01 / A1. Reason–act–observe (ReAct). Interleave reasoning and external actions. *Protected contract:* Action/observation interaction protocol. *Permitted variation:* Prompts and tools through

the action interface. *Consequence / validation:* Tool feedback can correct or compound errors; reasoning is not verification. *Source:* Yao et al. [57]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bReAct\b|\breason[_-]?act[_-]?observe\b|\bThought:\s|\bAction:\s
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : interleaved_reasoning_and_action
exemplar  : huggingface/smolagents src/smolagents/agents.py:270
support   : tests/test_agents.py:217 (test)
negative  : Chain-of-thought text without external action is not ReAct.
```

R02 / A2/A3. Verbal reflection memory. Reuse feedback across attempts. *Protected contract:* Feedback and memory retrieval/update interface. *Permitted variation:* Reflections through a verbal-memory loop. *Consequence / validation:* Persistent reflections can preserve mistaken explanations as well as useful advice. *Source:* Shinn et al. [43]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:Reflexion|verbal[_-]?reflection|reflection[_-]?memory|
            episodic[_-]?memory)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : reflectionmemory, episodicmemory, lessonslearned, reflexion
# anchoring and review
joinpoint : feedback_reuse_across_attempts
exemplar  : mastra-ai/mastra
            packages/memory/src/processors/observational-memory/reflector-agent.ts:50
support   : packages/memory/src/processors/observational-memory/__tests__/observational-
             memory.test.ts:10564 (test)
negative  : A generic conversation history is not a reflection-memory contract.
coded     : 1 exact candidate cell under 200 prompt profiles
```

E. Instantiated evolution mechanisms: not established recurring patterns

E01 / A1/A3. Inheritance and polymorphic routing. Specialize related harnesses. *Protected contract:* Base interfaces and inherited behavior constraints. *Permitted variation:* Subclasses and router through overrides and dispatch. *Consequence / validation:* Compare with composition; inheritance does not itself enforce safety. *Source:* Li et al. [25]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bclass\s+\w*Agent\w*|\bextends\s+\w*Agent\w*|
            \binherits?\s+from\s+\w*Agent\w*
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : harness_specialization_via_subtype
exemplar  : crewAIInc/crewAI lib/crewai/src/crewai/agent/core.py:223
support   : lib/crewai/tests/test_crew.py:4770 (test)
negative  : A class hierarchy with no harness dispatch does not count.
```

E02 / A3. Propose–Probe–Compose. Improve a harness using contrastive probes. *Protected contract:* Executor/evaluation interface and explicit edit scope. *Permitted variation:* Harness components through proposal, probing, and composition. *Consequence / validation:* Task-time adaptation needs its own permissions and cost accounting. *Source:* Xu et al. [55]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\bpropose[_-]?probe[_-]?compose\b|\bproposal\b.*\bprobe\b|
            \bprobe\b.*\bcompose\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : proposeprobecompose, candidateprobe, harnesseditcycle
# anchoring and review
joinpoint : harness_edit_cycle
exemplar  : google-research/harness2 harness2/core/recursion.py:360
support   : tests/test_workflow.py:139 (test)
negative  : A one-shot prompt rewrite without probes is not E02.
```

E03 / A2/A3. Regularized harness improvement. Limit overfitting during repeated edits. *Protected contract:* Acceptance protocol and evaluation-access rules. *Permitted variation:* Edit budgets, screening, and thresholds through regularized selection. *Consequence / validation:* Repeated selection data are not an untouched final test. *Source:* Xia et al. [53]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:regulariz(?:e|ed|ation)|overfit|hold[_-]?out|
            validation[_-]?suite)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : none
# anchoring and review
joinpoint : repeated_acceptance_decision
exemplar  : google-research/rrsi rrsi/critic.py:28
support   : tests/test_core.py:128 (test)
negative  : Best-of-many tuning on the test metric is not regularized improvement.
```

E04 / A2/A3. Multi-objective evolution and composition. Search among competing objectives. *Protected contract:* Evaluator interface and objective definitions. *Permitted variation:* Tools, skills, and logic through factorized search and composition. *Consequence / validation:* Report trade-offs and constraint failures, not only one aggregate score. *Source:* Yu et al. [59]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:multi[_-]?objective|pareto|fitness[_-]?function|
            objective[_-]?weights?)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : multiobjective, paretofront, objectiveweights, candidateselection
# anchoring and review
joinpoint : candidate_harness_selection
exemplar  : mingju-c/HarnessForge HarnessForge_4B/tools/half_select_harnesses.py:108
support   : HarnessForge_4B/registries/README.md:48 (documentation)
negative  : A single accuracy score is not multi-objective selection.
```

E05 / A1/A3. Composable harness foundry. Construct and evolve reusable harness components. *Protected contract:* Component and executor/evaluator interfaces. *Permitted variation:* Components through a compositional search space. *Consequence / validation:* Separate component reuse from leakage or extra search budget. *Source:* Chen et al. [13]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:harness[_-]?foundry|HarnessX|component[_-]?search|
            composable[_-]?harness)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : harnessfoundry, componentsearch, harnessbuild, composeharness
# anchoring and review
joinpoint : harness_component_build_and_evaluate
exemplar  : Darwin-Agent/HarnessX harnessx/core/builder.py:73
support   : tests/unit/test_builder.py:1 (test)
negative  : Separate helper functions without component contracts are insufficient.
coded     : 1 exact candidate cell under 200 prompt profiles
```

E06 / A3. Joint harness–policy evolution. Adapt runtime structure and policy together. *Protected contract:* Task interface and declared evaluation protocol. *Permitted variation:* Harness and policy through joint evolution. *Consequence / validation:* Separate policy gains from harness gains; the model is not necessarily fixed. *Source:* Chen et al. [12]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:joint[_-]?evolution|evolve\w*\s+(?:harness|policy)|
            policy[_-]?evolution)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : coevolution, jointoptim, harnesspolicy, policyevolution
# anchoring and review
joinpoint : coadaptive_training_loop
exemplar  : mingju-c/HarnessForge HarnessForge_4B/evolved_pairs/pairs.yaml:1
support   : README.md:15 (documentation)
negative  : Retraining only the model with a fixed harness is not joint evolution.
coded     : 1 exact candidate cell under 200 prompt profiles
```

E07 / A2/A3. Evaluator-guided program search. Evolve executable candidates. *Protected contract:* Execution and fitness-evaluation interface. *Permitted variation:* Candidate programs through generation and evaluation. *Consequence / validation:* Adjacent program-search precedent, not evidence that every harness is evolvable. *Source:* Novikov et al. [33]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:program[_-]?search|evolve\w*\s+programs?|AlphaEvolve|
            fitness[_-]?evaluation)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : programsearch, fitnessevaluation, evolveprogram, programevolution
# anchoring and review
joinpoint : executable_candidate_generation
exemplar  : Darwin-Agent/HarnessX recipe/gaia_evolver/run_meta.py:437
support   : tests/unit/test_gaia_gating.py:1 (test)
negative  : Prompt-level variation with no executable search is not E07.
```

E08 / A3. On-demand adaptation target selection. Choose harness versus weight adaptation. *Protected contract:* Embodied task/evaluation and adaptation-trigger interface. *Permitted variation:* Adaptation target through conditional self-improvement. *Consequence / validation:* Embodied evidence does not establish coding-agent transfer or reversibility. *Source:* Wang et al. [48]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:adaptation[_-]?target|weight[_-]?adaptation|
            on[_-]?demand[_-]?adaptation)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : adapttarget, targetselection, domainadapt, adaptationtarget
# anchoring and review
joinpoint : embodied_adaptation_decision
exemplar  : none; the record is anchored only in its source specification
negative  : A paper citation or generic fine-tuning script is not an E08 instance.
coded     : 2 exact candidate cells under 200 prompt profiles
```

E09 / A1/A3. Dual-loop assistance. Separate planning and execution feedback. *Protected contract:* Planner/executor and environment-interaction contracts. *Permitted variation:* Plans and assistance policies through linked feedback loops. *Consequence / validation:* Physical actions may be irreversible; evaluate authorization and recovery. *Source:* Wang et al. [49]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:dual[_-]?loop|planner[_-]?executor|assistance[_-]?loop|
            planning[_-]?feedback)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : dualloop, plannerexecutor, assistanceloop, planningfeedback
# anchoring and review
joinpoint : planner_executor_feedback_link
exemplar  : JIA-Lab-research/CarryOn src/carryon/main.py:176
support   : README.md:43 (documentation)
negative  : Two unrelated loops without a feedback link do not meet the pointcut.
```

E10 / A2/A3. Observability-driven harness evolution. Use traces to guide candidate changes. *Protected contract:* Trace/evaluation interface and authorized change scope. *Permitted variation:* Harness candidates through observation, editing, and evaluation. *Consequence / validation:* Better development scores require independent transfer and regression checks. *Source:* Lin et al. [26]

```
# detection: lexical cue, ripgrep -i over code, test, and supporting files
regex     : (?i)\b(?:observability[_-]?driven|trace[_-]?(?:guided|driven)|
            trajectory[_-]?optimi[sz]ation)\b
# matching: code symbol (Python AST or declaration name) -> snake_case -> regex
aliases   : observabilitydriven, tracedriven, traceguided, harnessevolution
# anchoring and review
joinpoint : trace_to_harness_change
exemplar  : china-qijizhifeng/agentic-harness-engineering evolve.py:5
support   : README.md:169 (documentation)
negative  : Logging without a trace-to-change decision is not E10.
```

A.2 Cue Coverage Records

Family coverage counts the 36 repository families with a lexical cue for the record; repository coverage counts the 41 current repositories. The values are raw panel counts of retrieval cues, not counts of pattern instances.

C01 — Mediator. Family coverage: 5/36; repository coverage: 5/41.
C02 — Observer. Family coverage: 29/36; repository coverage: 32/41.
C03 — Publish–subscribe. Family coverage: 24/36; repository coverage: 26/41.
C04 — Broker. Family coverage: 22/36; repository coverage: 23/41.
E01 — Inheritance and polymorphic routing. Family coverage: 33/36; repository coverage: 37/41.
E02 — Propose–Probe–Compose. Family coverage: 6/36; repository coverage: 6/41.
E03 — Regularized harness improvement. Family coverage: 12/36; repository coverage: 12/41.
E04 — Multi-objective evolution and composition. Family coverage: 8/36; repository coverage: 9/41.
E05 — Composable harness foundry. Family coverage: 2/36; repository coverage: 2/41.
E06 — Joint harness–policy evolution. Family coverage: 1/36; repository coverage: 1/41.
E07 — Evaluator-guided program search. Family coverage: 3/36; repository coverage: 3/41.
E08 — On-demand adaptation target selection. Family coverage: 0/36; repository coverage: 0/41.
E09 — Dual-loop assistance. Family coverage: 3/36; repository coverage: 3/41.
E10 — Observability-driven harness evolution. Family coverage: 1/36; repository coverage: 1/41.
P01 — Minimal linear loop. Family coverage: 35/36; repository coverage: 39/41.
P02 — Streaming concurrent batch loop. Family coverage: 36/36; repository coverage: 40/41.
P03 — Asynchronous state machine. Family coverage: 34/36; repository coverage: 38/41.
P04 — Middleware-pipeline loop. Family coverage: 34/36; repository coverage: 38/41.
P05 — Asynchronous-generator loop. Family coverage: 25/36; repository coverage: 28/41.
P06 — Functional core and steering queues. Family coverage: 25/36; repository coverage: 26/41.
P07 — Cache-dialect fanout. Family coverage: 34/36; repository coverage: 38/41.
P08 — Multi-provider transport abstraction. Family coverage: 28/36; repository coverage: 31/41.
P09 — Deferred tool loading. Family coverage: 32/36; repository coverage: 35/41.
P10 — Capped output and remediation errors. Family coverage: 36/36; repository coverage: 40/41.
P11 — Tool–workflow boundary. Family coverage: 30/36; repository coverage: 34/41.
P12 — Coordinator–worker spawn flow. Family coverage: 36/36; repository coverage: 41/41.
P13 — Log-as-queue loops. Family coverage: 22/36; repository coverage: 24/41.
P14 — Event-sourced conversation engine. Family coverage: 31/36; repository coverage: 34/41.
P15 — Declarative skills. Family coverage: 30/36; repository coverage: 33/41.
P16 — Hooks and event bus. Family coverage: 31/36; repository coverage: 34/41.
P17 — Verify-on-stop guards. Family coverage: 8/36; repository coverage: 8/41.
P18 — Hybrid loop detection. Family coverage: 8/36; repository coverage: 8/41.
P19 — Budgeted loop with caps. Family coverage: 27/36; repository coverage: 30/41.
P20 — Reflection-augmented loop. Family coverage: 29/36; repository coverage: 32/41.
P21 — Syntax-aware command permissioning. Family coverage: 2/36; repository coverage: 2/41.
P22 — Policy floor. Family coverage: 8/36; repository coverage: 8/41.
P23 — Layered permission and sandbox. Family coverage: 36/36; repository coverage: 40/41.
P24 — Guardian approval reviewer. Family coverage: 22/36; repository coverage: 23/41.
P25 — Scope-based authorization and profiles. Family coverage: 36/36; repository coverage: 41/41.

P26 — Session-tree version control. Family coverage: 30/36; repository coverage: 32/41.
P27 — Lineage and threshold compaction. Family coverage: 35/36; repository coverage: 39/41.
P28 — Agent-maintained memory pipelines. Family coverage: 34/36; repository coverage: 38/41.
P29 — Harness mimicry and service hosting. Family coverage: 29/36; repository coverage: 32/41.
R01 — Reason–act–observe (ReAct). Family coverage: 35/36; repository coverage: 39/41.
R02 — Verbal reflection memory. Family coverage: 1/36; repository coverage: 1/41.
W01 — Prompt chaining. Family coverage: 6/36; repository coverage: 7/41.
W02 — Routing. Family coverage: 36/36; repository coverage: 40/41.
W03 — Parallelization. Family coverage: 24/36; repository coverage: 28/41.
W04 — Orchestrator–workers. Family coverage: 30/36; repository coverage: 33/41.
W05 — Evaluator–optimizer. Family coverage: 17/36; repository coverage: 17/41.
W06 — Manager coordination. Family coverage: 27/36; repository coverage: 28/41.
W07 — Decentralized handoffs. Family coverage: 29/36; repository coverage: 33/41.

A.3 Evidence Scope of the Sources

This source note qualifies the inventory in this appendix; it does not add evidence for the position. Classical books and papers are scholarly references, including GoF, POSA, AOSD, DDD, modular decomposition, and test seams. Practitioner guides, software documentation, and commentary are cited as BibTeX `@misc` entries. Dates not established in the source records are marked "n.d." rather than inferred. Publication-year notes distinguish the publisher's first-publication dates from the copyright years for GoF and DDD.

POSA is a five-volume series: *A System of Patterns* (1996), *Patterns for Concurrent and Networked Objects* (2000), *Patterns for Resource Management* (2004), *A Pattern Language for Distributed Computing* (2007), and *On Patterns and Pattern Languages* (2007). Volume 4 is about distributed computing, not a dedicated testing catalog. The references distinguish these books rather than assigning one scope to the entire series.

Frontier-lab technical reports and system cards document model configurations and laboratory risk assessments [34, 35, 17, 18]. They do not replace independent evaluation of a particular harness. Constitutional AI is additional background on model-based feedback [4], not evidence for our taxonomy's completeness.

A.4 Representative UML Class Views

The inventory is a record catalog, not a plate book. These three views show the range of participant structures without repeating a full-page drawing after every record. Each class box is a proposed participant role; its operation compartment lists the calls that role receives. Numbered dashed arrows are call dependencies, and brown arrows are returns or failures. The relationship panel restates every call, so the drawing does not depend on following a crossing arrow. The pointcut, contract, variation, test, and negative-control panels are generated from the frozen specification.

The views are analytical reconstructions of proposed contracts, not observed execution traces or repository class declarations.




Figure 11 P01, Minimal linear loop: a UML class view of the proposed record. (A^2 coordinate A1.) Each role class lists the calls it receives; numbered dashed arrows are call dependencies, and brown arrows are returns or failures. The lower panels restate the pointcut, contract, variation, test obligation, negative control, and the complete numbered call list. The view is an analytical reconstruction of the proposed contract, not an observed execution or a repository class declaration.

B Exploratory Repository Audit: Protocol, Statistics, and Reproducibility

This appendix documents the protocol behind the exploratory lexical-cue audit whose observations are reported in Section 3.2, together with the sensitivity analyses and model-assisted coding that check them. The audit is an observational, model-assisted study of a purposive panel. It retrieves vocabulary, anchors each record in one curated exemplar, and codes a small set of exact structural candidates. All results describe this panel and this instrument. They are supporting material for the position and a sampling frame for the independently adjudicated study proposed in Section 7.4.

B.1 Evidence Model, Unit of Analysis, and Statistics

Each record has a frozen specification with a pointcut (context, trigger, structure, and effect), a contract (requires, ensures, invariant, and violation behavior), and a negative control. Detector queries retrieve lexical cues from the current source, test, documentation, and




Figure 12 P11, Tool–workflow boundary: a UML class view of the proposed record. (A^2 coordinate A1.) Each role class lists the calls it receives; numbered dashed arrows are call dependencies, and brown arrows are returns or failures. The lower panels restate the pointcut, contract, variation, test obligation, negative control, and the complete numbered call list. The view is an analytical reconstruction of the proposed contract, not an observed execution or a repository class declaration.

configuration surface of each repository and from sampled historical releases. A canonical locator anchors each record in one source exemplar. A second, layered matcher then looks for exact structural candidates, which are coded against the pointcut and contract fields. Appendix A.1 gives the matching method for every record, including its regular expression, aliases, canonical exemplar, and negative control.

Each candidate-family cell combines three evidence layers: a lexical cue in the frozen current source, test, documentation, and configuration surface, a cue at a sampled historical release, and a canonical source locator curated from the 52-record inventory. A cell with none of these remains *not observed in the available corpus*. This state is distinct from a tested negative: a detector may miss product-specific vocabulary, a surface may omit the relevant subsystem, or the implementation may reside in a different version.

The matrix contains 2,132 cells. A lexical cue was retrieved in 1,265 of them, and seven more are anchored only by a curated exemplar, for 1,272 cells with evidence in total: 44 with canonical and current evidence, seven with a canonical locator only, 565 with current and



Figure 13 E08, On-demand adaptation target selection: a UML class view of the proposed record. (A^2 coordinate A3.) Each role class lists the calls it receives; numbered dashed arrows are call dependencies, and brown arrows are returns or failures. The lower panels restate the pointcut, contract, variation, test obligation, negative control, and the complete numbered call list. The view is an analytical reconstruction of the proposed contract, not an observed execution or a repository class declaration.

historical cues, 637 with current-only cues, and 19 with historical-only cues. The remaining 860 cells are retained as unobserved. Curated exemplars are atlas evidence for a record; they are reported separately from retrieved cues and are not counted as repository observations. Canonical locators cover 51 of 52 candidates; E08 remains represented only by the AdaRSI specification.

The repository family is the independent unit for coverage, and repository-level values are descriptive. Family-level coverage is reported as a raw panel proportion. The panel is purposive and fully observed, so a proportion has no sampling uncertainty within the panel and is not generalized beyond it. Figure 3A also draws two-sided 95% Wilson score intervals; they indicate the resolution of a proportion over 36 units and are not population estimates.

Observed-pattern rarefaction uses 5,000 random orders of the 36 families. Differences among record categories and source pools are screened with exploratory Kruskal–Wallis diagnostics. Because the 52 candidate summaries share one family evidence base, nominal p-values are not confirmatory; a future confirmatory analysis must preserve candidate–family dependence through permutation or hierarchical partial pooling. Co-occurrence is screened for every candidate pair with phi and a two-sided Fisher test across the 36 family indicators, followed by Benjamini–Hochberg correction over 1,326 tests. Lifecycle sequences use a repository-cluster bootstrap with 2,000 resamples (seed 20261107), because states within one realization are repeated observations, and transition probabilities are row-conditional. Because repositories of one family share history, we repeat the bootstrap with the family as the cluster and report both intervals (Table 10). A missing detector cue is recorded as a signal gap, not as retirement, unless a later source or migration record explicitly documents removal. Prompt-profile sensitivity is summarized with pairwise agreement, Fleiss' κ, Gwet's AC1, and Krippendorff's α. The profiles share one model, so these coefficients describe sensitivity to prompts and do not carry their classical independent-rater interpretation.

One held-out retrieval check covered seven predeclared candidates and reported precision and recall of 0.954 on its operational labels. Those labels, queries, and adjudications were produced by the same underlying AI system, creating construction leakage. The result is a procedural consistency check, not an independently validated error model for the remaining 45 candidates or for a broader software population.

B.2 Audit Procedure and Sensitivity Analyses

B.2.0.1 Procedure.

The audit has three steps. Each record has a frozen specification with a pointcut, a contract, and a negative control (Appendix A). A frozen regular expression retrieves lexical cues from the current source, test, documentation, and configuration surface of each repository and from sampled historical releases. A curated exemplar anchors each record in one source location. A layered matcher then selects exact structural candidates, which one model codes against the specification under 200 prompt profiles (Appendix B.3). The first step is retrieval, the second is curation, and the third is model-assisted coding. None is independent human adjudication, and the panel is purposive, so every number in Section 3.2 describes this panel and this instrument. A cue is a retrieval signal, not a pattern instance, and an unobserved cell (860 of 2,132) is kept distinct from absence.

B.2.0.2 Coverage screens.

The exploratory Kruskal–Wallis screen of category coverage gave $H = 17.22$, $p = 0.00175$, and $\epsilon^2 = 0.281$ (five categories, $n = 52$ candidates). Source-pool richness did not differ under the same screen ($H = 1.28$, $p = 0.528$; three pools, $n = 36$ families). Several fully covered records have broad expressions: concurrency terms for P02, delegation terms for P12, sandbox terms for P23, scope terms for P25, and routing terms for W02. Their coverage shows that this vocabulary is common in harness code; it is not a count of pattern instances. The gradient across categories, languages, and source pools describes detector yield. It reflects detector breadth, record granularity, code layout, missing subsystems, and corpus composition as well as architecture, and is not a prevalence estimate. Activity coordinates are our assignments and are confounded with source family, so the activity contrast in Table 9 is descriptive.

Table 20 Sensitivity to family aggregation. The union rule combines all repositories in a family. A one-repository-per-family sample estimates how much this aggregation changes descriptive coverage. Intervals are the 2.5th–97.5th percentiles over 5,000 seeded samples.

Measure	Family union	One repo/family
Median family richness	35.0	34.7 [33.5, 35.0]
Mean pattern-family coverage	61.8%	60.2%
Patterns present in all families	6	4.0
Repository-count/richness correlation	$r = 0.187$	

Table 21 Sensitivity of retrieval coverage to evidence thresholds. All rows count detector or atlas evidence, not adjudicated pointcut matches. The canonical row reflects one atlas exemplar per supported pattern by construction.

Retrieval definition	Cells	Share
Any retrieval evidence	1,272	59.7%
At least one current cue	1,246	58.4%
At least two current cues	1,177	55.2%
At least five current cues	1,049	49.2%
At least one code path	1,077	50.5%
At least two code paths	932	43.7%
At least two code paths plus support	857	40.2%
Canonical atlas exemplar	51	2.4%

B.2.0.3 Family size.

Of the 36 families, 32 contain one repository, three contain two, and one contains three. A seeded sensitivity analysis selected one repository per family: median family richness changed only from 35.0 to 34.7, but the number of candidates present in every sampled family fell from six to about four (Table 20). The repository-count and richness correlation was $r = 0.187$. Family-union coverage therefore describes the combined family surface, not a repository-average prevalence estimate.

B.2.0.4 Evidence threshold.

Almost all observed cells rest on raw current cues, the entry level of retrieval evidence. Raising the threshold shrinks the set (Table 21); requiring at least two current code paths plus support retains 857 of 2,132 cells. Canonical and support locators give one anchor per record by construction, so they measure atlas coverage. A stricter threshold is still a retrieval rule: it removes some single-keyword hits, and how much precision it gains is unknown until cells are adjudicated.

B.2.0.5 Co-occurrence and trajectories.

All co-occurrence pairs reuse the same family matrix and detector vocabulary, so the 22 flags are exploratory. They may reflect detector vocabulary, shared architecture, or lineage, and do not identify dependency or causation. For the trajectories, resampling families instead of repositories moves the interval bounds by at most two percentage points. Of the 1,272 trajectories, 651 (51.2%) have no additional observed checkpoint, so sequence topology is not a complete lifetime reconstruction. Only 29 carry a commit-level introduction record, so

Table 22 Matcher-selected candidates and one-model profile disposition. C/A/R denotes confirmed, ambiguous, and rejected outputs from 200 role-conditioned profiles of one model. These eight cells form a provisional candidate-recall overlay kept separate from the frozen matrix; profile-majority-supported cells enter the overlay.

Pattern	Repository	Votes C/A/R	Disposition	Structural role reviewed
P17	DeerFlow	54/146/0	Unresolved	Post-completion acceptance verdict; checker exceptions do not change completed status, and no enforced stop gate is shown
P18	Pydantic AI	200/0/0	Supported	Live repeated-call/result/text detector with nudge and terminal error
P18	Roo Code	200/0/0	Supported	Consecutive identical tool calls blocked at a configured threshold
P21	Gemini CLI	88/112/0	Unresolved	Parsed commands feed confirmation policy, but the coarse fallback remains disputed
P21	OpenClaw	105/51/44	Supported	Parsed command steps feed allowlist and execution-approval decisions; contract depth varies across profiles
P21	Qwen Code	200/0/0	Supported	AST shell safety classification feeds the permission manager
P21	OpenCode	149/51/0	Supported	Shell scan resolves permission resources before execution; all four contract fields reach majority present coding
R02	CarryOn	200/0/0	Supported	Versioned reflection memory is loaded into later recovery execution

the remaining first observations mark detector entry rather than a dated origin, and the 398 changed trajectories are a lower bound. The labels track cue paths, a level below adjudicated architectural redesign. Sparse checkpoints and changing detectability can produce the same picture, so the sequence counts are not statements about adoption, utility, or architectural lifecycle, nor transition probabilities for unseen repositories. The absence of an explicit retirement record does not show that no mechanism was retired.

B.3 Profile Coding of the Exact Candidates

This subsection gives the details behind the observations in Section 3.2.2. To test whether some unobserved cells are query artifacts, we applied a second matcher over Python AST symbols, multi-language declaration syntax, test, documentation, and configuration artifacts, and path context. An unrestricted first pass overmatched general words, so it was rejected. A stricter pass retained exact symbol-level regex matches or compound aliases, and it retained 16 exact structural candidates. These cells were selected by the matcher rather than sampled from the 2,132-cell matrix, so their dispositions cannot estimate precision, false-negative risk, or contract prevalence. An AI-assisted source triage prioritized eight of them as a candidate-recall overlay: one P17, two P18, four P21, and one R02 realization (Table 22).

One model evaluated all 16 selected candidates under 200 role-conditioned prompt profiles using the same frozen pointcut and contract fields. The 3,200 judgments are correlated prompt




Figure 14 One-model profile sensitivity analysis of exact layered candidates. (A) Output composition for each of the 16 candidates; the dashed line marks the profile-majority threshold of 101 outputs. (B) Number of cells with invariant coding for each decision, pointcut, and contract field. (C) Percentage of profiles marking each contract field present among the six majority-supported pointcuts. Cells without a strict majority remain unresolved and are not promoted. The profiles share one model and are not human raters.

perturbations, not independent ratings or an effective sample size of 3,200. Twelve cells were invariant across profiles. Pairwise profile agreement averaged 0.882 (range 0.750–1.000); Fleiss' κ was 0.798 (cell-bootstrap 95% CI 0.633–0.946), Gwet's AC1 was 0.833, and Krippendorff's α was 0.798. The profiles were invariant on all 16 context and trigger judgments but on only 12 effect judgments. Instability therefore concerns whether a mechanism changes control flow, not whether the relevant code is present. All profiles completed all cells without missing profile–cell pairs. The 95% interval resampled the 16 cell summaries over 10,000 replicates. The agreement coefficients describe sensitivity to these prompt profiles only; their classical independent-rater interpretation does not apply. They are not estimates for the full inventory and do not substitute for human validation.

With supported and rejected dispositions requiring more than 50% of profile outputs, six cells were profile-majority supported: P18 in Pydantic AI and Roo Code, P21 in Qwen Code, OpenCode, and OpenClaw, and R02 in CarryOn. OpenCode received 149 confirmed and 51 ambiguous votes. OpenClaw crossed the majority threshold with 105 confirmed, 51 ambiguous, and 44 rejected votes. Eight cells had unanimous rejections. Two remained unresolved: P17 in DeerFlow (54 confirmed, 146 ambiguous) and P21 in Gemini CLI (88 versus 112). Five of the six supported cells recorded all four contract fields under majority coding. Contract completeness still varies at the individual-profile level, so this does not establish reusable responsibility contracts without further review. Requiring invariance would remove OpenCode and OpenClaw from the supported set, leaving four supported, eight invariantly rejected, and four unresolved cells. The other four supported cells and all eight rejected cells are invariant. The first 100 profiles produced the same 6/8/2 pointcut dispositions, but all six supported cells were then contract-complete. Across all 200 profiles, OpenClaw's violation support fell to 49.5%, reducing contract-complete supported cells to

Table 23 One-model prompt-profile sensitivity analysis of exact layered candidates. One model coded all 16 selected cells under 200 role-conditioned prompts. These correlated outputs are not human or independent raters. C/A/R denotes the model's confirmed, ambiguous, and rejected outputs. Supported and rejected dispositions require more than 50% of profiles; all others remain unresolved. Contract depth is the number of the four contract fields marked present; ranges indicate variation across review profiles.

Pattern	Repository	Votes C/A/R	Disposition	Contract	Interpretation
E05	openclaw/openclaw	0/0/200	Rejected	0/4	Declared effect or boundary absent
E06	openclaw/openclaw	0/0/200	Rejected	0/4	Declared effect or boundary absent
E08	cline/cline	0/0/200	Rejected	0/4	Declared effect or boundary absent
E08	openclaw/openclaw	0/0/200	Rejected	0/4	Declared effect or boundary absent
P17	bytedance/deer-flow	54/146/0	Unresolved	2/4 [2–3]	No absolute majority
P18	RooCodeInc/Roo-Code	200/0/0	Supported	4/4	Profile-majority pointcut match
P18	mastra-ai/mastra	0/0/200	Rejected	1/4	Declared effect or boundary absent
P18	pydantic/pydantic-ai	200/0/0	Supported	4/4	Profile-majority pointcut match
P21	QwenLM/qwen-code	200/0/0	Supported	4/4	Profile-majority pointcut match
P21	anomalyco/opencode	149/51/0	Supported	4/4 [2–4]	Profile-majority pointcut match
P21	bytedance/deer-flow	0/0/200	Rejected	0/4	Declared effect or boundary absent
P21	google-gemini/gemini-cli	88/112/0	Unresolved	2/4	No absolute majority
P21	openai/codex	0/0/200	Rejected	0/4	Declared effect or boundary absent
P21	openclaw/openclaw	105/51/44	Supported	3/4 [1–4]	Profile-majority pointcut match
P21	stablyai/orca	0/0/200	Rejected	0/4	Declared effect or boundary absent
R02	JIA-Lab-research/CarryOn	200/0/0	Supported	4/4	Profile-majority pointcut match

five of six. Pairwise agreement changed from 0.892 to 0.882 and Fleiss' κ from 0.814 to 0.798. The added evidence lenses therefore changed contract support without changing the pointcut-level consensus.

The eight-cell AI-assisted set is a candidate-recall overlay, not independently confirmed coverage. Under the profile-majority rule, six supported candidates raise audited candidate coverage from 1,272 to 1,278 of 2,132 cells (59.9%), leaving 854 unobserved. This overlay does not rewrite the frozen matrix. The unresolved cells remain visible because their near-split votes concern different enforcement boundaries and no separate adjudication was recorded.

These are dispositions of one model. Unanimity under 200 prompts shows that a disposition is stable to prompt wording; it does not show that the disposition is correct, and a unanimous rejection is not a tested negative. The 16 cells illustrate stable cases and failure modes; retrieval precision and contract prevalence are questions for independently adjudicated samples.

B.4 Detector Surface Check

An exploratory incremental scan of 17 additional source, test, and configuration extensions found 90 cue lines but no additional observed cell. The added extensions therefore did not change this detector's matrix. Pattern-specific vocabulary and structure, source-surface omissions, and genuine absence all remain candidate explanations for the unobserved cells; separating them takes adjudicated matching with known recall, which the next study supplies.

B.5 Reproducible Detection and Gated Iteration

The detector is a retrieval instrument, so its defects limit any claim drawn from cue coverage. We therefore rebuilt the cue path as a deterministic runner and audited it with a small gated loop rather than tuning the frozen matrix. The runner canonicalizes its query, codebook, and manifest inputs by SHA-256, emits cues sorted by stable identifier with no generation timestamp, and writes an observability ledger for decoded, oversized, excluded, and unsupported files together with a truncation ledger that records matched, emitted, and omitted lines for every candidate and artifact type. Two repeats of the same input produce byte-identical outputs.

The iteration loop evaluates the immutable baseline and explicitly versioned candidate policies on labeled development fixtures. A candidate is retained only when repeated runs are byte-identical, no labeled positive loses its cue, every labeled near miss stays unmatched, and no frozen output hash changes. The holdout is scored only after selection. Table 24 summarizes the ranked defects. The fixture audit verifies three implementation defects: `checkpoint_` identifiers are missed because the frozen boundary requires a non-word character after the term; the bare `route` alternative matches configuration strings; and a documented API mentioned only in a comment yields a cue. A pattern-final underscore fix is a no-op on these fixtures because the frozen boundary already rejects the tested near miss.

Table 24 Ranked detector-audit outcomes on labeled fixtures. A candidate is the first configuration to clear every gate. Fixture precision and recall describe six development cells; they are not corpus estimates.

Candidate	Dev. precision	Dev. recall	Decision
Frozen baseline 0.1.0	0.750	0.750	reference
Boundary guards 0.2.0–0.2.2	0.750	0.750	rejected
Comment guard 0.2.3	0.750	0.750	rejected
Router forms 0.2.4	1.000	0.750	rejected
Checkpoint continuation 0.2.5	0.800	1.000	rejected
Combined 0.2.6	1.000	1.000	accepted

The accepted configuration recovers the checkpoint positive and rejects the configuration-string near miss, and it leaves the frozen detector unchanged. On three post-selection holdout cells it reached precision 0.500 and recall 1.000: it recovered the checkpoint positive and kept a prefix near miss out, but it retained the comment-only false positive. These are non-generalizing fixture checks. Applying the candidate to the frozen corpus would require a new detector version, a full re-scan, and a re-audit of every cue-derived statistic, none of which this audit performs. Independent human adjudication of the fixtures is also still open. The audit therefore documents a verified reproducibility and regression path for the instrument, not an improved evidence estimate.

B.6 Reproducibility

The companion research artifact contains the frozen repository manifests, detector outputs, pointcut specifications, realization timelines, statistical tables, figure source data, and code. Repository working trees are excluded.