



# Introduction to Machine Learning [Fall 2022]

## Dimensionality Reduction

November 10, 2022


Lerrel Pinto

# Logistics

- We are nearing the end of the class!
  - HW5 & HW6.
  - Capstone Project.
- Syllabus changes:
  - <https://nyu-robot-learning.github.io/ml-class/docs/lectures>
- Want something covered in later classes? Mention on #class-discussion


# What we have covered so far

# What we have covered so far



# What we will cover in the remainder of the class

# What we will cover in the remainder of the class




# Unsupervised Learning

Credits: Langs et al. 2018




# Unsupervised Learning

Supervised  
Learning



Unsupervised  
Learning




Training data

Credits: Langs et al. 2018




# Unsupervised Learning

Supervised  
Learning



Unsupervised  
Learning



Training data

Resulting model

# Dimensionality Reduction

# Dimensionality Reduction

- High-dimensional data can be repetitive:
  - Document classification - Thousands of words per document

# Dimensionality Reduction

- High-dimensional data can be repetitive:
  - Document classification - Thousands of words per document
  - Netflix / Amazon review - number of users \* number of shows


	movie 1	movie 2	movie 3	movie 4	movie 5	movie 6
Tom	5	?	?	1	3	?
George	?	?	3	1	2	5
Susan	4	3	1	?	5	1
Beth	4	3	?	2	4	2

# Dimensionality Reduction

- Curse of dimensionality:
  - Redundant / Irrelevant features degrade performance. (Signal to noise)
  - Difficult to interpret and visualize.
  - Computation becomes infeasible for some algorithms.
  - Hard to store high dimensional data.




# Dimensionality Reduction



Credits: Aarti Singh



# Dimensionality Reduction



Credits: Aarti Singh



# Dimensionality Reduction

Credits: Aarti Singh, Jeff Howbert

# Dimensionality Reduction

- Option 1: Feature selection
  - Cons: Requires domain knowledge.

# Dimensionality Reduction

- Option 1: Feature selection
  - Cons: Requires domain knowledge.
- Option 2: Model Regularization
  - Cons: Requires supervised learning

# Dimensionality Reduction

- Option 1: Feature selection
  - Cons: Requires domain knowledge.
- Option 2: Model Regularization
  - Cons: Requires supervised learning
- Option 3: Learn mapping from high-D to low-D space
  - Either linear or non-linear mapping

# Linear Dimensionality Reduction

Credits: Aarti Singh, Jeff Howbert



# Linear Dimensionality Reduction

- Goal: given a dataset:  $X \in \mathbb{R}^{d \times n}$ , where  $\vec{x} \in \mathbb{R}^d$  corresponds to a data point.  
Project  $\vec{x} \rightarrow \vec{z}$ , where  $\vec{z} \in \mathbb{R}^k$  and  $k < d$

# Linear Dimensionality Reduction


- Goal: given a dataset:  $X \in \mathbb{R}^{d \times n}$ , where  $\vec{x} \in \mathbb{R}^d$  corresponds to a data point.  
Project  $\vec{x} \rightarrow \vec{z}$ , where  $\vec{z} \in \mathbb{R}^k$  and  $k < d$ 
  - Usually  $k \ll d$
  - Example: Project 1000 word features to 3 dimensions (horror, fiction, reading level)

# Linear Dimensionality Reduction

- Goal: given a dataset:  $X \in \mathbb{R}^{d \times n}$ , where  $\vec{x} \in \mathbb{R}^d$  corresponds to a data point.  
Project  $\vec{x} \rightarrow \vec{z}$ , where  $\vec{z} \in \mathbb{R}^k$  and  $k < d$ 
  - Usually  $k \ll d$
  - Example: Project 1000 word features to 3 dimensions (horror, fiction, reading level)
  - Linear:  $\vec{z} = A\vec{x}$


# How to solve this? (Intuitively)

# Principal Component Analysis (PCA)



Credits: Jeff Howbert

# Principal Component Analysis (PCA)




- First PC: Projection direction that maximizes variance of data.
- Second PC: Orthogonal to first and maximizes variance of data.

Credits: Jeff Howbert



# Principal Component Analysis (PCA)




- First PC: Projection direction that maximizes variance of data.
- Second PC: Orthogonal to first and maximizes variance of data.

Credits: Jeff Howbert



# Principal Component Analysis (PCA)


Step 1



Credits: Jeff Howbert

# Principal Component Analysis (PCA)


Step 1



Credits: <https://builtin.com/data-science/step-step-explanation-principal-component-analysis>

# Principal Component Analysis (PCA)

Step 1




Credits: <https://builtin.com/data-science/step-step-explanation-principal-component-analysis>



# Principal Component Analysis (PCA)

Step 2



Credits: Jeff Howbert

# Principal Component Analysis (PCA)

Interactive tool:

<https://setosa.io/ev/principal-component-analysis/>



# How to do PCA Efficiently?

# How to do PCA Efficiently?

- Step 1: Make the mean of the data zero (Standardize your data)

# How to do PCA Efficiently?

- Step 1: Make the mean of the data zero (Standardize your data)
- Step 2: Compute the Covariance Matrix  $C$

# How to do PCA Efficiently?

- Step 1: Make the mean of the data zero (Standardize your data)
- Step 2: Compute the Covariance Matrix  $C$
- Step 3: Calculate eigenvectors and eigenvalues of  $C$ 
  - Eigenvector with largest eigenvalue  $\lambda_1$  corresponds to the 1st PC (why?)
  - Eigenvector with  $k^{th}$  largest eigenvalue  $\lambda_k$  corresponds to  $k^{th}$  PC
  - $\frac{\lambda_k}{\sum_i \lambda_i} =$  proportion of variance captured by  $k^{th}$  PC

Questions?