

Xia Lixun (夏立勋)

Jinghua Apartment (菁华公寓),
Nanxieyu Street 18 (南榭雨街18号),
Suzhou Industry Park (SIP), 215025
Suzhou, Jiangsu, China P.R.

Mobile: 13013815427
Email: lixun.xia@outlook.com

LinkedIn

<http://www.linkedin.com/pub/lixun-xia/1b/212/219>

Working Experience

2014.6 - Sr. Digital Signal Processing engineer, Core of Competence, Harman Suzhou, China

- Development of vehicle audio amplifiers for Europe and North America markets.
- Development and maintenance of Audio Framework.
- Novel HW/SW co-design of amplifier power supply for higher efficiency.
- Hand-over EU/American project Active Noise Cancellation to Suzhou.
- Bug shooting of existing amplifier software.
- Documentation of HW/SW design of amplifier products.
- Work with system engineers for feature validation and integration.

2010.10 - 2014.3 Research and development engineer of Acosense AB, Göteborg, Sweden

- Start-up company making industrial instrument products.
- Lead the development of active acoustic spectroscopic sensors for fluid measurement.
- Determine the specifications for the sensor system with customers directly.
- Design of signal capture/conditioning hardware as well as processor circuitry.
- Design and implementation of data capture firmware for the FPGA.
- Design and implementation of signal processing software for the Linux server.
- Implement part of the machine learning code for the Linux server.
- SCADA interface and networking software design between sensor terminal and the Linux server.

Education

2008.9 - 2010.9 M.Sc. Integrated Electronic System Design, Chalmers University, Sweden.

2001.9 - 2008.6 B/M.Sc. Control Science and Engineering, Central South University, China.

Certifications

Certified Scrum Master by Scrum Alliance.

Project Experience

Audio Framework 2014 - 2015

Audio Framework is the software "Skeleton" defined for any amplifier products on how the audio data are routed and processed. Together with signal processing building blocks as the "muscle", the core functionality of an amplifier emerges. My achievement is, for the first time, a systematic description of the working mechanism of the "skeleton" and "muscle" has been formed within the company. The resultant document is extremely useful for both novice and experienced amplifier design engineers.

Active Noise Cancellation 2014 - 2015

Active Noise Cancellation is a widely used technique to suppress unwanted noise in an optimal sense via dynamic algorithms. The main purpose is to reduce engine sound orders for quieter cabinet in passenger cars. My achievement is the successful transfer of the project to Suzhou site, build of the application document after code analysis, and creation of a simulation tool for cross-amplifier porting. A verification bench environment has also been set up. It consists of amplifier running ANC algorithm and London BLU-80 DSP running vehicle cabinet emulation algorithm.

Novel Control of Tracking Power Supply 2014 - 2015

Control of tracking power supply often requires high precision DAC chip for rail indication. My achievement here is the elimination of the DAC chip but utilizing the digital port alone of the DSP chip for rail indication. Cost down has been achieved thanks to this novel method of power rail control in H-class PSU.

Chime Control via Block Based Processing 2014 - 2015

Chime or beep sounds are often implemented in the rear stages of a fixed point DSP for short time latency in sample-based fashion. Sometimes however, minimal hardware change criterion implies an implementation on block based DSP such as *SHARCTM*. The achievement here is such pilot implementation, showing acceptable latency in practice.

ACOspectroTM – non-invasive fluid measurement in real-time 2010 - 2014

Lead the development of the industrial fluid property measurement sensor based on active acoustic spectroscopy measurement. Products have been deployed among pulp and paper, chemical factories in Sweden. Some information can be found in www.acosense.com. The concept is based on IoT and cloud computing — compact, robust and low-cost sensor terminal group paired with one centralized server for data processing in star-topology network. Machine learning running in the backbone builds regression models for fluid property estimation. Hence multiple measurement points can be monitored non-invasively at extremely

low cost for modern data-driven factories. As the system designer and developer, my contribution: the path finder of such promising measurement method for the cloud computing age.

Technical highlight:

- Circuit built from scratch, including design, schematic capture and layout, containing middle-scale FPGA chip for MCU cluster. ADC(PCM4222) for high-dynamic range signal capture. DAC(PCM1794A) for high dynamic signal playback. DDR2 DRAM interfacing with the FPGA as the program space. SPI Flash for system boot load. Tri-port Ethernet switch chip for sensory data transmission with the Linux server via TCP/IP.
- All hardware components of the circuitry are carefully determined, taking into account factors like availability, performance and costs.
- Realization of a MCU cluster communication protocol for multi-tasking and synchronization based on FIFO queue, rather than using real-time operating system and single MCU core. This allows taking full advantage of the resources of a FPGA chip.
- Unit tests for all software components. Integration tests at system level.
- Work with members of orthogonal skill sets in agile development style.
- All codes and documentations managed by GIT server.
- Work with customers in Sweden closely to improve product quality and performance.
- Design, prototyping, assembly and testing within our own office and workshop.
- Hands-on experience in hardware design for EMI/EMC tests. CE certification verified.

Matrix Power Converter Design and Implementation 2007 - 2008

Matrix converter can be used as motor drivers(PSM, Induction Motor) thanks to its high power density. This is an academic project for my first graduate thesis. Matrix power converter has the merit of higher energy density compared to traditional back-to-back rectifier-inverter topology. Nevertheless the synchronized control of all semiconductor switchers poses harder control problem against the old. In this National Science Foundation project, theory of matrix converters has been studied and a prototype has been engineered. The novel prototype is based on four-leg structure thus allows for more intuitive implementation in a carrier-modulation style.

Technical Skills

Modeling, control and stability analysis of power converter for motor drivers.

Modelling and simulation using Matlab/Simulink.

Digital/Statistical signal processing.

Proficient in C/C++.

GCC tool chain for Linux platform.

Microsoft Visual Studio for Windows platform.

Applied knowledge in machine learning (Regression analysis).

Hardware description (VHDL) and verification (Testbench based).

Basic knowledge of digital communication.

Shell/Perl scripting language.

Embedded system design and development based upon FPGA/DSP/MCU.

Circuit simulation and analysis with SPICE tools.

Schematic capture, simple PCB layout (Altium Designer/Eagle PCB) and soldering.

Hands-on experience of workbench tools: oscilloscopes, function generator, spectrum analyzer UPV/UPL, AP etc.

Knowledge of piezoelectric sensors and actuators.

Hands-on experience of NI/Labview.

Knowledge of EMI/EMC concept and test procedures for product design(Experience in CE certification).

Professional documentation with \LaTeX and Microsoft Office.

Knowledge of Agile Development.

Language Skills

Mandarin: native

English: proficient

Swedish: novice

Publications

Xia Lixun, Liao Bin, "Hardware Platform For Active Acoustic Spectroscopy Sensors", Chalmers University of Technology, 2010.

Su Mei, Xia Lixun, Sun Yao, et al "Carrier modulation of four-leg matrix converter based on FPGA", Electrical Machines and Systems, 2008. ICEMS 2008. IEEE International Conference on. pp.1247-1250.

Yao Sun, Mei Su, Lixun Xia, et al "Randomized carrier modulation for four-leg matrix converter based on optimal Markov chain", Industrial Technology, 2008. ICIT 2008. IEEE International Conference on. pp.1-6.

Hengsi Qin, Mei Su, Lixun Xia, et al "A novel controller design method for power converters", IEEE 11th Workshop on Control and Modeling for Power Electronics, 2008. COMPEL 2008. IEEE International Conference on.

MSc. Courses in Chalmers Univ.

DAT091.Introduction to Electronic System Design
MCC090.CMOS VLSI Design
DAT105.Computer Architecture
EDA222.Real Time Systems
DAT095.Electronic System Design Project
DAT110.EDA Design Methods
MVE135.Probability and Random Process With Applications
SSY121.Introduction to Communication Engineering
SSY125.Digital Communication
SSY130.Applied Signal Processing
TDA956.Hardware Description and Verification
EDA092.Operating System
ENM060.Power Electronic Converters
TIN092.Algorithms

BSc. Courses in Central South Univ.

C Programming Language
Engineering Mathematics
Complex Analysis and Integral Transform
Physics and Experiments
Mathematical Experiment and Modelling
Circuit Theory
Analog Circuits
Digital Circuits
Machinery Tool Education
Electronics Design Project
Electronic Rotating Machinery and Driving
Control Theory
Computer Architecture and Assembly Language
Modern Measurement Technology

Process Control and Instruments
Fluid Dynamics
Computer Control
Power Electronics
Multi-media Technology
PLC and Applications
Micro-Controller Unit Technology
Driving System Control
Computer Simulation
Digital Signal Processing
Intelligent Control

MSc. Courses in Central South Univ.

Modern Control Theories
Power Electronics
Matrix Analysis
Functional Analysis and Optimization
System Identification

Driver's License: C1, China P.R.

Last updated: February 8, 2017