

# 一、在 CentOS Stream 9 操作系统上部署 MySQL-5.7

## 1.配置 yum 仓库

```
[root@localhost xcx]# rpm --import https://repo.mysql.com/RPM-GPG-KEY-mysql-2022
[root@localhost xcx]# rpm -Uvh http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm
```

由于 MySQL 并不在 CentOS 的官方仓库中，所以通过上述命令：

(1)导入 MySQL 的 密钥：`rpm --import https://repo.mysql.com/RPM-GPG-KEY-mysql-2022`

(2)配置 MySQL 的yum 仓库：`rpm -Uvh http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm`

```
[root@localhost xcx]# rpm -Uvh http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm
获取http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm
警告：/var/tmp/rpm-tmp.GUwvyT: 头V3 DSA/SHA1 Signature, 密钥 ID 5072e1f5: NOKEY
Verifying... ##### [100%]
准备中... ##### [100%]
正在升级/安装...
  1:mysql57-community-release-el7-7 ##### [100%]
```

## 2.使用 yum 来安装 MySQL

```
[root@localhost xcx]# rpm -Uvh http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm
获取http://repo.mysql.com//mysql57-community-release-el7-7.noarch.rpm
警告：/var/tmp/rpm-tmp.GUwvyT: 头V3 DSA/SHA1 Signature, 密钥 ID 5072e1f5: NOKEY
Verifying... ##### [100%]
准备中... ##### [100%]
正在升级/安装...
  1:mysql57-community-release-el7-7 ##### [100%]
[root@localhost xcx]# yum -y install mysql-community-server
CentOS Stream 9 - BaseOS                               11 kB/s | 4.6 kB  00:00
CentOS Stream 9 - BaseOS                               351 kB/s | 8.9 MB 00:26
CentOS Stream 9 - BaseOS                               20 kB/s | 5.0 kB  00:00
CentOS Stream 9 - AppStream                             2.3 MB/s | 27 MB  00:11
CentOS Stream 9 - AppStream                             12 kB/s | 5.4 kB  00:00
MySQL Connectors Community                             50 kB/s | 90 kB  00:01
MySQL Tools community                                  120 kB/s | 2.1 MB 00:17
MySQL 5.7 Community Server                             9.4 kB/s | 3.1 MB 05:43
错误：
问题：package mysql-community-server-5.7.44-1.el7.x86_64 from mysql57-community requires mysql-community-client(x86_64) >= 5.7.9, but none of the providers can be installed
- 无法为该任务安装最佳候选
- nothing provides libncurses.so.5()(64bit) needed by mysql-community-client-5.7.10-1.el7.x86_64 from mysql57-community
```

直接安装 MySQL-5.x 版本会发生报错，因为本身系统是 CentOS Stream 9, 更加适配 MySQL-8.x 版本，如果执意安装 5.x 版本，需要补充依赖

# 先安装 EPEL 扩展源：`dnf install -y epel-release`

# 安装兼容库，补齐缺少的 so.5 文件：`dnf install -y ncurses-compat-libs`

# 临时跳过 GPG 校验，重新安装：`dnf install -y mysql-community-server --nogpgcheck`

```
[root@localhost xcx]# mysql --version
mysql Ver 14.14 Distrib 5.7.44, for Linux (x86_64) using EditLine wrapper
[root@localhost xcx]#
```

## MySQL-5.7 安装完成

## 3.启动 MySQL

```
[root@localhost xcx]# systemctl start mysqld
[root@localhost xcx]# systemctl status mysqld
● mysqld.service - MySQL Server
   Loaded: loaded (/usr/lib/systemd/system/mysqld.service; enabled; preset: disabled)
   Active: active (running) since Wed 2026-04-22 15:49:31 CST; 1s ago
     Docs: man:mysqld(8)
           http://dev.mysql.com/doc/refman/en/using-systemd.html
   Process: 141854 ExecStartPre=/usr/bin/mysqld_pre_systemd (code=exited, status=0/SUCCESS)
   Process: 142289 ExecStart=/usr/sbin/mysqld --daemonize --pid-file=/var/run/mysqld/mysqld.pid $MYSQLD_OPTS (code=exited, status=0/SUCCESS)
   Main PID: 142291 (mysqld)
     Tasks: 27 (limit: 22966)
    Memory: 322.0M (peak: 324.7M)
       CPU: 4.144s
    CGroup: /system.slice/mysqld.service
            └─142291 /usr/sbin/mysqld --daemonize --pid-file=/var/run/mysqld/mysqld.pid

4月 22 15:49:24 localhost.localdomain systemd[1]: Starting MySQL Server...
4月 22 15:49:27 localhost.localdomain mysqld_pre_systemd[142069]: mysqld: Out of memory (Needed 4294967200 bytes)
4月 22 15:49:31 localhost.localdomain systemd[1]: Started MySQL Server.
```

## 4.配置：主要配置管理员用户以及配置允许远程登录的权限

(1) 先找到用户临时密码：

```
[root@localhost xcx]# cat /var/log/mysql.log | grep "temporary password"
2026-04-22T07:49:28.650336Z 1 [Note] A temporary password is generated for root@localhost: i7;4j4OUih19
[root@localhost xcx]#
```

初始密码为: **i7;4j4OUih19**

## (2) 登录 MySQL

```
[root@localhost xcx]# mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 3
Server version: 5.7.44

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

## (3)修改 root 用户密码

```
mysql> ALTER USER "root"@"localhost" IDENTIFIED BY "Root2026*";
Query OK, 0 rows affected (0.00 sec)

mysql>
```

已经修改 root 登录密码为: **Root2026\***

## (4)允许远程登录

```
mysql> grant all privileges on *.* to "root"@"%" identified by 'Xcx2026*' with grant option;
Query OK, 0 rows affected, 1 warning (0.00 sec)

mysql> flush privileges;
Query OK, 0 rows affected (0.01 sec)

mysql>
```

## 5.查看端口绑定情况

```
[root@localhost xcx]# netstat -anp | grep 3306
tcp6      0      0 :::3306          :::*              LISTEN      142291/mysqlld
[root@localhost xcx]#
```

MySQL 默认绑定在 **3306** 端口号上

## 二、在 CentOS Stream 9 操作系统上部署 MySQL-8.x

注意：由于我是在同一系统上安装部署 MySQL,我需要删除原本的 MySQL-5.7 的依赖和安装包

```
[root@localhost xcx]# rpm -qa | grep mysql | xargs rpm -e --nodeps
[root@localhost xcx]# rm -rf /etc/my.cnf
[root@localhost xcx]# rm -rf /etc/my.cnf.d/
[root@localhost xcx]# rm -rf /var/lib/mysql
[root@localhost xcx]# rm -rf /var/log/mysql.log
[root@localhost xcx]# rpm -e mysql57-community-release-el7-7
错误：未安装软件包 mysql57-community-release-el7-7
[root@localhost xcx]# # 列出本机所有mysql相关安装包
[root@localhost xcx]# rpm -qa | grep -i mysql
[root@localhost xcx]#
```

已经删除完成，现在开始安装 MySQL-8.0

### 1.配置 yum 仓库，和安装 5.0 一样

```
[root@localhost xcx]# rpm --import https://repo.mysql.com/RPM-GPG-KEY-mysql-2023
[root@localhost xcx]# dnf install -y https://dev.mysql.com/get/mysql80-community-release-el9-3.noarch.rpm
上次元数据过期检查：0:49:14 前，执行于 2026年04月22日 星期三 15时37分41秒。
```

(1)导入 MySQL 的 密钥：`rpm --import https://repo.mysql.com/RPM-GPG-KEY-mysql-2023`

(2)配置 MySQL 的 yum 仓库：`dnf install -y https://dev.mysql.com/get/mysql80-community-release-el9-3.noarch.rpm`

### 2.使用 dnf 安装 MySQL

```
[root@localhost xcx]# dnf install -y mysql-community-server
MySQL 8.0 Community Server
MySQL Connectors Community
```

安装完成

```
[root@localhost xcx]# mysql --version
mysql Ver 8.0.46 for Linux on x86_64 (MySQL Community Server - GPL)
[root@localhost xcx]#
```

### 3.设置为开机自启动状态

```
[root@localhost xcx]# systemctl start mysqld
[root@localhost xcx]# systemctl status mysqld
● mysqld.service - MySQL Server
   Loaded: loaded (/usr/lib/systemd/system/mysqld.service; enabled; preset: disabled)
   Active: active (running) since Wed 2026-04-22 16:36:29 CST; 1s ago
     Docs: man:mysqld(8)
           http://dev.mysql.com/doc/refman/en/using-systemd.html
   Process: 313082 ExecStartPre=/usr/bin/mysqld_pre_systemd (code=exited, status=0/SUCCESS)
   Main PID: 313693 (mysqld)
    Status: "Server is operational"
     Tasks: 38 (limit: 22966)
  Memory: 449.3M (peak: 464.8M)
       CPU: 5.516s
   CGroup: /system.slice/mysqld.service
           └─313693 /usr/sbin/mysqld

4月 22 16:36:20 localhost.localdomain systemd[1]: Starting MySQL Server...
4月 22 16:36:29 localhost.localdomain systemd[1]: Started MySQL Server.
[root@localhost xcx]# systemctl enable mysqld
[root@localhost xcx]#
```



#### 4.配置 MySQL:修改 root 密码

(1) 过滤出初始密码为: **Uaq\*!3urYS=k**

```
[root@localhost xcx]# cat /var/log/mysql.log | grep "temporary password"
2026-04-22T08:36:24.678233Z 6 [Note] [MY-010454] [Server] A temporary password is generated for root@localhost: Uaq*!3urYS=k
[root@localhost xcx]#
```

(2) 使用初始密码登录并修改 root 密码

```
[root@localhost xcx]# mysql -uroot -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 22
Server version: 8.0.46

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> ALTER USER "root"@"localhost" IDENTIFIED WITH mysql_native_password BY 'Xcx2026*';
Query OK, 0 rows affected (0.01 sec)
```

新的密码为: **Xcx2026\***

【拓展】配置 root 简单密码: 可以给 root 配置一个简单密码, 比如 2026

```
[root@localhost xcx]# mysql -uroot -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 23
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> set global validate_password.policy=0;
Query OK, 0 rows affected (0.01 sec)

mysql> set global validate_password.length=4;
Query OK, 0 rows affected (0.00 sec)

mysql> ALTER USER "root"@"localhost" IDENTIFIED WITH mysql_native_password BY '2026*';
Query OK, 0 rows affected (0.00 sec)
```

登录 MySQL, 进行简单密码配置

**set global validate\_password.policy=0;** //密码安全级别低

**set global validate\_password.length=4;** // 密码长度最少 4 位即可

**ALTER USER "root"@"localhost" IDENTIFIED WITH mysql\_native\_password BY '2026\*';**

新的简单密码为: **2026\***

## 5.查看绑定端口

```
[root@localhost ~]# netstat -anp | grep 3306
tcp6      0      0 :::33060          :::*               LISTEN     313693/mysqld
tcp6      0      0 :::3306           :::*               LISTEN     313693/mysqld
[root@localhost ~]#
```

绑定端口为：3306