```
VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 部门管理
    Caption             =    "部门管理"
    ClientHeight        =    6770
    ClientLeft          =    110
    ClientTop           =    450
    ClientWidth         =    9350.001
    OleObjectBlob       =    "部门管理.frx":0000
    StartUpPosition =    1    '所有者中心
End
Attribute VB_Name = "部门管理"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Private Sub CommandButton1_Click()
部门增加.show
End Sub

Private Sub CommandButton2_Click()
    Dim itm As ListItem
Dim deptID As Long
Dim found As Boolean

found = False
For Each itm In ListView1.ListItems
    If itm.Selected Then
        deptID = CLng(itm.text)
        found = True
        Exit For
    End If
Next itm

If Not found Then
    MsgBox "未选择部门", , "提示"
    Exit Sub
End If
    ' 调用部门修改窗体的初始化过程，填充对应数据
    部门修改.InitializeData deptID
    部门修改.show
End Sub
Private Sub CommandButton3_Click()
    Dim sh As Worksheet
    Dim itm As ListItem
```

```
    Dim sel As String
    Dim s As Variant
    Dim anySel As Boolean

    Set sh = Sheets("部门档案")
    anySel = False

    ' 遍历所有 ListItems，找第一个 Selected 的项
    For Each itm In ListView1.ListItems
        If itm.Selected Then
            anySel = True
            sel = itm.text
            Exit For
        End If
    Next itm

    If Not anySel Then
        ' 未选中：清空并允许手动输入
        With 部门删除
            .TextBox1.Enabled = True
            .TextBox1.BackColor = vbWhite
            .TextBox1.Value = ""        ' 清空
            .show
        End With
    Else
        ' 已选中：自动填充并禁止修改
        s = Application.Match(CLng(sel), sh.Range("A:A"), 0)
        If IsError(s) Then
            MsgBox "找不到对应部门编号！", , "提示"
            Exit Sub
        End If

        With 部门删除
            .TextBox1.Enabled = False
            .TextBox1.BackColor = &H8000000B
            .TextBox1.Value = sel
            .show
        End With
    End If
End Sub


Private Sub CommandButton4_Click()
Unload Me
```

```
系统平台.show

End Sub

Private Sub UserForm_Activate()
Call Flesh
End Sub

Public Sub Flesh()

ListView1.ColumnHeaders.Clear:
ListView1.ListItems.Clear '清空列表
Dim N, i As Integer
Set sh = Sheets("部门档案") '显示部门档案列表
Columnnumber = sh.Range("IV1").End(xlToLeft).Column
Rownumber = sh.Range("a65535").End(xlUp).Row
For i = 1 To 3
ListView1.ColumnHeaders.Add i, , sh.Cells(1, i), ListView1.Width / 3    '可设宽度
Next
ListView1.View = lvwReport: ListView1.FullRowSelect = True: ListView1.Gridlines
= True
For i = 2 To Rownumber
Set itm = ListView1.ListItems.Add
itm.text = sh.Cells(i, 1)
For j = 2 To 3
itm.SubItems(j - 1) = sh.Cells(i, j)
Next
Next

If ListView1.ListItems.count > 0 Then ListView1.ListItems(1).Selected = False
End Sub

Public Sub Flesh2()

TreeView1.Nodes.Clear

Dim Nodx As Node
Dim N As Integer
Dim i, j As Integer

Set bm = Sheets("部门档案")


Set Nodx = TreeView1.Nodes.Add(, , "总公司", "总公司部门结构") '总公司是顶级
```

```
节点的索引值,

    N = bm.Range("a65500").End(xlUp).Row
    For i = 2 To N
    If Len(bm.Cells(i, 1)) = 1 Then
        Set Nodx = TreeView1.Nodes.Add("总公司", tvwChild, , "(" & bm.Cells(i,
1) & ")" & bm.Cells(i, 2))
    ElseIf Len(bm.Cells(i, 1)) = 3 Then
        For j = 2 To N
            If Left(Trim(bm.Cells(i, 1)), 1) = Trim(bm.Cells(j, 1)) Then
                Set Nodx = TreeView1.Nodes.Add(FindNodeByText("(" &
bm.Cells(j, 1) & ")" & bm.Cells(j, 2)), tvwChild, , "(" & bm.Cells(i, 1) & ")" &
bm.Cells(i, 2))
            End If
         Next j
    End If

  Next i


For i = 1 To TreeView1.Nodes.count
     TreeView1.Nodes(i).Expanded = True
Next
End Sub
Private Sub UserForm_Initialize()
Dim Nodx As Node
Dim N As Integer
Dim i, j As Integer

Set bm = Sheets("部门档案")


Set Nodx = TreeView1.Nodes.Add(, , "总公司", "总公司部门结构") '总公司是顶级
节点的索引值,

    N = bm.Range("a65500").End(xlUp).Row
    For i = 2 To N
    If Len(bm.Cells(i, 1)) = 1 Then
        Set Nodx = TreeView1.Nodes.Add("总公司", tvwChild, , "(" & bm.Cells(i,
1) & ")" & bm.Cells(i, 2))
    ElseIf Len(bm.Cells(i, 1)) = 3 Then
        For j = 2 To N
            If Left(Trim(bm.Cells(i, 1)), 1) = Trim(bm.Cells(j, 1)) Then
                Set Nodx = TreeView1.Nodes.Add(FindNodeByText("(" &
```

```
bm.Cells(j, 1) & ")" & bm.Cells(j, 2)), tvwChild, , "(" & bm.Cells(i, 1) & ")" & bm.Cells(i, 2))
                End If
            Next j
        End If

    Next i


For i = 1 To TreeView1.Nodes.count
        TreeView1.Nodes(i).Expanded = True
Next


End Sub
Private Function FindNodeByText(text As String) As Node
    Dim Node As Node

    For Each Node In TreeView1.Nodes
        If Node.text = text Then
            Set FindNodeByText = Node
            Exit Function
        End If
    Next

    Set FindNodeByText = Nothing
End Function

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 部门删除
   Caption             =   "删除部门"
   ClientHeight        =   3860
   ClientLeft          =   110
   ClientTop           =   450
   ClientWidth         =   5590
   OleObjectBlob       =   "部门删除.frx":0000
   StartUpPosition =   1  '所有者中心
End
Attribute VB_Name = "部门删除"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Private Sub CommandButton1_Click()
```

```
    Dim sh As Worksheet
    Dim s As Variant
    Dim sel As String
    Dim selNum As Double

    Set sh = Sheets("部门档案")

    sel = Trim(TextBox1.Value)
    If sel = "" Then
        MsgBox "请输入部门编号", vbExclamation, "提示"
        Exit Sub
    End If

    ' 尝试转换成数字，如果失败就当成文本匹配
    On Error Resume Next
    selNum = CDbl(sel)
    On Error GoTo 0

    If IsNumeric(sel) Then
        ' 如果输入是数字，则匹配数字型部门编号
        s = Application.Match(selNum, sh.Range("A:A"), 0)
    Else
        ' 否则按文本匹配
        s = Application.Match(sel, sh.Range("A:A"), 0)
    End If

    If IsError(s) Then
        MsgBox "未找到匹配的部门", vbExclamation, "提示"
        Exit Sub
    Else
        sh.Rows(s).Delete
        Call 部门管理.Flesh
        Call 部门管理.Flesh2
        MsgBox "删除成功！", vbInformation, "提示"
    End If

    TextBox1.Value = ""
    Unload Me
End Sub



Private Sub CommandButton2_Click()
  Unload Me
```

```
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 部门修改
    Caption         =   "修改部门"
    ClientHeight    =   5130
    ClientLeft      =   110
    ClientTop       =   450
    ClientWidth     =   4940
    OleObjectBlob   =   "部门修改.frx":0000
    StartUpPosition =   1   '所有者中心
End
Attribute VB_Name = "部门修改"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

' 初始化并加载部门数据
Public Sub InitializeData(ByVal deptID As Long)
    Dim sh As Worksheet
    Dim rowIndex As Variant

    Set sh = ThisWorkbook.Sheets("部门档案")

    rowIndex = Application.Match(deptID, sh.Range("A:A"), 0)

    If IsError(rowIndex) Then
        MsgBox "部门编号不存在！", vbExclamation, "提示"
        Exit Sub
    End If

    ' 填充文本框
    TextBox1.Value = sh.Cells(rowIndex, 1).Value    ' 部门编号
    TextBox2.Value = sh.Cells(rowIndex, 2).Value    ' 部门名称
    TextBox3.Value = sh.Cells(rowIndex, 3).Value    ' 备注

    ' 编号不可修改
    TextBox1.Enabled = False
    TextBox1.BackColor = &H8000000B ' 灰色背景
End Sub

' 保存按钮点击事件，更新部门信息
```

```
Private Sub CommandButton1_Click()
    Dim no As String
    Dim na As String
    Dim ps As String
    Dim result As Variant
    Dim s As Long
    Dim sh As Worksheet

    Set sh = ThisWorkbook.Sheets("部门档案")

    no = Trim(TextBox1.text)
    na = Trim(TextBox2.text)
    ps = Trim(TextBox3.text)

    If na = "" Then
        MsgBox "未输入部门名称", , "提示"
        Exit Sub
    End If

    result = Application.Match(CLng(no), sh.Range("A:A"), 0)

    If IsError(result) Then
        MsgBox "部门编号不存在", , "提示"
        Exit Sub
    Else
        s = result
        sh.Cells(s, 2).Value = na
        sh.Cells(s, 3).Value = ps

        MsgBox "修改成功", , "提示"
        Unload Me
        Call  部门管理.Flesh
        Call  部门管理.Flesh2
    End If
End Sub

' 关闭按钮点击事件
Private Sub CommandButton2_Click()
    Unload Me
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F}  部门增加
   Caption         =     "增加部门"
```

```
    ClientHeight      =     5360
    ClientLeft        =     110
    ClientTop         =     450
    ClientWidth       =     4920
    OleObjectBlob     =     "部门增加.frx":0000
    StartUpPosition =     1   '所有者中心
End
Attribute VB_Name = "部门增加"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Private Sub CommandButton1_Click()
  Set sh = Sheets("部门档案")

no = TextBox1.text
na = TextBox2.text
ps = TextBox3.text
  If Len(TextBox1.text) <> 1 And Len(TextBox1.text) <> 3 Then
        MsgBox "编码方式不合法！"
        Exit Sub
End If
If na = "" Or no = "" Then MsgBox "部门编号和部门名称为必填项", , "提示": Exit
Sub

 ' 检查部门编号是否已存在
s = IsError(Application.Match(Val(no), sh.[A:A], 0))

If s = False Then MsgBox "部门已存在，请重新填写", , "提示": Exit Sub

' 检查部门名称是否已存在
    sna = Application.Match(na, sh.Range("B:B"), 0)
    If Not IsError(sna) Then
        MsgBox "部门名称已存在，请重新填写", vbExclamation, "提示"
        Exit Sub
    End If
 ' 找到最后一行
N = sh.[A65536].End(xlUp).Row
' 新增部门
sh.Cells(N + 1, 1) = no
sh.Cells(N + 1, 2) = na
sh.Cells(N + 1, 3) = ps
' 显示成功并关闭表单
MsgBox "新建部门成功", , "提示":
```

```
Unload Me

 ' 刷新部门管理表单
  Call  部门管理.Flesh
  Call  部门管理.Flesh2
End Sub

Private Sub CommandButton2_Click()
Unload Me
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F}  查看账表
    Caption             =     "查看账表"
    ClientHeight        =     8940.001
    ClientLeft          =     110
    ClientTop           =     450
    ClientWidth         =     16060
    OleObjectBlob       =     "查看账表.frx":0000
    StartUpPosition =     1    '所有者中心
End
Attribute VB_Name = "查看账表"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Private Sub ComboBox1_Change()

Set sh = Sheets("会计科目表")
lastRow = sh.Cells(sh.Rows.count, "A").End(xlUp).Row
ComboBox2.Clear

Select Case ComboBox1.Value

Case "总账"

For i = 2 To lastRow
If sh.Cells(i, 1) = sh.Cells(i, 2) Then ComboBox2.AddItem sh.Cells(i, 4)
Next

Case "明细账"
For i = 2 To lastRow - 1
If sh.Cells(i, 1) = sh.Cells(i, 2) And sh.Cells(i, 2) = sh.Cells(i + 1, 2) Then '不记有子
科目的一级科目
```

```
Else
ComboBox2.AddItem sh.Cells(i, 4)

End If

Next

ComboBox2.AddItem sh.Cells(lastRow, 4)

Case "现金日记账"

For i = 2 To lastRow

If sh.Cells(i, 7) = "Y" And sh.Cells(i, 8) = "" Then ComboBox2.AddItem sh.Cells(i, 4)
Next

Case "银行日记账"

For i = 2 To lastRow

If sh.Cells(i, 7) = "Y" And sh.Cells(i, 8) = "Y" Then ComboBox2.AddItem sh.Cells(i, 4)

Next
End Select
End Sub

Private Sub CommandButton1_Click()

zb = ComboBox1.text: km = ComboBox2.text '取得账表和科目

ListView1.ColumnHeaders.Clear: ListView1.ListItems.Clear '清空列表

If zb = "" Then MsgBox "未选择账表", , "提示": Exit Sub

If zb = "资产负债表" Or zb = "利润表" Then

    Set sh = Sheets(zb)

    lastColumn = sh.Cells(1, sh.Columns.count).End(xlToLeft).Column

    lastRow = sh.Cells(sh.Rows.count, "A").End(xlUp).Row
```

```
        For i = 1 To lastColumn
        ListView1.ColumnHeaders.Add i, , sh.Cells(1, i), ListView1.Width / 4
        Next
        ListView1.View = lvwReport: ListView1.FullRowSelect = True: ListView1.Gridlines = True
        For i = 2 To lastRow
        Set itm = ListView1.ListItems.Add
        itm.text = sh.Cells(i, 1)
        For j = 2 To lastColumn
        itm.SubItems(j - 1) = sh.Cells(i, j)
        Next
        Next
        Exit Sub
End If
If zb <> "发生额及余额表" And km = "" Then MsgBox "未选择科目", , "提示": Exit Sub


If zb = "发生额及余额表" Then
Set sh = Sheets(zb)
lastColumn = sh.Cells(1, sh.Columns.count).End(xlToLeft).Column
lastRow = sh.Cells(sh.Rows.count, "A").End(xlUp).Row

ListView1.ColumnHeaders.Add 1, , sh.Cells(1, 1), ListView1.Width / 8
ListView1.ColumnHeaders.Add 2, , sh.Cells(1, 4), ListView1.Width / 8
```

```
For i = 6 To lastColumn

    ListView1.ColumnHeaders.Add i - 3, , sh.Cells(1, i), ListView1.Width / 8

Next

ListView1.View = lvwReport: ListView1.FullRowSelect = True: ListView1.Gridlines
= True
    '用于存储合计的
    '借/贷期初余额
    sj = 0: sd = 0
    '借/贷发生额
    jf = 0: df = 0
    '借/贷期末余额
    fj = 0: fd = 0

    '用于存储小计的，每小计一次后重置
    xsj = 0: xsd = 0

    xjf = 0: xdf = 0

    xfj = 0: xfd = 0

biao = 1

For i = 2 To lastRow

If Val(Left(sh.Cells(i, 1), 1)) > biao And xsj + xsd + xjf + xdf + xfj + xfd > 0 Then

Set itm = ListView1.ListItems.Add

Select Case biao

Case "1"

itm.SubItems(1) = "资产小计"

Case "2"

itm.SubItems(1) = "负债小计"

Case "3"
```

```
itm.SubItems(1) = "共同小计"

Case "4"

itm.SubItems(1) = "权益小计"

Case "5"

itm.SubItems(1) = "成本小计"

End Select

itm.SubItems(2) = xsj: itm.SubItems(3) = xsd: itm.SubItems(4) = xjf: itm.SubItems(5) = xdf

itm.SubItems(6) = xfj: itm.SubItems(7) = xfd

xsj = 0: xsd = 0: xjf = 0: xdf = 0: xfj = 0: xfd = 0

biao = Left(sh.Cells(i, 1), 1)

End If

If sh.Cells(i, 6) > 0 Or sh.Cells(i, 7) > 0 Or sh.Cells(i, 8) > 0 Or sh.Cells(i, 9) > 0 Then

biao = Left(sh.Cells(i, 1), 1)

If sh.Cells(i, 1) = sh.Cells(i, 2) Then '如果是一级科目，只算一级科目的总和

    sj = sj + sh.Cells(i, 6): sd = sd + sh.Cells(i, 7): jf = jf + sh.Cells(i, 8): df = df + sh.Cells(i, 9)

    fj = fj + sh.Cells(i, 10): fd = fd + sh.Cells(i, 11)

    xsj = xsj + sh.Cells(i, 6): xsd = xsd + sh.Cells(i, 7): xjf = xjf + sh.Cells(i, 8): xdf = xdf + sh.Cells(i, 9)

    xfj = xfj + sh.Cells(i, 10): xfd = xfd + sh.Cells(i, 11)

End If

Set itm = ListView1.ListItems.Add
```

```
itm.text = sh.Cells(i, 1): itm.SubItems(1) = sh.Cells(i, 4)

For j = 6 To lastColumn

itm.SubItems(j - 4) = sh.Cells(i, j)

Next

End If

Next


Set itm = ListView1.ListItems.Add
'6 开头为损益类
itm.SubItems(1) = "损益小计"

itm.SubItems(2) = xsj: itm.SubItems(3) = xsd: itm.SubItems(4) = xjf: itm.SubItems(5) = xdf

itm.SubItems(6) = xfj: itm.SubItems(7) = xfd

Set itm = ListView1.ListItems.Add

itm.SubItems(1) = "合计"

itm.SubItems(2) = sj: itm.SubItems(3) = sd: itm.SubItems(4) = jf: itm.SubItems(5) = df

itm.SubItems(6) = fj: itm.SubItems(7) = fd

Exit Sub

End If

'总账

If zb = "总账" Then
Set sh = Sheets(zb)
lastColumn = sh.Cells(1, sh.Columns.count).End(xlToLeft).Column

lastRow = sh.Cells(sh.Rows.count, "A").End(xlUp).Row
```

```
For i = 5 To lastColumn

ListView1.ColumnHeaders.Add i - 4, , sh.Cells(1, i), ListView1.Width / 5 '可设宽度

Next

ListView1.View = lvwReport: ListView1.FullRowSelect = True: ListView1.Gridlines = True

Set zz = Sheets("发生额及余额表")

'找到匹配的科目名字
s = WorksheetFunction.Match(km, zz.[D:D], 0)

    Set itm = ListView1.ListItems.Add

    itm.text = "期初余额": itm.SubItems(1) = zz.Cells(s, 6): itm.SubItems(2) = zz.Cells(s, 7)

    If zz.Cells(s, 6) - zz.Cells(s, 7) > 0 Then itm.SubItems(3) = "借": itm.SubItems(4) = zz.Cells(s, 6) - zz.Cells(s, 7)

    If zz.Cells(s, 7) - zz.Cells(s, 6) > 0 Then itm.SubItems(3) = "贷": itm.SubItems(4) = zz.Cells(s, 7) - zz.Cells(s, 6)

    If zz.Cells(s, 6) = 0 And zz.Cells(s, 7) = 0 Then itm.SubItems(3) = "平": itm.SubItems(4) = 0


Set itm = ListView1.ListItems.Add

    itm.text = "发生额": itm.SubItems(1) = zz.Cells(s, 8): itm.SubItems(2) = zz.Cells(s, 9)

    If zz.Cells(s, 8) - zz.Cells(s, 9) > 0 Then itm.SubItems(3) = "借": itm.SubItems(4) = zz.Cells(s, 8) - zz.Cells(s, 9)

    If zz.Cells(s, 9) - zz.Cells(s, 8) > 0 Then itm.SubItems(3) = "贷": itm.SubItems(4) = zz.Cells(s, 9) - zz.Cells(s, 8)

    If zz.Cells(s, 8) = 0 And zz.Cells(s, 9) = 0 Then itm.SubItems(3) = "平": itm.SubItems(4) = 0

Set itm = ListView1.ListItems.Add
```

```
        itm.text = "期末余额": itm.SubItems(1) = zz.Cells(s, 10): itm.SubItems(2) = zz.Cells(s, 11)

        If zz.Cells(s, 10) - zz.Cells(s, 11) > 0 Then itm.SubItems(3) = "借": itm.SubItems(4) = zz.Cells(s, 10) - zz.Cells(s, 11)

        If zz.Cells(s, 11) - zz.Cells(s, 10) > 0 Then itm.SubItems(3) = "贷": itm.SubItems(4) = zz.Cells(s, 11) - zz.Cells(s, 10)

        If zz.Cells(s, 10) = 0 And zz.Cells(s, 11) = 0 Then itm.SubItems(3) = "平": itm.SubItems(4) = 0
Set itm = ListView1.ListItems.Add

        itm.text = "合计"
        sumj = Val(zz.Cells(s, 6)) + Val(zz.Cells(s, 8)) + Val(zz.Cells(s, 10))
        sumd = Val(zz.Cells(s, 7)) + Val(zz.Cells(s, 9)) + Val(zz.Cells(s, 11))
        itm.SubItems(1) = sumj
        itm.SubItems(2) = sumd

        If sumj - sumd > 0 Then itm.SubItems(3) = "借": itm.SubItems(4) = sumj - sumd

        If sumd - sumj > 0 Then itm.SubItems(3) = "贷": itm.SubItems(4) = sumd - sumj

        If sumj - sumd = 0 Then itm.SubItems(3) = "平": itm.SubItems(4) = 0

Exit Sub

End If

'明细账
If zb = "明细账" Or zb = "现金日记账" Or zb = "银行日记账" Then
Set sh = Sheets(zb)
lastColumn = sh.Cells(1, sh.Columns.count).End(xlToLeft).Column

lastRow = sh.Cells(sh.Rows.count, "A").End(xlUp).Row

For i = 1 To lastColumn

ListView1.ColumnHeaders.Add i, , sh.Cells(1, i), ListView1.Width / 9 '可设宽度

Next

ListView1.View = lvwReport: ListView1.FullRowSelect = True: ListView1.Gridlines
```

```
= True

Set zz = Sheets("发生额及余额表")

s = WorksheetFunction.Match(km, zz.[D:D], 0)

Set itm = ListView1.ListItems.Add

    itm.SubItems(4) = "期初余额": itm.SubItems(5) = zz.Cells(s, 6): itm.SubItems(6) = zz.Cells(s, 7)

    If zz.Cells(s, 6) - zz.Cells(s, 7) > 0 Then itm.SubItems(7) = "借": itm.SubItems(8) = zz.Cells(s, 6) - zz.Cells(s, 7)

    If zz.Cells(s, 7) - zz.Cells(s, 6) > 0 Then itm.SubItems(7) = "贷": itm.SubItems(8) = zz.Cells(s, 7) - zz.Cells(s, 6)

    If zz.Cells(s, 6) = 0 And zz.Cells(s, 7) = 0 Then itm.SubItems(7) = "平": itm.SubItems(8) = 0
    '明细的借贷合计
    mxhj = zz.Cells(s, 6): mxhd = zz.Cells(s, 7)

For i = 2 To lastRow
'寻找选择会计科目
    If sh.Cells(i, 1) = km Or km = "银行存款" Then

    Set itm = ListView1.ListItems.Add

    itm.text = sh.Cells(i, 1)

    mxhj = mxhj + sh.Cells(i, 6): mxhd = mxhd + sh.Cells(i, 7)

        For j = 2 To lastColumn - 1

            itm.SubItems(j - 1) = sh.Cells(i, j)

        Next
    If sh.Cells(i, 6) - sh.Cells(i, 7) > 0 Then itm.SubItems(lastColumn - 1) = sh.Cells(i, 6) - sh.Cells(i, 7)
    If sh.Cells(i, 7) - sh.Cells(i, 6) > 0 Then itm.SubItems(lastColumn - 1) = sh.Cells(i, 7) - sh.Cells(i, 6)
    If sh.Cells(i, 6) = 0 And sh.Cells(i, 7) = 0 Then itm.SubItems(lastColumn - 1) = 0

    End If
```

```
Next

Set itm = ListView1.ListItems.Add

itm.SubItems(4) = "期末余额": itm.SubItems(5) = zz.Cells(s, 10): itm.SubItems(6) = zz.Cells(s, 11)

    If zz.Cells(s, 10) - zz.Cells(s, 11) > 0 Then itm.SubItems(7) = "借": itm.SubItems(8) = zz.Cells(s, 10) - zz.Cells(s, 11)

    If zz.Cells(s, 11) - zz.Cells(s, 10) > 0 Then itm.SubItems(7) = "贷": itm.SubItems(8) = zz.Cells(s, 11) - zz.Cells(s, 10)

    If zz.Cells(s, 10) = 0 And zz.Cells(s, 11) = 0 Then itm.SubItems(7) = "平": itm.SubItems(8) = 0

    mxhj = mxhj + sh.Cells(i, 10): mxhd = mxhd + sh.Cells(i, 11)
Set itm = ListView1.ListItems.Add

    itm.SubItems(4) = "合计": itm.SubItems(5) = mxhj: itm.SubItems(6) = mxhd

    If mxhj - mxhd > 0 Then itm.SubItems(7) = "借": itm.SubItems(8) = mxhj - mxhd

    If mxhd - mxhj > 0 Then itm.SubItems(7) = "贷": itm.SubItems(8) = mxhd - mxhj

    If mxhj - mxhd = 0 Then itm.SubItems(7) = "平": itm.SubItems(8) = 0



End If
End Sub

Private Sub CommandButton4_Click()
Unload Me
End Sub


Private Sub UserForm_Activate()

ListView1.ColumnHeaders.Clear:
```

```
ListView1.ListItems.Clear '清空列表

ComboBox2.AddItem ""

ComboBox1.AddItem "总账": ComboBox1.AddItem "明细账"

ComboBox1.AddItem "现金日记账": ComboBox1.AddItem "银行日记账":
ComboBox1.AddItem "发生额及余额表"

ComboBox1.AddItem "资产负债表": ComboBox1.AddItem "利润表"

End Sub

Private Sub ymsy_Click()
Call 函数.利润结转
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 登录页面
    Caption         =    "登录"
    ClientHeight    =    3950
    ClientLeft      =    110
    ClientTop       =    450
    ClientWidth     =    6180
    OleObjectBlob   =    "登录页面.frx":0000
    StartUpPosition =    1    '所有者中心
End
Attribute VB_Name = "登录页面"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False

Private Sub CheckBox1_Click()

  If CheckBox1.Value = True Then
        TextBox2.PasswordChar = ""
    Else
        TextBox2.PasswordChar = "*"
    End If

End Sub

Private Sub CommandButton1_Click()
```

```
    Dim sh As Worksheet
    Dim user As Range
    Dim na As String
    Dim pw As String

    Set sh = Sheets("用户档案")
    na = ComboBox1.text
    pw = TextBox2.text

    If na = "" Or pw = "" Then
        MsgBox "未输入用户名或密码", vbExclamation
        Exit Sub
    End If

    Set user = sh.Range("B:B").Find(na, LookIn:=xlValues, LookAt:=xlWhole)

    If Not user Is Nothing Then
        If pw <> user.Offset(0, 1).Value Then
            MsgBox "密码错误！", vbCritical
            Exit Sub
        Else

        MsgBox "登录成功！", vbInformation
        currentUser = user.Row
            Me.Hide

            系统平台.show
        End If
    Else
        MsgBox "账户不存在！", vbExclamation
    End If
End Sub


Private Sub CommandButton2_Click()
Unload Me
    ThisWorkbook.save
    ThisWorkbook.Close
End Sub

Private Sub UserForm_Activate()
ComboBox1.text = ""
TextBox2.text = ""
'TextBox2.PasswordChar = "*"
```

```
End Sub

Private Sub UserForm_Initialize()
  Dim N As Long, i As Long
      Dim sht As Worksheet

      Set sht = Sheets("用户档案")
      ComboBox1.Clear
      N = sht.Cells(sht.Rows.count, "A").End(xlUp).Row

      For i = 2 To N
          If Trim(sht.Cells(i, "B").Value) <> "" Then
              ComboBox1.AddItem sht.Cells(i, "B").Value
          End If
      Next i

      CheckBox1.Value = False
      TextBox2.PasswordChar = "*"   ' 只在这里设置，确保不冲突
      TextBox2.text = ""                  ' 初始化内容
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 供应商管理
    Caption             =    "供应商管理"
    ClientHeight        =    7070
    ClientLeft          =    110
    ClientTop           =    450
    ClientWidth         =    10660
    OleObjectBlob       =    "供应商管理.frx":0000
    StartUpPosition =    1   '所有者中心
End
Attribute VB_Name = "供应商管理"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

' —— 窗体初始化时设置 ListView 属性 ——
Private Sub UserForm_Initialize()
      With Me.ListView1
          .MultiSelect = False       ' 单选
          .HideSelection = False
      End With
```

```
End Sub

' —— 窗体激活时刷新列表并清除选中 ——
Private Sub UserForm_Activate()
    RefreshListView
End Sub

' —— 窗体显示后也清除选中 ——
Private Sub UserForm_Show()
    ClearSelection
End Sub

' —— 刷新 ListView1 内容 ——
Public Sub RefreshListView()
    Dim ws As Worksheet
    Dim r As Long, i As Long
    Dim itm As ListItem

    Set ws = ThisWorkbook.Sheets("供应商档案")
    r = ws.Cells(ws.Rows.count, "A").End(xlUp).Row

    With Me.ListView1
        .View = lvwReport
        .Gridlines = True
        .FullRowSelect = True
        .MultiSelect = False
        .ColumnHeaders.Clear
        .ListItems.Clear

        .ColumnHeaders.Add , , "编号", 60
        .ColumnHeaders.Add , , "供应商名称", 120
        .ColumnHeaders.Add , , "供应物品", 100
        .ColumnHeaders.Add , , "分管业务员", 100

        For i = 2 To r
            If ws.Cells(i, 1).Value <> "" Then
                Set itm = .ListItems.Add(, , ws.Cells(i, 1).Value)
                itm.SubItems(1) = ws.Cells(i, 2).Value
                itm.SubItems(2) = ws.Cells(i, 3).Value
                itm.SubItems(3) = ws.Cells(i, 4).Value
            End If
        Next i

        ' 清除所有选中状态
```

```
            ClearSelection
        End With

        ' 将焦点移到“增加供应商”按钮，防止 ListView 自动选中
        Me.CommandButton1.SetFocus
End Sub

' —— 辅助：清除所有选中 ——
Private Sub ClearSelection()
        Dim itm As ListItem
        On Error Resume Next
        For Each itm In Me.ListView1.ListItems
            itm.Selected = False
        Next itm
        On Error GoTo 0
End Sub

' —— 增加供应商 ——
Private Sub CommandButton1_Click()
        供应商增加.show
End Sub

' —— 修改供应商 ——
Private Sub CommandButton2_Click()
        Dim itm As ListItem
        Dim id As Long
        Dim found As Boolean

        found = False
        ' 遍历 ListItems，只有真正选中时才赋值
        For Each itm In Me.ListView1.ListItems
            If itm.Selected Then
                id = CLng(itm.text)
                found = True
                Exit For
            End If
        Next itm

        If Not found Then
            MsgBox "请选择一个供应商进行修改！", vbExclamation, "提示"
            Exit Sub
        End If

        供应商修改.InitializeData id
```

```
    供应商修改.show
End Sub

' —— 删除供应商 ——
Private Sub CommandButton3_Click()
    Dim itm As ListItem, id As Long
    For Each itm In Me.ListView1.ListItems
        If itm.Selected Then
            id = CLng(itm.text)
            With 供应商删除
                .TextBox1.Value = id
                .TextBox1.Enabled = False
                .show
            End With
            Exit Sub
        End If
    Next
    MsgBox "请选择一个供应商进行删除！", vbExclamation, "提示"
End Sub

' —— 返回/关闭 ——
Private Sub CommandButton4_Click()
    Me.Hide
    系统平台.show
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 供应商删除
   Caption         =   "删除供应商"
   ClientHeight    =   3900
   ClientLeft      =   110
   ClientTop       =   450
   ClientWidth     =   5780
   OleObjectBlob   =   "供应商删除.frx":0000
   StartUpPosition =   1  '所有者中心
End
Attribute VB_Name = "供应商删除"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

Private Sub CommandButton1_Click()
```

```
    Dim ws As Worksheet, r As Variant, no As Long
    Set ws = ThisWorkbook.Sheets("供应商档案")

    no = Val(Me.TextBox1.Value)
    If no = 0 Then
        MsgBox "请输入要删除的编号", vbExclamation, "提示": Exit Sub
    End If

    r = Application.Match(no, ws.Range("A:A"), 0)
    If IsError(r) Then
        MsgBox "供应商编号不存在！", vbExclamation, "提示": Exit Sub
    End If

    ws.Rows(r).Delete
    MsgBox "删除成功！", vbInformation, "提示"
    Me.Hide
    供应商管理.RefreshListView
End Sub

Private Sub CommandButton2_Click()
    Me.Hide
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 供应商修改
   Caption         =   "修改供应商"
   ClientHeight    =   5770
   ClientLeft      =   110
   ClientTop       =   450
   ClientWidth     =   5280
   OleObjectBlob   =   "供应商修改.frx":0000
   StartUpPosition =   1  '所有者中心
End
Attribute VB_Name = "供应商修改"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

' 窗体初始化：加载分管业务员列表
Private Sub UserForm_Initialize()
    Dim wsP As Worksheet
    Dim lastRow As Long, i As Long
```

```
    Set wsP = ThisWorkbook.Sheets("人员档案")
    lastRow = wsP.Cells(wsP.Rows.count, "A").End(xlUp).Row

    Me.ComboBox1.Clear
    For i = 2 To lastRow
        If Trim(wsP.Cells(i, "G").Value) = "是" Then
            Me.ComboBox1.AddItem wsP.Cells(i, "B").Value
        End If
    Next i
End Sub

' 根据编号加载并显示当前供应商信息
Public Sub InitializeData(ByVal no As Long)
    Dim ws As Worksheet
    Dim r As Variant
    Set ws = ThisWorkbook.Sheets("供应商档案")

    r = Application.Match(no, ws.Range("A:A"), 0)
    If IsError(r) Then
        MsgBox "供应商编号不存在！", vbExclamation, "提示"
        Exit Sub
    End If

    Me.TextBox1.Value = ws.Cells(r, 1).Value
    Me.TextBox2.Value = ws.Cells(r, 2).Value
    Me.TextBox3.Value = ws.Cells(r, 3).Value

    ' 确保业务员列表已加载
    Call UserForm_Initialize

    Me.ComboBox1.Value = ws.Cells(r, 4).Value

    ' 编号不可修改
    Me.TextBox1.Enabled = False
    Me.TextBox1.BackColor = &H8000000B
End Sub

' 确认修改
Private Sub CommandButton1_Click()
    Dim ws As Worksheet
    Dim r As Variant
    Dim no As Long

    Set ws = ThisWorkbook.Sheets("供应商档案")
```

```
    no = Val(Me.TextBox1.Value)

    r = Application.Match(no, ws.Range("A:A"), 0)
    If IsError(r) Then
        MsgBox "供应商编号不存在！", vbExclamation, "提示"
        Exit Sub
    End If

    ws.Cells(r, 2).Value = Trim(Me.TextBox2.Value)
    ws.Cells(r, 3).Value = Trim(Me.TextBox3.Value)
    ws.Cells(r, 4).Value = Trim(Me.ComboBox1.Value)

    MsgBox "修改成功！", vbInformation, "提示"
    Me.Hide
    供应商管理.RefreshListView
End Sub

' 取消
Private Sub CommandButton2_Click()
    Me.Hide
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 供应商增加
   Caption         =   "增加供应商"
   ClientHeight    =   5880
   ClientLeft      =   110
   ClientTop       =   450
   ClientWidth     =   5490
   OleObjectBlob   =   "供应商增加.frx":0000
   StartUpPosition =   1  '所有者中心
End
Attribute VB_Name = "供应商增加"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

' 每次窗体显示前清空上次数据
Private Sub UserForm_Activate()
    Me.TextBox1.Value = ""
    Me.TextBox2.Value = ""
    Me.TextBox3.Value = ""
```

```
    Me.ComboBox1.Value = ""
End Sub

' 窗体初始化：加载分管业务员列表（首次载入）
Private Sub UserForm_Initialize()
    Dim wsP As Worksheet
    Dim lastRow As Long, i As Long
    Set wsP = ThisWorkbook.Sheets("人员档案")
    lastRow = wsP.Cells(wsP.Rows.count, "A").End(xlUp).Row

    Me.ComboBox1.Clear
    For i = 2 To lastRow
        If Trim(wsP.Cells(i, "G").Value) = "是" Then
            Me.ComboBox1.AddItem wsP.Cells(i, "B").Value
        End If
    Next i
End Sub

' 确认添加
Private Sub CommandButton1_Click()
    Dim ws As Worksheet
    Dim lastRow As Long
    Dim no As Long, na As String, Item As String, salesman As String

    Set ws = ThisWorkbook.Sheets("供应商档案")
    no = Val(Me.TextBox1.Value)
    na = Trim(Me.TextBox2.Value)
    Item = Trim(Me.TextBox3.Value)
    salesman = Trim(Me.ComboBox1.Value)

    ' 校验
    If no = 0 Or na = "" Or Item = "" Then
        MsgBox "编号、名称、物品不能为空！", vbExclamation, "提示"
        Exit Sub
    End If

    ' 查重
    If Not IsError(Application.Match(no, ws.Range("A:A"), 0)) Then
        MsgBox "该编号已存在！", vbExclamation, "提示"
        Exit Sub
    End If

    lastRow = ws.Cells(ws.Rows.count, "A").End(xlUp).Row + 1
    ws.Cells(lastRow, 1).Value = no
```

```
        ws.Cells(lastRow, 2).Value = na
        ws.Cells(lastRow, 3).Value = Item
        ws.Cells(lastRow, 4).Value = salesman

        MsgBox "添加成功！", vbInformation, "提示"
        Me.Hide
        供应商管理.RefreshListView
End Sub

' 取消
Private Sub CommandButton2_Click()
        Me.Hide
End Sub

VERSION 5.00
Begin {C62A69F0-16DC-11CE-9E98-00AA00574A4F} 会计科目
    Caption             =    "会计科目"
    ClientHeight        =    9070.001
    ClientLeft          =    110
    ClientTop           =    450
    ClientWidth         =    16960
    OleObjectBlob       =    "会计科目.frx":0000
    StartUpPosition =    1    '所有者中心
End
Attribute VB_Name = "会计科目"
Attribute VB_GlobalNameSpace = False
Attribute VB_Creatable = False
Attribute VB_PredeclaredId = True
Attribute VB_Exposed = False
Option Explicit

Private originalCode As String
Private originalName As String


' —— 窗体初始化 ——
Private Sub UserForm_Initialize()
        Dim ws As Worksheet
        Set ws = ThisWorkbook.Worksheets("会计科目表")

        originalCode = ""
        originalName = ""

        ' 初始化 ListView1
```

```
    filtered = filtered.filter((merchant) => merchant.distance <= 2.0)
  }

  if (filters.value.above45) {
    filtered = filtered.filter((merchant) => merchant.rating >= 4.5)
  }

  return filtered
})

// 处理商家点击
const handleMerchantClick = (merchant) => {
  console.log('点击商家:', merchant)
  router.push(`/merchant/${merchant.id}`)
}

// 处理搜索
const handleSearch = () => {
  console.log('搜索关键词:', searchKeyword.value)
}

// 清除搜索
const clearSearch = () => {
  searchKeyword.value = ''
}

// 筛选条件变化
const handleFilterChange = () => {
  console.log('筛选条件变化:', filters.value)
}

// 查看订单
const viewOrders = () => {
  router.push('/my-orders')
}

// 退出登录
const logout = () => {
  localStorage.removeItem('user')
  localStorage.removeItem('token')
  router.push('/login')
}

onMounted(() => {
  fetchMerchants()
})
</script>

<style scoped>
.consumer-dashboard {
  max-width: 1200px;
```

```
  margin: 0 auto;
  padding: 20px;
}

.header {
  display: flex;
  justify-content: space-between;
  align-items: center;
  margin-bottom: 20px;
}

.title {
  font-size: 32px;
  color: #ff6600;
  margin: 0;
}

.user-info {
  display: flex;
  align-items: center;
  gap: 15px;
}

.search-box {
  margin-bottom: 20px;
}

.filter-box {
  margin-bottom: 20px;
  display: flex;
  gap: 20px;
}

.merchant-list {
  display: grid;
  grid-template-columns: repeat(auto-fill, minmax(300px, 1fr));
  gap: 20px;
}

.merchant-item {
  border: 1px solid #e0e0e0;
  border-radius: 8px;
  padding: 15px;
  cursor: pointer;
  transition: all 0.3s;
  display: flex;
  gap: 15px;
}

.merchant-item:hover {
  box-shadow: 0 2px 12px rgba(0, 0, 0, 0.1);
```

```
  transform: translateY(-2px);
}

.merchant-item.highlight {
  border-color: #ff6600;
  background-color: #fff8f0;
}

.merchant-image {
  width: 80px;
  height: 80px;
  border-radius: 8px;
  overflow: hidden;
  flex-shrink: 0;
}

.merchant-img {
  width: 100%;
  height: 100%;
  object-fit: cover;
  transition: transform 0.3s;
}

.merchant-img:hover {
  transform: scale(1.05);
}

.image-placeholder {
  width: 100%;
  height: 100%;
  background-color: #ff6600;
  color: white;
  display: flex;
  align-items: center;
  justify-content: center;
  font-size: 20px;
  font-weight: bold;
}

.merchant-info {
  flex: 1;
}

.merchant-name {
  margin: 0 0 8px 0;
  font-size: 18px;
  color: #333;
}

.merchant-rating {
  margin-bottom: 8px;
```

```
}

.merchant-details {
  display: flex;
  gap: 15px;
  font-size: 14px;
  color: #666;
}

.merchant-details span {
  display: inline-block;
}

@media (max-width: 768px) {
  .merchant-list {
    grid-template-columns: 1fr;
  }
}
</style>
<template>
  <div class="merchant-detail">
    <!-- 返回按钮 -->
    <div class="header" v-if="merchant.name">
      <el-button type="text" @click="goBack" plain>
        <el-icon><ArrowLeft /></el-icon> 返回
      </el-button>
      <h1>{{ merchant.name }}</h1>
    </div>

    <!-- 商家信息 -->
    <div class="merchant-info" v-if="merchant.name">
      <div class="merchant-header">
        <div class="merchant-image">
          <img
            :src="getMerchantImage(merchant.name)"
            :alt="merchant.name"
            @error="handleImageError"
            class="merchant-img"
          />
        </div>
        <div class="merchant-meta">
          <h2>{{ merchant.name }}</h2>
          <div class="rating">
            <el-rate :model-value="merchant.rating" disabled show-score />
            <span class="score">{{ merchant.rating ? merchant.rating.toFixed(1) : '0.0' }}</span>
          </div>
          <div class="details">
            <span>人均 ¥{{ merchant.avgPrice || 0 }}</span>
            <span>起送 ¥{{ merchant.minDeliveryPrice || 0 }}</span>
            <span>{{ merchant.distance || 0 }}km</span>
          </div>
```

```
      </div>
    </div>
  </div>

  <!-- 菜品列表 -->
  <div class="dish-list" v-if="dishes.length > 0">
    <h3>菜品列表</h3>
    <div v-for="dish in dishes" :key="dish.id" class="dish-item">
      <div class="dish-info">
        <h4>{{ dish.name }}</h4>
        <p class="description">{{ dish.description }}</p>
        <p class="price">¥{{ dish.price ? dish.price.toFixed(2) : '0.00' }}</p>
      </div>
      <div class="dish-controls">
        <el-button-group>
          <el-button @click="decreaseQuantity(dish)" :disabled="getQuantity(dish) === 0">
            <el-icon><Minus /></el-icon>
          </el-button>
          <el-button disabled>{{ getQuantity(dish) }}</el-button>
          <el-button @click="increaseQuantity(dish)">
            <el-icon><Plus /></el-icon>
          </el-button>
        </el-button-group>
      </div>
    </div>
  </div>
  <div v-else class="loading">加载菜品中...</div>

  <!-- 购物车/订单汇总 -->
  <div class="order-summary">
    <div class="summary-content">
      <div class="selected-items">
        <h4>已选商品</h4>
        <div v-if="selectedItems.length === 0" class="empty-cart">暂无商品，请选择菜品</div>
        <div v-for="item in selectedItems" :key="item.dishId" class="selected-item">
          <span>{{ item.dishName }} x {{ item.quantity }}</span>
          <span>¥{{ (item.price * item.quantity).toFixed(2) }}</span>
        </div>
      </div>
      <div class="total">
        总计: <span class="total-amount">¥{{ totalAmount.toFixed(2) }}</span>
      </div>
      <el-button
        type="primary"
        size="large"
        @click="placeOrder"
        :disabled="selectedItems.length === 0"
        class="order-button"
      >
        支付下单
      </el-button>
```

```
      </div>
    </div>

    <!-- 支付成功对话框 -->
    <el-dialog
      v-model="showSuccessDialog"
      title="支付成功"
      width="400px"
      :show-close="false"
      :close-on-click-modal="false"
      :close-on-press-escape="false"
    >
      <div class="success-dialog">
        <el-icon color="#67C23A" size="64"><CircleCheck /></el-icon>
        <h3>支付成功！</h3>
        <p>订单号：{{ currentOrder?.orderNo }}</p>
        <p>商家已收到您的订单，正在准备中...</p>
        <div class="dialog-buttons">
          <el-button type="primary" @click="viewOrder">查看订单</el-button>
          <el-button @click="goBack">返回商家列表</el-button>
        </div>
      </div>
    </el-dialog>
  </div>
</template>

<script setup>
import { ref, onMounted, computed } from 'vue'
import { useRoute, useRouter } from 'vue-router'
import { ArrowLeft, Minus, Plus, CircleCheck } from '@element-plus/icons-vue'
import api from '@/api'

const route = useRoute()
const router = useRouter()
const merchantId = route.params.id
const merchant = ref({})
const dishes = ref([])
const cart = ref({}) // { dishId: quantity }
const showSuccessDialog = ref(false)
const currentOrder = ref(null)
const user = JSON.parse(localStorage.getItem('user') || '{}')

// 商家图片映射
const merchantImages = {
  华莱士: '/images/merchants/hualaisi.jpg',
  韩式炸鸡: '/images/merchants/korean_chicken.jpg',
  正新鸡排: '/images/merchants/zhengxin.jpg',
  沪上阿姨: '/images/merchants/hushang_ayi.jpg',
  夸父炸串: '/images/merchants/kuafu.jpg',
  袁记云饺: '/images/merchants/yuanji.jpg',
  花小小新疆炒米粉: '/images/merchants/huaxiaoxiao.jpg',
```

```
  张亮麻辣烫: '/images/merchants/zhangliang.jpg',
  肯德基: '/images/merchants/kfc.jpg',
  蜜雪冰城: '/images/merchants/mixue.jpg',
}

// 获取商家图片
const getMerchantImage = (merchantName) => {
  return merchantImages[merchantName] || '/images/merchants/default.jpg'
}

// 图片加载失败处理
const handleImageError = (event) => {
  event.target.src = '/images/merchants/default.jpg'
  event.target.onerror = null // 防止循环错误
}

// 添加一个加载状态
const isLoading = ref(true)

// 获取商家详情
const fetchMerchant = async () => {
  try {
    console.log('开始获取商家详情，ID:', merchantId)
    const response = await api.getMerchantById(merchantId)
    console.log('商家详情响应:', response)
    if (response.code === 200) {
      merchant.value = response.data
    } else {
      console.error('获取商家详情失败:', response.message)
    }
  } catch (error) {
    console.error('获取商家详情失败:', error)
  }
}

// 获取菜品列表
const fetchDishes = async () => {
  try {
    console.log('开始获取菜品，商家 ID:', merchantId)
    const response = await api.getDishesByMerchantId(merchantId)
    console.log('菜品响应:', response)
    if (response.code === 200) {
      dishes.value = response.data
    } else {
      console.error('获取菜品失败:', response.message)
    }
  } catch (error) {
    console.error('获取菜品失败:', error)
  } finally {
    isLoading.value = false
  }
```

```
}

// 获取菜品数量
const getQuantity = (dish) => {
  return cart.value[dish.id] || 0
}

// 增加数量
const increaseQuantity = (dish) => {
  if (!cart.value[dish.id]) {
    cart.value[dish.id] = 1
  } else {
    cart.value[dish.id]++
  }
}

// 减少数量
const decreaseQuantity = (dish) => {
  if (cart.value[dish.id] && cart.value[dish.id] > 0) {
    cart.value[dish.id]--
    if (cart.value[dish.id] === 0) {
      delete cart.value[dish.id]
    }
  }
}

// 计算选中的菜品
const selectedItems = computed(() => {
  return dishes.value
    .filter((dish) => (cart.value[dish.id] || 0) > 0)
    .map((dish) => ({
      dishId: dish.id,
      dishName: dish.name,
      price: dish.price,
      quantity: cart.value[dish.id],
    }))
})

// 计算总金额
const totalAmount = computed(() => {
  return selectedItems.value.reduce((total, item) => {
    return total + item.price * item.quantity
  }, 0)
})

// 下单
const placeOrder = async () => {
  try {
    if (!user.id) {
      alert('请先登录')
      router.push('/login')
```

```
      return
    }

    const orderData = {
      consumerId: user.id,
      consumerName: user.username,
      merchantId: merchant.value.id,
      merchantName: merchant.value.name,
      items: selectedItems.value,
    }

    console.log('下单数据:', orderData)
    const response = await api.createOrder(orderData)
    console.log('下单响应:', response)
    if (response.code === 200) {
      currentOrder.value = response.data
      showSuccessDialog.value = true
      // 清空购物车
      cart.value = {}
    } else {
      alert('下单失败: ' + response.message)
    }
  } catch (error) {
    console.error('下单失败:', error)
    alert('下单失败，请重试')
  }
}

// 查看订单
const viewOrder = () => {
  showSuccessDialog.value = false
  router.push('/my-orders')
}

// 返回上一页
const goBack = () => {
  router.back()
}

// 初始化
onMounted(() => {
  console.log('MerchantDetail 组件已挂载')
  fetchMerchant()
  fetchDishes()
})
</script>

<style scoped>
.merchant-detail {
  max-width: 800px;
  margin: 0 auto;
```

```
  padding: 20px;
  padding-bottom: 150px; /* 为底部订单汇总留出空间 */
}

.header {
  display: flex;
  align-items: center;
  margin-bottom: 20px;
}

.header h1 {
  margin-left: 20px;
  font-size: 24px;
  color: #333;
}

.merchant-info {
  background: white;
  border-radius: 8px;
  padding: 20px;
  margin-bottom: 20px;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
}

.merchant-header {
  display: flex;
  gap: 20px;
}

.merchant-image {
  width: 100px;
  height: 100px;
  border-radius: 8px;
  overflow: hidden;
  flex-shrink: 0;
}

.merchant-img {
  width: 100%;
  height: 100%;
  object-fit: cover;
}

.merchant-meta {
  flex: 1;
}

.merchant-meta h2 {
  margin: 0 0 10px 0;
  font-size: 24px;
  color: #333;
```

```
}

.rating {
  display: flex;
  align-items: center;
  margin-bottom: 10px;
}

.score {
  margin-left: 10px;
  font-size: 16px;
  color: #ff9900;
}

.details {
  display: flex;
  gap: 20px;
  color: #666;
}

.dish-list {
  background: white;
  border-radius: 8px;
  padding: 20px;
  margin-bottom: 20px;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
}

.dish-list h3 {
  margin: 0 0 20px 0;
  font-size: 18px;
  color: #333;
}

.dish-item {
  display: flex;
  justify-content: space-between;
  align-items: center;
  padding: 15px 0;
  border-bottom: 1px solid #eee;
}

.dish-item:last-child {
  border-bottom: none;
}

.dish-info h4 {
  margin: 0 0 8px 0;
  font-size: 16px;
  color: #333;
}
```

```css
.description {
  margin: 0 0 8px 0;
  font-size: 14px;
  color: #666;
}

.price {
  margin: 0;
  font-size: 16px;
  color: #ff6600;
  font-weight: bold;
}

.loading {
  text-align: center;
  padding: 40px;
  color: #666;
}

.order-summary {
  position: fixed;
  bottom: 0;
  left: 0;
  right: 0;
  background: white;
  border-top: 1px solid #e0e0e0;
  box-shadow: 0 -2px 10px rgba(0, 0, 0, 0.1);
  padding: 15px 20px;
}

.summary-content {
  max-width: 800px;
  margin: 0 auto;
  display: flex;
  align-items: center;
  justify-content: space-between;
}

.selected-items {
  flex: 1;
}

.selected-items h4 {
  margin: 0 0 10px 0;
  font-size: 14px;
  color: #333;
}

.empty-cart {
  color: #999;
```

```
  font-size: 14px;
}

.selected-item {
  display: flex;
  justify-content: space-between;
  font-size: 14px;
  margin-bottom: 5px;
}

.total {
  margin: 0 20px;
  font-size: 18px;
  font-weight: bold;
}

.total-amount {
  color: #ff6600;
  font-size: 20px;
}

.order-button {
  min-width: 120px;
}

.success-dialog {
  text-align: center;
  padding: 20px;
}

.success-dialog h3 {
  margin: 20px 0 10px 0;
  color: #67c23a;
}

.success-dialog p {
  margin: 10px 0;
  color: #666;
}

.dialog-buttons {
  margin-top: 30px;
  display: flex;
  gap: 20px;
  justify-content: center;
}
</style>
<template>
  <div class="my-orders">
    <!-- 顶部导航 -->
    <div class="header">
```

```
      <el-button type="link" @click="goBack">
        <el-icon><ArrowLeft /></el-icon> 返回
      </el-button>
      <h1>我的订单</h1>
    </div>

    <!-- 订单状态筛选 -->
    <div class="filter-tabs">
      <el-radio-group v-model="activeStatus" @change="filterOrders">
        <el-radio-button label="ALL">全部</el-radio-button>
        <el-radio-button label="PREPARING">准备中</el-radio-button>
        <el-radio-button label="DELIVERING">配送中</el-radio-button>
        <el-radio-button label="DELIVERED">已送达</el-radio-button>
        <el-radio-button label="COMPLETED">已完成</el-radio-button>
        <el-radio-button label="CANCELLED">已取消</el-radio-button>
      </el-radio-group>
    </div>

    <!-- 订单列表 -->
    <div class="order-list">
      <div v-if="loading" class="loading">
        <el-icon class="loading-icon"><Loading /></el-icon>
        加载中...
      </div>

      <div v-else-if="filteredOrders.length === 0" class="empty">
        <el-empty description="暂无订单" />
      </div>

      <div v-else>
        <div v-for="order in filteredOrders" :key="order.id" class="order-item">
          <div class="order-header">
            <div class="order-info">
              <span class="order-no">订单号: {{ order.orderNo }}</span>
              <span class="order-time">{{ formatTime(order.createTime) }}</span>
            </div>
            <div class="order-status">
              <el-tag :type="getStatusType(order.status)" size="small">
                {{ getStatusText(order.status) }}
              </el-tag>
            </div>
          </div>

          <div class="order-content">
            <div class="merchant-info">
              <span class="merchant-name">{{ order.merchantName }}</span>
              <span>外卖员: {{ order.riderName || '等待分配' }}</span>
            </div>

            <div class="order-items">
              <div v-for="item in getOrderItems(order.id)" :key="item.id" class="item">
```

```
              <span>{{ item.dishName }} × {{ item.quantity }}</span>
              <span>¥{{ item.price.toFixed(2) }}</span>
            </div>
          </div>

          <div class="order-total">
            <span
              >总计:
              <strong class="total-amount">¥{{ order.totalAmount.toFixed(2) }}</strong></span
            >
          </div>

          <!-- 操作按钮 -->
          <div class="order-actions">
            <!-- 准备中：可以取消订单 -->
            <el-button
              v-if="order.status === 'PREPARING'"
              type="warning"
              size="small"
              @click="cancelOrder(order.id)"
            >
              取消订单
            </el-button>

            <!-- 已送达：可以确认收货 -->
            <el-button
              v-if="order.status === 'DELIVERED'"
              type="success"
              size="small"
              @click="confirmReceipt(order.id)"
            >
              确认收货
            </el-button>

            <!-- 显示订单详情按钮 -->
            <el-button type="link" size="small" @click="viewOrderDetail(order.id)">
              查看详情
            </el-button>
          </div>
        </div>
      </div>
    </div>
  </div>
</template>

<script setup>
import { ref, onMounted, computed } from 'vue'
import { useRouter } from 'vue-router'
import { ArrowLeft, Loading } from '@element-plus/icons-vue'
import { ElMessageBox, ElMessage } from 'element-plus'
```

```
import api from '@/api'

const router = useRouter()
const user = JSON.parse(localStorage.getItem('user') || '{}')
const orders = ref([])
const orderItemsMap = ref({}) // { orderId: [items] }
const activeStatus = ref('ALL')
const loading = ref(true)

// 获取订单状态对应的标签类型
const getStatusType = (status) => {
  const types = {
    PREPARING: 'warning',
    DELIVERING: 'primary',
    DELIVERED: 'info',
    COMPLETED: 'success',
    CANCELLED: 'danger',
  }
  return types[status] || 'info'
}

// 获取订单状态对应的中文文本
const getStatusText = (status) => {
  const texts = {
    PREPARING: '准备中',
    DELIVERING: '配送中',
    DELIVERED: '已送达',
    COMPLETED: '已完成',
    CANCELLED: '已取消',
  }
  return texts[status] || status
}

// 格式化时间
const formatTime = (time) => {
  if (!time) return ''
  const date = new Date(time)
  return `${date.getFullYear()}-${padZero(date.getMonth() + 1)}-${padZero(date.getDate())}
${padZero(date.getHours())}:${padZero(date.getMinutes())}`
}

const padZero = (num) => {
  return num < 10 ? '0' + num : num
}

// 获取订单项
const getOrderItems = (orderId) => {
  return orderItemsMap.value[orderId] || []
}

// 过滤订单
```

```
const filteredOrders = computed(() => {
  if (activeStatus.value === 'ALL') {
    return orders.value
  }
  return orders.value.filter((order) => order.status === activeStatus.value)
})

// 获取用户订单
const fetchOrders = async () => {
  loading.value = true
  try {
    const response = await api.getOrdersByConsumer(user.id)
    if (response.code === 200) {
      orders.value = response.data
      // 获取每个订单的订单项
      for (const order of orders.value) {
        await fetchOrderItems(order.id)
      }
    }
  } catch (error) {
    console.error('获取订单失败:', error)
  } finally {
    loading.value = false
  }
}

// 获取订单项
const fetchOrderItems = async (orderId) => {
  try {
    const response = await api.getOrderItems(orderId)
    if (response.code === 200) {
      orderItemsMap.value[orderId] = response.data
    }
  } catch (error) {
    console.error('获取订单项失败:', error)
  }
}

// 取消订单
const cancelOrder = async (orderId) => {
  try {
    const confirm = await ElMessageBox.confirm('确定要取消该订单吗？', '提示', {
      confirmButtonText: '确定',
      cancelButtonText: '取消',
      type: 'warning',
    })

    if (confirm) {
      const response = await api.cancelOrder(orderId)
      if (response.code === 200) {
        ElMessage.success('订单已取消')
```

```
        // 刷新订单列表
        fetchOrders()
      } else {
        ElMessage.error(response.message || '取消失败')
      }
    }
  } catch (error) {
    console.error('取消订单失败:', error)
  }
}

// 确认收货
const confirmReceipt = async (orderId) => {
  try {
    const confirm = await ElMessageBox.confirm('确认已收到商品吗？', '提示', {
      confirmButtonText: '确定',
      cancelButtonText: '取消',
      type: 'info',
    })

    if (confirm) {
      const response = await api.updateOrderStatus(orderId, 'COMPLETED')
      if (response.code === 200) {
        ElMessage.success('已确认收货')
        // 刷新订单列表
        fetchOrders()
      } else {
        ElMessage.error(response.message || '操作失败')
      }
    }
  } catch (error) {
    console.error('确认收货失败:', error)
  }
}

// 查看订单详情
const viewOrderDetail = (orderId) => {
  // 这里可以跳转到订单详情页，暂时先用对话框显示
  const order = orders.value.find((o) => o.id === orderId)
  const items = orderItemsMap.value[orderId] || []

  ElMessageBox.alert(
    `
    <div style="text-align: left;">
      <p><strong>订单号:</strong> ${order.orderNo}</p>
      <p><strong>商家:</strong> ${order.merchantName}</p>
      <p><strong>外卖员:</strong> ${order.riderName || '等待分配'}</p>
      <p><strong>状态:</strong> ${getStatusText(order.status)}</p>
      <p><strong>下单时间:</strong> ${formatTime(order.createTime)}</p>
      <p><strong>商品列表:</strong></p>
      <ul>
```

```
        ${items.map((item) => `<li>${item.dishName} × ${item.quantity} = ¥${(item.price *
item.quantity).toFixed(2)}</li>`).join('')}
      </ul>
      <p><strong>总计:</strong> ¥${order.totalAmount.toFixed(2)}</p>
    </div>
    `,
    '订单详情',
    {
      dangerouslyUseHTMLString: true,
      confirmButtonText: '关闭',
    },
  )
}

// 筛选订单
const filterOrders = () => {
  // 计算属性会自动更新，这里不需要额外处理
}

// 返回上一页
const goBack = () => {
  router.back()
}

// 初始化
onMounted(() => {
  if (!user.id) {
    ElMessage.error('请先登录')
    router.push('/login')
    return
  }
  fetchOrders()
})
</script>

<style scoped>
.my-orders {
  max-width: 800px;
  margin: 0 auto;
  padding: 20px;
  min-height: 100vh;
}

.header {
  display: flex;
  align-items: center;
  margin-bottom: 20px;
}

.header h1 {
  margin-left: 20px;
```

```
  font-size: 24px;
  color: #333;
  flex: 1;
}

.filter-tabs {
  margin-bottom: 20px;
  padding: 15px;
  background: white;
  border-radius: 8px;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
}

.order-list {
  min-height: 300px;
}

.loading {
  text-align: center;
  padding: 50px;
  color: #999;
}

.loading-icon {
  margin-right: 10px;
  animation: rotating 2s linear infinite;
}

@keyframes rotating {
  from {
    transform: rotate(0deg);
  }
  to {
    transform: rotate(360deg);
  }
}

.empty {
  padding: 50px 20px;
}

.order-item {
  background: white;
  border-radius: 8px;
  margin-bottom: 15px;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
  overflow: hidden;
}

.order-header {
  display: flex;
```

```
  justify-content: space-between;
  align-items: center;
  padding: 15px 20px;
  background: #f8f9fa;
  border-bottom: 1px solid #e9ecef;
}

.order-info {
  display: flex;
  flex-direction: column;
}

.order-no {
  font-weight: bold;
  color: #333;
  margin-bottom: 5px;
}

.order-time {
  font-size: 12px;
  color: #999;
}

.order-content {
  padding: 20px;
}

.merchant-info {
  display: flex;
  justify-content: space-between;
  margin-bottom: 15px;
  padding-bottom: 15px;
  border-bottom: 1px solid #f0f0f0;
}

.merchant-name {
  font-weight: bold;
  color: #333;
}

.order-items {
  margin-bottom: 15px;
}

.item {
  display: flex;
  justify-content: space-between;
  padding: 8px 0;
  font-size: 14px;
  color: #666;
}
```

```
.order-total {
  text-align: right;
  padding: 10px 0;
  border-top: 1px solid #f0f0f0;
  margin-top: 10px;
}

.total-amount {
  color: #ff6600;
  font-size: 18px;
}

.order-actions {
  display: flex;
  justify-content: flex-end;
  gap: 10px;
  margin-top: 15px;
  padding-top: 15px;
  border-top: 1px solid #f0f0f0;
}

@media (max-width: 768px) {
  .my-orders {
    padding: 10px;
  }

  .header h1 {
    font-size: 20px;
  }

  .order-header {
    flex-direction: column;
    align-items: flex-start;
    gap: 10px;
  }

  .merchant-info {
    flex-direction: column;
    gap: 10px;
  }
}
</style>
<template>
  <div class="merchant-dashboard">
    <!-- 顶部导航 -->
    <div class="header">
      <h1>商家管理 - {{ merchant.name || '华莱士' }}</h1>
      <div class="user-info">
        <span>欢迎，{{ user.username }}</span>
        <el-button type="text" @click="logout">退出</el-button>
```

```
      </div>
    </div>

    <!-- 标签页 -->
    <div class="tabs">
      <el-tabs v-model="activeTab" @tab-change="handleTabChange">
        <el-tab-pane label="订单管理" name="orders">
          <OrderManagement
            :merchant-id="merchant.id"
            :merchant-name="merchant.name || '华莱士'"
            v-if="activeTab === 'orders' && merchant.id"
          />
        </el-tab-pane>
        <el-tab-pane label="菜品管理" name="dishes">
          <DishManagement :merchant-id="merchant.id" v-if="activeTab === 'dishes' && merchant.id" />
        </el-tab-pane>
        <el-tab-pane label="店铺信息" name="info">
          <ShopInfo :merchant="merchant" v-if="activeTab === 'info'" />
        </el-tab-pane>
      </el-tabs>
    </div>
  </div>
</template>

<script setup>
import { ref, onMounted } from 'vue'
import { useRouter } from 'vue-router'
import { ElMessage } from 'element-plus'
import OrderManagement from '@/components/merchant/OrderManagement.vue'
import DishManagement from '@/components/merchant/DishManagement.vue'
import ShopInfo from '@/components/merchant/ShopInfo.vue'
import api from '@/api'

const router = useRouter()
const user = JSON.parse(localStorage.getItem('user') || '{}')
const merchant = ref({})
const activeTab = ref('orders')

// 获取商家信息
const fetchMerchant = async () => {
  try {
    // 商家登录后直接获取华莱士的信息
    const response = await api.getMerchantByName('华莱士')
    if (response.code === 200) {
      merchant.value = response.data
    } else {
      ElMessage.error('获取商家信息失败')
    }
  } catch (error) {
    console.error('获取商家信息失败:', error)
    ElMessage.error('获取商家信息失败')
```

```
  }
}

// 处理标签页切换
const handleTabChange = (tabName) => {
  activeTab.value = tabName
}

// 退出登录
const logout = () => {
  localStorage.clear()
  router.push('/login')
}

// 初始化
onMounted(() => {
  if (!user.id) {
    ElMessage.error('请先登录')
    router.push('/login')
    return
  }

  if (user.role !== 'MERCHANT') {
    ElMessage.error('您不是商家用户')
    router.push('/login')
    return
  }

  fetchMerchant()
})
</script>

<style scoped>
.merchant-dashboard {
  max-width: 1200px;
  margin: 0 auto;
  padding: 20px;
  min-height: 100vh;
}

.header {
  display: flex;
  justify-content: space-between;
  align-items: center;
  margin-bottom: 20px;
  padding-bottom: 20px;
  border-bottom: 1px solid #e0e0e0;
}

.header h1 {
  margin: 0;
```

```
  font-size: 24px;
  color: #333;
}

.user-info {
  display: flex;
  align-items: center;
  gap: 15px;
}

.tabs {
  background: white;
  border-radius: 8px;
  padding: 20px;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
}

@media (max-width: 768px) {
  .merchant-dashboard {
    padding: 10px;
  }

  .header {
    flex-direction: column;
    align-items: flex-start;
    gap: 15px;
  }

  .user-info {
    align-self: flex-end;
  }
}
</style>
<template>
  <div class="rider-dashboard">
    <!-- 顶部导航 -->
    <div class="header">
      <h1>外卖员管理 - {{ riderName }}</h1>
      <div class="user-info">
        <span>欢迎，{{ user.username }}</span>
        <button @click="logout" class="logout-btn">退出</button>
      </div>
    </div>

    <!-- 简单标签页 -->
    <div class="simple-tabs">
      <div class="tab-buttons">
        <button :class="{ active: activeTab === 'delivering' }" @click="activeTab = 'delivering'">
          配送中订单
        </button>
        <button :class="{ active: activeTab === 'history' }" @click="activeTab = 'history'">
```

```
          历史订单
        </button>
        <button :class="{ active: activeTab === 'profile' }" @click="activeTab = 'profile'">
          个人资料
        </button>
      </div>

      <div class="tab-content">
        <!-- 配送中订单 -->
        <div v-if="activeTab === 'delivering'" class="tab-pane">
          <DeliveringOrders
            :rider-id="user.id"
            :rider-name="user.username"
            @order-delivered="handleOrderDelivered"
          />
        </div>

        <!-- 历史订单 -->
        <div v-if="activeTab === 'history'" class="tab-pane">
          <OrderHistory :rider-id="user.id" />
        </div>

        <!-- 个人资料 -->
        <div v-if="activeTab === 'profile'" class="tab-pane">
          <RiderProfile :rider="user" />
        </div>
      </div>
    </div>
  </div>
</template>

<script setup>
import { ref, onMounted } from 'vue'
import { useRouter } from 'vue-router'
import DeliveringOrders from '@/components/rider/DeliveringOrders.vue'
import OrderHistory from '@/components/rider/OrderHistory.vue'
import RiderProfile from '@/components/rider/RiderProfile.vue'

const router = useRouter()
const user = JSON.parse(localStorage.getItem('user') || '{}')
const activeTab = ref('delivering')
const riderName = ref(user.username || '外卖员')

// 处理订单送达事件
const handleOrderDelivered = () => {
  // 可以刷新订单列表或其他操作
  console.log('订单已送达')
}

// 退出登录
const logout = () => {
```

```
  localStorage.clear()
  router.push('/login')
}

// 初始化
onMounted(() => {
  if (!user.id) {
    alert('请先登录')
    router.push('/login')
    return
  }

  if (user.role !== 'RIDER') {
    alert('您不是外卖员用户')
    router.push('/login')
    return
  }
})
</script>

<style scoped>
.rider-dashboard {
  max-width: 1200px;
  margin: 0 auto;
  padding: 20px;
  min-height: 100vh;
}

.header {
  display: flex;
  justify-content: space-between;
  align-items: center;
  margin-bottom: 20px;
  padding-bottom: 20px;
  border-bottom: 1px solid #e0e0e0;
}

.header h1 {
  margin: 0;
  font-size: 24px;
  color: #333;
}

.user-info {
  display: flex;
  align-items: center;
  gap: 15px;
}

.logout-btn {
  background: #ff4444;
```

```
  color: white;
  border: none;
  padding: 8px 16px;
  border-radius: 4px;
  cursor: pointer;
}

.logout-btn:hover {
  background: #ff2222;
}

.simple-tabs {
  background: white;
  border-radius: 8px;
  overflow: hidden;
  box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
}

.tab-buttons {
  display: flex;
  background: #f5f5f5;
  border-bottom: 1px solid #e0e0e0;
}

.tab-buttons button {
  flex: 1;
  padding: 15px 20px;
  background: none;
  border: none;
  font-size: 16px;
  cursor: pointer;
  transition: all 0.3s;
}

.tab-buttons button:hover {
  background: #e0e0e0;
}

.tab-buttons button.active {
  background: white;
  color: #409eff;
  border-bottom: 2px solid #409eff;
}

.tab-content {
  padding: 20px;
}

.tab-pane {
  min-height: 400px;
}
```

```
@media (max-width: 768px) {
  .rider-dashboard {
    padding: 10px;
  }

  .header {
    flex-direction: column;
    align-items: flex-start;
    gap: 15px;
  }

  .user-info {
    align-self: flex-end;
  }

  .tab-buttons {
    flex-direction: column;
  }
}
</style>
<template>
  <router-view />
</template>

<script>
export default {
  name: 'App',
}
</script>

<style>
* {
  margin: 0;
  padding: 0;
  box-sizing: border-box;
}

body {
  font-family:
    -apple-system, BlinkMacSystemFont, 'Segoe UI', Roboto, 'Helvetica Neue', Arial, sans-serif;
  -webkit-font-smoothing: antialiased;
  -moz-osx-font-smoothing: grayscale;
}
</style>
import { createApp } from 'vue'
import App from './App.vue'
import router from './router'
import ElementPlus from 'element-plus'
import 'element-plus/dist/index.css'
import * as ElementPlusIconsVue from '@element-plus/icons-vue' // 导入所有图标
```

```
const app = createApp(App)

app.use(router)
app.use(ElementPlus)

// 注册所有 Element Plus 图标
for (const [key, component] of Object.entries(ElementPlusIconsVue)) {
  app.component(key, component)
}

// 配置 axios
import axios from 'axios'
axios.defaults.baseURL = 'http://localhost:8080'
axios.defaults.headers.common['Content-Type'] = 'application/json'

// 请求拦截器
axios.interceptors.request.use(
  (config) => {
    const token = localStorage.getItem('token')
    if (token) {
      config.headers.Authorization = `Bearer ${token}`
    }
    return config
  },
  (error) => {
    return Promise.reject(error)
  },
)

// 响应拦截器
axios.interceptors.response.use(
  (response) => {
    return response.data
  },
  (error) => {
    if (error.response && error.response.status === 401) {
      localStorage.removeItem('token')
      localStorage.removeItem('user')
      router.push('/login')
    }
    return Promise.reject(error)
  },
)

// 挂载到全局
app.config.globalProperties.$axios = axios

app.mount('#app')
```