

dlrinstitutes.sty

Andreas Klöckner

March 10, 2015

1 The package

The package `dlrinstitutes` provides DLR institute and site information to other packages via simple interface commands. The package can be loaded by `\usepackage{dlrinstitutes}`. This will provide the following commands to the user:

1.1 `\dlrinstitute{<abbreviation>}`

Use this command to load the given institute's information. The information must be provided in a file called `dlrinstitutes_inst<abbreviation>.sty`. If no such file is present, an error will be issued. Default is `\dlrinstitute{RMC}`. Please see the respective institute definition file for an example, how to define your own institute. You can also specify the institute, by passing the option `"institute=<abbreviation>"` to the package.

1.2 `\dlrsite{<abbreviation>}`

This command is the equivalent for site information. Default is `\dlrsite{OP}`. You can also call this command from within your institute definition. You can also specify the site, by passing the option `"site=<abbreviation>"` to the package.

1.3 Order of loading and using definitions

In order to use data of institutes or site definitions, these definitions must be loaded prior to using them with one of the two commands described above. The order of loading definitions (and thus also the arguments to the package) is important, as loading a definition makes it the default for use in the document. Note that institutes usually define a default site. If you wish to use a different site other than the default site, you must load the site after the institute definition. Data can only be loaded in the preamble. Make sure, you load all institutes and sites there!

1.4 `\DLR{<info type>}`

This command is used to retrieve global information about the DLR. The command respects language changes by the babel package. E.g. `\DLR{name}` will return "German Aerospace Center", when used with english language. Typical info types are listed in table 1.

abbreviation	= DLR
name	e.g. German Aerospace Center
url	e.g. www.dlr.de/en

Table 1: `\DLR` info types

1.5 `\INST[<institute definition>]{<info type>}`

This command retrieves information about the institute. The requested information must be defined by the institute definition file and loaded in the preamble. Otherwise, an error is issued. If the optional argument is omitted, the current default institute is used. The default institute can be switched using `\dlrinstitute`. Typical info types are listed in table 2.

abbreviation	The abbreviation of the department
name	The name of the institute
department	The name of the department
head	The head of the department
operator	The operator's dial-through
fax	The operator's fax
url	The departments web site

Table 2: `\INST` info types

1.6 `\SITE[<site definition>]{<info type>}`

This command retrieves information about the site. The requested information must be defined by the site definition file and loaded in the preamble. Otherwise, an error is issued. If the optional argument is omitted, the current default site is used. The default site can be switched using `\dlrsite`. Typical info types are listed in table 3.

abbreviation	The site's abbreviation
name	The site's full name
street	The site's street adress
zip	The site's ZIP code
city	The name of the site's city
prefix	The site telephone area code
subscriber	The site telephone subscriber number
operator	The site's operator dial-through
url	The site's web..., well site

Table 3: \SITE info types