DATA SET 1	DATA SET 2
Enter the subroutine with these values:	
FC = 0.1	FC = 0.1
LH = 0	LH = 1
PR = 0	PR = 10
NP = 4	NP = 4
P% = 1	P% = 2
PI = 3.141592	PI = 3.141592
These values should be present at line 1200:	
RP = -0.923879	RP = -0.136178
IP = 0.382683	IP = 0.933223
ES = not used	ES = 0.484322
VX = not used	VX = 0.368054
KX = not used	KX = 1.057802
These values should be present at line 1310:	
T = 1.092605	T = 1.092605
W = 0.628318	W = 0.628318
M = 1.000000	M = 0.889450
D = 9.231528	D = 5.656972
X0 = 0.129316	X0 = 0.211029
X1 = 0.258632	X1 = 0.422058
X2 = 0.129316	X2 = 0.211029
Y1 = 0.607963	Y1 = 1.038784
Y2 = -0.125227	Y2 = -0.789584
These values should be return to the main program:	
A0 = 0.061885	A0 = 0.922919
A1 = 0.123770	A1 = -1.845840
A2 = 0.061885	A2 = 0.922919
B1 = 1.048600	B1 = 1.446913
B2 = -0.296140	B2 = -0.836653

TABLE 20-6
Debugging data. This table contains two sets of data for debugging the subroutine listed in Table 20-5.

be obtained from the program in Table 20-4. The subroutine in Table 20-5 is called once for each stage in the cascade. For example, it is called three times for a six pole filter. At the completion of the subroutine, five variables are return to the main program: *A0*, *A1*, *A2*, *B1*, & *B2*. These are the recursion coefficients for the two pole stage being worked on, and can be used to implement the filter in stages.