Python代码-04-调整权重

1. 2024.05.14-调整评估函数各惩罚逻辑之间权重关系、调整总天数与总惩罚值之间权重关系：

遗传派工算法0514 复制代码

```
import pandas as pd
import numpy as np
from deap import base, creator, tools, algorithms
import random
from sqlalchemy import create_engine
from collections import defaultdict

# MySQL 连接信息
mysql_connection_string =
'mysql+pymysql://ncc_01:ncc%21%40%23%24@211.138.201.6:3506/pcms_2022'
mysql_engine = create_engine(mysql_connection_string)

# 查询语句
query = """
SELECT *
FROM v_pp_weldlist
WHERE unitCode = '马来西亚项目'
AND (alterType IS NULL OR alterType NOT IN ('c', 'f', 'w'))
AND TRIM(remark) <> ''
"""
# 执行查询
df_mysql = pd.read_sql(query, mysql_engine)

# 关闭数据库连接
mysql_engine.dispose()

# 导出到 Excel
excel_path = '数据表.xlsx'
df_mysql.to_excel(excel_path, index=False)

# 使用pandas的isna()函数来检查空值
df = df_mysql[pd.isna(df_mysql['finishDate']) |
(df_mysql['finishDate'].astype(str).str.strip() == '')].copy()

# 读取 Excel 文件
df_welders = pd.read_excel('焊工台账.xlsx')
```

```python
# 筛选 '焊接对象' 为 '管道' 并且 '焊工证下发情况' 为 '已下发'
df_welders_filtered = df_welders[(df_welders['焊接对象'] == '管道') &
(df_welders['焊工证下发情况'] == '已下发')]

# 提取 '焊工号' 和 'WPS No.'
df_welders_filtered = df_welders_filtered[['焊工号', 'WPS No.']]

# 读取 WPS 数据
df_wps = pd.read_excel('WPS.xlsx')

# 定义材料映射字典
material_mapping = {
    'A105': 'A106 Gr.B',
    'A106': 'A106 Gr.B',
    'A106-CE': 'A106 Gr.B',
    'API 5L': 'A106 Gr.B',
    'A335 GR.P11': 'P11'
}

# 对于不在映射字典中的材料，保持原值
def map_material(material):
    if material in material_mapping:
        return material_mapping[material]
    else:
        return material

# 将df中的材料名称映射到WPS中使用的标准名称
df['material_standard'] = df['material'].apply(map_material)

# 解析壁厚范围，创建新列
df_wps[['min_thickness', 'max_thickness']] = df_wps['壁厚范围'].str.split('~',
expand=True).astype(float)

# 初始化匹配的WPS列表列
df['matched_WPS'] = np.empty((len(df), 0)).tolist()

# 遍历每行数据，匹配WPS
for index, row in df.iterrows():
    matched_wps = df_wps[(df_wps['材质'] == row['material_standard']) &
                         (df_wps['min_thickness'] <= row['thickness']) &
                         (df_wps['max_thickness'] >= row['thickness'])]['PQR
No.'].tolist()
    df.at[index, 'matched_WPS'] = matched_wps

    # 如果没有找到匹配的WPS编号，打印警告
```

南京南化建设有限公司 夏斐 | 5299

```python
    if not matched_wps:
        print(f"警告：行 {index} 没有匹配到任何WPS编号。材料：
{row['material_standard']}，厚度：{row['thickness']}")

# 创建适应度函数和个体类
creator.create("FitnessMin", base.Fitness, weights=(-1.0,))  # 最小化适应度函数
creator.create("Individual", list, fitness=creator.FitnessMin)  # 基于适应度函数
的个体类

# 创建一个字典来存储每个WPS可以由哪些焊工执行
wps_to_welders = defaultdict(set)
for _, row in df_welders_filtered.iterrows():
    for wps in [row['WPS No.']]:  # 确保 WPS No. 正确处理
        wps_to_welders[wps].add(row['焊工号'])

# 将集合转换为列表（如果需要在之后的处理中使用列表）
for wps in wps_to_welders:
    wps_to_welders[wps] = list(wps_to_welders[wps])

# 改进的初始化策略
def create_individual():
    individual = []
    for _, task in df.iterrows():
        # 获取这个任务对应的合格焊工列表
        qualified_welders = set()
        for wps in task['matched_WPS']:
            if wps in wps_to_welders:
                qualified_welders.update(wps_to_welders[wps])

        qualified_welders = list(qualified_welders)  # 将集合转换为列表以使用
random.choice

        if qualified_welders:
            welder = random.choice(qualified_welders)
        else:
            # 如果没有合格焊工，分配默认值
            welder = "NONE"
            print(f"No qualified welders found for WPS: {task['matched_WPS']}")

        individual.append(welder)
    return creator.Individual(individual)

# 设置遗传算法的工具箱
toolbox = base.Toolbox()
```

```
toolbox.register("attr_welder", random.choice, df_welders_filtered['焊工号'].unique().tolist())  # 随机选择一个焊工号作为属性
toolbox.register("individual", create_individual)  # 使用新的个体创建策略
toolbox.register("population", tools.initRepeat, list, toolbox.individual)  # 创建种群，种群由多个个体组成

# 构建管线的应检测点口数量映射
line_to_inspection_spots = {}
for line, group in df_mysql.groupby('lineCode'):
    if 'rtRate' in group.columns and not group['rtRate'].isnull().all():
        rt_rate = group['rtRate'].dropna().astype(float).iloc[0] / 100  # 取第一个非空的rtRate并转换为比例
        if rt_rate > 0:  # 只有当rtRate大于0时，计算应检测点口数量
            bw_count = group[group['jtype'] == 'BW'].shape[0]
            if bw_count > 0:  # 只有当存在BW类型的焊接时，才需要检测
                inspection_spots = np.ceil(bw_count * rt_rate)
                line_to_inspection_spots[line] = int(inspection_spots)
    else:
        line_to_inspection_spots[line] = 0  # 若无rtRate或全部为NaN，设置检测点口数量为0

# 构建管线到已用焊工的映射
line_welders = defaultdict(set)
for line, welder in df_mysql[['lineCode', 'coverWelder']].dropna().values:
    line_welders[line].add(welder)

# 评估函数
def evalWelding(individual):
    total_days = 0
    total_penalty = 0
    tasks_remaining = df.copy()
    task_days = {}  # 记录任务被安排的天数
    daily_summaries = []  # 新增一个列表来存储每天的摘要信息

    # 初始化welders_per_line包含line_welders中的数据
    welders_per_line = defaultdict(set, {k: set(v) for k, v in line_welders.items()})

    while not tasks_remaining.empty:
        daily_workloads = {}
        tasks_to_drop = []
        welders_used_today = set()

        for i, (index, task) in enumerate(tasks_remaining.iterrows()):
            welder = individual[i]
```

```
            line_code = task['lineCode']
            # 获取该管线的应检测点口数量
            inspection_spots = line_to_inspection_spots.get(line_code, 0)

            if welder == "NONE":
                tasks_to_drop.append(index)
                continue

            if welder not in daily_workloads:
                daily_workloads[welder] = 0

            if daily_workloads[welder] + task['jsize'] <= 50:
                daily_workloads[welder] += task['jsize']
                tasks_to_drop.append(index)
                task_days[index] = total_days + 1  # 记录任务的安排天数
                welders_used_today.add(welder)
            else:
                continue

            # 计算超出的焊工号数
            if inspection_spots > 0 and welder != "NONE":
                # 在添加前检查焊工号是否已在集合中
                initial_welder_count = len(welders_per_line[line_code])

                # 添加焊工号
                welders_per_line[line_code].add(welder)

                # 如果集合大小增加了，说明这是一个新的焊工号
                if len(welders_per_line[line_code]) > initial_welder_count:
                    # 如果超出应检测点口数量，增加惩罚
                    if len(welders_per_line[line_code]) > inspection_spots:
                        total_penalty += 10

        daily_total = sum(daily_workloads.values())
        tasks_remaining.drop(tasks_to_drop, inplace=True)
        daily_summaries.append(f"第 {total_days + 1} 天: 完成 {daily_total} 寸,
剩余总寸径量 {tasks_remaining['jsize'].sum()}, 当天焊工人数
{len(welders_used_today)}")

        # 惩罚1: 每天焊接量不足1500寸径量
        if daily_total < 1500:
            total_penalty += 100  # 不足1500寸径量的惩罚

        # 惩罚2: 每天每有一个焊工没有安排工作
```

```
        total_penalty += (len(df_welders_filtered['焊工号'].unique()) -
len(welders_used_today)) * 5

        # 惩罚3: 每个派出的焊工每天工作量不足20寸径量
        for welder, workload in daily_workloads.items():
            if workload < 20:
                total_penalty += 5  # 每个工作不饱和的焊工惩罚

        total_days += 1
        print(f"第 {total_days} 天: 完成 {daily_total} 寸, 剩余总寸径量
{tasks_remaining['jsize'].sum()}, 当天焊工人数 {len(welders_used_today)}")

        if not tasks_to_drop:  # 如果一天没有任务被分配
            total_penalty += 1000  # 增加高额惩罚以避免无限循环
            break

    print(f"个体评估: 总天数 = {total_days}, 总惩罚值 = {total_penalty}\n")  # 打
印每个个体的总天数和总惩罚值
    return total_days, total_penalty, task_days, daily_summaries  # 返回总天数和
任务天数映射

# 注册遗传算法的操作
toolbox.register("evaluate", evalWelding)  # 注册评估函数，确保它只返回适应度相关
的一个值
toolbox.register("mate", tools.cxTwoPoint)  # 注册交叉操作
toolbox.register("mutate", tools.mutShuffleIndexes, indpb=0.2)  # 注册变异操作
toolbox.register("select", tools.selTournament, tournsize=3)  # 注册选择操作

# 运行遗传算法
population = toolbox.population(n=30)  # 初始化种群
NGEN = 24  # 设置迭代次数
for gen in range(NGEN):
    print(f"第 {gen + 1} 代: ")
    offspring = algorithms.varAnd(population, toolbox, cxpb=0.8, mutpb=0.2)  #
生成后代
    # 使用map函数来计算每个个体的适应度
    fits = list(toolbox.map(toolbox.evaluate, offspring))
    # 更新适应度
    for fit, ind in zip(fits, offspring):
        # 增加总天数的权重因子
        weighted_fitness = 1000 * fit[0] + fit[1]  # fit[0] 是总天数, fit[1] 是
总惩罚值
        ind.fitness.values = (weighted_fitness,)  # 更新适应度值

    population = toolbox.select(offspring, k=len(population))  # 选择新的种群
```

```
# 输出最佳解
best_ind = tools.selBest(population, 1)[0]  # 选择最佳个体
total_days, total_penalty, task_days, best_daily_summaries =
evalWelding(best_ind)  # 独立调用评估，获取任务天数和总天数

# 输出每日摘要信息
print("最优解的每日任务摘要：")
for summary in best_daily_summaries:
    print(summary)
print(f"个体评估：总天数 = {total_days}, 总惩罚值 = {total_penalty}\n")

# 再次计算最佳个体的加权适应度，以便输出
best_fitness = 1000 * total_days + total_penalty
best_ind.fitness.values = (best_fitness,)  # 更新适应度

# 更新DataFrame
df['Assigned Welder'] = best_ind  # 将最佳个体的焊工分配结果存入原数据框
df['Day Assigned'] = df.index.map(lambda x: task_days.get(x, 'Not Assigned'))
# 用 get 方法避免 KeyError

# 输出和保存结果
```

2. 按单元生成共现矩阵图：

生成共现矩阵 复制代码

```
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt

# 设置 matplotlib 支持中文显示
plt.rcParams['font.sans-serif'] = ['SimHei']  # 设置使用的字体
plt.rcParams['axes.unicode_minus'] = False  # 正确显示负号

# 读取数据
df = pd.read_excel('Updated_Data.xlsx')

# 映射 'areaCode' 列的值
area_code_map = {'900-01': '900', '900-02': '900', '900-03': '900', '900-04':
'900', '900-05': '900'}
df['areaCode'] = df['areaCode'].replace(area_code_map)

# 创建一个透视表来计算共现矩阵
co_occurrence_matrix = df.pivot_table(index='areaCode', columns='Day
Assigned', values='Assigned Welder', aggfunc=lambda x: len(set(x)))
```

```python
# 重命名行和列的名称
co_occurrence_matrix.index.name = '单元'
co_occurrence_matrix.columns.name = '天数'

# 绘制热图
plt.figure(figsize=(20, 15))
sns.heatmap(co_occurrence_matrix, annot=True, cmap='Blues', cbar=True,
linewidths=.5, yticklabels=1, xticklabels=1)
plt.yticks(rotation=0)  # 将纵轴标签设置为水平显示
plt.title('各单元每日派工数量共现矩阵')

# 保存图片，设置高清晰度
plt.savefig('各单元每日派工数量共现矩阵.png', dpi=300, bbox_inches='tight')

# 显示图片
plt.show()
```

南京南化建设有限公司 夏斐 | 5299