## Exercise on Feature Point & RANSAC

April 25, 2019

## 1 Harris Corner Detector

```
imColor=imread('./data/library2.jpg');
    figure; imshow (imColor);
    if size(imColor,3) == 3
        imGray=rgb2gray(imColor);
        imGray = imColor;
6
    im = im2double(imGray);
    % here starts your code
11
12
14
    [row, col] = nonmaxsuppts(C, 'radius', 2);
15
    % plot result
17
    img=imshow(imColor), title('my-Harris'),
19
    hold on
    plot(col,row, 'ro','MarkerSize',10),
    hold off
```

In this exercise, you will work on Harris corner detector. You could do as follows:

- 1. load image (convert to gray image if the input image is a color image), convert to double array. Useful Matlab functions: **imread**, **rgb2gray**, **im2double**.
- 2. compute horizontal and vertical first order derivatives:  $I_x$  and  $I_y$  and show them. Useful Matlab functions: edge, imshow.
- 3. Compute three intermediate images  $I_x^2 = I_x \cdot *I_x$ ,  $I_{xy} = I_x \cdot *I_y$ ,  $I_y^2 = I_y \cdot *I_y$  (.\* means per-element product), show them.
- 4. Smooth them  $(I_x^2, I_{xy}, I_y^2)$  with the Gaussian template. Useful MATLAB functions: fspecial, imfilter.
- 5. Recall that  $\mathbf{M} = \begin{bmatrix} I_x^2 & I_{xy} \\ I_{xy} & I_y^2 \end{bmatrix}$  and  $\mathbf{C} = \det(\mathbf{M}) k \operatorname{trace}(\mathbf{M})^2$ , now you need to compute the response (score) of the corner detector at each pixel. **Hint**: you do not need to form  $\mathbf{M}$  explicitly since the determinant and trace of a  $2 \times 2$  matrix  $\begin{bmatrix} a & b \\ c & d \end{bmatrix}$  are ab cd and a + d, respectively. Thus,

$$\mathbf{C} = I_x^2 \cdot * I_y^2 - I_{xy}^2 - k \cdot * (I_x^2 + I_y^2)^2$$

Here,  $.*, .^2$  are per-element operations. k is usually set to 0.04-0.06.

6. Threshold C as

$$\mathbf{C}(\mathbf{C} < \tau) = 0$$

Typical value for  $\tau$  ranges from 0.1 to 0.8 times the maximum value of C.

7. Apply Non-maxima suppression (code is provided), e.g. [row,col] = nonmaxsuppts(C,'radius', 2). Images can be found in a folder called data. You can use the sample code listed above.




Figure 1: Example of Harris corner detection.

## 2 RANSAC

In this exercise, you will work on line fitting using RANSAC. Use the following code to generate simulated data.

```
clc; close all; clear all;
    % generate 500 points
3
       [X, lineTrue] = gen_line_data(500);
5
    % inhomogeneous to homogeneous
6
      ph = tohomo(X);
8
       % your code starts here, do RANSAC line fitting,
9
       % the result is the parameters of the fitted line, i.e. params(1) *x + params(2) *y + params(3) = 0
10
      params = xxxx(ph);
11
12
       % Results Visualization
13
14
       figure;
       hold on
15
      xmin = min(X(1,:));
16
17
       xmax = max(X(1,:));
       xx = linspace(xmin, xmax, 100);
18
      yy1 = -(lineTrue(1).*xx+lineTrue(3))./(lineTrue(2)+le-6);
19
      yy2 = -(params(1).*xx+params(3))./(params(2)+1e-6);
      plot(xx, yy1, 'k-.', 'LineWidth',1);
plot(xx, yy2, 'm--', 'LineWidth',2);
21
22
       xlabel('x')
       ylabel('y')
24
       title('RANSAC results for 2D line estimation')
25
       axis equal tight
       set(gca, 'FontName', 'Arial', 'FontSize', 20);
```

Recall the pipeline of RANSAC:

1. Randomly select n samples from observations: for 2D line fitting, we need at least 2 points, so n=2. Useful Matlab functions: **randperm**.

- 2. Model estimation: here we need to estimate the line parameters. Recall estimating a line from two points with homogeneous coordinates which you have already done in the first assignment.
- 3. Compute Consensus: apply a model-specific loss function to each observation and the model obtained, the response could serve as the consensus. So here we can use the point-to-line distance as the model-specific loss function. The distance obtained is the consensus.
- 4. Classifier inliers and outliers using a predefined threshold. You can try with different threshold. Save the model with the largest number of iniliers.
- 5. Iterate.

## Result expected:




Figure 2: Example of RANSAC line fitting.