



US009375624B2

(12) **United States Patent**
Boyd et al.

(10) **Patent No.:** **US 9,375,624 B2**
(45) **Date of Patent:** **Jun. 28, 2016**

(54) **GOLF CLUBS AND GOLF CLUB HEADS**

(2013.01); *A63B 53/10* (2013.01); *A63B 53/14*
(2013.01); *A63B 69/3617* (2013.01); *A63B*
2053/005 (2013.01); *A63B 2053/0433*
(2013.01);

(71) Applicant: **Nike, Inc.**, Beaverton, OR (US)

(72) Inventors: **Robert Boyd**, Flower Mound, TX (US);
John T. Stites, Weatherford, TX (US);
Mario A. Lafortune, Tigard, OR (US);
Philip Hatton, Portland, OR (US);
Michael Wallans, Beaverton, OR (US)

(Continued)

(58) **Field of Classification Search**

USPC 473/219, 223–227, 231–233
See application file for complete search history.

(73) Assignee: **NIKE, Inc.**, Beaverton, OR (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 176 days.

U.S. PATENT DOCUMENTS

569,438 A 10/1896 Urquhart
632,885 A 9/1899 Sweny

(Continued)

(21) Appl. No.: **13/907,366**

(22) Filed: **May 31, 2013**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2013/0267339 A1 Oct. 10, 2013

CA 2139690 7/1996
CN 2411030 Y 12/2000

(Continued)

OTHER PUBLICATIONS

ISR & WO dated Aug. 2, 2013, from PCT/US2013/043656.

(Continued)

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/250,051,
filed on Sep. 30, 2011, now Pat. No. 8,668,595.

(60) Provisional application No. 61/653,771, filed on May
31, 2012, provisional application No. 61/480,322,
filed on Apr. 28, 2011.

Primary Examiner — Ronald Laneau

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

(51) **Int. Cl.**

A63B 57/00 (2015.01)
A63B 69/36 (2006.01)

(Continued)


(57) **ABSTRACT**

Golf clubs according to at least some example aspects of this
disclosure may include a golf club head and a shaft configured
to engage with the golf club head which includes a grip
engaged with the shaft. Further, the golf club may include a
monitoring device, which includes a sensor and a transmitter.
Additionally, the monitoring device may be configured to
determine data related to the characteristics of a golf swing.
Further, the monitoring device may be configured to transmit
the data related to the characteristics of a golf swing to a
remote computer.

(52) **U.S. Cl.**

CPC *A63B 69/36* (2013.01); *A63B 53/047*
(2013.01); *A63B 53/0466* (2013.01); *A63B*
69/3632 (2013.01); *A63B 69/3685* (2013.01);
G06F 3/0346 (2013.01); *G06K 9/0055*
(2013.01); *G06K 9/00342* (2013.01); *G09B*
19/0038 (2013.01); *A63B 53/00* (2013.01);
A63B 53/0475 (2013.01); *A63B 53/0487*

31 Claims, 47 Drawing Sheets



- (51) **Int. Cl.**
- | | | | | |
|---|-----------|-------------|---------|-------------------|
| <i>A63B 53/04</i> | (2015.01) | 2,520,701 A | 8/1950 | Verderber |
| <i>G06F 3/0346</i> | (2013.01) | 2,520,702 A | 8/1950 | Verderber |
| <i>G06K 9/00</i> | (2006.01) | 2,550,846 A | 5/1951 | Milligan |
| <i>G09B 19/00</i> | (2006.01) | 2,571,970 A | 10/1951 | Verderber |
| <i>A63B 53/00</i> | (2015.01) | 2,576,866 A | 11/1951 | Verderber |
| <i>A63B 53/10</i> | (2015.01) | 2,593,368 A | 4/1952 | Verderber |
| <i>A63B 53/14</i> | (2015.01) | 2,691,525 A | 10/1954 | Callaghan, Sr. |
| <i>A63B 71/06</i> | (2006.01) | 2,705,147 A | 3/1955 | Winter |
| | | 2,750,194 A | 6/1956 | Clark |
| | | 2,777,694 A | 1/1957 | Winter |
| | | 2,847,219 A | 8/1958 | Shoemaker et al. |
| | | 2,962,286 A | 11/1960 | Brouwer |
| (52) U.S. Cl. | | 3,045,371 A | 7/1962 | Kurlinski |
| CPC <i>A63B 2071/0647</i> (2013.01); <i>A63B 2220/16</i> | | 3,061,310 A | 10/1962 | Giza |
| (2013.01); <i>A63B 2220/30</i> (2013.01); <i>A63B</i> | | 3,064,980 A | 11/1962 | Steiner |
| <i>2220/40</i> (2013.01); <i>A63B 2220/53</i> (2013.01); | | 3,084,940 A | 4/1963 | Cissel |
| <i>A63B 2220/803</i> (2013.01); <i>A63B 2220/833</i> | | 3,170,698 A | 2/1965 | Schoeffler et al. |
| (2013.01); <i>A63B 2225/15</i> (2013.01); <i>A63B</i> | | 3,212,783 A | 10/1965 | Bradley |
| <i>2225/20</i> (2013.01); <i>A63B 2225/50</i> (2013.01) | | 3,270,564 A | 9/1966 | Evans |
| | | 3,305,235 A | 2/1967 | Williams, Jr. |
| | | 3,477,720 A | 11/1969 | Saba |
| | | 3,519,271 A | 7/1970 | Smith |
| | | 3,601,399 A | 8/1971 | Agens et al. |
| | | 3,606,327 A | 9/1971 | Gorman |
| | | 3,788,647 A | 1/1974 | Evans |
| | | 3,791,647 A | 2/1974 | Verderber |
| | | 3,792,863 A | 2/1974 | Evans |
| | | 3,806,131 A | 4/1974 | Evans |
| | | 3,810,631 A | 5/1974 | Braly |
| | | 3,814,437 A | 6/1974 | Winquist |
| | | 3,840,231 A | 10/1974 | Moore |
| | | 3,945,646 A | 3/1976 | Hammond |
| | | 3,966,210 A | 6/1976 | Rozmus |
| | | 3,970,236 A | 7/1976 | Rogers |
| | | 3,976,299 A | 8/1976 | Lawrence et al. |
| | | 3,980,301 A | 9/1976 | Smith |
| | | 3,997,170 A | 12/1976 | Goldberg |
| | | 4,165,874 A | 8/1979 | Lezatte et al. |
| | | 4,194,739 A | 3/1980 | Thompson |
| | | 4,291,883 A | 9/1981 | Smart et al. |
| | | 4,313,607 A | 2/1982 | Thompson |
| | | 4,322,083 A | 3/1982 | Imai |
| | | 4,398,965 A | 8/1983 | Campau |
| | | 4,431,192 A | 2/1984 | Stuff, Jr. |
| | | 4,438,931 A | 3/1984 | Motomiya |
| | | 4,444,392 A | 4/1984 | Duclos |
| | | 4,511,145 A | 4/1985 | Schmidt |
| | | 4,523,759 A | 6/1985 | Igarashi |
| | | 4,534,558 A | 8/1985 | Yoneyama |
| | | 4,535,990 A | 8/1985 | Yamada |
| | | 4,582,321 A | 4/1986 | Yoneyama |
| | | 4,630,827 A | 12/1986 | Yoneyama |
| | | 4,635,941 A | 1/1987 | Yoneyama |
| | | 4,664,383 A | 5/1987 | Aizawa |
| | | 4,667,963 A | 5/1987 | Yoneyama |
| | | 4,681,321 A | 7/1987 | Chen et al. |
| | | 4,697,814 A | 10/1987 | Yamada |
| | | 4,708,347 A | 11/1987 | Kobayashi |
| | | 4,728,105 A | 3/1988 | Kobayashi |
| | | 4,732,389 A | 3/1988 | Kobayashi |
| | | 4,811,949 A | 3/1989 | Kobayashi |
| | | 4,811,950 A | 3/1989 | Kobayashi |
| | | 4,842,280 A | 6/1989 | Hilton |
| | | 4,856,782 A | 8/1989 | Cannan |
| | | 4,867,458 A | 9/1989 | Sumikawa et al. |
| | | 4,871,174 A | 10/1989 | Kobayashi |
| | | 4,878,666 A | 11/1989 | Hosoda |
| | | 4,895,371 A | 1/1990 | Bushner |
| | | 4,898,387 A | 2/1990 | Finney |
| | | 4,898,389 A | 2/1990 | Plutt |
| | | 4,927,144 A | 5/1990 | Stormon |
| | | 4,928,972 A | 5/1990 | Nakanishi et al. |
| | | 4,930,781 A | 6/1990 | Allen |
| | | 4,940,236 A | 7/1990 | Allen |
| | | 4,991,850 A | 2/1991 | Wilhelm |
| | | 5,004,242 A | 4/1991 | Iwanaga et al. |
| | | 5,009,425 A | 4/1991 | Okumoto et al. |
| | | D318,703 S | 7/1991 | Shearer |
| | | 5,028,049 A | 7/1991 | McKeighen |
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | |
|-------------|---------|--------------------|
| 648,256 A | 4/1900 | Hartley |
| 651,920 A | 6/1900 | Cushing, Jr. |
| 670,522 A | 3/1901 | Thompson |
| 727,086 A | 5/1903 | Burnam |
| 777,400 A | 12/1904 | Clark |
| 1,058,463 A | 4/1913 | Pringle |
| 1,083,434 A | 1/1914 | Curry |
| 1,133,129 A | 3/1915 | Govan |
| 1,135,621 A | 4/1915 | Roberts |
| 1,137,457 A | 4/1915 | Breitenbaugh |
| 1,165,559 A | 12/1915 | Vories |
| 1,190,589 A | 7/1916 | Rolfe |
| 1,206,104 A | 11/1916 | Goodrich |
| 1,206,105 A | 11/1916 | Goodrich |
| 1,219,417 A | 3/1917 | Vories |
| 1,222,770 A | 4/1917 | Kaye |
| 1,235,922 A | 8/1917 | Pittar |
| 1,250,301 A | 12/1917 | Goodrich |
| 1,258,212 A | 3/1918 | Goodrich |
| 1,429,569 A | 9/1922 | Craig |
| 1,529,959 A | 3/1925 | Martin |
| 1,549,265 A | 8/1925 | Kaden |
| 1,556,928 A | 10/1925 | Ganders |
| 1,568,485 A | 1/1926 | Turney |
| 1,594,850 A | 8/1926 | Perkins |
| 1,605,140 A | 11/1926 | Perkins |
| 1,620,588 A | 3/1927 | Wilson |
| 1,644,177 A | 10/1927 | Collins |
| 1,676,518 A | 7/1928 | Boles |
| 1,697,846 A | 1/1929 | Anderson |
| 1,697,998 A | 1/1929 | Novak et al. |
| 1,705,997 A | 3/1929 | Williams |
| 1,818,359 A | 8/1931 | Samaras et al. |
| 1,840,924 A | 1/1932 | Tucker |
| 1,854,548 A | 4/1932 | Hunt |
| 1,916,792 A | 7/1933 | Hadden |
| 1,974,224 A | 9/1934 | Van Der Linden |
| 1,993,928 A | 3/1935 | Glover |
| 2,004,968 A | 6/1935 | Young |
| 2,041,676 A | 5/1936 | Gallagher |
| 2,087,685 A | 7/1937 | Hackney |
| 2,179,034 A | 11/1939 | Duncan, Jr. |
| 2,217,338 A | 10/1940 | Fuller |
| 2,242,670 A | 5/1941 | Fuller |
| 2,305,270 A | 12/1942 | Nilson |
| 2,329,313 A | 9/1943 | Winter |
| 2,381,636 A | 8/1945 | Bancroft |
| 2,384,333 A | 9/1945 | Nilson |
| 2,429,351 A | 10/1947 | Fetterolf |
| 2,451,262 A | 10/1948 | Watkins |
| 2,455,150 A | 11/1948 | Verderber |
| 2,475,926 A | 7/1949 | Verderber |
| 2,477,438 A | 7/1949 | Brouwer |
| 2,495,444 A | 1/1950 | Chamberlain et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

5,060,951 A	10/1991	Allen	5,570,886 A	11/1996	Rigal et al.
5,067,715 A	11/1991	Schmidt et al.	5,580,058 A	12/1996	Coughlin
5,076,585 A	12/1991	Bouquet	5,581,993 A	12/1996	Strobel
5,078,397 A	1/1992	Aizawa	5,586,947 A	12/1996	Hutin
5,080,366 A	1/1992	Okumoto et al.	5,586,948 A	12/1996	Mick
D326,130 S	5/1992	Chorne	5,595,552 A	1/1997	Wright et al.
5,133,553 A	7/1992	Divnick	5,601,498 A	2/1997	Antonious
5,186,465 A	2/1993	Chorne	5,603,668 A	2/1997	Antonious
5,205,560 A	4/1993	Hoshi et al.	5,607,365 A	3/1997	Wolf
5,211,401 A	5/1993	Hainey	5,616,088 A	4/1997	Aizawa et al.
5,213,328 A	5/1993	Long et al.	5,616,832 A	4/1997	Nauck
5,221,088 A	6/1993	McTeigue et al.	5,626,528 A	5/1997	Toulon
5,228,689 A	7/1993	Donofrio, Sr.	5,626,530 A	5/1997	Schmidt et al.
5,228,694 A	7/1993	Okumoto et al.	5,634,855 A	6/1997	King
5,233,544 A	8/1993	Kobayashi	D381,382 S	7/1997	Fenton, Jr.
5,245,537 A	9/1993	Barber	5,669,829 A	9/1997	Lin
5,253,869 A	10/1993	Dingle et al.	5,681,993 A	10/1997	Heitman
5,269,517 A	12/1993	Petrucelli et al.	D386,550 S	11/1997	Wright et al.
5,282,625 A	2/1994	Schmidt et al.	D386,551 S	11/1997	Solheim et al.
5,290,036 A	3/1994	Fenton et al.	D387,113 S	12/1997	Burrows
5,295,689 A	3/1994	Lundberg	D387,405 S	12/1997	Solheim et al.
5,301,941 A	4/1994	Allen	5,692,968 A	12/1997	Shine
5,301,946 A	4/1994	Schmidt et al.	5,692,972 A	12/1997	Langslet
5,316,305 A	5/1994	McCabe	5,695,409 A	12/1997	Jackson
5,326,106 A	7/1994	Meyer	5,709,613 A	1/1998	Sheraw
5,330,187 A	7/1994	Schmidt et al.	5,709,615 A	1/1998	Liang
5,332,225 A	7/1994	Ura	5,711,722 A	1/1998	Miyajima et al.
D350,176 S	8/1994	Antonious	5,718,641 A	2/1998	Lin
5,333,871 A	8/1994	Wishon	D392,007 S	3/1998	Fox
5,340,104 A	8/1994	Griffin	5,724,265 A	3/1998	Hutchings
5,354,063 A	10/1994	Curchod	5,728,006 A	3/1998	Teitell et al.
5,364,093 A	11/1994	Huston et al.	5,735,754 A	4/1998	Antonious
5,372,365 A	12/1994	McTeigue et al.	5,746,664 A	5/1998	Reynolds, Jr.
D354,103 S	1/1995	Allen	5,749,795 A	5/1998	Schmidt et al.
5,377,985 A	1/1995	Ohnishi	5,766,094 A	6/1998	Mahaffey et al.
5,380,010 A	1/1995	Werner et al.	5,772,525 A	6/1998	Klein
5,385,346 A	1/1995	Carroll et al.	5,779,555 A	7/1998	Nomura et al.
5,393,056 A	2/1995	Richardson	5,785,609 A	7/1998	Sheets et al.
5,407,196 A	4/1995	Busnardo	D397,387 S	8/1998	Allen
5,413,337 A	5/1995	Goodman et al.	5,788,584 A	8/1998	Parente et al.
5,413,345 A	5/1995	Nauck	5,792,000 A	8/1998	Weber et al.
5,419,556 A	5/1995	Take	5,792,001 A	8/1998	Henwood
5,419,560 A	5/1995	Bamber	D398,687 S	9/1998	Miyajima et al.
5,429,366 A	7/1995	McCabe	D398,946 S	9/1998	Kenmi
5,435,551 A	7/1995	Chen	5,803,830 A	9/1998	Austin et al.
5,437,456 A	8/1995	Schmidt et al.	D399,274 S	10/1998	Bradford
5,441,269 A	8/1995	Henwood	5,820,481 A	10/1998	Raudman
5,447,307 A	9/1995	Antonious	5,826,874 A	10/1998	Teitell et al.
5,451,056 A	9/1995	Manning	D400,945 S	11/1998	Gilbert et al.
5,451,058 A	9/1995	Price et al.	5,839,975 A	11/1998	Lundberg
D363,749 S	10/1995	Kenmi	5,863,261 A	1/1999	Eggiman
5,464,211 A	11/1995	Atkins, Sr.	5,873,791 A	2/1999	Allen
5,464,217 A	11/1995	Shenoha et al.	5,888,148 A	3/1999	Allen
5,467,988 A	11/1995	Henwood	5,908,356 A	6/1999	Nagamoto
5,472,201 A	12/1995	Aizawa et al.	5,908,357 A	6/1999	Hsieh
5,472,203 A	12/1995	Schmidt et al.	5,928,087 A	7/1999	Emberton et al.
5,478,082 A	12/1995	De Knight et al.	5,941,782 A	8/1999	Cook
5,480,152 A	1/1996	Schmidt et al.	D414,234 S	9/1999	Darrah
5,489,097 A	2/1996	Simmons	5,947,841 A	9/1999	Silvestro
5,492,327 A	2/1996	Biafore, Jr.	5,951,410 A	9/1999	Butler et al.
5,497,995 A	3/1996	Swishhelm	5,955,667 A	9/1999	Fyfe
5,505,453 A	4/1996	Mack	5,971,868 A	10/1999	Kosmatka
5,516,106 A	5/1996	Henwood	5,973,596 A	10/1999	French et al.
5,518,243 A	5/1996	Redman	5,997,415 A	12/1999	Wood
5,524,081 A	6/1996	Paul	6,001,030 A	12/1999	Delaney
D371,817 S	7/1996	Olsavsky et al.	6,007,432 A	12/1999	Kosmatka
D372,063 S	7/1996	Hueber	6,012,988 A	1/2000	Burke
5,531,439 A	7/1996	Azzarella	6,015,354 A	1/2000	Ahn et al.
5,533,725 A	7/1996	Reynolds, Jr.	6,018,705 A	1/2000	Gaudet et al.
5,533,728 A	7/1996	Pehoski et al.	D422,041 S	3/2000	Bradford
5,538,245 A	7/1996	Moore	6,042,486 A	3/2000	Gallagher
5,547,188 A	8/1996	Dumontier et al.	6,044,704 A	4/2000	Sacher
5,547,427 A	8/1996	Rigal et al.	6,045,364 A	4/2000	Dugan et al.
5,564,705 A	10/1996	Kobayashi et al.	6,048,278 A	4/2000	Meyer et al.
D375,987 S	11/1996	Lin	6,052,654 A	4/2000	Gaudet et al.
			6,074,309 A	6/2000	Mahaffey
			6,080,068 A	6/2000	Takeda
			6,086,485 A	7/2000	Hamada et al.
			6,095,931 A	8/2000	Hettinger et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,117,022 A	9/2000	Crawford et al.	D484,208 S	12/2003	Burrows
6,120,384 A	9/2000	Drake	6,663,503 B1	12/2003	Kenmi
6,149,533 A	11/2000	Finn	6,676,533 B1	1/2004	Hsien
6,149,534 A	11/2000	Peters et al.	6,688,989 B2	2/2004	Best
6,159,109 A	12/2000	Langslet	6,695,715 B1	2/2004	Chikaraishi
6,176,791 B1	1/2001	Wright	6,697,820 B1	2/2004	Tarlie
6,193,614 B1	2/2001	Sasamoto et al.	6,719,641 B2	4/2004	Dabbs et al.
6,196,932 B1	3/2001	Marsh et al.	6,719,645 B2	4/2004	Kouno
6,203,449 B1	3/2001	Kenmi	6,739,983 B2	5/2004	Helmstetter et al.
6,206,788 B1	3/2001	Krenzler	6,743,112 B2	6/2004	Nelson
6,217,461 B1	4/2001	Galy	6,757,572 B1	6/2004	Forest
6,224,493 B1	5/2001	Lee et al.	6,767,292 B1	7/2004	Skalla, Sr.
6,248,021 B1	6/2001	Ognjanovic	6,773,360 B2	8/2004	Willett et al.
6,261,102 B1	7/2001	Dugan et al.	6,780,123 B2	8/2004	Hasebe
6,270,422 B1	8/2001	Fisher	6,800,037 B2	10/2004	Kosmatka
6,270,423 B1	8/2001	Webb	6,800,038 B2	10/2004	Willett et al.
6,299,546 B1	10/2001	Wang	6,800,039 B1	10/2004	Tseng
6,299,553 B1	10/2001	Petuchowski et al.	6,802,772 B1	10/2004	Kunzle et al.
6,302,807 B1	10/2001	Rohrer	D498,508 S	11/2004	Antonious
6,319,149 B1	11/2001	Lee	6,811,496 B2	11/2004	Wahl et al.
6,319,150 B1	11/2001	Werner et al.	6,819,247 B2	11/2004	Birnback et al.
6,332,848 B1	12/2001	Long et al.	6,821,209 B2	11/2004	Manwaring et al.
6,338,683 B1	1/2002	Kosmatka	D501,036 S	1/2005	Burrows
6,342,018 B1	1/2002	Mason	6,837,800 B2	1/2005	Rollinson et al.
6,344,000 B1	2/2002	Hamada et al.	6,840,872 B2	1/2005	Yoneyama
6,344,001 B1	2/2002	Hamada et al.	D502,232 S	2/2005	Antonious
6,348,009 B1	2/2002	Dischler	6,863,620 B2	3/2005	Tucker, Sr.
6,348,013 B1	2/2002	Kosmatka	6,876,947 B1	4/2005	Darley et al.
6,354,956 B1	3/2002	Doong	6,878,071 B1	4/2005	Schwieger et al.
6,354,961 B1	3/2002	Allen	6,882,955 B1	4/2005	Ohlenbusch et al.
RE37,647 E	4/2002	Wolf	6,887,165 B2	5/2005	Tsurumaki
6,368,234 B1	4/2002	Galloway	6,899,638 B2	5/2005	Iwata et al.
6,386,987 B1	5/2002	Lejeune, Jr.	6,900,759 B1	5/2005	Katayama
6,394,910 B1	5/2002	McCarthy	6,923,729 B2	8/2005	McGinty et al.
6,402,634 B2	6/2002	Lee et al.	6,923,733 B2	8/2005	Chen
6,402,637 B1	6/2002	Sasamoto et al.	6,926,618 B2	8/2005	Sanchez et al.
6,402,638 B1	6/2002	Kelley	6,929,558 B2	8/2005	Manwaring et al.
6,413,167 B1	7/2002	Burke	6,960,142 B2	11/2005	Bissonnette et al.
6,422,951 B1	7/2002	Burrows	6,991,552 B2	1/2006	Burke
6,428,423 B1	8/2002	Merko	6,991,555 B2	1/2006	Reese
6,430,843 B1	8/2002	Potter et al.	6,991,560 B2	1/2006	Tseng
6,431,990 B1	8/2002	Manwaring	D515,642 S	2/2006	Antonious
6,435,982 B1	8/2002	Galloway et al.	6,994,635 B2	2/2006	Poynor
6,441,745 B1	8/2002	Gates	7,004,848 B2	2/2006	Konow
6,443,857 B1	9/2002	Chuang	7,018,303 B2	3/2006	Yamamoto
6,447,405 B1	9/2002	Chen	7,018,304 B2	3/2006	Bradford
6,454,665 B2	9/2002	Antonious	7,021,140 B2	4/2006	Perkins
6,456,938 B1	9/2002	Barnard	7,025,692 B2	4/2006	Erickson et al.
6,471,603 B1	10/2002	Kosmatka	7,037,198 B2	5/2006	Hameen-Anttila
D465,251 S	11/2002	Wood et al.	7,041,003 B2	5/2006	Bissonnette et al.
6,478,690 B2	11/2002	Helmstetter et al.	7,041,014 B2	5/2006	Wright et al.
6,482,107 B1	11/2002	Urbanski et al.	7,048,646 B2	5/2006	Yamanaka et al.
6,506,126 B1	1/2003	Goodman	D523,498 S	6/2006	Chen et al.
6,506,129 B2	1/2003	Chen	7,056,229 B2	6/2006	Chen
6,514,154 B1	2/2003	Finn	7,066,835 B2	6/2006	Evans et al.
6,524,197 B2	2/2003	Boone	D524,392 S	7/2006	Madore et al.
6,524,198 B2	2/2003	Takeda	7,070,513 B2	7/2006	Takeda et al.
6,533,679 B1	3/2003	McCabe et al.	7,070,515 B1	7/2006	Liu
6,551,199 B2	4/2003	Viera	7,083,530 B2	8/2006	Wahl et al.
6,558,271 B1	5/2003	Beach et al.	7,086,964 B2	8/2006	Chen et al.
6,561,917 B2	5/2003	Manwaring	7,090,590 B2	8/2006	Chen
6,602,149 B1	8/2003	Jacobson	7,118,498 B2	10/2006	Meadows et al.
6,605,007 B1	8/2003	Bissonnette et al.	7,121,956 B2	10/2006	Lo
6,607,450 B1	8/2003	Hackman	7,121,962 B2	10/2006	Reeves
6,607,451 B2	8/2003	Kosmatka et al.	7,125,340 B1	10/2006	Priester et al.
6,616,547 B2	9/2003	Vincent et al.	7,128,660 B2	10/2006	Gillig
6,634,956 B1	10/2003	Pegg	7,128,663 B2	10/2006	Bamber
6,638,175 B2	10/2003	Lee et al.	7,134,971 B2	11/2006	Franklin et al.
D482,089 S	11/2003	Burrows	7,137,907 B2	11/2006	Gibbs et al.
D482,090 S	11/2003	Burrows	7,140,975 B2	11/2006	Bissonnette et al.
D482,420 S	11/2003	Burrows	7,140,977 B2	11/2006	Atkins, Sr.
6,641,490 B2	11/2003	Ellemor	7,147,569 B2	12/2006	Tang et al.
6,648,769 B2	11/2003	Lee et al.	7,156,750 B2	1/2007	Nishitani et al.
6,652,390 B2	11/2003	Bradford	7,160,200 B2	1/2007	Grober
6,652,391 B1	11/2003	Kubica et al.	7,163,468 B2	1/2007	Gibbs et al.
			7,163,470 B2	1/2007	Galloway et al.
			7,169,059 B2	1/2007	Rice et al.
			7,175,177 B2	2/2007	Meifu et al.
			7,175,511 B2	2/2007	Ueda et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,175,541 B2	2/2007	Lo	7,753,809 B2	7/2010	Cackett et al.
7,186,185 B2	3/2007	Nagy	7,758,452 B2	7/2010	Soracco
7,186,188 B2	3/2007	Gilbert et al.	7,766,760 B2	8/2010	Priester et al.
7,192,364 B2	3/2007	Long	7,771,263 B2	8/2010	Telford
7,201,668 B1	4/2007	Pamias	7,771,285 B2	8/2010	Porter
7,207,898 B2	4/2007	Rice et al.	7,771,290 B2	8/2010	Bezilla et al.
7,211,006 B2	5/2007	Chang	7,780,535 B2	8/2010	Hagood et al.
7,214,138 B1	5/2007	Stivers et al.	7,789,742 B1	9/2010	Murdock et al.
7,226,366 B2	6/2007	Galloway	7,800,480 B1	9/2010	Joseph et al.
7,234,351 B2	6/2007	Perkins	7,801,575 B1	9/2010	Balardeta et al.
7,235,020 B1	6/2007	Christensen	7,803,066 B2	9/2010	Solheim et al.
7,241,230 B2	7/2007	Tsunoda	7,804,404 B1	9/2010	Balardeta et al.
7,244,189 B1	7/2007	Stobbe	7,811,182 B2	10/2010	Ligotti, III et al.
7,247,104 B2	7/2007	Poynor	7,821,407 B2	10/2010	Shears et al.
7,255,653 B2	8/2007	Saso	7,824,277 B2	11/2010	Bennett et al.
7,258,631 B2	8/2007	Galloway et al.	7,825,815 B2	11/2010	Shears et al.
7,261,643 B2	8/2007	Rice et al.	7,831,212 B1	11/2010	Balardeta et al.
D551,310 S	9/2007	Kuan et al.	7,837,574 B2	11/2010	Brunner
7,264,554 B2	9/2007	Bentley	7,837,575 B2	11/2010	Lee et al.
7,264,555 B2	9/2007	Lee et al.	7,837,577 B2	11/2010	Evans
D552,701 S	10/2007	Ruggiero et al.	7,846,036 B2	12/2010	Tanaka
7,278,926 B2	10/2007	Frame	7,853,211 B1	12/2010	Balardeta et al.
7,294,064 B2	11/2007	Tsurumaki et al.	7,857,705 B1	12/2010	Galloway
7,297,071 B2	11/2007	Hyman	7,857,711 B2	12/2010	Shear
7,297,073 B2	11/2007	Jung	7,867,105 B2	1/2011	Moon
7,310,895 B2	12/2007	Whittlesey et al.	7,871,336 B2	1/2011	Breier et al.
7,326,121 B2	2/2008	Roake	7,878,924 B2	2/2011	Clausen et al.
7,335,112 B1	2/2008	Bitondo	7,881,499 B2	2/2011	Bissonnette et al.
D566,214 S	4/2008	Evans et al.	7,883,428 B1	2/2011	Balardeta et al.
7,351,157 B2	4/2008	Priester et al.	7,887,440 B2	2/2011	Wright et al.
7,351,161 B2	4/2008	Beach	7,892,102 B1	2/2011	Galloway
7,367,898 B2	5/2008	Hawkins et al.	7,896,753 B2	3/2011	Boyd et al.
7,387,579 B2	6/2008	Lin et al.	7,918,745 B2	4/2011	Morris et al.
7,396,289 B2	7/2008	Soracco et al.	7,922,596 B2	4/2011	Vanderbilt et al.
7,396,293 B2	7/2008	Soracco	7,922,603 B2	4/2011	Boyd et al.
7,396,296 B2	7/2008	Evans	7,927,231 B2	4/2011	Sato et al.
7,407,443 B2	8/2008	Franklin et al.	7,931,545 B2	4/2011	Soracco et al.
7,431,660 B2	10/2008	Hasegawa	7,934,998 B2	5/2011	Yokota
7,431,663 B2	10/2008	Pamias	7,935,003 B2	5/2011	Matsunaga et al.
7,435,189 B2	10/2008	Hirano	7,938,739 B2	5/2011	Cole et al.
7,442,132 B2	10/2008	Nishio	7,941,097 B1	5/2011	Balardeta et al.
7,445,563 B1	11/2008	Werner	7,946,926 B1	5/2011	Balardeta et al.
7,470,201 B2	12/2008	Nakahara et al.	7,957,767 B2	6/2011	Rofougaran
7,473,186 B2	1/2009	Best et al.	7,959,519 B2	6/2011	Zielke et al.
7,476,161 B2	1/2009	Williams et al.	7,959,523 B2	6/2011	Rae et al.
7,494,426 B2	2/2009	Nishio et al.	7,967,699 B2	6/2011	Soracco
D588,223 S	3/2009	Kuan	7,978,081 B2	7/2011	Shears et al.
7,500,924 B2	3/2009	Yokota	7,988,565 B2	8/2011	Abe
7,509,842 B2	3/2009	Kostuj	7,993,211 B2	8/2011	Bardha
7,520,820 B2	4/2009	Dimarco	7,993,213 B1	8/2011	D'Eath
7,530,901 B2	5/2009	Imamoto et al.	7,997,999 B2	8/2011	Roach et al.
7,540,810 B2	6/2009	Hettinger et al.	8,007,371 B2	8/2011	Breier et al.
7,559,850 B2	7/2009	Gilbert et al.	8,012,041 B2	9/2011	Gibbs et al.
7,563,176 B2	7/2009	Roberts et al.	8,016,694 B2	9/2011	Llewellyn et al.
7,572,193 B2	8/2009	Yokota	8,025,586 B2	9/2011	Teramoto
7,575,523 B2	8/2009	Yokota	8,043,166 B2	10/2011	Cackett et al.
7,575,524 B2	8/2009	Willett et al.	8,052,539 B2	11/2011	Kimber
7,582,024 B2	9/2009	Shear	8,070,622 B2	12/2011	Schmidt
7,602,301 B1	10/2009	Stirling et al.	8,074,495 B2	12/2011	Kostuj
7,618,331 B2	11/2009	Hirano	8,092,316 B2	1/2012	Breier et al.
7,621,820 B2	11/2009	Clausen et al.	8,100,779 B2	1/2012	Solheim et al.
7,627,451 B2	12/2009	Vock et al.	8,105,175 B2	1/2012	Breier et al.
7,632,193 B2	12/2009	Thielen	8,117,903 B2	2/2012	Golden et al.
7,641,568 B2	1/2010	Hoffman et al.	8,172,697 B2	5/2012	Cackett et al.
7,641,569 B2	1/2010	Best et al.	8,177,661 B2	5/2012	Beach et al.
7,647,071 B2	1/2010	Rofougaran et al.	8,177,664 B2	5/2012	Horii et al.
7,651,409 B1	1/2010	Mier	8,182,364 B2	5/2012	Cole et al.
7,691,004 B1	4/2010	Lueders	8,187,116 B2	5/2012	Boyd et al.
7,713,138 B2	5/2010	Sato et al.	8,206,241 B2	6/2012	Boyd et al.
7,717,803 B2	5/2010	DiMarco	8,226,495 B2	7/2012	Savarese et al.
7,717,807 B2	5/2010	Evans et al.	8,235,841 B2	8/2012	Stites et al.
7,722,478 B2	5/2010	Ebner	8,235,844 B2	8/2012	Albertsen et al.
7,736,242 B2	6/2010	Stites et al.	8,241,143 B2	8/2012	Albertsen et al.
D619,666 S	7/2010	DePaul	8,241,144 B2	8/2012	Albertsen et al.
7,749,101 B2	7/2010	Imamoto et al.	8,251,834 B2	8/2012	Curtis et al.
			8,251,836 B2	8/2012	Brandt
			8,257,195 B1	9/2012	Erickson
			8,257,196 B1	9/2012	Abbott et al.
			8,272,974 B2	9/2012	Mickelson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,277,337 B2	10/2012	Shimazaki	8,941,723 B2	1/2015	Bentley et al.
8,282,506 B1	10/2012	Holt	D722,122 S	2/2015	Greensmith
8,303,434 B1	11/2012	DePaul	8,986,133 B2	3/2015	Bennett et al.
8,308,583 B2	11/2012	Morris et al.	8,994,826 B2	3/2015	Bentley
8,328,659 B2	12/2012	Shear	2001/0005695 A1	6/2001	Lee et al.
8,330,284 B2	12/2012	Weston et al.	2001/0035880 A1	11/2001	Musatov et al.
8,337,325 B2	12/2012	Boyd et al.	2001/0041628 A1	11/2001	Thorne et al.
8,337,335 B2	12/2012	Dugan	2001/0053720 A1	12/2001	Lee et al.
8,342,978 B2	1/2013	Tamura	2002/0004723 A1	1/2002	Meifu et al.
8,353,782 B1	1/2013	Beach et al.	2002/0019265 A1	2/2002	Allen
8,353,786 B2	1/2013	Beach et al.	2002/0019677 A1	2/2002	Lee
D675,691 S	2/2013	Oldknow et al.	2002/0049507 A1	4/2002	Hameen-Anttila
D675,692 S	2/2013	Oldknow et al.	2002/0052246 A1	5/2002	Burke
D676,512 S	2/2013	Oldknow et al.	2002/0052750 A1	5/2002	Hirooka
D676,909 S	2/2013	Oldknow et al.	2002/0072815 A1	6/2002	McDonough et al.
D676,913 S	2/2013	Oldknow et al.	2002/0077189 A1	6/2002	Tuer et al.
D676,914 S	2/2013	Oldknow et al.	2002/0082775 A1	6/2002	Meadows et al.
D676,915 S	2/2013	Oldknow et al.	2002/0107085 A1	8/2002	Lee et al.
8,382,604 B2	2/2013	Billings	2002/0123386 A1	9/2002	Perlmutter
D677,353 S	3/2013	Oldknow et al.	2002/0137576 A1	9/2002	Dammen
D678,913 S	3/2013	Chu	2002/0151994 A1	10/2002	Sisco
D678,964 S	3/2013	Oldknow et al.	2002/0160848 A1	10/2002	Burke
D678,965 S	3/2013	Oldknow et al.	2002/0173364 A1	11/2002	Boscha
D678,968 S	3/2013	Oldknow et al.	2002/0173365 A1	11/2002	Boscha
D678,969 S	3/2013	Oldknow et al.	2002/0183134 A1	12/2002	Allen et al.
D678,970 S	3/2013	Oldknow et al.	2002/0183657 A1	12/2002	Socci et al.
D678,971 S	3/2013	Oldknow et al.	2002/0189356 A1	12/2002	Bissonnette et al.
D678,972 S	3/2013	Oldknow et al.	2003/0008722 A1	1/2003	Konow
D678,973 S	3/2013	Oldknow et al.	2003/0009913 A1	1/2003	Potter et al.
8,403,771 B1	3/2013	Rice et al.	2003/0013545 A1	1/2003	Vincent et al.
D679,354 S	4/2013	Oldknow et al.	2003/0014134 A1	1/2003	Morgan
8,430,763 B2	4/2013	Beach et al.	2003/0036436 A1	2/2003	Casanova et al.
8,430,764 B2	4/2013	Bennett et al.	2003/0040380 A1	2/2003	Wright et al.
8,430,770 B2	4/2013	Dugan	2003/0045371 A1	3/2003	Wood et al.
8,435,134 B2	5/2013	Tang et al.	2003/0054900 A1	3/2003	Tindale
8,435,135 B2	5/2013	Stites et al.	2003/0132844 A1	7/2003	Walker
8,491,416 B1	7/2013	Demille et al.	2003/0190975 A1	10/2003	Fagot
8,517,855 B2	8/2013	Beach et al.	2003/0191547 A1	10/2003	Morse
8,517,860 B2	8/2013	Albertsen et al.	2003/0207718 A1	11/2003	Perlmutter
8,562,453 B2	10/2013	Sato	2003/0220154 A1	11/2003	Anelli
8,579,728 B2	11/2013	Morales et al.	2004/0009829 A1	1/2004	Kapilow
8,591,351 B2	11/2013	Albertsen et al.	2004/0018890 A1	1/2004	Stites et al.
8,591,352 B2	11/2013	Hirano	2004/0023729 A1	2/2004	Nagai et al.
8,591,353 B1	11/2013	Honea et al.	2004/0067797 A1	4/2004	Knecht
8,593,286 B2	11/2013	Razoumov et al.	2004/0106460 A1	6/2004	Lee et al.
8,608,587 B2	12/2013	Henrikson et al.	2004/0121852 A1	6/2004	Tsurumaki
D697,152 S	1/2014	Harbert et al.	2004/0142603 A1	7/2004	Walker
8,628,433 B2	1/2014	Stites et al.	2004/0177531 A1	9/2004	DiBenedetto et al.
8,632,419 B2	1/2014	Tang et al.	2004/0180730 A1	9/2004	Franklin et al.
8,641,555 B2	2/2014	Stites et al.	2004/0192463 A1	9/2004	Tsurumaki et al.
8,663,027 B2	3/2014	Morales et al.	2004/0204257 A1	10/2004	Boscha et al.
8,690,704 B2	4/2014	Thomas	2004/0219991 A1	11/2004	Suprock et al.
8,696,450 B2	4/2014	Rose et al.	2004/0225199 A1	11/2004	Evanyk et al.
8,696,491 B1	4/2014	Myers	2004/0259651 A1	12/2004	Storek
8,702,531 B2	4/2014	Boyd et al.	2005/0009630 A1	1/2005	Chao et al.
8,715,096 B2	5/2014	Cherbini	2005/0017454 A1	1/2005	Endo et al.
8,734,265 B2	5/2014	Soracco	2005/0032582 A1	2/2005	Mahajan et al.
D707,768 S	6/2014	Oldknow et al.	2005/0032586 A1	2/2005	Willett et al.
D707,769 S	6/2014	Oldknow et al.	2005/0037862 A1	2/2005	Hagood et al.
D707,773 S	6/2014	Oldknow et al.	2005/0043109 A1	2/2005	Buckley et al.
D708,281 S	7/2014	Oldknow et al.	2005/0049075 A1	3/2005	Chen et al.
D709,575 S	7/2014	Oldknow et al.	2005/0054457 A1	3/2005	Eyestone et al.
8,784,228 B2 *	7/2014	Morin et al. 473/223	2005/0070371 A1	3/2005	Chen et al.
8,801,532 B2	8/2014	Katayama	2005/0079922 A1	4/2005	Priester et al.
8,821,312 B2	9/2014	Burnett et al.	2005/0096151 A1	5/2005	Hou et al.
8,827,831 B2	9/2014	Burnett et al.	2005/0096761 A1	5/2005	Hanover et al.
8,827,836 B2	9/2014	Thomas	2005/0101407 A1	5/2005	Hirano
8,834,289 B2	9/2014	de la Cruz et al.	2005/0119068 A1	6/2005	Onoda et al.
8,834,290 B2	9/2014	Bezilla et al.	2005/0119070 A1	6/2005	Kumamoto
8,840,483 B1	9/2014	Steusloff et al.	2005/0124435 A1	6/2005	Gambetta et al.
8,845,454 B2	9/2014	Boyd et al.	2005/0137024 A1	6/2005	Stites et al.
D714,893 S	10/2014	Atwell	2005/0188566 A1	9/2005	Whittlesey et al.
8,858,360 B2	10/2014	Rice et al.	2005/0192118 A1	9/2005	Rice et al.
8,870,679 B2	10/2014	Oldknow	2005/0215340 A1	9/2005	Stites et al.
8,888,607 B2	11/2014	Harbert et al.	2005/0215350 A1	9/2005	Reyes et al.
			2005/0227775 A1	10/2005	Cassady et al.
			2005/0227780 A1	10/2005	Cover et al.
			2005/0227781 A1	10/2005	Huang et al.
			2005/0240294 A1	10/2005	Jones et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0261073	A1	11/2005	Farrington et al.	2008/0085788	A1	4/2008	Rainer et al.
2005/0266933	A1	12/2005	Galloway	2008/0119303	A1	5/2008	Bennett et al.
2005/0282650	A1	12/2005	Miettinen et al.	2008/0125239	A1	5/2008	Clausen et al.
2005/0288119	A1	12/2005	Wang et al.	2008/0125244	A1	5/2008	Meyer et al.
2006/0000528	A1	1/2006	Galloway	2008/0125246	A1	5/2008	Matsunaga
2006/0019770	A1	1/2006	Meyer et al.	2008/0125288	A1	5/2008	Case
2006/0025229	A1	2/2006	Mahajan et al.	2008/0139339	A1	6/2008	Cheng
2006/0029916	A1	2/2006	Boscha	2008/0146370	A1	6/2008	Beach et al.
2006/0035718	A1	2/2006	Soracco et al.	2008/0171610	A1	7/2008	Shin
2006/0040757	A1	2/2006	Rosselli	2008/0182682	A1	7/2008	Rice et al.
2006/0040765	A1	2/2006	Sano	2008/0188310	A1	8/2008	Murdock
2006/0046868	A1	3/2006	Murphy	2008/0200275	A1	8/2008	Wagen et al.
2006/0052173	A1	3/2006	Telford	2008/0218343	A1	9/2008	Lee et al.
2006/0063600	A1	3/2006	Grober	2008/0242354	A1	10/2008	Rofougaran
2006/0068932	A1	3/2006	Rice et al.	2008/0248896	A1	10/2008	Hirano
2006/0073908	A1	4/2006	Tavares et al.	2008/0287205	A1	11/2008	Katayama
2006/0073910	A1	4/2006	Imamoto et al.	2008/0318703	A1	12/2008	Mooney
2006/0079349	A1	4/2006	Rae et al.	2009/0018795	A1	1/2009	Priester et al.
2006/0084516	A1	4/2006	Eyestone et al.	2009/0048070	A1	2/2009	Vincent et al.
2006/0084525	A1	4/2006	Imamoto et al.	2009/0062032	A1	3/2009	Boyd et al.
2006/0089845	A1	4/2006	Marcell et al.	2009/0075751	A1	3/2009	Gilbert et al.
2006/0090549	A1	5/2006	Kostuj	2009/0098949	A1	4/2009	Chen
2006/0094520	A1	5/2006	Kostuj	2009/0111602	A1	4/2009	Savarese et al.
2006/0094524	A1	5/2006	Kostuj	2009/0120197	A1	5/2009	Golden et al.
2006/0094531	A1	5/2006	Bissonnette et al.	2009/0131190	A1	5/2009	Kimber
2006/0105849	A1	5/2006	Brunner	2009/0131191	A1	5/2009	Priester et al.
2006/0105853	A1	5/2006	Glass	2009/0163285	A1	6/2009	Kwon et al.
2006/0105857	A1	5/2006	Stark	2009/0163294	A1	6/2009	Cackett et al.
2006/0109116	A1	5/2006	Keays	2009/0165530	A1	7/2009	Golden et al.
2006/0111201	A1	5/2006	Nishio et al.	2009/0165531	A1	7/2009	Golden et al.
2006/0122002	A1	6/2006	Konow	2009/0186717	A1	7/2009	Stites et al.
2006/0122004	A1	6/2006	Chen et al.	2009/0203460	A1	8/2009	Clark
2006/0166737	A1	7/2006	Bentley	2009/0209358	A1	8/2009	Niegowski
2006/0166738	A1	7/2006	Eyestone et al.	2009/0221380	A1	9/2009	Breier et al.
2006/0183564	A1	8/2006	Park	2009/0221381	A1	9/2009	Breier et al.
2006/0184336	A1	8/2006	Kolen	2009/0247312	A1	10/2009	Sato et al.
2006/0194178	A1	8/2006	Goldstein	2009/0254204	A1	10/2009	Kostuj
2006/0194644	A1	8/2006	Nishio	2009/0260426	A1	10/2009	Lieberman et al.
2006/0199659	A1	9/2006	Caldwell	2009/0264214	A1	10/2009	De La Cruz et al.
2006/0224306	A1	10/2006	Workman et al.	2009/0270743	A1	10/2009	Dugan et al.
2006/0276256	A1	12/2006	Storek	2009/0286611	A1	11/2009	Beach et al.
2006/0281582	A1	12/2006	Sugimoto	2009/0318245	A1	12/2009	Yim et al.
2006/0287118	A1	12/2006	Wright et al.	2010/0016095	A1	1/2010	Burnett et al.
2007/0006489	A1	1/2007	Case et al.	2010/0029402	A1	2/2010	Noble et al.
2007/0010341	A1	1/2007	Miettinen et al.	2010/0035701	A1	2/2010	Kusumoto
2007/0011919	A1	1/2007	Case	2010/0048314	A1	2/2010	Hsu et al.
2007/0015601	A1	1/2007	Tsunoda et al.	2010/0049468	A1	2/2010	Papadourakis
2007/0021234	A1	1/2007	Tsurumaki et al.	2010/0056298	A1	3/2010	Jertson et al.
2007/0026961	A1	2/2007	Hou	2010/0063778	A1	3/2010	Schrock et al.
2007/0049400	A1	3/2007	Imamoto et al.	2010/0063779	A1	3/2010	Schrock et al.
2007/0049407	A1	3/2007	Tateno et al.	2010/0067566	A1	3/2010	Rofougaran et al.
2007/0049415	A1	3/2007	Shear	2010/0069171	A1	3/2010	Clausen et al.
2007/0049417	A1	3/2007	Shear	2010/0093457	A1	4/2010	Ahern et al.
2007/0087866	A1	4/2007	Meadows et al.	2010/0093458	A1	4/2010	Davenport et al.
2007/0111811	A1	5/2007	Grober	2010/0093463	A1	4/2010	Davenport et al.
2007/0117648	A1	5/2007	Yokota	2010/0099509	A1	4/2010	Ahern et al.
2007/0129178	A1	6/2007	Reeves	2010/0113174	A1	5/2010	Ahern
2007/0135225	A1	6/2007	Nieminen et al.	2010/0113183	A1	5/2010	Soracco
2007/0135237	A1	6/2007	Reeves	2010/0113184	A1	5/2010	Kuan et al.
2007/0149309	A1	6/2007	Ford	2010/0117837	A1	5/2010	Stirling et al.
2007/0155538	A1	7/2007	Rice et al.	2010/0121227	A1	5/2010	Stirling et al.
2007/0191126	A1	8/2007	Mandracken	2010/0121228	A1	5/2010	Stirling et al.
2007/0225085	A1	9/2007	Koide et al.	2010/0130298	A1	5/2010	Dugan et al.
2007/0238538	A1	10/2007	Priester	2010/0144455	A1	6/2010	Ahern
2007/0238551	A1	10/2007	Yokota	2010/0144456	A1	6/2010	Ahern
2007/0270214	A1	11/2007	Bentley	2010/0154255	A1	6/2010	Robinson et al.
2008/0009360	A1	1/2008	Purtill	2010/0190573	A1	7/2010	Boyd
2008/0015047	A1	1/2008	Rice et al.	2010/0197423	A1	8/2010	Thomas et al.
2008/0032817	A1	2/2008	Lo	2010/0197426	A1	8/2010	De La Cruz et al.
2008/0039222	A1	2/2008	Kiraly	2010/0201512	A1	8/2010	Stirling et al.
2008/0039228	A1	2/2008	Breier et al.	2010/0210371	A1	8/2010	Sato et al.
2008/0051208	A1	2/2008	Lee et al.	2010/0216563	A1	8/2010	Stites et al.
2008/0064523	A1	3/2008	Chen	2010/0216564	A1	8/2010	Stites et al.
2008/0076580	A1	3/2008	Murdock et al.	2010/0216565	A1	8/2010	Stites et al.
2008/0085778	A1	4/2008	Dugan	2010/0222152	A1	9/2010	Jaekel et al.
				2010/0234127	A1	9/2010	Snyder et al.
				2010/0255922	A1	10/2010	Lueders
				2010/0261546	A1	10/2010	Nicodem
				2010/0273569	A1	10/2010	Soracco

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0292024 A1 11/2010 Hagood et al.
 2010/0304877 A1 12/2010 Iwahashi et al.
 2010/0304887 A1 12/2010 Bennett et al.
 2010/0308105 A1 12/2010 Savarese et al.
 2011/0021284 A1 1/2011 Stites et al.
 2011/0028230 A1 2/2011 Balardeta et al.
 2011/0053698 A1 3/2011 Stites et al.
 2011/0081978 A1 4/2011 Murdock et al.
 2011/0082571 A1 4/2011 Murdock et al.
 2011/0087344 A1 4/2011 Murdock et al.
 2011/0092260 A1 4/2011 Murdock et al.
 2011/0092310 A1 4/2011 Breier et al.
 2011/0098127 A1 4/2011 Yamamoto
 2011/0098128 A1 4/2011 Clausen et al.
 2011/0118051 A1 5/2011 Thomas
 2011/0130223 A1 6/2011 Murdock et al.
 2011/0151977 A1 6/2011 Murdock et al.
 2011/0152001 A1 6/2011 Hirano
 2011/0195798 A1 8/2011 Sander et al.
 2011/0212757 A1 9/2011 Murdock et al.
 2011/0217757 A1 9/2011 Chaplin et al.
 2011/0218053 A1 9/2011 Tang et al.
 2011/0224011 A1 9/2011 Denton et al.
 2011/0224025 A1 9/2011 Balardeta et al.
 2011/0230273 A1 9/2011 Niegowski et al.
 2011/0256951 A1 10/2011 Soracco et al.
 2011/0256954 A1 10/2011 Soracco
 2011/0281621 A1 11/2011 Murdock et al.
 2011/0294599 A1 12/2011 Albertsen et al.
 2011/0306435 A1 12/2011 Seo
 2012/0019140 A1 1/2012 Maxik et al.
 2012/0052972 A1 3/2012 Bentley
 2012/0077615 A1 3/2012 Schmidt
 2012/0083362 A1 4/2012 Albertsen et al.
 2012/0083363 A1 4/2012 Albertsen et al.
 2012/0120572 A1 5/2012 Bentley
 2012/0122601 A1 5/2012 Beach et al.
 2012/0142447 A1 6/2012 Boyd et al.
 2012/0142452 A1 6/2012 Burnett et al.
 2012/0165110 A1 6/2012 Cheng
 2012/0165111 A1 6/2012 Cheng
 2012/0184393 A1 7/2012 Franklin
 2012/0191405 A1 7/2012 Molyneux et al.
 2012/0196701 A1 8/2012 Stites et al.
 2012/0202615 A1 8/2012 Beach et al.
 2012/0289354 A1* 11/2012 Cottam et al. 473/223
 2012/0302366 A1 11/2012 Murphy
 2013/0041590 A1* 2/2013 Burich et al. 702/19
 2013/0065705 A1 3/2013 Morales et al.
 2013/0065711 A1* 3/2013 Ueda et al. 473/409
 2013/0102410 A1 4/2013 Stites et al.
 2013/0165254 A1 6/2013 Rice et al.
 2013/0210542 A1 8/2013 Harbert et al.
 2013/0260922 A1 10/2013 Yontz et al.
 2013/0324274 A1 12/2013 Stites
 2014/0018184 A1* 1/2014 Bezilla et al. 473/335
 2014/0080629 A1 3/2014 Sargent et al.
 2014/0228649 A1 8/2014 Rayner et al.
 2014/0364246 A1 12/2014 Davenport

FOREIGN PATENT DOCUMENTS

CN 2431912 Y 5/2001
 CN 2487416 Y 4/2002
 CN 2688331 Y 3/2005
 CN 1602981 A 4/2005
 CN 1984698 A 6/2007
 CN 101352609 A 1/2009
 CN 101927084 A 12/2010
 CN 102218209 A 10/2011
 CN 101918090 A 12/2012
 DE 202007013632 U1 12/2007
 EP 2332619 A1 6/2011
 EP 2377586 A2 10/2011

FR 2672226 A1 8/1992
 FR 2717701 A1 9/1995
 FR 2717702 A1 9/1995
 GB 2280380 A 2/1995
 GB 2388792 A 11/2003
 GB 2422554 A 8/2006
 JP S5163452 U 5/1976
 JP H05317465 A 12/1993
 JP H06237 1/1994
 JP H06114127 A 4/1994
 JP H0639036 U 6/1994
 JP 06190088 A 7/1994
 JP H07255886 A 10/1995
 JP H07275407 A 10/1995
 JP H07284546 A 10/1995
 JP H08000785 1/1996
 JP H08131599 A 5/1996
 JP H08141117 A 6/1996
 JP 08-173586 7/1996
 JP H08243195 A 9/1996
 JP H0947528 A 2/1997
 JP H09135932 A 5/1997
 JP H9-239075 9/1997
 JP H09239074 A 9/1997
 JP H09276455 A 10/1997
 JP H9-299521 11/1997
 JP H10277180 A 10/1998
 JP H10305119 A 11/1998
 JP H1157082 A 3/1999
 JP H1169493 A 6/1999
 JP H11244431 A 9/1999
 JP 2980002 B2 11/1999
 JP 11299938 11/1999
 JP 2000-126340 A 5/2000
 JP 11114102 6/2000
 JP 2000176056 A 6/2000
 JP 2000197718 7/2000
 JP 2000271253 A 10/2000
 JP 2001009069 A 1/2001
 JP 2001054596 A 2/2001
 JP 2001062004 3/2001
 JP 20010158015 3/2001
 JP 2001137396 5/2001
 JP 2001145712 5/2001
 JP 2001-293113 A 10/2001
 JP 3216041 B2 10/2001
 JP 2002017908 A 1/2002
 JP 2002017912 A 1/2002
 JP 2002052099 2/2002
 JP 2002052099 A 2/2002
 JP 2002165905 A 6/2002
 JP 2002177416 A 6/2002
 JP 2002239040 A 8/2002
 JP 2002248183 A 9/2002
 JP 2002306646 10/2002
 JP 2002306647 A 10/2002
 JP 2002320692 11/2002
 JP 2003000774 1/2003
 JP 2003079769 3/2003
 JP 2003093554 A 4/2003
 JP 2003180887 A 7/2003
 JP 2003210627 7/2003
 JP 2004174224 A 6/2004
 JP 2004216131 A 8/2004
 JP 2004313762 11/2004
 JP 2004329544 11/2004
 JP 2004351054 A 12/2004
 JP 2004351173 12/2004
 JP 2004351173 A 12/2004
 JP 2005013529 A 1/2005
 JP 2005131280 A 5/2005
 JP 2005193069 7/2005
 JP 2005253973 A 9/2005
 JP 2005305178 A 11/2005
 JP 2006000435 A 1/2006
 JP 2006020817 A 1/2006
 JP 2006175135 A 7/2006
 JP 2006198251 A 8/2006
 JP 2006223701 A 8/2006

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2006247023	A	9/2006
JP	20060231063		9/2006
JP	2007209722	A	8/2007
JP	2007530151	A	11/2007
JP	2008036050	A	2/2008
JP	2008036315	A	2/2008
JP	2008506421	A	3/2008
JP	2008073210	A	4/2008
JP	2008515560	A	5/2008
JP	2008200118		9/2008
JP	2008237689	A	10/2008
JP	2008289866	A	12/2008
JP	2009201744	A	9/2009
JP	2009534546	A	9/2009
JP	2010148652	A	7/2010
JP	2010148653	A	7/2010
JP	2010154875		7/2010
JP	2010154887	A	7/2010
JP	2010279847	A	12/2010
JP	2011024999	A	2/2011
KR	1020060114969		11/2006
KR	1020070095407		9/2007
KR	20090129246	A	12/2009
KR	1020100020131		2/2010
KR	10-2010-0095917	A	9/2010
KR	101002846	B1	12/2010
KR	20110005247	A	1/2011
TW	498774	U	8/2002
TW	I292575		1/2008
TW	I309777		5/2009
WO	9920358	A1	4/1999
WO	9965574	A2	12/1999
WO	0149376	A1	7/2001
WO	0215993	A1	2/2002
WO	2004056425	A2	7/2004
WO	2005035073	A1	4/2005
WO	2005058427	A2	6/2005
WO	2005079933	A1	9/2005
WO	2005094953	A2	10/2005
WO	2005118086	A1	12/2005
WO	2006014459	A2	2/2006
WO	2006073930	A2	7/2006
WO	2007123970	A2	11/2007
WO	2008093710	A1	8/2008
WO	2008157691	A2	12/2008
WO	2009035345	A1	3/2009
WO	2009091636	A1	7/2009
WO	2009152456	A2	12/2009
WO	2010090814	A1	8/2010
WO	2012027726	A2	3/2012
WO	2012138543	A2	10/2012
WO	2012149385	A1	11/2012
WO	2014070343	A1	5/2014

OTHER PUBLICATIONS

International Search Report in International Application No. PCT/US2012/035542; dated Sep. 10, 2012.

International Search Report in International Application No. PCT/US2012/035476; dated Aug. 24, 2012.

Aug. 21, 2015—(WO) Search Report PCT/US2015/036578.

Jan. 22, 2009—(WO) Partial International Search Report and Written Opinion—App. PCT/US2008/067499.

May 19, 2009—(WO) International Search Report and Written Opinion App. No. PCT/US2008/067499.

Apr. 12, 2010—(WO) Partial Search Report App. No. PCT/US2010/021355.

Jan. 7, 2010—(WO) International Preliminary Report on Patentability App. PCT/US2008/067499.

Jul. 7, 2010—(WO) International Search Report and Written Opinion, App. PCT/US2010/021355.

Nov. 26, 2010—(WO) International Search Report and Written Opinion App. No. PCT/US2010/043073.

Nov. 5, 2010—(WO) International Search Report & Written Opinion, App. No. PCT/US2009/064164.

May 6, 2011—(WO) International Search Report and Written Opinion—App. PCT/US2011/023968.

Sep. 9, 2011—(WO) International Search Report and Written Opinion, App. No. PCT/US2011/023678.

Dec. 18, 2012—(WO) International Search Report and Written Opinion App. No. PCT/US2012/057490.

May 30, 2012—(WO) International Search Report and Written Opinion App. No. PCT/US2012/022027.

Nov. 30, 2012—(WO) International Search Report and Written Opinion App. PCT/US2012/052107.

Aug. 14, 2013—(WO) International Search Report and Written Opinion—App. PCT/US2013/025615.

Aug. 8, 2013—(WO) International Preliminary Report on Patentability App. No. PCT/US2012/022027.

Feb. 27, 2013—(WO) International Search Report and Written Opinion—App. PCT/US2012/067050.

Jul. 31, 2013—(WO) International Search Report and Written Opinion—App. No. PCT/US2013/043700.

Nov. 6, 2013—(WO) Partial Search Report, App. No. PCT/US2013/043641.

Mar. 20, 2014—(WO) International Search Report and Written Opinion App. No. PCT/US2013/043641.

Mar. 24, 2014—(WO) International Search Report and Written Opinion—App. PCT/US2013/061812.

Sep. 4, 2014—(WO) International Search Report and Written Opinion—App. PCT/US2014/029044.

“Photographs 1, 2 and 3”, presented in parent U.S. Appl. No. 12/842,650, of unknown source, taken after the filing date of the U.S. Appl. No. 12/842,650, depicting a golf club product; presented to the Patent Office for consideration on Oct. 7, 2011.

Aug. 7, 2013—(TW) Search Report with English Translation, App. No. 100104424.

Dec. 4, 2013—(EP) Office Action—App. 10700927.6, pp. 1-5.

Dec. 9, 2013—(EP) Communication from European Patent Office, App. No. 09756099.9.

Feb. 20, 2013—(CN) Office Action, App. No. CN200980146633.0.

Jun. 19, 2013—(JP) Notice of Reasons for Rejection (with English translation) App. No. 2011-537510.

Mar. 1, 2013—(JP) Third-Party Submission of Information, App. No. 2011-537510.

Sep. 2, 2013—(JP) Notice of Reasons for Rejection (with English translation) App. No. 2012-521833.

Dec. 16, 2014—(KR) Office Action—App. 10-2013-7030795.

Dec. 16, 2014—(KR) Office Action—App. 10-2013-7030898.

Dec. 16, 2014—(KR) Office Action—App. 10-2013-7030950.

Dec. 16, 2014—(KR) Office Action—App. 10-2013-7030958.

Jan. 20, 2014—(JP) Office Action—App. 2013-500052.

Apr. 24, 2015—(EP) Office Action—App. 10700927.6.

Feb. 4, 2015—(JP) Office Action—App. 2014-508612.

Feb. 10, 2015—(CN) Office Action—App. 2012800322199.

Feb. 25, 2015—(JP) Office Action—App. 2014-508129.

Mar. 12, 2015—(JP) Office Action—App. 2014-508604.

Mar. 13, 2015—(CN) Office Action—App. 2012800321213.

Mar. 16, 2015—(JP) Office Action—App. 2014-508605.

Mar. 19, 2015—(CN) Office Action—App. 201280032016.X.

Mar. 20, 2015—(CN) Office Action—App. 2012800322292.

United States Golf Association; Procedure for Measuring the Flexibility of a Golf Clubhead, USGA-TPX3004; Revision 1.0.0; May 1, 2008; p. 1-11.

Aug. 2, 2012—(WO) Partial International Search Report PCT/US2012/031233.

Aug. 2, 2012—(WO) Partial International Search Report PCT/US2012/031844.

Sep. 5, 2012—(WO) ISR PCT/US2012/031131.

Aug. 16, 2013—(WO) International Search Report and Written Opinion PCT/US2013/021466.

Jan. 2, 2013—(WO) ISR PCT/US2012/031101.

Jan. 30, 2013—(WO) International Search Report and Written Opinion PCT/US2012/031844.

(56)

References Cited

OTHER PUBLICATIONS

Jan. 30, 2013—(WO) ISR PCT/US2012/031233.
Oct. 8, 2013—(WO) IPER PCT/US2012/031101.

Oct. 8, 2013—(WO) IPER PCT/US2012/031131.
Oct. 8, 2013—(WO) IPER PCT/US2012/031233.
<http://www.sureshotgps.com/sureshotgps.php>, Feb. 7, 2007.
Sureshot GPS advertisement (date unknown).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 5H




FIG. 5I




FIG. 5J




FIG. 5K




FIG. 6B




FIG. 6A




FIG. 7A





FIG. 7B






FIG. 8A




FIG. 9




FIG. 9A




FIG. 10




FIG. 11






FIG. 12






FIG. 14A




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 16C





FIG. 16D



17A
17B
17C
17D
17E
17F
17G
17H
17I
17J
17K
17L
17M
17N
17O
17P
17Q
17R
17S
17T
17U
17V
17W
17X
17Y
17Z
17AA
17AB
17AC
17AD
17AE
17AF
17AG
17AH
17AI
17AJ
17AK
17AL
17AM
17AN
17AO
17AP
17AQ
17AR
17AS
17AT
17AU
17AV
17AW
17AX
17AY
17AZ
17BA
17BB
17BC
17BD
17BE
17BF
17BG
17BH
17BI
17BJ
17BK
17BL
17BM
17BN
17BO
17BP
17BQ
17BR
17BS
17BT
17BU
17BV
17BW
17BX
17BY
17BZ
17CA
17CB
17CC
17CD
17CE
17CF
17CG
17CH
17CI
17CJ
17CK
17CL
17CM
17CN
17CO
17CP
17CQ
17CR
17CS
17CT
17CU
17CV
17CW
17CX
17CY
17CZ
17DA
17DB
17DC
17DD
17DE
17DF
17DG
17DH
17DI
17DJ
17DK
17DL
17DM
17DN
17DO
17DP
17DQ
17DR
17DS
17DT
17DU
17DV
17DW
17DX
17DY
17DZ
17EA
17EB
17EC
17ED
17EE
17EF
17EG
17EH
17EI
17EJ
17EK
17EL
17EM
17EN
17EO
17EP
17EQ
17ER
17ES
17ET
17EU
17EV
17EW
17EX
17EY
17EZ
17FA
17FB
17FC
17FD
17FE
17FF
17FG
17FH
17FI
17FJ
17FK
17FL
17FM
17FN
17FO
17FP
17FQ
17FR
17FS
17FT
17FU
17FV
17FW
17FX
17FY
17FZ
17GA
17GB
17GC
17GD
17GE
17GF
17GG
17GH
17GI
17GJ
17GK
17GL
17GM
17GN
17GO
17GP
17GQ
17GR
17GS
17GT
17GU
17GV
17GW
17GX
17GY
17GZ
17HA
17HB
17HC
17HD
17HE
17HF
17HG
17HH
17HI
17HJ
17HK
17HL
17HM
17HN
17HO
17HP
17HQ
17HR
17HS
17HT
17HU
17HV
17HW
17HX
17HY
17HZ
17IA
17IB
17IC
17ID
17IE
17IF
17IG
17IH
17II
17IJ
17IK
17IL
17IM
17IN
17IO
17IP
17IQ
17IR
17IS
17IT
17IU
17IV
17IW
17IX
17IY
17IZ
17JA
17JB
17JC
17JD
17JE
17JF
17JG
17JH
17JI
17JJ
17JK
17JL
17JM
17JN
17JO
17JP
17JQ
17JR
17JS
17JT
17JU
17JV
17JW
17JX
17JY
17JZ
17KA
17KB
17KC
17KD
17KE
17KF
17KG
17KH
17KI
17KJ
17KK
17KL
17KM
17KN
17KO
17KP
17KQ
17KR
17KS
17KT
17KU
17KV
17KW
17KX
17KY
17KZ
17LA
17LB
17LC
17LD
17LE
17LF
17LG
17LH
17LI
17LJ
17LK
17LL
17LM
17LN
17LO
17LP
17LQ
17LR
17LS
17LT
17LU
17LV
17LW
17LX
17LY
17LZ
17MA
17MB
17MC
17MD
17ME
17MF
17MG
17MH
17MI
17MJ
17MK
17ML
17MM
17MN
17MO
17MP
17MQ
17MR
17MS
17MT
17MU
17MV
17MW
17MX
17MY
17MZ
17NA
17NB
17NC
17ND
17NE
17NF
17NG
17NH
17NI
17NJ
17NK
17NL
17NM
17NN
17NO
17NP
17NQ
17NR
17NS
17NT
17NU
17NV
17NW
17NX
17NY
17NZ
17OA
17OB
17OC
17OD
17OE
17OF
17OG
17OH
17OI
17OJ
17OK
17OL
17OM
17ON
17OO
17OP
17OQ
17OR
17OS
17OT
17OU
17OV
17OW
17OX
17OY
17OZ
17PA
17PB
17PC
17PD
17PE
17PF
17PG
17PH
17PI
17PJ
17PK
17PL
17PM
17PN
17PO
17PP
17PQ
17PR
17PS
17PT
17PU
17PV
17PW
17PX
17PY
17PZ
17QA
17QB
17QC
17QD
17QE
17QF
17QG
17QH
17QI
17QJ
17QK
17QL
17QM
17QN
17QO
17QP
17QQ
17QR
17QS
17QT
17QU
17QV
17QW
17QX
17QY
17QZ
17RA
17RB
17RC
17RD
17RE
17RF
17RG
17RH
17RI
17RJ
17RK
17RL
17RM
17RN
17RO
17RP
17RQ
17RR
17RS
17RT
17RU
17RV
17RW
17RX
17RY
17RZ
17SA
17SB
17SC
17SD
17SE
17SF
17SG
17SH
17SI
17SJ
17SK
17SL
17SM
17SN
17SO
17SP
17SQ
17SR
17SS
17ST
17SU
17SV
17SW
17SX
17SY
17SZ
17TA
17TB
17TC
17TD
17TE
17TF
17TG
17TH
17TI
17TJ
17TK
17TL
17TM
17TN
17TO
17TP
17TQ
17TR
17TS
17TT
17TU
17TV
17TW
17TX
17TY
17TZ
17UA
17UB
17UC
17UD
17UE
17UF
17UG
17UH
17UI
17UJ
17UK
17UL
17UM
17UN
17UO
17UP
17UQ
17UR
17US
17UT
17UU
17UV
17UW
17UX
17UY
17UZ
17VA
17VB
17VC
17VD
17VE
17VF
17VG
17VH
17VI
17VJ
17VK
17VL
17VM
17VN
17VO
17VP
17VQ
17VR
17VS
17VT
17VU
17VV
17VW
17VX
17VY
17VZ
17WA
17WB
17WC
17WD
17WE
17WF
17WG
17WH
17WI
17WJ
17WK
17WL
17WM
17WN
17WO
17WP
17WQ
17WR
17WS
17WT
17WU
17WV
17WW
17WX
17WY
17WZ
17XA
17XB
17XC
17XD
17XE
17XF
17XG
17XH
17XI
17XJ
17XK
17XL
17XM
17XN
17XO
17XP
17XQ
17XR
17XS
17XT
17XU
17XV
17XW
17XX
17XY
17XZ
17YA
17YB
17YC
17YD
17YE
17YF
17YG
17YH
17YI
17YJ
17YK
17YL
17YM
17YN
17YO
17YP
17YQ
17YR
17YS
17YT
17YU
17YV
17YW
17YX
17YY
17YZ
17ZA
17ZB
17ZC
17ZD
17ZE
17ZF
17ZG
17ZH
17ZI
17ZJ
17ZK
17ZL
17ZM
17ZN
17ZO
17ZP
17ZQ
17ZR
17ZS
17ZT
17ZU
17ZV
17ZW
17ZX
17ZY
17ZZ
17AAA
17AAB
17AAC
17AAD
17AAE
17AAF
17AAG
17AAH
17AAI
17AAJ
17AAK
17AAL
17AAM
17AAN
17AAO
17AAP
17AAQ
17AAR
17AAS
17AAT
17AAU
17AAV
17AAW
17AAX
17AAZ
17AAA
17AAB
17AAC
17AAD
17AAE
17AAF
17AAG
17AAH
17AAI
17AAJ
17AAK
17AAL
17AAM
17AAN
17AAO
17AAP
17AAQ
17AAR
17AAS
17AAT
17AAU
17AAV
17AAW
17AAX
17AAZ
17AAA
17AAB
17AAC
17AAD
17AAE
17AAF
17AAG
17AAH
17AAI
17AAJ
17AAK
17AAL
17AAM
17AAN
17AAO
17AAP
17AAQ
17AAR
17AAS
17AAT
17AAU
17AAV
17AAW
17AAX
17AAZ
17AAA
17AAB
17AAC
17AAD
17AAE
17AAF
17A




FIG. 17B




FIG. 18A




FIG. 18B





FIG. 18C



80




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 20




FIG. 21A





FIG. 21B








FIG. 23A








FIG. 25A




FIG. 25B




FIG. 25C




FIG. 26




FIG. 27A




FIG. 27B

1

GOLF CLUBS AND GOLF CLUB HEADS**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims priority to and is a non-provisional of U.S. Provisional Application No. 61/653,771, filed May 31, 2012, and this application also claims priority to and is a continuation-in-part of U.S. patent application Ser. No. 13/250,051 filed Sep. 30, 2011, which, in turn, claims priority to and is a non-provisional of U.S. Provisional Application No. 61/480,322, filed Apr. 28, 2011, all of which prior applications are hereby incorporated by reference in its entirety and made part hereof.

FIELD OF THE DISCLOSURE

The present disclosure relates to golf clubs and golf club heads. Particular example aspects of this disclosure relate to the golf clubs and golf club heads which may include monitoring devices for monitoring aspects of a golfer's swing or overall golf game.

BACKGROUND

Golf is enjoyed by a wide variety of players—players of different genders and dramatically different ages and/or skill levels. Golf is somewhat unique in the sporting world in that such diverse collections of players can play together in golf events, even in direct competition with one another (e.g., using handicapped scoring, different tee boxes, in team formats, etc.), and still enjoy the golf outing or competition. These factors, together with the increased availability of golf programming on television (e.g., golf tournaments, golf news, golf history, and/or other golf programming) and the rise of well-known golf superstars, at least in part, have increased golf's popularity in recent years, both in the United States and across the world.

Golfers at all skill levels seek to improve their performance, lower their golf scores, and reach that next performance "level." Manufacturers of all types of golf equipment have responded to these demands, and in recent years, the industry has witnessed dramatic changes and improvements in golf equipment. For example, a wide range of different golf ball models now are available, with balls designed to complement specific swing speeds and/or other player characteristics or preferences, e.g., with some balls designed to fly farther and/or straighter; some designed to provide higher or flatter trajectories; some designed to provide more spin, control, and/or feel (particularly around the greens); some designed for faster or slower swing speeds; etc. A host of swing and/or teaching aids also are available on the market that promise to help lower one's golf scores.

Being the sole instrument that sets a golf ball in motion during play, golf clubs also have been the subject of much technological research and advancement in recent years. For example, the market has seen dramatic changes and improvements in putter designs, golf club head designs, shafts, and grips in recent years. Additionally, other technological advancements have been made in an effort to better match the various elements and/or characteristics of the golf club and characteristics of a golf ball to a particular user's swing features or characteristics (e.g., club fitting technology, ball launch angle measurement technology, ball spin rates, etc.). Further technological advancement in golf club design has also involved the incorporation of various types of monitoring devices or sensors in the golf club. Many such designs, how-

2

ever, have been cumbersome and unreliable. In addition, further processing of the data recorded by the sensors has been limited or not performed in a suitable manner to be most useful to golfers.

While the industry has witnessed dramatic changes and improvements to golf equipment in recent years, there is room in the art for further advances in golf club technology. Thus, while golf equipment according to the prior art provide a number of advantageous features, they nevertheless have certain limitations. The present invention seeks to overcome certain of these limitations and other drawbacks of the prior art, and to provide new features not heretofore available.

SUMMARY OF THE DISCLOSURE

The following presents a general summary of aspects of the disclosure in order to provide a basic understanding of the disclosure and various aspects of it. This summary is not intended to limit the scope of the disclosure in any way, but it simply provides a general overview and context for the more detailed description that follows.

It would be advantageous to have the ability to monitor and analyze aspects of a golfer's golf game, such as a golfer's golf swing. For example, it would be beneficial to be able to monitor and analyze golf swings a golfer takes during practice (such as in a teaching facility or on a driving range) or golf swings a golfer takes while actually playing a round of golf on a golf course. Therefore, particular aspects of the disclosure are directed to a golf club which includes a monitoring device.

According to aspects of the disclosure, golf clubs may include a golf club head and a shaft configured to engage with the golf club head which includes a grip engaged with the shaft. The golf club may include a monitoring device, which may include a sensor and a transmitter. Additionally, the monitoring device may be configured to determine data related to the characteristics of a golf swing. Further, the monitoring device may be configured to transmit the data related to the characteristics of a golf swing to a remote computer.

According to aspects of the disclosure, the monitoring device may include one or more sensors for monitoring data related to aspects of a golfer's golf game (such as the golfer's golf swing) and a transmitter/transceiver configured to transmit such data. According to aspects of the disclosure, the transmitted data may be analyzed (as will be described in below) and used to aid a golfer in improving the golfer's abilities (e.g., the golfer's golf swing). It is noted that according to particular example aspects of the disclosure, other data (e.g., particular club data, on-course data (such as particular golf swings and the approximate location where the swings were taken on a golf course) may be monitored, transmitted and coordinated with the data regarding the aspects of a golfer's golf game (such as the golfer's golf swing) and analyzed as well. Further aspects of the disclosure may include sensing impact location on the golf club face upon a golfer impacting a golf ball during a golf swing. Communication of sensed data may be transmitted, wirelessly or via other means, to a remote location for further processing and display to the golfer.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure is illustrated by way of example and not limited in the accompanying figures, in which like reference numerals indicate similar elements throughout, and in which:

3

FIG. 1 is an illustrative embodiment of a wood-type golf club structure according to aspects of the disclosure;

FIG. 2 is an enlarged bottom view of the wood-type golf club head shown in FIG. 1;

FIG. 3 is an exploded view of the wood-type golf club head shown in FIG. 2 and showing a monitoring device;

FIG. 4 is a cartridge according to an illustrative embodiment of the disclosure;

FIGS. 4A and 4B illustrate a monitoring device according to an illustrative embodiment of the disclosure;

FIGS. 5A and 5B illustrate a monitoring device according to an illustrative embodiment of the disclosure;

FIG. 5C is an exploded view of the monitoring device shown in FIGS. 5A and 5B;

FIG. 5D is an illustrative embodiment of another wood-type golf club structure supporting a monitoring device according to aspects of the disclosure;

FIG. 5E is an exploded view of the wood-type golf club head shown in FIG. 5D;

FIG. 5F is an illustrative embodiment of another wood-type golf club structure supporting a monitoring device according to aspects of the disclosure;

FIG. 5G is an illustrative embodiment of another wood-type golf club structure supporting a monitoring device according to aspects of the disclosure;

FIG. 5H illustrates an instrumented golf club that includes a magnetic field sensor, in accordance with an embodiment of the invention;

FIG. 5I illustrates how velocity, time and orientation measurements may be used to determine the swing path of a golf club, in accordance with an embodiment of the invention;

FIG. 5J illustrates an instrumented golf club that includes a gyroscope module, in accordance with an embodiment of the invention;

FIG. 5K illustrates a method of determining the face angle of a golf club with the use of a gyroscope, in accordance with an embodiment of the invention;

FIGS. 6A and 6B illustrate a remote computer system according to an illustrative embodiment of the disclosure;

FIGS. 7A and 7B illustrate wireless communication between the monitoring device and the remote computer system according to an illustrative embodiment of the disclosure;

FIG. 8 is a perspective view of another embodiment of a golf club according to an illustrative embodiment of the disclosure, including an exploded view of a grip portion of the golf club having a cartridge supporting a monitoring device;

FIG. 8A is a perspective view of another embodiment of a golf club according to an illustrative embodiment of the disclosure, including an exploded view of a grip portion of the golf club configured to receive a monitoring device;

FIG. 9 is a perspective view of another embodiment of a golf club according to an illustrative embodiment of the disclosure, including an exploded view of a grip portion of the golf club having a monitoring device;

FIG. 9A is an illustrative user interface according to an embodiment of the disclosure;

FIG. 10 is an illustrative embodiment of an iron-type golf club structure according to aspects of the disclosure;

FIG. 11 is a rear view of the iron-type golf club head shown in FIG. 10 wherein a cartridge is removed from the iron-type golf club head;

FIG. 12 is a cross-sectional view along line 12-12 of the iron-type golf club head shown in FIG. 11;

FIG. 13 is an exploded view of the iron-type golf club head shown in FIG. 10;

4

FIG. 14 is a rear view of the iron-type golf club head shown in FIG. 10 wherein the cartridge is inserted the iron-type golf club head;

FIG. 14A is an illustrative embodiment of another iron-type golf club structure supporting a monitoring device according to aspects of the disclosure;

FIG. 15A is an illustrative embodiment of an putter golf club head structure supporting a monitoring device according to aspects of the disclosure;

FIG. 15B is an exploded view of the putter golf club head shown in FIG. 15A;

FIG. 16A is an exploded view of an illustrative embodiment of an putter golf club head structure having a monitoring device according to aspects of the disclosure;

FIG. 16B is an exploded view of the putter golf club head shown in FIG. 16A wherein the weight is attached the golf club head;

FIG. 16C is an exploded view of an illustrative embodiment of another putter golf club head structure supporting a monitoring device according to aspects of the disclosure;

FIG. 16D is a view of an illustrative embodiment of another putter golf club head structure according to aspects of the disclosure;

FIGS. 17A and 17B are an illustrative embodiment of the interior of an embodiment of a monitoring device according to aspects of the disclosure;

FIGS. 18A-D are illustrative embodiments of circuitry of a monitoring device according to aspects of the disclosure;

FIGS. 19A-B are graphs illustrating the magnitude of acceleration and angular velocities for a typical putt;

FIGS. 19C-D are graphs illustrating the magnitude of acceleration and angular velocities for a typical golf swing associated with a driver;

FIG. 20 is an illustrative monitoring device with openings according to aspects of the disclosure;

FIGS. 21A-B are illustrative removable sections of a golf club according to aspects of the disclosure;

FIG. 22 illustrates golf clubs with have an identical distance between their respective centers of mass and monitoring devices according to aspects of the disclosure;

FIG. 23A shows illustrative removable sections of a golf club according to aspects of the disclosure;

FIG. 23B shows the illustrative removable sections of 23A in combination with their respective golf clubs according to aspects of the disclosure;

FIG. 24 is illustrates a monitoring device configured to be engaged with various different pieces of sports equipment according to aspects of the disclosure;

FIGS. 25A-C show illustrative removable sections of pieces of sports equipment according to aspects of the disclosure;

FIG. 26 is an illustrative monitoring device with openings according to aspects of the disclosure configured to be engaged with the removable sections of FIGS. 25A-C; and

FIGS. 27A-B illustrate swing path profiles of a golf swing and the swing of a baseball bat, respectively.

The reader is advised that the various parts shown in these drawings are not necessarily drawn to scale.

DETAILED DESCRIPTION

The following description and the accompanying figures disclose features of golf club heads and golf clubs in accordance with examples of the present disclosure.

5

I. GENERAL DESCRIPTION OF EXAMPLE
GOLF CLUB HEADS, GOLF CLUBS, AND
METHODS IN ACCORDANCE WITH THIS
DISCLOSURE

Aspects of this disclosure relate to golf club heads and golf clubs. Golf club heads according to at least some example aspects of this disclosure may include: (a) a golf club head body; and (b) a removable section or member which may include a monitoring device. Golf club heads according to at least some example aspects of this disclosure may also include: (c) one or more sensors and (d) a transmitter for transmitting data obtained by the one or more sensors. For example, the one or more sensors and the transmitter may be included in the monitoring device. According to some aspects of the disclosure, the golf club head may be configured to receive the removable section. Further, according to some aspects of the disclosure the golf club head may be configured to receive the monitoring device directly, without a removable section. Further, golf club heads of at least some example aspects of this disclosure may include wood-type golf club heads, iron-type golf club heads and putter type golf club heads.

Aspects of this disclosure also relate to golf club shafts and golf club grips. Golf club shafts according to at least some example aspects of this disclosure may include: (a) a grip portion; and (b) a removable section which may include a monitoring device. The monitoring device according to at least some example aspects of this disclosure may also include: (c) one or more sensors and (d) a transmitter for transmitting data obtained by the one or more sensors. According to some aspects of the disclosure, the grip portion or other portion of the shaft may be configured to receive the removable section. Further, according to some aspects of the disclosure the golf club shaft (e.g., the grip portion) may be configured to receive the monitoring device directly, without a removable section. Golf club shafts of at least some example aspects of this disclosure may include metal shafts, carbon fiber shafts, etc. and be directed to wood-type golf clubs, iron-type golf clubs and putter type golf clubs.

Additional aspects of this disclosure relate to golf club structures that include golf club heads or golf club shafts, e.g., of the types described above. Such golf club structures further may include one or more of: a shaft attached to the golf club head (optionally via a shaft engaging member (e.g., a hosel) or directly inserted otherwise engaged with the shaft); a grip or handle attached to the shaft; etc.

Still additional aspects of this disclosure relate to methods for producing golf club heads and golf club structures in accordance with examples of this disclosure. Such methods may include, for example, one or more of the following steps in any desired order and/or combinations: (a) providing a golf club head of the various types described above (including any or all of the various structures, features, and/or arrangements described above), e.g., by manufacturing or otherwise constructing the golf club head body, by obtaining it from a third party source, etc.; (b) engaging a shaft of the various types described above (including any or all of the various structures, features, and/or arrangements described above) with the golf club head; and (c) engaging a grip of the various types described above (including any or all of the various structures, features, and/or arrangements described above) with the shaft.

Given the general description of various example aspects of the disclosure provided above, more detailed descriptions of various specific examples of golf clubs and golf club head structures according to the disclosure are provided below.

6

II. DETAILED DESCRIPTION OF EXAMPLE
GOLF CLUB HEADS, GOLF CLUB
STRUCTURES, AND METHODS ACCORDING
TO THE DISCLOSURE

As discussed above, it would be advantageous to have the ability to monitor and analyze aspects of a golfer's golf game, such as a golfer's golf swing. Therefore, particular aspects of the disclosure are directed to a golf club which includes a monitoring device. According to aspects of the disclosure, the monitoring device may include one or more sensors for monitoring data related to aspects of a golfer's golf game (such as the golfer's golf swing) and a transmitter configured to transmit such data. It is further understood that the data may be further processed if necessary or desired. According to aspects of the disclosure, the transmitted data may be analyzed (as will be described in below) and used to aid a golfer in improving the golfer's abilities (e.g., the golfer's golf swing). It is noted that in according to particular example aspects of the disclosure, other data (e.g., particular club data, on the course data (such as particular golf swings and the approximate location where the swings were taken on a golf course) may be monitored, transmitted and analyzed as well.

Further, it would also be beneficial to configure the golf club such that the monitoring device is able to be removable from the golf club. For example, if a golfer wanted to use the monitoring device during practice (e.g., on a driving range) and did not want to use it during play on a golf course, it would be beneficial to have a golf club configured to allow the monitoring device to be easily engageable with, and removable from, the golf club in order to allow the golfer to selectively configure the golf club to their particular preference at a given time. If the golfer did not wish to use the monitoring device during an actual round of golf, the cartridge with monitoring device could be removed from the club and replaced with a replacement member without a monitoring device wherein the monitoring device had characteristics such as weighting and aerodynamic features so as to not change the overall characteristics of the golf club from when the monitoring device was installed on the golf club.

Therefore, aspects of the disclosure are directed to a golf club which is configured to receive and secure the monitoring device, and is also configured to release the monitoring device. For example, aspects of the disclosure relate to a golf club which includes a golf club head which is configured to receive and secure the monitoring device in the golf club head. Further, example embodiments of the disclosure relate to golf club heads configured to receive and secure a removable section or a cartridge (e.g., a cartridge containing the monitoring device). Other aspects of the disclosure relate to a golf club which includes a golf club shaft which is configured to receive and secure the monitoring device in the golf club shaft. For example, the grip of the golf club shaft may be configured to receive and secure the monitoring device in the grip of the golf club shaft. Further, example embodiments of the disclosure relate to a golf club shaft configured to receive and secure a removable section or a cartridge (e.g., a cartridge containing the monitoring device).

The following discussion and accompanying figures describe various example golf clubs and golf club head structures in accordance with the present disclosure. When the same reference number appears in more than one drawing, that reference number is used consistently in this specification and the drawings to refer to the same or similar parts throughout.

More specific examples and features of golf club heads and golf club structures according to this disclosure will be

described in detail below in conjunction with the example golf club structures illustrated in FIGS. 1-18.

FIG. 1 generally illustrates an example of a wood-type golf club 100 according to aspects of the disclosure. As seen in FIG. 1, the wood-type golf club may include a wood-type golf club head 101 in accordance with the present disclosure.

In addition to the golf club head 101, the overall golf club structure 100 may include a shaft 103 and a grip or handle 105 attached to the shaft 103. The shaft 103 may be received in, engaged with, and/or attached to the golf club head 101 in any suitable or desired manner, including in conventional manners known and used in the art, without departing from the disclosure. As more specific examples, the shaft 103 may be engaged with the golf club head 101 through a shaft-receiving sleeve or element extending into the club head 101 (e.g., a hosel), and/or directly to the club head structure 101, e.g., via adhesives, cements, welding, soldering, mechanical connectors (such as threads, retaining elements, or the like). If desired, the shaft 103 may be connected to the golf club head 101 in a releasable manner using mechanical connectors to allow easy interchange of one shaft for another on the head. The shaft 103 may be made from any suitable or desired materials, including conventional materials known and used in the art, such as graphite based materials, composite or other non-metal materials, steel materials (including stainless steel), aluminum materials, other metal alloy materials, polymeric materials, combinations of various materials, and the like.

The grip or handle 105 may be attached to, engaged with, and/or extend from the shaft 103 in any suitable or desired manner, including in conventional manners known and used in the art, e.g., using adhesives or cements, etc. As another example, if desired, the grip or handle 105 may be integrally formed as a unitary, one-piece construction with the shaft 103. Additionally, any desired grip or handle materials may be used without departing from this disclosure, including, for example: rubber materials, leather materials, rubber or other materials including cord or other fabric material embedded therein, polymeric materials, and the like.

Further, according to aspects of the disclosure, the golf club 100 may include a hosel. According to aspects of the disclosure, the shaft 103 may be received in and/or inserted into and/or through the hosel. If desired, the hosel may be configured such that the shaft 103 may be engaged with the hosel in a releasable manner using mechanical connectors to allow easy interchange of one shaft for another on the head. For example, threads, locking mechanisms, etc. may be incorporated into the hosel and the end of the shaft 103 that is to be engaged with the hosel may be configured with a corresponding configuration. Also, the shaft 103 may be secured to the hosel via bonding with adhesives or cements, welding (e.g., laser welding), soldering, brazing, or other fusing techniques, etc. Further, optionally, if desired, the hosel may be eliminated and the shaft 103 may be directly attached to the golf club head 101. For example, the shaft 103 may be directly engaged with the golf club head 101 (e.g., by bonding with adhesives or cements, welding (e.g., laser welding), soldering, brazing, or other fusing techniques, etc.).

According to aspects of the disclosure, the golf club head 101 may include a ball striking face (e.g., a ball striking face which includes a face plate) 107. The ball striking face 107 may be provided integrally with the golf club head 101. Also, the ball striking face 107 may include a separate element, such as a face plate, which is configured to be engaged with the golf club head. For example, the golf club head may include a structure, such as a recess, notch or other configuration for receiving the face plate. The face plate may be

engaged with the golf club head in a variety of ways. For example, the face plate may be engaged with the golf club head by press fitting, bonding with adhesives or cements, welding (e.g., laser welding), soldering, brazing, or other fusing techniques, mechanical connectors, etc.

The ball striking face 107 may be comprised of one or more materials. The material(s) of the ball striking face should be relatively durable to withstand the repeated impacts with the golf ball. For example, the ball striking face 107 may comprise a high strength steel. Further, other materials, such as titanium or other metals or alloys may be used as well. Further, the ball striking face 107 may include one or more score lines which extend generally horizontally across the ball striking face 107.

According to aspects of the disclosure, the golf club head may include a crown 101a, a sole 101b, a toe 101c, and a heel 101d. Further, the golf club head 101 may be constructed in any suitable or desired manner and/or from any suitable or desired materials without departing from this disclosure, including from conventional materials and/or in conventional manners known and used in the art. In fact, it is noted that wide varieties of overall club head constructions are possible without departing from this disclosure. For example, if desired, some or all of the various individual parts of the club head body described above may be made from multiple pieces that are connected together (e.g., by adhesives or cements; by welding, soldering, brazing, or other fusing techniques; by mechanical connectors; etc.). The various parts (e.g., crown, sole, face, etc.) may be made from any desired materials and combinations of different materials, including materials that are conventionally known and used in the art, such as metal materials, including lightweight metal materials (e.g., titanium, titanium alloys, aluminum, aluminum alloys, magnesium, magnesium alloys, etc.), composite materials, polymer materials, etc. The club head 101 and/or its various parts may be made by forging, casting, molding, machining, and/or using other techniques and processes, including techniques and processes that are conventional and known in the art.

It is noted that a wide variety of overall club head constructions are possible without departing from this disclosure. For example, it is noted that the dimensions and/or other characteristics of the golf club head 101 according to examples of this disclosure may vary significantly without departing from the disclosure. For example, the above described features and configurations may be incorporated into any wood-type club heads including, for example: wood-type hybrid clubs, fairway woods, drivers, etc.

The depicted golf club 100 is an illustrative embodiment of a golf club which includes aspects of the disclosure. As seen in FIGS. 2 and 3, the golf club head 101 may include a port 109 configured to receive a section, member or cartridge, 200. The cartridge 200 may be configured to house the monitoring device 201. The monitoring device 201 may be configured to house at least one sensor 202 (FIG. 4) for determining various aspects of a golf swing. Further, if desired, the monitoring device 201 may be configured to house a transmitter 203 (or a transceiver). Such features of the golf club 100 will be described in detail below.

As seen in FIG. 3, the cartridge 200 may be configured to engage with the port 109 of the golf club head 100. For example, the cartridge 200 may be sized to directly engage with interior walls of the port 109, such that the cartridge 200 is firmly secured within the golf club head 101.

According to example embodiments of the disclosure, the cartridge 200 may be configured such that when the cartridge 200 is engaged with the port 109, the cartridge 200 becomes

an exterior surface of the golf club head **101**. For example, the cartridge **200** may be configured with a first portion (e.g., an exterior portion) **200a** which is shaped so as to not protrude from the golf club head **101** and, instead, to fit seamlessly, or relatively seamlessly, with the exterior of the golf club head **101**, once the cartridge **200** is engaged with the golf club head **101**. For example, the first portion **200a** of the golf club head **101** may form an exterior portion of the rear of the golf club head **101**. Further, the first portion **200a** of the golf club head **101** may form an exterior portion of crown **101a**, sole **101b**, toe **101c**, heel **101d**, etc. of the golf club head **101** or some combination thereof (e.g., the exterior of a rear portion and a sole portion of the golf club head **101**), and depending on the location of the port **109**. In such a configuration, wherein the first portion **200a**, fits seamlessly, or relatively seamlessly, with the exterior of the golf club head **101**, the aerodynamics of the golf club head **101** will be improved as compared with a golf club head wherein a sensor or transmitter protrudes beyond the surface of the exterior of the golf club head **101**.

Further, according to example aspects of the disclosure, the cartridge **200** may include a second portion (e.g., an insert portion) **200b** which is configured to be inserted into the interior of the port **109** of the golf club head **101**. The second portion **200b** may be configured to house a monitoring device **201** which, in turn, houses the at least one sensor **202** and the transmitter **203**. As seen in the depicted embodiment, the monitoring device **201** may be secured within the second portion **200b** such that the sensor **202** and the transmitter **203** are stationary with regard to the second portion **200b**. In such a configuration wherein the sensor **202** and the transmitter **203** are held stationary with the second portion **200b** and the second portion **200b** is housed within the interior of the golf club head **101**, the sensor **202** and transmitter **203** are relatively well protected (e.g., from the elements (water and other environmental conditions) encountered during use and from potential impacts the golf club head incurs during use of the golf club **100** or during typical storage or transport of the golf club **100** (e.g., in a golf bag).

According to aspects of the disclosure, the cartridge **200** may be made from any desired materials and combinations of different materials, including materials that are conventionally known and used in the art, such as metal materials, including lightweight metal materials (e.g., titanium, titanium alloys, aluminum, aluminum alloys, magnesium, magnesium alloys, etc.), composite materials, polymer materials, etc. For example, according to aspects of the disclosure, the first portion **200a** of the cartridge **200** may be made from the same material from which the exterior of the golf club head **101** is made. In this way, when the cartridge **200** is engaged with the golf club head **101**, the first portion of the cartridge **200** facilitates the appearance of the seamless, or relatively seamless, fit described above between the first portion of the cartridge **200** with the exterior of the golf club head **101**. Further, the second portion **200b** of the cartridge **200** may be a plastic or polymer. The second portion **200b** may be configured to receive the monitoring device **201**. Alternatively, if desired, the second portion **200b** and the monitoring device **201** may be integral. Alternatively, if desired, the monitoring device **201** may be the second portion **200b**. The sensor **201** and the transmitter **202** may be encased within the monitoring device **201** or the second portion **200b**. Further, if desired, shock absorbers may be positioned in the monitoring device **201** or second portion **200b** and configured to surround, or contact, the sensor **201** and the transmitter **202**.

According to aspects of the disclosure, the first portion **200a** may be curved to match the exterior portion of the portion of golf club head **101** with which it is engaged. Fur-

ther, the first portion **200a** may have a length of 1 inch, a width of $\frac{3}{4}$ inch and a thickness of $\frac{1}{10}$ inch. According to aspects of the disclosure, the second portion **200b** may be rectangular, or generally rectangular, extend from the center, or the relative center of the first portion **200a** and may have a length of 1 inch, a width of $\frac{3}{4}$ inch and a height of $\frac{1}{2}$ inch. Further, according to aspects of the disclosure, the cartridge **200** may have a relatively light weight.

According to aspects of the disclosure, the cartridge **200** may include one or more Light Emitting Diodes (LEDs). For example, the first portion **200a** may be configured to be translucent and the one or more LEDs may be configured to emit light through the translucent first portion **200a**. It is noted that, if desired, one or more indicators may be positioned on the cartridge. For example, logos may be inscribed on the first portion **200a** of the cartridge **200**. Further, such logos may be illuminated by the LEDs in particular embodiments of the disclosure.

As seen in the exploded view of FIG. 3, in the depicted embodiment, the port **109** is positioned in the rear or the sole **101b** of the golf club head **101**. However, the port **109** may be positioned in other areas of the golf club head **101** as well (e.g., the crown **101a**). It is noted that according to aspects of the disclosure, the port **109** may be positioned within the golf club head **101** such that when the cartridge **200** is engaged with the golf club head, it is less likely to be contacted during use or transport. For example, the port **109** may be positioned near the rear of the golf club head wherein the cartridge **200** is less likely to contact the ground during a golf swing or when the golf club head **101** is inverted during transport in a golf bag. Such a configuration, wherein the cartridge is less likely to be contacted during the use or transport, reduces the likelihood that the cartridge **200** may be impacted or inadvertently dislodged from its engaged position.

Further, according to aspects of the disclosure, the port **109** may be configured with any size and shape adequate to receive the cartridge **200**. For example, as seen in the depicted embodiment, the port **109** may be relatively rectangular. Further, according to particular embodiments of the disclosure, the port **109** may include a length of 1 inch, a width of $\frac{3}{4}$ inch and a height of $\frac{1}{2}$ inch. Of course, such dimensions are merely exemplary and other sizes may be used as well. As long as the port **109** is configured to receive and securely hold the cartridge **200**, the shape and size of the port **109** can be configured as desired.

It is noted that the port **109** may be configured with a recessed or lipped portion **109a** at its exterior that is configured to receive or, engage with, the first portion **200a** of the cartridge. In this way, the above described seamless, or relatively seamless, fit between with the exterior of the golf club head **101** and the cartridge **200** may be achieved when the cartridge **200** is engaged with the golf club head **101**.

According to aspects of the disclosure, the port **109** may be made from any desired materials and combinations of different materials, including the materials described above with reference to the golf club head **101**, such as metal materials, including lightweight metal materials (e.g., titanium, titanium alloys, aluminum, aluminum alloys, magnesium, magnesium alloys, etc.), composite materials, polymer materials, etc. It is noted that port **109** may be configured separately and then engaged with the golf club head **101** (e.g., by adhesives or cements; by welding, soldering, brazing, or other fusing techniques; by mechanical connectors; etc.) or, also, the port **109** may be integral with the golf club head (e.g., made during the manufacture of the golf club head **101** by forging, casting,

molding, machining, and/or using other techniques and processes, including techniques and processes that are conventional and known in the art).

The cartridge 200 may be secured in the port 109 of the golf club head 101 in a variety of ways. For example, as discussed above, according to aspects of the disclosure, the cartridge 200 may be removably engaged with the golf club head 101. Therefore, mechanical fasteners may be used to secure the cartridge 200 in the port 109. For example, example embodiments of the disclosure may include a cartridge 200 which is configured to be engaged with the golf club head 101 via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc.

Further, one of the advantages of the golf club head 101 is that the cartridge 200 is easily removable from the golf club head 101. Therefore, according to aspects of the disclosure, the golf club head 101 may include a release mechanism for releasing the cartridge 200 from its secured position within the port 109. For example, according to a particular embodiment of the disclosure, the port 109 and cartridge 200 are engaged via a mechanism which includes a spring loaded feature. The spring loaded feature of the release mechanism is configured such that when the cartridge 200 is secured in the port 109, the first portion 200a of the cartridge 200 is seamlessly, or relatively seamlessly, engaged with the exterior of the golf club head 101 as described above. In order to disengage the cartridge 200 from the port 109, the user will press the cartridge 200 which will be depressed a short distance into the golf club head 101. For example, the port 109 may include recessed portion along its exterior opening which allows the cartridge 200 to be depressed a short distance into the port 109. This movement of the cartridge 200 a short predetermined distance into the golf club head 101 disengages the cartridge 200 from its secured position within the golf club head 101. Subsequent to the user depressing the cartridge 200 the predetermined, short distance into the golf club head 101, the user releases the cartridge 200, and the spring loaded release mechanism ejects the cartridge 200 to a short, predetermined distance such that at least a portion of the cartridge 200 protrudes outside the golf club head 101 so that the user can easily grasp and remove the cartridge 200 from the golf club head 101.

As discussed above, the golf club head 101 may include other engagement and release mechanisms. Further, it is noted that the cartridge 200 and the port 109 may include guide features. For example, the port 109 may include one or more grooves and the cartridge 200 may include one or more protrusions which are configured to engage with and be guided by the grooves of the port 109. In example embodiments of the disclosure, the port 109 may include a groove on two or four of the interior walls of the port 109 and the second portion 200b of the cartridge 200 may include a corresponding number of protrusions.

As described above, aspects of the disclosure, are directed to a golf club configured to allow the one or more sensors and transmitter to be easily removable from the golf club head, so that the golfer can choose whether or not the golfer wants to have the one or more sensors and the transmitter engaged with the golf club head during golf swings. For example, as described above, a golfer may only want to use the one or more sensors and transmitter during practice (e.g., on a driving range or in a practice round) and not want the one or more sensors and transmitter engaged with the golf club head during play on a golf course during a round of golf.

Therefore, aspects of the disclosure relate to a weight cartridge 200' which is configured to be engaged with the port 109. The weight cartridge may be configured similarly to the cartridge 200 described above with the exception that the

weight cartridge does not include a monitoring device 201 or a sensor 202 or a transmitter 203. Since the configuration of the weight cartridge is similar to the above described cartridge 200, the structure of the weight cartridge will not be recited here again for the sake or brevity. Further, it is noted that the weight cartridge may be configured to engage with the port 109 in the same manner as the corresponding cartridge 200. Hence, again, for the sake of brevity, the engaging and releasing structure of the weight cartridge and the port 109 will not be elaborated on here.

According to aspects of the disclosure, when the golfer does not want to have the monitoring device 201 housed within the golf club 100, the golfer may disengage and remove the cartridge 200 from the port 109 of the golf club head 101 and engage and secure the weight cartridge with the port 109 of the golf club head 101. By replacing the cartridge 200 with the weight cartridge 200', the golf club head 101 may retain the same exterior shape of the golf club head 101. The golf club 100 will also have the same weighting characteristics as the weight cartridge 200' is also weighted to correspond to the overall weight of the cartridge 200. Hence, the golf club 100 may be used just as it would be for any golf swing when the cartridge 200 is engaged with the golf club head 101 and the aerodynamics and weighting of the golf club head 101 will not be altered.

It is noted that the term weight cartridge is used merely to distinguish the weight cartridge from the cartridge 200 and does not necessarily imply that the cartridge 200 must be weighted. For example, according to aspects of the disclosure, the weight cartridge may have the same mass and weight as the cartridge 200. In such a configuration, the golfer's golf swing will not be affected regardless of which cartridge is engaged with the golf club head 101. However, if desired, the weight cartridge may include one or more weighted portions.

Therefore, based on the above disclosure, it is understood that aspects of the disclosure are directed to a golf club which is configured to receive interchangeable sections or cartridges, wherein one of the interchangeable cartridges may house the one or more sensors and the transmitter and a second of the interchangeable cartridges does not house a sensor or a transmitter. In this way, the golfer may selectively configure the golf club to include, or not include, the one or more sensors and the transmitter, at the golfer's discretion.

The monitoring device 201 may be configured to measure a multitude of different aspects of a golfer's golf game. For example, the monitoring device 201 may be configured to measure golf swing data. According to aspects of the disclosure, golf swing data may include information on a variety of different characteristics of a golf swing. Further, according to particular embodiments of the disclosure, the monitoring device 201 may also be configured to identify the particular golf club in which the sensor is positioned. For example, an RFID tag may be used. Further, according to particular embodiments of the disclosure, the monitoring device 201 may also be configured to identify a location where a particular golf swing was taken. For example, the monitoring device 201 may include Global Positioning Satellite (GPS) technology. Such information may be incorporated with maps of the golf course on which the golf shots were taken in order to provide a golfer with information on each shot during a round of golf. Each of these features will be described in further detail below.

FIG. 4 illustrates one example of a monitoring device 201 that may be employed according to various examples of the disclosure to measure various aspects of a golfer's abilities and game. The monitoring device 201 may include a processor 204 for processing the electrical signals output by the

13

sensors **202**. With some implementations of the disclosure, the processor **204** may be a programmable microprocessor. For still other implementations of the invention, however, the processor **204** may be a purpose-specific circuit device, such as an ASIC. The processor **204** may be configured to perform any desired operation on the signals output from the sensors **202**, such as curve smoothing, noise filtering, outlier removal, amplification, summation, integration, or the like. The processor **204** may be configured to provide the processed signals to transmitter **203** (or transceiver). Further, the monitoring device **201** may be configured to transmit the processed signals to a remote computer system **400** via the transmitter **203** (or transceiver), as will be discussed below. In one exemplary embodiment, the processed data may be transmitted wirelessly. The monitoring device **201** may also include a power supply **206**, for providing power to the sensors **202**, the processor **204**, and the transmitter **203** (or transceiver) as needed. The power supply **206** may be, for example, a battery. Further, as discussed below, embodiments of the monitoring device **201** may include a memory (e.g., a flash memory). The memory may include both a read-only memory (ROM) and a random access memory (RAM). As will be appreciated by those of ordinary skill in the art, both the read-only memory (ROM) and the random access memory (RAM) may store software instructions for execution by the processor **204**.

It is noted that while the depicted embodiment illustrates a processor **204**, according to other aspects of the disclosure, the monitoring device **201** does not need to include a processor to process the data from the sensors **202**. Instead, according to such aspects of the disclosure, the "raw" data from the sensors **202** may be transmitted, such as by wireless transmission, without being processed.

As discussed above, according to particular embodiments of the disclosure, the monitoring device **201** may be configured to measure golf swing data. Examples of golf swing data may include, the velocity of the golf club (or club head) during a golf swing, the acceleration of the club (or club head) during a golf swing, the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), swing tempo, the impact of the ball with the golf club head during a golf swing, aspects of the impact of the ball with the golf club head during a golf swing (e.g., loft, etc.), etc. Further, the sensors may be configured to measure the position (e.g. a spatial position with regard to a particular frame of reference) of the golf club at various points in time in order to provide data on a golf swing. In this way, acceleration, velocity, positioning of the golf club may be determined and analyzed in 3 dimensions. Further, some or all of the above data may be leveraged to create a graphical representation (e.g., a picture or video) of the golf swing. For example, a swing path may be graphically represented in 3 dimensions along an X-Y-Z frame of reference. Further, areas of the "3D golf swing" during which acceleration is taking place may be represented differently than areas of constant velocity or deceleration. For example, high acceleration takes place may be shown in red, while areas in the swing path during which constant velocity or deceleration takes place may be shown in yellow.

According to aspects of the disclosure, the monitoring device **201** may include one or more sensors **202**. It is noted that the sensors **202** may be accelerometers (such as piezoelectric accelerometers), magnetometers, or gyroscopes. Further, one skilled in the art will appreciate that numerous additional sensors may be used in connection with aspects of the disclosure (e.g., impact sensors, strain gauges, etc.). According to particular embodiments of the disclosure, the sensors **202** may be similar to sensors used in the NIKE+™

14

athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg. For example, the sensors **202** may measure golf swing data in a manner akin to the measurement of data in NIKE+™ athletic performance monitoring systems (e.g., speed information, such as velocity and acceleration information, etc.). According to aspects of the disclosure, the sensors **202** will produce electrical signals corresponding to the specific golfing characteristic it is monitoring. As known in the art, these signals can then be used to generate data representative of the golfing activity performed by the golfer.

FIGS. 4A and 4B illustrate a particular embodiment of a monitoring device **201** according to aspects of the disclosure. As seen in FIGS. 4A and 4B, the monitoring device **201** may include a generally rectangular compartment in which sensors **202** are housed. The compartment may be similar to the compartment used to house sensors used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg. For example, according to aspects of the disclosure, the compartment may be rectangular with rounded ends and has a length in the range of 1.0-1.5 inches, a width of 0.4-1.0 inches and thickness of 0.2-0.45 inches. Other dimensions may be used as well. Further, the monitoring device **201** illustrated in FIGS. 5A-C may include three accelerometers, three gyroscopes and a magnetometer. Additionally, the monitoring device **201** illustrated in FIGS. 5A-C may include a transmitter **203** (or transceiver) for wirelessly transmitting data determined by the three accelerometers, three gyroscopes and a magnetometer.

According to aspects of the disclosure, the compartment of the monitoring device **201** may be made of plastic. It is noted that other materials may be used as well. The compartment of the monitoring device **201** may be opened to provide access to the sensors **202** and the other components housed inside the monitoring device **201**. For example, as seen in FIGS. 4A and 4B, the compartment of the monitoring device **201** may include a cover which is configured to slide to provide access to various components of the monitoring device, such as the battery **206**. Further, the compartment of the monitoring device **201** may house a circuit board or the like which may include various elements described above, such as the processor **204**, sensors **202**, transmitter **203**, power supply **206**, memory, etc.

FIGS. 5A-C illustrate a particular embodiment of the monitoring device **201**. Specifically, FIG. 5A is a perspective view of the monitoring device **201**. FIG. 5B is a perspective view of the bottom of the monitoring device **201**. FIG. 5C is an exploded view of the monitoring device **201**. As seen in FIGS. 5A-C, in the depicted embodiment, the monitoring device **201** includes a generally rectangular compartment in which sensors **202** are housed. The compartment may be similar to the compartment used to house sensors used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg. Further, the monitoring device **201** illustrated in FIGS. 5A-C may include three accelerometers, three gyroscopes and a magnetometer. Additionally, the monitoring device **201** illustrated in FIGS. 5A-C may include a transmitter **203** (or transceiver) for wirelessly transmitting data determined by the three accelerometers, three gyroscopes and a magnetometer.

According to aspects of the disclosure, the compartment of the monitoring device **201** may be made of plastic. It is noted that other materials may be used as well. As seen in FIG. 5C, the compartment of the monitoring device **201** may be opened to provide access to the sensors **202** and the other components housed inside the monitoring device **201**. For example, as seen in FIG. 5B, the compartment of the monitoring device

15

201 may include a locking mechanism which allows the compartment to be unlocked and opened. As seen in FIG. 5C, the compartment of the monitoring device 201 may house a circuit board or the like which may include various elements described above, such as the processor 204, sensors 202, transmitter 203, power supply 206, memory, etc.

According to the aspects of the disclosure, the monitoring device 201 may be configured to engage with the golf club head 101 in a variety of ways. FIGS. 5D-5G show various illustrative embodiments in which the monitoring device 201 is engaged with the golf club head 101. For example, FIG. 5D illustrates an embodiment according to the disclosure, wherein the monitoring device 201 and a removable section 200 are engaged with the golf club head 101. FIG. 5E is an exploded view of the embodiment shown in FIG. 5E. As seen in FIGS. 5D and E, the removable section 200 is engaged with the golf club head via a threaded fastener. However, the removable section 200 may be configured to be engaged with the golf club head 101 via other methods as well, such as press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), etc. As seen, the removable section 200 may include an opening configured to surround the monitoring device 201 and through which the monitoring device is visible. The removable section 200 may be configured to provide support and stability to the monitoring device 201.

Further, as seen in FIGS. 5D and 5E, the monitoring device 201 is engaged with the golf club head 101. The engagement of the monitoring device 201 with the golf club head 101 can be done in a variety of ways, e.g., mechanical fasteners, press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc. As seen in FIG. 5E, the golf club head 101 may include a recess configured to receive the monitoring device 201. For example, the recess may be configured to surround and engage the monitoring device 201 in order to support and stabilize the monitoring device 201. Further, it is noted that the golf club head 101 may include a structure configured to receive the removable section 200. The golf club head 101, the removable section 200 and the monitoring device 201 may be configured so as not to affect the aerodynamics of the golf club head 101 during a golf swing. For example, the golf club head 101, the removable section 200 and the monitoring device 201 may be configured such that when engaged, the golf club head 101 resembles the sole of the traditional wood-type golf club head with a relatively seamless surface.

FIG. 5F illustrates another illustrative embodiment of a golf club head 150 according to aspects of the disclosure. As seen in FIG. 5F, the golf club head 150 includes a U or V-shaped sole structure between the sole of the golf club head 150 is configured to receive the monitoring device 201. For example, the portion of the sole of the golf club head 101 between the legs of the U or V-shaped sole structure may include a recess configured to receive the monitoring device 201. The engagement of the monitoring device 201 with the golf club head 150 can be done in a variety of ways, such as in the above described embodiments.

FIG. 5G illustrates another illustrative embodiment of a golf club head 175 according to aspects of the disclosure. As seen in FIG. 5G, the golf club head 175 includes a recess in the rear of the golf club head 175. The recess may be configured to receive the monitoring device 201. For example, the portion of the rear of the golf club head 101 may include a smaller recess configured to receive the monitoring device 201. The engagement of the monitoring device 201 with the golf club head 175 can be done in a variety of ways, such as in the above described embodiments.

16

According to aspects of the disclosure, the monitoring device 201 may include an activation system. The activation system may be used for selectively activating the monitoring device 201 and/or at least some functions of the monitoring device 201 (e.g., data transmission/reception functions, data storage functions, data calculation functions, etc.). A wide variety of different activation systems may be used without departing from this disclosure.

For example, input from the activation system may be provided in any desired form or format without departing from the disclosure. As some more specific examples, if desired, the activation system may include a simple button, switch, or other input source that simply provides an activation or deactivation signal to the monitoring device 201 (e.g., a logical "1" or "0"). If desired, in at least some examples according to this disclosure, the activation system may activate the monitoring device 201, based on input it receives from the remote computer 400 (described below). For example a golfer may manually activate the monitoring device 201 by providing input (e.g., pressing a button) on the remote computer 400. Alternatively, the activation system may activate the monitoring device 201 automatically upon a certain action being performed. For example, when a golfer moves the club in which the monitoring device 201 is inserted, the activation system may induce the monitoring device 201 or its functions to operate. For example, if the monitoring device 201 includes an accelerometer and the golfer waggles the club (e.g., moves the club) over a pre-defined speed or length of time, the activation system may automatically activate the monitoring device 201 and/or at least some functions of the monitoring device 201 (e.g., data transmission/reception functions, data storage functions, data calculation functions, etc.). Further, the activation system may activate the monitoring device 201 when the golf club expands on impact (e.g., an impact with a golf ball). Further, it is noted that a monitoring device 201 may be configured to enter a sleep mode to conserve battery power if the monitoring device 201 is not used for a predetermined amount of time.

As discussed above, according to aspects of the disclosure, one of the sensors 202 may be an accelerometer. An accelerometer is a device used to measure acceleration. For example, an accelerometer may measure the magnitude and the direction of acceleration. An accelerometer according to aspects of the disclosure may include a three-axis accelerometer for measuring acceleration along three orthogonal axes. According to aspects of the disclosure, one or more accelerometers may be included in the golf club 100. For example, one or more accelerometers may be included in the monitoring device 201 or other a micro-electromechanical system (MEMS) configured to be engaged within the golf club head body 101 or shaft 103/grip 105.

According to aspects of the disclosure, the accelerometer may be configured to measure the velocity of the golf club 100 (e.g., club head 101, shaft 103, grip 105) during a golf swing, the acceleration of the club 100 (e.g., club head 101, shaft 103, grip 105) during a golf swing, etc.

According to aspects of the disclosure, one of the sensors 202 may be a magnetometer. A magnetometer is an instrument used to measure the strength and or the direction of a magnetic field around the instrument. According to aspects of the disclosure, one or more magnetometers may be included in the golf club 100. For example, one or more magnetometers may be included in the monitoring device 201 or other MEMS configured to be engaged within the golf club head body 101 or shaft 103/grip 105.

According to aspects of the disclosure, one or more magnetometers may also be used to determine golf swing parameters. As shown in FIG. 5H, the earth's magnetic field represented by vector **302** is relatively constant in the vicinity of a golfer. A magnetometer **304** resolves magnetic field vector **302** into three component vectors **306**, **308** and **310**. Magnetometer **304** may be implemented with an anisotropic magnetoresistive (AMR) device, a giant magnetoresistor (GMR) device or other suitable devices. As golf club head **101** moves, the magnetic field vector **302** is resolved into component vectors **306**, **308** and **310** such that the respective components have different magnitudes. According to aspects of the disclosure, the changing magnitudes of the component vectors may then be used to determine golf swing parameters.

For example, a club head face angle may be determined by first taking a reference measurement of the magnetic field before the back swing and then taking another measurement of the magnetic field just prior to impact. For example, the magnitude of component vectors **306**, **308** and **310** will have first values before the back swing and second values just prior to impact. The different component vector values can then be used to determine the face angle. If the magnetic field in the x-y plane is assumed to be 0.3 Gauss, the component X of the field with respect to component vector **308** (x axis) is determined by $X=0.3 \cos \theta$ and the component Y of the field with respect to component vector **310** (y axis) is determined by $Y=0.3 \sin \theta$.

A 1 degree difference would cause a change in the magnitudes of vector components **308** and **310** as follows:

$$\Delta X=0.3(\cos \theta-\cos(\theta+1))$$

$$\Delta Y=0.3(\sin \theta-\sin(\theta+1))$$

The smallest change that needs to be detected along each vector component may be determined by taking the derivative of each component and determining where the derivative crosses the 0 axis.

$$dX/d\theta=-0.3 \sin \theta=0 \text{ at } \theta=0 \text{ degrees}$$

$$dY/d\theta=0.3 \cos \theta=0 \text{ at } \theta=90 \text{ degrees}$$

The highest resolution in the x-component is needed when the angle rotates from 0 to 1 degree and corresponds to 45.7 μ G. The same resolution is needed when the y-component rotates from 89 to 90 degrees.

Other golf swing parameters may be determined by magnetometers. For example, according to aspects of the disclosure, swing tempo may be determined by using vector component **306** (z axis) as a tilt sensor. A reference measurement of vector component **306** may be recorded before the back swing. The period required for the club head to return to a position such that the vector component **306** returns to the measured reference value corresponds to the swing tempo. In an alternative embodiment, velocity information may also be just to determine impact time and the resulting swing tempo.

Further, several different measurements may be used to determine the swing path. For example, FIG. 5I shows a diagram of how velocity, time and orientation measurements may be used to determine the swing path. For example, velocity and time information measurements may be used to determine a first locus of points **310**. Next, an orientation measurement may then be used to determine a first location **312** along first locus of points **310**. The process of identifying club locations may be repeated several times to determine a swing path **314**. In one embodiment, measurements are taken at least 1 kHz during a swing. Swing path **314** may be determined relative to a reference orientation and impact location.

According to aspects of the disclosure, one of the sensors **202** may be a gyroscope. A gyroscope is a device used to measure orientation and rotation. For example, a gyroscope may measure orientation based on the principles of the conservation of angular momentum. Further, according to aspects of the disclosure, a three-axis gyroscope may be used to increase accuracy. When combined with an accelerometer, the combination of the gyroscope and the accelerometer may provide a more accurate indication of movement within a 3-D space when compare to an accelerometer alone. According to aspects of the disclosure, one or more gyroscopes may be included in the golf club **100**. For example, one or more gyroscopes may be included in the monitoring device **201** or other MEMS configured to be engaged within the golf club head body **101** or shaft **103**/grip **105**.

FIG. 5J shows an embodiment in which a gyroscope **320** is placed within a golf club head **101** to measure golf swing parameters. Gyroscope **320** may be implemented with a micro-electromechanical system (MEMS) or other device or module capable of fitting within golf club head **101**. A three-axis gyroscope may be used to increase accuracy.

According to aspects of the disclosure, the gyroscope **320** may be configured to determine golf swing parameters by assuming that the point of rotation is a golfer's shoulders. Club head velocity may be determined by an accelerometer (such as described above) that is part of the same MEMS, an external accelerometer or some other device. For golf swing parameter determination purposes, in the proximity of a golf ball the movement of golf club head **101** may be modeled as an object moving on the surface of a sphere. The sphere has a radius equal to the length of the club plus the length of the golfer's arms. In one embodiment, a standard radius of 62.5 inches is used. In other embodiments, a golfer may provide his or her arm length and/or club length for more accurate determinations.

The face angle of golf club head **101** may be determined as a function of the shaft rotation rate. The shaft rotation rate may be determined by gyroscope **320**. FIG. 5K illustrates one exemplary method of determining the face angle with the use of a gyroscope. First, in step **330** the start of the back swing is determined. A velocity sensor may be used to determine the start of the back swing. In step **340** impact of the golf club with a ball is detected. Step **350** may be performed by the impact sensors described above. The shaft rotational rate as a function of time may be determined by gyroscope **320** in step **350**. Step **350** preferably includes determining the shaft rotational rate from at least the start in step **330** until at least the impact in step **340**. Next, in step **360**, the golf club shaft rotational rate is integrated with respect to time from the start in step **330** until the impact in step **340** in accordance with the following formula:

$$\text{Face Angle Change} = \int_{\text{BackswingStart}}^{\text{Impact}} \text{Shaft Rotation Rate } (t) dt$$

The face angle is then determined by adding the face angle change to the original face angle in step **370**.

Club head speed may be determined as a function of the radius (arm length plus club length) and angular velocity. In particular, the club head speed is the product of the radius and the angular velocity of golf club head **101**.

Swing tempo may be determined by first determining when the angular rate is zero and begins to increase at the start of the back swing. The time of impact may then be determined by a spike in the angular rate that accompanies the impact or from one or more other sensors, such as an accelerometer or impact sensor.

19

Rotational velocities may also be used to determine the swing path. In one embodiment in which gyroscope **320** is implemented with a three axis gyroscope and in which the z-axis is used to determine changes in face angle, the y-axis is used to determine motion in a target reference plane and the x-axis is used to determine motion parallel to the target reference plane, the swing path may be estimated by the following formula:

$$\text{SwingPath} = \text{atan}\left(\frac{x\text{AxisRotationalVelocity}}{y\text{AxisRotationalVelocity}}\right)$$

Therefore, as demonstrated above, the monitoring device can determine various aspects of a golfer's golf swing, including: the velocity of the golf club (or club head) during a golf swing, the acceleration of the club (or club head) during a golf swing, the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), swing tempo, the impact of the ball with the golf club head during a golf swing, etc.

As described above, the golf club **100** may include a transmitter **203**. Further, it is noted that while a transmitter is the depicted embodiment, according to particular embodiments of the disclosure, the transmitter **203** may be a transceiver which is capable of receiving data as well as transmitting data. Data determined from each of the one or more sensors **202** may be communicated to the transmitter **203**. For example, the one or more sensors **202** may be electrically connected to transmitter **203**. Alternatively, data may be communicated wirelessly from the one or more sensors **201** to the transmitter **203**. Regardless of how the data is communicated from the one or more sensors **202** to the transmitter **203**, the transmitter **203** may be configured to transmit the data determined by the one or more sensors **202** to a remote computer system **400** (e.g., a portable computer device with a receiver configured to receive the data from the transmitter **203**). While not shown, according to aspects of the disclosure, the monitoring device **201** may include a memory. The memory may be configured to store data from the one or more sensors **202**. More specifically, the memory may store data while the golfing activity takes place and save it for later transmission to the remote computer system **400** (as discussed below).

While the data may be transmitted from the transmitter **202** in any desired manner, wireless type transmissions may be used in embodiments of the disclosure. Any desired wireless transmission system and method may be used without departing from the scope of the disclosure, including the use of any desired wireless data transmission format or protocol, including the transmission systems and protocols currently in use in NIKE+™ athletic performance monitoring systems. According to example aspects of the disclosure, the transmitter **203** may be configured to transmit data using a variety of conventional protocols. For example, the monitoring device **201** may be configured to communicate using the Bluetooth wireless communication protocol, so that it can be employed with Bluetooth-capable mobile telephones, personal digital assistants, watches or personal computers. Further, other methods of transmitting may be used as well, such as Bluetooth2, RFID, infrared transmission, cellular transmissions, etc.

Further, according to example aspects of the disclosure, the transmitter **203** may be configured to transmit data via an antenna. For example, in one embodiment of the invention, a ferrule is used as an antenna. The ferrule may be formed of a metal material or other type of antenna material. In another embodiment, shaft **103** may function as an antenna. An

20

antenna may also be plated onto shaft **103**, embedded under grip **105** or placed in any other location that does not interfere with a golf swing. The monitoring device **201** and the golf club head **101** may be configured such that a connection is made between the transmitter **203** and the antenna when the monitoring device **201** is engaged with the golf club head **101**.

While wireless communication between the monitoring device **201** and the remote computer system **400** is described above, it is noted that any desired manner of communicating between the monitoring device **201** and the remote computer system **400** may be used without departing from the scope of the disclosure, including wired connections. For example, if desired, monitoring device **201** may include its own data storage system for storing data from the one or more sensors **202**. Further, the monitoring device **201** may be configured to be engaged with the remote computer system **400** in order to transmit data to the remote computer **400**. For example, monitoring device **201** may include an interface (e.g., a USB connection) configured to engage with a port of the remote computer system **400** in order to transmit data to the remote computer **400**.

According to aspects of the disclosure, data collected from the sensors **202** may be stored during a practice session or a round of golf. Then, at a convenient time, such as after the practice session or round of golf, the golfer may disengage the monitoring device **201** from the golf club head and engage it with the remote computer system **400** in order to transmit the data to the remote computer system **400**. Any type of connection system may be used without departing from the scope of the disclosure, including a wireless connection, a hardwired connection, connection via an input port (such as a USB port, or the like), etc.

Other data storage and/or transmission arrangements also are possible without departing from the scope of the invention. For example, any desired way of placing data derived from the physical data from the monitoring device **201** in the proper form or format for communication to the remote computer system **400** may be provided without departing from the invention. For example, as discussed above, the monitoring device **201** may include a receiver (e.g., the transmitter **203** may be a transceiver) which determines whether a transmission from transmitter **203** has been or is being received by the remote computer **400**. If the transmission from transmitter **203** is not received by the remote computer **400**, the monitoring device **201** may be configured to store the data on the memory (e.g., if the remote computer system **400** is not in range or is turned off). In this way, data collected by the sensors **202** will be stored locally so that it will not be lost and can be downloaded later to the remote computer system **400**.

The remote computer system **400** may be any desired type of computer system, at any desired location, without departing from the scope of the disclosure.

An example remote computer **400** may include a processor system (which may include one or more processors or micro-processors, which may be configured to execute software instructions), a memory, a power supply, an output device, other user input devices, and data transmission/reception system (e.g., a wireless transceiver). The processor system and the memory may be connected, either directly or indirectly, through a bus or alternate communication structure to one or more peripheral devices. For example, the processor system or the memory may be directly or indirectly connected to additional memory storage, such as a hard disk drive, a removable magnetic disk drive, an optical disk drive, and a flash memory card. The processor system and the memory also may be directly or indirectly connected to one or more input devices and one or more output devices. The input

21

devices may include, for example, a keyboard, touch screen, a remote control pad, a pointing device (such as a mouse, touchpad, stylus, trackball, or joystick), a scanner, a camera or a microphone. The output devices may include, for example, a monitor display, speakers, etc.

Still further, the processor system may be directly or indirectly connected to one or more network interfaces for communicating with a network. This type of network interface, also sometimes referred to as a network adapter or network interface card (NIC), translates data and control signals from the processor system into network messages according to one or more communication protocols, such as the Transmission Control Protocol (TCP), the Internet Protocol (IP), and the User Datagram Protocol (UDP). These protocols are well known in the art, and thus will not be discussed here in more detail. The data transmission/reception system may employ any suitable connection agent for connecting to a network, including, for example, a wireless transceiver, a power line adapter, a modem, or an Ethernet connection.

It should be appreciated that, in addition to the input, output and storage peripheral devices specifically listed above, the computing device may be connected to a variety of other peripheral devices, including some that may perform input, output and storage functions, or some combination thereof.

Of course, still other peripheral devices may be included with or otherwise connected to the remote computer system 400, as is well known in the art. In some cases, a peripheral device may be permanently or semi-permanently connected to the processor system. For example, as with many computers, the processor system, the hard disk drive, the removable optical disk drive and a display are semi-permanently encased in a single housing. Still other peripheral devices may be removably connected to the remote computer system. The remote computer system may include, for example, one or more communication ports through which a peripheral device can be connected to the processor unit (either directly or indirectly through the bus). These communication ports may thus include a parallel bus port or a serial bus port, such as a serial bus port using the Universal Serial Bus (USB) standard or the IEEE 1394 High Speed Serial Bus standard (e.g., a Firewire port). Alternately or additionally, the remote computer system 400 may include a wireless data "port," such as a Bluetooth interface, a Wi-Fi interface, an infrared data port, or the like.

According to aspects of the disclosure, the transmission/reception system may be configured for communication with the transmitter 203 of the monitoring device via the above described transmission/reception systems and/or through any type of known electronic communications. If desired, in accordance with at least some examples of this invention, the remote computer system 400 may include a display and/or a user input system, such as one or more rotary input devices, switches, buttons, mouse or trackball elements, touch screens, or the like, or some combination thereof.

The display may be employed to show, for example, information relating to the golfing information signals being received by the remote computer system 400, etc. The user input system may be employed, for example: to control one or more aspects of the processing of the input data received, to control input data receipt (e.g., timing, types of information received, on-demand data requests, etc.), to control data output, to control the monitoring device, etc. Alternatively or additionally, if desired, the input system on the remote computer system 400 (e.g., buttons, a touch screen, a digitizer/stylus based input, a rotary input device, a trackball or roller ball, a mouse, etc.), may be used to provide user input data to the monitoring device 201. As still another example, if

22

desired, a voice input system may be provided with the interface device and/or the remote computer system 400, e.g., to enable user input via voice commands. Any other desired type of user input system, for control of any system elements and/or for any purpose, may be provided without departing from the scope of the disclosure. For example, the remote computer system 400 may include additional input and/or output elements, e.g., such as ports e.g., for headphones (or other audio output), power supplies, wireless communications, infrared input, microphone input, or other devices.

According to aspects of the disclosure, the remote computer system 400 may be, for example, portable audio and/or video players, cellular telephones, personal digital assistants, pagers, beepers, palm top computers, laptop computers, desktop computers, servers, or any type of computer controlled device, optionally a computer controlled device that generates or displays a human perceptible output and/or interface.

FIG. 6 illustrates one example of a remote computer system 400 that may be employed according to various examples of the invention to measure various information corresponding to a golfer's abilities and game. As shown in this figure, the remote computer system 400 may be a cellular telephone (e.g., a Bluetooth enabled cellular telephone, such as an IPHONE®, BLACKBERRY®, DROID®, or other smart phone, etc.). FIG. 6 also illustrates a schematic rendering of the remote computer system 400. As seen in FIG. 6, the cellular telephone may include a processor system 402, a memory 404, a power supply 406, and a data transmission/reception system (e.g., a wireless receiver or transceiver) 408. The memory 404 may include both a read-only memory (ROM) and a random access memory (RAM). As will be appreciated by those of ordinary skill in the art, both the read-only memory (ROM) and the random access memory (RAM) may store software instructions for execution by the processor system 400. The data transmission/reception system 408 may be configured to receive, from the transmitter 203, data that corresponds to the measured golfing parameter. Further, as shown, the data transmission/reception system 408 may be configured to provide the received data to the processor 402.

For example, according to aspects of the disclosure, the data transmission/reception system 408 receives the signals (e.g., processed or unprocessed signals) transmitted by the transmitter 203 in the monitoring device 201. The data transmission/reception system 408 may be configured to relay the signals to the processor 402, which processes the signals further. Like the processor 204, the processor 402 may perform any desired operation on the processed signals, such as curve smoothing, noise filtering, outlier removal, amplification, summation, integration, or the like.

According to aspects of the disclosure, the processor 402 may initially store the processed signals in a memory 404. Further, with some implementations of the disclosure, the processor 402 may operate on the processed signals provided by the monitoring device 201 to generate a set of data corresponding to the golf activity performed by the golfer. For example, if the monitoring device 201 includes accelerometers for measuring the acceleration of the golf club head 101, the processor 402 may analyze the signals from the monitoring device 201 to generate a set of data describing the acceleration of the golf club head 101 at specific instances during the golf swing. It is noted that the transmitted data set may also include a time value associated with each speed value.

Once the processor 402 has generated a set of data from the information provided by the monitoring device 201, the processor 402 may store the data set in the memory 404. As will be discussed in more detail below, when the remote computer

23

system **400** subsequently is connected to a second computing device **500** implementing a golf information collection tool, the computing unit **404** may be configured download the data to a display configuration tool.

It is noted that the above described monitoring system (which includes the monitoring device **201** and the remote computer system **400**) may be configured to be active, real-time transmitting systems that provides data to the remote computer system **400** as the golf activity is taking place. Optionally, if desired, the remote computer system **400** may be configured to provide the golfer with real-time performance feedback (e.g., velocity of the golf club head, acceleration of the golf club head, the impact position of the golf ball on the ball striking face, path of the swing path of a particular swing, face angle of the ball striking face of the club head throughout the swing (e.g., during impact), etc.) while the golfing performance is taking place. The real-time performance feedback could be in the form of an audio or visual message. For example, if desired, the remote computer system **400** may be configured to provide an output based on the received data from the sensors **202**, wherein the output provides feedback to the golfer in real time, such as when the athletic performance is taking place. For example, the output may be as a visual display such as an alphanumeric, video, or textual output. Additionally, or alternatively, the output may be an audio output, such as an audio tone, message, etc.

According to example aspects of the disclosure, the output may include a visual display provided on the display screen of the cellular telephone, wherein the visual display includes one of: an illustration of a swing path of a golf swing, a numeric value of a maximum acceleration of the golf club head **101** during a golf swing (and, if desired, at a particular time relative to the duration of the golf swing when that maximum acceleration was reached), a numeric value of the acceleration or velocity of the golf club head **101** at a particular time relative to the duration of the golf swing (e.g., the acceleration or velocity of the golf club head **101** during impact or on the backswing), the angle of the ball striking face **107** at a particular time relative to the duration of the golf swing (e.g., the angle of the ball striking face **107** during impact; this may be represented with characters (e.g., "Open Face", "Closed Face", etc.) or graphically (e.g., pictures of a golf club head with an "Open Face", "Closed Face", etc.), the impact location of the golf ball on ball striking face, messages (e.g., "Great Shot!" or "You Hit a Slice"), etc. Similarly, audio messages may be employed as well. For example, recorded messages (e.g., recorded by well-known golfers) may be stored in the memory and played based on predefined circumstances being achieved.

It should be appreciated that, while some specific embodiments of the invention described above relate to a cellular telephone, alternate examples of the disclosure may be implemented using other portable electronic device. For example, with some implementations of the invention, the monitoring device **201** may be used in conjunction with a digital music or video player, a watch, a personal digital assistant, another type of music player (such as a compact disc or satellite radio music player), a portable computer, or any other desired electronic device. For example, remote computer system **400** may be in the form of a wrist band, such as a watch or other wrist borne data receiving device, or an arm band, or other apparel. Therefore, it is understood that while several examples of the remote computer system **400** are described above, the remote computer system **400** may take on a variety of different forms without departing from the scope of the disclosure.

It is noted, that if the remote computer system **400** does not have an internal electronic interface device (e.g., if the remote

24

computer **400** is a digital music player, such as an iPod®, the data transmission/reception system **408** (e.g., the receiver or transceiver) may be a separate device which is configured to engage with the remote computer system **400**. For example, the data transmission/reception system **408** may include a connector system that physically plugs into and connects with a conventional input port provided on remote computer system **400**. The input port into which the connector system of the data transmission/reception system **408** connects may be any desired type of input port for transferring data, such as a parallel data port, a serial data port, an earphone or microphone jack, etc. The connector system may include any suitable connecting devices, such as wires, pins, electrical connectors, and the like, so as to make an electrical connection or other suitable connection with corresponding elements provided in the input port of the remote computer system **400** (e.g., to allow electronic and/or data communications between the remote computer system and the electronic interface device). If necessary or desired, additional securing elements may be provided to securely connect the interface device to the remote computer system **400**, such as straps, hooks, buckles, clips, clamps, clasps, retaining elements, mechanical connectors, and the like. In this way, when the external data transmission/reception system **408** is engaged with the remote computer system **400**, the remote computer system **400** may communicate wirelessly with the monitoring device **201**.

FIGS. 7A and 7B show an illustrative transmission from the monitoring device **201** to the remote computer system **400** according to aspects of the disclosure. Specifically, FIG. 7B illustrates the transmitter (or transceiver) **203** of the monitoring device **201** communicating with the transmission reception system **408** of the remote computer **400**. As described above, in embodiments in which the monitoring device **201** includes a transceiver **203**, the communication may be two-way, i.e., from the transceiver **203** to the transmission reception system **408** of the remote computer **400** and, also, from the transmission reception system **408** to the transceiver **203**. However, in embodiments in which the monitoring device **201** includes a transmitter **203**, the communication will be one way, i.e., from the transmitter **203** to the transmission reception system **408** of the remote computer **400**.

According to aspects of the disclosure, the determination of data by the monitoring device **201** and the transmission of data between the monitoring device **201** and the remote computer **400** may be performed in a variety of ways.

For example, according to a first method in which the monitoring device **201** determines data and then communicates the data to the remote computer **400**, the monitoring device **201** includes sensors **202** (e.g., one or more accelerometers, one or more gyroscopes, and/or one or more magnetometers), a transmission module **203** (e.g., a transmitter or transceiver configured to transmit/receive data wirelessly (e.g., through RF, Bluetooth, Bluetooth2, etc.)), a processor **204** (e.g., microprocessor) and a power source **206** (e.g., a battery). Further, according to such a method, data determined by the monitoring unit is transmitted to the remote computer **400** (e.g., a portable telephone, a computer (e.g., a PC), a sport tablet, an electronic range finder, such as SKY CADDIE® available from SKY GOLF®, etc. Further, according to such a method, data may be determined by the sensors **202**. Once the data is determined by the sensors, the processor **204** in the monitoring device **201** may use the data to calculate golf metrics or variables (e.g., a swing path representation as discussed). According to aspects of the method, the golf metrics or variables may be transmitted wirelessly via the transmission module **203** to the remote computer **400**.

25

Alternatively, according to other aspects of the method, the golf metrics or variables may be stored in a memory in the monitoring device 201. Afterwards, (e.g., after a number of golf shots), the golf metrics or variables may be transmitted wirelessly via the transmission module 203 to the remote computer 400. According to aspects of this method, the remote computer 400 may be configured to store the golf metrics or variables, communicate the golf metrics or variables to the user, e.g., through video or audio means, and/or further transmit the golf metrics or variables to other devices.

According to another method in which the monitoring device 201 determines data and then communicates the data to the remote computer 400, the monitoring device 201 includes sensors 202 (e.g., one or more accelerometers, one or more gyroscopes, and/or one or more magnetometers), a transmission module 203 (e.g., a transmitter or transceiver configured to transmit/receive data wirelessly (e.g., through RF, Bluetooth, Bluetooth2, etc.)), a processor 204 (e.g., a microprocessor) and a power source 206 (e.g., a battery). Further, according to such a method, data determined by the monitoring unit is transmitted to the remote computer 400 (e.g., a portable telephone, a computer (e.g., a PC), a sport tablet, an electronic range finder, such as SKY CADDIE® available from SKY GOLF®, etc. Further, according to such a method, data may be determined by the sensors 202. Once the data is determined by the sensors, the processor 204 in the monitoring device 201 may use the data to calculate kinematics (e.g., computed acceleration data). According to aspects of the method, the kinematics may be transmitted wirelessly via the transmission module 203 to the remote computer 400. For example, the kinematics may be transmitted during each golf shot or after each golf shot. Alternatively, according to other aspects of the method, the kinematics may be stored in a memory in the monitoring device 201. Afterwards, (e.g., after a number of golf shots or whenever the golfer desires), the kinematics may be transmitted wirelessly via the transmission module 203 to the remote computer 400. Regardless of when the kinematics are transmitted from the monitoring device 201 to the remote computer 400, once the kinematics are received by the remote computer 400 (e.g., via the transmission reception system 408), the remote computer 400 may be configured to process the kinematics to calculate golf metrics or variables. According to aspects of this method, the remote computer 400 may be configured to store the golf metrics or variables, communicate the golf metrics or variables to the user, e.g., through video or audio means, and/or further transmit the golf metrics or variables to other devices.

According to another method in which the monitoring device 201 determines data and then communicates the data to the remote computer 400, the monitoring device 201 includes sensors 202 (e.g., one or more accelerometers, one or more gyroscopes, and/or one or more magnetometers), a transmission module 203 (e.g., a transmitter or transceiver configured to transmit/receive data wirelessly (e.g., through RF, Bluetooth, Bluetooth2, etc.)), a processor 204 (e.g., a microprocessor) and a power source 206 (e.g., a battery). Further, according to such a method, data determined by the monitoring unit is transmitted to the remote computer 400 (e.g., a portable telephone, a computer (e.g., a PC), a sport tablet, an electronic range finder, such as SKY CADDIE® available from SKY GOLF®, etc. Further, according to such a method, data may be determined by the sensors 202. Once the data is determined by the sensors, the processor 204 in the monitoring device 201 may use the data to calculate individual processed sensor signals (e.g., processed electrical signals from the sensors). According to aspects of the method, the individual processed sensor signals may be transmitted

26

wirelessly via the transmission module 203 to the remote computer 400. For example, the individual processed sensor signals may be transmitted during each golf shot or after each golf shot. Alternatively, according to other aspects of the method, the individual processed sensor signals may be stored in a memory in the monitoring device 201. Afterwards, (e.g., after a number of golf shots or whenever the golfer desires), the individual processed sensor signals may be transmitted wirelessly via the transmission module 203 to the remote computer 400. Regardless of when the individual processed sensor signals are transmitted from the monitoring device 201 to the remote computer 400, once the individual processed sensor signals are received by the remote computer 400 (e.g., via the transmission reception system 408), the remote computer 400 may be configured to process the individual processed sensor signals to calculate golf metrics or variables. According to aspects of this method, the remote computer 400 may be configured to store the golf metrics or variables, communicate the golf metrics or variables to the user, e.g., through video or audio means, and/or further transmit the golf metrics or variables to other devices.

According to another method in which the monitoring device 201 determines data and then communicates the data to the remote computer 400, the monitoring device 201 includes sensors 202 (e.g., one or more accelerometers, one or more gyroscopes, and/or one or more magnetometers), a transmission module 203 (e.g., a transmitter or transceiver configured to transmit/receive data wirelessly (e.g., through RF, Bluetooth, Bluetooth2, etc.)), a power source 206 (e.g., a battery). Further, according to such a method, data determined by the monitoring unit 201 is transmitted to the remote computer 400 (e.g., a portable telephone, a computer (e.g., a PC), a sport tablet, an electronic range finder, such as SKY CADDIE® available from SKY GOLF®, etc. Further, according to such a method, data may be determined by the sensors 202. Once the data is determined by the sensors, data may be transmitted wirelessly via the transmission module 203 to the remote computer 400. For example, the data may be transmitted to the remote computer 400 without being processed (e.g., raw data such as electrical signals from the sensors). According to such a method, the unprocessed data may be transmitted during each golf shot or after each golf shot. Alternatively, according to other aspects of the method, the unprocessed data may be stored in a memory in the monitoring device 201. Afterwards, (e.g., after a number of golf shots or whenever the golfer desires), the unprocessed data may be transmitted wirelessly via the transmission module 203 to the remote computer 400. Regardless of when the unprocessed data is transmitted from the monitoring device 201 to the remote computer 400, once the unprocessed data is received by the remote computer 400 (e.g., via the transmission reception system 408), the remote computer 400 may be configured to process the unprocessed data to calculate golf metrics or variables. According to aspects of this method, the remote computer 400 may be configured to store the golf metrics or variables, communicate the golf metrics or variables to the user, e.g., through video or audio means, and/or further transmit the golf metrics or variables to other devices.

While the above methods described various methods for determining data by the monitoring device 201 and the communicating the data between the monitoring device 201 and the remote computer 400, they should not be construed as limiting. In contrast, they are provided to assist the reader with understanding the disclosure and other methods for determining data by the monitoring device 201 and the com-

municating the data between the monitoring device **201** and the remote computer **400** may be considered within the scope of the disclosure.

It also should be appreciated that, while specific examples of monitoring devices **201** have been described above for ease of understanding, any type of desired monitoring device **201** can be employed with various embodiments of the disclosure. For example, according to aspects of the disclosure, the monitoring device **201** may be configured to engage with the shaft **103** of the golf club **100**. For example, the monitoring device **201** may be configured with a shape and size such that the monitoring device **201** is able to be positioned within the grip **105** of the golf club.

For example, according to aspects of the disclosure, the grip **105** may be configured to receive a removable section or cartridge **200**. Further, the removable section **200** may be configured to receive the monitoring device **201**. FIG. **8** shows an illustrative embodiment of such aspects of the disclosure.

As seen in FIG. **8**, the removable section **200** may include a circular portion which forms the top of the shaft and, also, an elongated portion configured to house the monitoring device **201**. According to aspects of the disclosure, the elongated portion of the removable section **200** may include guides to aid in positioning and securing the monitoring device **201** within the removable section **200**. It is noted that the removable section **200** may be configured to secure the monitoring device **201** in such a way that the monitoring device **201** does not move within the removable section **200**. For example, the removable section **200** may be configured to engage with the monitoring device **201** (e.g., a compartment which includes the exterior of the monitoring device **201**) via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), mechanical fasteners, etc. For example, the elongate portion may include a first arched end configured to engage a first rounded end of the compartment, a second arched end configured to engage a second rounded end of the compartment and a back portion which extends between the first arched portion and the second arched portion and is configured to engage a side of the compartment. In this way, the removable section **200** may be configured to support and stabilize the monitoring device **201**. For example, the elongate portion may be configured to secure the compartment which may be rectangular with first and second rounded ends and have a length in the range of 1.0-1.5 inches, a width of 0.4-1.0 inches and thickness of 0.2-0.45 inches. According to aspects of the disclosure, the removable section **200** may be made of plastic. It is noted that other materials, such as rubber, or combinations thereof may be used as well.

The removable section or cartridge **200** may be configured to be engaged with the grip **105** in a variety of ways. For example, the grip **105** may be configured with an opening at its terminal end that is configured to receive the removable section **200**. Further, the grip **105** may be configured with guides within the interior of the grip **105** that guide the removable section during insertion into the grip **105**. Also, the grip may be configured with a locking mechanism, such as threads which line the interior of the grip **105**. The removable section **200** may include a corresponding structure through which the removable section **200** is engaged and locked with the grip **105** upon twisting the removable section **200** into the grip **105**. Alternatively, the removable section **200** may be configured to engage with the grip **105** via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), other mechanical fasteners, etc.

FIG. **8A** illustrates an exploded view of another embodiment of a removable section or cartridge according to aspects

of the disclosure. For example, as seen in FIG. **8A**, the cartridge **200** may be configured to fit within a top portion of the grip **105**. The top portion of the grip **105** may include a first portion which is configured to receive the cartridge supporting the monitoring device **201** and a second portion configured to engage with the interior of the shaft **103** of the golf club. Hence, the top portion of the grip **105** may be configured to removably fit within the golf club shaft **103**. The removable top portion of the grip and the cartridge **200** may be configured to be attached to each other. For example, as seen in FIG. **8A**, the cartridge **200** and the top portion of the grip **105** may be configured to be fastened together by a threaded fastener. For example, the circular portion of the removable section **200** may include an orifice configured to receive a threaded fastener and configured to align with a second orifice in the top portion of the grip **105** configured to receive the threaded fastener. Further, as seen in FIG. **8A**, the first portion of the grip **105** configured to receive the cartridge supporting the monitoring device **201** may be configured to surround and securely hold the cartridge **200** and thereby further protect the monitoring device **201** from damage due to impact or the elements. It is understood that the monitoring device **201** held in the cartridge **200** can take any of the various exemplary embodiments as described herein. The cartridge **200** includes holder members that cooperatively engage the monitoring device **201** in an interference fit in an exemplary embodiment. The cartridge **200** fits flush in the end of the grip portion of the golf club and may include a screw fastener. Other fastening mechanisms such as snap-fitting configurations or interference fittings as well as other mechanical configurations may also be included.

According to other aspects of the disclosure, the grip **105** may be configured to receive and secure the monitoring device **201** directly, without the inclusion of a separate removable section or cartridge **200**. FIG. **9** shows an illustrative embodiment of such aspects of the disclosure.

The monitoring device **201** may be configured to be engaged with the grip **105** in a variety of ways. For example, the grip **105** may be configured with an opening at its terminal end that is configured to receive the monitoring device **201**. For example, as seen in FIG. **9**, the grip **105** may include a slit that is configured to receive the monitoring device **201** when the monitoring device **201** is inserted into the grip along the monitoring device's longitudinal axis. The slit may be configured to provide a tight interference fit with the monitoring device **201**. It is noted that in this way, the grip **105** may be configured to secure the monitoring device **201** such that the monitoring device **201** does not move within the grip **105**. In this way, the removable section **200** may be configured to support and stabilize to the monitoring device **201**.

Further, the grip **105** may be configured with guides within the interior of the grip **105** that guide the monitoring device **201** during insertion into the grip **105**. Also, the grip may be configured with a locking mechanism, such as a cover which includes flaps through which the monitoring device is inserted. It is noted that monitoring device **201** may be configured to engage with the grip **105** via other methods as well, including snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), other mechanical fasteners, etc.

While, the engagement of the monitoring device **201** and the removable section **200** with the shaft is described above with respect to the grip **105**, it is noted that, alternatively, the shaft **103** may be configured to receive the monitoring device **201** and/or the removable section **200** at the butt end of the shaft **103**. Further, the interior of the shaft **103** may be con-

figured to position the monitoring device **201** at any point along the length of the shaft **103** (e.g., at the butt end, the grip end, the center, etc.).

According to aspects of the disclosure, the grip end of the shaft **103** (or a portion thereof) may be removable to allow the monitoring device **201** to be inserted. Additionally, or alternatively, as described above, the butt end of the shaft may be removably engaged with the golf club head **101**. Hence, the monitoring device **201** may be inserted into that end of the shaft **103** as well. Further, it is noted that, if desired, more than one monitoring device **201** may be inserted into the shaft **103** in order to measure various different locations or different portions of the shaft **103** during the golf swing.

According to aspects of the disclosure, golf club **101** may include a monitoring device **201** in both the shaft **103** and in the golf club head **101**. For example, the golf club **101** may include two monitoring devices **201**, such as a first monitoring device **201** which is positioned in the grip **105** (such as shown in FIG. **8**) and a second monitoring device **201** which is positioned in the golf club head **101** such as shown in FIG. **5D**. In such embodiments, wherein the golf club **101** includes a first monitoring device **201** positioned in the grip **105** and a second monitoring device **201** positioned in the golf club head **101**, data may be collected from both monitoring devices and used together in one of the manners described above with regard to providing golf metrics and variables. For example, the first monitoring device **201** positioned in the grip **105** and a second monitoring device **201** positioned in the golf club head **101** may be configured to collect data related to different aspects of a golf swing. For example, first monitoring device **201** positioned in the grip **105** may collect data regarding acceleration while the second monitoring device **201** positioned in the golf club head **101** may collect data regarding the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), or the impact of the ball with the golf club head during a golf swing. Such data may be combined in calculating the golf metrics in order to provide more detailed feedback to the golfer. It is noted that according to other aspects of the disclosure, the first monitoring device **201** positioned in the grip **105** and a second monitoring device **201** positioned in the golf club head **101** may be configured to collect data related to the same or similar aspects of a golf swing. For example, both the first and second monitoring devices **201** may be configured to collect data related to acceleration. Again, such data may be combined in calculating the golf metrics in order to provide more detailed feedback to the golfer. Such golf metrics that may be determined by one or more of the monitoring devices may include bending, torsion, deflection, kick, etc. of the shaft during a golf swing.

Regardless of how many monitoring devices **201** are included in the golf club and the positioning of the monitoring devices **201** on or within the golf club, according to aspects of the disclosure, a first monitoring device **201** may be configured to be a “master” monitoring device **201** and the other monitoring devices **201** may be configured to communicate data to the “master” monitoring device **201**. Further, the “master” monitoring device **201** may be configured to receive, from the other monitoring devices **201**, the data determined by such monitoring devices **201** and perform any necessary calculations, comparisons, etc. as described in this disclosure and/or transmit the data to the remote computer **400**.

The “master” monitoring device **201** and other monitoring devices may communicate wirelessly (e.g., through RF, Bluetooth, Bluetooth2, etc.) or may be hardwired to each other. Although it is noted that if the “master” monitoring device

201 and other monitoring devices communicate via wiring, the wiring may be removably connected via ports or other interfaces. Further, according to aspects of the disclosure, the “master” monitoring device **201** and other monitoring devices may not have the same configuration. For example, the “master” monitoring device **201** may include a processor **204** such as a programmable microprocessor, a purpose-specific circuit device (e.g., an ASIC), etc. Further, the “master” monitoring device **201** may also include sensors **202**, a transmitter **203** (or transceiver) configured to transmit the processed signals to a remote computer system **400**, a power supply **206**, and a memory (e.g., a flash memory). According to aspects of the disclosure, the other monitoring devices **201** may or may not have the same structure as the “master” monitoring device **201**. For example, the other monitoring devices **201** may not include the same processor **204** which performs any necessary calculations, comparisons, etc. as described in this disclosure. Further, other monitoring devices **201** may not include the same transmitter **203** (or transceiver) configured to transmit the data to the remote computer **400**. In some embodiments, the other monitoring devices **201** may be configured to submit the “raw” data from the sensors **202** to the “master” monitoring device **201**, such as by wireless transmission, without being processed.

For example, according to an illustrative embodiment, a “master” monitoring device **201** such as described above may be included in the shaft **103** in a first position (e.g., the grip) and another monitoring device **201** such as one of the other monitoring devices **201** described above may be included at a second position in the shaft **103** which is different from the first position. Additionally, monitoring device **201** such as one of the other monitoring devices **201** described above may be included at other locations in the golf club **100** (e.g., in the golf club head **101** or at other positions in the shaft **103**). It is further understood that the exemplary embodiments of the golf club **100** described herein can also cooperate with golf balls having various types of sensors operably associated therewith.

Further, it is noted that, if desired, strain gauges may be used in conjunction with the monitoring device **201** in order to provide measurements regarding the axial strain, bending moments or other characteristics of the shaft **103** or other features of the golf swing. Such data may be combined in calculating the golf metrics in order to provide more detailed feedback to the golfer. Such strain gauges are known in the art and will not be elaborated on here for the sake of brevity.

As discussed above, according to particular embodiments of the disclosure, the monitoring device **201** may also be configured to identify the particular golf club in which the monitoring device **201** is engaged. For example, golf club **100** may include a chip (e.g., an RFID chip) which communicates with the monitoring device **201** when the cartridge **200** or the monitoring device **201** is engaged with the golf club **100**. This could be through direct electrical connection, wireless transmission, etc. The chip may be configured to indicate to the monitoring device **201** with which golf club the monitoring device **201** is engaged. Of course, other methods of identification may be used as well. For example, prior to use, the monitoring device **201** may be programmed such that it reflects the golf club with which it will be used prior to even being engaged with the golf club head **202**.

Regardless of how the monitoring device **201** is aware of the particular golf club with which it is engaged, according to aspects of the disclosure, such information may be incorporated with the data collected from the sensors **202** of the monitoring device **201**. For example, the characteristics of a particular golf shot (e.g., the velocity of the golf club (or club

31

head) during a golf swing, the acceleration of the club (or club head) during a golf swing, the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), swing tempo, the impact of the ball with the golf club head during a golf swing, etc.) may be coordinated with the particular golf club with which the shot was made (e.g., the processor 204 of the monitoring device may be configured to calculate and coordinate such data).

Such coordinated identification information may then be transmitted by the transmitter 203 and/or stored in a memory (if applicable) along with the data from the sensors 202 (e.g., through methods such as discussed above). Of course, the identification information and the data from the sensors 202 may be coordinated at the remote computer system 400 if desired (e.g., through methods such as discussed above). Regardless of where the identification information and data from the sensors or golf metrics are coordinated, such coordinated information may be included with a data set generated from the information provided by the monitoring device 201.

According to aspects of the disclosure, the processor 204 of the monitoring device 201 or remote computer system 400 may use such golf club identification information and data from the sensors 202 of the monitoring device 201 to determine an estimated distance of the golf shot. For example, the remote computer system 400 may be configured to use characteristics of the golf swing (e.g., velocity of the golf club head at impact, the angle of the golf club head at impact, etc.) and the particular golf club which the golf shot was taken in order to estimate the distance and the direction the golf ball will travel. Such information may be useful to the golfer. For example, if the remote computer system 400 is a portable electronic device that the golfer has during a round of golf, the golfer may consult a remote computer system and use such information to potentially find a lost golf ball. Of course, the data may be used for other purposes as well. For example, the golfer's round of golf may be tracked and used for later analysis, such as to determine potential tendencies or habits in a golfer's swing of a particular golf club.

As discussed above, according to aspects of the disclosure, the monitoring device 201 may include a GPS technology. For example, the monitoring device 201 may include a GPS device which determines the location of the golf club 100 in which the monitoring device 201 is engaged. Alternatively, the golf club 100 may include a separate GPS device (e.g., a GPS transmitter/transceiver and, if desired, a processor). According to aspects of the disclosure, the location information may be incorporated with data determined by the sensors of monitoring device 201. For example, the action of a golf swing may be determined by the sensors 202 of the monitoring device 201. Hence, by coordinating such data with the location information from the GPS device (in a manner similar to the methods described above), the location of each golf shot taken during a round of golf may be determined.

Further, according to aspects of the disclosure, the above described location of each golf shot may be incorporated with maps of the golf course on which the golf shots were taken in order to provide a golfer with information on each golf shot during a round of golf. For example, according to aspects of the disclosure, maps of the golf course may be downloaded to the remote computer system 400. Thereafter, the golf shots (determined in a manner such as described above) may be superimposed or otherwise represented on the maps of the golf course in order to represent the golfer's round of golf.

Further, according to aspects of the disclosure, the above described location of a particular golf shot on the golf course may be incorporated with the data collected from the sensors

32

202. For example, the characteristics of a particular golf shot (e.g., the velocity of the golf club (or club head) during a golf swing, the acceleration of the club (or club head) during a golf swing, the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), swing tempo, the impact of the ball with the golf club head during a golf swing, etc.) may be coordinated with the location on the golf course at which that particular golf shot was taken.

Further, according to aspects of the disclosure, the above described location of a particular golf shot on the golf course may be incorporated with information about the particular golf club with which the golf shot was taken. For example, such aspects of the determining the particular golf club with which a shot is taken are described above and may be used in combination with the above described GPS technology. Further, such coordinated information may be included with a data set generated from the information provided by the monitoring device 201. For example, based on the data transmitted by the monitoring device 201, it may be determined that a golfer used a 3-iron to make a golf shot at a point 170 yards from the flag at the 2nd hole of a golf course.

Some or all of the above described determining information, such as determined golf swing characteristics (e.g., the velocity of the golf club (or club head) during a golf swing, the acceleration of the club (or club head) during a golf swing, the angle of the golf club (or club head) during a golf swing (e.g., relative to one or more reference points), swing tempo, the impact of the ball with the golf club head during a golf swing, etc.), golf club identification, location of the golf shot, golf course positioning information, etc., (including combinations and permutations thereof) may be coordinated and the coordinated information may be included with a data set generated from the information provided by the monitoring device 201. Therefore, according to aspects of the disclosure, detailed information of the practice session or round of golf may be recorded and analyzed.

According to aspects of the disclosure, the remote computer system 400 does not have to be a portable computer system. For example, as discussed above, the remote computer system 400 may be a desktop computer or other type of computer system. In such embodiments, the data collected by the monitoring device 201 may be stored locally in a memory as described above.

When the golfer has finished the practice session or round, the golfer may disengage the monitoring device 201 from the golf club head and engage it with the remote computer system 400 in order to transmit the data to the remote computer system 400. It is noted, that any type of connection system may be used without departing from the scope of the disclosure, including a wireless connection, a hardwired connection, connection via an input port (such as a USB port, or the like), etc. For example, according to some aspects of the disclosure, the monitoring device 201 does not have to be disengaged from the golf club head 101 and instead can transmit the data to the remote computer system 400 wirelessly. Other data storage and/or transmission arrangements also are possible without departing from the scope of the invention. For example, any desired way of placing data derived from the physical data from the monitoring device 201 in the proper form or format for communication to the remote computer system 400 may be provided without departing from the invention.

It is noted that according to some aspects of the disclosure, the monitoring device 201 may be configured to transmit data to the remote computer system 400 (e.g., a portable computer system, such as a cellular telephone) and the remote computer system 400 may be configured to transmit data to a secondary

computer system (such as a desktop computer) or a network as described below. For example, the remote computer system **400** may be connected to the secondary computer via a USB cable or other connection. Alternatively, a wireless connection such as described above (e.g., telecommunication means of a smartphone) may be used as well. In such a configuration, wherein the remote computer system **400** is portable, it could be used during play (e.g., at a practice session on a driving range or on the course during play) to give real time feedback to the golfer (e.g., during the round or practice session). Thereafter or in real-time, the data from the portable remote computer system **400** may be downloaded or uploaded to the secondary computer system for further analysis. For example, the data could be uploaded over telecommunication lines (e.g., through a smart phone) to a network which could compare the uploaded data with predetermined tables, charts, etc. and provide appropriate feedback based on the comparisons. For example, a system according to an exemplary embodiment can provide coaching videos, drills, challenges, product selection recommendations, etc. as described in detail below based on the uploaded data and comparisons of the uploaded data with predetermined data. It is noted that in some embodiments (e.g., wherein the secondary computer system is a network), the secondary computer system may include databases which are configured to store profiles for an individual golfer and update the profile of the golfer based on the uploaded data.

Additional aspects of this disclosure relate to the presentation of data to the golfer, coach, or other person(s). Such systems help the golfer measure and track his or her capabilities, mark improvements over time, determine areas that require additional work, etc. Data can be collected over single rounds of golf, portions of rounds of golf, single practices, portions of practices, multiple rounds of golf (or portions thereof), multiple practices (or portions thereof), multiple seasons (or portions thereof), etc.

FIG. 9A illustrates an example user interface screen **600** that may be used in systems and methods in accordance with at least some examples of this disclosure. As shown in FIG. 9A, the interface screen **600** may present much information to the player, including information relating to a specific round of golf or practice session, as well as information relating to more long term use of systems and methods in accordance with this disclosure. For example, as shown in FIG. 9A, user interface **600** may provide a display of the above described location of each golf shot incorporated with a map of the golf course on which the golf shots were taken in order to provide a golfer with information on each golf shot during a round of golf. For example, according to aspects of the disclosure, maps of the golf course may be downloaded to the remote computer system **400** and the golf shots (determined in a manner such as described above) have been superimposed on the map of the golf course in order to represent the golfer's round of golf. Further additional data may be displayed as shown.

Additionally, in accordance with this disclosure, other interfaces may provide information relating to: the overall total number of rounds of golf and/or practice sessions played by the golfer, the total overall strokes logged by the golfer using the system, the golfer's handicap over that time period, the golfer's top swing speed during those rounds or practice sessions, the number of times the golfer had an open club face during impact, the number of times the golfer had a closed club face during impact, the number of strokes that the club head was within a predetermined angle during a predetermined portion of the golf swing (e.g., the backswing or downswing), etc., the number of strokes that the club head was

within a predetermined velocity or acceleration range during the entire or a predetermined portion of the golf swing, etc.

The interface may also provide information for an individual round or practice session (with the ability to select among the various stored rounds of golf or practice sessions on the system). For example, the interface may display information relating to the speed of the golf swing during this specific practice session. Also, if desired, the user interface could be adapted to allow user selection of various different metrics or information to be displayed.

Systems and methods in accordance with at least some examples of this disclosure may include "goals" or "challenges." While the goals may be set by the individual golfer for himself or herself, optionally, the goals or challenges may be set by others (e.g., a coach, etc.). For example, a user interface may present one or more data metric which includes "grayed out" blocks that represent a player's "goal" or "challenge" for that metric. For example, the data from a round of golf may be displayed with an indication of the player's performance in that round of golf (e.g., in blackened in boxes) along with an indication of where the golfer's performance stood with respect to their "goal" or "challenge" levels (e.g., in grayed out boxes). The specific metric for the "goal" or "challenge" may be displayed in any desired manner, e.g., by clicking on the last box associated with the goal or challenge, by hovering over a grayed-out box, through a continuous display, etc. For example, the system may indicate that the player's overall top swing speed goal or challenge is 70 mph, while in the present round they had only run at a top swing speed of 65 mph.

In the next round, however, if the golfer achieved his or her speed goal by swinging at 70 mph, the systems and methods in accordance with at least some examples of this disclosure may provide a congratulatory message (e.g., textually, visually, audibly, etc., note the changes in the display. Furthermore, if desired, in an effort to keep the golfer motivated, a new "goal" or "challenge" can be calculated and displayed for the golfer. Also, if desired, when presented as a challenge from a coach, systems and methods in accordance with at least some examples of this disclosure may send a message to the golfer (or offer to let the golfer compose a message to others (e.g., a coach)) to advise that the challenge had been met. Other "rewards," motivational information, or other interaction may be provided, if desired, without departing from the scope of this disclosure.

User interfaces for athletic performance monitoring systems and methods in accordance with this invention may take on a wide variety of forms and formats and provide a variety of different types of displays and information without departing from this invention. Displays of other metrics or combinations of metrics are possible without departing from the scope of this disclosure. Other graphical or other displays of the desired metric information also may be provided without departing from the scope of this disclosure.

According to aspects of the disclosure, data collected from the above described system and metrics determined by the above described system may be uploaded to a network. For example, similar to aspects of the NIKE+™ athletic performance monitoring systems, such data may be uploaded to and shared on various social networking sites like FACEBOOK® or TWITTER®. In particular, the user may be able to enable or disable activity broadcasts. Activity broadcasts may include the automatic sharing of completed rounds of golf, goals and challenges. Additionally or alternatively, the user may enable or disable a function that notifies other users (e.g., placing a post or status update on the user's network site page) whenever the user playing a round of golf or practicing at a

driving range. This may enable other users to post messages of encouragement and to track the user's progress during the round of golf or the practice session. Golf data may also be posted to social network sites and social networking feeds mid-run and in real-time. Various other features and functions may also be configured by the user for sharing information.

Golfers may choose to share information or portions thereof with one or more other users, friends or through a social networking site. If the golfer chooses to share workout data through a social network site such as FACEBOOK® or TWITTER®, an interface may be displayed. Such an interface may include an automatically generated round of golf update message and allow the golfer to include additional information or notes. Upon approving the message, the user may publish the data to the social networking site by selecting publish option of the interface.

While wood-type golf clubs and wood-type golf club heads have been described in detail above, other aspects of this disclosure relate to iron-type golf club heads and iron-type golf clubs. For example, FIG. 10 illustrates an example of an iron-type golf club 700 according to aspects of the disclosure. As seen in FIG. 10, the iron-type golf club 700 may include an iron-type golf club head 701 in accordance with the present disclosure.

In addition to the golf club head 701, the overall golf club structure 400 may include a shaft 703 and a grip or handle 705 attached to the shaft 703. The shaft 703 may be received in, engaged with, and/or attached to the golf club head 701 in any suitable or desired manner, including in conventional manners known and used in the art, without departing from the disclosure. As more specific examples, the shaft 703 may be engaged with the golf club head 701 through a shaft-receiving sleeve or element extending into the club head 701 (e.g., a hosel), and/or directly to the club head structure 701, e.g., via adhesives, cements, welding, soldering, mechanical connectors (such as threads, retaining elements, or the like). If desired, the shaft 703 may be connected to the golf club head 701 in a releasable manner using mechanical connectors to allow easy interchange of one shaft for another on the head. Also, the grip or handle 705 may be attached to, engaged with, and/or extend from the shaft 703 in any suitable or desired manner, including in conventional manners known and used in the art, e.g., using adhesives or cements, etc. The shaft 703 and the grip or handle 705 may be made from any suitable materials such as those described above with regard to the wood type golf club 100.

According to aspects of the disclosure, the golf club head 701 may also include a ball striking face (e.g., a ball striking face which includes a face plate) 711. According to aspects of the disclosure, the golf club head 701 may be constructed in any suitable or desired manner and/or from any suitable or desired materials without departing from this disclosure, including from conventional materials and/or in conventional manners known and used in the art. For example, the club head 701 and/or its various parts may be made by forging, casting, molding, and/or using other techniques and processes, including techniques and processes that are conventional and known in the art. According to aspects of the disclosure, the golf club head 701 may be a blade type iron golf club head. According to other aspects the golf club head 701 may be a perimeter weighted and/or cavity back type golf club head or other iron type golf club head structure.

According to aspects of the disclosure, the golf club head 701 may include a crown, a sole, a toe end, and a heel end. Further, as seen in FIGS. 11 and 12 the golf club head 701 may include a cavity, or port, 709 behind the ball striking face

711. The port 709 may extend substantially along the length of the rear of the ball striking face 711.

According to aspects of the disclosure, and as seen in FIGS. 13 and 14, the port 709 may be configured to receive a cartridge 800. Further, if desired, cartridge 800 may be secured within to the golf club head 701 by securing means. It is noted, that the cartridge 800 may be secured in the port 709 of the golf club head 701 in a variety of ways. For example, as discussed above, according to aspects of the disclosure, the cartridge 800 may be removably engaged with the golf club head 701. Therefore, mechanical fasteners may be used to secure the cartridge 800 in the port 709. For example, example embodiments of the disclosure may include a cartridge 800 which is configured to be engaged with the golf club head 701 via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc. Other securing means, such as described above with regard to wood-type golf club, may be used as well.

According to example embodiments of the disclosure, the cartridge 800 may be configured with a first portion (e.g., an exterior portion) 800a. Further, according to example aspects of the disclosure, the cartridge 800 may include a second portion (e.g., an insert portion) 800b which is configured to be inserted into the interior of the port 709 of the golf club head 701. The cartridge 800 may be made from any desired materials and combinations of different materials such as described above with regard to cartridge 200.

The second portion may be configured to house a monitoring device 201 similar to the one described above with regard to the wood-type golf club. For example, the monitoring device 201 may be configured to house the sensors 202, the transmitter/transceiver 203, processor 204, power supply 206, memory, etc. The monitoring device 201, its capabilities and functions are similar to the monitoring device 201 described above and, therefore, for the sake of brevity, will not be elaborated on here. Further, the above described methods for determining and transmitting data to the remote computer 400 are applicable with the iron-type golf clubs as well and, therefore, will not be repeated for the sake of brevity.

While not shown in the depicted embodiment, aspects of the disclosure, relate to a weight cartridge which is configured to be engaged with the port 709. The weight cartridge may be configured similarly to the cartridge 800 described above with the exception that the weight cartridge does not include a monitoring device 201. It is noted that the weight cartridge may be configured to engage with the port 709 in the same manner as the corresponding cartridge 800. Hence, again, for the sake of brevity, the engaging and releasing structure of the weight cartridge and the port 709 will not be elaborated on here.

According to aspects of the disclosure, when the golfer does not want to have the monitoring device 201 housed within the golf club 700, the golfer may disengage and remove the cartridge 800 from the port 709 of the golf club head 701 and engage and secure the weight cartridge with the port 709 of the golf club head 701. It is noted that according to aspects of the disclosure, the weight cartridge may be configured to act as a dampening member.

Based on the above disclosure, it is understood that aspects of the disclosure are directed to a golf club configured to receive interchangeable sections or cartridges, wherein one of the interchangeable cartridges may house a monitoring device 201 and a second of the interchangeable cartridges does not house a monitoring device. In this way, the golfer may selectively configure the golf club to include, or not include, the monitoring device 201 at the golfer's discretion.

It is noted that, if desired, neither the cartridge **800** or the weight cartridge has to be included in the golf club head **701** and, instead, the golfer may remove the cartridge **800** and play with the port **709** being open and unfilled.

FIG. **14A** shows another iron-type golf club **800** according to aspects of the disclosure. As seen in FIG. **14A**, the iron-type golf club **800** may include an iron-type golf club head **801** in accordance with the present disclosure. Further, the iron-type golf club **800** may be configured to engage with a removable section or cartridge **200** and a monitoring device **201**.

According to the aspects of the disclosure, the monitoring device **201** may be configured to engage with the golf club head **801** in a variety of ways. For example, as seen in FIG. **14A**, the removable section **200** is engaged with the golf club head **801** via a threaded fastener. However, the removable section **200** may be configured to be engaged with the golf club head **801** via other methods as well, such as press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), etc. As seen, the removable section **200** may include an opening configured to surround the monitoring device **201** and through which the monitoring device is visible. The removable section **200** may be configured to provide support and stability to the monitoring device **201**. According to aspects of the disclosure, the removable section **200** may be made of plastic or other materials.

Further, as seen in FIG. **14A**, the monitoring device **201** is engaged with the golf club head **801**. The engagement of the monitoring device **201** with the golf club head **801** can be done in a variety of ways, e.g., mechanical fasteners, press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc. The golf club head **801** may include a recess configured to receive the monitoring device **201**. For example, the recess may be configured to surround and engage the monitoring device **201** in order to support and stabilize the monitoring device **201**.

The golf club head **801**, the removable section **200** and the monitoring device **201** may be configured to provide desirable weight placement in the club head **801**. For example, the golf club head **101**, the removable section **200** and the monitoring device **201** may be configured such that when engaged, the golf club head **801** it is in the lower portion of the golf club head **801**.

A wide variety of overall club head constructions are possible without departing from this disclosure. For example, it is noted that the dimensions and/or other characteristics of the golf club heads **701**, **801** according to examples of this disclosure may vary significantly without departing from the disclosure. For example, the above described features and configurations may be incorporated into any iron-type club heads including, for example: wedges (e.g., pitching wedges, lob wedges, gap wedges, sand wedges, etc.), iron-type hybrid clubs, driving irons, 0 through 10 irons, etc.

Further, the above described features and configurations in the aspects of the disclosure may be incorporated into a blade type golf club heads, a perimeter weighted and/or cavity back type golf club head or other iron type golf club head structure without departing from this disclosure. For example, a perimeter weighted and/or cavity back type golf club head including the golf club heads **701**, **801** according to aspects of the disclosure, may include a rear surface opposite the ball striking face **711** which includes a perimeter weighting member extending rearward from the ball striking face and along at least a portion of a circumferential area of the golf club head body.

While wood-type golf clubs and iron-type golf clubs have been described in detail above, other aspects of this disclosure

relate to putter type golf club heads and putters. For example, FIGS. **15A** and **15B** generally illustrate an example of a putter-type golf club head **1001** according to aspects of the disclosure. The putter-type golf club head **1001** may be included in a putter which includes a shaft and a grip or handle (not shown). It is noted that the shaft and the grip or handle may be configured and attached to, or engaged with, the putter-type golf club head **1001** any suitable or desired manner such as those described above with regard to the wood type golf club **100** and iron-type golf club **700**.

According to aspects of the disclosure, the golf club head **1001** may also include a ball striking face (e.g., a ball striking face which includes a face plate) **1111**. According to aspects of the disclosure, the golf club head **1001** may be constructed in any suitable or desired manner and/or from any suitable or desired materials without departing from this disclosure, including from conventional materials and/or in conventional manners known and used in the art. For example, the club head **1001** and/or its various parts may be made by forging, casting, molding, and/or using other techniques and processes, including techniques and processes that are conventional and known in the art.

According to aspects of the disclosure, the golf club head **701** may include a crown, a sole, a toe end, and a heel end. Further, as seen in FIG. **15B** the golf club head **1001** may include a cavity, or port, **1009** behind the ball striking face **1011**. The port **1009** may be positioned centrally in the golf club head **1001** and behind the rear of the ball striking face **1011**.

According to aspects of the disclosure, and as seen in FIG. **15B**, the port **1009** may be configured to receive a cartridge **1100**. Further, if desired, the cartridge **1100** may be secured within the golf club head **1001** by securing means. It is noted, that the cartridge **1100** may be secured in the port **1009** of the golf club head **1001** in a variety of ways. For example, as discussed above, according to aspects of the disclosure, the cartridge **1100** may be removably engaged with the golf club head **1001**. Therefore, mechanical fasteners may be used to secure the cartridge **1100** in the port **1009**. For example, example embodiments of the disclosure may include a cartridge **1100** which is configured to be engaged with the golf club head **1001** via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc. Other securing means, such as described above with regard to wood-type golf club, may be used as well.

According to aspects of the disclosure, the cartridge **1100** may be made from any desired materials and combinations of different materials such as described above with regard to cartridge **200**. Further, according to example embodiments of the disclosure, the cartridge **1100** may be configured with configured to house a monitoring device **201** similar to the one described above with regard to the wood-type golf club. For example, the monitoring device **201** may be configured to house the sensors **202**, the transmitter/transceiver **203**, processor **204**, power supply **206**, memory, etc. The monitoring device **201**, its capabilities and functions are similar to the monitoring device **201** described above and, therefore, for the sake of brevity, will not be elaborated on here. Further, the above described methods for determining and transmitting data to the remote computer **400** are applicable with the iron-type golf clubs as well and, therefore, will not be repeated for the sake of brevity.

As seen in FIG. **15B**, aspects of the disclosure, relate to a weight cartridge **1200** which is configured to be engaged with the port **1009**. The weight cartridge **1200** may be configured similarly to the cartridge **1100** described above with the

exception that the weight cartridge **1200** does not include a monitoring device **201**. It is noted that the weight cartridge **1200** may be configured to engage with the port **1009** in the same manner as the corresponding cartridge **1100**. Hence, again, for the sake of brevity, the engaging and releasing structure of the weight cartridge **1200** and the port **1009** will not be elaborated on here.

According to aspects of the disclosure, when the golfer does not want to have the monitoring device **201** housed within the golf club **1000**, the golfer may disengage and remove the cartridge **1100** from the port **1009** of the golf club head **1001** and engage and secure the weight cartridge **1200** with the port **1009** of the golf club head **1001**. It is noted that according to aspects of the disclosure, the weight cartridge **1100** may be weighted as desired to provide appropriate balancing to the putter-type golf club head **1001**.

Therefore, based on the above disclosure, it is understood that aspects of the disclosure are directed to a golf club configured to receive interchangeable sections or cartridges, wherein one of the interchangeable cartridges may house the monitoring device **201** and a second of the interchangeable cartridges does not house the monitoring device **201**. In this way, the golfer may selectively configure the golf club to include, or not include, the monitoring device **201** at the golfer's discretion.

A wide variety of overall club head constructions are possible without departing from this disclosure. For example, it is noted that the dimensions and/or other characteristics of the golf club heads **1001** according to examples of this disclosure may vary significantly without departing from the disclosure. For example, the above described features and configurations may be incorporated into any putter-type club heads including, for example: mallet heads, blade-type putters, etc.

For example, FIGS. **16A** and **16B** show an alternative embodiment of a putter-type golf club according to aspects of the disclosure. FIG. **16A** is an exploded view of an illustrative embodiment of a putter golf club head structure according to aspects of the disclosure wherein a monitoring device **201** is used. FIG. **16B** is an exploded view of the putter golf club head shown in FIG. **16A** wherein the weight cartridge **1200** is used instead of the monitoring device **201**.

As seen in FIGS. **16A** and **16B**, the putter-type golf club may include a putter-type golf club head **1301** in accordance with the present disclosure. The golf club head **1301** may include a recess configured to receive the monitoring device **201**. For example, the recess may be configured to surround and engage the monitoring device **201** in order to support and stabilize the monitoring device **201**. As seen in FIG. **16A**, the recess may be configured in the rear of the golf club head **1301** behind the ball striking face of the golf club head **1301**. According to the aspects of the disclosure, the monitoring device **201** may be configured to engage with the golf club head **1301** in a variety of ways, such as mechanical fasteners, press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc.

The golf club head **1301** and the monitoring device **201** may be configured to provide desirable weight placement in the club head **1301**. For example, the golf club head **1301**, and the monitoring device **201** may be configured such that when engaged, the golf club head **1301** is directly behind the center of the ball striking face of the golf club head **1301**. While not illustrative, it is noted that in alternative embodiments, the removable section **200** may be used to engage the monitoring device with the golf club head **1301**.

As seen in FIG. **16B**, aspects of the disclosure, relate to a weight cartridge **1200** which is configured to be engaged with the recess. The weight cartridge **1200** may be configured

similarly to the monitoring device **201** described above with the exception that the weight cartridge **1200** does not include a monitoring device **201**. It is noted that the weight cartridge **1200** may be configured to engage with the recess in the same manner as the monitoring device **201**. Hence, for the sake of brevity, the engaging and releasing structure of the weight cartridge **1200** and the recess will not be elaborated on here.

FIG. **16C** shows an alternative embodiment of a putter-type golf club according to aspects of the disclosure. FIG. **16C** is an exploded view of an illustrative embodiment of a putter golf club head structure according to aspects of the disclosure wherein a monitoring device **201** is used.

As seen in FIG. **16C**, the putter-type golf club may include a putter-type golf club head **1401** in accordance with the present disclosure. The golf club head **1401** may include a recess configured to receive the monitoring device **201**. For example, the recess may be configured to surround and engage the monitoring device **201** in order to support and stabilize the monitoring device **201**. As seen in FIG. **16C**, the recess may be configured in the ball striking face of the golf club head **1401**. According to the aspects of the disclosure, the monitoring device **201** may be configured to engage with the golf club head **1401** in a variety of ways, such as mechanical fasteners, press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), threaded fasteners, etc.

The golf club head **1401** and the monitoring device **201** may be configured to provide desirable weight placement in the club head **1401**. For example, the golf club head **1401**, and the monitoring device **201** may be configured such that when engaged, the golf club head **1401** is in center of the ball striking face of the golf club head **1401**. While not illustrative, it is noted that in alternative embodiments, the removable section **200** may be used to engage the monitoring device with the golf club head **1401**.

FIG. **16D** shows an alternative embodiment of a putter-type golf club according to aspects of the disclosure. FIG. **16D** is a view of an illustrative embodiment of a putter golf club head structure according to aspects of the disclosure wherein two monitoring devices **201** are used. For example, as seen in FIG. **16**, a first monitoring device **201** may be positioned in a heel of the putter-type golf club head and a second monitoring device **201** may be positioned in a toe of the putter-type golf club head. According to aspects of the disclosure, by using data from both the first and second monitoring devices **201**, the position of where the golf ball impacts the face of the golf club head may be determined. It is noted that while this feature of having two monitoring devices **201** in a golf club head is depicted in a putter, this feature is applicable to any type of golf club head, including: wood-type golf club heads, iron-type golf club heads, hybrid-type golf club heads, etc. It is further understood that the pair of monitoring devices **201** may be positioned proximate the face of the club head and proximate the heel and toe of the club head.

According to aspects of the disclosure, monitoring devices **201** may include one or more sensors configured to detect the impact of the golf ball with the golf club head **101**. For example, a force sensor, a pressure sensor (e.g., a piezoelectric sensor), or the like may be configured to detect the location of the impact on the ball striking face **107** of the golf club head and, further, the force generated from the impact. Such data generated from the impact sensors may be communicated through the monitoring device **201** and, further, transmitted via the transmitter **203** along with the other data from the other one or more sensors of the monitoring device **201** described above. Further, according to embodiments of such

a disclosure, the data from the impact sensors can be incorporated with data from the above described sensors. For example, the data from the impact sensors can be used to determine various characteristics of the golf swing such as described above. Further, according to aspects of the disclosure, by using data from one or more impact sensors, the position of where the golf ball impacts the face of the golf club head may be determined.

According to aspects of the disclosure, embodiments of the disclosure may include one or more monitoring devices **201** located in various positions throughout the golf club. For example, according to aspects of the disclosure, the first and second monitoring devices **201** may be positioned at or near the ball striking face of the golf club head. However, according to other aspects of the disclosure, embodiments may have one or more monitoring devices **201** positioned away from the ball striking face of the golf club head. For example, in the embodiment depicted in FIG. **16D**, the first and second monitoring devices **201** are positioned in the rear of the golf club head.

It is noted that in embodiments wherein the sensors are not positioned at the ball striking face, the data determined by sensors may need to be manipulated or adjusted in order to provide accurate measurements. For example, in the embodiment shown in FIG. **16D**, because sensors are positioned in the rear of the golf club head, they may provide data that is different from data determined by sensors in monitoring devices **201** positioned at or near the ball striking face of the golf club head. Therefore, data collected from sensors of the embodiment shown in FIG. **16D** may be manipulated (e.g., recalculated or otherwise modified) in order to account from the positioning of the sensors within the rear of the golf club head. In this way, the manipulated data can be used to determine accurate golf metrics, variables and kinematics, such as described above.

It is noted that while the above description of manipulating data is with respect to a distance from the ball striking face of the golf club head, any reference point may be used. Accordingly, the data collected from sensors positioned away from that particular reference point may be manipulated (e.g., recalculated or otherwise modified) in order to account from the positioning of those sensors away from the particular reference point.

According to aspects of the disclosure, the data from sensors may be subjected a transformation matrix which manipulates the data (e.g., recalculates or modifies the data) in order to account for the exact positioning of the sensor within the golf club. The transformation matrix may be a series of calculations which modifies that data according to the exact positioning of the sensor within the golf club. Therefore, it is understood that a different transformation matrix may be required for each of individual sensors positioned at different locations within the golf club. For example, in the embodiment shown in FIG. **16D**, a first transformation matrix may be used to calculate data obtained the first sensor in the heel of the golf club head and a second, different, transformation matrix may be used to calculate data obtained the second sensor in the toe of the golf club head.

The transformation matrix may be included in a software package that may be downloaded to the remote computer **400** to which the data from the monitoring device **201** is transmitted. For example, the software package may be available for download from a website. For example, a website may include software packages or applications designed for particular golf clubs or sets of golf clubs. Those software packages may contain transformation matrices designed for the

specific positions of sensors and remote monitoring devices **201** in the respective golf clubs.

Therefore, if a golfer was using a particular putter (e.g., putter A), the golfer could download the particular software package or application designed for putter A to the remote computer **400**. Hence, when data (obtained by the sensors of the remote monitoring device(s) **201** in that particular golf club) is transmitted to the remote computer **400**, the downloaded software package or application for that particular golf club would recalculate the obtained data and output accurate measurements, golf metrics, variables and kinematics.

According to aspects of the disclosure, a monitoring device **201** may contain identification codes which allow data transmitted from a particular monitoring device **201** to synchronize with the remote computer **400** used by the golfer. For example, the upon downloading the software package or application for the particular golf club to the remote computer **400**, the golfer may manually enter an identification code into the remote computer **400** to synchronize the monitoring device **201** with the remote computer **400**. Hence, by allowing the particular monitoring device **201** to be synchronized with the remote computer **400**, the monitoring devices could be interchangeable within various golf clubs.

For example, a golfer may download an application or software package which contains transformation matrices for each golf clubs that a golfer owns. By synchronizing the monitoring device(s) **201** in each of the golf clubs (e.g., the monitoring device(s) **201** in each of: a pitching wedge, a sand wedge, a 10-iron, a 9-iron . . . a 3-wood, a driver, etc.), with the remote computer **400**, the remote computer **400** would recognize the data from a particular monitoring device **201** and associate that data with the respective golf club and, additionally, appropriate location of the sensor within the respective golf club. Hence, using the transformation matrix for the respective golf club, the remote computer **400** would output correct measurements, golf metrics, variables and kinematics. Therefore, as demonstrated, provided that the monitoring device(s) **201** are synchronized correctly, the monitoring device(s) **201** may be interchangeable within golf clubs. It is noted that, if desired, the identification code could be transmitted to the remote computer **400** by the monitoring device **201** along with the data. In this way, the identification code would not have entered by the golfer and, instead, the synchronization and coordination of the monitoring device **201** with remote computer **400** could be done automatically.

FIGS. **17A** and **17B** are an illustrative embodiment of the interior of an embodiment of a monitoring device **201**, or general schematic sensor layout, according to aspects of the disclosure. For example, as seen in FIGS. **17A** and **B**, a monitoring device **201** may include a power source, a transceiver, an accelerometer (e.g., 3-axis accelerometer), one or more: capacitors, diodes, antennas, inductors, resistors, filters, integrated circuits for controllers (e.g., mixed signal controllers), transceivers, memory and digital motion sensors, voltage regulators, inertial measurement units, etc. One of ordinary skill in the art would realize that modification to, or exclusion of, one or more of the above components or the inclusion of additional components in monitoring device may be used as desired to configure the monitoring device to function as described above. Such inclusions, modifications, etc. are considered within the scope of the disclosure. FIGS. **18A-D** are illustrative embodiments of circuitry of a monitoring device according to aspects of the disclosure. It is understood that various components as described above can be incorporated into the schematic layouts and circuitry disclosed herein.

Embodiment with Different Sensitivity Ranges for Putter/Driver

As discussed above, aspects of the disclosure relate to a monitoring device **201** that is configured to measure displacement, position, orientation, velocity, acceleration or other characteristics of associated with a golf stroke. According to further aspects of the disclosure, a monitoring device **201** may be configured to fit in any golf club of a set of golf clubs in accordance with one or more embodiments of the disclosure. In other words, a monitoring device **201** according to aspects of the disclosure may be “universal” with respect to the golf clubs in such a set of golf clubs. For example, the monitoring device **201** may be configured to fit in a putter of the golf club set, an iron-type golf club of the golf club set and in a wood-type golf club of the golf club set.

However, the displacement, velocity, acceleration or other characteristics associated with a golf stroke may vary dramatically depending on the particular golf stroke. For example, velocity, acceleration or other characteristics associated with a putt may vary dramatically from the velocity, acceleration or other characteristics associated with the golf swing of a driver or iron.

For example, during a golf swing with a driver, the velocity of the club head may be between 0-125 miles per hour (mph) (roughly about 0-56 meters per second). In contrast, during a putt with a putter, the velocity of the club head may be between 0-7 miles per hour (roughly 0-3.0 meters per second). Further, during a golf swing with a driver, the angular velocity of the club head may be between 0-3000 degrees per second (roughly about 0-52 radians per second). In contrast, during a putt with a putter, the angular velocity of the club head may be between 0-150 degrees per second (roughly 0-3 radians per second).

Similarly, during a golf swing with a driver, the acceleration of the club head may be between 0-3000 feet/sec² (roughly about 0-1000 meters per second (m/s²)). In contrast, during a putt with a putter, the acceleration of the club head may be between 0-3000 feet/sec² (roughly about 0-15.0 m/s²).

For example, according to an illustrate embodiment, FIGS. **19A-B** show graphically the magnitude of acceleration and angular velocities for a typical putt. As seen in FIGS. **19A-B**, the acceleration during a putt may be 1.1 g (11 m/s²). Further, the angular velocity during a putt may be 80 dps (1.5 rad/second). In contrast, FIGS. **19C-D**, show graphically the magnitude of acceleration and angular velocities for an illustrative golf swing with a driver. As seen in FIG. **19-B**, the acceleration during a golf swing with the driver may be 15 g (150 m/s²). Further, the angular velocity during the golf swing with a driver may be 1500 dps (26 rad/second). Hence, it is understood, that as discussed above, velocity, acceleration or other characteristics associated with a putt may vary dramatically from the velocity, acceleration or other characteristics associated with a golf swing of a driver.

As described above, a monitoring device **201** may include one or more sensors **202** and the sensors **202** may be accelerometers (such as piezoelectric accelerometers), magnetometers, or gyroscopes which are configured to measure a plurality of data including velocity, acceleration, orientation, gravitational forces, etc. Hence, a monitoring device **201** according to aspects of the disclosure may include an Inertial Measuring Unit (IMU) which is one or more sensors (e.g., accelerometers and/or gyroscopes, or some combination thereof in an exemplary embodiment) that are configured to measure velocity, acceleration, orientation, gravitational forces, etc.

Given the above described disparity in velocity ranges between the different types of golf stroke, it may be difficult for a single IMU to accurately determine the displacement, velocity and acceleration of the club during the golf stroke. For example, in order to achieve an accurate reading of the angular velocity of a putting stroke, an IMU configured to measure a putt may be extremely sensitive to small changes in angular velocity, wherein small is relative to the velocity ranges discussed above with respect to a putting stroke (e.g., fractions of a meter per second). Similarly, in order to achieve an accurate reading of the velocity of a golf swing for an iron-type golf club or a wood-type golf club, an IMU configured to measure such a golf swing may be less sensitive to small changes in velocity and able to determine larger changes in velocity, wherein large is relative to the velocity ranges discussed above with respect to a golf swing of an iron-type golf club or a wood-type golf club (e.g., at least several meters per second).

Similarly, given the disparity in acceleration ranges between the different types of golf stroke, it may be difficult for a single IMU to accurately determine the acceleration of the club during the golf stroke. For example, in order to achieve an accurate reading of the acceleration of a putting stroke, an IMU configured to measure a putt may be extremely sensitive to small changes in acceleration, wherein small is relative to the acceleration ranges discussed above with respect to a putting stroke (e.g., 0-15 m/s²). Similarly, in order to achieve an accurate reading of the acceleration of a golf swing for an iron-type golf club or a wood-type golf club, an IMU configured to measure such a golf swing may be less sensitive to small changes in acceleration and able to determine larger changes in acceleration, wherein large is relative to the acceleration ranges discussed above with respect to a golf swing of an iron-type golf club or a wood-type golf club (e.g., 0-1000 m/s²).

As aspects of the disclosure are directed to a monitoring device **201** which is “universal” with respect to engaging with any of the golf clubs in the golf club set, a monitoring device **201** according to aspects of the disclosure may include more than one IMU, wherein each of the IMUs is configured differently in order to accurately measure a particular type of golf stroke. For example, one of the IMUs may be configured to measure angular velocity and/or acceleration and may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s²). As discussed above, such an IMU may be beneficial in determining characteristics associated with a putting stroke. Further, another of the IMUs may be configured to measure velocity and/or acceleration and may be less sensitive to small changes in velocity and/or acceleration (as compared with the first IMU) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s²). As discussed above, such an IMU may be beneficial in determining characteristics associated with a golf swing for an iron-type golf club or a wood-type golf club.

Therefore, according to aspects of the disclosure a single monitoring device **201** may be configured to include a first IMU directed to determining data associated with a putting stroke and a second IMU, which is different from the first IMU, and is directed to determining data associated with a golf swing for an iron-type golf club or a wood-type golf club.

Aspects of the disclosure are directed to determining which of the one or more IMUs to use in collecting data related to the golf stroke. For example, aspects of the disclosure are directed to selectively using data (e.g., for calculations as will be described below) from the first IMU instead of the second

45

IMU or the second IMU instead of the first IMU based on the type of club with which the monitoring device **201** is engaged. Further aspects of the disclosure are directed to receiving data (related to the golf stroke) collected from each (or more than one) of the IMUs and then determining which of data from the one or more IMUs to use (e.g., for calculations as will be described below) based on the type of club with which the monitoring device **201** is engaged. For example, the data from a particular IMU may be selected for use in calculations and/or for transmission to the remote computer **400** based on the data received from each of the IMUs and the type of golf club or other information indicated by the data received from each of the IMUs. In this way, the monitoring device **201** may switch between using and/or transmitting data from a first IMU and a second IMU based on data received from both IMUs.

For example, according to one embodiment of the disclosure, the monitoring device **201** may be configured to be engaged with a golf club of a set of golf clubs which are each configured to receive the monitoring device **201** and the engagement between the monitoring device **201** and the particular golf club of the set causes the selection of the appropriate IMU to be used in conjunction with that particular golf club of the set. In other words, the one or more IMUs that is selected to be used to capture data associated with the golf stroke is determined by the engagement of the monitoring device **201** with the particular golf club. Further, in another example wherein data is collected from each IMU of the golf club, the monitoring device **201** may be configured to be engaged with a golf club of a set of golf clubs which are each configured to receive the monitoring device **201** and the engagement between the monitoring device **201** and the particular golf club of the set causes the selection of the appropriate IMU from which the data should be used for a particular purpose in conjunction with that particular golf club of the set. In other words, data from one of the IMUs (and associated with the golf stroke) is selected to be used for a particular purpose based on the engagement of the monitoring device **201** with the particular golf club. For example, while data is collected from both a first and second IMU, based on the engagement of the monitoring device **201** with the particular golf club, data from the first IMU, instead of the second IMU may be used for determining angular velocity of the golf swing.

By way of example, the grips of each of the golf clubs in the set of golf clubs may be configured to receive the monitoring device **201** in a manner discussed above with regard to FIGS. 8-9. For example, as discussed above, according to particular embodiments of the disclosure, monitoring device **201** may be similar to those used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Ore. For example, as seen in FIGS. 4A and 4B, the monitoring device **201** may include a generally rectangular compartment which may be similar to the compartment used to house sensors used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Ore. Further, the compartment of the monitoring device **201** may house various elements described above, such as the processor **204**, sensors **202**, transmitter **203**, power supply **206**, memory, etc. Further, as described above, according to aspects of the disclosure, the monitoring device **201** may be configured to engage with the grip **105** of the golf club. For example, as described with regard to FIG. 8, the grip **105** may be configured to receive a removable section or cartridge **200** and the removable section **200** may be configured to receive the monitoring device **201**.

46

According to aspects of the disclosure, the engagement between the monitoring device **201** and removable section **200** the particular golf club may cause a particular IMU of the monitoring device **201** to be selectively activated. For example, as seen in FIG. 20, in one such embodiment, the monitoring device **201** may include one or more openings **201o** configured to receive one or more protrusions (e.g., prongs) that extend from the removable section **200** of the particular golf club. According to aspects of the disclosure, a particular IMU of the monitoring device **201** may be activated based on which of the openings in the monitoring device **201** receive a protrusion of the removable section **200**.

For example, the monitoring device **201** may include four openings **201o**. Further, as seen in FIG. 21A, a removable section **200** of a putter of the set of golf clubs may have two protrusions **200p** that are configured to engage with the first and second of the four openings **201o** of monitoring device **201**. When the first and second holes are engaged by the two protrusions of the a removable section **200** of a putter, a first IMU of the monitoring device **201** that is configured to measure velocity and/or acceleration associated with a putting stroke (e.g., an IMU that may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s²)) may be selected and/or activated.

Conversely, as seen in FIG. 21B, a removable section **200** of an iron-type golf club or a wood-type golf club of the set of golf clubs may have two protrusions that are configured to engage with the third and fourth of the four openings **201o** of monitoring device **201**. When the third and fourth openings **201o** are engaged by the two protrusions of the a removable section **200** of the iron-type golf club or the wood-type golf club, a second IMU of the monitoring device **201** that is configured to measure velocity and/or acceleration associated with a golf swing for the iron-type golf club or the wood-type golf club (e.g., an IMU that may be less sensitive to small changes in velocity and/or acceleration (as compared with the first IMU) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s²)) may be activated.

It is noted that in some embodiments, the protrusions of the removable section **200** may be configured to activate detecting switches within monitoring device **201** which cause the processor **204** to determine which of the IMUs to use. For example, engagement of the protrusions **200p** with the openings **201o** of the removable section **200** may cause the detecting switches within the openings **201o** to move from a first position to second position. The processor **204** may be configured to recognize this movement and activate either the first or second IMU depending on which of the detecting switches have been moved. Alternatively, there may be electrical connections made between the protrusions and the elements (e.g., leads) within the opening openings **201o** of the removable section **200**. The processor **204** may be configured to recognize these connections and activate either the first or second IMU depending on which of the elements are contacted. Of course, such embodiments are just examples and other methods of selectively determining which of the IMUs to use in capturing data associated with the golf stroke may be used.

Other embodiments may be implemented as well. For example, while the above embodiment describes selectively activating either the first or second IMU based on the processor **204** being able to recognize movement of the detecting switches or insertion of the protrusions, in other embodiments, each of the first or second IMU may be already activated, and the processor **204** may be configured to selectively use data from each (or more than one) of the IMUs based of

the recognition of movement of the detecting switches or insertion of the protrusions. For example, based on the processor's recognition of movement of the detecting switches or insertion of the protrusions, data from the first IMU may be used for determining angular velocity while data from a second IMU may be used for other purposes (e.g., confirming velocity is above or below a predetermined range, determining other characteristics of the golf swing, etc.). In this way, the protrusions, detecting switches, etc. may be used as an information source for determining aspects of the golf club and which data from the IMUs to use for predetermined purposes or calculations (e.g., the processor/firmware may be configured to use data from a first IMU instead of a second IMU for determining velocity when data received from the first IMU and/or the second IMU is within a predetermined range) rather than a physical switching or selectively activating a particular IMU. These features may be used in any of the embodiments described herein. As seen in FIGS. 21A and 21B, the removable section 200 may include an elongated portion configured to aid in housing the monitoring device 201. As described above, the elongated portion may include a first arched end configured to engage a first rounded end of the compartment, a second arched end configured to engage a second rounded end of the compartment and a back portion which extends between the first arched portion and the second arched portion and is configured to engage a side of the compartment. According to aspects of the disclosure, the elongated portion of the removable section 200 may include the protrusions 200p. Further, the flat side of the compartment of the monitoring device 201 may be configured to include the openings 201o. Additionally, or alternatively, one or both of the rounded ends of the compartment of the monitoring device 201 may be configured to include the openings 201o which are configured to receive the protrusions 200p which are positioned on the first arched portion and/or the second arched portion of the removable section 200.

The protrusions 200p and openings 201o may be arranged such that the monitoring device 201 can only be engaged with the removable section in an intended orientation. For example, while the "universal" monitoring device 201 may have four holes, the protrusions 200p on the removable section 200 and openings 201o on the monitoring device 201 are arranged such that they will align only when the monitoring device 201 is engaged with the removable section 200 in the intended orientation.

It is noted that according to other aspects of the disclosure, and as shown in FIG. 9, the grip 105 may be configured to receive and secure the monitoring device 201 directly, without the inclusion of a separate removable section. As discussed above, the monitoring device 201 may be configured to be engaged with the grip 105 in a variety of ways. For example, the grip 105 may be configured with an opening at its terminal end that is configured to receive the monitoring device 201. However, regardless of how the monitoring device 201 is engaged with the grip 105, the grip 105 itself may be configured with the above discussed protrusions 200p configured to engage with the openings 201o in the monitoring device 201 to selectively determine which of the IMUs of the monitoring device 201 to use in capturing data associated with the golf stroke. For example, the grip 105 may include a slit that is configured to receive the monitoring device 201 when the monitoring device 201 is inserted into the grip along the monitoring device's longitudinal axis. Further, one or both of the rounded ends of the compartment of the monitoring device 201 may be configured to include the openings 201o which are configured to receive the protrusions 200p and the lower end of the slit may include the one or more

protrusions 200p. Additionally, or alternatively, the protrusions 200p may be positioned on the sides of the slit and may be spring loaded, flexible, etc. in order to accommodate the insertion and removability of the monitoring device 201.

It is noted that while four openings 201o and four protrusions 200p are discussed in the illustrative embodiment, it is clear that any combination of openings 201o and protrusions 200p may be used provided the combination will sufficiently allow the monitoring device 201 to selectively determine which of the IMUs of the monitoring device 201 to use in capturing data associated with the golf stroke.

Memory Wire

In addition to the above described embodiment which includes protrusions for activating detection switches, shape memory alloy may be used as well. Shape memory alloy is a substance which is configured to return to its original shape upon heating.

RFID Technology

Further, while the above embodiment discussed the structural engagement between the monitoring device 201 and the golf club 100 as a means of allowing the monitoring device 201 to selectively determine which of the IMUs of the monitoring device 201 to use in capturing data associated with the golf stroke, other methods and means may be used as well.

For example, as discussed above, according to particular embodiments of the disclosure, the monitoring device 201 may also be configured to identify the particular golf club in which the monitoring device 201 is engaged. For example, golf club 100 may include a chip (e.g., an RFID chip) which communicates with the monitoring device 201 when the monitoring device 201 is engaged with the golf club 100. This could be through direct electrical connection, wireless transmission, etc. The chip may be configured to indicate to the monitoring device 201 with which golf club the monitoring device 201 is engaged. For example, the transceiver of the monitoring device 201 may be configured to receive or "read" ID data from the chip which indicates which golf club of the golf club set the monitoring device is engaged. Accordingly, once the monitoring device 201 has determined the golf club with which it is engaged (based on the data provided from the chip), the processor of the monitoring device 201 can selectively choose one of the IMUs of the monitoring device 201 to use to capture data associated with the golf stroke.

For example, when the monitoring device 201 has received data from the chip (e.g., RFID chip) engaged with golf club, that the golf club is a putter, the processor may select, activate, and/or use the data from a first IMU of the monitoring device 201 that is configured to measure velocity and/or acceleration associated with a putting stroke (e.g., an IMU that may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s²)). Conversely, when the monitoring device 201 has received data from the chip (e.g., RFID chip) engaged with golf club, that the golf club is an iron-type golf club or a wood-type golf club, the processor may select, activate, and/or use the data from a second IMU of the monitoring device 201 that is configured to measure velocity and/or acceleration associated with a golf swing for the iron-type golf club or the wood-type golf club (e.g., an IMU that may be less sensitive to small changes in velocity and/or acceleration (as compared with the first IMU) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s²)).

Sensor Self-Aware Based on Speed

Further, while the above embodiments discussed the structural engagement between the monitoring device 201 and the golf club 100 or the use of a chip (e.g., an RFID chip) as

means of allowing the monitoring device **201** to selectively determine which of the IMUs of the monitoring device **201** to use in capturing data associated with the golf stroke (or selectively determine, from the data collected by each of the IMUs, which IMU's data to use in calculating or transmitting data to the remote computer), other methods and means may be used as well. For example, according to aspects of the disclosure, the monitoring device **201** may be configured to selectively determine which of the IMUs of the monitoring device **201** to use in capturing data associated with the golf stroke (or selectively determine, from the data collected by each of the IMUs, which IMU's data to use in calculating or transmitting data to the remote computer) based on the movement of the golf club. Further, the monitoring device **201** may be configured to determine the golf club with which the monitoring device **201** has been engaged based on the movement of the golf club.

According to aspects of the disclosure, the processor **204** may be configured to receive data from each of the IMUs in the monitoring device **201**. If the data indicates that a characteristic is above a predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a corresponding, predefined IMU as the determined data and discard the data from the other IMU(s). Conversely, if the data indicates that a characteristic is below that predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a second corresponding, predefined IMU as the determined data and discard the data from the other IMU(s).

For example, if the processor **204** receives data from the IMUs which indicates the club was swung at a velocity that is below a predefined value (e.g., 3 mph), then the processor **204** of the monitoring device **201** will assume the golf club with which the monitoring device **201** is engaged is a putter. Therefore, the processor **204** may use the data received from a first IMU of the monitoring device **201** that is configured to measure velocity and/or acceleration associated with a putting stroke (e.g., an IMU that may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s²)) and discard the data from other IMU(s).

Conversely, if the processor receives data from the IMUs which indicates the club was swung at a velocity that is above a predefined value (e.g., 3 mph), then the processor **204** of the monitoring device **201** will assume the golf club with which the monitoring device **201** is engaged is an iron-type golf club or a wood-type golf club. Therefore, the processor **204** may use the data received from a second IMU of the monitoring device **201** that is configured to measure velocity and/or acceleration associated with a golf swing for the iron-type golf club or the wood-type golf club (e.g., an IMU that may be less sensitive to small changes in velocity and/or acceleration (as compared with the first IMU) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s²)) and discard the data from other IMU(s).

According to additional aspects of the disclosure, the processor **204** may be configured to receive data from each (or more than one) of the IMUs in the monitoring device **201** and compare that data with predetermined values or ranges to determine the data from which IMU to use for a particular purpose. For example, as discussed above with regard to FIGS. 19A and 19B, the acceleration and angular velocity for a putting stroke may be have a particular graphical range or "signature." Similarly, as discussed above with regard to FIGS. 19C and 19D, the acceleration and angular velocity for a golf swing associated with a driver may have a particular graphical range or "signature." Such graphical range or "sig-

nature" may be stored in a memory which the processor **204** may access. Therefore, in some embodiments of the disclosure, the processor **204** may be configured to receive data from each of the IMUs in the monitoring device **201** and compare that data with the stored graphical ranges or "signatures." If the data matches a particular graphical range or "signature" associated with the putting stroke, the processor may determine that the swing was a putting stroke and accordingly use data from a first IMU in making particular calculations (or transmitting that data to the remote computer). Alternatively, if the data matches particular graphical range or "signature" associated with a swing of a driver, the processor may determine that the swing was associated with a driver and accordingly use data from a second IMU in making particular calculations (or transmitting that data to the remote computer). It is noted that while the above embodiment discusses graphical ranges or "signatures" other data could be used instead (e.g., numerical ranges or values may be used as "signatures"). Further, it is noted that tolerances may be incorporated into the comparison of the collected data with saved values, ranges, "signatures", etc. such that the collected data does not have to match exactly in order for the swing to be identified. For example, either the processor **204** may be configured to account for a predefined tolerance when comparing the data with the saved values, ranges, "signatures", etc. or the saved values, ranges, "signatures", etc. may already include a predefined tolerance. Accordingly, if the receive data from each of the IMUs in the monitoring device **201** does not exactly match the signature of a particular predetermined swing with a predetermined club, but is still within a tolerance or predetermined range of the particular predetermined swing with a particular club, then the monitoring device **201** may be configured to identify the club with which pending swing was produced as the particular club associated with the signature.

It is noted that while a swing with a driver and a stroke with a putter are described above, such features (e.g., signatures, predetermined ranges for particular swings, etc.) may be used for any type of golf club (or other sporting equipment as described below).

If the data indicates that a characteristic is above a predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a corresponding, predefined IMU as the determined data (and perhaps discard the data from the other IMU(s)). Conversely, if the data indicates that a characteristic is below that predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a second corresponding, predefined IMU as the determined data (and perhaps discard the data from the other IMU(s)).

It is noted that the above described aspects of having the processor (or other firmware) receive data from each of the IMUs and then use the data to determine with which type of club the monitoring device **201** is engaged (and thereby determine which of the particular IMU's data to use and/or transmit) may be applied to or used in combination with the other features in the other embodiments described herein. For example, in the above described embodiments, which include prongs and detecting switches to determine with which type of club the monitoring device **201** is engaged, the processor (or other firmware) may still collected data from each IMU and then use or transmit such data accordingly. For example, data from each IMU may still be relevant for various characteristics of the golf swing and even though data from one IMU is selected for determining a particular characteristic based on the above described methods, data from other IMUs may still be used for determining other characteristics and/or transmitted to the remote device.

The above discussed embodiments do not preclude other means of allowing the monitoring device **201** to selectively determine which of the IMUs of the monitoring device **201** to use in capturing data associated with the golf stroke. Instead, other methods and means may be used as well.

For example, while the above discussed embodiments describe features which “automatically” determine which of the IMUs of the monitoring device **201** to use in capturing data associated with the golf stroke (i.e., without the user taking an affirmative step to manually choose between the different IMUs), this should not be interpreted to mean that embodiments which allow the user to manually determine and select which of the IMUs of the monitoring device **201** to use in capturing data associated with the golf stroke are precluded. Instead, according to aspects of the disclosure, the monitoring device **201** may be configured to receive instructions from the user to use a particular IMU of the monitoring device **201** to use in capturing data associated with the golf stroke.

For example, according to an embodiment of the disclosure, the monitoring device **201** could include a switch which the user can manually move between different positions. Further, the processor **204** of the monitoring device **201** may be configured to interpret the different positions of the switch as instruction to use a particular IMU (e.g., the first IMU instead of the second IMU) in capturing data associated with the golf stroke.

Alternatively, the processor **204** of the monitoring device **201** could receive instructions from the remote computer **400** discussed above, to use a particular IMU (e.g., the first IMU instead of the second IMU) in capturing data associated with the golf stroke. For example, the particular IMU (e.g., the first IMU instead of the second IMU) whose data is collected and used may be chosen by the user affirmatively instructing the processor **204** via the remote computer **400**. Alternatively, the particular IMU (e.g., the first IMU instead of the second IMU) whose data is collected and used may be chosen/dictated by the particular software application being run by the remote computer. In other words, a particular software application may require that data from first IMU instead of a second IMU to be used to calculate the particular value (even though data from the second IMU may still be collected and stored or used for other purposes). For example, the application directed to determining driver angular velocity may specify that the processor **204** use data from the first IMU instead of the data from the second IMU. It is noted that such instructions could be stored in the memory until the monitoring unit **201** receives other instructions which override such instructions.

Voice Commands

Alternatively, the particular IMU (e.g., the first IMU instead of the second IMU) whose data is collected and used may be chosen/dictated by the user through voice commands. For example, the remote computer **400** (e.g., a mobile telephone, such as a smart phone as described above) may be positioned near the golfer when the golfer is preparing to make a golf shot. The remote computer **400** may include a particular software application that transmits instructions to the processor of the monitoring device **201** to use a particular IMU (e.g., the first IMU instead of the second IMU) based on the remote computer **400** receiving a predetermined voice command. For example, the remote computer **400** may have voice recognition software which interprets the golfer’s command of “Driver”, “I am using a driver” of other predetermined phrases as an instruction to transmit data to the remote computer **400** to use a first IMU. Further, the remote computer **400** may interpret the golfer’s command of “Putter”, “I am using a putter” of other predetermined phrases as an

instruction to transmit data to the remote computer **400** to use a second IMU. Alternatively, the golf club **100** itself could be configured to have the voice recognition software and a microphone for receiving the voice commands. Hence, in such an embodiment, the golf club **100** itself may receive the voice commands and interpret them to activate or use a particular IMU (e.g., the first IMU instead of the second IMU).

As described in the above discussed embodiments, according to aspects of the disclosure, one of the IMUs in the monitoring device **201** is used in capturing data associated with the golf stroke. In some embodiments, this may include receiving data from each IMU in the monitoring device **201** and then using or transferring the data collected from only the selected IMU (i.e., selected according to one of the above described embodiments).

Alternatively, according to aspects of the disclosure, selecting one of the IMUs in the monitoring device **201** to be used in capturing data associated with the golf stroke includes using and transferring the data collected from each of the IMUs and then specifying in the data transmission to the remote computer **400** which data in the transmission is the data from the selected IMU.

Alternatively, the remote computer **400** may receive the data and be configured to determine which data is from the selected IMU. Alternatively, according to aspects of the disclosure, selecting one of the IMUs in the monitoring device **201** to be used in capturing data associated with the golf stroke includes determining data with only a single IMU (e.g., the IMU selected according to one of the above described embodiments) and not determining data with the other IMU(s). For example, the other IMUs may not be activated. Further, it is noted that various combinations of the above described embodiments of selecting one of the IMUs in the monitoring device **201** to be used in capturing data associated with the golf stroke may be used.

It is noted that while the measured characteristics described above have related to velocity, position, orientation, angular velocity, acceleration and angular acceleration, the above described features are not limited to measuring these feature and other characteristics of the golf stroke may be measured as well. Also, it is noted that regardless of how the IMU in the monitoring device **201** that is to be used in capturing data associated with the golf stroke is selected, once the IMU is selected, data can be determined, processed, transmitted, etc. according to any of the above discussed aspects of the disclosure.

Single IMU with Different Sensitivity Ranges

It is noted that while the above embodiments describe choosing to use a particular IMU (e.g., a first IMU instead of a second IMU) to collect data or, alternatively, receiving data from more than one IMU and choosing to use data from a particular IMU (e.g., a first IMU instead of a second IMU), other aspects of the disclosure relate to a monitoring device **201** which includes an IMU which has more than one sensitivity range. Therefore, rather than selectively choosing between different IMUs or between data from different IMUs, aspects of the disclosure are directed to selectively choosing between different sensitivity ranges in a single IMU. For example, aspects of the disclosure relate to a single IMU which includes a first sensitivity range configured to measure angular velocity and/or acceleration and may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s²). Such a sensitivity range may be beneficial in determining characteristics associated with a putting stroke. Further, the IMU may include a second sensitivity range configured to measure

velocity and/or acceleration and may be less sensitive to small changes in velocity and/or acceleration (as compared with the first sensitivity range) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s^2). Such a sensitivity range may be beneficial in determining characteristics associated with a golf swing for an iron-type golf club or a wood-type golf club. Therefore, according to aspects of the disclosure a single monitoring device **201** may be configured to include a first IMU which is both directed to determining data associated with a putting stroke and is also directed to determining data associated with a golf swing for an iron-type golf club or a wood-type golf club.

Aspects of the disclosure are directed to a monitoring device **201** which is configured to choose a particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range). Any of the above described methods for choosing to use a particular IMU (e.g., a first IMU instead of a second IMU) to collect data or, alternatively, receiving data from more than one IMU and choosing to use data from a particular IMU (e.g., a first IMU instead of a second IMU), may be used to select the particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range) of the single variable IMU. For example, selecting the particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range) of the single variable IMU may be done via the above described: structural engagement (e.g., protrusions **200p** activating detection switches), RFID techniques, based on the movement of the golf club (e.g., if the signature of the current swing matches, or falls within a tolerance of, a predetermined signature stored in a memory), commands from the remote computer **400** (e.g., manual commands, such as voice commands, automatic commands from a software application), manual commands based on activation of a switch on the club or monitoring device itself, etc. “Waking Up” Golf Club

According to aspects of the disclosure, the monitoring device **201** may be activated during insertion of the monitoring device **201** into golf club. Further, the monitoring device **201** may be continuously sensing and collecting data. However, according to other aspects of the disclosure, the monitoring device **201** may be selectively activated. For example, the monitoring device **201** may be configured to enter a “sleep” or “hibernation” state when the monitoring device has not been active for a predetermined amount of time (e.g., 1 minute, 5 minutes, 1 or 5 seconds after the monitoring device **201** determines that golf shot is completed (as will be described below), etc.). It is noted that in some embodiments, the IMU of the monitoring device **201** may recognize that the golf club has been held in an inverted state for a predetermined amount of time (e.g., indicating that the golf club has been placed in the golf bag) and enter a “sleep” or “hibernation” state once that predetermined amount of time has elapsed. In this “sleep” or “hibernation” state only the components needed for determining activation of the monitoring device **201** may continue to receive power. In other embodiments of the “sleep” or “hibernation” state, components may receive less power than they do in a use state. Further, the monitoring device may be selectively activated manually, or automatically upon the occurrence of an event (e.g., movement of the club or movement of the club in a particular fashion, such as a pre-shot routine). Other structures for detecting “sleep” or “hibernation” may be associated with the golf club **100** as well.

For example, in an illustrative embodiment of the disclosure, the movement of the club may act as a trigger to cause the monitoring device **201** to exit the “sleep” or “hibernation”

state and/or fully activate (i.e., “wake up”). For example, the monitoring device **201** may be configured to receive data from the IMUs that the golf club has been moved and based on the data exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). According to aspects of the disclosure, the monitoring device **201** may be configured to compare the data from the IMUs with a predetermined threshold and only exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”) if the data from the IMUs is above the predetermined threshold. For example, the data from the IMUs must be above a predetermined angular velocity or acceleration in order to “wake up” the monitoring device **201**. In this way, incidental movement (e.g., golf clubs jostling in the golf bag while being carried) will not “wake up” the monitoring device **201**.

In an illustrative embodiment of the disclosure, the predetermined movement of the club may act as a trigger to cause the monitoring device **201** to exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). For example, as discussed above, the monitoring device **201** may be configured to receive data from the IMUs that the golf club has been moved in a predetermined movement (e.g., a pre-shot routine) and based on the data, exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). According to aspects of the disclosure, the monitoring device **201** may be configured to compare the data from the IMUs with a predetermined range(s) or value(s) (e.g., such as the above discussed graphical or numerical range or signatures which indicate a driver swing or putting stroke) and only exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”) if the data from the IMUs is above the predetermined threshold. For example, the predetermined range(s) or value(s) may be a “signature” which indicates a practice swing. Therefore, when the data from the IMUs match (or are within a tolerance or the signature) the monitoring device **201** “wakes up”.

In another illustrative embodiment, the user may manually cause the monitoring device **201** to enter to exit the “sleep” or “hibernation” state. For example, the user may use the remote computer **400** (e.g., a smart phone with a software application that configures the smartphone to receive and transmit data to the monitoring device **201**) to cause the monitoring device to enter or to exit the “sleep” or “hibernation” state. This could be done by inputting data to the smartphone (e.g., voice commands or touching a touch screen) which instructs the monitoring device **201** to enter or to exit the “sleep” or “hibernation” state.

Zeroing

According to aspects of the disclosure, similar methods may be used to correlate data to a particular swing and, thereby, indicate individual golf swings/distinguish between different golf swings. For example, in embodiments where the monitoring device **201** may be activated and continually receiving data from the IMUs during the entire time the monitoring device **201** is activated, aspects of the disclosure are directed to correlating data for a particular golf stroke (e.g., as distinguished from a practice swing or movement not related to the swing, such as when the club is removed from the bag or being carried to the location of the shot).

According to particular aspects of the disclosure, the pre-shot routine (e.g., the end of a pre-shot routine) may “zero” the monitoring device **201** (i.e., cause the monitoring device **201** to recognize that the upcoming movement is the beginning of an individual golf swing). For example, as discussed above, the monitoring device **201** may be configured to receive data from the IMUs that the golf club has been moved in a predetermined movement, such as pre-shot routine. The monitoring device **201** may be configured to recognize the

predetermined range(s) or value(s) as the “signature” which indicates the pre-shot routine and determine that any movement after (or subsequent to a predetermined time after) the recognized pre-shot routine is part of golf swing or stroke. Accordingly, only movement of the golf club after (or subsequent to a predetermined time after) the pre-shot routine will be correlated with the particular golf stroke. In other words, only movement of the golf club which occurs after the IMUs provide data to the monitoring device **201** that the golf club is at rest in the address position after having completed the pre-shot routine will be correlated with the particular golf stroke.

It is noted that the monitoring device **201** may be configured to account for, or include, a predetermined time after the pre-shot routine is completed and after the golf swing is completed in determining which data is related to the golf swing or stroke. For example, the monitoring device **201** may be configured to allow for a predetermined time (e.g., 1 or 2 seconds) once the monitoring device **201** has determined that the pre-shot routine has been completed (i.e., the IMUs provide data to the monitoring device **201** that the golf club is at rest in the address position after having completed the pre-shot routine) before beginning to associate data with the particular golf stroke. Similarly, the monitoring device **201** may be configured to allow for a predetermined time (e.g., 1 or 2 seconds) once the monitoring device **201** has determined that the golf swing or stroke has been completed (i.e., the IMUs provide data to the monitoring device **201** that the golf club has completed the stroke (e.g., the follow through of the golf swing or stroke has been completed) as defined by the stored signature of the typical swing or stroke) before ending the association data with the particular golf stroke.

In some embodiments, the pre-shot routine may include one or more practice swings. Further, it is noted that the pre-shot routine may be customized to the particular golfer. For example, the pre-shot routine may include one or more “waggles” of the golf club after the one or more practices swing(s) and prior to the golf club coming to rest in the address position after having completed the pre-shot routine depending on the particular golfer’s habits. It is further understood that the pre-shot routine could comprise a combination of practice swings, waggles etc. and also could comprise holding the golf club **100** stationary at the address position for a predetermined amount of time. Such information regarding the pre-shot routine may be stored on in the monitoring device. For example, the particular signature of a golfer’s pre-shot routine may be stored to the monitoring device **201** (e.g., uploaded to the memory of the monitoring device **201** via the remote computer **400** or the remote computer **400** could instruct the monitoring device **201** to record data from the IMU for a particular amount during which the golfer performs the pre-shot routine and then store the recorded data as the signature of the pre-shot routine). According to aspects of the disclosure, a the monitoring device **201** may be configured to determine a practice swing as a swing whose signature is within a particular range relative to the signature of an actual swing. For example, a practice swing may be defined as a predetermined amount or range which corresponds to predetermined value (e.g., 70% of the angular velocity of an actual swing or 70% of the radial length of an actual swing). Alternatively, a practice swing may be defined with its own digital signature which identifies the swing as a practice swing as described above.

According to some embodiments of the disclosure, the golfer may manually correlate data to a particular swing and, thereby, indicate individual golf swings/distinguish between different golf swings. For example, the golfer may activate a

switch which “zeros” the monitoring device **201** (i.e., cause the monitoring device **201** to recognize that the upcoming movement is the beginning of an individual golf swing). For example, the golfer may activate a switch on the golf club itself the transmits information to the monitoring device **201** that causes the monitoring device **201** to recognize that the upcoming movement is the beginning of an individual golf swing. Further, the golfer may activate a switch on the remote computer **400** (e.g., pressing a button on a smart phone) that causes the monitoring device **201** to recognize that the upcoming movement is the beginning of an individual golf swing. Further, the golfer may use voice commands to zero the monitoring device **201**. For example, the remote computer **400** (e.g., a smart phone) may be configured to receive the voice commands from the golfer and transmit data to the monitoring device which indicates the beginning and end of the golf shot. For instance, the remote computer **400** may be configured to interpret the golfer saying “begin” or “start” as the beginning of the golf shot and transmit instructions to the remote computer to begin recording data from the IMUs or being associating data from the IMUs as a particular, individual golf shot. Conversely, the remote computer **400** may be configured to interpret the golfer saying “done” or “end” as the end of the golf shot and transmit instructions to the remote computer to stop recording data from the IMUs or stop associating data from the IMUs as a particular, individual golf shot. Other structures are possible such as sensors located in the grip of the golf club that are configured to detect a squeeze or tightened grip by the user for activation.

In some embodiments of the disclosure impact sensors such as described above may be used to determine a recordable golf shot. For example, if a particular swing has characteristics which resemble both a practice swing and an actual swing (e.g., above a threshold angular velocity), the monitoring device **201** may be configured to receive data from an impact sensor which indicates whether impact with the golf ball was made during the golf swing. In such embodiments, the occurrence of an impact may serve as validating that the swing should not be interpreted as a practice swing, but instead a particular golf swing for which characteristics of the swing should be measured/determined.

Charging

According to aspects of the disclosure, the monitoring device **201** may be configured to be charged. As described above, the monitoring device **201** may include a power supply (e.g., a battery). Further, the monitoring device **201** may be configured to receive a charging cable which will provide power to recharge the power supply. In some embodiments, the monitoring device **201** may be configured to receive the charging cable while the monitoring device **201** is in the golf club itself. For example, in embodiments where the monitoring device **201** is positioned in the shaft/grip of the golf club, the end of the golf club may be removed and the charging cable may be hooked into the monitoring device **201**.

Alternatively, according to aspects of the disclosure, the monitoring device **201** may be configured to be charged via induction charging.

According to aspects of the disclosure, the monitoring device **201** is configured to receive information via a charging cable. For example, the charging cable may be a USB cable which is configured to connect the monitoring device **201** with computer (e.g., the remote computer **400**) or other data source. Accordingly, during the connected with the computer, the monitoring device **201** can update firmware, reboot the system, and conduct other diagnostic checks and updates as needed or instructed.

Sensor Determines if it has been Put in Backwards

As discussed above, according to aspects of the disclosure, the data from sensors in the monitoring device **201** may be subjected to a transformation matrix which manipulates the data (e.g., recalculates or modifies the data) in order to account for the exact positioning of the sensor within the golf club. As discussed, the transformation matrix may be a series of calculations which modifies that data according to the exact positioning of the sensor within the golf club. Therefore, in an embodiment such as discussed above, wherein the monitoring device **201** (which includes the sensors) is positioned in the grip **105** or the shaft of the golf club, the data from the sensors of the monitoring device may be subjected to a transformation matrix in order to provide feedback to the golfer.

As discussed above, the transformation matrix may be included in a software package that may be downloaded to the remote computer **400** to which the data from the monitoring device **201** is transmitted. Alternatively, according to some aspects of the disclosure, the transformation matrix may be included as firmware in the monitoring device **201** (e.g., in the memory of the monitoring device). As discussed above, such transformation matrices may be designed for the specific positions of sensors and remote monitoring devices **201** in the respective golf clubs. Accordingly, if the sensor is not provided in the appropriate location, the feedback may be incorrect. For example, if the monitoring device **201** is inserted into the removable section **200** in an orientation that is different from the intended position (e.g., inverted from the intended position or backwards to the intended position), the sensors within the monitoring device **200** may provide inaccurate data to the transformation matrix.

Hence, as described above, according to some embodiments of the disclosure, the grips **105** or the removable section **201** are configured with structure that prevents the monitoring device **201** from being inserted into the removable section **200** or the grip **105** in an orientation other than the intended orientation. However, according to embodiments of the disclosure (e.g., which do not have such structure), when the monitoring device **201** is inserted into the removable section **200** in an orientation that is different from the intended position, the monitoring device **201** can be configured to recognize the incorrect positioning of the monitoring device **201**. Further, according to aspects of the disclosure, when the monitoring device **201** recognizes the incorrect positioning of the monitoring device **201**, the monitoring device may be configured to correct the data by applying an alternate transformation matrix to the data (e.g., prior to transmitting the data to the remote computer **400**).

For example, according to aspects of the disclosure, the memory in the monitoring device may be configured to store a predetermined range of values which correspond to “acceptable” values for the data received from the sensors when the monitoring device is positioned in the correct position and orientation. If the processor receives data from the sensors, compares the data with the “acceptable” range of values and determines that the data is outside the range of “acceptable” values, the processor **204** may be configured to determine that the monitoring device **201** is in an incorrect orientation. Upon recognizing that the monitoring device **201** is positioned in an incorrect orientation, the monitoring device may receive that data and apply a transformation matrix to the data in order to correct the data.

For example, if the monitoring device **201** is inserted into the removable section **200** inverted from the intended position, the monitoring device **201** may receive data from the one or more sensors, compare the received data with the “acceptable” range of values and determine that the data is outside the

range of “acceptable” values. According to aspects of the disclosure, the processor may then access a transformation matrix from the memory, wherein the transformation matrix accounts for the altered distance of the sensors in the inverted state as compared with the intended positioning of sensors. The process may then apply such a transformation matrix to the data to thereby calculate “correct” feedback (i.e., the corrected data may be used according to the above described methods for calculations to determine properties and characteristics associated with a swing to the user), even though the monitoring device **201** is still in the “incorrect” (e.g., inverted) orientation. Thereafter, in some embodiments the processor may cause the data to be transmitted to the remote computer **400**. Further, according to some aspects of the disclosure, upon the monitoring device **201** recognizing that it is positioned in an “incorrect” orientation, it may send a message to the remote computer indicating such, in order to provide notification to the user. This message could be in addition to, or as an alternative to, providing the correct feedback and data from the transformation matrix described above.

It is noted that, if desired, the above described corrective transformation matrix which is configured to account for incorrect positioning of the sensor(s) may be used in conjunction with the previously discussed transformation matrices specific to the individual golf club which recalculate the obtained data (obtained by the sensors of the remote monitoring device(s) **201** in that particular golf club) and output accurate measurements, golf metrics, variables and kinematics. Further, it is noted that these previously discussed transformation matrices may also be firmware stored in the monitoring device **201** instead of software downloaded onto the remote computer. In this way, feedback may be calculated by the processor **204** in the monitoring device **201** and then transmitted to the remote computer **400**. Further, such feedback could include an identification of the club from which it is being transmitted.

Left Vs. Right Hand Golf Clubs

According to aspects of the disclosure, similar features may be used to differentiate between left handed golf clubs and right handed golf clubs. For example, according to aspects of the disclosure, left handed golf clubs may have a structure (e.g., a removable section) which is configured to receive the monitoring device **201** in a first orientation. In contrast, right handed golf clubs may have a structure (e.g., a removable section) which is configured to receive the monitoring device **201** in a second orientation different from the first orientation of that for left handed golf clubs. As described above, when the monitoring device **201** is inserted into the removable section in the first orientation, the monitoring device **201** can be configured to recognize the first orientation of the monitoring device **201** and determine that the golf club is a left handed golf club. Further, when the monitoring device **201** is inserted into the removable section in the second orientation, the monitoring device **201** can be configured to recognize the second orientation of the monitoring device **201** and determine that the golf club is a right handed golf club.

Hence, according to aspects of the disclosure, the monitoring device **201** may be configured to distinguish between a right handed golf club and a left handed golf club. Further, according to aspects of the disclosure, when the monitoring device **201** recognizes the orientation of the monitoring device **201**, the monitoring device **201** may be configured to manipulate the data from the sensors (e.g., by applying a particular transformation matrix to the data (e.g., prior to transmitting the data to the remote computer **400**)).

It is noted that, according to aspects of the disclosure, other methods in which the monitoring device **201** distinguishes between a right handed golf club and a left handed golf club may be used as well. For example, the protrusions **200p** discussed above could be configured to engage with and activate detection switches which indicate whether the club is right handed or left handed. Additionally, the RFID methods of identifying a club may include right handed and left handed information regarding the particular club.

End Cap that Goes into Grip

According to aspects of the disclosure, a set of golf clubs which are configured to receive and hold a monitoring device (such as monitoring device **201** described above) may be configured such that each of the golf clubs in the set secures its respective monitoring device **201** at a common point relative to each of the golf clubs in the set. Further, according to aspects of the disclosure, each of the golf clubs in the set may be configured to secure its respective monitoring device **201**, such that the monitoring device **201** is offset by a specified distance from a reference point which is common to each of the golf clubs in the set. The specified distance from the reference point may be identical for each of the clubs.

For example, according to an illustrative embodiment of the disclosure, each of the golf clubs in the set may be configured to position the monitoring device **201** such that it is located a distance X (e.g., 20 inches) from the center of mass of the respective golf club. The center of mass of the golf club is the point (e.g., a point in space) wherein the entire mass of the golf club is concentrated. For a golf club (as with all rigid bodies), the center of mass is a fixed point in relation to the golf club. In a set of golf clubs, which includes different types of golf clubs (e.g., a 14 club set of the golf clubs which includes putter, iron-type golf club heads, wood type golf club heads, etc.) the center of mass of each of the different golf clubs will be different. Accordingly, in such an embodiment, each golf club in the set may have the monitoring device **201** secured at a different position along its respective shaft, however, the distance between the monitoring device **201** in each golf club and the fixed center of mass of each golf club would be constant (e.g., 20 inches from the center of mass of the respective golf club).

FIG. 22 illustrates an example set of golf clubs according to aspects of the disclosure. As seen in FIG. 22, a shorter club, such as a wedge (e.g., a pitching wedge) **2200** has a center of mass indicated by the point **2200a**. Further, the point where the monitoring device **201** is located is indicated by the point **2200b**. Similarly, a longer club, such as a hybrid club **2201**, has a center of mass indicated by the point **2201a**. Further, the point where the monitoring device **201** is located is indicated by the point **2201b**. Also, an even longer club of the set, such as a driver **2202**, has a center of mass indicated by the point **2202a**. Further, the point where the monitoring device **201** is located is indicated by the point **2202b**. As seen in FIG. 22, the distance between the center of mass for each of the respective clubs and the positioning of monitoring devices **201** for each of the respective clubs is indicated by the lines drawn between the points. This distance is identical for each of the clubs **2200**, **2201** and **2202**.

The above described feature of positioning the monitoring device **201** in each of the golf clubs in the set such that the monitoring device **201** is offset by the identical specified distance from a reference point which is common to each of the golf clubs in the set may be accomplished in many ways according to aspects of the disclosure. For example, as described above, each of the golf clubs in the set of golf clubs may include a removable section **200** of the type discussed above with regard to FIGS. 8 and 8A that is configured to be

engaged with the grip **105** of the respective golf club. Further, as discussed above the removable section **200** may be configured to receive the monitoring device **201** wherein according to particular embodiments of the disclosure, the monitoring device **201** may be similar to those used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg.

As seen in FIGS. 21A and B, the removable section **200** may include a circular portion which forms the top of the shaft and, also, an elongated portion configured to house the monitoring device **201**. According to aspects of the disclosure, the elongated portion of the removable section **200** may include guides to aid in positioning and securing the monitoring device **201** within the removable section **200**. It is noted that the removable section **200** may be configured to secure the monitoring device **201** in such a way that the monitoring device **201** does not move within the removable section **200**. For example, the removable section **200** may be configured to engage with the monitoring device **201** (e.g., a compartment which includes the exterior of the monitoring device **201**) via press fitting, snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), mechanical fasteners, etc. For example, the elongated portion may include a first arched end configured to engage a first rounded end of the compartment, a second arched end configured to engage a second rounded end of the compartment and a back portion which extends between the first arched portion and the second arched portion and is configured to engage a side of the compartment. In this way, the removable section **200** may be configured to support and stabilize the monitoring device **201**. For example, the elongate portion may be configured to secure the compartment which may be rectangular with first and second rounded ends and have a length in the range of 1.0-1.5 inches, a width of 0.4-1.0 inches and thickness of 0.2-0.45 inches.

According to aspects of the disclosure, the elongate portion of the removable section **200** may be configured to have a particular length such that when the removable section **200** is engaged with the grip of the golf club, the removable section **200** positions the monitoring device **201** within the shaft such that the monitoring device **201** is offset by a specified distance from a reference point. For example, according to one embodiment, the elongate portion of the removable section **200** may include the first arched end configured to engage a first rounded end of the compartment, the second arched end configured to engage a second rounded end of the compartment and the back portion which extends between the first arched portion and the second arched portion and is configured to engage a side of the compartment, but the first arched end, second arched end and back portion are spaced further away from the round portion of the removable section which forms the end cap. For example, the first arched end, second arched end and back portion may be spaced from the round portion by a section of the elongate portion that extends between the round portion and the upper arched end of the guide for receiving the monitoring device.

The section of the elongate portion that extends between the round portion and the upper arched end of the guide may be a particular length such that when the removable section **200** is engaged with the shaft, of the golf club, the removable section **200** positions the monitoring device **201** within the shaft such that the monitoring device **201** is offset by a specified distance from a reference point. Further, as each different golf club in the set of golf club has a center of mass that is in a different location than the other golf clubs in the set, the removable section **200** associated with each of the respective, different golf clubs in the set may have to be configured

61

differently in order to ensure the that the respective monitoring device **201** is positioned within the shaft, such that the monitoring device **201** is offset by a specified distance from a reference point. For example, the length of the section of the elongate portion that extends between the round portion and the upper arched end of the guide may be a different for each of the respective removable sections **200** in the golf club set in order to ensure the that the respective monitoring device **201** is positioned within the shaft, such that the monitoring device **201** is offset by a specified distance from a reference point.

FIG. **23A** illustrates embodiments of such removable sections **201**. As seen in FIG. **23**, according to a particular embodiment of the disclosure, a first removable section **200** associated with a first golf club of the set of golf clubs may have a first elongate portion that has a first length, while a second removable section **200** associated with a second, different golf club of the set of golf clubs may have a second elongate portion that has a second length which is different (e.g., longer) from the first length. Further, as seen in FIG. **23A**, according to a particular embodiment of the disclosure, a third removable section **200** associated with a third, different golf club of the set of golf clubs may have a third elongate portion that has a third length, which is different (e.g., longer) than the first or second lengths. For example, a shorter club (e.g., a pitching wedge) may have the removable section **200** with the elongate portion that has the first length while a longer club (e.g., a long iron or hybrid type golf club) may have the removable section **200** with the elongate portion that has the second length. Further, an even longer club (e.g., a driver) may have the removable section **200** with the elongate portion that has the third length. It is noted that while only three embodiments are shown in FIG. **23A**, each of the golf clubs in the set could have a removable section **200** with an elongated portion of a different length (e.g., increasing longer as the length of the club increases) in order to position the monitoring device **201** in the correct positioning.

For example, as seen in FIG. **23B**, the wedge **2200** (e.g., pitching wedge) may have a removable section **200** with the elongate portion that has the first length. The hybrid club **2201** may have a removable section **200** with the elongate portion that has the second length. The wood-type club **2201** (e.g., a driver) may have the removable section **200** with the elongate portion that has the third length. As seen in FIG. **22**, the third length of the elongate portion of the removable section **200** associated with the wood-type club **2202** is longer than the second length of the elongate portion of the removable section **200** associated with the hybrid **2201**. Further, the second length of the elongate portion of the removable section **200** associated with the hybrid **2201** is longer than the first length of the elongate portion of the removable section **200** associated with the wedge **2200**.

As seen in FIGS. **23A** and **B**, each of the removable sections **201** are configured (e.g., the length of the elongate portion of the removable sections is configured) in order to ensure the that the respective monitoring device **201** is positioned within the shaft, such that the monitoring device **201** is offset by an identical specified distance from a reference point. In this case, the monitoring devices **201** of the wedge, the hybrid **2201** and the wood-type club **2202** are positioned such that they are offset by an identical specified distance from the center of mass of the respective golf club. While only three club of the set are illustrated, it is understood that similar structures may be applied to each of the golf clubs in the set. For example, the removable section **200** of each of a lob wedge, sand wedge, pitching wedge, 10 iron and 9 iron of a set of golf clubs may have an elongated portion of a different

62

length (e.g., increasing longer as the length of the club increases) in order to position the monitoring device **201** in the correct positioning.

According to other embodiments of the disclosure, the removable sections **200** may have other structures as well. For example, according to some embodiments of the disclosure, the removable sections **200** may be a self-locating, conical structure in which the monitoring device **201** is received. The conical structure may be configured to engage with the interior of the shaft **103** of the golf club **100** in order to position the monitoring device **201** in the appropriate position within the shaft **103**. For example, the multitude of conical removable sections **200** for engagement with the different clubs in a set of golf clubs may be longer and wider (e.g., have an increased diameter) to position the monitoring device **201** in the appropriate position within the shaft **103**. According to some embodiments of the disclosure, the interior of the golf club shaft **103** may include a structured (e.g., positioning recesses/protrusions or ledges) which are configured to engage with the removable sections **200** and position the monitoring device **201** in the appropriate position within the shaft **103**.

While the concept of a set of golf clubs in which each club may be configured such that it secures its respective monitoring device **201** at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set) has been illustrated with respect to a removable section **200**, it is noted that other means may be used as well.

For example, instead of a removable section configured as described above, a plurality of inserts with other structures that hold the monitoring device **201** may be employed to achieve the above described goal. For example, one or more of the inserts may each have varying lengths which are based on the golf club with which the inserts are associated such that the inserts secures its respective monitoring device **201** at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set). The particular structure of the group of inserts may vary provided the group of inserts achieves the above recited goal of securing its respective monitoring device **201** at a common point respective to each of the golf clubs in the set.

While the concept of a set of golf clubs in which each club may be configured such that it secures its respective monitoring device **201** at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set) has been illustrated with respect to removable sections and inserts, it is noted that the grip **105** itself may be configured to receive and secure the monitoring device **201** directly, without the inclusion of a separate removable section or cartridge **200**.

For example, as discussed with regard to FIG. **9**, the grip **105** may be configured with an opening at its terminal end that is configured to receive the monitoring device **201**. For example, the grip **105** may include a slit that is configured to receive the monitoring device **201** when the monitoring device **201** is inserted into the grip along the monitoring device's longitudinal axis. The slit may be configured to provide a tight interference fit with the monitoring device **201**. Further, the one or more of the slits may each have varying depths that are based on their respective golf clubs. In this way, the depth of the slits may be configured such that

63

each of the slits secures the monitoring device **201** it receives at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set).

It is noted that monitoring device **201** may be configured to engage with the grip **105** via other methods as well, including snap fit mechanisms (e.g., spring loaded protrusions and corresponding detents), other mechanical fasteners, etc. provided that the respective monitoring devices **201** are secured at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set).

It is noted that while the center of mass has been discussed above with respect to the illustrative embodiments, this is not meant to suggest that other reference points may be used. On the contrary, other fixed reference points of the golf club, such as the center of gravity of the club head, the hosel, the top of the grip, etc. may be used as well.

It is noted that by providing a set of golf clubs in which each golf club secures its respective monitoring device **201** at a common point respective to each of the golf clubs in the set (e.g., such that the monitoring device **201** is offset by an identical specified distance from a reference point which is common to each of the golf clubs in the set), the data received from each monitor device **201** can be interpreted relative to the common reference point. For example, in an embodiment wherein the reference point is the center of mass, each of the monitoring devices **201** in the golf clubs may be offset from the center of mass of the respective golf club by an identical distance. Hence, in calculating data (e.g., such as when using transformation matrices as discussed above) data can be interpreted without having to account for a different distance from the center of mass for each club. For example, in some embodiments of the disclosure, formulas and transformation matrices used to calculate data and provide feedback can be uniformly applied for the set of golf clubs.

It is noted that according to aspects of the disclosure, the structure of the golf club and/or the separate removable section or cartridge **200** may be configured so that the swing weight of the club may be chosen as desired. For example, the longer separate removable section or cartridge **200** described above may be formed of a material of a lighter weight/density than the shorter separate removable section or cartridge **200** described above. Further, the structure of the separate removable sections or cartridges may be varied throughout the set of golf clubs. For example, the longer separate removable sections or cartridges **200** may include openings to remove weight and the thickness of shorter separate removable sections or cartridges **200** may be increased to add weight. In these ways, consistency in the swing weight may be achieved throughout the set of golf clubs.

Calibration

Interchangeable Puck for Different Sports Equipment

As discussed above, a monitoring device **201** according to aspects of the disclosure may be “universal” with respect to the golf clubs in such a set of golf clubs. For example, the monitoring device **201** may be configured to fit in a putter of the golf club set, an iron-type golf club of the golf club set and in a wood-type golf club of the golf club set. According to further aspects of the disclosure, a monitoring device **201** may be “universal” with respect to other sports equipment. For example, a monitoring device **201** according to aspects of the disclosure may be “universal” with respect to the golf clubs, tennis racquets, bats (e.g., baseball, softball, cricket, etc.), hockey sticks (e.g., ice hockey, field hockey), lacrosse

64

sticks, etc. Thus, exemplary embodiments described herein are applicable to any implements that incorporate monitoring devices etc.

However, the characteristics to be measured for each piece of sports equipment may vary dramatically. For example, the rotation of the piece of sports equipment around its longitudinal axis may be more relevant in some sports than in others. For example, the rotation of a golf club around its longitudinal axis during a golf swing (e.g., which may be used to provide information about the angle club face throughout the swing) may be more valuable information for the user’s feedback than the rotation of a baseball bat around its longitudinal axis during a swing of the baseball bat. Similarly, the rotation of a tennis racquet around its longitudinal axis during a tennis stroke (e.g., which may provide information about the angle of the face of the tennis racquet throughout the swing) may be more valuable information for the user’s feedback than the rotation of a baseball bat around its longitudinal axis during a swing of the baseball bat.

Therefore, aspects of the disclosure are directed to a monitoring device **201** (and/or system) that is configured to determine different characteristics of a swing or stroke according on the type of sports equipment with which the monitoring device **201** is engaged. For example, aspects of the disclosure are directed to a monitoring device **201** (and/or system) that is configured with the ability to selectively collect particular data based on the type of sports equipment with which the monitoring device **201** is engaged. Further, according to aspects of the disclosure, the monitoring device **201** may be configured to automatically determine the type of sports equipment with which the monitoring device **201** is engaged and automatically configure itself to selectively collect particular data based on that type of sports equipment.

For example, according to aspects of the disclosure, if the monitoring device **201** (and/or system) determines that the monitoring device **201** is engaged with a golf club, the monitoring device **201** (and/or system) may configure itself to measure various characteristics, such as angular rotation about the longitudinal axis of the golf club. Further, the monitoring device **201** may configure itself to measure velocity, acceleration, etc. at a first rate (e.g., a first refresh rate). In contrast, according to aspects of the disclosure, if the monitoring device **201** (and/or system) determines that the monitoring device **201** is engaged with a baseball bat, the monitoring device **201** (and/or system) may configure to measure various characteristics that do not include angular rotation about the longitudinal axis of the baseball bat. Further, the monitoring device **201** may configure to measure velocity, acceleration, etc. at a second rate (e.g., a second refresh rate) which is different from the first rate used for the golf club. While these examples are merely illustrative, it is understood that according to aspects of the disclosure, the monitoring device **201** (and/or system) is configured to determine the piece of sports equipment with which the monitoring device **201** is engaged, differentiate that piece of sports equipment with which the monitoring device **201** is engaged from other pieces of sports equipment, change the characteristics that the monitoring device **201** will measure and/or the data the monitoring device **201** will collect based on the piece of sports equipment with which the monitoring device **201** is engaged.

Further, in addition to changing the characteristics that the monitoring device **201** will measure and/or the data the monitoring device **201** will collect based on the piece of sports equipment with which the monitoring device **201** is engaged, other aspects of the disclosure are directed to determining which of one or more IMUs in the piece of sports equipment to use in collecting data related to the swing or stroke. For

65

example, aspects of the disclosure are directed to selectively using data (e.g., for calculations such as described above) from the first IMU instead of the second IMU or the second IMU instead of the first IMU based on the type of sports equipment with which the monitoring device **201** is engaged.

Further aspects of the disclosure are directed to receiving data (related to the stroke or swing) collected from each (or more than one) of the IMUs in the sports equipment and then determining which of data from the one or more IMUs to use (e.g., use for calculations as will be described below) based on the type of sports equipment with which the monitoring device **201** is engaged. For example, the data from a particular IMU may be selected for use in calculations and/or for transmission to the remote computer **400** based on the data received from each of the IMUs and the type of sports equipment or other information indicated by the data received from each of the IMUs. In this way, the monitoring device **201** may switch between using and/or transmitting data from a first IMU and a second IMU based on data received from both IMUs.

It is noted that while the above embodiments describe choosing to use a particular IMU (e.g., a first IMU instead of a second IMU) to collect data or, alternatively, receiving data from more than one IMU and choosing to use data from a particular IMU (e.g., a first IMU instead of a second IMU), other aspects of the disclosure relate to a monitoring device **201** which includes an IMU which has more than one sensitivity range. Therefore, rather than selectively choosing between different IMUs or between data from different IMUs, aspects of the disclosure are directed to selectively choosing between different sensitivity ranges in a single IMU.

For example, aspects of the disclosure relate to a single IMU which includes a first sensitivity range configured to measure angular velocity and/or acceleration and may be extremely sensitive to small changes in velocity and/or acceleration (e.g., fractions of a meter per second or m/s^2). Such a sensitivity range may be beneficial in determining characteristics associated with a particular piece of sports equipment. Further, the IMU may include a second sensitivity range configured to measure velocity and/or acceleration and may be less sensitive to small changes in velocity and/or acceleration (as compared with the first sensitivity range) and able to more accurately determine larger changes in velocity and/or acceleration (e.g., at least several meters per second or m/s^2). Such a sensitivity range may be beneficial in determining characteristics associated with a different piece of sports equipment. Therefore, according to aspects of the disclosure a single monitoring device **201** may be configured to include a first IMU which is both directed to determining data associated with a piece of sports equipment and is also directed to determining data associated with a second piece of sports equipment.

Aspects of the disclosure are directed to a monitoring device **201** which is configured to choose a particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range). Any of the above or below described methods for choosing to use a particular IMU (e.g., a first IMU instead of a second IMU) to collect data or, alternatively, receiving data from more than one IMU and choosing to use data from a particular IMU (e.g., a first IMU instead of a second IMU), may be used to select the particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range) of the single variable IMU. For example, selecting the particular sensitivity range (e.g., a first sensitivity range instead of a second sensitivity range) of the single variable IMU may be done via the above described: structural

66

engagement (e.g., protrusions **200p** activating detection switches), RFID techniques, based on the movement of the sports equipment (e.g., if the signature of the current swing matches, or falls within a tolerance of, a predetermined signature stored in a memory), commands from the remote computer **400** (e.g., manual commands, such as voice commands, automatic commands from a software application), manual commands based on activation of a switch on the sports equipment or monitoring device itself, etc. It is noted that, as discussed above, the monitoring device **201** may be engaged with a golf club in any of the manners described above (e.g., removable section **200**, other types of inserts which hold the monitoring device **201**, the monitoring device **201** may be engaged directly with the grip of the grip club, etc.). According to aspects of the disclosure, and as shown in FIG. **24**, the monitoring device **201** may be engaged with the handle of a tennis racquet similarly to any of the manners described above (e.g., a similar removable section **200** configured to engage with the handle of the tennis racquet, other types of inserts which hold the monitoring device **201**, or the monitoring device **201** may be engaged directly with the handle of the tennis racquet). Further, according to aspects of the disclosure, and as shown in FIG. **24**, the monitoring device **201** may be engaged with the grip of a baseball bat or a hockey or lacrosse stick similarly to any of the manners described above (e.g., a similar removable sections **200** configured to engage with the grip of the baseball bat or hockey stick, other types of inserts which hold the monitoring device **201**, or the monitoring device **201** may be engaged directly with the grip of the baseball bat or hockey or lacrosse stick).

Further, as discussed above, aspects of the disclosure relate to determining the type of sports equipment with which the monitoring device **201** is engaged. According to one embodiment of the disclosure, the engagement between the monitoring device **201** and the particular piece of sports equipment causes the monitoring device **201** to determine the piece of sports equipment with which the monitoring device **201** is engaged and, further, configure the monitoring device **201** to select the particular characteristics it will measure and data it will collect.

By way of example, the grips or handles of each of the pieces of sports equipment (e.g., the golf clubs, tennis racquets, bats, hockey sticks, etc.) may be configured to receive the monitoring device **201** in a manner discussed above with regard to FIGS. **8-9**. For example, as discussed above, according to particular embodiments of the disclosure monitoring device **201** may be similar to those used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg. For example, as seen in FIGS. **4A** and **4B**, the monitoring device **201** may include a generally rectangular compartment which may be similar to the compartment used to house sensors used in the NIKE+™ athletic performance monitoring systems available from NIKE, Inc. of Beaverton, Oreg. Further the compartment of the monitoring device **201** may house various elements described above, such as the processor **204**, sensors **202**, transmitter **203**, power supply **206**, memory, etc. Further, as described above, according to aspects of the disclosure, the monitoring device **201** may be configured to engage with the grip **105** of the respective piece of sports equipment. For example, as described above, the grip **105** may be configured to receive a removable section or cartridge **200** and the removable section **200** may be configured to receive the monitoring device **201**.

According to aspects of the disclosure, the engagement between the monitoring device **201** and removable section **200** the particular piece of sports equipment may cause the

67

monitoring device **201** to determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, configure the monitoring device **201** to select the particular characteristics that the monitoring device **201** will measure and the data that monitoring device **201** will collect. For example, the engagement between the monitoring device **201** and removable section **200** may cause the monitoring device **201** to selectively activate different components of the monitoring device **201** (e.g., different IMUS) or collect data at different rates (e.g., slower or faster data refresh rates).

In one embodiment of the disclosure, the “universal” monitoring device **201** may be configured with one or more openings **201o** configured to receive one or more protrusions **200p** (e.g., prongs) that extend from the removable section **200** of the particular piece of sports equipment. According to aspects of the disclosure, the monitoring device **201** based on which of the openings **201o** in the monitoring device **201** receive a protrusion **200p** of the removable section **200**, the monitoring device **201** determines the piece of sports equipment with which the monitoring device **201** has been engaged and, further, is configured to select the particular characteristics it will measure and the data it will collect.

For example, the monitoring device **201** may include have plurality of **201o**. Further, a removable section **200** of one piece of sports equipment may have a set of protrusions **200p** that are configured to engage with some of the holes of the plurality of openings **201o** of monitoring device **201**. When that particular combination of opening **201o** is engaged by the respective protrusions **200p** of the removable section **200** of particular piece of sports equipment, the monitoring device **201** determines the piece of sports equipment with which the monitoring device **201** has been engaged and, further, is configured to select the particular characteristics it will measure and the data it will collect. Similarly, a removable section **200** of a second, different, piece of sports equipment may have a different set of protrusions **200p** that are configured to engage with some of the openings **201o** of the plurality of openings of monitoring device **201**. When that particular combination of openings **201o** is engaged by the respective protrusions **200p** of the removable section **200** of second, different piece of sports equipment, the monitoring device **201** determines the second, different piece of sports equipment with which the monitoring device has **201** been engaged and, further, is configured to select the particular (and potentially different) characteristics the monitoring device **201** will measure and the particular (and potentially different) data the monitoring device will collect.

FIGS. **25A-C** show illustrative removable sections **200** according to aspects of this disclosure. As seen in FIGS. **25A-C**, each of the removable sections **200** may include an elongated portion configured to aid in housing the monitoring device **201**. As described above, each of the elongate portions may include a first arched end configured to engage a first rounded end of the compartment, a second arched end configured to engage a second rounded end of the compartment and a back portion which extends between the first arched portion and the second arched portion and is configured to engage a side of the compartment of the monitoring device **201**. According to aspects of the disclosure, the elongated portion of each of the removable section **200** may include the one or more protrusions **200p**. As seen FIG. **25A**, the illustrative removable section **200T** includes a plurality of protrusions **201p** which are arranged in unique positioning. In this case there are five protrusions **200p** arranged in the unique positioning. It is noted that the number of protrusions **200p** and the unique positioning of those protrusions **200p** may be configured such that when engaged with the monitoring

68

device **201**, they indicate to the monitoring device to the piece of sports equipment with which the monitoring device **201** is engaged. For example, the number of protrusions **200p** and the unique positioning of those protrusions **200p** in illustrative removable section **200T** may indicate to the monitoring device **201** that the monitoring device **201** is engaged with a tennis racquet.

Similarly, FIGS. **25B-C** each show other illustrative removable sections **200** with their own respective plurality of protrusions **201p** which are arranged in unique arrangements. For example, as seen in FIG. **25B**, the illustrative removable section **200H** may include six protrusions **200p** arranged in a unique positioning which may indicate to the monitoring device **201** that the monitoring device **201** is engaged with a hockey stick. Further, as seen in FIG. **25C**, the illustrative removable section **200L** may include seven protrusions **200p** arranged in a unique positioning which may indicate to the monitoring device **201** that the monitoring device **201** is engaged with a lacrosse stick.

FIG. **26** shows an illustrative monitoring device **201** according to aspects of this disclosure. As seen in FIG. **26**, the flat side of the compartment of the monitoring device **201** may be configured to include the one or more openings **201o** (which are configured to receive the protrusions **200p**. Additionally, or alternatively, one or both of the rounded ends of the compartment of the monitoring device **201** may be configured to include the openings **201o** which are configured to receive the protrusions **200p** which are positioned on the first arched portion and/or the second arched portion of the removable section **200**.

As seen FIG. **26**, the illustrative monitoring device **201** includes a plurality of openings **201o** which are arranged such that the openings **201o** can accommodate each of the unique arrangements of the protrusions of the various removable sections **200**. In this example, there are nine opening **201o** which are configured to receive the protrusions of the various removable sections **200**. Further, as seen in FIG. **26**, the openings **201o** can receive each of the unique arrangements of the protrusions of the various removable sections **200T**, **200H**, **200L**.

It is noted that these embodiments are merely illustrative and not meant to be limiting. For example, while nine openings and 5-7 protrusions are discussed in the illustrative embodiments, it is clear that any combination of openings and protrusions may be used provided the combination will sufficiently allow the monitoring device **201** to selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect. For example, other protrusions **200p** (e.g., number of protrusions, arrangements of protrusions) and sets of openings **201o** (e.g., number of openings, arrangements of openings) may be used in accordance with aspects of the disclosure.

It is noted that in some embodiments, the protrusions of the removable sections **200** may be configured to activate detecting switches within monitoring device **201** which cause the processor **204** to determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, is configured to select the particular characteristics it will measure and the data it will collect. For example, engagement of the protrusions with the openings of the removable section **200** may cause the detecting switches within the openings to move from a first position to second position. The processor **204** may be configured to recognize this movement and depending on which of the detecting switches have been moved, determine the piece of sports equipment with which

the monitoring device **201** has been engaged and, further, is select the particular characteristics it will measure and the data it will collect. Alternatively, there may be electrical connections made between the protrusions and the elements (e.g., leads) within the opening of the removable section **200**. The processor **204** may be configured to recognize these connections and depending on which of the elements are contacted and, thereby, determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect. Of course, these are just examples and other methods of selectively determining the piece of sports equipment with which the monitoring device **201** has been engaged and, further, selecting the particular characteristics it will measure and the data it will collect may be used.

The protrusions and openings may be arranged such that the monitoring device **201** can only be engaged with the removable section in an intended orientation. For example, while the “universal” monitoring device **201** may have nine holes, the protrusions on the removable section **200** and holes on the monitoring device **201** are arranged such that they will align only when the monitoring device **201** is engaged with the removable section **200** in the intended orientation.

It is noted that as discussed above, according to other aspects of the disclosure, the grip **105** may be configured to receive and secure the monitoring device **201** directly, without the inclusion of a separate removable section or cartridge **200**. As discussed above, the monitoring device **201** may be configured to be engaged with the grip **105** in a variety of ways. For example, the grip **105** may be configured with an opening at its terminal end that is configured to receive the monitoring device **201**. However, regardless of how the monitoring device **201** is engaged with the grip **105**, the grip **105** itself may be configured with the above discussed protrusions configured to engage with the openings in the monitoring device **201** to selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect accordingly. For example, the grip **105** may include a slit that is configured to receive the monitoring device **201** when the monitoring device **201** is inserted into the grip along the monitoring device’s longitudinal axis. Further, one or both of the rounded ends of the compartment of the monitoring device **201** may be configured to include the openings which are configured to receive the protrusions and the lower end of the slit may include the one or more protrusions. Additionally, or alternatively, the protrusions may be positioned on the sides of the slit and may be spring loaded, flexible, etc. in order to accommodate the insertion and removable of the monitoring device **201**.

Memory Wire

In addition to the above described embodiment which includes protrusions for activating detection switches, shape memory alloy may be used as well. Shape memory alloy is substance which is configured to return to its original shape upon heating.

RFID Technology

Further, while the above embodiment discussed the structural engagement between the monitoring device **201** and the piece of sports equipment as a means of allowing the monitoring device **201** to selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect, other methods and means may be used as well.

For example, the piece of sports equipment may include a chip (e.g., an RFID chip) which communicates with the moni-

toring device **201** when the monitoring device **201** is engaged with the piece of sports equipment. This could be through direct electrical connection, wireless transmission, etc. The chip may be configured to indicate to the monitoring device **201** with which piece of sports equipment the monitoring device **201** is engaged. For example, the transceiver of the monitoring device **201** may be configured to receive or “read” ID data from the chip which indicates which piece of sports equipment the monitoring device **201** is engaged. Accordingly, once the monitoring device **201** has determined the piece of sports equipment with which it is engaged (based on the data provided from the chip), the processor **204** of the monitoring device **201** can selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect.

For example, when the monitoring device **201** has received data from the chip (e.g., RFID chip) engaged with golf club, the processor **204** of the monitoring device **201** (and/or system) may configure the monitoring device **201** to measure various characteristics, such as angular rotation about the longitudinal axis of the golf club. Further, the monitoring device **201** (and/or system) may configure the monitoring device **201** to measure velocity, acceleration, etc. at a first rate (e.g., a first refresh rate). In contrast, according to aspects of the disclosure, when the monitoring device **201** has received data from the chip (e.g., RFID chip) that the monitoring device **201** is engaged with a baseball bat, the monitoring device **201** (and/or system) may configure the monitoring device **201** to measure various characteristics that do not include angular rotation about the longitudinal axis of the baseball bat. Further, the monitoring device **201** (and/or system) may configure the monitoring device **201** to measure velocity, acceleration, etc. at a second rate (e.g., a second refresh rate) which is different from the first rate used for the golf club.

Sensor Self-Aware Based on Practice Swings

Further, while the above referenced embodiments discussed the structural engagement between the monitoring device **201** and the piece of sports equipment or the use of a chip (e.g., an RFID chip) as means of allowing the monitoring device **201** to selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect, other methods and means may be used as well.

According to aspects of the disclosure, the monitoring device **201** may be configured to determine the piece of sports equipment with which the monitoring device **201** has been engaged based on the movement of the piece of sports equipment. For example, the monitoring device **201** may be configured to determine the piece of sports equipment with which the monitoring device **201** has been engaged based on “practice” swings of the piece of sports equipment.

According to aspects of the disclosure, the processor **204** may be configured to receive data from components of the monitoring device **201** (e.g., the IMUs in the monitoring device **201**). For example, the processor **204** may be configured to receive data from an accelerometer, gyroscope, etc. which indicates the orientation of the piece of sports equipment, the velocity or acceleration of the sports equipment, etc. According to aspects of the disclosure, based on this data, the monitoring device **201** may be configured to determine the piece of sports equipment with which the monitoring device **201** has been engaged and further, select the particular characteristics it will measure and the data it will collect.

For example, if the data indicates that a characteristic is above a predetermined value (or within a predetermined range), the processor **204** may determine the piece of sports equipment with which the monitoring device **201** has been engaged is a first type of sports equipment and further, select the particular characteristics it will measure and the data it will collect accordingly. Further, if the data indicates that a characteristic is below a predetermined value (or within a predetermined range or non-existent), the processor may determine the piece of sports equipment with which the monitoring device **201** has been engaged is a second type of sports equipment and further, select the particular characteristics it will measure and the data it will collect accordingly.

For example, if the processor receives data from the IMUs which indicates the piece of sports equipment was swung in a particular orientation or swing path, then the processor **204** of the monitoring device **201** will assume the piece of sports equipment with which the monitoring device **201** is engaged is a piece of sports equipment that corresponds to such an orientation or swing path. For example, it is noted that orientation and/or swing path profiles for each of respective pieces of sports equipment (e.g., golf clubs, tennis racquets, bats, hockey sticks, etc.) may be saved in memory and as accessible by the processor **204**. Therefore, the processor of the monitoring device **201** may compare the measured orientation or swing path with the saved orientations or swing path profiles in the memory and determine which piece of sports equipment the monitoring device **201** is engaged with by matching (or by substantially matching) the measured characteristics with one of the saved profiles. Hence, thereafter, the monitoring device **201** may select the particular characteristics it will measure and the data it will collect accordingly.

For example, FIGS. **27A** and **27B** illustrate swing paths for a golf swing and the swing of a baseball bat, respectively. As seen by comparing these swings, they each have different swing paths and orientations throughout the swing. For example, the swing of the baseball bat has an orientation that is relatively horizontal through the middle of the swing path. In contrast the golf swing has an orientation that is relatively vertical through the middle of the swing path. Such data regarding the orientation of the piece of sports equipment throughout the swing path or a portion of the swing path may be determined by the sensors of the monitoring device **201**, and then used by the monitoring device **201** to determine the piece of sports equipment with which the monitoring device is engaged in a manner such as discussed above (e.g., comparing the measured characteristics with the saved profiles).

It is noted that in addition to the saved orientations or swing path profiles, velocity and acceleration (and other characteristics) profiles for each of respective pieces of sports equipment (e.g., golf clubs, tennis racquets, bats, hockey sticks, etc.) may be saved in memory and accessible by the processor **204** as well. In this way, such data can also be used to determine the piece of sports equipment with which the monitoring device **201** is engaged with accordingly. For example, the processor of the monitoring device **201** may compare the measured velocity and acceleration (and other characteristics) with the saved velocity and acceleration (and other characteristic) profiles in the memory. For example, the processor may determine if the measured velocity, acceleration (and/or other characteristic) is within a predetermined range of a saved profile. The results of the comparison (e.g., if it is, or is not, within a particular profile) may at least aid in determining the piece of sports equipment with which the monitoring device **201** is engaged. Hence, thereafter, the monitoring device **201** may select the particular characteristics it will measure and the data it will collect.

Similarly, according to additional aspects of the disclosure, the processor **204** may be configured to receive data from each (or more than one) of the IMUs in the monitoring device **201** and compare that data with predetermined values or ranges to determine the data from which IMU to use for a particular purpose. For example, as discussed above with regard to putting and driver signatures in FIGS. **19A-19D**, the acceleration and angular velocity for other pieces of sports equipment may have particular graphical ranges or "signatures." Such graphical ranges or "signatures" may be stored in a memory which the processor **204** may access. Therefore, in some embodiments of the disclosure, the processor **204** may be configured to receive data from each (or more than one) of the IMUs in the monitoring device **201** and compare that data with the stored graphical ranges or "signatures." If the data matches a particular graphical range or "signature" associated with a first type of sports equipment, the processor may determine that the swing was the first type of sports equipment and accordingly use data from a first IMU in making particular calculations (or transmitting that data to the remote computer) or select the particular characteristics the monitoring device **201** will measure and the data it will collect. Alternatively, if the data matches a particular graphical range or "signature" associated with a second type of sports equipment, the processor may determine that the swing was associated with the second type of sports equipment and accordingly use data from a second IMU in making particular calculations (or transmitting that data to the remote computer) or select the particular characteristics the monitoring device **201** will measure and the data it will collect. It is noted that while the above embodiment discusses graphical ranges or "signatures" other data could be used instead (e.g., numerical ranges or signatures). Further, it is noted that tolerances may be incorporated into the comparison of the collected data with saved values, ranges, "signatures", etc. such that the collected data does not have to match exactly in order for the type of sports equipment to be identified. For example, either the processor **204** may be configured to account for a predefined tolerance when comparing the data with the saved values, ranges, "signatures", etc. or the saved values, ranges, "signatures", etc. may already include a predefined tolerance. Accordingly, if the receive data from each of the IMUs in the monitoring device **201** does not exactly match the signature of a particular predetermined swing with a predetermined piece of sports equipment, but is still within a tolerance or predetermined range of the particular predetermined swing with a particular piece of sports equipment, then the monitoring device **201** may be configured to identify the piece of sports equipment with which pending swing was produced as the particular piece of sports equipment associated with the signature.

If the data indicates that a characteristic is above a predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a corresponding, predefined IMU as the determined data (and perhaps discard the data from the other IMU(s)). Conversely, if the data indicates that a characteristic is below that predetermined value (or within a predetermined range), the processor **204** may be configured to use the data from a second corresponding, predefined IMU as the determined data (and perhaps discard the data from the other IMU(s)).

It is noted that the above described aspects of having the processor (or other firmware) receive data from each (or more than one) of the IMUs and then use the data to determine with which type of sports equipment the monitoring device **201** is engaged (and thereby determine which of the particular IMU's data to use and/or transmit or select the particular

characteristics the monitoring device **201** will measure and the data it will collect) may be applied to or used in combination with the other features in the other embodiments described herein. For example, in the above described embodiments, which include prongs and detecting switches to determine with which type of club the monitoring device **201** is engaged, the processor (or other firmware) may still collect data from each IMU and then use or transmit such data accordingly. For example, data from each IMU may still be relevant for various characteristics of the golf swing and even though data from one IMU is selected for determining a particular characteristic based on the above described methods, data from other IMUs may still be used for determining other characteristics and/or transmitted to the remote device.

The above discussed embodiments do not preclude other means of allowing the monitoring device **201** to selectively determine the piece of sports equipment with which the monitoring device **201** has been engaged and, further, select the particular characteristics it will measure and the data it will collect. Other methods and means may be used as well.

For example, while the above discussed embodiments describe features which “automatically” determine which of pieces of sports equipment the monitoring device **201** is engaged (i.e., without the user taking an affirmative step to manually choose between the different pieces of sports equipment), this should not be interpreted to mean that embodiments which allow the user to manually determine which piece of sports equipment the monitoring device **201** is engaged with and manually configure the monitoring device **201** to measure particular characteristics and collect particular data accordingly are precluded. Instead, according to aspects of the disclosure, the monitoring device **201** may be configured to receive instructions from the user as to which piece of sports equipment it is engaged. For example, according to an embodiment of the disclosure, the monitoring device **201** could include a switch which the user can manually move between different positions. Further, the processor **204** of the monitoring device **201** could be configured to interpret the different positions of the switch as instructions as to which piece of sports equipment it is engaged.

Alternatively, the processor **204** of the monitoring device **201** could receive instructions from the remote computer **400** discussed above, as to the piece of sports equipment with which it is engaged. It is noted that such instructions could be stored in the memory until the monitoring unit **201** receives other instructions which override such instructions. For example, the particular piece of sports equipment or a particular IMU (e.g., the first IMU instead of the second IMU) whose data is collected and used may be chosen by the user affirmatively instructing the processor **204** via the remote computer **400**. Alternatively, particular piece of sports equipment or a particular IMU whose data is collected and used may be chosen/dictated by the particular software application being run by the remote computer. In other words, a particular software application may choose which data or characteristics of the sports equipment is to be measured and/or require that data from first IMU instead of a second IMU to be used to calculate the particular value (even though data from the second IMU may still be collected and stored or used for other purposes). For example, the application directed to determining bat speed may specify that the processor **204** use data from the first IMU instead of the data from the second IMU.

Voice Commands

Alternatively, the particular IMU (e.g., the first IMU instead of the second IMU) whose data is collected and used, the piece of sports equipment with which the monitoring device **201** is engaged/the particular characteristics of the

swing or stroke to be measured (e.g., based on the type of sports equipment) may be chosen/dictated by the user through voice commands. For example, the remote computer **400** (e.g., a mobile telephone, such as a smart phone as described above) may be positioned near the user when the user is preparing to make a swing or stroke. The remote computer **400** may include a particular software application that transmits instructions to the processor of the monitoring device to use a particular IMU (e.g., the first IMU instead of the second IMU), identify the type of sports equipment with which the monitoring device is engaged and/or measure particular characteristics of the swing or stroke based on the remote computer **400** receiving a predetermined voice command. For example, the remote computer **400** may have voice recognition software which interprets the user's command of “baseball bat”, “measure baseball bat speed” of other predetermined phrases as an instruction to transmit data to the remote computer **400** to use a first IMU or identify the type of sports equipment with which the monitoring device is engaged as a baseball bat and/or measure particular characteristics of the swing (e.g., bat speed). Similar embodiments and phrases may be used for other sports equipment, characteristics, or IMUs. Alternatively, the sports equipment itself could be configured to have the voice recognition software and a microphone for receiving the voice commands. Hence, in such an embodiment, the sports equipment itself may be receive the voice commands and interpret them to use a particular IMU or identify the type of sports equipment with which the monitoring device is engaged and/or measure particular characteristics of the swing or stroke.

According to aspects of the disclosure, the remote computer **400** may be configured to receive data from the monitoring device **201** and then associate the data with a particular piece of sports equipment (e.g., by comparing the received data from the monitoring device **201** with swing path, orientation, velocity, acceleration, etc. profiles that are stored on the remote computer similarly to as discussed above). Alternatively, as discussed above, according to aspects of the disclosure, the monitoring device **201** may capture the data associated with the swing and transfer the data collected wherein the data transmission to the remote computer **400** specifies to which piece of sports equipment the data in the transmission relates (e.g., wherein the piece of sporting equipment is selected according to one of the above described embodiments). Further, it is noted that various combinations of the above described embodiments of determining the piece of sports equipment with which the monitoring device **201** has been engaged and, further, selecting the particular characteristics the monitoring device **201** will measure and the data the monitoring device **201** will collect may be used.

It is noted that while the measured characteristics described above have related to rotation, orientation, swing path, velocity, angular velocity, acceleration and angular acceleration, etc. the above described features are not limited to measuring these feature and other characteristics of the swing may be measured as well. Also, it is noted that regardless of how the piece of sports equipment with which the monitoring device **201** has been engaged is selected, once the piece of sports equipment with which the monitoring device **201** has been engaged is selected, data can be determined, processed, transmitted, etc. according to any of the above discussed aspects of the disclosure.

“Waking Up” Sports Equipment

According to aspects of the disclosure, the monitoring device **201** may be activated during insertion of the monitoring device **201** into sports equipment. Further, the monitoring device **201** may be continuously sensing and collecting data.

However, according to other aspects of the disclosure, the monitoring device **201** may be selectively activated. For example, the monitoring device **201** may be configured to enter a “sleep” or “hibernation” state when the monitoring device has not been active for a predetermined amount of time (e.g., 1 minute, 5 minutes, 1 or 5 seconds after the monitoring device **201** determines that swing or stroke is completed (as will be described below), etc.). In this “sleep” or “hibernation” state only the components needed for determining activation of the monitoring device **201** may continue to receive power. In other embodiments of the “sleep” or “hibernation” state, components may receive less power than they do in a use state. Further, the monitoring device **201** may be selectively activated manually, or automatically upon the occurrence of an event (e.g., movement of the sports equipment or movement of the sports equipment in a particular fashion).

For example, in an illustrative embodiment of the disclosure, the movement of the sports equipment may act as a trigger to cause the monitoring device **201** to exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). For example, the monitoring device **201** may be configured to receive data from the IMUs that the sports equipment has been moved and based on the data exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). According to aspects of the disclosure, the monitoring device **201** may be configured compare the data from the IMUs with a predetermined threshold and only exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”) if the data from the IMUs is above the predetermined threshold. For example, the data from the IMUs must be above a predetermined angular velocity or acceleration in order to “wake up” the monitoring device **201**. In this way, incidental movement will not “wake up” the monitoring device **201**.

In an illustrative embodiment of the disclosure, the predetermined movement of the sports equipment may act as a trigger to cause the monitoring device **201** to exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”). According to aspects of the disclosure, the monitoring device **201** may be configured compare the data from the IMUs with a predetermined range(s) or value(s) (e.g., such as the above discussed graphical or numerical range or signatures which indicate a stroke or swing of the piece of sports equipment) and only exit the “sleep” or “hibernation” state and/or fully activate (i.e., “wake up”) if the data from the IMUs is above the predetermined threshold. For example, the predetermined range(s) or value(s) may indicate be a “signature” which indicates a practice swing. Therefore, when the data from the IMUs match (or are within a tolerance or the signature) the monitoring device **201** “wakes up”.

In another illustrative embodiment, the user may manually cause the monitoring device **201** to enter to exit the “sleep” or “hibernation” state. For example, the user may use the remote computer **400** (e.g., a smart phone with a software application that configure the smartphone to receive and transmit data to the monitoring device **201**) to cause the monitoring device to enter to exit the “sleep” or “hibernation” state. This could be done by inputting data to the smartphone (e.g., voice commands or touching a touch screen) which instructs the monitoring device **201** to enter to exit the “sleep” or “hibernation” state.

Zeroing

According to aspects of the disclosure, similar methods may be used to correlate data to a particular swing and, thereby, indicate individual swings/distinguish between different swings. For example, in embodiments where the monitoring device **201** may be activated and continually receiving data from the IMUs during the entire time the monitoring

device **201** is activated, aspects of the disclosure are directed to correlating data for a particular swing (e.g., as distinguished from a practice swing or movement not related to the swing, such as when the sports equipment is being carried to the location of the swing).

According to particular aspects of the disclosure, the pre-shot routine may “zero” the monitoring device **201** (i.e., cause the monitoring device **201** to recognize that the upcoming movement is the beginning of an individual swing). For example, as discussed above, the monitoring device **201** may be configured to receive data from the IMUs that the sports equipment has been moved in a predetermined movement. The monitoring device **201** may be configured to recognize the predetermined range(s) or value(s) as the “signature” which indicates the predetermined movement and determine that any movement after the recognized predetermined movement is part of swing or stroke. Accordingly, only movement of the sports equipment after the predetermined movement will be correlated with the particular swing or stroke. In other words, only movement of the golf club which occurs after the IMUs provide data to the monitoring device **201** that the sports equipment is at rest in the ready position after having completed the predetermined movement will be correlated with the particular swing or stroke.

It is noted that the monitoring device **201** may be configured to account for, or include, a predetermined time after the predetermined movement is completed and after the swing is completed in determining which data is related to the swing or stroke. For example, the monitoring device **201** may be configured to allow for a predetermined time (e.g., 1 or 2 seconds) once the monitoring device **201** has determined that the predetermined movement has been completed (i.e., the IMUs provide data to the monitoring device **201** that the sports equipment is at rest in the ready position after having completed the predetermined movement) before beginning to associate data with the particular stroke. Similarly, the monitoring device **201** may be configured to allow for a predetermined time (e.g., 1 or 2 seconds) once the monitoring device **201** has determined that the swing or stroke has been completed (i.e., the IMUs provide data to the monitoring device **201** that the sports equipment has completed the stroke (e.g., the follow through of the swing or stroke has been completed) as defined by the stored signature of the typical swing or stroke) before ending the association data with the particular stroke.

In some embodiments, the predetermined movement may include one or more practice swings. Further, it is noted that the predetermined movement may be customized to the particular user. For example, the predetermined movement may include one or more practices swing(s) prior to the sports equipment coming to rest in the ready position after having completed the predetermined movement depending on the particular user’s habits. Such information regarding the predetermined movement may be stored on in the monitoring device **201**. For example, the particular signature of a user’s predetermined movement of the sports equipment may be stored to the monitoring device **201** (e.g., uploaded to the memory of the monitoring device **201** via the remote computer **400** or the remote computer **400** could instruct the monitoring device **201** to record data from the IMU for a particular amount during which the user performs the predetermined movement of the sports equipment and then store the recorded data as the signature of the predetermined movement of the sports equipment). According to aspects of the disclosure, the monitoring device **201** may be configured to determine a practice swing and a swing whose signature is within a particular range relative to the signature of an actual

swing. For example, a practice swing may be defined as a predetermined amount or range which corresponds to predetermined value (e.g., 70% of the angular velocity of an actual swing or 70% of the radial length of an actual swing). Alternatively, a practice swing may be defined with its own digital signature which identifies the swing as a practice swing as described above.

According to some embodiments of the disclosure, the user may manually correlate data to a particular swing and, thereby, indicate individual swings/distinguish between different swings. For example, the golfer may activate a switch which “zeros” the monitoring device 201 (i.e., cause the monitoring device 201 to recognize that the upcoming movement is the beginning of an individual swing). For example, the user may activate a switch on the sports equipment itself that transmits information to the monitoring device 201 that causes the monitoring device 201 to recognize that the upcoming movement is the beginning of an individual swing. Further, the user may activate a switch on the remote computer 400 (e.g., pressing a button on a smart phone) that causes the monitoring device 201 to recognize that the upcoming movement is the beginning of an individual swing. Further, the golfer may use voice commands to zero the monitoring device 201. For example, the remote computer 400 (e.g., a smart phone) may be configured to receive the voice commands from the user and transmit data to the monitoring device which indicates the beginning and end of the shot. For instance, the remote computer 400 may be configured to interpret the user saying “begin” or “start” as the beginning of the swing and transmit instructions to the remote computer to begin recording data from the IMUs or being associating data from the IMUs as a particular, individual swing. Conversely, the remote computer 400 may be configured to interpret the user saying “done” or “end” as the end of the swing and transmit instructions to the monitoring device to stop recording data from the IMUs or stop associating data from the IMUs as a particular, individual swing.

In some embodiments of the disclosure impact sensors such as described above may be used to determine a recordable swing. For example, if a particular swing has characteristics which resemble both a practice swing and an actual swing (e.g., above a threshold angular velocity), the monitoring device 201 may be configured to receive data from an impact sensor which indicates whether impact with the object (e.g., a baseball, tennis ball, etc.) was made during the swing. In such embodiments, the occurrence of an impact may serve as validating that the swing should not be interpreted as a practice swing, but instead a particular swing for which characteristics of the swing should be measured/determined.

System which Recommends Product/Strategy to Improve Performance

As discussed above, according to aspects of the disclosure, data collected from the above described system and metrics determined by the above described system may be uploaded to a network. For example, such data may be uploaded to a network which can interpret the received data and provide recommendations to the golfer. For example, in some embodiments of the disclosure, the collected data and determined metrics may be uploaded to a network which can compare the data and metrics with a predefined set of characteristics in order to recommend products which will aid the golfer in improving various aspects of their games.

By way of example, swing speed data determined by the monitoring device 201 may be uploaded to such a network system. Further, data on shaft of the golf club from which the swing speed data was taken (as identified by one of the above described methods) may also be uploaded to such a network

system. The network system may include a database which stores data on swing speeds and a database which stores data on a plurality of shaft stiffnesses. Further, the database may store tables which correlate various swing speeds with ideal shaft stiffness for such swing speeds. For example, the table may correlate a first shaft stiffness for a swing speed of 90 mph, and a second shaft stiffness for a swing speed of 125 mph. The system may be configured to determine whether the shaft used for the golf swing is the type of shaft the table considers the ideal shaft for the determined swing speed. If the system determines that the shaft is not the ideal shaft based on the table data, the system may send a message to the remote computer 400 of the golfer which recommends the ideal shaft based on the table data. For example, if data uploaded to the network showed that the swing speed determined by the monitoring device 201 was 125 mph and a golfer using the first shaft stiffness, then the system would send a message to the remote computer recommending the golfer use a shaft with the second shaft stiffness because their golf swing speed was 125 mph. In this way, the system could aid in improving the golfer’s game by providing recommendations regarding the appropriate equipment based on the golfer’s swing. While the above described example, discusses swing speed and shaft stiffness, it is understood that various other characteristics and products may also be used.

Further, in addition to recommending products to improve the golfer’s swing, according to aspects of the disclosure, the system may also recommend strategies to correct the golfer’s swing directly. For example, the monitoring device 201 could provide rotation data for the club which shows the angle of club face at the point of impact with the golf ball. Further, the network system may include a database which stores data correlating the angle of the club face at the point of impact with the golf ball with the profiled of golf shots (e.g., slices and hooks). If data uploaded to the network showed that the angle of the club face was open as impact, then the system would send a message to the remote computer 400 recommending the golfer adjust their swing to close the club face at the point of impact. In this way, the system could aid in improving the golfer’s game by providing recommendations correcting the golfer’s swing. While the above described example, discusses angle of the club face at impact with the golf ball, it is understood that various other characteristics and strategies may also be used.

Further, the system may also provide coaching to correct the golfer’s swing. For example, as described above, the monitoring device 201 could provide data for the club which indicates the swing path of the golf swing. If data uploaded to the network showed that the swing path was producing a “sliced” or a “hooked” golf shot, then the system would send instructions to the remote computer 400 describing how the golfer may adjust their swing to correct the slice or hook. For example, the system could provide coaching videos in which coaches provide instructions and describe methods for correcting a slice or hook. Additionally, when the golfer completes a first video, the system may register the completion of the video and provide additional videos (e.g., more advanced correction techniques). Further, the system could provide drills which the golfer can use to correct a slice or hook. Additionally, when the golfer completes a drill, the golfer may communicate completion of the drill to the system and the system may provide additional drills (e.g., more advanced correction drills). Alternatively, the remote computer may be configured to determine when the golfer has completed the drills through the data received from the monitoring device 201. Accordingly, the remote computer 400 may be configured to automatically communicate completion of the drill to

the system and the system may provide additional drills (e.g., more advanced correction drills).

While the above described examples discuss the angle of the club face at impact with the golf ball and swing path of the golf swing, it is understood that various other characteristics and strategies may also be used. For example, the monitoring device 201 could provide data on the position/orientation of the golf club shaft or golf club head when the golfer has positioned the golf club at the address position.

As discussed above, according to aspects of the disclosure, data collected from the above described system and metrics determined by the above described system may be uploaded to a network. However, alternatively, instead of uploading such data to a network, the remote computer 400 itself may be configured to compare the data and metrics with a predefined set of characteristics in order to provide coaching or drills which will aid the golfer in improving various aspects of their games. For example, the remote computer 400 (e.g., as configured by a software application) may include a databases which stores data on characteristics of a swing or stroke and, also, stores tables which correlate various characteristics with various coaching videos, drills, etc. Therefore, the remote computer 400 may provide the golfer with various “on board” coaching videos, drills, etc. It is noted that while the above described embodiments relate to golf swings, as described above, monitoring devices and system may be used with other sports equipment as well. Therefore, aspects of the disclosure are directed to providing similar recommendations in other sports based on the received data from the respective pieces of sports equipment. For example, the system may be configured to provide recommendations on: a particular type of tennis racquet based on the speed of a serve or stroke, a particular type of baseball bat based on swing speed, etc. While the above described examples, discusses swing or stroke speed, it is understood that various other characteristics and products may also be used. Further, the system could provide recommendations on strategies to correct the athlete’s swing or stroke directly in a manner similar to as described above.

III. CONCLUSION

The present disclosure is described above and in the accompanying drawings with reference to a variety of example structures, features, elements, and combinations of structures, features, and elements. The purpose served by the disclosure, however, is to provide examples of the various features and concepts related to the disclosure, not to limit the scope of the disclosure. One skilled in the relevant art will recognize that numerous variations and modifications may be made to the embodiments described above without departing from the scope of the present disclosure, as defined by the appended claims. For example, the various features and concepts described above in conjunction with FIGS. 1 through 27B may be used individually and/or in any combination or subcombination without departing from this disclosure.

What is claimed is:

1. A golf club comprising:

a golf club head having a body with a striking face configured for striking a ball;

a shaft connected to the head and extending from the head; and

a port located in the head or the shaft, the port configured to receive a monitoring device for measuring at least one characteristic of a golf swing, wherein the port has an engagement mechanism configured to engage the monitoring device in an engagement configuration that is configured to cause the monitoring device to operate in

a selected manner; and wherein the monitoring device is configured to be pressed to the engagement mechanism.

2. The golf club of claim 1, wherein the engagement mechanism is configured to releasably engage the monitoring device to permit the monitoring device to be inserted or removed.

3. The golf club of claim 2, wherein the engagement mechanism further comprises a removable section configured to be received in the head or the shaft, wherein the removable section is configured to engage the monitoring device in the engagement configuration.

4. The golf club of claim 3, wherein the removable section comprises a plurality of protrusions forming the engagement configuration, wherein the protrusions are configured to be received in openings in the monitoring device to cause the monitoring device to operate in the selected manner.

5. The golf club of claim 4, wherein the removable section comprises holder members configured to engage the monitoring device and a surface between the holder members configured to confront the monitoring device when engaged by the holder members, and wherein the protrusions are located on the surface between the holder members.

6. The golf club of claim 3, wherein the port is located in an end of the shaft distal from the head, and wherein the removable section is received within the end of the shaft.

7. The golf club of claim 6, wherein the removable section comprises an end cap positioned at the end of the shaft.

8. The golf club of claim 1, wherein the golf club head includes multiple ports, including at least a first port located in the head and a second port located in an end of the shaft distal from the head.

9. The golf club of claim 8, wherein the first port and the second port each include engagement mechanisms configured to engage the monitoring device in the engagement configuration that is configured to cause the monitoring device to operate in the selected manner.

10. The golf club of claim 1, further comprising the monitoring device, wherein the monitoring device comprises a plurality of sensors, and wherein the monitoring device is configured to utilize input from at least a first sensor when engaged by the engagement mechanism in the engagement configuration.

11. A set of golf clubs comprising:

a first golf club comprising:

a first golf club head having a body with a striking face configured for striking a ball,

a first shaft connected to the first head and extending from the first head, and

a first port located in the first head or the first shaft, the first port configured to receive a monitoring device for measuring at least one characteristic of a golf swing, wherein the first port has a first engagement mechanism configured to engage the monitoring device in a first engagement configuration that is configured to cause the monitoring device to operate in a first selected manner, wherein the monitoring device is configured to be pressed to the first engagement mechanism; and

a second golf club comprising:

a second golf club head having a body with a striking face configured for striking the ball,

a second shaft connected to the second head and extending from the second head, and

a second port located in the second head or the second shaft, the second port configured to receive the monitoring device, wherein the second port has a second engagement mechanism configured to engage the

81

monitoring device in a second engagement configuration that is different from the first engagement configuration, and wherein the second engagement configuration is configured to cause the monitoring device to operate in a second selected manner that is different from the first selected manner, wherein the monitoring device is configured to be pressed to the second engagement mechanism.

12. The set of claim 11, wherein the first and second engagement mechanisms are configured to releasably engage the monitoring device to permit the monitoring device to be inserted or removed.

13. The set of claim 12, wherein the first engagement mechanism further comprises a first removable section configured to be received in the first head or the first shaft, wherein the first removable section is configured to engage the monitoring device in the first engagement configuration, and wherein the second engagement mechanism further comprises a second removable section configured to be received in the second head or the second shaft, wherein the second removable section is configured to engage the monitoring device in the second engagement configuration.

14. The set of claim 13, wherein the first removable section comprises a first plurality of protrusions arranged to form the first engagement configuration, wherein the first protrusions are configured to be received in first openings in the monitoring device to cause the monitoring device to operate in the first selected manner, and wherein the second removable section comprises a second plurality of protrusions arranged to form the second engagement configuration, wherein the second protrusions are arranged differently from the first protrusions, and wherein the second protrusions are configured to be received in second openings in the monitoring device, including at least one different opening from the first openings, to cause the monitoring device to operate in the second selected manner.

15. The set of claim 13, wherein the first port is located in an end of the first shaft distal from the first head, and wherein the first removable section is received within the end of the first shaft.

16. The set of claim 15, wherein the first removable section comprises a first end cap positioned at the end of the first shaft.

17. The set of claim 11, wherein the set further comprises:
a third golf club head having a body with a striking face configured for striking the ball,
a third shaft connected to the second head and extending from the second head, and
a third port located in the third head or the third shaft, the third port configured to receive the monitoring device, wherein the third port has a third engagement mechanism configured to engage the monitoring device in a third engagement configuration that is different from the first engagement configuration and the second engagement configuration, and wherein the third engagement configuration is configured to cause the monitoring device to operate in a third selected manner that is different from the first selected manner and the second selected manner, wherein the monitoring device is configured to be pressed to the third engagement mechanism.

18. The set of claim 11, further comprising the monitoring device, wherein the monitoring device comprises a plurality of sensors, and wherein the monitoring device is configured to utilize input from at least a first sensor when engaged by the first engagement mechanism in the first engagement configuration, and wherein the monitoring device is configured to

82

utilize input from at least a second sensor when engaged by the second engagement mechanism in the second engagement configuration.

19. A golf club comprising:

a golf club head having a body with a striking face configured for striking a ball;

a shaft connected to the head and extending from the head; and

a removable section at least partially received in the head or the shaft, the removable section configured to receive a monitoring device for measuring at least one characteristic of a golf swing, wherein the removable section comprises one or more protrusions in an arrangement, the one or more protrusions configured to be received in one or more openings of the monitoring device, such that the arrangement of the one or more protrusions is configured to cause the monitoring device to operate in a selected manner, wherein the monitoring device is configured to be pressed to the removable section.

20. The golf club of claim 19, wherein the removable section further comprises a plurality of protrusions spaced from each other on a flat surface.

21. The golf club of claim 19, wherein the removable section is configured to releasably engage the monitoring device to permit the monitoring device to be inserted or removed.

22. The golf club of claim 19, wherein the removable section is received within an end of the shaft distal from the head.

23. The golf club of claim 22, wherein the removable section comprises an end cap positioned at the end of the shaft.

24. The golf club of claim 19, further comprising the monitoring device, wherein the monitoring device comprises a plurality of sensors and has a plurality of openings therein, and wherein the monitoring device is configured to utilize input from at least a first sensor when the protrusions are received into the openings.

25. The golf club of claim 19, wherein the removable section comprises holder members configured to engage the monitoring device and a surface between the holder members configured to confront the monitoring device when engaged by the holder members, and wherein the protrusions are located on the surface between the holder members.

26. A set of golf clubs comprising:

a first golf club comprising:

a first golf club head having a body with a striking face configured for striking a ball,

a first shaft connected to the first head and extending from the first head, and

a first removable section at least partially received in the first head or the first shaft, the first removable section configured to receive a monitoring device for measuring at least one characteristic of a golf swing, wherein the first removable section comprises one or more first protrusions in a first arrangement, the one or more first protrusions configured to be received in one or more first openings of the monitoring device, such that the first arrangement of the one or more first protrusions is configured to cause the monitoring device to operate in a first selected manner, wherein the monitoring device is configured to be pressed to the first removable section; and

a second golf club comprising:

a second golf club head having a body with a striking face configured for striking the ball,

83

a second shaft connected to the second head and extending from the second head, and

a second removable section at least partially received in the second head or the second shaft, the second removable section configured to receive the monitoring device, wherein the second removable section comprises one or more second protrusions in a second arrangement that is different from the first arrangement, the one or more second protrusions configured to be received in one or more second openings of the monitoring device, including at least one different opening from the first openings, such that the second arrangement of the one or more second protrusions is configured to cause the monitoring device to operate in a second selected manner that is different from the first selected manner, wherein the monitoring device is configured to be pressed to the second removable section.

27. The set of claim 26, wherein the first and second removable sections are each configured to releasably engage the monitoring device to permit the monitoring device to be inserted or removed.

84

28. The set of claim 27, wherein the first removable section is received within the end of the first shaft.

29. The set of claim 28, wherein the first removable section comprises a first end cap positioned at the end of the first shaft.

30. The set of claim 26, wherein the first removable section further comprises a plurality of the first protrusions spaced from each other on a first flat surface, and wherein the second removable section further comprises a plurality of the second protrusions spaced from each other on a second flat surface, wherein the second protrusions include at least one protrusion arranged differently from the first protrusions.

31. The set of claim 26, further comprising the monitoring device, wherein the monitoring device comprises a plurality of sensors and has a plurality of openings therein, and wherein the monitoring device is configured to utilize input from at least a first sensor when the first protrusions are received into the openings, and wherein the monitoring device is configured to utilize input from at least a second sensor that is different from first sensor when the second protrusions are received into the openings.

* * * * *