

# Learning to Select Features

Xianchao Xiu

Department of Automation



The Hong Kong Polytechnic University, March 20, 2025

Joint work with Anning Yang (SHU), Long Chen (SHU), Jianhao Li (SHU) and others

# Outline

Introduction

Sparse Coding


Contrastive Learning

Deep Unfolding Networks

Large Language Models

Future Work

- ▶ Unsupervised feature selection *vs.* Feature extraction
- ▶ Select a subset of input features without labels



@Danny Butwink

# PCA

- Given  $X = (\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n) \in \mathbb{R}^{d \times n}$ , principal component analysis (PCA) is

$$\min_{W \in \mathbb{R}^{d \times p}} \frac{1}{2} \|X - WW^\top X\|_F^2$$

$$\text{s.t. } W^\top W = I_p$$

$\Updownarrow$

$$\min_{W \in \mathbb{R}^{d \times p}} -\text{Tr}(W^\top X X^\top W)$$

$$\text{s.t. } W^\top W = I_p$$

- Unsupervised feature selection by sparse PCA

$$\min_{W \in \mathbb{R}^{d \times p}} -\text{Tr}(W^\top X X^\top W)$$

$$\text{s.t. } W^\top W = I_p, \|W\|_{2,0} \leq s$$

- The  $i$ -th feature can be measured by  $\|\mathbf{w}^i\|$  since  $\mathbf{z}_i = (\mathbf{w}^{1\top}, \mathbf{w}^{2\top}, \dots, \mathbf{w}^{d\top})\mathbf{x}_i$
- The dimension number is often omitted when it does not cause ambiguity

# SOTA

- ▶ Li-Nie-Bian et al, Sparse PCA via  $\ell_{2,p}$ -Norm Regularization for Unsupervised Feature Selection, IEEE TPAMI, 2023

$$\begin{aligned} \min_W \quad & -\text{Tr}(W^\top X X^\top W) + \lambda \|W\|_{2,p}^p \quad (0 < p < 1) \\ \text{s.t.} \quad & W^\top W = I \end{aligned}$$


- ▶ Li-Sun-Zhang, Unsupervised Feature Selection via Nonnegative Orthogonal Constrained Regularized Minimization, arXiv:2403.16966

$$\begin{aligned} \min_{W,Y} \quad & \text{Tr}(Y^\top LY) + \alpha \|Y - X^\top W\|_{2,1} + \beta \|W\|_{2,1} + \gamma \|W\|_F^2 \\ \text{s.t.} \quad & Y^\top Y = I, \quad Y \geq 0 \end{aligned}$$

- ▶ Hu-Wang-Zhang et al, Bi-Level Spectral Feature Selection, IEEE TNNLS, 2025
- ▶ Jiao-Xue-Zhang, Sparse Learning-Based Feature Selection in Classification: A Multi-Objective Perspective, IEEE TETCI, 2025
- ▶ Li-Yu-Yang et al, Exploring Feature Selection With Limited Labels: A Comprehensive Survey of Semi-Supervised and Unsupervised Approaches, IEEE TKDE, 2024

# Contribution

- ▶ Learning to select features
  - ▶ (Q1) How to learn feature structures ⇒ **Sparse coding**
  - ▶ (Q2) How to learn data distributions ⇒ **Contrastive learning**
  - ▶ (Q3) How to learn regularization parameters ⇒ **Deep unfolding networks**
  - ▶ (Q4) How to learn feature selection ⇒ **Large language models**



# Outline

Introduction

Sparse Coding

Contrastive Learning

Deep Unfolding Networks

Large Language Models

Future Work


# Model

- (Q1) How to learn feature structures

$$\begin{aligned} \min_W \quad & -\text{Tr}(W^\top X X^\top W) \\ \text{s.t.} \quad & W^\top W = I, \|W\|_{2,0} \leq s_1 \end{aligned}$$

↓

$$\begin{aligned} \min_W \quad & -\text{Tr}(W^\top X X^\top W) \\ \text{s.t.} \quad & W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2 \end{aligned}$$



- Double Sparsity Constrained Optimization for Feature Selection (DSCOFS)

- $\|W\|_{2,0} \leq s_1$ : Global feature selection
- $\|W\|_0 \leq s_2$ : Local feature selection

## Algorithm

- ▶ Proximal alternating method (PAM)
- ▶ Model reformulation

$$\min_W - \text{Tr}(W^\top X X^\top W)$$

$$\text{s.t. } W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2$$

↓

$$\min_{W,Y,Z} - \text{Tr}(W^\top X X^\top W)$$

$$\text{s.t. } W^\top W = I, \|Y\|_{2,0} \leq s_1, \|Z\|_0 \leq s_2$$

$$W = Y, W = Z$$

↓

$$\min_{W,Y,Z} - \text{Tr}(W^\top X X^\top W) + \mu_1 \|W - Y\|_F^2 + \mu_2 \|W - Z\|_F^2$$

$$\text{s.t. } W^\top W = I, \|Y\|_{2,0} \leq s_1, \|Z\|_0 \leq s_2$$

# Algorithm

► Input:  $X, \mu_1, \mu_2, s_1, s_2, \tau_1, \tau_2, \tau_3$

► Initialize:  $(W^0, Y^0, Z^0)$

► While not converged do

► Update  $W^{k+1}$  by

$$\begin{aligned} \min_W \quad & -\text{Tr}(W^\top X X^\top W) + \mu_1 \|W - Y^k\|_{\text{F}}^2 + \mu_2 \|W - Z^k\|_{\text{F}}^2 + \tau_1 \|W - W^k\|_{\text{F}}^2 \\ \text{s.t.} \quad & W^\top W = I \end{aligned}$$

► Update  $Y^{k+1}$  by

$$\begin{aligned} \min_Y \quad & \|W^{k+1} - Y\|_{\text{F}}^2 + \tau_2 \|Y - Y^k\|_{\text{F}}^2 \\ \text{s.t.} \quad & \|Y\|_{2,0} \leq s_1 \end{aligned}$$

► Update  $Z^{k+1}$  by

$$\begin{aligned} \min_Z \quad & \|W^{k+1} - Z\|_{\text{F}}^2 + \tau_3 \|Z - Z^k\|_{\text{F}}^2 \\ \text{s.t.} \quad & \|Z\|_0 \leq s_2 \end{aligned}$$

# Convergence

- ▶ Denote the objective function as

$$f(W, Y, Z) = -\text{Tr}(W^\top X X^\top W) + \mu_1 \|W - Y\|_F^2 + \mu_2 \|W - Z\|_F^2$$

- ▶ Suppose that  $\beta \geq \max\{2(\lambda_0 + \lambda_1), 2m\lambda_2\}$
- ▶ **(Theorem)** Let  $\{(W^k, Y^k, Z^k)\}$  be the generated sequence. Then the following properties hold:
  - ▶  $\{f(W^k, Y^k, Z^k)\}$  is strictly nonincreasing
  - ▶ The sequence  $\{(W^k, Y^k, Z^k)\}$  is bounded
  - ▶  $\lim_{k \rightarrow \infty} \|(W^{k+1}, Y^{k+1}, Z^{k+1}) - (W^k, Y^k, Z^k)\|_F = 0$
  - ▶ Any accumulation point  $(W^*, Y^*, Z^*)$  of the sequence  $\{(W^k, Y^k, Z^k)\}$  is a stationary point in the sense that

$$0 \in \nabla f(W^*, Y^*, Z^*) + N(W^*, Y^*, Z^*)$$
















# Experiments

- ▶ Compared methods
  - ▶ **LapScore**: He-Cai-Niyogi, NIPS, 2005
  - ▶ **UDFS**: Yang-Shen-Ma et al, IJCAI, 2011
  - ▶ **SOGFS**: Nie-Zhu-Li, IEEE TKDE, 2021
  - ▶ **RNE**: Liu-Ye-Li-Wang et al, KBS, 2020
  - ▶ **SPCAFS**: Li-Nie-Bian-Wu et al, IEEE TPAMI, 2023
  - ▶ **FSPCA**: Nie-Tian-Wang et al, IEEE TPAMI, 2023
  - ▶ **SPCA-PSD**: Zheng-Zhang-Liu et al, arXiv:2309.06202
- ▶ Implementation setups
  - ▶ **Initialization**: RandOrthhMat
  - ▶ **Sparsity level**:  $s_1 \in \{10, 20, \dots, 100\}$ ,  $s_2 \in \{0.1, 0.2, \dots, 0.9\}dp$
  - ▶ **Stopping criteria**:

$$\frac{|f(X^{k+1}, Y^{k+1}, Z^{k+1}) - f(X^k, Y^k, Z^k)|}{1 + |f(X^k, Y^k, Z^k)|} \leq 10^{-3}$$

# Experiments

## ► Synthetic datasets



# Experiments

- Real datasets: Accuracy (ACC) ↑

| Datasets      | ALLfea     | LapScore            | UDFS                        | SOGFS                      | RNE                 | FSPCA                       | SPCAFS                      | SPCA-PSD                   | DSCOFS                      |
|---------------|------------|---------------------|-----------------------------|----------------------------|---------------------|-----------------------------|-----------------------------|----------------------------|-----------------------------|
| COIL20        | 57.74±4.93 | 54.82±3.91<br>(100) | <b>58.71±3.47<br/>(100)</b> | 49.66±4.81<br>(100)        | 55.84±4.41<br>(90)  | 50.15±4.70<br>(100)         | 54.39±3.67<br>(100)         | 56.57±3.05<br>(100)        | <b>60.51±4.63<br/>(100)</b> |
| USPS          | 65.12±4.95 | 62.02±4.09<br>(90)  | 59.52±2.97<br>(60)          | 55.58±3.07<br>(100)        | 46.04±2.69<br>(100) | <b>67.38±4.36<br/>(60)</b>  | 67.34±4.49<br>(100)         | 65.38±4.26<br>(100)        | <b>69.67±4.97<br/>(100)</b> |
| lung_discrete | 65.10±6.44 | 59.29±6.33<br>(70)  | 68.58±6.99<br>(100)         | 65.12±6.89<br>(100)        | 64.05±6.65<br>(100) | 60.19±6.55<br>(40)          | 71.37±7.68<br>(100)         | <b>72.22±8.02<br/>(80)</b> | <b>73.12±8.48<br/>(100)</b> |
| GLIOMA        | 56.84±5.24 | 58.88±3.96<br>(90)  | 56.80±4.85<br>(100)         | <b>57.44±6.16<br/>(70)</b> | 58.32±7.31<br>(90)  | 47.92±4.61<br>(80)          | 50.60±5.02<br>(20)          | <b>59.28±5.01<br/>(90)</b> | <b>60.88±6.31<br/>(80)</b>  |
| UMIST         | 41.07±2.38 | 40.13±2.79<br>(100) | 47.12±2.49<br>(40)          | 41.70±3.17<br>(100)        | 40.35±2.26<br>(90)  | 46.70±2.29<br>(100)         | 46.78±2.51<br>(90)          | <b>47.98±2.91<br/>(90)</b> | <b>48.10±3.01<br/>(70)</b>  |
| warpPIE10P    | 25.67±1.90 | 28.94±1.66<br>(100) | 41.42±3.18<br>(20)          | 46.90±3.89<br>(20)         | 29.57±2.96<br>(90)  | 28.01±2.27<br>(50)          | <b>48.76±3.86<br/>(50)</b>  | 43.74±3.91<br>(70)         | <b>49.00±3.88<br/>(40)</b>  |
| Isolet        | 57.89±3.82 | 52.21±2.76<br>(100) | 41.95±2.07<br>(100)         | 49.31±2.32<br>(100)        | 47.12±2.06<br>(90)  | <b>53.62±2.36<br/>(100)</b> | 53.04±2.33<br>(100)         | 51.91±2.15<br>(70)         | <b>59.67±3.46<br/>(100)</b> |
| MSTAR         | 77.04±7.98 | 67.87±3.49<br>(90)  | 78.15±5.80<br>(90)          | 73.74±5.89<br>(100)        | 69.16±6.03<br>(100) | 75.52±6.22<br>(70)          | <b>80.80±5.95<br/>(100)</b> | 79.70±6.43<br>(90)         | <b>82.59±7.41<br/>(100)</b> |
| Average       | 55.81±4.71 | 53.02±3.62          | 56.53±4.04                  | 54.93±4.53                 | 51.31±4.30          | 53.69±4.47                  | 59.14±4.44                  | <b>59.60±4.47</b>          | <b>62.94±5.27</b>           |

# Experiments

- Real datasets: Normalized mutual information (NMI) ↑


| Datasets      | ALLfea     | LapScore            | UDFS                        | SOGFS                | RNE                 | FSPCA                       | SPCAFS                      | SPCA-PSD                    | DSCOFS                      |
|---------------|------------|---------------------|-----------------------------|----------------------|---------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| COIL20        | 75.37±1.96 | 69.59±1.48<br>(100) | <b>73.54±1.76<br/>(100)</b> | 68.92±1.84<br>(100)  | 70.43±1.92<br>(100) | 68.50±1.56<br>(100)         | 69.98±1.45<br>(100)         | 69.85±1.41<br>(100)         | <b>76.25±1.71<br/>(100)</b> |
| USPS          | 61.12±2.01 | 59.46±1.80<br>(100) | 54.69±2.11<br>(100)         | 52.96±1.54<br>(100)  | 45.36±1.93<br>(90)  | <b>62.00±1.87<br/>(60)</b>  | 60.98±2.37<br>(100)         | 60.90±2.02<br>(100)         | <b>64.06±2.58<br/>(100)</b> |
| lung_discrete | 62.85±5.13 | 56.79±3.99<br>(100) | 64.84±5.09<br>(100)         | 59.70±5.24<br>(100)  | 61.63±5.83<br>(70)  | 58.26±6.39<br>(40)          | 69.09±5.61<br>(100)         | <b>70.93±5.46<br/>(80)</b>  | <b>70.98±7.00<br/>(100)</b> |
| GLIOMA        | 48.86±5.72 | 51.03±2.48<br>(100) | 47.22±3.53<br>(10)          | 48.67±10.98<br>(100) | 48.62±6.32<br>(100) | 21.94±5.28<br>(100)         | 24.14±6.97<br>(100)         | <b>51.44±5.62<br/>(90)</b>  | <b>51.06±6.19<br/>(80)</b>  |
| UMIST         | 63.67±1.85 | 61.16±1.71<br>(100) | 62.00±1.58<br>(100)         | 60.79±1.54<br>(100)  | 55.92±1.57<br>(70)  | 65.27±1.58<br>(100)         | 66.23±1.60<br>(90)          | <b>66.25±1.72<br/>(100)</b> | <b>67.24±1.85<br/>(100)</b> |
| warpPIE10P    | 25.07±2.88 | 25.13±1.73<br>(90)  | 46.18±3.30<br>(20)          | 52.12±3.25<br>(20)   | 32.67±3.31<br>(90)  | 23.90±2.01<br>(50)          | <b>52.63±3.33<br/>(50)</b>  | 46.02±3.70<br>(70)          | <b>52.65±3.29<br/>(50)</b>  |
| Isolet        | 75.72±1.70 | 69.77±1.20<br>(100) | 56.29±1.11<br>(100)         | 67.40±1.44<br>(100)  | 64.27±0.95<br>(90)  | <b>70.79±1.12<br/>(100)</b> | 67.71±1.33<br>(100)         | 69.69±0.80<br>(100)         | <b>75.01±1.35<br/>(100)</b> |
| MSTAR         | 82.42±3.31 | 74.10±1.76<br>(100) | 76.45±2.47<br>(90)          | 76.39±1.70<br>(100)  | 66.87±1.99<br>(80)  | 78.39±2.17<br>(90)          | <b>80.33±2.50<br/>(100)</b> | 79.17±2.77<br>(90)          | <b>81.14±3.13<br/>(100)</b> |
| Average       | 61.89±3.07 | 58.38±2.02          | 60.15±2.62                  | 60.87±3.44           | 55.72±2.98          | 56.13±2.75                  | 61.39±3.15                  | <b>64.28±2.94</b>           | <b>67.30±3.39</b>           |

# Experiments


- ▶ Ablation studies: Feature similarity rate (FSR)

$$\text{FSR} = \frac{|\mathbb{T}_{\text{our}} \cap \mathbb{T}_{2,0}|}{n}$$


| Datasets       | $\ W\ _0 \leq s_2$ | ACC $\uparrow$   | NMI $\uparrow$   | FSR |
|----------------|--------------------|------------------|------------------|-----|
| COIL20         | ✗                  | 60.25 $\pm$ 4.52 | 75.89 $\pm$ 1.58 | 84  |
|                | ✓                  | 60.51 $\pm$ 4.42 | 76.25 $\pm$ 1.71 |     |
| USPS           | ✗                  | 68.69 $\pm$ 4.79 | 61.25 $\pm$ 2.39 | 68  |
|                | ✓                  | 69.67 $\pm$ 4.97 | 64.06 $\pm$ 2.58 |     |
| lung\_discrete | ✗                  | 71.42 $\pm$ 7.95 | 69.74 $\pm$ 6.11 | 92  |
|                | ✓                  | 73.12 $\pm$ 8.48 | 70.98 $\pm$ 7.00 |     |
| GLIOMA         | ✗                  | 58.24 $\pm$ 5.04 | 49.76 $\pm$ 6.12 | 85  |
|                | ✓                  | 60.88 $\pm$ 6.31 | 51.06 $\pm$ 6.19 |     |
| UMIST          | ✗                  | 47.33 $\pm$ 3.05 | 67.44 $\pm$ 1.88 | 95  |
|                | ✓                  | 48.10 $\pm$ 3.01 | 67.24 $\pm$ 1.85 |     |
| warpPIE10P     | ✗                  | 47.91 $\pm$ 4.99 | 51.19 $\pm$ 3.79 | 89  |
|                | ✓                  | 49.00 $\pm$ 3.88 | 52.65 $\pm$ 3.29 |     |
| Isolet         | ✗                  | 57.29 $\pm$ 3.44 | 72.82 $\pm$ 1.87 | 52  |
|                | ✓                  | 59.67 $\pm$ 3.46 | 75.01 $\pm$ 1.35 |     |
| MSTAR          | ✗                  | 82.06 $\pm$ 6.87 | 81.01 $\pm$ 2.41 | 99  |
|                | ✓                  | 82.59 $\pm$ 7.41 | 81.14 $\pm$ 3.13 |     |




(a) USPS



(b) Isolet



(c) USPS



(d) Isolet

# Outline

Introduction

Sparse Coding

Contrastive Learning

Deep Unfolding Networks

Large Language Models


Future Work

# Motivation

- ▶ (Q2) How to learn data distributions

$$\begin{aligned} \min_W \quad & \frac{1}{2} \|X - WW^\top X\|_F^2 \\ \text{s.t.} \quad & W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2 \end{aligned}$$

- ▶ Convex loss:  $\ell_1$ -norm,  $\ell_{2,1}$ -norm, quantile, Huber
- ▶ Nonconvex loss:  $\ell_p$ -norm,  $\ell_{2,p}$ -norm, SCAD, MCP, capped  $\ell_1$
- ▶ Contrastive learning: learn a discrimination model between positive and negative pairs



# Motivation

- ▶ Let  $X = (\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n)$  and  $Y = (\mathbf{y}_1, \mathbf{y}_2, \dots, \mathbf{y}_n)$  be two different pairs, the contrastive loss is defined as

$$L_c(X, Y) = \frac{1}{2n} \sum_{i=1}^n (L_c(\mathbf{x}_i) + L_c(\mathbf{y}_i))$$

$$L_c(\mathbf{x}_i) = -\log \frac{\exp(s(\mathbf{x}_i, \mathbf{y}_i)/\tau)}{\sum_{j=1, j \neq i}^n \exp(s(\mathbf{x}_i, \mathbf{x}_j)/\tau) + \sum_{j=1}^n \exp(s(\mathbf{x}_i, \mathbf{y}_j)/\tau)}$$

$$L_c(\mathbf{y}_i) = -\log \frac{\exp(s(\mathbf{y}_i, \mathbf{x}_i)/\tau)}{\sum_{j=1, j \neq i}^n \exp(s(\mathbf{y}_i, \mathbf{y}_j)/\tau) + \sum_{j=1}^n \exp(s(\mathbf{y}_i, \mathbf{x}_j)/\tau)}$$

- ▶  $s(\mathbf{x}, \mathbf{y}) = \mathbf{x}^\top \mathbf{y}$  is the similarity metric,  $\tau$  is the temperature parameter

A simple framework for **contrastive learning** of visual representations

[T Chen](#), [S Kornblith](#), [M Norouzi](#)... - ... on machine learning, 2020 - proceedings.mlr.press

... In our **contrastive learning**, as positive pairs are computed in the same device, the model can exploit the local information leakage to improve prediction accuracy without improving ...

☆ 保存 引用 被引用次数: 22684 相关文章 所有 24 个版本 »

# Model

- DSCOFS with contrastive learning (DSCOFS-CL)

$$\min_W \frac{1}{2} \|X - WW^\top X\|_F^2$$

$$\text{s.t. } W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2$$

↓

$$\min_W L_c(X, WW^\top X)$$

$$\text{s.t. } W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2$$

↓

$$\min_{W,Z} \lambda L_c(X, XZ) + (1 - \lambda) L_c(W^\top X, W^\top XZ)$$


$$\text{s.t. } W^\top W = I, \|W\|_{2,0} \leq s_1, \|W\|_0 \leq s_2$$

$$\text{rank}(Z) \leq r, \text{Diag}(Z) = 0$$

- $\text{rank}(Z) \leq r$  represents the global structure
- $\text{Diag}(Z) = 0$  avoids the case where  $Z = E$

# Architecture

- DSCOFS-CL = Double Sparsity + Graph Learning + Contrastive Learning



# Algorithm

- ▶ Proximal alternating method (PAM)

$$\min_{W,Z} \quad \lambda L_c(X, XZ) + (1 - \lambda) L_c(W^\top X, W^\top XZ)$$

$$\text{s.t.} \quad W^\top W = I, \quad \|W\|_{2,0} \leq s_1, \quad \|W\|_0 \leq s_2 \\ \text{rank}(Z) \leq r, \quad \text{Diag}(Z) = 0$$

↓

$$\min_{W,Z,Y,P,Q} \quad \lambda L_c(X, XZ) + (1 - \lambda) L_c(W^\top X, W^\top XZ)$$

$$\text{s.t.} \quad \|P\|_{2,0} \leq s_1, \quad \|Q\|_0 \leq s_2, \quad \text{rank}(Y) \leq r, \quad \text{Diag}(Z) = 0 \\ W^\top W = I, \quad Z = Y, \quad W = P, \quad W = Q$$

↓

$$\min_{W,Z,Y,P,Q} \quad \lambda L_c(X, XZ) + (1 - \lambda) L_c(W^\top X, W^\top XZ) + \mu \|W^\top W - I\|_F^2$$

$$+ \alpha \|Z - Y\|_F^2 + \beta \|W - P\|_F^2 + \gamma \|W - Q\|_F^2$$

$$\text{s.t.} \quad \|P\|_{2,0} \leq s_1, \quad \|Q\|_0 \leq s_2, \quad \text{rank}(Y) \leq r, \quad \text{Diag}(Z) = 0$$

# Algorithm

- **Input:**  $X, \lambda, \mu, \alpha, \beta, \gamma, s_1, s_2, r, \tau_1, \tau_2, \tau_3, \tau_4, \tau_5$
- **Initialize:**  $(W^0, Z^0, Y^0, P^0, Q^0)$
- **While** not converged **do**
  - Update  $W^{k+1}$  by

$$\begin{aligned} \min_W \quad & (1 - \lambda)L_c(W^\top X, W^\top XZ^k) + \mu\|W^\top W - I\|_F^2 \\ & + \beta\|W - P^k\|_F^2 + \gamma\|W - Q^k\|_F^2 + \tau_1\|W - W^k\|_F^2 \end{aligned}$$

- Update  $Z^{k+1}$  by

$$\begin{aligned} \min_Z \quad & \lambda L_c(X, XZ) + (1 - \lambda)L_c(W^{k+1,\top} X, W^{k+1,\top} XZ) \\ & + \alpha\|Z - Y^k\|_F^2 + \tau_2\|Z - Z^k\|_F^2 \\ \text{s.t.} \quad & \text{Diag}(Z) = 0 \end{aligned}$$

- Update  $Y^{k+1}$
- Update  $P^{k+1}$
- Update  $Q^{k+1}$

# Algorithm

- ▶ Define

$$\begin{aligned} f(W, Z, Y, P, Q) = & \lambda L_c(X, XZ) + (1 - \lambda)L_c(W^\top X, W^\top XZ) \\ & + \mu\|W^\top W - I\|_F^2 + \alpha\|Z - Y\|_F^2 + \beta\|W - P\|_F^2 + \gamma\|W - Q\|_F^2 \\ & + \delta(Z) + \delta(Y) + \delta(P) + \delta(Q) \end{aligned}$$

- ▶ We call  $(W, Z, Y, P, Q)$  is a critical point if  $0 \in \partial f(W, Z, Y, P, Q)$
- ▶ (**Theorem**) For each  $k$ , the sequence  $\{(W^k, Z^k, Y^k, P^k, Q^k)\}$  generated by our PAM algorithm converges and  $0 \in \partial f(W^*, Z^*, Y^*, P^*, Q^*)$  with


$$\lim_{k \rightarrow +\infty} (W^k, Z^k, Y^k, P^k, Q^k) = (W^*, Z^*, Y^*, P^*, Q^*)$$

- ▶ Sufficient decreasing
- ▶ Lower bounds for iterations
- ▶ Kurdyka-Łojasiewicz properties


## Experiments

- ▶ Real datasets: Accuracy (ACC) ↑


| Datasets | ALLfea     | LapScore            | UDFS                | SOGFS               | RNE                 | SPCAFS              | SPCA-PSD            | DSCOFS                      | SPCA-CL                     | DSCOFS-CL                   |
|----------|------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|-----------------------------|-----------------------------|-----------------------------|
| COIL20   | 57.74±4.93 | 54.82±3.91<br>(100) | 58.71±3.47<br>(100) | 49.66±4.81<br>(100) | 55.84±4.41<br>(90)  | 54.39±3.67<br>(100) | 56.57±3.05<br>(100) | <b>60.51±4.63<br/>(100)</b> | 60.31±3.49<br>(90)          | <b>61.32±5.18<br/>(80)</b>  |
| USPS     | 65.12±4.95 | 62.02±4.09<br>(90)  | 59.52±2.97<br>(60)  | 55.58±3.07<br>(100) | 46.04±2.69<br>(100) | 67.34±4.49<br>(100) | 65.38±4.26<br>(100) | <b>69.67±4.97<br/>(100)</b> | 68.88±4.05<br>(80)          | <b>70.82±4.77<br/>(100)</b> |
| GLIOMA   | 56.84±5.24 | 58.88±3.96<br>(90)  | 56.80±4.85<br>(100) | 57.44±6.16<br>(70)  | 58.32±7.31<br>(90)  | 50.60±5.02<br>(20)  | 59.28±5.01<br>(90)  | 60.88±6.31<br>(80)          | <b>61.48±6.20<br/>(40)</b>  | <b>63.16±7.46<br/>(50)</b>  |
| UMIST    | 41.07±2.38 | 40.13±2.79<br>(100) | 47.12±2.49<br>(40)  | 41.70±3.17<br>(100) | 40.35±2.26<br>(90)  | 46.78±2.51<br>(90)  | 47.98±2.91<br>(90)  | 48.10±3.01<br>(70)          | <b>49.55±3.00<br/>(60)</b>  | <b>50.95±3.15<br/>(70)</b>  |
| Isolet   | 57.89±3.82 | 52.21±2.76<br>(100) | 41.95±2.07<br>(100) | 49.31±2.32<br>(100) | 47.12±2.06<br>(90)  | 53.04±2.33<br>(100) | 51.91±2.15<br>(70)  | 59.67±3.46<br>(100)         | <b>60.53±3.75<br/>(90)</b>  | <b>63.22±3.50<br/>(90)</b>  |
| MSTAR    | 77.04±7.98 | 67.87±3.49<br>(90)  | 78.15±5.80<br>(90)  | 73.74±5.89<br>(100) | 69.16±6.03<br>(100) | 80.80±5.95<br>(100) | 79.70±6.43<br>(90)  | <b>82.59±7.41<br/>(100)</b> | <b>81.57±6.28<br/>(100)</b> | 81.22±5.59<br>(100)         |
| Average  | 59.28±4.88 | 55.99±3.50          | 57.04±3.69          | 54.57±4.24          | 52.81±4.13          | 58.83±4.00          | 60.14±3.97          | 63.57±4.96                  | <b>63.72±4.46</b>           | <b>65.12±4.94</b>           |




(a) COIL20




(b) USPS




(c) GLIOMA



(d) UMIST



(e) Isolet




(f) MSTAR


## Experiments

- ▶ Real datasets: Normalized mutual information (NMI) ↑


| Datasets | ALLfea     | LapScore            | UDFS                | SOGFS                | RNE                 | SPCAFS                      | SPCA-PSD                   | DSCOFS                      | SPCA-CL                     | DSCOFS-CL                   |
|----------|------------|---------------------|---------------------|----------------------|---------------------|-----------------------------|----------------------------|-----------------------------|-----------------------------|-----------------------------|
| COIL20   | 75.37±1.96 | 69.59±1.48<br>(100) | 73.54±1.76<br>(100) | 68.92±1.84<br>(100)  | 70.43±1.92<br>(100) | 69.98±1.45<br>(100)         | 69.85±1.41<br>(100)        | <b>76.25±1.71<br/>(100)</b> | 74.79±1.48<br>(100)         | <b>75.76±1.76<br/>(90)</b>  |
| USPS     | 61.12±2.01 | 59.46±1.80<br>(100) | 54.69±2.11<br>(100) | 52.96±1.54<br>(100)  | 45.36±1.93<br>(90)  | 60.98±2.37<br>(100)         | 60.90±2.02<br>(100)        | <b>64.06±2.58<br/>(100)</b> | 62.29±2.40<br>(100)         | <b>63.95±2.67<br/>(100)</b> |
| GLIOMA   | 48.86±5.72 | 51.03±2.48<br>(100) | 47.22±3.53<br>(10)  | 48.67±10.98<br>(100) | 48.62±6.32<br>(100) | 24.14±6.97<br>(100)         | <b>51.44±5.62<br/>(90)</b> | 51.06±6.19<br>(80)          | 50.95±4.10<br>(60)          | <b>51.71±5.03<br/>(70)</b>  |
| UMIST    | 63.67±1.85 | 61.16±1.71<br>(100) | 62.00±1.58<br>(100) | 60.79±1.54<br>(100)  | 55.92±1.57<br>(70)  | 66.23±1.60<br>(90)          | 66.25±1.72<br>(100)        | 67.24±1.85<br>(100)         | <b>69.98±1.84<br/>(80)</b>  | <b>70.54±1.70<br/>(70)</b>  |
| Isolet   | 75.72±1.70 | 69.77±1.20<br>(100) | 56.29±1.11<br>(100) | 67.40±1.44<br>(100)  | 64.27±0.95<br>(90)  | 67.71±1.33<br>(100)         | 69.69±0.80<br>(100)        | 75.01±1.35<br>(100)         | <b>75.41±1.51<br/>(100)</b> | <b>77.32±1.37<br/>(100)</b> |
| MSTAR    | 82.42±3.31 | 74.10±1.76<br>(100) | 76.45±2.47<br>(90)  | 76.39±1.70<br>(100)  | 66.87±1.99<br>(80)  | <b>80.33±2.50<br/>(100)</b> | 79.17±2.77<br>(90)         | <b>81.14±3.13<br/>(100)</b> | 78.63±2.50<br>(100)         | 78.88±1.60<br>(100)         |
| Average  | 67.86±2.76 | 64.19±1.74          | 61.70±2.09          | 62.52±3.17           | 58.58±2.45          | 61.56±2.70                  | 66.22±2.39                 | <b>69.13±2.80</b>           | 68.68±2.31                  | <b>69.69±2.36</b>           |




(a) COIL20




(b) USPS




(c) GLIOMA



(d) UMIST



(e) Isolet




(f) MSTAR

# Experiments

- ▶ Friedman tests ( $H_0$ : There is no significant difference of compared methods)

| Methods   | Ranking | P-value | Hypothesis |
|-----------|---------|---------|------------|
| LapScore  | 6.83    | 0.00001 | Reject     |
| UDFS      | 6.50    |         |            |
| SOGFS     | 7.50    |         |            |
| RNE       | 7.50    |         |            |
| SPCAFS    | 5.83    |         |            |
| SPCA-PSD  | 4.83    |         |            |
| DSCOFS    | 2.33    |         |            |
| SPCA-CL   | 2.33    |         |            |
| DSCOFS-CL | 1.33    |         |            |

- ▶ Post-hoc Nemenyi tests



# Outline

Introduction

Sparse Coding

Contrastive Learning

Deep Unfolding Networks

Large Language Models

Future Work

# Motivation

## ► (Q3) How to learn regularization parameters

$$\begin{aligned} \min_{W, Z, Y, P, Q} \quad & \lambda L_c(X, XZ) + (1 - \lambda)L_c(W^\top X, W^\top XZ) + \mu \|W^\top W - I\|_F^2 \\ & + \alpha \|Z - Y\|_F^2 + \beta \|W - P\|_F^2 + \gamma \|W - Q\|_F^2 \\ \text{s.t.} \quad & \|P\|_{2,0} \leq s_1, \|Q\|_0 \leq s_2, \text{rank}(Y) \leq r, \text{Diag}(Z) = 0 \end{aligned}$$

►  $\mu, \alpha, \beta, \gamma \in \{10^{-6}, 10^{-4}, 10^{-2}, 10^0, 10^2, 10^4, 10^6\}$

►  $s_1 \in \{10, 20, \dots, 100\}$

►  $s_2 \in \{0.1, 0.2, \dots, 0.5\}dp$

►  $r = 0.1d$

►  $\lambda = 0.5$

## ► From iterative optimization to **deep unfolding networks**

► Gregor-LeCun, Learning Fast Approximations of Sparse Coding, ICML, 2010

► Chen-Liu-Yin, Learning to optimize: A Tutorial for Continuous and Mixed-Integer Optimization, SCCM, 2024

# Model

- ▶ Consider structured sparse PCA

$$\begin{aligned} \min_W \quad & \frac{1}{2} \|X - WW^\top X\|_F^2 + \lambda \|W\|_{2,1} + \mu \|W\|_1 \\ \text{s.t.} \quad & W^\top W = I \end{aligned}$$

- ▶ Alternating direction method of multipliers (ADMM)

$$\begin{aligned} \min_W \quad & \frac{1}{2} \|X - WW^\top X\|_F^2 + \lambda \|Y\|_{2,1} + \mu \|Z\|_1 \\ \text{s.t.} \quad & W^\top W = I, \quad W = Y, \quad W = Z \end{aligned}$$

↓

$$\begin{aligned} \mathcal{L}(W, Y, Z, \Lambda, \Pi) = & \frac{1}{2} \|X - WW^\top X\|_F^2 + \lambda \|Y\|_{2,1} + \mu \|Z\|_1 \\ & + \langle \Lambda, W - Y \rangle + \frac{\alpha}{2} \|W - Y\|_F^2 + \langle \Pi, W - Z \rangle + \frac{\beta}{2} \|W - Z\|_F^2 \end{aligned}$$

# SPCA-Net

- ▶ Update  $W$ -block

$$\min_W \quad f(W) := \frac{1}{2} \|X - WW^\top X\|_F^2 + \frac{\alpha}{2} \|W - Y^k + \Lambda^k/\alpha\|_F^2 + \frac{\beta}{2} \|W - Z^k + \Pi^k/\beta\|_F^2$$

$$\text{s.t. } W^\top W = I$$

↓

$$\min_W \quad f(W^k) + \langle \nabla f(W^k), W - W^k \rangle + \frac{1}{2\eta} \|W - W^k\|_F^2$$


$$\text{s.t. } W^\top W = I$$

↓

$$W^{k+1} = UV^\top$$

↓

$$W^{k+1} = \text{LargNet}(U, V^\top)$$



# SPCA-Net

- ▶ Update  $Y$ -block

$$\min_Y \lambda \|Y\|_{2,1} + \frac{\alpha}{2} \|X^{k+1} - Y + \Lambda^k/\alpha\|_F^2$$

$\Downarrow$


$$Y^{k+1} = \text{sign}(\|X^{k+1} + \Lambda^k/\alpha\|_2) \circ \max(\|X^{k+1} + \Lambda^k/\alpha\|_2 - \lambda/\alpha, 0)$$

$\Downarrow$

$$Y^{k+1} = \frac{X^{k+1} + \Lambda^k/\alpha}{\|X^{k+1} + \Lambda^k/\alpha\|_2} \text{ReLU}(\|X^{k+1} + \Lambda^k/\alpha\|_2 - \lambda/\alpha)$$

$\Downarrow$

$$Y^{k+1} = \text{GSoftNet}(X^{k+1} + \Lambda^k/\alpha, \lambda/\alpha)$$



# SPCA-Net

- ▶ Update  $Z$ -block

$$\min_Z \mu \|Z\|_1 + \frac{\beta}{2} \|X^{k+1} - Z + \Pi^k / \beta\|_F^2$$

↓


$$Z^{k+1} = \text{sign}(X^{k+1} + \Pi^k / \beta) \circ \max(|X^{k+1} + \Pi^k / \beta| - \mu / \beta, 0)$$

↓

$$Z^{k+1} = \frac{X^{k+1} + \Pi^k / \beta}{|X^{k+1} + \Pi^k / \beta|} \text{ReLU}(|X^{k+1} + \Pi^k / \beta| - \mu / \beta)$$

↓

$$Z^{k+1} = \text{SoftNet}(X^{k+1} + \Pi^k / \beta, \mu / \beta)$$



# SPCA-Net

- ▶ **Input:**  $X, \lambda, \mu, \alpha, \beta$
- ▶ **Initialize:**  $(W^0, Y^0, Z^0, \Lambda^0, \Pi^0)$
- ▶ **While**  $k = 1, \dots, K$  **do**
  - ▶ Update  $W^{k+1}$  by

$$W^{k+1} = \text{LargNet}(U, V^\top)$$

- ▶ Update  $Y^{k+1}$  by

$$Y^{k+1} = \text{GSoftNet}(X^{k+1} + \Lambda^k / \alpha, \lambda / \alpha)$$

- ▶ Update  $Z^{k+1}$  by

$$Z^{k+1} = \text{SoftNet}(X^{k+1} + \Pi^k / \beta, \mu / \beta)$$

- ▶ Update  $\Lambda^{k+1}, \Pi^{k+1}$  by


$$\Lambda^{k+1} = \text{Linear}(W^{k+1}, Y^{k+1}, \Lambda^k, \alpha), \quad \Pi^{k+1} = \text{Linear}(W^{k+1}, Z^{k+1}, \Pi^k, \beta)$$

- ▶ **Output:** Trained  $W$

# Architecture

- ▶ All parameters  $(\lambda, \mu, \alpha, \beta)$  are trained in an end-to-end manner
- ▶ The loss is defined as





$$\text{Loss} = \frac{1}{2} \|X - \bar{W}\bar{W}^T X\|_F^2 + \lambda\|\bar{W}\|_{2,1} + \mu\|\bar{W}\|_1$$



# Experiments

► Real datasets: Accuracy (ACC) ↑


| Datasets | ALLfea             | LapScore            | UDFS                        | SOGFS               | RNE                 | FSPCA                      | SPCAFS                     | SPCA-Net                    |
|----------|--------------------|---------------------|-----------------------------|---------------------|---------------------|----------------------------|----------------------------|-----------------------------|
| COIL20   | 58.97±4.99<br>(10) | 53.91±3.61<br>(100) | <b>56.70±3.09<br/>(70)</b>  | 49.66±3.63<br>(100) | 55.16±3.35<br>(20)  | 51.71±3.05<br>(50)         | 54.63±3.64<br>(100)        | <b>57.46±2.76<br/>(90)</b>  |
| Isolet   | 59.18±3.19<br>(10) | 52.55±2.83<br>(100) | 41.11±1.71<br>(100)         | 48.93±2.69<br>(100) | 47.39±2.91<br>(80)  | <b>54.15±2.69<br/>(70)</b> | 52.26±2.81<br>(100)        | <b>58.43±4.31<br/>(100)</b> |
| UMIST    | 41.68±2.46<br>(10) | 39.71±3.28<br>(100) | 38.64±1.61<br>(40)          | 43.81±2.98<br>(80)  | 41.01±2.25<br>(90)  | 46.58±2.34<br>(100)        | <b>47.32±3.48<br/>(80)</b> | <b>47.58±4.97<br/>(70)</b>  |
| MSTAR    | 80.81±8.76<br>(10) | 68.21±4.57<br>(100) | <b>81.25±7.48<br/>(100)</b> | 73.46±5.61<br>(100) | 77.82±6.16<br>(100) | 78.74±5.20<br>(30)         | 78.63±8.68<br>(90)         | <b>81.90±6.87<br/>(100)</b> |




## Experiments

- ▶ Real datasets: Normalized mutual information (NMI) ↑


| Datasets | ALLfea             | LapScore            | UDFS                | SOGFS               | RNE                               | FSPCA                            | SPCAFS                            | SPCA-Net                          |
|----------|--------------------|---------------------|---------------------|---------------------|-----------------------------------|----------------------------------|-----------------------------------|-----------------------------------|
| COIL20   | 76.04±1.69<br>(10) | 69.01±1.53<br>(100) | 69.12±1.17<br>(80)  | 68.03±1.59<br>(100) | <b>70.76±2.07</b><br><b>(100)</b> | 68.41±1.60<br>(100)              | 70.29±1.31<br>(100)               | <b>72.21±2.68</b><br><b>(90)</b>  |
| Isolet   | 76.09±1.77<br>(10) | 69.86±1.26<br>(100) | 56.73±1.05<br>(100) | 67.15±1.45<br>(100) | 64.74±1.28<br>(90)                | <b>71.12±1.11</b><br><b>(80)</b> | 69.18±1.33<br>(100)               | <b>71.80±1.59</b><br><b>(100)</b> |
| UMIST    | 64.07±1.76<br>(10) | 61.23±2.15<br>(100) | 55.43±1.50<br>(80)  | 61.46±2.03<br>(70)  | 56.08±1.80<br>(60)                | 64.94±1.65<br>(100)              | <b>66.26±1.74</b><br><b>(100)</b> | <b>66.62±7.52</b><br><b>(70)</b>  |
| MSTAR    | 83.96±3.14<br>(10) | 73.90±1.62<br>(100) | 78.18±3.64<br>(90)  | 76.56±1.54<br>(100) | 78.26±2.51<br>(100)               | 78.87±2.52<br>(90)               | <b>79.62±2.30</b><br><b>(100)</b> | <b>80.67±3.47</b><br><b>(90)</b>  |




(a) COIL20



(b) Isolet



(e) UMIST



(d) MSTAR


# Experiments

## ► Ablation studies

| Datasets | Network | ACC ↑             | NMI ↑             |
|----------|---------|-------------------|-------------------|
| COIL20   | ✗       | <b>55.12±2.67</b> | <b>70.44±1.37</b> |
|          | ✓       | <b>57.46±2.76</b> | <b>72.21±2.68</b> |
| Isolet   | ✗       | <b>51.84±2.82</b> | <b>67.02±1.43</b> |
|          | ✓       | <b>58.43±4.31</b> | <b>71.80±1.59</b> |
| UMIST    | ✗       | <b>40.65±2.29</b> | <b>55.88±1.62</b> |
|          | ✓       | <b>47.58±4.97</b> | <b>66.62±7.52</b> |
| MSTAR    | ✗       | <b>80.65±6.47</b> | <b>80.53±2.41</b> |
|          | ✓       | <b>81.90±6.87</b> | <b>80.67±3.47</b> |

| Datasets | Dynamic | ACC ↑             | NMI ↑             |
|----------|---------|-------------------|-------------------|
| COIL20   | ✗       | <b>56.71±3.83</b> | <b>71.49±3.67</b> |
|          | ✓       | <b>57.46±2.76</b> | <b>72.21±2.68</b> |
| Isolet   | ✗       | <b>52.06±3.71</b> | <b>68.91±2.36</b> |
|          | ✓       | <b>58.43±4.31</b> | <b>71.80±1.59</b> |
| UMIST    | ✗       | <b>42.63±2.78</b> | <b>60.12±1.69</b> |
|          | ✓       | <b>47.58±4.97</b> | <b>66.62±7.52</b> |
| MSTAR    | ✗       | <b>80.74±5.28</b> | <b>80.59±3.67</b> |
|          | ✓       | <b>81.90±6.87</b> | <b>80.67±3.47</b> |

## ► Effect of deep unfolding stages



# Outline

Introduction

Sparse Coding

Contrastive Learning

Deep Unfolding Networks


Large Language Models

Future Work

# Motivation

- ▶ (Q4) How to learn feature selection


$$\begin{aligned} \min_W \quad & -\text{Tr}(W^\top X X^\top W) \\ \text{s.t.} \quad & W^\top W = I, \|W\|_{2,0} \leq s_1 \end{aligned}$$



- ▶ From deep learning to **large language models (LLMs)**
  - ▶ Cho-Cund-Srivastava et al, LMPriors: Pre-Trained Language Models as Task-Specific Priors, NeurIPS, 2022
  - ▶ Han-Yoon-Arik et al, Large Language Models Can Automatically Engineer Features for Few-Shot Tabular Learning, ICML, 2024
  - ▶ Li-Tan-Liu, Exploring Large Language Models for Feature Selection: A Data-centric Perspective, SIGKDD, 2025

# DeepSeek

- ▶ Guo-Yang-Zhang et al, DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning, arXiv:2501.12948
- ▶ Arrieta-Ugarte-Valle et al, o3-mini vs DeepSeek-R1: Which One is Safer? arXiv:2501.18438
- ▶ Muennighoff-Yang-Shi et al, S1: Simple Test-time Scaling, arXiv:2501.19393
- ▶ Gao-Jin-Ke et al, A Comparison of DeepSeek and Other LLMs, arXiv:2502.03688



# Method

## ► Dataset-specific Context

Using data collected via a telemarketing campaign at a Portuguese banking institution from 2008 to 2013, we wish to build a machine learning model that can predict whether a client will subscribe to a term deposit (target variable). The dataset contains a total of 16 features (e.g., age, marital status, whether the client has a housing loan). Prior to training the model, we first want to identify a subset of the 16 features that are most important for reliable prediction of the target variable.

## ► Main System Prompt

For each feature input by the user, your task is to provide a feature importance score (between `<0.0>` and `<1.0>`; larger value indicates greater importance) for predicting whether an individual will subscribe to a term deposit and a reasoning behind how the importance score was assigned. The results need to be written directly into a JSON file. Therefore, please do not include any extra text and return the results strictly in the given format. The scores for each feature should be different from one another.

## ► Output Format Instruction

Here is an example output: `"concept-1": "has credit in default ", "reasoning": "Clients with credits in default might be more hesitant to open new financial products due to their current financial situation and may be deemed a higher risk by the bank. Therefore, the score is 0.9.", "score": 0.9.`

## ► Main User Prompt

Provide a score and reasoning formatted according to the output schema above.

# Method

## ► Dataset-specific Context

Using data collected via a telemarketing campaign at a Portuguese banking institution from 2008 to 2013, we wish to build a machine learning model that can predict whether a client will subscribe to a term deposit (target variable). The dataset contains a total of 16 features (e.g., age, marital status, whether the client has a housing loan). Prior to training the model, we first want to identify a subset of the 16 features that are most important for reliable prediction of the target variable.

## ► Main System Prompt

Please use the Random Forest (/ forward sequential selection / backward sequential selection / recursive feature elimination RFE / minimum redundancy maximum relevance selection MRMR / filtering by mutual information MI ) model to directly analyze the dataset samples. This is a classification task, where "Class" represents the classification. Please analyze the importance scores of these features. The score range is [0.0, 1.0], and the score of each feature should be different. The output format is as follows, in JSON file format.

## ► Output Format Instruction

Here is an example output: "concept-1": "has credit in default ", "reasoning": "Clients with credits in default might be more hesitant to open new financial products due to their current financial situation and may be deemed a higher risk by the bank. Therefore, the score is 0.9.", "score": 0.9.

## ► Main User Prompt

Provide a score and reasoning formatted according to the output schema above.

# Experiments


- ▶ Compared methods
  - ▶ DeepSeek-R1 (2025-01-20)
  - ▶ GPT-o3mini (2025-01-31)
  - ▶ GPT-4.5preview (2025-02-27)
  - ▶ LASSO
  - ▶ Forward sequential selection (Forward)
  - ▶ Backward sequential selection (Backward)
  - ▶ Recursive feature elimination (RFE)
  - ▶ Minimum redundancy maximum relevance selection (MRMR)
  - ▶ Mutual information (MI)
  - ▶ Random feature selection (Random)

- ▶ Statistics of datasets


| Datasets              | Samples | Features |
|-----------------------|---------|----------|
| Bank                  | 45211   | 16       |
| Credit-G              | 1000    | 20       |
| Pima Indians Diabetes | 768     | 8        |
| Give Me Some Credit   | 120269  | 10       |

# Experiments


► LLMs vs. Data-driven methods




(a) Bank



(b) Credit-G







(c) Pima Indians Diabetes



(d) Give Me Some Credit



# Experiments

- LLMs + Data-driven methods vs. LLMs vs. Data-driven methods



# Experiments

- More interesting things should be investigated
  - Consider **large datasets** with more features, especially larger than thousands
  - Apply DeepSeek-R1 with **different parameters**, including 7B, 14B, 32B, 70B
  - Try **RAG** and **fine-tuning** to improve the stability and reliability
  - Expand to **regression tasks**, analyze feature correlation, etc



# Outline

Introduction

Sparse Coding

Contrastive Learning

Deep Unfolding Networks

Large Language Models

Future Work

## LLMs for Optimization

- ▶ Ramamonjison-Yu-Li et al, NL4Opt Competition: Formulating Optimization Problems Based on Their Natural Language Descriptions, NeurIPS, 2022
- ▶ Yang-Wang-Lu et al, Large Language Models as Optimizers, ICLR, 2024
- ▶ AhmadiTeshnizi-Gao-Udell, OptiMUS: Scalable Optimization Modeling with (MI)LP Solvers and Large Language Models, ICML, 2024
- ▶ Romera-Paredes-Barekatain et al, Mathematical Discoveries from Program Search with Large Language Models, Nature, 2024
- ▶ Jiang-Shu-Qian et al, LLMOPT: Learning to Define and Solve General Optimization Problems from Scratch, ICLR, 2025
- ▶ Fan-Ghaddar-Wang et al, Artificial Intelligence for Operations Research: Revolutionizing the Operations Research Process, arXiv:2401.03244
- ▶ Liu-Yao-Guo et al, A Systematic Survey on Large Language Models for Algorithm Design, arXiv:2410.14716
- ▶ Gong-Voskanyan-Brookes et al, Language Models for Code Optimization: Survey, Challenges and Future Directions, arXiv:2501.01277

# Pruning for LLMs

- ▶ Frantar-Alistarh, SparseGPT: Massive Language Models Can be Accurately Pruned in One-Shot, ICML, 2023
- ▶ Sun-Liu-Bair et al, A Simple and Effective Pruning Approach for Large Language Models, ICLR, 2024
- ▶ Fang-Yin-Muralidharan et al, MaskLLM: Learnable Semi-Structured Sparsity for Large Language Models, NeurIPS, 2024
- ▶ Boza, Fast and Effective Weight Update for Pruned Large Language Models, TMLR, 2024
- ▶ Hu-Zhao-Li et al, FASP: Fast and Accurate Structured Pruning of Large Language Models, arXiv:2501.09412
- ▶ Cheng-Zhang-Shi, A Survey on Deep Neural Network Pruning: Taxonomy, Comparison, Analysis, and Recommendations, IEEE TPAMI, 2024
- ▶ Wan-Wang-Liu et al, Efficient Large Language Models: A Survey, TMLR, 2024

**Thank you for your attention**

**xcxiu@shu.edu.cn**