

NumPy for MATLAB users

Help

MATLAB/Octave	Python	Description
<code>doc</code>	<code>help()</code>	Browse help interactively
<code>help -i % browse with Info</code>		
<code>help help or doc doc</code>	<code>help</code>	Help on using help
<code>help plot</code>	<code>help(plot) or ?plot</code>	Help for a function
<code>help splines or doc splines</code>	<code>help(pylab)</code>	Help for a toolbox/library package
<code>demo</code>		Demonstration examples

Searching available documentation

MATLAB/Octave	Python	Description
<code>lookfor plot</code>		Search help files
<code>help</code>	<code>help(); modules [Numeric]</code>	List available packages
<code>which plot</code>	<code>help(plot)</code>	Locate functions

Using interactively

MATLAB/Octave	Python	Description
<code>octave -q</code>	<code>ipython -pylab</code>	Start session
<code>TAB or M-?</code>	<code>TAB</code>	Auto completion
<code>foo(.m)</code>	<code>execfile('foo.py') or run foo.py</code>	Run code from file
<code>history</code>	<code>hist -n</code>	Command history
<code>diary on [...] diary off</code>		Save command history
<code>exit or quit</code>	<code>CTRL-D</code>	End session
	<code>CTRL-Z # windows</code>	
	<code>sys.exit()</code>	

Operators

MATLAB/Octave	Python	Description
<code>help -</code>		Help on operator syntax

Arithmetic operators

MATLAB/Octave	Python	Description
<code>a=1; b=2;</code>	<code>a=1; b=1</code>	Assignment; defining a number

<code>a + b</code>	<code>a + b</code> <i>or</i> <code>add(a,b)</code>	Addition
<code>a - b</code>	<code>a - b</code> <i>or</i> <code>subtract(a,b)</code>	Subtraction
<code>a * b</code>	<code>a * b</code> <i>or</i> <code>multiply(a,b)</code>	Multiplication
<code>a / b</code>	<code>a / b</code> <i>or</i> <code>divide(a,b)</code>	Division
<code>a .^ b</code>	<code>a ** b</code> <code>power(a,b)</code> <code>pow(a,b)</code>	Power, a^b
<code>rem(a,b)</code>	<code>a % b</code> <code>remainder(a,b)</code> <code>fmod(a,b)</code>	Remainder
<code>a+=1</code>	<code>a+=b</code> <i>or</i> <code>add(a,b,a)</code>	In place operation to save array creation overhead
<code>factorial(a)</code>		Factorial, $n!$

Relational operators

MATLAB/Octave	Python	Description
<code>a == b</code>	<code>a == b</code> <i>or</i> <code>equal(a,b)</code>	Equal
<code>a < b</code>	<code>a < b</code> <i>or</i> <code>less(a,b)</code>	Less than
<code>a > b</code>	<code>a > b</code> <i>or</i> <code>greater(a,b)</code>	Greater than
<code>a <= b</code>	<code>a <= b</code> <i>or</i> <code>less_equal(a,b)</code>	Less than or equal
<code>a >= b</code>	<code>a >= b</code> <i>or</i> <code>greater_equal(a,b)</code>	Greater than or equal
<code>a ~= b</code>	<code>a != b</code> <i>or</i> <code>not_equal(a,b)</code>	Not Equal

Logical operators

MATLAB/Octave	Python	Description
<code>a && b</code>	<code>a and b</code>	Short-circuit logical AND
<code>a b</code>	<code>a or b</code>	Short-circuit logical OR
<code>a & b</code> <i>or</i> <code>and(a,b)</code>	<code>logical_and(a,b)</code> <i>or</i> <code>a and b</code>	Element-wise logical AND
<code>a b</code> <i>or</i> <code>or(a,b)</code>	<code>logical_or(a,b)</code> <i>or</i> <code>a or b</code>	Element-wise logical OR
<code>xor(a, b)</code>	<code>logical_xor(a,b)</code>	Logical EXCLUSIVE OR
<code>~a</code> <i>or</i> <code>not(a)</code>	<code>logical_not(a)</code> <i>or</i> <code>not a</code>	Logical NOT
<code>~a</code> <i>or</i> <code>!a</code>		
<code>any(a)</code>		True if any element is nonzero
<code>all(a)</code>		True if all elements are nonzero

root and logarithm

MATLAB/Octave	Python	Description
<code>sqrt(a)</code>	<code>math.sqrt(a)</code>	Square root
<code>log(a)</code>	<code>math.log(a)</code>	Logarithm, base e (natural)
<code>log10(a)</code>	<code>math.log10(a)</code>	Logarithm, base 10

<code>log2(a)</code>	<code>math.log(a, 2)</code>	Logarithm, base 2 (binary)
<code>exp(a)</code>	<code>math.exp(a)</code>	Exponential function

Round off

MATLAB/Octave	Python	Description
<code>round(a)</code>	<code>round(a)</code> <i>or</i> <code>math.round(a)</code>	Round
<code>ceil(a)</code>	<code>ceil(a)</code>	Round up
<code>floor(a)</code>	<code>floor(a)</code>	Round down
<code>fix(a)</code>	<code>fix(a)</code>	Round towards zero

Mathematical constants

MATLAB/Octave	Python	Description
<code>pi</code>	<code>math.pi</code>	$\pi=3.141592$
<code>exp(1)</code>	<code>math.e</code> <i>or</i> <code>math.exp(1)</code>	$e=2.718281$

Missing values; IEEE-754 floating point status flags

MATLAB/Octave	Python	Description
<code>NaN</code>	<code>nan</code>	Not a Number
<code>Inf</code>	<code>inf</code>	Infinity, $+\infty$
	<code>plus_inf</code>	Infinity, $+\infty$
	<code>minus_inf</code>	Infinity, $-\infty$
	<code>plus_zero</code>	Plus zero, $+0$
	<code>minus_zero</code>	Minus zero, -0

Complex numbers

MATLAB/Octave	Python	Description
<code>i</code>	<code>z = 1j</code>	Imaginary unit
<code>z = 3+4i</code>	<code>z = 3+4j</code> <i>or</i> <code>z = complex(3,4)</code>	A complex number, $3+4i$
<code>abs(z)</code>	<code>abs(3+4j)</code>	Absolute value (modulus)
<code>real(z)</code>	<code>z.real</code>	Real part
<code>imag(z)</code>	<code>z.imag</code>	Imaginary part
<code>arg(z)</code>		Argument
<code>conj(z)</code>	<code>z.conj(); z.conjugate()</code>	Complex conjugate

Trigonometry

MATLAB/Octave	Python	Description
<code>atan(a,b)</code>	<code>atan2(b,a)</code>	Arctangent, $\arctan(b/a)$
	<code>hypot(x,y)</code>	Hypotenuse; Euclidean distance

Generate random numbers

MATLAB/Octave	Python	Description
<code>rand(1,10)</code>	<code>random.random((10,))</code> <code>random.uniform((10,))</code>	Uniform distribution
<code>2+5*rand(1,10)</code>	<code>random.uniform(2,7,(10,))</code>	Uniform: Numbers between 2 and 7
<code>rand(6)</code>	<code>random.uniform(0,1,(6,6))</code>	Uniform: 6,6 array
<code>randn(1,10)</code>	<code>random.standard_normal((10,))</code>	Normal distribution

Vectors

MATLAB/Octave	Python	Description
<code>a=[2 3 4 5];</code>	<code>a=array([2,3,4,5])</code>	Row vector, $1 \times n$ -matrix
<code>adash=[2 3 4 5]';</code>	<code>array([2,3,4,5])[:,NewAxis]</code> <code>array([2,3,4,5]).reshape(-1,1)</code> <code>r_[1:10,'c']</code>	Column vector, $m \times 1$ -matrix

Sequences

MATLAB/Octave	Python	Description
<code>1:10</code>	<code>arange(1,11, dtype=Float)</code> <code>range(1,11)</code>	1,2,3, ... ,10
<code>0:9</code>	<code>arange(10.)</code>	0.0,1.0,2.0, ... ,9.0
<code>1:3:10</code>	<code>arange(1,11,3)</code>	1,4,7,10
<code>10:-1:1</code>	<code>arange(10,0,-1)</code>	10,9,8, ... ,1
<code>10:-3:1</code>	<code>arange(10,0,-3)</code>	10,7,4,1
<code>linspace(1,10,7)</code>	<code>linspace(1,10,7)</code>	Linearly spaced vector of $n=7$ points
<code>reverse(a)</code>	<code>a[::-1]</code> <i>or</i>	Reverse
<code>a(:) = 3</code>	<code>a.fill(3), a[:] = 3</code>	Set all values to same scalar value

Concatenation (vectors)

MATLAB/Octave	Python	Description
<code>[a a]</code>	<code>concatenate((a,a))</code>	Concatenate two vectors
<code>[1:4 a]</code>	<code>concatenate((range(1,5),a), axis=1)</code>	

Repeating

MATLAB/Octave	Python	Description
---------------	--------	-------------

[a a]	concatenate((a,a))	1 2 3, 1 2 3
	a.repeat(3) <i>or</i>	1 1 1, 2 2 2, 3 3 3
	a.repeat(a) <i>or</i>	1, 2 2, 3 3 3

Miss those elements out

MATLAB/Octave	Python	Description
a(2:end)	a[1:]	miss the first element
a([1:9])		miss the tenth element
a(end)	a[-1]	last element
a(end-1:end)	a[-2:]	last two elements

Maximum and minimum

MATLAB/Octave	Python	Description
max(a,b)	maximum(a,b)	pairwise max
max([a b])	concatenate((a,b)).max()	max of all values in two vectors
[v,i] = max(a)	v,i = a.max(0),a.argmax(0)	

Vector multiplication

MATLAB/Octave	Python	Description
a.*a	a*a	Multiply two vectors
dot(u,v)	dot(u,v)	Vector dot product, $u \cdot v$

Matrices

MATLAB/Octave	Python	Description
a = [2 3;4 5]	a = array([[2,3],[4,5]])	Define a matrix

Concatenation (matrices); rbind and cbind

MATLAB/Octave	Python	Description
[a ; b]	concatenate((a,b), axis=0) vstack((a,b))	Bind rows
[a , b]	concatenate((a,b), axis=1) hstack((a,b))	Bind columns
	concatenate((a,b), axis=2) dstack((a,b))	Bind slices (three-way arrays)
[a(:), b(:)]	concatenate((a,b), axis=None)	Concatenate matrices into one vector
[1:4 ; 1:4]	concatenate((r_[1:5],r_[1:5])).reshape(2,-1) vstack((r_[1:5],r_[1:5]))	Bind rows (from vectors)

```
[1:4 ; 1:4]'
```

Bind columns (from
vectors)

Array creation

MATLAB/Octave	Python	Description
<code>zeros(3,5)</code>	<code>zeros((3,5),Float)</code>	0 filled array
	<code>zeros((3,5))</code>	0 filled array of integers
<code>ones(3,5)</code>	<code>ones((3,5),Float)</code>	1 filled array
<code>ones(3,5)*9</code>		Any number filled array
<code>eye(3)</code>	<code>identity(3)</code>	Identity matrix
<code>diag([4 5 6])</code>	<code>diag((4,5,6))</code>	Diagonal
<code>magic(3)</code>		Magic squares; Lo Shu
	<code>a = empty((3,3))</code>	Empty array

Reshape and flatten matrices

MATLAB/Octave	Python	Description
<code>reshape(1:6,3,2)';</code>	<code>arange(1,7).reshape(2,-1)</code> <code>a.setshape(2,3)</code>	Reshaping (rows first)
<code>reshape(1:6,2,3);</code> <code>a'(:)</code>	<code>arange(1,7).reshape(-1,2).transpose()</code> <code>a.flatten()</code> <i>or</i>	Reshaping (columns first) Flatten to vector (by rows, like comics)
<code>a(:)</code>	<code>a.flatten(1)</code>	Flatten to vector (by columns)
<code>vech(a)</code>		Flatten upper triangle (by columns)

Shared data (slicing)

MATLAB/Octave	Python	Description
<code>b = a</code>	<code>b = a.copy()</code>	Copy of a

Indexing and accessing elements (Python: slicing)

MATLAB/Octave	Python	Description
<code>a = [11 12 13 14 ... 21 22 23 24 ... 31 32 33 34]</code>	<code>a = array([[11, 12, 13, 14], [21, 22, 23, 24], [31, 32, 33, 34]])</code>	Input is a 3,4 array
<code>a(2,3)</code>	<code>a[1,2]</code>	Element 2,3 (row,col)
<code>a(1,:)'</code>	<code>a[0,]</code>	First row
<code>a(:,1)</code>	<code>a[:,0]</code>	First column
<code>a([1 3],[1 4]);</code>	<code>a.take([0,2]).take([0,3], axis=1)</code>	Array as indices

<code>a(2:end,:)</code>	<code>a[1:,]</code>	All, except first row
<code>a(end-1:end,:)</code>	<code>a[-2:,]</code>	Last two rows
<code>a(1:2:end,:)</code>	<code>a[:,2:,]</code>	Strides: Every other row
	<code>a[:,...,2]</code>	Third in last dimension (axis)
<code>a(:,[1 3 4])</code>	<code>a.take([0,2,3],axis=1)</code>	Remove one column
	<code>a.diagonal(offset=0)</code>	Diagonal

Assignment

MATLAB/Octave	Python	Description
<code>a(:,1) = 99</code>	<code>a[:,0] = 99</code>	
<code>a(:,1) = [99 98 97]'</code>	<code>a[:,0] = array([99,98,97])</code>	
<code>a(a>90) = 90;</code>	<code>(a>90).choose(a,90)</code>	Clipping: Replace all elements over 90
	<code>a.clip(min=None, max=90)</code>	
	<code>a.clip(min=2, max=5)</code>	Clip upper and lower values

Transpose and inverse

MATLAB/Octave	Python	Description
<code>a'</code>	<code>a.conj().transpose()</code>	Transpose
<code>a.' or transpose(a)</code>	<code>a.transpose()</code>	Non-conjugate transpose
<code>det(a)</code>	<code>linalg.det(a)</code> <i>or</i>	Determinant
<code>inv(a)</code>	<code>linalg.inv(a)</code> <i>or</i>	Inverse
<code>pinv(a)</code>	<code>linalg.pinv(a)</code>	Pseudo-inverse
<code>norm(a)</code>	<code>norm(a)</code>	Norms
<code>eig(a)</code>	<code>linalg.eig(a)[0]</code>	Eigenvalues
<code>svd(a)</code>	<code>linalg.svd(a)</code>	Singular values
<code>chol(a)</code>	<code>linalg.cholesky(a)</code>	Cholesky factorization
<code>[v,l] = eig(a)</code>	<code>linalg.eig(a)[1]</code>	Eigenvectors
<code>rank(a)</code>	<code>rank(a)</code>	Rank

Sum

MATLAB/Octave	Python	Description
<code>sum(a)</code>	<code>a.sum(axis=0)</code>	Sum of each column
<code>sum(a')</code>	<code>a.sum(axis=1)</code>	Sum of each row
<code>sum(sum(a))</code>	<code>a.sum()</code>	Sum of all elements
	<code>a.trace(offset=0)</code>	Sum along diagonal
<code>cumsum(a)</code>	<code>a.cumsum(axis=0)</code>	Cumulative sum (columns)

Sorting

MATLAB/Octave	Python	Description
<code>a = [4 3 2 ; 2 8 6 ; 1 4 7]</code>	<code>a = array([[4,3,2],[2,8,6],[1,4,7]])</code>	Example data
<code>sort(a(:))</code>	<code>a.ravel().sort()</code> <i>or</i>	Flat and sorted
<code>sort(a)</code>	<code>a.sort(axis=0)</code> <i>or</i> <code>msort(a)</code>	Sort each column
<code>sort(a')'</code>	<code>a.sort(axis=1)</code>	Sort each row
<code>sortrows(a,1)</code>	<code>a[a[:,0].argsort(),:]</code>	Sort rows (by first row)
	<code>a.ravel().argsort()</code>	Sort, return indices
	<code>a.argsort(axis=0)</code>	Sort each column, return indices
	<code>a.argsort(axis=1)</code>	Sort each row, return indices

Maximum and minimum

MATLAB/Octave	Python	Description
<code>max(a)</code>	<code>a.max(0)</code> <i>or</i> <code>amax(a [,axis=0])</code>	max in each column
<code>max(a')</code>	<code>a.max(1)</code> <i>or</i> <code>amax(a, axis=1)</code>	max in each row
<code>max(max(a))</code>	<code>a.max()</code> <i>or</i>	max in array
<code>[v i] = max(a)</code>		return indices, i
<code>max(b,c)</code>	<code>maximum(b,c)</code>	pairwise max
<code>cummax(a)</code>		
	<code>a.ptp(); a.ptp(0)</code>	max-to-min range

Matrix manipulation

MATLAB/Octave	Python	Description
<code>fliplr(a)</code>	<code>fliplr(a)</code> <i>or</i> <code>a[:,::-1]</code>	Flip left-right
<code>flipud(a)</code>	<code>flipud(a)</code> <i>or</i> <code>a[::-1,]</code>	Flip up-down
<code>rot90(a)</code>	<code>rot90(a)</code>	Rotate 90 degrees
<code>repmat(a,2,3)</code>	<code>kron(ones((2,3)),a)</code>	Repeat matrix: [a a a ; a a a]
<code>kron(ones(2,3),a)</code>		
<code>triu(a)</code>	<code>triu(a)</code>	Triangular, upper
<code>tril(a)</code>	<code>tril(a)</code>	Triangular, lower

Equivalents to "size"

MATLAB/Octave	Python	Description
<code>size(a)</code>	<code>a.shape</code> <i>or</i> <code>a.getshape()</code>	Matrix dimensions
<code>size(a,2)</code> <i>or</i> <code>length(a)</code>	<code>a.shape[1]</code> <i>or</i> <code>size(a, axis=1)</code>	Number of columns
<code>length(a(:))</code>	<code>a.size</code> <i>or</i> <code>size(a[, axis=None])</code>	Number of elements
<code>ndims(a)</code>	<code>a.ndim</code>	Number of dimensions
	<code>a.nbytes</code>	Number of bytes used in memory

Matrix- and elementwise- multiplication

MATLAB/Octave	Python	Description
<code>a .* b</code>	<code>a * b</code> <i>or</i> <code>multiply(a,b)</code>	Elementwise operations
<code>a * b</code>	<code>matrixmultiply(a,b)</code>	Matrix product (dot product)
	<code>inner(a,b)</code> <i>or</i>	Inner matrix vector multiplication $a \cdot b'$
	<code>outer(a,b)</code> <i>or</i>	Outer product
<code>kron(a,b)</code>	<code>kron(a,b)</code>	Kronecker product
<code>a / b</code>		Matrix division, $b \cdot a^{-1}$
<code>a \ b</code>	<code>linalg.solve(a,b)</code>	Left matrix division, $b \cdot a^{-1}$ (solve linear equations)
	<code>vdot(a,b)</code>	Vector dot product
	<code>cross(a,b)</code>	Cross product

Find; conditional indexing

MATLAB/Octave	Python	Description
<code>find(a)</code>	<code>a.ravel().nonzero()</code>	Non-zero elements, indices
<code>[i j] = find(a)</code>	<code>(i,j) = a.nonzero()</code> <code>(i,j) = where(a!=0)</code>	Non-zero elements, array indices
<code>[i j v] = find(a)</code>	<code>v = a.compress((a!=0).flat)</code> <code>v = extract(a!=0,a)</code>	Vector of non-zero values
<code>find(a>5.5)</code>	<code>(a>5.5).nonzero()</code>	Condition, indices
	<code>a.compress((a>5.5).flat)</code>	Return values
<code>a .* (a>5.5)</code>	<code>where(a>5.5,0,a)</code> <i>or</i> <code>a * (a>5.5)</code>	Zero out elements above 5.5
	<code>a.put(2,indices)</code>	Replace values

Multi-way arrays

MATLAB/Octave	Python	Description
<code>a = cat(3, [1 2; 1 2], [3 4; 3 4]);</code> <code>a(1, :, :)</code>	<code>a = array([[[1,2],[1,2]], [[3,4],[3,4]]])</code> <code>a[0,...]</code>	Define a 3-way array

File input and output

MATLAB/Octave	Python	Description
<code>f = load('data.txt')</code>	<code>f = fromfile("data.txt")</code> <code>f = load("data.txt")</code>	Reading from a file (2d)
<code>f = load('data.txt')</code>	<code>f = load("data.txt")</code>	Reading from a file (2d)

<code>x = dlmread('data.csv', ';')</code>	<code>f = load('data.csv', delimiter=';')</code>	Reading from a CSV file (2d)
<code>save -ascii data.txt f</code>	<code>save('data.csv', f, fmt='%0.6f', delimiter=';')</code>	Writing to a file (2d)
	<code>f.tofile(file='data.csv', format='%0.6f', sep=';')</code>	Writing to a file (1d)
	<code>f = fromfile(file='data.csv', sep=';')</code>	Reading from a file (1d)

Plotting

Basic x-y plots

MATLAB/Octave	Python	Description
<code>plot(a)</code>	<code>plot(a)</code>	1d line plot
<code>plot(x(:,1),x(:,2),'o')</code>	<code>plot(x[:,0],x[:,1],'o')</code>	2d scatter plot
<code>plot(x1,y1, x2,y2)</code>	<code>plot(x1,y1,'bo', x2,y2,'go')</code>	Two graphs in one plot
<code>plot(x1,y1)</code>	<code>plot(x1,y1,'o')</code>	Overplotting: Add new plots to current
<code>hold on</code>	<code>plot(x2,y2,'o')</code>	
<code>plot(x2,y2)</code>	<code>show() # as normal</code>	
<code>subplot(211)</code>	<code>subplot(211)</code>	subplots
<code>plot(x,y,'ro-')</code>	<code>plot(x,y,'ro-')</code>	Plotting symbols and color

Axes and titles

MATLAB/Octave	Python	Description
<code>grid on</code>	<code>grid()</code>	Turn on grid lines
<code>axis equal</code>	<code>figure(figsize=(6,6))</code>	1:1 aspect ratio
<code>axis('equal')</code>		
<code>replot</code>		
<code>axis([0 10 0 5])</code>	<code>axis([0, 10, 0, 5])</code>	Set axes manually
<code>title('title')</code>		Axis labels and titles
<code>xlabel('x-axis')</code>		
<code>ylabel('y-axis')</code>		
	<code>text(2,25,'hello')</code>	Insert text

Log plots

MATLAB/Octave	Python	Description
<code>semilogy(a)</code>	<code>semilogy(a)</code>	logarithmic y-axis
<code>semilogx(a)</code>	<code>semilogx(a)</code>	logarithmic x-axis
<code>loglog(a)</code>	<code>loglog(a)</code>	logarithmic x and y axes

Filled plots and bar plots

MATLAB/Octave

```
fill(t,s,'b', t,c,'g')
% fill has a bug?
```

Python

```
fill(t,s,'b', t,c,'g',
alpha=0.2)
```

Description

Filled plot

Functions

MATLAB/Octave

```
f = inline('sin(x/3) -
cos(x/5)')
ezplot(f,[0,40])
fplot('sin(x/3) - cos(x/5)',
[0,40])
% no ezplot
```

Python

```
x = arange(0,40,.5)
y = sin(x/3) - cos(x/5)
plot(x,y, 'o')
```

Description

Defining functions

Plot a function for given range

Polar plots

MATLAB/Octave

```
theta = 0:.001:2*pi;
r = sin(2*theta);
polar(theta, rho)
```

Python

```
theta = arange(0,2*pi,0.001)
r = sin(2*theta)
polar(theta, rho)
```

Description

Histogram plots

MATLAB/Octave

```
hist(randn(1000,1))
hist(randn(1000,1), -4:4)
plot(sort(a))
```

Python**Description**

3d data

Contour and image plots

MATLAB/Octave

```
contour(z)

contourf(z); colormap(gray)

image(z)
colormap(gray)
```

Python

```
levels, colls = contour(Z, V,
origin='lower', extent=
(-3,3,-3,3))
clabel(colls, levels, inline=1,
fmt='%1.1f', fontsize=10)

contourf(Z, V,
cmap=cm.gray,
origin='lower',
extent=(-3,3,-3,3))

im = imshow(Z,
interpolation='bilinear',
origin='lower',
extent=(-3,3,-3,3))
```

Description

Contour plot

Filled contour plot

Plot image data

	# imshow() and contour() as above	Image with contours
quiver()	quiver()	Direction field vectors

Perspective plots of surfaces over the x-y plane

MATLAB/Octave	Python	Description
<pre>n=-2:.1:2; [x,y] = meshgrid(n,n); z=x.*exp(-x.^2-y.^2); mesh(z) surf(x,y,z) <i>or</i> surf1(x,y,z) % no surf1()</pre>	<pre>n=arrayrange(-2,2,.1) [x,y] = meshgrid(n,n) z = x*power(math.e,-x**2-y**2)</pre>	<p>Mesh plot</p> <p>Surface plot</p>

Scatter (cloud) plots

MATLAB/Octave	Python	Description
plot3(x,y,z, 'k+')		3d scatter plot

Save plot to a graphics file

MATLAB/Octave	Python	Description
<pre>plot(1:10) print -depsc2 foo.eps gset output "foo.eps" gset terminal postscript eps plot(1:10)</pre>	<pre>savefig('foo.eps')</pre>	PostScript
	<pre>savefig('foo.pdf')</pre>	PDF
	<pre>savefig('foo.svg')</pre>	SVG (vector graphics for www)
<pre>print -dpng foo.png</pre>	<pre>savefig('foo.png')</pre>	PNG (raster graphics)

Data analysis

Set membership operators

MATLAB/Octave	Python	Description
<pre>a = [1 2 2 5 2]; b = [2 3 4];</pre>	<pre>a = array([1,2,2,5,2]) b = array([2,3,4]) a = set([1,2,2,5,2]) b = set([2,3,4])</pre>	Create sets
unique(a)	<pre>unique1d(a) unique(a) set(a)</pre>	Set unique
union(a,b)	<pre>union1d(a,b) a.union(b)</pre>	Set union

<code>intersect(a,b)</code>	<code>intersect1d(a)</code> <code>a.intersection(b)</code>	Set intersection
<code>setdiff(a,b)</code>	<code>setdiff1d(a,b)</code> <code>a.difference(b)</code>	Set difference
<code>setxor(a,b)</code>	<code>setxor1d(a,b)</code> <code>a.symmetric_difference(b)</code>	Set exclusion
<code>ismember(2,a)</code>	<code>2 in a</code> <code>setmember1d(2,a)</code> <code>contains(a,2)</code>	True for set member

Statistics

MATLAB/Octave	Python	Description
<code>mean(a)</code>	<code>a.mean(axis=0)</code> <code>mean(a [,axis=0])</code>	Average
<code>median(a)</code>	<code>median(a)</code> <i>or</i> <code>median(a [,axis=0])</code>	Median
<code>std(a)</code>	<code>a.std(axis=0)</code> <i>or</i> <code>std(a [,axis=0])</code>	Standard deviation
<code>var(a)</code>	<code>a.var(axis=0)</code> <i>or</i> <code>var(a)</code>	Variance
<code>corr(x,y)</code>	<code>correlate(x,y)</code> <i>or</i> <code>corrcoef(x,y)</code>	Correlation coefficient
<code>cov(x,y)</code>	<code>cov(x,y)</code>	Covariance

Interpolation and regression

MATLAB/Octave	Python	Description
<code>z = polyval(polyfit(x,y,1),x)</code> <code>plot(x,y,'o', x,z ,'-')</code> <code>a = x\y</code>	<code>(a,b) = polyfit(x,y,1)</code> <code>plot(x,y,'o', x,a*x+b,'-')</code> <code>linalg.lstsq(x,y)</code>	Straight line fit Linear least squares $y = ax + b$
<code>polyfit(x,y,3)</code>	<code>polyfit(x,y,3)</code>	Polynomial fit

Non-linear methods

Polynomials, root finding

MATLAB/Octave	Python	Description
	<code>poly()</code>	Polynomial
<code>roots([1 -1 -1])</code>	<code>roots()</code>	Find zeros of polynomial
<code>f = inline('1/x - (x-1)')</code> <code>fzero(f,1)</code>		Find a zero near $x = 1$
<code>solve('1/x = x-1')</code>		Solve symbolic equations
<code>polyval([1 2 1 2],1:10)</code>	<code>polyval(array([1,2,1,2]),arange(1,11))</code>	Evaluate polynomial

Differential equations

MATLAB/Octave

```
diff(a)
```

Python

```
diff(x, n=1, axis=0)
```

Description

Discrete difference function and approximate derivative
Solve differential equations

Fourier analysis

MATLAB/Octave

```
fft(a)
```

```
ifft(a)
```

Python

```
fft(a) or
```

```
ifft(a) or
```

```
convolve(x,y)
```

Description

Fast fourier transform
Inverse fourier transform
Linear convolution

Symbolic algebra; calculus

MATLAB/Octave

```
factor()
```

Python

Description

Factorization

Programming

MATLAB/Octave

```
.m
```

```
%
```

```
% or #
```

```
% must be in MATLABPATH
```

```
% must be in LOADPATH
```

```
string='a=234';
```

```
eval(string)
```

Python

```
.py
```

```
#
```

```
from pylab import *
```

```
string="a=234"
```

```
eval(string)
```

Description

Script file extension
Comment symbol (rest of line)

Import library functions

Eval

Loops

MATLAB/Octave

```
for i=1:5; disp(i); end
```

```
for i=1:5
```

```
disp(i)
```

```
disp(i*2)
```

```
end
```

Python

```
for i in range(1,6): print(i)
```

```
for i in range(1,6):
```

```
print(i)
```

```
print(i*2)
```

Description

for-statement

Multiline for statements

Conditionals

MATLAB/Octave

```
if 1>0 a=100; end
```

```
if 1>0 a=100; else a=0; end
```

Python

```
if 1>0: a=100
```

Description

if-statement

if-else-statement

Debugging

MATLAB/Octave	Python	Description
<code>ans</code>		Most recent evaluated expression
<code>whos</code> <i>or</i> <code>who</code>		List variables loaded into memory
<code>clear x</code> <i>or</i> <code>clear [all]</code>		Clear variable <code>\$x\$</code> from memory
<code>disp(a)</code>	<code>print a</code>	Print

Working directory and OS

MATLAB/Octave	Python	Description
<code>dir</code> <i>or</i> <code>ls</code>	<code>os.listdir(".")</code>	List files in directory
<code>what</code>	<code>grep.grep("*.py")</code>	List script files in directory
<code>pwd</code>	<code>os.getcwd()</code>	Displays the current working directory
<code>cd foo</code>	<code>os.chdir('foo')</code>	Change working directory
<code>!notepad</code>	<code>os.system('notepad')</code>	Invoke a System Command
<code>system("notepad")</code>	<code>os.popen('notepad')</code>	

Time-stamp: "2007-11-09T16:46:36 vidar"

©2006 Vidar Bronken Gundersen, /mathesaurus.sf.net

Permission is granted to copy, distribute and/or modify this document as long as the above attribution is retained.