

AUTOMATED GUIDED VEHICLE APPLICATION:

PRECISION AGRICULTURE

XIANGNAN GONG

Submitted to the faculty of the School of Informatics in partial
fulfillment of the requirements for the degree of Master of Science in
Electrical and Computer Engineering, Purdue University

Indianapolis, Indiana

July 20, 2016

Table of Contents

1	Introduction	1
1.1	Introduction to subject	1
1.2	Importance of subject	1
1.3	Knowledge gap	1
2	Background	3
2.1	Related research	3
2.2	Current understanding	4
2.3	Hypothesis or research question	4
2.4	Intended project	6
3	Methods	6
3.1	Materials and instruments	6
3.2	Laser guided	7
3.2.1	Imaging processing	7
3.2.2	Buffer design	8
3.2.3	Improvement	8
3.3	Object guided	10
3.4	Vision guided	11
3.5	Alternate plans: Ultrasonic guided	12
4	Results	12
4.1	Introduction	12
4.2	Important highlights	13
4.3	Feasibility	13
4.4	Constraints	13
4.5	Application to other areas	14
5	Conclusion	14
5.1	Importance of outdoor-AGV	14
5.2	Overview of significant	15
5.3	Limitations	15
5.4	Further improvement	15
6	REFERENCES	17
A	Appendix A	18

List of Tables

1	Landratio	2
2	Productivityratio	3
3	Parts	7

List of Figures

1	Farm	2
2	Twoears	4
3	Buffer	5
4	Imaging	8
5	1D	9
6	2D	9
7	3D	10
8	Curtain	10
9	Objectperspective	11
10	Perspective	12

Abstract

Nowadays, there are many types of automated guided vehicle (AGV) running in different field of industries. Typically their job is moving raw materials or parts around the manufacturing facility. And they can be very accurate in working by following the guide from the wires in the floor, magnets, laser, or vision. However, they all requires an indoor condition. Therefore, the purpose of this thesis report is to discuss the implement of the outdoor AGV. An outdoor AGV has much more constrains than indoor. The environment indoor can be easily controlled while the door is not. The condition could be rough ground, no preset guiding wire or magnets, vision blocking by dust, and so on. The solution, which will talk in this paper, to achieve the outdoor AGV is using laser or vision to guide. In addition, a buffer will be set to stabilize the cargo or others working devices, to prevent them from the shaking due to the rough ground. To be more specific, a prototype will be built to simulate the working of seeder. In agriculture, it is very important to plant corns in a straight line. It benefits not only in absorbing sunlight and ventilation, but also reduce the work of irrigation, fertilizing, and harvest. Because a straight line of corn also mean a straight line of aisle. And more importantly, to achieve unmanned agriculture, a corn field with straight line of aisle will be a good condition for other agriculture robots.




Figure 1: Farm

人均土地比

Table 1: Landratio

This is the Knowledge gap. [Evers and Koppers, 1996]This is the Knowledge gap.
This is the Knowledge gap. This is the Knowledge gap. This is the Knowledge gap.
This is the Knowledge gap. This is the Knowledge gap. This is the Knowledge gap.
This is the Knowledge gap. This is the Knowledge gap. This is the Knowledge gap.
This is the Knowledge gap. This is the Knowledge gap. This is the Knowledge gap.

产量比

Table 2: Productivityratio

This is the Knowledge gap. This is the Knowledge gap. This is the Knowledge gap.
This is the Knowledge gap. This is the Knowledge gap.
This is the Knowledge gap. [Gaskins and TANCHOCO, 1987]
4 5 6

2 Background

2.1 Related research

This is the Related research. This is the Related research. This is the Related
research. This is the Related research. This is the Related research. This is the
Related research. This is the Related research. This is the Related research. This is
the Related research. This is the Related research. This is the Related research.
This is the Related research. This is the Related research. This is the Related
research. This is the Related research. This is the Related research. This is the
Related research. This is the Related research. This is the Related research. This is
the Related research. This is the Related research. This is the Related research.
[Lenain et al., 2006] 7

2.2 Current understanding

This is the Current understanding. This is the Current understanding. This is the Current understanding. [Lenain et al., 2006] This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. [Douglas and Bencel, 2000] This is the Current understanding. This is the Current understanding. This is the Current understanding. This is the Current understanding. [Egbelu and Tanchoco, 1984] GPS7 23

2.3 Hypothesis or research question

This is the Hypothesis or research question. This is the Hypothesis or research
question. This is the Hypothesis or research question. This is the Hypothesis or
research question. This is the Hypothesis or research question. This is the
Hypothesis or research question. This is the Hypothesis or research question. This
is the Hypothesis or research question. This is the Hypothesis or research question.
This is the Hypothesis or research question. This is the Hypothesis or research
question. This is the Hypothesis or research question. This is the Hypothesis or




Figure 2: Twoears

research question. This is the Hypothesis or research question. This is the Hypothesis or research question. This is the Hypothesis or research question. This

此处应有图片

缓冲器模型

question. This is the Hypothesis or research question. This is the Hypothesis or research question. This is the Hypothesis or research question. This is the

此处应有图片

Figure 5: 1D

此处应有图片

Figure 6: 2D

improvement. This is the improvement. This is the improvement. This is the
improvement. This is the improvement. This is the improvement. This is the
improvement. This is the improvement. This is the improvement. This is the
improvement. This is the improvement. This is the improvement. This is the
improvement. This is the improvement. This is the improvement. 3D CAD CAD

此处应有图片

Figure 7: 3D

此处应有图片

Figure 8: Curtain

3.3 Object guided

This is the object guided. This is the object guided. This is the object guided. This
is the object guided. This is the object guided. This is the object guided. This is
the object guided. This is the object guided. This is the object guided. This is the

object guided. This is the object guided. This is the object guided. This is the
object guided. This is the object guided. This is the object guided. This is the
object guided. This is the object guided. This is the object guided. This is the




Figure 9: Objectperspective

object guided. This is the object guided. This is the object guided. This is the
object guided. This is the object guided. This is the object guided. This is the
object guided. This is the object guided. This is the object guided. Traffic Cone

3.4 Vision guided

[illegible]

6 REFERENCES

References

- [Bozer and Srinivasan, 1991] Bozer, Y. A. and Srinivasan, M. M. (1991). Tandem configurations for automated guided vehicle systems and the analysis of single vehicle loops. *IIE transactions*, 23(1):72–82.
- [Douglas and Bencel, 2000] Douglas, B. D. and Bencel, J. A. (2000). Navigation system for automatic guided vehicle. US Patent 6,049,745.
- [Egbelu and Tanchoco, 1986] Egbelu, P. J. and Tanchoco, J. (1986). Potentials for bi-directional guide-path for automated guided vehicle based systems. *International Journal of Production Research*, 24(5):1075–1097.
- [Egbelu and Tanchoco, 1984] Egbelu, P. J. and Tanchoco, J. M. (1984). Characterization of automatic guided vehicle dispatching rules. *The International Journal of Production Research*, 22(3):359–374.
- [Evers and Koppers, 1996] Evers, J. J. and Koppers, S. A. (1996). Automated guided vehicle traffic control at a container terminal. *Transportation Research Part A: Policy and Practice*, 30(1):21–34.
- [Gaskins and TANCHOCO, 1987] Gaskins, R. and TANCHOCO, J. A. (1987). Flow path design for automated guided vehicle systems. *International Journal of Production Research*, 25(5):667–676.
- [Lenain et al., 2006] Lenain, R., Thuilot, B., Cariou, C., and Martinet, P. (2006). High accuracy path tracking for vehicles in presence of sliding: Application to farm vehicle automatic guidance for agricultural tasks. *Autonomous robots*, 21(1):79–97.
- [Muller, 1983] Muller, T. (1983). Automated guided vehicles.
- [Vis, 2006] Vis, I. F. (2006). Survey of research in the design and control of automated guided vehicle systems. *European Journal of Operational Research*, 170(3):677–709.
- [Wu and Zhou, 2004] Wu, N. and Zhou, M. (2004). Modeling and deadlock control of automated guided vehicle systems. *IEEE/ASME transactions on mechatronics*, 9(1):50–57.

A Appendix A

This is appendix A