Network Layer:
Distance Vector Protocols Variations
Link-State Protocol

Qiao Xiang

https://qiaoxiang.me/courses/cnns-xmuf21/index.shtml

12/02/2021

This deck of slides are heavily based on CPSC 433/533 at Yale University, by courtesy of Dr. Y. Richard Yang.

Outline

- Admin and recap
- Network overview
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
      - Link state protocols (distributed state synchronization)

Admin

- Lab assignment six posted
  - Due Jan. 4, 2022

Recap: Routing Context

Routing

Goal: determine "good" paths (sequences of routers) thru networks from source to dest.



Often depends on a graph abstraction:

- graph nodes are routers
- graph edges are physical links
  - links have properties: delay, capacity, $ cost, policy



Recap: Routing Design Space

- Routing has a large design space
  - who decides routing?
    - source routing: end hosts make decision
    - network routing: networks make decision
  - how many paths from source s to destination d?
    - multi-path routing
    - single path routing
  - what does routing compute?
    - network cost minimization (shortest path routing)
    - QoS aware
  - will routing adapt to network traffic demand?
    - adaptive routing
    - static routing
  - ...



Recap: Distance Vector Routing: Basic Idea (Bellman-Ford Alg)

- At node i, the basic update rule

$$d_i = \min_{j \in N(i)} (d_{ij} + d_j)$$

where

- d_i denotes the distance estimation from i to the destination,
- N(i) is set of neighbors of node i, and
- d_{ij} is the distance of the direct link from i to j



Recap: Synchronous Bellman-Ford (SBF)

- Nodes update in rounds:
  - there is a global clock;
  - at the beginning of each round, each node sends its estimate to all of its neighbors;
  - at the end of the round, updates its estimation

$$d_i(h+1) = \min_{j \in N(i)} (d_{ij} + d_j(h))$$



Recap: SBF/∞



- Initialization (time 0):

$$d_i(0) = \begin{cases} 0 & \text{i} = \text{dest} \\ \infty & \text{otherwise} \end{cases}$$

Example

$$d_i(h+1) = \min_{j \in N(i)} (d_{ij} + d_j(h))$$



Consider D as destination; d(t) is a vector consisting of estimation of each node at round t

	A	B	C	E	D
d(0)	∞	∞	∞	∞	0
d(1)	∞	∞	2	2	0
d(2)	12	3	2	2	0
d(3)	10	3	2	2	0
d(4)	10	3	2	2	0

Observation: $d(0) \geq d(1) \geq d(2) \geq d(3) \geq d(4) = d^*$

$$d_i(h+1) = \min_{j \in N(i)} (d_{ij} + d_j(h))$$

A Nice Property of SBF: Monotonicity

- Consider two configurations d(t) and d'(t)
- If d(t) ≥ d'(t)
  - i.e., each node has a higher estimate in one scenario (d) than in another scenario (d'),
- then d(t+1) ≥ d'(t+1)
  - i.e., each node has a higher estimate in d than in d' after one round of synchronous update.

Recap: SBF at another Initial Configuration: SBF/-1



- Initialization (time 0):

$$d_i(0) = \begin{cases} 0 & \text{i} = \text{dest} \\ -1 & \text{otherwise} \end{cases}$$

Example

$$d_i(h+1) = \min_{j \in N(i)} (d_{ij} + d_j(h))$$



Consider D as destination

	A	B	C	E	D
d(0)	-1	-1	-1	-1	0
d(1)	6	0	0	2	0
d(2)	7	1	1	2	0
d(3)	8	2	2	2	0
d(4)	9	3	3	2	0
d(5)	10	3	3	2	0
d(6)	10	3	3	2	0

Observation: $d(0) \leq d(1) \leq d(2) \leq d(3) \leq d(4) \leq d(5) = d(6) = d^*$

Correctness of SBF/-1

- SBF/-1 converges due to monotonicity
- Remaining question:
  - Can we guarantee that SBF/-1 converges to shortest path?

Correctness of SBF/-1

- Common between SBF/∞ and SBF/-1: they solve the Bellman equation

$$d_i = \min_{j \in N(i)} (d_{ij} + d_j)$$

where $d_D = 0$.

- We have proven SBF/∞ is the shortest path solution.
- SBF/-1 computes shortest path if Bellman equation has a unique solution.

$$d_i = \min_{j \in N(i)} (d_{ij} + d_j)$$

Uniqueness of Solution to BE

- Assume another solution d, we will show that d = d*

case 1: we show d ≥ d*

Since d is a solution to BE, we can construct paths as follows: for each i, pick a j which satisfies the equation; since d* is shortest, d ≥ d*



$$d_i = \min_{j \in N(i)} (d_{ij} + d_j)$$

Uniqueness of Solution to BE

Case 2: we show d ≤ d*

assume we run SBF with two initial configurations:

- one is d
- another is SBF/∞ (d^∞),

-> monotonicity and convergence of SBF/∞ imply that d ≤ d*

Discussion

- Will SBF converge under other non-negative initial conditions?

- Problems of running *synchronous* BF?

Outline

- Admin and recap
- Network overview
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - *Distributed distance vector protocols*
        - synchronous Bellman-Ford (SBF)
        - *asynchronous Bellman-Ford (ABF)*

Asynchronous Bellman-Ford (ABF)

- No notion of global iterations
  - each node updates at its own pace
- Asynchronously each node i computes

$$d_i = \min_{j \in N(i)} (d_{ij} + d_j^i)$$

using last received value d^i_j from neighbor j.

- Asynchronously node j sends its estimate to its neighbor i:
  - We assume that there is an upper bound on the delay of estimate packet

ABF: Example



Below is just one step! The protocol repeats forever!

	distance tables from neighbors			computation			E's distance table	distance table E sends to its neighbors
$d_E()$	A	B	D	A	B	D		
A	0	7	∞	10	15	∞	A: 10	A: 10
B	7	0	∞	17	8	∞	B: 8	B: 8
C	∞	1	2	∞	9	4	D: 4	C: 4
D	∞	∞	0	∞	∞	2	D: 2	D: 2
	10	8	2					E: 0

destinations

Asynchronous Bellman-Ford (ABF)

- ABF will eventually converge to the shortest path
  - links can go down and come up – but if topology is stabilized after some time t and connected, ABF will eventually converge to the shortest path !

ABF Convergence Proof Complexity: Complex System State



What is system state?

System State



three types of distance state from node j:

- d_j: current distance estimate state at node j

- d^i_j: last d_j that neighbor i received

- d^i_j: those d_j that are still in transit to neighbor i

ABF Convergence Proof: The Sandwich Technique

- Basic idea:
  - bound system state using extreme states
- Extreme states:
  - SBF/∞; call the sequence U()
  - SBF/-1; call the sequence L()

ABF Convergence

- Consider the time when the topology is stabilized as time 0

- U(0) and L(0) provide upper and lower bounds at time 0 on all corresponding elements of states
  - $L_j(0) \le d_j \le U_j(0)$ for all d_j state at node j
  - $L_j(0) \le d^i_j \le U_j(0)$
  - $L_j(0) \le$ `update messages` $d^i_j \le U_j(0)$

ABF Convergence

- d_j
  - after at least one update at node j: d_j falls between $L_j(1) \le d_j \le U_j(1)$
- d^i_j :
  - eventually all d^i_j that are only bounded by $L_j(0)$ and $U_j(0)$ are replaced with in $L_j(1)$ and $U_j(1)$



Asynchronous Bellman-Ford: Summary

- Distributed
  - each node communicates its routing table to its directly-attached neighbors
- Iterative
  - continues periodically or when link changes, e.g. detects a link failure
- Asynchronous
  - nodes need *not* exchange info/iterate in lock step!
- Convergence
  - in finite steps, independent of initial condition if network is connected

Summary: Distributed Distance-Vector

- Tool box: a key technique for proving convergence (liveness) of distributed protocols: monotonicity and bounding-box (sandwich) design
  - Consider two configurations d(t) and d'(t):
    - if d(t) <= d'(t), then d(t+1) <= d'(t+1)
  - Identify two extreme configurations to sandwich any real configurations

Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
        - synchronous Bellman-Ford (SBF)
        - asynchronous Bellman-Ford (ABF)
        - *properties of DV*

Properties of Distance-Vector Algorithms

- Good news propagate fast



B	C	D	E	
∞	∞	∞	∞	Initially
1	∞	∞	∞	After 1 exchange
1	2	∞	∞	After 2 exchanges
1	2	3	∞	After 3 exchanges
1	2	3	4	After 4 exchanges

Properties of Distance-Vector Algorithms

- Bad news propagate slowly



A-B link down

1	2	3	4	Initially
3	2	3	4	After 1 exchange
3	4	3	4	After 2 exchanges
5	4	5	4	After 3 exchanges
5	6	5	6	After 4 exchanges
7	6	7	6	After 5 exchanges
7	8	7	8	After 6 exchanges
	⋮			
∞	∞	∞	∞	

- This is called the *counting-to-infinity* problem
- Q: what causes counting-to-infinity?

Counting-To-Infinity is Because of Routing Loop

- Counting-to-infinity is caused by a routing loop, which is a global state (consisting of the nodes' local states) at a global moment (observed by an oracle) such that there exist nodes A, B, C, … E such that A (locally) thinks B as next hop, B thinks C as next hop, … E thinks A as next hop

Discussion

- Why avoid routing loops is hard?
- Any proposals to avoid routing loops?

Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
        - synchronous Bellman-Ford (SBF)
        - asynchronous Bellman-Ford (ABF)
        - properties of DV
          - DV w/ loop prevention
            - *reverse poison*

The Reverse-Poison (Split-horizon) Hack



If the path to dest is through neighbor h, report ∞ to neighbor h for dest.

distance tables from neighbors

computation

E's distance table

$D^E()$

destinations	A	B	D	A	B	D	E's distance table
A	0	7	∞	1	15	∞	1, A
B	7	0	∞	8	8	∞	8, B
C	∞	1	2	∞	9	4	4, D
D	∞	∞	0	∞	∞	2	2, D
	1	8	2				
	c(E,A)	c(E,B)	c(E,D)				

distance

through neighbor

distance table E sends to its neighbors

To A	To B	To D
A: ∞	A: 1	A: 1
B: 8	B: ∞	B: 8
C: 4	C: 4	C: ∞
D: 2	D: 2	D: ∞
E: 0	E: 0	E: 0

DV+RP => RIP
(Routing Information Protocol)

- Included in BSD-UNIX Distribution in 1982
- Link cost: 1
- Distance metric: # of hops
- Distance vectors
  - exchanged every 30 sec via Response Message (also called **advertisement**) using UDP
  - each advertisement: route to up to 25 destination nets



RIP: Link Failure and Recovery

If no advertisement heard after 180 sec --> neighbor/link declared dead

- routes via neighbor invalidated
- new advertisements sent to neighbors
- neighbors in turn send out new advertisements (if tables changed)
- link failure info quickly propagates to entire net
- reverse-poison used to prevent ping-pong loops
- set infinite distance = 16 hops (why?)

General Routing Loops and Reverse-poison

- Exercise: Can Reverse-poison guarantee no loop for this network?



General Routing Loops and Reverse-poison

- Reverse-poison removes two-node loops but may not remove more-node loops



  - Unfortunate timing can lead to a loop
    - When the link between C and D fails, C will set its distance to D as ∞
    - A receives the bad news (∞) from C, A will use B to go to D
    - A sends the news to C
    - C sends the news to B

Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
        - synchronous Bellman-Ford (SBF)
        - asynchronous Bellman-Ford (ABF)
        - properties of DV
          - DV w/ loop prevention
            - reverse poison
            - *destination-sequenced DV (DSDV)*

Destination-Sequenced Distance Vector protocol (DSDV)

- Basic idea: use sequence numbers to partition computation
  - tags each route with a sequence number
  - each destination node D periodically advertises monotonically increasing even-numbered sequence numbers
  - when a node realizes that the link it uses to reach destination D is broken, it advertises an infinite metric and a sequence number which is one greater than the previous route (i.e., an odd seq. number)
    - the route is repaired by a later even-number advertisement from the destination

DSDV: More Detail



- Let's assume the destination node is D
- There are optimizations but we present a simple version:
  - each node B maintains (S^B, d^B), where S^B is the sequence number at B for destination D and d^B is the best distance using a neighbor from B to D
- Both periodical and triggered updates
  - periodically: D increases its seq. by 2 and broadcasts with (S^D, 0)
  - if B is using C as next hop to D and B discovers that C is no longer reachable
    - B increases its sequence number S^B by 1, sets d^B to ∞, and sends (S^B, d^B) to all neighbors

Example



Will this trigger an update?

Example



Will this trigger an update?

DSDV: Update Alg.



- Consider simple version, no optimization
- Update after receiving a message
  - assume B sends to A its current state (S^B, d^B)
  - when A receives (S^B, d^B)
    - if $S^B > S^A$, then
      // always update if a higher seq#
      - » $S^A = S^B$
      - » if ($d^B == \infty$) $d^A = \infty$; else $d^A = d^B + d(A,B)$
    - else if $S^A == S^B$, then
      - » if $d^A > d^B + d(A,B)$
        // update for the same seq# only if better route
        $d^A = d^B + d(A,B)$ and uses B as next hop

Example



Exercise: update process after D increases its seq# to next even number.

Claim: DSDV will NEVER Form a Loop

- Initially no loop (no one has next hop so no loop)
- Derive contradiction if a loop forms after a node processes an update,
  - e.g., when A receives the update from B, A decides to use B as next hop and forms a loop



Technique: Global Invariants

- Global Invariant is a very effective method in understanding safety of distributed asynchronous protocols
- Invariants are defined over the states of the distributed nodes

- Consider any node B.
- Let's identify some invariants over the state of node B, i.e., (S^B, d^B).

Invariants of a Single Node B

- Some invariants about the state of a node B
  - [I1] S^B is non-decreasing
  - [I2] d^B is non-increasing for the same sequence number



Invariants of if A Considers B as Next Hop

- Some invariants if A considers B as next hop

  - [I3] d^A is not ∞
  - [I4] $S^B >= S^A$

    because A is having the seq# which B last sent to A; B's seq# might be increased after B sent its state

    - [I5] if $S^B == S^A$
    - then $d^B < d^A$ because d^A is based on d^B which B sent to A some time ago, $d^B < d^A$ since all link costs are positive; d^B might be decreased after B sent its state

Loop Freedom of DSDV

- Consider a critical moment
  - A starts to consider B as next hop, and we have a loop
- According to invariant I4 for each link in the loop (X considers Y as next hop) : $S^Y >= S^X$
- Two cases:
  - exists $S^Y > S^X$
    - by transition along the loop $S^B > S^B$
  - all nodes along the loop have the same sequence number
    - apply I5, by transition along the loop $d^B > d^B$



Issue of DSDV



Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
        - synchronous Bellman-Ford (SBF)
        - asynchronous Bellman-Ford (ABF)
        - properties of DV
          - DV w/ loop prevention
            - reverse poison
            - destination-sequenced DV (DSDV)
            - *diffusive update algorithm (DUAL) and EIGRP*

Basic Idea

- DSDV guarantees no loop, but at the price of not using any backup path before destination re-announces reachability.

- Basic idea: Sufficient condition to guarantee no loop using backup paths (called switching)?



Key Idea: Feasible Successors

- If the reported distance of a neighbor n is lower than the total distance using primary (current shortest), the neighbor n is a feasible successor



$$d_n + d_{i \to \text{n}} \geq d_{\text{primary}} + d_{i \to \text{primary}} > d_{\text{n}}$$

Intuition

- Since the reported distance of B is lower than my total distance, B cannot be using me (along a path) to reach the destination



Example



- Assume A is destination, consider E

	Reported Dist.	Total Dist.
Neighbor C	3	6
Neighbor D	4	5

Summary: Distance Vector Routing

- Basic DV protocol
  - take away: use monotonicity as a technique to understand liveness/convergence
    - highly recommended reading of Bersekas/Gallager chapter
- Fix counting-to-infinity problem
  - DSDV
    - Idea: uses sequence number to avoid routing loops
      - seq# partitions routing updates from different outside events
      - within same event, no loop so long each node only decreases its distance
    - Analysis: use global invariants to understand/design safety/no routing loops
  - EIRGP (DUAL)
    - Idea: introduces a sufficient condition for local recovery

Discussion: Distance Vector Routing

- What do you like about distributed, distance vector routing?

- What do you not like about distributed, distance vector routing?

Churns of DV: One Example

Initially converged.
All links have cost 1
Event: Cost of 1->2 reduces to 0



Message sequences

1. Node 2 tells 3. Node 3 tells 4…Node N tells N+1. (N-1 messages)
2. Node N+1 tells N+2, N+2 tells N+3,…,2N. (N-1 messages)
3. Now node N-1 tells node N+1
4. Step 2 repeats
5. Now node N-2 tells node N+1
6. …

A total of $O(N^2)$ messages

Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
      - *Link state protocols (distributed state synchronization)*

Link-State Routing

- Basic idea: Not distributed computing, only distributed state distribution
- Net topology, link costs are distributed to all nodes
  - all nodes have same info
  - Each node computes its shortest paths from itself to all other nodes
    - standard Dijkstra's algorithm as path compute alg
    - Allows multiple same-cost paths
    - Multiple cost metrics per link (for type of service routing)
- Most commonly used routing protocol (e.g., OSPF/ISIS) by most networks in Internet

Example: Link State and Directed Graph (OSPFv2)



https://tools.ietf.org/html/rfc1583#page-12

Example: Link State and Directed Graph (OSPFv2)



Figure 2: A sample Autonomous System

FROM

TO	RT1	RT2	RT3	RT4	RT5	RT6	RT7	RT8	RT9	RT10	RT11	RT12	N3	N6	N8	N9
RT1													0			
RT2													0			
RT3						6							0			
RT4					8								0			
RT5				8		6	6									
RT6			8		7					5						
RT7					6									0		
* RT8														0		
* RT9																0
T RT10						7								0	0	
O RT11															0	0
* RT12																0
* N1	3															
N2		3														
N3	1	1	1	1												
N4			2													
N6							1	1		1						
N7								4								
N8										3	2					
N9									1		1	1				
N10												2				
N11									3							
N12					8		2									
N13					8											
N14					8											
N15							9									
H1												10				

Figure 3: The resulting directed graph

Outline

- Admin and recap
- Network control plane
  - Routing
    - Link weights assignment
    - Routing computation
      - Distance vector protocols (distributed computing)
      - *Link state protocols (distributed state synchronization)*
        - data structure to be distributed
        - *state distribution protocol*

Basic Link State Broadcast Protocol

Basic event structure at node n

- on initialization:
  - broadcast LSA[e] for each link e connected to n
- on state change to a link e connected to n:
  - broadcast LSA[e] = new status
- on receiving an LSA[e]:
  - if (does not have LSA[e])
    forwards LSA[e] to all links except the incoming link

Link State Broadcast

Node S updates link states connected to it.



Link State Broadcast



To avoid forwarding the same link state announcement (LSA) multiple times (forming a loop), each node remembers the received LSAs.
- Second LSA[S] received by E from C is discarded
- Second LSA[S] received by C from E is discarded as well
- Node H receives LSA[S] from two neighbors, and will discard one of them

Discussion

- Issues of the basic link state protocol?
  - Recall: goal is to efficiently distribute to each node to a correct, complete link state map

Link State Broadcast: Issues

- Problem: Out of order delivery
  - link down and then up
  - A node may receive up first and then down

- Solution
  - Each link update is given a sequence number: (initiator, seq#, link, status)
    - the initiator should increase the seq# for each new update
  - If the seq# of an update of a link is not higher than the highest seq# a router has seen, drop the update
  - Otherwise, forward it to all links except the incoming link (real implementation using packet buffer)

  - Problem of solution: seq# corruption
  - Solution: age field (e.g., https://tools.ietf.org/html/rfc1583#page-102)

Link State Broadcast: Issues

- Problem: network partition and then reconnect, how to sync across the reconnected components
- Solution: updates are sent periodically

Link State Broadcast: Issues

- Problem: Broadcast redundancy





https://hal.inria.fr/inria-00072756/document

Hierarchical OSPF



- Link-state advertisements only in area each nodes has detailed area topology;
- only know direction (shortest path) to nets in other areas.

Two-level hierarchy: local area, backbone.

Summary: Link State

- Basic LS protocol
  - take away: instead of computing routing results using distributed computing, distributed computing is for only link state distribution (synchronization)
- Link state distribution can still have much complexity, e.g., out of order delivery, partition and reconnect, scalability