

# Pseudo Code for Repair Algorithm

Arthur Feng

April 12, 2019

## 1 Introduction

In this section, we define some important definitions and algorithms....

**Definition 1.1.** (Mixed Integer Programming)

In this report we consider a generic mixed-integer programming problem (MIP) in the following form

$$\begin{aligned} \text{(MIP)} \quad & \min \quad c^T x \\ \text{s.t.} \quad & Ax \geq b \\ & x_j \in \mathbb{Z} \quad \forall j \in \mathcal{I} \\ & x_j \in \mathbb{R} \quad \forall j \in \mathcal{N} \setminus \mathcal{I} \end{aligned}$$

where the vector  $b \in \mathbb{R}^m$  and the vector  $c \in \mathbb{R}^n$  are input vectors.  $A$  is a input matrix of size  $m \times n$ , the variable input set  $\mathcal{I} \subseteq \mathcal{N} = \{1, 2, \dots, n\}$ . We denote  $\mathcal{P}$  for this problem, which called a mixed-integer programming problem (MIP) with minimize objective function  $c^T x$  subject to the constraints  $Ax \geq b$ . Besides, some variables are restricted to integer values while the else of are restricted to real value.  $S$  is a set of feasible solution if  $S$  satisfy all the constraints in the problem. A vector  $s^*$  with  $s^* \in S$  is called *optimal solution* when  $c^T x_{s^*} \leq c^T x_s$  for  $\forall s \in S$ . When all of the variables are restricted to integer, the problem is called *pureintegerlinearprogram*(IP) for  $\mathcal{I} = \mathcal{N}$ . If there is no integrality constraint, the program is called *linearprogram*

$$\begin{aligned} \text{(MIP)} \quad & \min \quad c^T x \\ \text{s.t.} \quad & Ax \geq b \\ & x_j \in \mathbb{R} \quad \forall j \in \mathcal{N} \end{aligned}$$

**Definition 1.2.** (LP-relaxation)

Lp *relaxation* is obtained by removing all integrity constraints  $\mathcal{I} \leftarrow \emptyset$ . LP-*relaxation* is the foundation of LP-based branch-and-bound technology. As the searching space is increase by removing integrity restrictions, the optimal solution in MIP problem could not better than LP-*relaxation*, which is  $s_{MIP}^* \geq s_{LP}^*$ . This means the optimal solution found in LP problem could provide a lower or prime bound for MIP problem.

## 2 Input

- A MIP problem  $\mathcal{P}^0$  with  $n$  variables  $x$ , constraint set  $C^0$  with an optimal solution  $s^0$ , where  $s^0$  is a  $n$ -vector.
- A MIP problem  $\mathcal{P}^1$  with  $n$  variables  $x$ , constraint set  $C^1$ , such that  $C^0 \subsetneq C^1$ .

## 3 Output

- An optimal solution  $s^1$  to  $\mathcal{P}^1$ , where  $s^1$  is a  $n$ -vector too.

## 4 Pseudo Code

---

### Algorithm 1: Solving Problem with Reoptimization

---

**Input:**  $\mathcal{P}^1$  where  $C^0 \subsetneq C^1$  and  $s^0, u, k$

**Output:** optimal solution  $s^*$  to  $\mathcal{P}^1$

---

```

1 begin
2   if  $s^0$  is feasible to  $\mathcal{P}^1$  then
3     return  $s^0$ 
4   else
5      $\mathcal{I} \leftarrow$  index set of integer or binary variables in  $\mathcal{P}^1$ 
6     for  $i$  in  $\mathcal{I}$  do
7        $\mathcal{P}^2 \leftarrow$  create new variables  $y_i$  and add it to  $\mathcal{P}^1$ :           // add new variables
8        $\mathcal{P}^2 \leftarrow$  add new constraints to  $\mathcal{P}^2 : y_i \geq x_i - s_i^0$        // add new constraints
9        $\mathcal{P}^2 \leftarrow$  add new constraints to  $\mathcal{P}^2 : y_i \geq s_i^0 - x_i$ 
10    end
11    if the sense of  $\mathcal{P}^2$  is not minimize then
12      change the sense of  $\mathcal{P}^2$  to minimize
13    end
14     $\alpha \leftarrow c^T s^0$ 
15    stop gap  $\leftarrow 0.5$ 
16    for  $l$  in  $\{k, k-1, \dots, 0\}$  do
17       $\alpha \leftarrow \alpha \times u \times \frac{l}{k}$ 
18      the coefficients of variables  $y$  in  $\mathcal{P}^2 \leftarrow \alpha$ 
19      if  $l = 0$  then
20        stop gap  $\leftarrow 0.0$ 
21      end
22       $s^* \leftarrow$  solving the sub-MIP problem to stop gap with reoptimization
23    end
24    return  $s^*$ 
25  end
26 end

```

---