

libwrf_coupling

global

Option	Value (Standard)	Range	Description
coupling	1	-1..2	Coupling between WRF and XPN -1: NOAH, WRF structure filled with NOAH values 0: Noah, WRF structure filled with Expert-N values (but no feedback to WRF) 1: Expert-N (without Noah), with feedback to WRF 2: Expert-N only, WRF structure not written by Expert-N vars, WRF - structure has to be written by any other module or by using an cdb input file

Global Options

Option	Value (Standard)	Range	Description
--------	------------------	-------	-------------

WRF Coupling

Option	Value (Standard)	Range	Description
coupling	1	-1..2	Coupling between WRF and XPN -1: NOAH, WRF structure filled with NOAH values 0: Noah, WRF structure filled with Expert-N values (but no feedback to WRF) 1: Expert-N (without Noah), with feedback to WRF 2: Expert-N only, WRF structure not written by Expert-N vars, WRF - structure has to be written by any other module or by using an cdb input file
use cdb input file	0	0/1	Use cdb input file, to simulate coupling of WRF
WRF Coupling.cdb filename	\$(BASE_PATH)/input/ \$PROJECT_NAME_\$R EG_STR_hpm_param.c db\$>		Weather Input File Name

Appendix (Templates)

Option	Result (Example)	Description
\$<filename.cfg\$>	filename.cfg	has no effect in Expert-N it is used to mark files in the GUI
\$REG_STR	0_0_0_0	ID - String: consists of nest ID, grid i coordinate, grid j coordinate, Instance number of Expert N in this nest
\$ID	0	ID Number of Expert-N (0..N)
\$PROJECT_NAME	project1	Name of the Expert-N project (project file without path and file extension)
\$BASE_PATH	~/expertn50/built	base path to Expert-N