

Package ‘amapR’

May 12, 2021

Type Package

Title An R package using AMap Web Service API to convert between addresses and coordinates

Version 0.2.2

Author Xiaojun Lin <linxiaojun@scu.edu.cn>

Maintainer Xiaojun Lin <linxiaojun@scu.edu.cn>

Description

This R package provides useful tools for research using AMap Web Service API. 'amapR' currently can be use to convert between Chinese addresses and coordinates. Benefiting from the R parallel computing, this package has speed advantage in handling large data of addresses or coordinates. Theoratically, the more CPU cores you have, the faster the functions in this package will be. Please note that the Amap Web Service API have set the query limit for developers (e.g., the upper query limits for personal certified developer are 200 times per second and 3 million times per day).

URL <https://github.com/xiaojunlin/amapR>

BugReports <https://github.com/xiaojunlin/amapR/issues>

Imports data.table, jsonlite, progress, parallel, doSNOW, foreach, stringr, stats, utils

NeedsCompilation no

Depends R (>= 4.0.0)

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.1

R topics documented:

geocoord	2
geolocation	3
transcoord	4

Index	5
-------	---

geocoord

*Convert addresses into coordinates***Description**

Convert addresses into coordinates

Usage

```
geocoord(data, address, ncore = 999, nquery = 10)
```

Arguments

data	The dataset, a data.frame or data.table
address	The column name of address
ncore	The specific number of CPU cores used (ncore = 999 by default, which indicates the maximum of CPU cores minus 1 were used in parallel computing if your CPU is less than 999 cores)
nquery	The number of query in each batch (nquery = 10 by default). This argument is used to avoid the http 413 error when the request url is too long.

Value

a data.table which adds the formatted address, longitude and latitude in the original data set.

Note

According to the official document of AMap Web Service API, the address in the data set should be in Chinese format. If a address is in English or includes special characters (i.e., ?, -, >, _, etc.), the function may return empty result for this address automatically.

References

Amap. Official documents for developers: Web Service API. <https://lbs.amap.com/api/webservice/summary>

Examples

```
## Not run:
library(AMapR)
options(AMapR.key = "xxxxxxxxxxxx")

# Note: The "address" is the column having Chinese addresses, and the data set named "test"
# should be a data.frame or a data.table.
results <- geocoord(data = test, address = "address")

# Set the specific number of CPU cores used and the number of query in each batch
results <- geocoord(data = test, address = "address", ncore = 4, nquery = 5)

## End(Not run)
```

geolocation

*Convert the coordinates into formatted addresses***Description**

Convert the coordinates into formatted addresses

Usage

```
geolocation(data, longitude, latitude, ncore = 999)
```

Arguments

data	The dataset, a data.frame or data.table
longitude	The column having longitude
latitude	The column having latitude
ncore	The specific number of CPU cores used (ncore = 999 by default, which indicates the maximum of CPU cores minus 1 were used in parallel computing if your CPU is less than 999 cores)

Value

a data.table which adds the formatted address in the original data set.

Note

The value of "longitude" or "latitude" should be digits in numeric or character format. If not, the function may return empty result for this coordinate automatically.

References

Amap. Official documents for developers: Web Service API. <https://lbs.amap.com/api/webservice/summary>

Examples

```
## Not run:
library(AMAP)
options(AMAP.key = "xxxxxxxxxxxxxxxx")

# Completed data
test <- data.frame(n = 1:5000, lng = c(114.4345,104.0837), lat = c(30.51105, 30.63087))
results <- geolocation(data = test, longitude = "lng", latitude = "lat")

# When the column 'lng' has missing value
test <- data.frame(n = 1:5000, lng = c(114.4345,''), lat = c(30.51105, 30.63087))
results <- geolocation(data = test, longitude = "lng", latitude = "lat")

# When the column 'lng' has special characters
test <- data.frame(n = 1:5000, lng = c(114.4345,'?'), lat = c(30.51105, 30.63087))
results <- geolocation(data = test, longitude = "lng", latitude = "lat")

## End(Not run)
```

transcoord	<i>Transform the coordinates from other coordinate systems to Amap system</i>
------------	---

Description

This function supports to transform the coordinates from three other coordinate systems (including baidu, GPS and mapbar) to Amap system

Usage

```
transcoord(data, longitude, latitude, coordsys = "autonavi", ncore = 999)
```

Arguments

data	The dataset, a data.frame or data.table
longitude	The column having longitude
latitude	The column having latitude
coordsys	The coordinate system of your original location data, such as "gps", "baidu", "mapbar" and "autonavi" (coordsys = "autonavi" by default)
ncore	The specific number of CPU cores used (ncore = 999 by default, which indicates the maximum of CPU cores minus 1 were used in parallel computing if your CPU is less than 999 cores)

Value

a data.table which adds the transformed longitude and latitude using Amap System in the original data set

Note

The value of "longitude" or "latitude" should be digits in numeric or character format. If not, the function may return empty result for this coordinate automatically

References

Amap. Official documents for developers: Web Service API. <https://lbs.amap.com/api/webservice/summary>

Examples

```
## Not run:
library(AMAP)
options(AMAP.key = "xxxxxxxxxxxxxxxx")

# Completed data
test <- data.frame(n = 1:500, lng = c(114.4345, 104.0837), lat = c(30.51105, 30.63087))
results <- transcoord(data = test, longitude = "lng", latitude = "lat", coordsys = "baidu")

## End(Not run)
```

Index

geocoord, [2](#)
geolocation, [3](#)
transcoord, [4](#)