

git--push报错解决方案

1、push报错

```
remote: error: refusing to update checked out branch: refs/heads/master
```

```
remote: error: By default, updating the current branch in a non-bare repository
```

```
remote: error: is denied, because it will make the index and work tree inconsistent
```

```
remote: error: with what you pushed, and will require 'git reset --hard' to match
```

```
remote: error: the work tree to HEAD.
```

```
remote: error:
```

```
remote: error: You can set 'receive.denyCurrentBranch' configuration variable to
```

```
remote: error: 'ignore' or 'warn' in the remote repository to allow pushing into
```

```
remote: error: its current branch; however, this is not recommended unless you
```

```
remote: error: arranged to update its work tree to match what you pushed in some
```

```
remote: error: other way.
```

```
remote: error:
```

```
remote: error: To squelch this message and still keep the default behaviour, set
```

```
remote: error: 'receive.denyCurrentBranch' configuration variable to 'refuse'.
```

```
To git@192.168.1.X:/var/git.server/.../web
```

```
! [remote rejected] master -> master (branch is currently checked out)
```

```
error: failed to push some refs to 'git@192.168.1.X:/var/git.server/.../web'
```

解决方案:

这是由于git默认拒绝了push操作，需要进行设置，修改.git/config文件后面添加如下代码

```
[receive]
```

```
denyCurrentBranch = ignore
```

无法查看push后的git中文件的原因与解决方法

在初始化远程仓库时最好使用

```
git --bare init
```

而不要使用: git init

git init 和 git --bare init 的具体区别:<http://blog.haohtml.com/archives/12265>