

+886 (3) 358-8799 +86 75526653899







Features

- Ultra-compact size: 138 x 100 x 57mm (5.43"x 3.94"x 2.24")
- 3rd GenIntel® Atom™ Processor, Celeron® Processor (formerly Bay Trail)
- Wide-Range DC voltage input: 9V~32V
- Fanless system, aluminum alloy structure
- 2x RJ45 GbE Ethernet
- 4x USB 3.0/2.0 ports
- 8-bit isolated GPI & 8-bit isolated GPO
- 4x RS-232 ports

Specifications


	. - 		
System	1 4 18 0 4 18 14 18 18 18 18 18 18 18 18 18 18 18 18 18		
CPU	Intel® Celeron® J1900 2.0 GHz, Quad Core L2 cache 2MB, 10W TDP		
Chipset	Intergated in SoC		
BIOS	AMI Aptio® UEFI 2.x firmware		
Memory	DDR3L with 1333 MT/s, 8GB (Max.)		
Graphics			
Display	1x HDMI		
Controller	Intel® HD Graphics Generation 7		
Power			
DC Input	9~32VDC		
Mechanical			
Dimensions (W x D x H)	138 x 100 x 57mm (5.43"x 3.94"x 2.24")		
Weight	0.76kg		
External IO			
Ethernet	2x RJ45 GbE		
USB 3.0/2.0	4x USB 3.0/2.0 port, 1x USB 2.0 port TypeA (internal)		
COM	4x 05B 3.0/2.0 port, 1x 05B 2.0 port TypeA (internal) 4x RS-232 (U7-300)		
COIVI			
Digital I/O	3x RS-232 (U7-300T) 8-bit Isolated GPI & 8-bit Isolated GPO		
Digital I/O Audio			
Audio	1x Mic in, 1x Line out		
Storage			
SATA	1x mSATA socket		
Drive Bay	2.5" HDD/SSD, Share with CFast (optional)		
SIM	1x USIM slot		
Olivi	TA CONVESION		
Expansion Slot			
Mini-PCle	1x full length Mini-PCle socket (PCle + USB + USIM)		
	1x half length Mini-PCle socket (PCle + USB)		
Other			
Watchdog	Multistage watchdog		
Antenna	2x antenna openings		
Environment			
Operating Temperature	Operation: -20°C~60°C		
Storage Temperature	Storage: -40°C~85°C Operation:10% to 90%		
Operating Humidity	10% ~ 90% Humidity, non-condensing		
Storage Humidity	5% ~ 95% Humidity, non-condensing		
Certification	CE/CB/FCC Class A		
OS Support			
Optional OS Installation	Windows 10		
	Windows 10 IoT		
	Windows 8		
	Windows Embedded 8 Standard		
	Windows 7		
	Windows 7 embedded compact		
	Linux		

Order Information

Model Name

U7-331	Intel® Celeron® N2807, 4GB	
U7-333	Intel® Celeron® J1900, 4GB	
U7-331T	Intel® Celeron® N2807, 4GB	
U7-333T	Intel® Celeron® J1900, 4GB	

I/O Interfaces



Optional Accessories

Model Name

SSD	mSATA 32GB/64GB/128GB/256GB
Adapter	12VDC/40W Power Adapter
Power Cord	US / Germany / UK / Australia / China
Wireless Module	3G/3G+GPS/4G/4G+GPS/4G+WIFI

^{*} Please contact sales representative