Chapter 2:
Application Layer

Instructor: Zhuozhao Li

Lab: Qing Wang

Department of Computer Science and Engineering

Application layer: overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS

- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Application layer: overview

Our goals:

- conceptual *and* implementation aspects of application-layer protocols
  - transport-layer service models
  - client-server paradigm
  - peer-to-peer paradigm
- learn about protocols by examining popular application-layer protocols
  - HTTP
  - SMTP, IMAP
  - DNS
- programming network applications
  - socket API

Some network apps

- social networking
- Web
- text messaging
- e-mail
- multi-user network games
- streaming stored video (bilibili, Migu)
- P2P file sharing
- voice over IP (e.g., Skype)
- real-time video conferencing
- Internet search
- remote login
- …

Q: your favorites?

Creating a network app

write programs that:

- run on (different) end systems
- communicate over network
- e.g., web server software communicates with browser software

no need to write software for network-core devices

- network-core devices do not run user applications
- applications on end systems allows for rapid app development, propagation



Client-server paradigm

server:

- always-on – long-running
- permanent IP address
- often in data centers, for scaling

clients:

- contact, communicate with server
- may be intermittently connected
- may have dynamic IP addresses
- do *not* communicate directly with each other

- examples: HTTP, IMAP, FTP



Peer-to-peer (P2P) paradigm

- *no* always-on server
- arbitrary end systems directly communicate
- peers request service from other peers, provide service in return to other peers
  - *self scalability* – new peers bring new service capacity, as well as new service demands
- peers are intermittently connected and change IP addresses
  - complex management
- example: P2P file sharing



Processes communicating

process: program running within a host

- within same host, two processes communicate using inter-process communication (defined by OS)
- processes in different hosts communicate by exchanging messages

clients, servers

client process: process that initiates communication

server process: process that waits to be contacted

- note: applications with P2P architectures have client processes & server processes

Sockets

- process sends/receives messages to/from its socket
- socket analogous to courier（快递员）
  - sending process shoves message out courier
  - sending process relies on transport infrastructure on other side of door to deliver message to socket at receiving process
  - two sockets involved: one on each side



Addressing processes

- to receive messages, process must have *identifier*
- host device has unique 32-bit IP address
- *Q:* does IP address of host on which process runs suffice for identifying the process?
  - *A:* no, *many* processes can be running on same host

- *identifier* includes both IP address and port numbers associated with process on host.
- example port numbers:
  - HTTP server: 80
  - mail server: 25
- to send HTTP message to gaia.cs.umass.edu web server:
  - IP address: 128.119.245.12
  - port number: 80
- more shortly…

An application-layer protocol defines:

- types of messages exchanged,
  - e.g., request, response
- message syntax:
  - what fields in messages & how fields are delineated
- message semantics
  - meaning of information in fields
- rules for when and how processes send & respond to messages

open protocols:

- defined in RFCs, everyone has access to protocol definition
- allows for interoperability
- e.g., HTTP, SMTP

proprietary protocols:

- e.g., Skype, Zoom

What transport service does an app need?

data integrity

- some apps (e.g., file transfer, web transactions) require 100% reliable data transfer
- other apps (e.g., audio) can tolerate some loss

timing

- some apps (e.g., Internet telephony, interactive games) require low delay to be “effective”

throughput

- some apps (e.g., multimedia) require minimum amount of throughput to be “effective”
- other apps (“elastic apps”) make use of whatever throughput they get

security

- encryption, data integrity, …

Transport service requirements: common apps

application	data loss	throughput	time sensitive?
file transfer/download	no loss	elastic	no
e-mail	no loss	elastic	no
Web documents	no loss	elastic	no
real-time audio/video	loss-tolerant	audio: 5Kbps-1Mbps video:10Kbps-5Mbps	yes, 10's msec
streaming audio/video	loss-tolerant	same as above	yes, few secs
interactive games	loss-tolerant	Kbps+	yes, 10's msec
text messaging	no loss	elastic	yes and no

Internet transport protocols services

TCP service:

- *reliable transport* between sending and receiving process
- *flow control:* sender won't overwhelm receiver
- *congestion control:* throttle sender when network overloaded
- *does not provide:* timing, minimum throughput guarantee, security
- *connection-oriented:* setup required between client and server processes

UDP service:

- *unreliable data transfer* between sending and receiving process
- *does not provide:* reliability, flow control, congestion control, timing, throughput guarantee, security, or connection setup.

Internet transport protocols services

application	application layer protocol	transport protocol
file transfer/download	FTP [RFC 959]	TCP
e-mail	SMTP [RFC 5321]	TCP
Web documents	HTTP 1.1 [RFC 7320]	TCP
Internet telephony	SIP [RFC 3261], RTP [RFC 3550], or proprietary	TCP or UDP
streaming audio/video	HTTP [RFC 7320], DASH	TCP
interactive games	WOW, FPS (proprietary)	UDP or TCP

Securing TCP

Vanilla TCP & UDP sockets:

- no encryption
- cleartext passwords sent into socket traverse Internet in cleartext (!)

Transport Layer Security (TLS)

- provides encrypted TCP connections
- data integrity
- end-point authentication

TLS implemented in application layer

- apps use TLS libraries, that use TCP in turn

TLS socket API

- cleartext sent into socket traverse Internet *encrypted*
- see Chapter 8

Application layer: overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Web and HTTP

First, a quick review…

- web page consists of *objects,* each of which can be stored on different Web servers
- object can be HTML file, JPEG image, Java applet, audio file,…
- web page consists of *base HTML-file* which includes *several referenced objects, each* addressable by a *URL (Uniform Resource Locator),* e.g.,

`www.someschool.edu/someDept/pic.gif`

host name | path name

HTTP overview

HTTP: hypertext transfer protocol

- Web's application layer protocol
- client/server model:
  - *client:* browser that requests, receives, (using HTTP protocol) and "displays" Web objects
  - *server:* Web server sends (using HTTP protocol) objects in response to requests



HTTP overview (continued)

HTTP uses TCP:

- client initiates TCP connection (creates socket) to server, port 80
- server accepts TCP connection from client
- HTTP messages (application-layer protocol messages) exchanged between browser (HTTP client) and Web server (HTTP server)
- TCP connection closed

HTTP is "stateless"

- server maintains *no* information about past client requests

aside

protocols that maintain "state" are complex!

- past history (state) must be maintained
- if server/client crashes, their views of "state" may be inconsistent, must be reconciled

HTTP connections: two types

Non-persistent HTTP（HTTP 1.0）

1. TCP connection opened
2. at most one object sent over TCP connection
3. TCP connection closed

downloading multiple objects required multiple connections

Persistent HTTP（HTTP 1.1）

- TCP connection opened to a server
- multiple objects can be sent over *single* TCP connection between client and that server
- TCP connection closed

Non-persistent HTTP: example

User enters URL: **`www.someSchool.edu/someDepartment/home.index`**
(containing text, references to 10 jpeg images)

1a. HTTP client initiates TCP connection to HTTP server (process) at www.someSchool.edu on port 80

1b. HTTP server at host www.someSchool.edu waiting for TCP connection at port 80 "accepts" connection, notifying client

2. HTTP client sends HTTP *request message* (containing URL) into TCP connection socket. Message indicates that client wants object someDepartment/home.index

3. HTTP server receives request message, forms *response message* containing requested object, and sends message into its socket

time

Non-persistent HTTP: example (cont.)

User enters URL: **`www.someSchool.edu/someDepartment/home.index`**
(containing text, references to 10 jpeg images)

4. HTTP server closes TCP connection.

5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects

6. Steps 1-5 repeated for each of 10 jpeg objects

time

Non-persistent HTTP: response time

RTT (definition): time for a small packet to travel from client to server and back

HTTP response time (per object):

- one RTT to initiate TCP connection
- one RTT for HTTP request and first few bytes of HTTP response to return
- obect/file transmission time



Non-persistent HTTP response time = 2RTT+ file transmission time

Persistent HTTP (HTTP 1.1)

Non-persistent HTTP issues:

- requires 2 RTTs per object
- OS overhead for *each* TCP connection
- browsers often open multiple parallel TCP connections to fetch referenced objects in parallel

Persistent HTTP (HTTP1.1):

- server leaves connection open after sending response
- subsequent HTTP messages between same client/server sent over open connection
- client sends requests as soon as it encounters a referenced object
- as little as one RTT for all the referenced objects (cutting response time in half)

HTTP request message

- two types of HTTP messages: *request, response*
- HTTP request message:
  - ASCII (human-readable format)



https://en.wikipedia.org/wiki/List_of_HTTP_header_fields

HTTP request message: general format



Other HTTP request messages

POST method:

- web page often includes form input
- user input sent from client to server in entity body of HTTP POST request message

GET method (for sending data to server):

- include user data in URL field of HTTP GET request message (following a '?'):

```
www.somesite.com/animalsearch?monkeys&banana
```

HEAD method:

- requests headers (only) that would be returned *if* specified URL were requested with an HTTP GET method.

PUT method:

- uploads new file (object) to server
- completely replaces file that exists at specified URL with content in entity body of POST HTTP request message

Other HTTP request messages

POST method:

- web page often includes form input
- user input sent from client to server in entity body of HTTP POST request message

GET method (for sending data to server):

- include user data in URL field of HTTP GET request message (following a '?'):

```
www.somesite.com/animalsearch?monkeys&banana
```

HEAD method:

- requests headers (only) that would be returned *if* specified URL were requested with an HTTP GET method.

PUT method:

- uploads new file (object) to server
- completely replaces file that exists at specified URL with content in entity body of POST HTTP request message

Other HTTP request messages

Properties of request methods

Request method	RFC	Request has payload body	Response has payload body	Safe	Idempotent	Cacheable
GET	RFC 9110	Optional	Yes	Yes	Yes	Yes
HEAD	RFC 9110	Optional	No	Yes	Yes	Yes
POST	RFC 9110	Yes	Yes	No	No	Yes
PUT	RFC 9110	Yes	Yes	No	Yes	No
DELETE	RFC 9110	Optional	Yes	No	Yes	No
CONNECT	RFC 9110	Optional	Yes	No	No	No
OPTIONS	RFC 9110	Optional	Yes	Yes	Yes	No
TRACE	RFC 9110	No	Yes	Yes	Yes	No
PATCH	RFC 5789	Yes	Yes	No	No	No

HTTP response message

status line (protocol status code status phrase)

header lines

data, e.g., requested HTML file

```
HTTP/1.1 200 OK\r\n
Date: Sun, 26 Sep 2010 20:09:20 GMT\r\n
Server: Apache/2.0.52 (CentOS)\r\n
Last-Modified: Tue, 30 Oct 2007 17:00:02
   GMT\r\n
ETag: "17dc6-a5c-bf716880"\r\n
Accept-Ranges: bytes\r\n
Content-Length: 2652\r\n
Keep-Alive: timeout=10, max=100\r\n
Connection: Keep-Alive\r\n
Content-Type: text/html; charset=ISO-8859-
   1\r\n
\r\n
data data data data data ...
```

https://en.wikipedia.org/wiki/List_of_HTTP_header_fields

HTTP response status codes

需要继续进行操作

- status code appears in 1st line in server-to-client response message.
- some sample codes:

200 OK

- request succeeded, requested object later in this message

301 Moved Permanently 重定向.更换网址.

- requested object moved, new location specified later in this message (in Location: field)

400 Bad Request 客户端出错.

- request msg not understood by server

404 Not Found

- requested document not found on this server

505 HTTP Version Not Supported

服务器端发生错误

1. Informational responses (100 – 199)
2. Successful responses (200 – 299)
3. Redirection messages (300 – 399)
4. Client error responses (400 – 499)
5. Server error responses (500 – 599)

http1.1 本身是 stateless 的. 只是通过 cookie 使之可以记忆状态

Maintaining user/server state: cookies

请求发送时会带上 cookie 的信息.
cookie 被保存在本地文件夹.

Web sites and client browser use *cookies* to maintain some state between transactions

four components:

1) cookie header line of HTTP *response* message
2) cookie header line in next HTTP *request* message
3) cookie file kept on user's host, managed by user's browser
4) back-end database at Web site

Example:

- Susan uses browser on laptop, visits specific e-commerce site for first time
- when initial HTTP requests arrives at site, site creates:
  - unique ID (aka "cookie")
  - entry in backend database for ID
- subsequent HTTP requests from Susan to this site will contain cookie ID value, allowing site to "identify" Susan

Maintaining user/server state: cookies



涉及 data privacy

HTTP cookies: comments

What cookies can be used for:

- authorization - 部分 cookie 有时限.
- shopping carts
- recommendations
- user session state (Web e-mail)

Challenge: How to keep state:

- protocol endpoints: maintain state at sender/receiver over multiple transactions
- cookies: HTTP messages carry state

aside

cookies and privacy:

- cookies permit sites to *learn* a lot about you on their site.
- third party persistent cookies (tracking cookies) allow common identity (cookie value) to be tracked across multiple web sites

Web caches (proxy servers)

Goal: satisfy client request without involving origin server

- user configures browser to point to a *Web cache* 容量有限 布署在接入网附近
- browser sends all HTTP requests to cache 先缓存在本地 least commonly use. 减轻对服务器请求压力
  - *if* object in cache: cache returns object to client
  - *else* cache requests object from origin server, caches received object, then returns object to client



Web caches (proxy servers)

- Web cache acts as both client and server
  - server for original requesting client
  - client to origin server
- typically cache is installed by ISP (university, company, residential ISP)

Why Web caching?

- reduce response time for client request
  - cache is closer to client
- reduce traffic on an institution's access link
- Internet is dense with caches
  - enables "poor" content providers to more effectively deliver content

Caching example

Scenario:

- access link rate: 1.54 Mbps
- RTT from institutional router to server: 2 sec
- Web object size: 100K bits
- Average request rate from browsers to origin servers: 15/sec
  - average data rate to browsers: 1.50 Mbps

Performance:

- access link utilization = .97 — *problem:* large delays at high utilization!
- LAN utilization: .0015
- end-end delay = Internet delay + access link delay + LAN delay
  = 2 sec + minutes + usecs



Caching example: buy a faster access link

Scenario:

- access link rate: 1.54 Mbps → 154 Mbps
- RTT from institutional router to server: 2 sec
- Web object size: 100K bits
- Avg request rate from browsers to origin servers: 15/sec
  - avg data rate to browsers: 1.50 Mbps



Performance:

- LAN utilization: .0015
- access link utilization = .97 → .0097
- end-end delay = Internet delay + access link delay + LAN delay
  = 2 sec + minutes + usecs → msecs

Cost: faster access link (expensive!)

Caching example: install a web cache

Scenario:

- access link rate: 1.54 Mbps
- RTT from institutional router to server: 2 sec
- Web object size: 100K bits
- Avg request rate from browsers to origin servers: 15/sec
  - avg data rate to browsers: 1.50 Mbps

Performance:

- LAN utilization: .?
- access link utilization = ?
- average end-end delay = ?

How to compute link utilization, delay?

Cost: web cache (cheap!)



Caching example: install a web cache

Calculating access link utilization, end-end delay with cache: 查询时已经在 web cache 里面 -- hit

- suppose cache hit rate is 0.4: 40% requests satisfied at cache, 60% requests satisfied at origin
- access link: 60% of requests use access link
- data rate to browsers over access link
  = 0.6 * 1.50 Mbps = .9 Mbps
- utilization = 0.9/1.54 = .58
- average end-end delay (estimation)
  = 0.6 * (delay from origin servers)
  + 0.4 * (delay when satisfied at cache)
  = 0.6 * (2.01) + 0.4 * (~msecs) = ~ 1.2 secs



lower average end-end delay than with 154 Mbps link (and cheaper too!)

Conditional GET

Web cache时常用

Goal: don't send object if cache has up-to-date cached version

- no object transmission delay
- lower link utilization

- *cache:* specify date of cached copy in HTTP request

  If-modified-since: <date> 何时更新，未更新则web cache时已有，无须重复获取.

- *server:* response contains no object if cached copy is up-to-date:

  HTTP/1.0 304 Not Modified



HTTP/2

Key goal: decreased delay in multi-object HTTP requests

HTTP1.1: introduced multiple, pipelined GETs over single TCP connection

- server responds *in-order* (FCFS: first-come-first-served scheduling) to GET requests
- with FCFS, small object may have to wait for transmission (head-of-line (HOL) blocking) behind large object(s) 都要按順序.
- loss recovery (retransmitting lost TCP segments) stalls object transmission

HTTP/2

Key goal: decreased delay in multi-object HTTP requests

HTTP/2: [RFC 7540, 2015] increased flexibility at *server* in sending objects to client:

- methods, status codes, most header fields unchanged from HTTP 1.1
- ② transmission order of requested objects based on client-specified object priority (not necessarily FCFS) 每个请求得到一定的资源
- ③ *push* unrequested objects to client 识别请求A后可能继续请求B. 并把B提前push出来.
- ① divide objects into frames, schedule frames to mitigate HOL blocking

HTTP/2: mitigating HOL blocking

HTTP 1.1: client requests 1 large object (e.g., video file, and 3 smaller objects)



objects delivered in order requested: O_2, O_3, O_4 wait behind O_1

HTTP/2: mitigating HOL blocking

HTTP/2: objects divided into frames, frame transmission interleaved



O_2, O_3, O_4 delivered quickly, O_1 slightly delayed

HTTP/2 to HTTP/3

Key goal: decreased delay in multi-object HTTP requests

HTTP/2 over single TCP connection means:

- recovery from packet loss still stalls all object transmissions
  - as in HTTP 1.1, browsers have incentive to open multiple parallel TCP connections to reduce stalling, increase overall throughput
- no security over vanilla TCP connection
- HTTP/3: adds security , per object error- and congestion-control (more pipelining) over UDP 可以不继续重传.
  - more on HTTP/3 in transport layer 将可靠部分单独移出.

https 默认端口号为 443.

Application layer: overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

E-mail

Three major components:

- user agents
- mail servers 朝向公网心服务器.
- simple mail transfer protocol: SMTP

User Agent

- a.k.a. “mail reader”
- composing, editing, reading mail messages
- e.g., Outlook, phone mail client
- outgoing, incoming messages stored on server



E-mail: mail servers

mail servers:

- *mailbox* contains incoming messages for user
- *message queue* of outgoing (to be sent) mail messages 向外发送的消息队列
- *SMTP protocol* between mail servers to send email messages
  - client: sending mail server
  - "server": receiving mail server



Scenario: Alice sends e-mail to Bob

1) Alice uses UA to compose e-mail message “to” bob@someschool.edu

2) Alice’s UA sends message to her mail server; message placed in message queue

3) client side of SMTP opens TCP connection with Bob’s mail server

4) SMTP client sends Alice’s message over the TCP connection

5) Bob’s mail server places the message in Bob’s mailbox

6) Bob invokes his user agent to read message



SMTP RFC (5321)

- uses TCP to reliably transfer email message from client (mail server initiating connection) to server, port 25
  - direct transfer: from sending server (acting like client) to receiving server
- three phases of transfer
  - SMTP handshaking (greeting)
  - SMTP transfer of messages
  - SMTP closure
- command/response interaction (like HTTP)
  - commands: ASCII text
  - response: status code and phrase



Sample SMTP interaction 报文package的内容.

```
S: 220 hamburger.edu
C: HELO crepes.fr
S: 250  Hello crepes.fr, pleased to meet you
C: MAIL FROM: <alice@crepes.fr>
S: 250 alice@crepes.fr... Sender ok
C: RCPT TO: <bob@hamburger.edu>
S: 250 bob@hamburger.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Do you like ketchup?
C: How about pickles?
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 hamburger.edu closing connection
```

发自 →

发给 →

. 以点或新行结束.

SMTP: closing observations

comparison with HTTP:

区别 ☆

- HTTP: pull 拉下来 请求什么给什么
- SMTP: push (反向) 内容推到服务器处
- both have ASCII command/response interaction, status codes
- HTTP: each object encapsulated in its own response message
- SMTP: multiple objects sent in a multipart message

- SMTP uses persistent connections
- SMTP requires message (header & body) to be in 7-bit ASCII
- SMTP server uses CRLF.CRLF to determine end of message

Mail message format

SMTP: protocol for exchanging e-mail messages, defined in RFC 531 (like HTTP)

RFC 822 defines *syntax* for e-mail message itself (like HTML)

- header lines, e.g.,
  - To:
  - From:
  - Subject:

  these lines, within the body of the email message area different from SMTP MAIL FROM:, RCPT TO: commands!
- Body: the "message" , ASCII characters only



Mail access protocols



默认端口是25. 加密后端口为465.

- SMTP: delivery/storage of e-mail messages to receiver's server
- mail access protocol: retrieval from server
  - IMAP: Internet Mail Access Protocol [RFC 3501]: messages stored on server, IMAP provides retrieval, deletion, folders of stored messages on server
- HTTP: gmail, Hotmail, Yahoo!Mail, etc. provides web-based interface on top of STMP (to send), IMAP (or POP) to retrieve e-mail messages

浏览器上发邮件直接使用HTTP协议. 内部服务那端用 SMTP.

Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- **The Domain Name System DNS**
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

应用层的协议

DNS: Domain Name System

分布式的数据库

提供域名和IP地址的转换服务.

people: many identifiers:

- student ID, name, passport #

Internet hosts, routers:

- IP address (32 bit) - used for addressing datagrams
- "name", e.g., cs.umass.edu - used by humans

Q: how to map between IP address and name, and vice versa ?

Domain Name System:

- *distributed database* implemented in hierarchy of many *name servers*
- *application-layer protocol:* hosts, name servers communicate to *resolve* names (address/name translation)
  - note: core Internet function, *implemented as application-layer protocol*

    基于传输层的UDP协议.
  - complexity at network's "edge"

DNS: services, structure

DNS services

浏览器会先访问DNS服务器.

- hostname to IP address translation
- host aliasing 别名.
  - canonical, alias names
- mail server aliasing
- load distribution
  - replicated Web servers: many IP addresses correspond to one name

顶级域名服务器

distributing & hierarchical

Q: Why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database
- maintenance

A: doesn't scale!

- Comcast DNS servers alone: 600B DNS queries per day

DNS: a distributed, hierarchical database



Root

TLD

Top Level Domain

顶级域名服务器

Authoritative

权威域名服务器

Client wants IP address for www.amazon.com; 1st approximation:

- client queries root server to find .com DNS server 返回TLD服务器
- client queries .com DNS server to get amazon.com DNS server 返回 ns.amazon.com
- client queries amazon.com DNS server to get IP address for www.amazon.com

DNS: root name servers

- official, contact-of-last-resort by name servers that can not resolve name
- *incredibly important* Internet function
  - Internet couldn't function without it!
  - DNSSEC – provides security (authentication and message integrity)
- ICANN (Internet Corporation for Assigned Names and Numbers) manages root DNS domain

13 logical root name "servers" worldwide each "server" replicated many times (~200 servers in US)



Top-Level Domain, and authoritative servers

Top-Level Domain (TLD) servers:

- responsible for .com, .org, .net, .edu, .aero, .jobs, .museums, and all top-level country domains, e.g.: .cn, .uk, .fr, .ca, .jp
- Network Solutions: authoritative registry for .com, .net TLD
- Educause: .edu TLD

Authoritative DNS servers:

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider

Local DNS name servers

- does not strictly belong to hierarchy
- each ISP (residential ISP, company, university) has one
  - also called “default name server”
- when host makes DNS query, query is sent to its local DNS server
  - has local cache of recent name-to-address translation pairs (but may be out of date!)
  - acts as proxy, forwards query into hierarchy

DNS name resolution: iterated query

Example: host at engineering.nyu.edu wants IP address for gaia.cs.umass.edu

大部查询：

不断地提交请求

Iterated query:

- contacted server replies with name of server to contact
- "I don't know this name, but ask this server"



DNS name resolution: recursive query

Example: host at engineering.nyu.edu wants IP address for gaia.cs.umass.edu

Recursive query:

- puts burden of name resolution on contacted name server
- heavy load at upper levels of hierarchy?



多层次的caching

Caching, Updating DNS Records

- once (any) name server learns mapping, it *caches* mapping
  - cache entries timeout (disappear) after some time (TTL) time to leave 何时有效
  - TLD servers typically cached in local name servers 过期则需更新查询.
    - thus root name servers not often visited
- cached entries may be *out-of-date* (best-effort name-to-address translation!)
  - if name host changes IP address, may not be known Internet-wide until all TTLs expire!

flags: qr aa ra ; QUERY: 1. ANSWER: 1 AUTHORITY: 2. ADDITIONAL: 5

NS1.

example 下载 WinBIND

dig.exe 直接运行

dig +trace sakai.sustech.edu.cn.

根域名服务器：本地配置好的

A IPV4 32位.

AAAA IPV6 128位

dig +norecurse @某服务器 网址.

DNS records

DNS: distributed database storing resource records (RR)

RR format: (name, value, type, ttl)

name: 域名; value: 返回的值; type: 类型; ttl: 保存时间

value: IP地址 / TLD服务器地址 / Authority

type=A

- name is hostname
- value is IP address

type=NS

name server. 给下一个使可以继续查询

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME

需要继续查询 canonial name 的地址

- name is alias name for some "canonical" (the real) name 别名.
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

baidu.shifeng — 182.61.200.7 — 6

计算机集群 内部有内部外网IP只有1个.

一个网址有两个IP地址.

type=MX

- value is name of mailserver associated with name

DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:

message header:

- identification: 16 bit # for query, reply to query uses same #
- flags:
  - query or reply
  - recursion desired
  - recursion available
  - reply is authoritative



DNS protocol messages

DNS *query* and *reply* messages, both have same *format:*



dig / wireshark.

Inserting records into DNS

创建网站之后可被DNS解析.

Example: new startup “Network Utopia”

ICANN组织来管理.

- register name networkuptopia.com at *DNS registrar* (e.g., Network Solutions)
  - provide names, IP addresses of authoritative name server (primary and secondary)
  - registrar inserts NS, A RRs into .com TLD server:

    `(networkutopia.com, dns1.networkutopia.com, NS)`

    `(dns1.networkutopia.com, 212.212.212.1, A)`
- create authoritative server locally with IP address `212.212.212.1`
  - type A record for www.networkuptopia.com
  - type MX record for networkutopia.com

DNS security

DDoS attacks

- bombard root servers with traffic
  - not successful to date
  - traffic filtering
  - local DNS servers cache IPs of TLD servers, allowing root server bypass
- bombard TLD servers
  - potentially more dangerous

Redirect attacks

- man-in-middle
  - intercept DNS queries
- DNS poisoning
  - send bogus relies to DNS server, which caches

Exploit DNS for DDoS

- send queries with spoofed source address: target IP
- requires amplification

DNSSEC
[RFC 4033]

Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS

- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

Peer-to-peer (P2P) architecture

开机时 服务器在

- *no* always-on server
- arbitrary end systems directly communicate
- peers request service from other peers, provide service in return to other peers
  - *self scalability* – new peers bring new service capacity, and new service demands
- peers are intermittently connected and change IP addresses
  - complex management
- examples: P2P file sharing (BitTorrent), streaming (KanKan), VoIP (Skype)



File distribution: client-server vs P2P

throughput

Q: how much time to distribute file (size *F*) from one server to *N peers*?

- peer upload/download capacity is limited resource



整条链路带宽取决于瓶颈带宽

File distribution time: client-server

- *server transmission:* must sequentially send (upload) *N* file copies:
  - time to send one copy: F/u_s
  - time to send *N* copies: NF/u_s
- *client:* each client must download file copy
  - d_{min} = min client download rate
  - min client download time: F/d_{min}



上传一个文件需要的时间.

time to distribute F to N clients using client-server approach

$$D_{c\text{-}s} \geq max\{NF/u_s, F/d_{min}\}$$

下载

increases linearly in N

File distribution time: P2P

- *server transmission:* must upload at least one copy:
  - time to send one copy: F/u_s
- *client:* each client must download file copy
  - min client download time: F/d_{min}
- *clients:* as aggregate must download NF bits
  - max upload rate (limiting max download rate) is $u_s + \Sigma u_i$



上传-份到网络中 下载 充分利用所有用户的上传带宽

time to distribute F to N clients using P2P approach

$$D_{P2P} \geq max\{F/u_s, F/d_{min}, NF/(u_s + \Sigma u_i)\}$$

increases linearly in N …
… but so does this, as each peer brings service capacity

Client-server vs. P2P: example

client upload rate = u, F/u = 1 hour, $u_s = 10u$, $d_{min} \geq u_s$



受上传带宽限制

上传带宽 < 下载带宽

内容消费者.

P2P file distribution: BitTorrent

文件发送软件.

文件块

- file divided into 256Kb chunks
- peers in torrent send/receive file chunks

tracker: tracks peers participating in torrent

torrent: group of peers exchanging chunks of a file



P2P file distribution: BitTorrent

- peer joining torrent:
  - has no chunks, but will accumulate them over time from other peers
  - registers with tracker to get list of peers, connects to subset of peers ("neighbors")



- while downloading, peer uploads chunks to other peers
- peer may change peers with whom it exchanges chunks
- *churn:* peers may come and go
- once peer has entire file, it may (selfishly) leave or (altruistically) remain in torrent

Application layer: overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- **video streaming and content distribution networks**
- socket programming with UDP and TCP

Video Streaming and CDNs: context

- stream video traffic: major consumer of Internet bandwidth
  - Netflix, YouTube, Amazon Prime: 80% of residential ISP traffic (2020)
- challenge: scale - how to reach ~1B users?
  - single mega-video server won't work (why?)
- challenge: heterogeneity
  - different users have different capabilities (e.g., wired versus mobile; bandwidth rich versus bandwidth poor)
- *solution: distributed, application-level infrastructure*

Multimedia: video

- video: sequence of images displayed at constant rate
  - e.g., 24 images/sec
- digital image: array of pixels
  - each pixel represented by bits
- coding: use redundancy *within* and *between* images to decrease # bits used to encode image 时间
  - spatial (within image) 空间
  - temporal (from one image to next)

spatial coding example: instead of sending *N* values of same color (all purple), send only two values: color value (*purple*) *and number of repeated values* (N)



frame *i*

frame *i+1*

temporal coding example: instead of sending complete frame at i+1, send only differences from frame i

Multimedia: video

高bit rate → 视频质量更好.

- CBR: (constant bit rate): video encoding rate fixed
- VBR: (variable bit rate): video encoding rate changes as amount of spatial, temporal coding changes
- examples: 编码方式.
  - MPEG 1 (CD-ROM) 1.5 Mbps
  - MPEG2 (DVD) 3-6 Mbps
  - MPEG4 (often used in Internet, 64Kbps – 12 Mbps, e.g., mp4)

根据网络压缩成不同质量视频

mp4运用上是 MPEG4.

spatial coding example: instead of sending *N* values of same color (all purple), send only two values: color value (*purple*) *and number of repeated values* (N)

frame *i*

temporal coding example: instead of sending complete frame at i+1, send only differences from frame i

frame *i+1*

Streaming stored video

simple scenario:



Main challenges:

- server-to-client bandwidth will *vary* over time, with changing network congestion levels (in house, in access network, in network core, at video server)
- packet loss and delay due to congestion will delay playout, or result in poor video quality

Streaming stored video



streaming: at this time, client playing out early part of video, while server still sending later part of video

Streaming stored video: challenges

- continuous playout constraint (连续播放限制): once client playout begins, playback must match original timing
  - … but network delays are variable (jitter晃动), so will need client-side buffer to match playout requirements



- other challenges:
  - client interactivity: pause, fast-forward, rewind, jump through video
  - video packets may be lost, retransmitted

Streaming stored video: playout buffering



- *client-side buffering and playout delay:* compensate for network-added delay, delay jitter

Streaming multimedia: DASH

- *DASH: D*ynamic, *A*daptive *S*treaming over *H*TTP
- *server:*
  - divides video file into multiple chunks
  - each chunk stored, encoded at different rates
  - *manifest file:* provides URLs for different chunks



所有的文件的比特率.

- *client:*
  - periodically measures server-to-client bandwidth

带宽测试.

  - consulting manifest, requests one chunk at a time
    - chooses maximum coding rate sustainable given current bandwidth
    - can choose different coding rates at different points in time (depending on available bandwidth at time)

Streaming multimedia: DASH

决策，请求都在客户端完成.

- *"intelligence"* at client: client determines
  - *when* to request chunk (so that buffer starvation, or overflow does not occur)
  - *what encoding rate* to request (higher quality when more bandwidth available)
  - *where* to request chunk (can request from URL server that is "close" to client or has high available bandwidth)



Streaming video = encoding + DASH + playout buffering

三种技术同时实现.

Content distribution networks (CDNs)

- *challenge:* how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- option 1: single, large "mega-server"
  - single point of failure
  - point of network congestion
  - long path to distant clients
  - multiple copies of video sent over outgoing link

….quite simply: this solution *doesn't scale*

Content distribution networks (CDNs)

- *challenge:* how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?
- option 2: store/serve multiple copies of videos at multiple geographically distributed sites *(CDN)*
  - *enter deep:* push CDN servers deep into many access networks
    - close to users
    - Akamai: 240,000 servers deployed in more than 120 countries (2015)
  - *bring home:* smaller number (10's) of larger clusters in Points of Presence (POPs) near (but not within) access networks
    - used by Limelight

Content distribution networks (CDNs)

- CDN: stores copies of content at CDN nodes
  - e.g. Netflix stores copies of MadMen
- subscriber requests content from CDN
  - directed to nearby copy, retrieves content
  - may choose different copy if network path congested



Content distribution networks (CDNs)

Internet host-host communication as a service

分布式架构.

OTT challenges: coping with a congested Internet

- from which CDN node to retrieve content?
- viewer behavior in presence of congestion?
- what content to place in which CDN node?

DNS解析到不同心服务器
实现负载心均衡

卫星信号/电视信号

Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP

传输层

Socket programming（套接字编程）

UDP
TCP

goal: learn how to build client/server applications that communicate using sockets

socket: like a courier between application process and end-end-transport protocol



Socket programming

Two socket types for two transport services:

- *UDP:* unreliable datagram
  - 有明确的消息边界
  - 不需要建立连接.
- *TCP:* reliable, byte stream-oriented
  - 1个receive有很多send 也可以形式存在.

Application Example:

1. client reads a line of characters (data) from its keyboard and sends data to server
2. server receives the data and converts characters to uppercase
3. server sends modified data to client
4. client receives modified data and displays line on its screen

创建两个socket连起来

Socket programming with UDP

UDP: no “connection” between client & server

- no handshaking before sending data
- sender explicitly attaches IP destination address and port # to each packet
- receiver extracts sender IP address and port # from received packet

UDP: transmitted data may be lost or received out-of-order

Application viewpoint:

- UDP provides *unreliable* transfer of groups of bytes (“datagrams”数据报) between client and server

Client/server socket interaction: UDP



server (running on serverIP)

create socket, port= x:
serverSocket =
socket(AF_INET,SOCK_DGRAM)

read datagram from
serverSocket

write reply to
serverSocket
specifying
client address,
port number

client

create socket:
clientSocket =
socket(AF_INET,SOCK_DGRAM)

Create datagram with server IP and
port=x; send datagram via
clientSocket

read datagram from
clientSocket

close
clientSocket

Example app: UDP client

Python UDPClient

include Python's socket library →
```
from socket import *
```
```
serverName = 'hostname'
serverPort = 12000
```
create UDP socket for server →
```
clientSocket = socket(AF_INET,
                      SOCK_DGRAM)
```
get user keyboard input →
```
message = raw_input('Input lowercase sentence:')
```
attach server name, port to message; send into socket →
```
clientSocket.sendto(message.encode(),
                    (serverName, serverPort))
```
read reply characters from socket into string →
```
modifiedMessage, serverAddress =
                    clientSocket.recvfrom(2048)
```
print out received string and close socket →
```
print(modifiedMessage.decode())
clientSocket.close()
```

Example app: UDP server

Python UDPServer

```
from socket import *
serverPort = 12000
serverSocket = socket(AF_INET, SOCK_DGRAM)
serverSocket.bind(('', serverPort))
print ("The server is ready to receive")
while True:
    message, clientAddress = serverSocket.recvfrom(2048)
    modifiedMessage = message.decode().upper()
    serverSocket.sendto(modifiedMessage.encode(),
                        clientAddress)
```

create UDP socket →

bind socket to local port number 12000 →

loop forever →

Read from UDP socket into message, getting client's address (client IP and port) →

send upper case string back to this client →

connect 点对点的新的socket
进程之间绑定的服务器和客户端.

Socket programming with TCP

Client must contact server

- server process must first be running
- server must have created socket that welcomes client's contact

Client contacts server by:

- Creating TCP socket, specifying IP address, port number of server process
- *when client creates socket:* client TCP establishes connection to server TCP

- when contacted by client, *server TCP creates new socket* for server process to communicate with that particular client
  - allows server to talk with multiple clients
  - source port numbers used to distinguish clients (more in Chap 3)

Application viewpoint

TCP provides reliable, in-order byte-stream transfer ("pipe") between client and server

Client/server socket interaction: TCP



server (running on hostid)

client 



Example app: TCP client

Python TCPClient

```
from socket import *
serverName = 'servername'
serverPort = 12000
clientSocket = socket(AF_INET, SOCK_STREAM)
clientSocket.connect((serverName,serverPort))
sentence = raw_input('Input lowercase sentence:')
clientSocket.send(sentence.encode())
modifiedSentence = clientSocket.recv(1024)
print ('From Server:', modifiedSentence.decode())
clientSocket.close()
```

create TCP socket for server, remote port 12000

No need to attach server name, port

Example app: TCP server

Python TCPServer

```
 from socket import *
serverPort = 12000
serverSocket = socket(AF_INET,SOCK_STREAM)
serverSocket.bind(('',serverPort))
serverSocket.listen(1)
print 'The server is ready to receive'
while True:
    connectionSocket, addr = serverSocket.accept()

    sentence = connectionSocket.recv(1024).decode()
    capitalizedSentence = sentence.upper()
    connectionSocket.send(capitalizedSentence.
                                        encode())
    connectionSocket.close()
```

create TCP welcoming socket →

server begins listening for incoming TCP requests →

loop forever →

server waits on accept() for incoming requests, new socket created on return →

read bytes from socket (but not address as in UDP) →

close connection to this client (but *not* welcoming socket) →

Chapter 2: Summary

our study of network application layer is now complete!

- application architectures
  - client-server
  - P2P
- application service requirements:
  - reliability, bandwidth, delay
- Internet transport service model
  - connection-oriented, reliable: TCP
  - unreliable, datagrams: UDP
- specific protocols:
  - HTTP
  - SMTP, IMAP
  - DNS
  - P2P: BitTorrent
- video streaming, CDNs
- socket programming: TCP, UDP sockets

Chapter 2: Summary

Most importantly: learned about *protocols*!

- typical request/reply message exchange:
  - client requests info or service
  - server responds with data, status code
- message formats:
  - *headers*: fields giving info about data
  - *data:* info (payload) being communicated

important themes:

- centralized vs. decentralized
- stateless vs. stateful
- scalability
- reliable vs. unreliable message transfer
- "complexity at network edge"