

Homework #5 Amazon Web Services (AWS) with Python


This semester we are allowing all students to explore cloud computing as offered by Amazon's Web Services. Using the instructions below one can establish a service at AWS. Once established, you will be able to move your Python back-end program developed for Assignment #6 to your AWS instance and have it executed there.

1. Sign up for AWS

To sign up for AWS, you need a credit card. If you do not have one, buy a \$25 American Express Gift card at Ralphs or other grocery store.

To sign up go to:

<http://aws.amazon.com>



and click on **Create a Free Account**. Follow the instructions to create your AWS account using the "AWS Free Usage Tier".

Note: Please select Account Type: Personal when setting up the account.

After you are signed up, from the drop down next to your name, select **My Account**. In the *Account Settings* section, you will notice the *Account Id*. This is the **AWS Account ID** to be used next when signing up for AWS Educate.

Please note that many of the URLs listed from now on will only be available if you are

signed up to AWS.

2. Sign up for AWS Educate

To sign up for AWS Educate and get a \$100 credit (USC is a member of AWS Educate) go to:

<http://aws.amazon.com/education/awseducate>

Click on the *Join AWS Educate* button.

On Step 1, click on the arrow in *Student* button.

On Step 2, fill out the form appropriately. **University of Southern California** will auto-complete. Leave the **Promo Code** field empty and click **NEXT**.

On Step 3, Scroll to view the complete Term and Conditions. Select the checkbox **I Agree**.

Click **SUBMIT** and finish the sign-up process.

After your application is reviewed and approved, you will receive a welcome e-mail from AWS Educate Support, which includes details to set your password, as shown below:

Congratulations!

Your AWS Educate application has been approved. As a member of the AWS Educate program, you will gain access to the benefits listed below:

AWS Educate Student Portal

The AWS Educate Student Portal is the hub for AWS Educate students around the world to find AWS content to help with classwork, connect to self-paced labs and training resources.

[Click here](#) to set your password and log in to the AWS Educate Student Portal. After logging in, click **AWS Account** at the top of the page to choose how you would like to access AWS services.

Bookmark the AWS Educate Student Portal for easy access, or [click here](#) to sign in directly.

You can access a video walk-through of the AWS Educate Student portal [here](#).

Free AWS Essentials Training

To access our foundational AWS Cloud Practitioner Essentials online learning class for free and find other self-paced labs, you must have either an AWS account or an Amazon ID.

- If you have an AWS account, sign in and [click here](#) to receive these benefits.
- If you do not have an AWS account, [click here](#) and follow the instructions to create an Amazon ID to access these benefits.

Once you access the Training and Certification portal, click "Learning Library" and search for "AWS Cloud Practitioner Essentials" to easily locate and enroll in AWS Cloud Practitioner Essentials on-line training. You can access AWS training any time after setting up your account by clicking [here](#).

Thank you again for participating in AWS Educate and we hope you enjoy the program!

Good luck with your continued studies,

The AWS Educate Team

2.2 Issues Sign up for AWS Educate

If you are having issues signing up for AWS Educate, and your initial application is rejected, you can create a Support Case at <https://console.aws.amazon.com/support>, where you describe the problem and attached a copy of the front and back of your USC ID. Alternatively you could also contact AWS Educate Support directly at:

<http://aws.amazon.com/education/awseducate/contact-us>


3. Apply the \$100 credit

Once you have completed signing up for both AWS and AWS Educate, login to your AWS Educate account.

Then go to the URL:

<https://www.awseducate.com/student/s/awssite>


Click on **AWS Account** in the toolbar. Select “I would like to use a personal AWS Account”. Enter the *AWS Account ID* to get the **Promo Code** which will be displayed in a box saying, “Show my AWS Promotional Credit”.



The screenshot shows the AWS Educate student portal. At the top is a blue navigation bar with the 'awseducate' logo and links for Portfolio, Career Pathways, Badges, Jobs, AWS Account, and Logout. The main content area features a cartoon character on the left holding a laptop. To the right is a video player titled 'How to access AWS Services' with a progress bar at 0:00 / 3:07. Below the video, the text 'Choose an option to get started!' is followed by two radio button options: 'I would like to use a personal AWS Account' and 'I would like to use an AWS Educate Starter Account'.

4. Provide Credit Card or Gift Card Information


- In the top menu, click on your name and select **My Billing Dashboard** in the drop-down menu.



- In the left menu select **Payment Methods**
- Click on **Add a Card** button
- Provide your card information (Credit Card Number, Name of Cardholder, Expiration Date)
- Optionally Edit your billing address.
- The \$100 promotional credit will be available in your billing section inside the “Credits” tab.

5. Set up the Default Elastic Beanstalk Application

- Click the top left menu **Services**
- From the list of Amazon Web Services, select **Elastic Beanstalk**, under **Compute**.



- Select **Create New Application** in the top right, right underneath your account

name, and follow the Wizard.

- In the **Application Name** field, enter a name for your application.

Create New Application

Application Name PythonApp
Maximum length of 100 characters, not including forward slash (/).

Description My first cloud Python App
Maximum length of 200 characters.

Tags
Apply up to 50 tags. You can use tags to group and filter your resources. A tag is a key-value pair. The key must be unique within the resource and is case-sensitive.
[Learn more](#)

Key (127 characters maximum)	Value (255 characters maximum)
<input type="text"/>	<input type="text"/>

50 remaining

[Cancel](#) [Create](#)

- Click **Create**.
- In the **Environment** section click on the **Create One now** hyperlink

aws Services Resource Groups

Elastic Beanstalk NodeJS-APP PythonApp [Create New Application](#)

All Applications > PythonApp [Actions](#)

Environments
Application versions
Saved configurations

No environments currently exist for this application. [Create one now.](#)

- In the **Choose an environment tier** dialog select **Web server environment** and click on **Select** button.



Select environment tier

AWS Elastic Beanstalk has two types of environment tiers to support different types of web applications. Web servers are standard applications that listen for and then process HTTP requests, typically over port 80. Workers are specialized applications that have a background processing task that listens for messages on an Amazon SQS queue. Worker applications post those messages to your application by using HTTP.

Web server environment



Run a website, web application, or web API that serves HTTP requests.

[Learn more](#)

Worker environment



Run a worker application that processes long-running workloads on demand or performs tasks on a schedule.

[Learn more](#)

[Cancel](#)

[Select](#)

- In the **Environment Information** section, select a **Domain** (use the default or check availability of your own subdomain of elasticbeanstalk.com). Click on “**Check availability**” button. Your URL should be green. Otherwise you should change the environment URL.

Create a web server environment

Launch an environment with a sample application or your own code. By creating an environment, you allow AWS Elastic Beanstalk to manage AWS resources and permissions on your behalf. [Learn more](#)

Environment information

Choose the name, subdomain, and description for your environment. These cannot be changed later.

Application name PythonApp

Environment name Pythonapp-env

Domain

csci571-python

.us-east-1.elasticbeanstalk.com

Check availability

csci571-python.us-east-1.elasticbeanstalk.com is available.

Description

- In the **Base configuration** section, choose the **Preconfigured platform**, and the following option in the drop-down list:
 - Choose a platform: **Preconfigured - Python**

Base configuration

Platform ☒ Preconfigured platform
Platforms published and maintained by AWS Elastic Beanstalk.

Application code ☒ Sample application
Get started right away with sample code.

☐ Existing version
Application versions that you have uploaded for PythonApp.

☐ Upload your code
Upload a source bundle from your computer or copy one from Amazon S3.

Choose a platform --

- Beta**
 - Corretto 11
 - Corretto 8
- Generic**
 - Docker
 - Multi-container Docker
- Preconfigured**
 - Elastic Beanstalk Packer Builder
 - Go
 - .NET (Windows/IIS)
 - Java
 - Node.js
 - Ruby
 - PHP
 - Python**
 - Tomcat
- Preconfigured - Docker**
 - GlassFish
 - Go

- In the **Application Code** section, select **Sample application**.

Application code ☒ Sample application
Get started right away with sample code.

☐ Existing version
Application versions that you have uploaded for PythonApp.

☐ Upload your code
Upload a source bundle from your computer or copy one from Amazon S3.

ZIP or WAR

- Click **Create environment**.
- After a minute or so the “**Creating <environment-name>**” dialog appears, with the message “This will take a few minutes...”

All Applications > NewPHP > Newphp-env (Environment ID: e-ethjxs5uzy, URL: csc571-php-us-east-1.elasticbeanstalk.com) Actions

Creating Newphp-env
This will take a few minutes....

```
1:45pm Environment health has transitioned from Pending to Ok. Initialization completed 9 seconds ago and took 4 minutes.
1:43pm Added instance [i-037c397c9487d2d3a] to your environment.
1:42pm Waiting for EC2 instances to launch. This may take a few minutes.
1:41pm Environment health has transitioned to Pending. Initialization in progress (running for 16 seconds). There are no instances.
1:41pm Created EIP: 54.83.201.175
1:40pm Created security group named:
aws-ec2-sg-us-east-1-231003652661 as Amazon S3 storage bucket for environment data.
1:40pm Using elasticbeanstalk-us-east-1-231003652661 as Amazon S3 storage bucket for environment data.
1:40pm createEnvironment is starting.
```

Learn More

- Get started using Elastic Beanstalk
- Modify the code
- Create and connect to a database
- Add a custom domain

Featured

- Create your own custom platform
- Command Line Interface (v3)
- Installing the AWS EB CLI
- EB CLI Command Reference

You will need to wait for several minutes as your **Amazon Linux + Python 3.6** instance is created and launched. You will see several messages appear as the instance is being created and deployed. a *rotating wheel* next to the “**Monitor**” button. Once creation and launch are completed, you will see the wheel turn into a green round circle with a check mark in the middle.

Overview

[Refresh](#)**Health****Ok**[Causes](#)**Running Version**

Sample Application

[Upload and Deploy](#)**Platform**Python 3.6 running on 64bit
Amazon Linux/2.9.4[Change](#)

Recent Events

[Show All](#)


Time	Type	Details
2020-01-06 14:37:11 UTC-0800	INFO	Environment health has transitioned from Pending to Ok. Initialization completed 11 seconds ago and took 2 minutes.
2020-01-06 14:36:46 UTC-0800	INFO	Successfully launched environment: Pythonapp-env
2020-01-06 14:36:44 UTC-0800	INFO	Application available at csci571-python.us-east-1.elasticbeanstalk.com.
2020-01-06 14:36:11 UTC-0800	INFO	Added instance [i-0990b8c74ccda915e] to your environment.
2020-01-06 14:36:06 UTC-0800	INFO	Waiting for EC2 instances to launch. This may take a few minutes.

Python Instance Dashboard

Beside "<YourEnvironment>" subtitle there is a **URL** such as *YourAppName-env.elasticbeanstalk.com*.

The screenshot shows the AWS console interface. At the top, there's a navigation bar with the AWS logo, 'Services', 'Resource Groups', and user information. Below this, a breadcrumb trail reads 'All Applications > PythonApp > Pythonapp-env'. The 'Pythonapp-env' subtitle is followed by '(Environment ID: e-5xm2drmbjk, URL: csci571-python.us-east-1.elasticbeanstalk.com)'. The URL is highlighted with a red rectangular box. To the right of the URL is an 'Actions' dropdown menu. In the background, there are tabs for 'Elastic Beanstalk', 'NodeJS-APP', and 'PythonApp', with a 'Create New Application' button on the right.

Click on it. You should see the "Congratulations" page. If you see it as shown below, your application and environment have been created properly.



Python Sample Application

You have two options listed for deploying web apps in Python on AWS:

- **Flask** web application framework
- **Django** web application framework

We personally recommend that you use Flask, as we believe it is simpler to install and maintain. You are free to use either Python Web Framework, but we will support in Piazza only the Flask deployment.

6. Deploy your Python application

6.1 Installing Python

On **MacOS** we recommend you use the “brew” package manager to install Python and pip. Flask requires Python 2.7 (which is preloaded on every Mac) or Python 3.4 or newer. We personally recommend **Python 3.7** and **pip3**. In the latter case you should change your shell startup files to point to Python 3.7 instead of Python 2.7.

Note: steps for Installing **Python 3.7** can be found in section 2, “*Setting up a Python development environment*”, in the file entitled “*Homework #5 Google Cloud Platform (GCP) with Python*”, available at:

https://csci571.com/hw/hw5/HW5_Google_Python.pdf

On **Windows 10**, you can [install the Windows Subsystem for Linux](#) to get a Windows-integrated version of Ubuntu and Bash.

You can deploy your applications using the AWS Elastic Beanstalk console **Upload and Deploy** or the Elastic Beanstalk Command Line Interface (**EB CLI**).

6.2 Deploying a Flask Application to AWS Elastic Beanstalk using “Upload and Deploy”

This is the installation that we recommend, as it uses the Sample Application environment set up in **section 5. Set up the Default Elastic Beanstalk Application**.

Windows ONLY: download and install **PowerShell**.

- a. Create a project folder:

```
$ mkdir eb-flask
```

```
$ cd eb-flask
```

- b. Create an isolated Python environment:

```
$ python3 -m venv env
```

```
$ source env/bin/activate
```

(the terminal prompt will add (env) to the terminal prompt)

- c. Install flask with pip install:

```
(env) $ pip install flask==1.0.2
```

- d. View installed libraries with pip freeze:

```
(env) $ pip freeze
Click==7.0
Flask==1.0.2
itsdangerous==1.1.0
Jinja2==2.10.3
MarkupSafe==1.1.1
Werkzeug==0.16.0
```

- e. Create requirement.txt

```
(env) $ pip freeze > requirements.txt
```

- f. Next, create an application that you'll deploy using Elastic Beanstalk Upload and Deploy. We'll create a "Hello World" RESTful web service.

- g. Create a new text file in this directory named application.py with the following contents:

- h. Download new sample code (RESTful app) from:


<https://csci571.com/hw/hw5/application.py>

save the file as `application.py`. Using `application.py` as the filename and providing a callable application object (the Flask object, in this case) allows Elastic Beanstalk to easily find your application's code.

- i. Run `application.py` locally with Python on port 5000:

```
(env) $ python application.py
* Serving Flask app "application" (lazy loading)
* Environment: production
  WARNING: Do not use the development server in a production
environment.
  Use a production WSGI server instead.
* Debug mode: on
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
* Restarting with stat
* Debugger is active!
* Debugger PIN: 305-600-227
```

- j. Test your application locally, by opening `http://127.0.0.1:5000/` in your web browser. You should see the application running, showing the index page:




You can stop the web server and return to your virtual environment by typing **Ctrl+C**.

- k. You are ready now to upload and deploy. First of all, “xip” the two needed files, `application.py` and `requirements.txt`:

```
(env $ zip eb-deploy.zip application.py requirements.txt
  adding: application.py (deflated 48%)
  adding: requirements.txt (deflated 9%)
(env) $
```

- l. Now go to the AWS EB console, and click the **Upload and Deploy** button:



- m. Choose the eb-deploy.zip file from your desktop. Enter a unique Version label. Click **Deploy**. The AWS EB server will restart and update your environment.

Recent Events [Show All](#)

Time	Type	Details
2020-01-11 17:15:45 UTC-0800	INFO	Environment update completed successfully.
2020-01-11 17:15:45 UTC-0800	INFO	New application version was deployed to running EC2 instances.
2020-01-11 17:14:57 UTC-0800	INFO	Environment health has transitioned from Ok to Info. Application update in progress (running for 20 seconds).
2020-01-11 17:14:55 UTC-0800	INFO	Deploying new version to instance(s).
2020-01-11 17:14:15 UTC-0800	INFO	Environment update is starting.

- n. You are ready now to run the updated AWS “cloud” version of your app.



- o. Modify application.py for the next exercises, as appropriate.

6.3 Deploying a Flask Application to AWS Elastic Beanstalk using “EB CLI”

Click on the corresponding link in the sample application, or follow the tutorial at:

<https://docs.aws.amazon.com/elasticbeanstalk/latest/dg/create-deploy-python-flask.html>

The Tutorial above includes all of the following:

- Prerequisites
- Flask Framework installation
- Details on installing and configuring the EB CLI

- Set Up a Python Virtual Environment with Flask
- Create a Flask Application
- Run the application locally on your Mac or PC
- Deploy your site with the EB CLI
- Cleanup

Once you have created, deployed and tested the tutorial application, you will have the basic skeleton for a **RESTful web service**.

Additional Notes:

The instructions in this Tutorial creates a new Elastic Beanstalk environment and deploys using the EB CLI.

Also, you will likely get an error such as “zlib not available” during the installation using EB CLI. As mentioned in:

<https://github.com/aws/aws-elastic-beanstalk-cli-setup/issues/23>

this can be fixed by running:

```
pip install virtualenv
python ./scripts/ebcli_installer.py
```

instead of:

```
brew install awsebcli
```

or installing the EB CLI using Setup Scripts (as in the Tutorial).

6.4 Deploying a Django Application to AWS Elastic Beanstalk

Click on the corresponding link in the sample application, or follow the tutorial available at:

<https://docs.aws.amazon.com/elasticbeanstalk/latest/dg/create-deploy-python-django.html>

Follow the steps listed in the tutorial.

7. Set up Exploring Your Instance (Optional)

If you want to explore your Instance and create your own domain-based URL with SSH control, you can add the following steps.

7.1 Get and Setup SSH

Once the Python app with SSH-enabled environment is running, you can get access using SSH. You can use SSH on a Mac running MacOS, or Putty when running on Windows.

On a Mac, SSH is built into MacOS and can be accessed through the **Terminal** app and there is no additional setup needed.

On a Windows PC, you will need to download the complete PuTTY distribution at:

<http://www.chiark.greenend.org.uk/~sgtatham/putty/download.html>

You should download the file **putty.zip** that contains all the binaries, including **PuTTYgen** as see in this snapshot from the website above:

Alternative binary files		
The installer packages above will provide all of these (except PuTTYtel), but you can download them one by one. (Not sure whether you want the 32-bit or the 64-bit version? Read the FAQ entry .)		
putty.exe (the SSH and Telnet client itself)		
32-bit:	putty.exe	(or by FTP) (signature)
64-bit:	putty.exe	(or by FTP) (signature)
pscp.exe (an SCP client, i.e. command-line secure file copy)		
32-bit:	pscp.exe	(or by FTP) (signature)
64-bit:	pscp.exe	(or by FTP) (signature)
psftp.exe (an SFTP client, i.e. general file transfer sessions much like FTP)		
32-bit:	psftp.exe	(or by FTP) (signature)
64-bit:	psftp.exe	(or by FTP) (signature)
puttytel.exe (a Telnet-only client)		
32-bit:	puttytel.exe	(or by FTP) (signature)
64-bit:	puttytel.exe	(or by FTP) (signature)
plink.exe (a command-line interface to the PuTTY back ends)		
32-bit:	plink.exe	(or by FTP) (signature)
64-bit:	plink.exe	(or by FTP) (signature)
pageant.exe (an SSH authentication agent for PuTTY, PSCP, PSFTP, and Plink)		
32-bit:	pageant.exe	(or by FTP) (signature)
64-bit:	pageant.exe	(or by FTP) (signature)
puttygen.exe (a RSA and DSA key generation utility)		
32-bit:	puttygen.exe	(or by FTP) (signature)
64-bit:	puttygen.exe	(or by FTP) (signature)
putty.zip (a ZIP archive of all the above)		
32-bit:	putty.zip	(or by FTP) (signature)
64-bit:	putty.zip	(or by FTP) (signature)


PuTTY needs additional setup as it needs to use a converted version of the private key. The instructions on how to perform such conversion are available here:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/putty.html>

The major step is to use **PuTTYgen** to convert your private key format (.pem) generated by Amazon EC2 into the required PuTTY format (.ppk).

8.2 Create a Key Pair

- From the **Services** drop down, under the **Compute** section, select the **EC2**.



- Under **NETWORK AND SECURITY** select **Key Pairs**.
- Click on the button **Create Key Pair**.
- Enter a name like *pythonhosts* (you must have your own random name!) and click on **Create**.
- A download of your private key should start automatically. Save the key, like *pythonhosts.pem*, in an appropriate location.

8.2.1 Associate your Instance to the Key Pair

- You now need to associate your Instance with the just created key pair.
- Select the **Elastic Beanstalk** under **Services**.
- Select your environment but clicking anywhere in the “green” rectangle.
- Click on **Configuration** on the left menu.
- Click on the **Modify** button next to **Security**.
- Select the key pair you just created for the **EC2 key pair** field. Click **Refresh icon**.

Service role

Service role

Virtual machine permissions

EC2 key pair

IAM instance profile

[Cancel](#) [Continue](#) [Apply](#)

- Hit **Apply** and then **Confirm** and wait for several minutes for the configuration changes to take place. You may get INFO, WARN and sometimes **SEVERE** messages during this time. Wait until the update of the environment has completed, and **Health** is back to **Ok**.
- Go back to your EC2 instance (listed under **INSTANCES – Instances**) after some time and check under **Key Name**, you should now see your associated key pair.

Name	Instance ID	Instance Type	Availability Zone	Instance State	Status Checks	Alarm Status	Public DNS (IPv4)	IPv4 Public IP	IPv6 IPs	Key Name
Pythonapp-env	i-097bfa3c2e0bd4d17	t2.micro	us-east-1c	running	2/2 checks ...	None	ec2-3-233-231-125.co...	3.233.231.125	-	pythonhosts
Pythonapp-env	i-0990b8c74ccda915e	t2.micro	us-east-1c	terminated		None	-	-	-	
NodejsApp-env	i-0ec03d138015b4afc	t2.micro	us-east-1c	running	2/2 checks ...	None	ec2-3-232-16-111.comp...	3.232.16.111	-	

8.3 Open port 22

To open port 22, which is needed by SSH, follow these steps:

1. In the EC2 Management Console, click on **Instances**.
2. Under **NETWORK & SECURITY**, click on **Security Groups**.
3. Select the security group (present as a link) configured for your instance.
4. For the security group, edit (or verify) the "Inbound rules" (**Inbound** tab present on the bottom of the pane) by clicking the **Edit** button.
5. If missing, add a new rule for Type = SSH, Protocol = TCP, Port Range = 22, Source = Custom 0.0.0.0/0. Click **Save**. If rule is already present, **do nothing**.


Edit inbound rules

Type	Protocol	Port Range	Source
HTTP	TCP	80	Custom 0.0.0.0/0
SSH	TCP	22	Custom 0.0.0.0/0

[Add Rule](#) [Cancel](#) [Save](#)


8.3.1 Errors when Connecting

If you fail to either open port 22 or associate your instance to a key pair, you will get an error popup when you try to **Connect to Your Instance** using EC2 Dashboard >> INSTANCES >> Instances >> select instance >> Connect, as show in the picture below.



8.4 Access your Linux Instance with SSH

- To see how to launch your SSH client go to **Services** and select **EC2**.
- Under the **INSTANCES** section in the navigation pane on the left, select **Instances**.
- Select your instance in the table (the check box turns **blue**) and select the **Connect** button next to Launch Instance.
- The **Connect to your instance** popup will display. Select the radio button **A standalone SSH client**. Notice the hyperlink "connect using PuTTY" (see section 7.4.2). See the snapshot below, showing Elastic IP connection string.



8.4.1 Mac running MacOS / ssh

Change the permission of pythonhosts.pem first:

```
chmod 400 pythonhosts.pem
```


On a Mac you will need to enter a command like this one (when using **Public DNS**):

```
ssh -i "pythonhosts.pem" ec2-user@ec2-3-233-231-125.compute-1.amazonaws.com
```

type **yes**, when asked. Make sure that you are executing the ssh command in the same folder that contains the key. You should see output like this one (using **Public DNS**):

```
$ ssh -i "phphosts.pem" ec2-user@ec2-204-236-235-251.compute-1.amazonaws.com
```

Last login: Tue Oct 27 16:22:06 2015 from 159.83.115.214

The logo for Amazon Linux AMI, featuring the word "Amazon" in a stylized font with horizontal lines, followed by "Linux" and "AMI" in a simpler font. Below the text is a horizontal line with a small "v" symbol on the left and a small "x" symbol on the right.

```
This EC2 instance is managed by AWS Elastic Beanstalk. Changes
made via SSH
WILL BE LOST if the instance is replaced by auto-scaling. For
more information
on customizing your Elastic Beanstalk environment, see our
documentation here:
http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/customize-
containers-ec2.html
[ec2-user@ip-10-30-13-153 ~]$
```

```
Mac-mini:Desktop marcopapa$ chmod 400 pythonhosts.pem
```

```
Mac-mini:Desktop marcopapa$ ssh -i "pythonhosts.pem" ec2-  
user@ec2-3-233-231-125.compute-1.amazonaws.com  
The authenticity of host 'ec2-3-233-231-125.compute-  
1.amazonaws.com (3.233.231.125)' can't be established.  
ECDSA key fingerprint is  
SHA256:u0+G0tC6c90JOixq3uGWW7S9u8wb74kC8MW15qZ3yHw.  
Are you sure you want to continue connecting (yes/no)? yes  
Warning: Permanently added 'ec2-3-233-231-125.compute-  
1.amazonaws.com,3.233.231.125' (ECDSA) to the list of known  
hosts.
```



This EC2 instance is managed by AWS Elastic Beanstalk. Changes made via SSH WILL BE LOST if the instance is replaced by auto-scaling. For more information on customizing your Elastic Beanstalk environment, see our documentation here: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/customize-containers-ec2.html>
[ec2-user@ip-172-31-19-89 ~]\$

You can find more info here:


https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AccessingInstances.html?console_help=true

8.4.2 PC running Windows / PuTTY


In the popup windows titled **Connect To Your Instance**, click on **Connect using PuTTY**. You will be redirected to the URL.

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/putty.html>

Follow the steps under **Starting a PuTTY Session** to connect to your the Linux instance using PuTTY. The first time you connect by clicking **Open** to start the session, PuTTY displays a **PuTTY Security Alert** dialog box, as show in the following snapshot. Click the **Yes** button.



Once connected, PuTTY will open, and log you in, as shown in the next snapshot.



As with SSH, you can either use tout Public DNS or your Elastic IP to log in.

8.5 Explore

You can now explore your Instance. When you log in with SSH, your account home directory will be located at:

```
/home/ec2-user
```

That folder is empty and is not where your **Python** files are. Run 'ps ax', and you should see several instances of Apache **httpd** and **Python 2.7**:

```
[ec2-user@ip-172-31-19-89 ~]$ ps ax
  PID TTY          STAT       TIME COMMAND
...
 3005 ?            Ss          0:00 /usr/bin/python2.7
/usr/local/bin/supervisord --nodaemon -c /opt/python
...
 1940 ?            S           0:00 /usr/sbin/httpd -D FOREGROUND
 1941 ?            S1          0:00 /usr/sbin/httpd -D FOREGROUND
 1942 ?            S1          0:00 /usr/sbin/httpd -D FOREGROUND
 1944 ?            S1          0:00 /usr/sbin/httpd -D FOREGROUND
 1945 ?            S1          0:00 /usr/sbin/httpd -D FOREGROUND
...
 3325 ?            Ss1         2:07 /usr/bin/python2.7 /opt/aws/bin/cfn-
hup
...
```

```
[ec2-user@ip-172-31-19-89 ~]$
```

To see your mounted volumes, run 'df -h':

```
[ec2-user@ip-172-31-19-89 ~]$ df -h
Filesystem      Size  Used Avail Use% Mounted on
devtmpfs        483M   60K  483M   1% /dev
tmpfs           493M    0   493M   0% /dev/shm
/dev/xvda1      7.9G  1.6G  6.2G  21% /
[ec2-user@ip-172-31-19-89 ~]$
```

To see the Python (2.7 and 3.6) folders:

```
[ec2-user@ip-172-31-19-89 ~]$ ls /usr/bin/pyth*
/usr/bin/python          /usr/bin/python36
/usr/bin/python3.6m-x86_64-config
/usr/bin/python27        /usr/bin/python3.6
/usr/bin/python3-config
/usr/bin/python2.7       /usr/bin/python3.6-config
/usr/bin/python-config
/usr/bin/python2.7-config /usr/bin/python3.6m
/usr/bin/python-config2
/usr/bin/python3         /usr/bin/python3.6m-config
[ec2-user@ip-172-31-19-89 ~]$
```

To see your Python files, located in the “bundle” folder:

```
[ec2-user@ip-172-31-19-89 ~]$ ls /opt/python
bin  bundle  current  etc  log  run
[ec2-user@ip-172-31-19-89 ~]$ ls /opt/python/bin
httpdlaunch
[ec2-user@ip-172-31-19-89 ~]$ ls -l /opt/python/bundle
total 4
drwxr-xr-x 3 root root 4096 Jan  6 23:53 2
[ec2-user@ip-172-31-19-89 ~]$ ls -l /opt/python/bundle/2
total 8
drwxr-xr-x 2 wsgi root 4096 Jan  6 23:53 app
-rw-r--r-- 1 root root  103 Jan  6 23:53 env
[ec2-user@ip-172-31-19-89 ~]$ ls -l /opt/python/bundle/2/app
total 12
-rw-r--r-- 1 wsgi root 5065 Apr  2  2015 application.py
-rw-r--r-- 1 wsgi root   84 Apr  2  2015 cron.yaml
[ec2-user@ip-172-31-19-89 ~]$ ls -l
/opt/python/bundle/2/app/application.py
-rw-r--r-- 1 wsgi root 5065 Apr  2  2015
/opt/python/bundle/2/app/application.py
```

To see the Python application file that creates the “sample application” HTML page:

```
[ec2-user@ip-172-31-19-89 ~]$ more  
/opt/python/bundle/2/app/application.py
```

Note: the “bundle number” (2 above) will increase as you update and deploy new versions.

8.6 Additional Resources

An additional tutorial entitled “*Deploy a Python Web App*” on AWS, is available at:

<https://aws.amazon.com/getting-started/projects/deploy-python-application/>

This is a more complex application, that will incur some charges. We recommend deleting the environment once the app is tested.

Have fun exploring AWS!!