

Applied Machine Learning

Markov Chains II

Markov Chains II

- Simulation
- Stationary distribution
- M-grams

Markov Chains: States and Transition Probabilities


- State encoding:
[hot = 0, warm = 1, cool = 2]

- Transition Probability Matrix P

- $p_{i,j} = P(X_n = j | X_{n-1} = i)$

- $$P = \begin{bmatrix} 0.3 & 0.7 & 0 \\ 0.2 & 0.7 & 0.1 \\ 0 & 0.8 & 0.2 \end{bmatrix}$$

- $$\sum_j P(x_n = j | X_{n-1} = i) = \sum_j p_{i,j} = 1$$



Simulating Probability Distributions

- Initial probability distribution $P(X_0 = i)$

- $\pi_{[1 \times k]}$


- $\pi = [0.0, 0.20, 0.80]$

- Probability distribution at time 1:

$$\begin{aligned} P(X_1 = j) &= \sum_i P(X_1 = j, X_0 = i) \\ &= \sum_i P(X_1 = j | X_0 = i) P(X_0 = i) \\ &= \sum_i p_{i,j} \pi_i \end{aligned}$$

- As matrix multiplication: $\pi_1 = \pi P$

- $\pi_1 = [0.04, 0.78, 0.18]$



Simulating Probability Distributions

- Initial probability distribution $P(X_0 = i)$

- $\pi_{[1 \times k]}$


- $\pi = [0.0, 0.20, 0.80]$

- Probability distribution at time 2:


$$\begin{aligned} P(X_2 = j) &= \sum_i P(X_2 = j, X_1 = i) \\ &= \sum_i P(X_2 = j | X_1 = i) P(X_1 = i) \\ &= \sum_i p_{i,j} \left(\sum_{k,i} p_{k,i} \pi_k \right) \end{aligned}$$

- As matrix multiplication: $\pi_n = \pi_{n-1} P = \pi P^n$

- $\pi_1 = [0.04, 0.78, 0.18], \pi_{10} = [0.20, 0.71, 0.09]$



Stationary Distribution



- After a number of time steps
 - stuck at absorbing state
 - stabilize at some distribution
- Irreducible chain
 - finite number of states
 - no isolated state, so no absorbing state and all the states have probability greater than 0
 - evolve into stationary distribution s
 - $\lim_{n \rightarrow \infty} \pi P^n = s$
- Probability of states after enough steps to make it independent on where the walk started
 - Probability of reaching each state
- Advancing one more step leads to the same distribution s
 - $sP = s$
 - s is eigenvector of P^T with eigenvalue 1 divided by 1-norm, so probabilities sum 1.
 - if irreducible, there is only one such eigenvector
 - $s^T = [0.20, 0.71, 0.09]$

M-Order Markov Models

- Sentence: “Markov chains are cool”
- Markov chain to produce text
- Order 0: Single elements, no dependency
- Order 1: Dependency from previous element
 - pairs
 - bi-grams
- Order 2: Dependence from two previous elements
 - triplets
 - tri-grams
- Order M: M-gram



M-Grams

- Produce sequences of bits, characters, words
- Identify likely errors in sequences of bits, characters, words
- Text examples
 - frequency of M-grams, probability of transitions
 - there may be rare M-grams, even unseen M-grams
- Smoothing
 1. fixed low probability for each unseen M-gram
 2. distribute fixed probability among all unseen M-grams
 - Issue: frequency of unseen M-grams vary

Markov Chains II

- Simulation
- Stationary distribution
- M-grams

Applied Machine Learning

Markov Chains II