

Overview of Java Parallel Streams: Transitioning to Parallelism

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt



Professor of Computer Science


**Institute for Software
Integrated Systems**

**Vanderbilt University
Nashville, Tennessee, USA**



Learning Objectives in this Part of the Lesson



- Know how aggregate operations from Java sequential streams are applied in the parallel streams framework



Transitioning from Sequential Streams to Parallel Streams



Transitioning from Sequential Streams to Parallel Streams

- A Java stream is a pipeline of aggregate operations that process a sequence of elements (aka, "values" or "data")



Transitioning from Sequential Streams to Parallel Streams



- A Java stream is a pipeline of aggregate operations that process a sequence of elements (aka, "values" or "data")



Aggregate operations use internal iteration & behaviors to process elements in a stream


Transitioning from Sequential Streams to Parallel Streams

- By default, a stream executes sequentially, so all its aggregate operations run behaviors in a single thread of control



Transitioning from Sequential Streams to Parallel Streams

- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool



Search Phrases

`parallelStream()`


`map(phrase -> searchForPhrase(...))`

`filter(not(SearchResults::isEmpty))`

`collect(toList())`

See docs.oracle.com/javase/8/docs/api/java/util/concurrent/ForkJoinPool.html


- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool



Threads in the fork-join pool (non-deterministically) process different chunks

Transitioning from Sequential Streams to Parallel Streams


- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool



Intermediate operations iterate over & process behaviors on these chunks in parallel

Transitioning from Sequential Streams to Parallel Streams

- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool



Search Phrases

`parallelStream()`

`map(phrase -> searchForPhrase(...))`


`filter(not(SearchResults::isEmpty))`

`collect(toList())`


A terminal operation then combines the chunks into a single result

Transitioning from Sequential Streams to Parallel Streams

- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool




Search Phrases



(Stateless) Java 8 lambda expressions & method references are used to pass behaviors

Transitioning from Sequential Streams to Parallel Streams

- When a stream executes in parallel, it is partitioned into multiple substream “chunks” that run in the common fork-join pool



Search Phrases

stream() vs. *parallelStream()*

map(phrase -> searchForPhrase(...))

filter(not(SearchResults::isEmpty))

collect(toList())

Ideally, minuscule changes needed to transition from sequential to parallel stream

Transitioning from Sequential Streams to Parallel Streams

- The same aggregate operations can be used for sequential & parallel streams

Modifier and Type	Method and Description
boolean	allMatch (Predicate<? super T> predicate) Returns whether all elements of this stream match the provided predicate.
boolean	anyMatch (Predicate<? super T> predicate) Returns whether any elements of this stream match the provided predicate.
static <T> Stream.Builder<T>	builder () Returns a builder for a Stream.
<R,A> R	collect (Collector<? super T,A,R> collector) Performs a mutable reduction operation on the elements of this stream using a Collector.
<R> R	collect (Supplier<R> supplier, BiConsumer<R,? super T> accumulator, BiConsumer<R,R> combiner) Performs a mutable reduction operation on the elements of this stream.
static <T> Stream<T>	concat (Stream<? extends T> a, Stream<? extends T> b) Creates a lazily concatenated stream whose elements are all the elements of the first stream followed by all the elements of the second stream.
long	count () Returns the count of elements in this stream.
Stream<T>	distinct () Returns a stream consisting of the distinct elements (according to <code>Object.equals(Object)</code>) of this stream.
static <T> Stream<T>	empty () Returns an empty sequential Stream.
Stream<T>	filter (Predicate<? super T> predicate) Returns a stream consisting of the elements of this stream that match the given predicate.
Optional<T>	findAny () Returns an Optional describing some element of the stream, or an empty Optional if the stream is empty.
Optional<T>	findFirst () Returns an Optional describing the first element of this stream, or an empty Optional if the stream is empty.
<R> Stream<R>	flatMap (Function<? super T,? extends Stream<? extends R>> mapper) Returns a stream consisting of the results of replacing each element of this stream with the contents of a mapped stream produced by applying the provided mapping function to each element.

See docs.oracle.com/javase/8/docs/api/java/util/stream/Stream.html

Transitioning from Sequential Streams to Parallel Streams

- The same aggregate operations can be used for sequential & parallel streams

e.g., SearchStreamGang uses the same aggregate operations for both SearchWithSequentialStreams & SearchWithParallelStreams implementations


<<Java Class>>

 **SearchWithSequentialStreams**

◆ processStream():List<List<SearchResults>>


■ processInput(String):List<SearchResults>

<<Java Class>>

 **SearchWithParallelStreams**

◆ processStream():List<List<SearchResults>>

■ processInput(CharSequence):List<SearchResults>



Search Phrases

stream() vs. parallelStream()

map(phrase -> searchForPhrase(...))


filter(not(SearchResults::isEmpty))

collect(toList())

See github.com/douglasraigschmidt/LiveLessons/tree/master/SearchStreamGang

Transitioning from Sequential Streams to Parallel Streams

- The same aggregate operations can be used for sequential & parallel streams
- Java streams can thus treat parallelism as an optimization & leverage all available cores!



Search Phrases

`parallelStream()`

`map(phrase -> searchForPhrase(...))`

`filter(not(SearchResults::isEmpty))`

`collect(toList())`

Transitioning from Sequential Streams to Parallel Streams

- The same aggregate operations can be used for sequential & parallel streams
 - Java streams can thus treat parallelism as an optimization & leverage all available cores!
 - Naturally, behaviors run by these aggregate operations must be designed carefully to avoid accessing unsynchronized shared state..



Search Phrases

`parallelStream()`

`map(phrase -> searchForPhrase(...))`

`filter(not(SearchResults::isEmpty))`

`collect(toList())`

End of Overview of Java Parallel Streams: Transitioning to Parallelism